

هتحص نم ققحتلاو BGP راسم دي دحت نيوكت في IOS-XR

تايوت حمل

[عمدق مالا](#)

[ةيساس ا تامولعم](#)

[صخلم](#)

[راس مالا تاسايس في راس مالا دي دحت رماو اني عت](#)

[1. راس مالا دي دحت نم ةيطايت حالالا ةخسن لبا تي بثت ني عت](#)

[2. راس مالا دي دحت ل 1 يطايت حالالا ةخسن لبا تانالعا ني عت](#)

[3. تانالعالا تي بثت ةادا 1 راس مالا دي دحت ل يطايت حالالا ةخسن لبا ةادا ني عت](#)

[4. تانالعالا ل كل راس مالا دي دحت تانالعا ني عت](#)

[5. راس مالا دي دحت ل راسم لصف اني عت](#)

[6. راس مالا دي دحت ل تاراس مالا ددعت م نالعا ني عت](#)

[7. ةيامح-تاراس مالا ددعت م تي بثت 1 ةيطايت حالالا ةخسن لبا دي دحت-راسم ني عت](#)

[8. ةيامح ل ل تاراس مالا ددعت م تي بثت 1 يطايت حالالا ةخسن ل ل راس مالا دي دحت تانالعا ني عت](#)

[9. راسم دي دحت ةومجم لصف ال تانالعا ني عت](#)

[10. -تاراس مالا ددعت م نالعا تي بثت 1 راس مالا دي دحت ل يطايت حالالا ةخسن لبا ةيلمع ني عت
نالعا-protect](#)

[11. ةيامح ل ل تاراس مالا ددعت م نالعا راس مالا دي دحت ل تاراس مالا ددعت م ناو نع ني عت](#)

[12. -تاراس مالا ددعت م ةيامح ل تاراس مالا ددعت م راس مالا دي دحت ل تاراس مالا ددعت م نالعا ني عت
نالعا](#)

[Cisco IOS®-XR 7.3.1 عم لالعا وه امك دي دج راسم دي دحت كولس](#)

[نكمم راج ل راسم دي دحت](#)

[دحاو راسم جهن في ةومجم مالا ددعت م راسم دي دحت تارابعب حامس لبا متي](#)

[هب اهللابقتسا متي يذلا بيترت لبا BGP تاراسم راهظا](#)

[\(ةددعت مالا تاراس مالا ةيامح\) يطايت حالالا ةخسن لبا لباقم يطايت حالالا ةخسن لبا راسم](#)

[IGP سايق بسح بلطالا](#)

عمدق مالا

ةرابعالا لوكوتوربل راسم ةسايس في راس مالا دي دحت ةومجم نايب دنن تسمالا اذه فصبي
Cisco IOS®-XR لخاد (BGP) ةي دودحالا

ةيساس ا تامولعم

ةدحاو ةئدابل ةددعت م تاراسم نع نلعتو BGP دحت ناى ل تاميمصتلا نم دي دعالا فدهت

اذه نع نالعالا متي و، راسم لصف ا ك طوقف دحاو BGP راسم دي دحت متي، يضا رتفا لكشبو
يلي ام BGP راسم دي دحت ةيمزراوخ دحت. طوقف لصف ال راسم لبا

[لصف ال BGP راسم دي دحت ةيمزراوخ](#)

نكمي. يطايتحالال خسنلل راسمك ناث راسم لضفأ رايخ| نكمي، راسم لضفأ بناج يلاو لقتسم براق) PIC BGP ةقاطب تاذ تاميمصتلا ي ف اذه يطايتحالال خسنلل راسم مادختسا (ةئدابلاب).

كلذ نوكي نأ نكمي. لالمحالال ةنزاوم قيقيحتل ةددعتم تاراسم تيبتب BGP موقوي نأ نكمي Equal Cost Multipath Balancing (ECMP) Load Balancing و Unequal Cost Cost Multipath (UCMP). لودج و اتانايبلل يوتسمو (RIB) هيچوتلل لودج ي ف ةددعتم تاراسم لاهه تيبتب متي و CEF لودج ب اضيأ FIB لودج فرعي. لالمحالال ةنزاوم قيقيحتل (FIB) هيچوتلل ةداع| ليثم ةدعاق (Cisco نم عيرسلا هيچوتلل ةداع).

نن يفده يلع ةلاقملا هذه زكرت:

- اهتبتب متيل ةددعتم تاراسم رايخ BGP لعجن فيك؟
- ةددعتم تاراسم نع نلعي BGP لعجن فيك؟

(ةيفاضال تاراسملا) ةيفاضال تاراسملا يهو BGP لبق نم ةمدختسم رخأ ةزيم كانه ةدحاو BGP ةسلج ربع راسم نم رثكأ نع نالعال BGP ل ةزيملا هذه حيتت.

صخلم

- ام أطخ كانهف، كلذك رمال نكي مل ن| BGP ةطساوب امئاد لضفأال راسملا ءاقتنا متي. تاهويرانيسلا هذه يطغت ال ةلاقملا هذه.
- BGP لالملا ليبس يلع) ةدحمال ةزيملا نيوكت مت اذا يطايتحالال خسن راسم رايخ| نكمي (PIC).
- يتل تاراسملا ديدحتل BGP ل ةدحمن نيوانع ةومجم نمض راسملا ةسايس نيوكت نكمي. اهنع نالعال و/أو اهتبتب متيس.
- راسملا جهن ي ف طقف دحاو راسم ديدحت نايب لمعد كانه، Cisco IOS®-XR 7.3.1 لبق. ةنعم ةئدابلا تاراسم ديدحتل.
- جهن ي ف ةومجملا ةددعتملا راسملا ديدحت لمجل معد كانه، Cisco IOS®-XR 7.3.1 عم ءدبلل. ةنعم ةئدابلا تاراسم ديدحتل راسملا.
- راسملا ةسايس مادختسا نكمي شيح ةزيم ةفاضل تم، Cisco IOS®-XR 7.3.1 نم ءدب. BGP ةراج يلا BGP ةئدابلا ةدحمال تاراسم نع نالعال.

امهم. تاراسملا مالتسال بيترتلاب BGP ةطساوب تاراسملا ةددعتملا تاراسملا ديدحت متي. يمجعم بيترت ي ف رمم BGP ل رما يدب بgp ضرعلا.

BGP تاراسم ةيؤرل - Cisco IOS®-XR 7.3.1 ي ف هميدقت مت- ديدج رما مادختسا نكمي. هه اهلابقتسا مت يذلا بيترتلاب:

```
show bgp <afi> rd <rd> <path_details>
```

لحي هن| اهالحا واهئاطخأ فاشكتساو ةددعتملا تاراسملا نم ققحتلا ي ف اذه دعاسي رخأ سيلي و تاراسملا ددعتم راسمك راسم رايخ| متي اذا مل نع يساسال لاؤسلا.

يحمي هنكلو تاراسملا ددعتم سيلي يطايتحالال خسن راسم وه تاراسملا ةددعتم ةيامل راسم. رخأال ةددعتملا تاراسملا لك.

Multipath-protect-Advertising ةديجال ةيساسال ةمكلال هذه كانه، Cisco IOS®-XR 7.3.1 نم ءدب.

بناج تاراسملا ةددعت م ةيماحل راسم نع نالعالل اهمادختسا نكمي . راسملا نييغت نايب
اهمادختسا متيس يتلا ةلماكل رماوالا . ةددعتملا تاراسملا بناج واطاي تحاللا خسنلا راسم
في ه route-policy

```
set path-selection backup 1 install multipath-protect advertise multipath-protect-advertise
set path-selection multipath advertise multipath-protect multipath-protect-advertise
```

هبة صاخلا ةيساسالا تاملكلا تاومجم عيجم عم **set path-selection** رمالا يلع ةماع ةرطن هذه
يلالات مسقلا في ةلثم او اليصفت رثكأ حرش دجوي

يلع) اطخ كانهف ، كلذك نكت مل اذا . لصفالا راسملا تيبتت متي ، هاندأ تالاحل عيجم في
set path-selection رمالاب قلعتي ال اذه نكلو ، (ةحيحص ريغ ةيلالاتلا ةوطخللا ، لاثملا ليبس

راسم ديحتب حمست BGP لوكوتوربل ةزيم نيكمت بجي ، طاي تحاللا خسنلا راسم ديحتل
BGP PIC لاثملا ليبس يلع : طاي تحاللا BGP خسن

maximum-paths: ناوعللا ةلئاع رمالال خ نم BGP في ةددعتملا تاراسملا نيكمت متي

```
maximum-paths {ebgp | eibgp | ibgp} <2-32> (unequal-cost)
```


ديحولا راسملا وه راسم لصفأ . تاراسملا ددعت م راسم وه راسم لصفأ ، فيرعتلا بسح
نكمي . BGP لوكوتوربل تاراسملا ددعت م نيكمت متي مل اذا هيحوتلا لودج في تبتتملا
maximum-paths رمالا مادختساب هيحوتلا لودج في ةتبتتملا BGP تاراسم ددع في مكنحلال
{ebgp | eibgp | ibgp} <2-32> (ةيواسم ريغ ةفلكت)

نم ديزمل **set path-selection** رمالا مادختساب تارايلال لك يلع ةماع ةرطن لودجلا اذه رفوي
انه ةمدقم ةلاح لكل يلاتلا مسقلا يلإ عجرا ، ةلثمالا او لياصافتلا

فرط	تيبتت	نالعا
1	خسنلا تيبتت م ديحت نم ةيطاي تحاللا 1 راسملا	رمال نع نالعالا متي طقف لصفالا
2	خسنلا تانالعا نييغت ديحتلل 1 طاي تحاللا راسملا يلع ديحت ةيلمع نييغت خسنلا راسملا	راسم نع نالعالا متي يطاي تحاللا خسنلا
3	خسنلا راسملا نالعا 1 ةيطاي تحاللا تيبتت	راسم نع نالعالا متي يطاي تحاللا خسنلا
4	ديحت تانالعا نييغت لكل راسملا	يجم نع نالعالا متي رمال لصفأ) تاراسملا طاي تحاللا خسن راسمو راسملا ددعت م راسمو تاراسملا ددعت م ريغو
5	راسم لصفأ طبض ديحتلل	رمال نع نالعالا متي طقف لصفالا
6	ددعت نالعا نييغت ديحتل تاراسملا راسملا	رمال نع نالعالا متي تاراسملا ةددعت م

7	دي دجت-راسم ني يع 1 ة يطاي تحال ة خسن لل -تاراسم لل ددع تم تي ب ث ت ة ا م ح	ة ددع تم تاراسم لل ة ت ب ث م تاراسم لل ر خ آ راسم تي ب ث ت م تي يطاي تحا خسن راسم ك خسن لل' راسم) ة ا م ح) يطاي تحال ا ذ ا ' (ة ددع تم تاراسم لل ك انه ل ا ز ت ال ت ن ا ك تاراسم لل ر ا و ج ب تاراسم ة ددع تم لل	م لل ن ع ن ال ع ا ل ا م تي ط ق ف ل ض ف ا ل ا
8	دي دجت تان ال ع ا د ا ع ا خسن لل راسم لل تي ب ث ت 1 يطاي تحال ة ا م ح لل تاراسم لل ددع تم	ة ددع تم تاراسم لل ة ت ب ث م تاراسم لل ر خ آ راسم تي ب ث ت م تي يطاي تحا خسن راسم ك خسن لل' راسم) ة ا م ح) يطاي تحال ا ذ ا ' (ة ددع تم تاراسم لل ك انه ل ا ز ت ال ت ن ا ك تاراسم لل ر ا و ج ب تاراسم ة ددع تم لل	م لل ن ع ن ال ع ا ل ا م تي م لل راسم و ل ض ف ا ل ا يطاي تحال م ن ع ن ال ع ا ل ا م تي م ل () يطاي تحال خسن لل () (ة ددع تم تاراسم لل
9	ل ض ف ا ل تان ال ع ا ني يع راسم دي دجت ة و م ح م	ل ض ف ا ل ة و م ح م ل ا دي دجت AS ل كل راسم ل ض ف ا و ه ة ل ا ت ة و ط خ ل كل ل ك ذ ك و ة ددع تم تاراسم لل ة ت ب ث م تاراسم لل	ي م ح ن ع ن ال ع ا ل ا م تي م لل تاراسم ل ض ف ا
10	set path-selection backup Multipath- protect Advertising Multipath-protect-adverads	ة ددع تم تاراسم لل ة ت ب ث م تاراسم لل ر خ آ راسم تي ب ث ت م تي يطاي تحا خسن راسم ك خسن لل' راسم) ة ا م ح) يطاي تحال ا ذ ا ' (ة ددع تم تاراسم لل ك انه ل ا ز ت ال ت ن ا ك تاراسم لل ر ا و ج ب تاراسم ة ددع تم لل	م لل ن ع ن ال ع ا ل ا م تي م لل راسم و ل ض ف ا ل ا ل ا راسم و يطاي تحال ة ا م ح) يطاي تحال () (ة ددع تم تاراسم لل
11	راسم دي دجت ني يع ن ال ع ا تاراسم لل ددع تم ة ا م ح لل تاراسم لل ددع تم	ة ددع تم تاراسم لل ة ت ب ث م تاراسم لل	م لل ن ع ن ال ع ا ل ا م تي تاراسم لل ة ددع تم م ن ع ن ال ع ا ل ا م تي م ل () يطاي تحال خسن لل () (ة ددع تم تاراسم لل
12	دي دجت تان ال ع ا ني يع تاراسم لل ددع تم راسم تاراسم لل ددع تم ة ا م ح ل ن ال ع ا ل - تاراسم لل ددع تم	ة ددع تم تاراسم لل ة ت ب ث م تاراسم لل ر خ آ راسم تي ب ث ت م تي يطاي تحا خسن راسم ك خسن لل' راسم) ة ا م ح) يطاي تحال ا ذ ا ' (ة ددع تم تاراسم لل ك انه ل ا ز ت ال ت ن ا ك تاراسم لل ر ا و ج ب تاراسم ة ددع تم لل	م لل ن ع ن ال ع ا ل ا م تي تاراسم لل ة ددع تم م ن ع ن ال ع ا ل ا م تي ل () يطاي تحال خسن لل () (ة ددع تم تاراسم لل

لمالك لاب دنتسمل اذه يف ةمدختسمل ايجولوبطال ايه هذو.



PE6 و (راسملا سكاغ) RR نبي Add-Path نبيكم متي، تالاحل ايجي يف

VPN4 يداحأل ثبلا هيچوت لثم ةئدابلا سفن نع PE1 و PE2 و PE3 و PE4 و PE5 و PE6 نلعي و RR.

RR نم ةئدابلا هذو لبق تسبي يذلاو، PE لخدملا وه PE6.

دحل نبيوكت متي و BGP ةسلج لك ىلع Add-PATH نبيكم متي، كلذ فالخ ركذي مل ام VPN4 ناو ناعلا ةلئاعل يداحأل ثبلا RR ىلع 3 IBGP تاراسملا لىصقألا.

نم رثكأ CEF و RIB لودج يف لىصقأ دحك تبتثم دحاو يطايتحإ خسن راسم دجوي: **ةظحال** م رثكأ RIB لودج و BGP لودج يف يطايتحإ ةخسنك راسملا زيي متي. موعدم/نكمم ريغ دحاو CEF لودج.

نكمي. ةلاقملا هذو يف BGP لوكوتورب ةطساوب امئاد يطايتحإلا خسنلا راسم رايتحإ متي BGP نوكتي ام امئاد انه نكلو، ىرخأ ةزييم ةطساوب يطايتحإلا خسنلا راسم رايتحإ

تاراسملا ةددعتم تاراسم تيبثت متي دق، BGP لوكوتورب ل ةددعتم تاراسم نبيوكت متي اذإ خسنلا راسم. **ةددعتملا تاراسملا** اهلل ةمالع عضو متي. BGP لودج يف (ECMP أو UCMP) ناك اذإ تاراسملا ةددعتم تاراسملا دحا نوكتي نا بجي كلذل، راسم لىصقأ يثا وه يطايتحإلا (ةددعتملا تاراسملا ةيامح) يطايتحإلا ةخسنك انه نوكتي نا نكمي هنأ ينعي اذهو. اهنم يا كانه **تاراسملا ةيامح** ةساسالا ةملكلا) ةزيملا هذو نبيوكت متي اذإ BGP ةطساوب اهرايتحإ متي خسنلا راسم نإ، لاحلا وه اذه ناك اذإ. (ةساسا-راسم ديحت-راسم نبييغت نايب يف ةددعتملا نإ CEF و RIB لودج يف يطايتحإلا خسنلا راسم وه اذه (ةددعتملا تاراسملا ةيامح) يطايتحإلا نم لكشلا اذو هيلع ةمالع عضو متي و BGP لبق نم هرايتحإ متي يذلا يطايتحإلا خسنلا راسم تاراسملا ددعتم راسم درجم وه لب، يطايتحإلا خسنلا راسم ذئنيح سيل BGP لبق

ناك اذإ ريبك لكشب ايقطنم (RR) يطايتحإلا لوجم لوجم ىلع يطايتحإلا راسملا نوكتي ال وي دارلا ددرت هبعلي يذلا رودلا طقف اذه وي دارلا ددرت.

خسن راسم دي دحتب مق ،ةلجال هذه في PE هجوم اضيأ وه RR نأ ضررت في ،ةلاقملا هذه في BGP ةقابطل يطايتجالا خسنلا راسم مادختسا نكمي .يقطنم لكشبت ويطايتجالا PIC.

ةدحمل ةئدابلل دي دحت دنع RIB في يطايتجالا خسنلاب يطايتجالا خسنلا راسم زييمت متي ةئدابلل دي دحت متي مل اذا "!" مادختساب وأ

```
RP/0/RP0/CPU0:RR#show route vrf one 10.1.1.1/32
Routing entry for 10.1.1.1/32
  Known via "bgp 65000", distance 200, metric 0
  Number of pic paths 1 , type internal
  Installed Sep 17 13:25:25.064 for 00:03:27
  Routing Descriptor Blocks
    10.0.0.1, from 10.0.0.1, BGP multi path
      Nexthop in Vrf: "default", Table: "default", IPv4 Unicast, Table Id: 0xe0000000
      Route metric is 0
    10.0.0.2, from 10.0.0.2, BGP backup path
      Nexthop in Vrf: "default", Table: "default", IPv4 Unicast, Table Id: 0xe0000000
      Route metric is 0
    10.0.0.3, from 10.0.0.3, BGP multi path
      Nexthop in Vrf: "default", Table: "default", IPv4 Unicast, Table Id: 0xe0000000
      Route metric is 0
    10.0.0.4, from 10.0.0.4, BGP multi path
      Nexthop in Vrf: "default", Table: "default", IPv4 Unicast, Table Id: 0xe0000000
      Route metric is 0
  No advertising protos.
```

```
RP/0/RP0/CPU0:RR#show route vrf one
```

```
Codes: C - connected, S - static, R - RIP, B - BGP, (>) - Diversion path
       D - EIGRP, EX - EIGRP external, O - OSPF, IA - OSPF inter area
       N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2
       E1 - OSPF external type 1, E2 - OSPF external type 2, E - EGP
       i - ISIS, L1 - IS-IS level-1, L2 - IS-IS level-2
       ia - IS-IS inter area, su - IS-IS summary null, * - candidate default
       U - per-user static route, o - ODR, L - local, G - DAGR, l - LISP
       A - access/subscriber, a - Application route
       M - mobile route, r - RPL, t - Traffic Engineering, (!) - FRR Backup path
```

```
Gateway of last resort is not set
```

```
B    10.1.1.1/32 [200/0] via 10.0.0.1 (nexthop in vrf default), 00:02:16
      [200/0] via 10.0.0.2 (nexthop in vrf default), 00:02:16 (!)
      [200/0] via 10.0.0.3 (nexthop in vrf default), 00:02:16
      [200/0] via 10.0.0.4 (nexthop in vrf default), 00:02:16
```

راسملا تاسايس في راسملا دي دحت رماو نيينت

ةلئاعل راسملا ةسايس في ةمدختسملا راسملا نيينت تارابع عي مج مسقلا اذه يطغي هجوملل BGP لوكوتورب نمض ةدحمل نيوانعلا

اذه pre-أو post-Cisco IOS®-XR 7.3.1 وه Cisco IOS®-XR رادصا نرع رظنلا ضغب اذه

نيناوكتلا:

```
router bgp 65000
  address-family ipv4 unicast
```

```
!  
address-family vpnv4 unicast  
additional-paths receive  
additional-paths send  
additional-paths selection route-policy BGP-Path-Selection  
!  
neighbor 10.0.0.1  
remote-as 65000  
update-source Loopback0  
address-family ipv4 unicast  
route-reflector-client  
!  
address-family vpnv4 unicast  
route-reflector-client  
!  
!  
neighbor 10.0.0.2  
remote-as 65000  
update-source Loopback0  
address-family ipv4 unicast  
route-reflector-client  
!  
address-family vpnv4 unicast  
route-reflector-client  
!  
!  
neighbor 10.0.0.3  
remote-as 65000  
update-source Loopback0  
address-family ipv4 unicast  
route-reflector-client  
!  
address-family vpnv4 unicast  
route-reflector-client  
!  
!  
neighbor 10.0.0.4  
remote-as 65000  
update-source Loopback0  
address-family ipv4 unicast  
route-reflector-client  
!  
address-family vpnv4 unicast  
route-reflector-client  
!  
!  
neighbor 10.0.0.5  
remote-as 65000  
update-source Loopback0  
address-family ipv4 unicast  
route-reflector-client  
!  
address-family vpnv4 unicast  
route-reflector-client  
!  
!  
neighbor 10.0.0.6  
remote-as 65000  
update-source Loopback0  
address-family ipv4 unicast  
route-reflector-client  
!  
address-family vpnv4 unicast  
route-reflector-client
```

```

!
!
vrf one
rd 1:1
address-family ipv4 unicast
  maximum-paths ibgp 3
  additional-paths selection route-policy BGP-Path-Selection
  redistribute connected
!
!
!

```

ةلئاعل يداحألأ شبلأ تحت ةعوومجملأ راسملا ديدحت تارابع عم راسملا ةسايس قيبطت متي وناونعلال vpv4.

مزلي ناك اذا بولطم اذهو. VRF يلع راسملا نييعت تارابع عم راسملا جهن قيبطت متي امك ربع هنع نالعالأ و) VRF لوكوتوربب صاخلا RIB/CEF لودج يفي طايحتإ خسن راسم تيبتت (PE-CE طابتراربع BGP لمع ةسلج).

تحت ةفلتخم تاسايس قيبطت نكمي نكلو، اهسفن يه راسملا تاسايس نم الك، انه VRF تحت لباقم وناونعلال ةلئاع.

لصي ام دوجو ةيناكلما ديدحت عم VRF One نمض *iBGP 3* راسملا صقألا دحلا مادختسا متي ل RIB/CEF لودج يفي ECMP تاراسم ةثالث ل.

راسملا ديدحت نييعت عم راسملا جهن تايناكلما عيمج تالاحل هذه رهظت.

1. راسملا ديدحت نم ةيطايتحالا ةخسنلا تيبتت نييعت

```

route-policy BGP-Path-Selection
  set path-selection backup 1 install
end-policy
!

```

```
RP/0/RP0/CPU0:RR#show bgp vpv4 unicast rd 1:1 10.1.1.1/32
```

BGP routing table entry for 10.1.1.1/32, Route Distinguisher: 1:1

Versions:

Process	bRIB/RIB	SendTblVer
Speaker	5	5

Last Modified: Sep 17 13:14:35.907 for 00:04:41

Paths: (5 available, best #1)

Advertised to update-groups (with more than one peer):

0.2 0.3

Path #1: Received by speaker 0

Advertised to update-groups (with more than one peer):

0.2 0.3

Local, (Received from a RR-client)

10.0.0.1 (metric 2) from 10.0.0.1 (10.0.0.1)

Received Label 24012

Origin incomplete, metric 0, localpref 100, valid, internal, **best**, **group-best**, **multipath**,

import-candidate, imported

Received Path ID 0, Local Path ID 1, version 5

Extended community: RT:65000:1

Source AFI: VpNv4 Unicast, Source VRF: one, Source Route Distinguisher: 1:1

Path #2: Received by speaker 0

Not advertised to any peer

Local, (Received from a RR-client)

10.0.0.2 (metric 2) from 10.0.0.2 (10.0.0.2)

```

Received Label 24012
Origin incomplete, metric 0, localpref 100, valid, internal, multipath, backup, add-path,
import-candidate, imported
Received Path ID 0, Local Path ID 2, version 5
Extended community: RT:65000:1
Source AFI: VPNv4 Unicast, Source VRF: one, Source Route Distinguisher: 1:1
Path #3: Received by speaker 0
Not advertised to any peer
Local, (Received from a RR-client)
  10.0.0.3 (metric 2) from 10.0.0.3 (10.0.0.3)
    Received Label 24012
    Origin incomplete, metric 0, localpref 100, valid, internal, import-candidate, imported
    Received Path ID 0, Local Path ID 0, version 0
    Extended community: RT:65000:1
    Source AFI: VPNv4 Unicast, Source VRF: one, Source Route Distinguisher: 1:1
Path #4: Received by speaker 0
Not advertised to any peer
Local, (Received from a RR-client)
  10.0.0.4 (metric 2) from 10.0.0.4 (10.0.0.4)
    Received Label 24013
    Origin incomplete, metric 0, localpref 100, valid, internal, import-candidate, imported
    Received Path ID 0, Local Path ID 0, version 0
    Extended community: RT:65000:1
    Source AFI: VPNv4 Unicast, Source VRF: one, Source Route Distinguisher: 1:1
Path #5: Received by speaker 0
Not advertised to any peer
Local, (Received from a RR-client)
  10.0.0.5 (metric 2) from 10.0.0.5 (10.0.0.5)
    Received Label 24014
    Origin incomplete, metric 0, localpref 100, valid, internal, multipath, import-candidate,
imported
    Received Path ID 1, Local Path ID 0, version 0
    Extended community: RT:65000:1
    Source AFI: VPNv4 Unicast, Source VRF: one, Source Route Distinguisher: 1:

```

RP/0/RP0/CPU0:RR#**show route vrf one 10.1.1.1/32**

Routing entry for 10.1.1.1/32

Known via "bgp 65000", distance 200, metric 0

Number of pic paths 1 , type internal

Installed Sep 17 13:25:25.064 for 00:03:27

Routing Descriptor Blocks

10.0.0.1, from 10.0.0.1, **BGP multi path**

Nexthop in Vrf: "default", Table: "default", IPv4 Unicast, Table Id: 0xe0000000

Route metric is 0

10.0.0.2, from 10.0.0.2, **BGP backup path**

Nexthop in Vrf: "default", Table: "default", IPv4 Unicast, Table Id: 0xe0000000

Route metric is 0

10.0.0.3, from 10.0.0.3, **BGP multi path**

Nexthop in Vrf: "default", Table: "default", IPv4 Unicast, Table Id: 0xe0000000

Route metric is 0

10.0.0.4, from 10.0.0.4, **BGP multi path**

Nexthop in Vrf: "default", Table: "default", IPv4 Unicast, Table Id: 0xe0000000

Route metric is 0

No advertising protos.

RP/0/RP0/CPU0:RR#**show cef vrf one 10.1.1.1/32**

10.1.1.1/32, version 119, internal 0x5000001 0x30 (ptr 0xd96a770) [1], 0x0 (0xe3662a8), 0xa08 (0xf4e10a8)

Updated Sep 17 13:25:25.068

Prefix Len 32, traffic index 0, precedence n/a, priority 3

via 10.0.0.1/32, 3 dependencies, recursive, **bgp-multipath** [flags 0x6080]

path-idx 0 NHID 0x0 [0xdab2bc0 0x0], Internal 0xd6a2730

recursion-via-/32

```

next hop VRF - 'default', table - 0xe0000000
next hop 10.0.0.1/32 via 24003/0/21
  next hop 10.1.101.1/32 Gi0/0/0/0    labels imposed {ImplNull 24012}
via 10.0.0.2/32, 2 dependencies, recursive, backup [flags 0x6100]
  path-idx 1 NHID 0x0 [0xdab2e48 0x0]
  recursion-via-/32
next hop VRF - 'default', table - 0xe0000000
next hop 10.0.0.2/32 via 24001/0/21
  next hop 10.2.101.2/32 Gi0/0/0/4    labels imposed {ImplNull 24012}
via 10.0.0.3/32, 3 dependencies, recursive, bgp-multipath [flags 0x6080]
  path-idx 2 NHID 0x0 [0xdab2060 0x0], Internal 0xd6a2550
  recursion-via-/32
next hop VRF - 'default', table - 0xe0000000
next hop 10.0.0.3/32 via 24007/0/21
  next hop 10.3.101.3/32 Gi0/0/0/6    labels imposed {ImplNull 24012}
via 10.0.0.4/32, 3 dependencies, recursive, bgp-multipath [flags 0x6080]
  path-idx 3 NHID 0x0 [0xdab2c98 0x0], Internal 0xd6a2190
  recursion-via-/32
next hop VRF - 'default', table - 0xe0000000
next hop 10.0.0.4/32 via 24000/0/21
  next hop 10.4.101.4/32 Gi0/0/0/7    labels imposed {ImplNull 24013}

```

اهن ع نل عمل تاراسم ل ن م ق قحت

```

RP/0/RP0/CPU0:PE6#show bgp vpnv4 unicast rd 1:1 10.1.1.1/32
BGP routing table entry for 10.1.1.1/32, Route Distinguisher: 1:1
Versions:
  Process          bRIB/RIB  SendTblVer
  Speaker          87        87
Last Modified: Sep 17 13:50:32.649 for 00:00:42
Paths: (1 available, best #1)
  Not advertised to any peer
  Path #1: Received by speaker 0
  Not advertised to any peer
Local
  10.0.0.1 (metric 3) from 10.0.0.101 (10.0.0.1)
    Received Label 24012
    Origin incomplete, metric 0, localpref 100, valid, internal, best, group-best, import-
candidate, imported
    Received Path ID 1, Local Path ID 1, version 87
    Extended community: RT:65000:1
    Originator: 10.0.0.1, Cluster list: 10.0.0.101
    Source AFI: VPNv4 Unicast, Source VRF: one, Source Route Distinguisher: 1:1

```

راسم ل ن ع نال ع ل م تي. VRF في RR ل ع ت ب ث م د ح او ي ط ا ي ت ح ل خ س ن ر ا س م د ج و ي : ة م ت ا خ ل ا ط ق ف ل ض ف ا ل ا

2. راسم ل دي دحت ل 1 ي ط ا ي ت ح ل ا خ س ن ل ا ت ا ن ا ل ع ل ن ي ع ت

```

route-policy BGP-Path-Selection
  set path-selection backup 1 advertise
end-policy
!
```

```

RP/0/RP0/CPU0:RR#show bgp vpnv4 unicast rd 1:1 10.1.1.1/32
BGP routing table entry for 10.1.1.1/32, Route Distinguisher: 1:1
Versions:
  Process          bRIB/RIB  SendTblVer
  Speaker          5         5
Last Modified: Sep 17 13:38:03.907 for 00:02:04
Paths: (5 available, best #1)

```

```

Advertised to update-groups (with more than one peer):
  0.2 0.3
Path #1: Received by speaker 0
Advertised to update-groups (with more than one peer):
  0.2 0.3
Local, (Received from a RR-client)
  10.0.0.1 (metric 2) from 10.0.0.1 (10.0.0.1)
    Received Label 24012
    Origin incomplete, metric 0, localpref 100, valid, internal, best, group-best, multipath,
import-candidate, imported
    Received Path ID 0, Local Path ID 1, version 5
    Extended community: RT:65000:1
    Source AFI: VPNv4 Unicast, Source VRF: one, Source Route Distinguisher: 1:1
Path #2: Received by speaker 0
Advertised to update-groups (with more than one peer):
  0.3
Local, (Received from a RR-client)
  10.0.0.2 (metric 2) from 10.0.0.2 (10.0.0.2)
    Received Label 24012
    Origin incomplete, metric 0, localpref 100, valid, internal, multipath, backup, add-path,
import-candidate, imported
    Received Path ID 0, Local Path ID 2, version 5
    Extended community: RT:65000:1
    Source AFI: VPNv4 Unicast, Source VRF: one, Source Route Distinguisher: 1:1
Path #3: Received by speaker 0
Not advertised to any peer
Local, (Received from a RR-client)
  10.0.0.3 (metric 2) from 10.0.0.3 (10.0.0.3)
    Received Label 24012
    Origin incomplete, metric 0, localpref 100, valid, internal, import-candidate, imported
    Received Path ID 0, Local Path ID 0, version 0
    Extended community: RT:65000:1
    Source AFI: VPNv4 Unicast, Source VRF: one, Source Route Distinguisher: 1:1
Path #4: Received by speaker 0
Not advertised to any peer
Local, (Received from a RR-client)
  10.0.0.4 (metric 2) from 10.0.0.4 (10.0.0.4)
    Received Label 24013
    Origin incomplete, metric 0, localpref 100, valid, internal, multipath, import-candidate,
imported
    Received Path ID 0, Local Path ID 0, version 0
    Extended community: RT:65000:1
    Source AFI: VPNv4 Unicast, Source VRF: one, Source Route Distinguisher: 1:1
Path #5: Received by speaker 0
Not advertised to any peer
Local, (Received from a RR-client)
  10.0.0.5 (metric 2) from 10.0.0.5 (10.0.0.5)
    Received Label 24014
    Origin incomplete, metric 0, localpref 100, valid, internal, import-candidate, imported
    Received Path ID 1, Local Path ID 0, version 0
    Extended community: RT:65000:1
    Source AFI: VPNv4 Unicast, Source VRF: one, Source Route Distinguisher: 1:1

```

RP/0/RP0/CPU0:RR#**show route vrf one 10.1.1.1/32**

Routing entry for 10.1.1.1/32

Known via "bgp 65000", distance 200, metric 0, type internal

Installed Sep 17 13:38:04.233 for 00:04:26

Routing Descriptor Blocks

10.0.0.1, from 10.0.0.1, **BGP multi path**

Nexthop in Vrf: "default", Table: "default", IPv4 Unicast, Table Id: 0xe0000000

Route metric is 0

10.0.0.2, from 10.0.0.2, **BGP multi path**

Nexthop in Vrf: "default", Table: "default", IPv4 Unicast, Table Id: 0xe0000000

```
Route metric is 0
10.0.0.4, from 10.0.0.4, BGP multi path
NextHop in Vrf: "default", Table: "default", IPv4 Unicast, Table Id: 0xe0000000
Route metric is 0
No advertising protos.
```

```
RP/0/RP0/CPU0:RR#show cef vrf one 10.1.1.1/32
```

```
10.1.1.1/32, version 135, internal 0x5000001 0x30 (ptr 0xd96a770) [1], 0x0 (0xe3662a8), 0xa08 (0xf696158)
```

```
Updated Sep 17 13:38:04.236
```

```
Prefix Len 32, traffic index 0, precedence n/a, priority 3
```

```
via 10.0.0.1/32, 3 dependencies, recursive, bgp-multipath [flags 0x6080]
```

```
path-idx 0 NHID 0x0 [0xdab2bc0 0x0]
```

```
recursion-via-/32
```

```
next hop VRF - 'default', table - 0xe0000000
```

```
next hop 10.0.0.1/32 via 24003/0/21
```

```
next hop 10.1.101.1/32 Gi0/0/0/0 labels imposed {ImplNull 24012}
```

```
via 10.0.0.2/32, 3 dependencies, recursive, bgp-multipath [flags 0x6080]
```

```
path-idx 1 NHID 0x0 [0xdab2e48 0x0]
```

```
recursion-via-/32
```

```
next hop VRF - 'default', table - 0xe0000000
```

```
next hop 10.0.0.2/32 via 24001/0/21
```

```
next hop 10.2.101.2/32 Gi0/0/0/4 labels imposed {ImplNull 24012}
```

```
via 10.0.0.4/32, 3 dependencies, recursive, bgp-multipath [flags 0x6080]
```

```
path-idx 2 NHID 0x0 [0xdab2c98 0x0]
```

```
recursion-via-/32
```

```
next hop VRF - 'default', table - 0xe0000000
```

```
next hop 10.0.0.4/32 via 24000/0/21
```

```
next hop 10.4.101.4/32 Gi0/0/0/7 labels imposed {ImplNull 24013}
```

اهن نل عمل تاراسملا نم ققحت

```
RP/0/RP0/CPU0:PE6#show bgp vpnv4 unicast rd 1:1 10.1.1.1/32
```

```
BGP routing table entry for 10.1.1.1/32, Route Distinguisher: 1:1
```

```
Versions:
```

```
Process bRIB/RIB SendTblVer
```

```
Speaker 73 73
```

```
Last Modified: Sep 17 13:38:05.649 for 00:02:47
```

```
Paths: (2 available, best #1)
```

```
Not advertised to any peer
```

```
Path #1: Received by speaker 0
```

```
Not advertised to any peer
```

```
Local
```

```
10.0.0.1 (metric 3) from 10.0.0.101 (10.0.0.1)
```

```
Received Label 24012
```

```
Origin incomplete, metric 0, localpref 100, valid, internal, best, group-best, import-candidate, imported
```

```
Received Path ID 1, Local Path ID 1, version 73
```

```
Extended community: RT:65000:1
```

```
Originator: 10.0.0.1, Cluster list: 10.0.0.101
```

```
Source AFI: VPNv4 Unicast, Source VRF: one, Source Route Distinguisher: 1:1
```

```
Path #2: Received by speaker 0
```

```
Not advertised to any peer
```

```
Local
```

```
10.0.0.2 (metric 3) from 10.0.0.101 (10.0.0.2)
```

```
Received Label 24012
```

```
Origin incomplete, metric 0, localpref 100, valid, internal, import-candidate, imported
```

```
Received Path ID 2, Local Path ID 0, version 0
```

```
Extended community: RT:65000:1
```

```
Originator: 10.0.0.2, Cluster list: 10.0.0.101
```

```
Source AFI: VPNv4 Unicast, Source VRF: one, Source Route Distinguisher: 1:1
```

يطايتحال خسنللا راسم نع نالعالإ م تي .يطايتحال خسنللا راسم تي بثت م تي مل :ةمخال

تانالعالإ تي بثت ةأدا 1 راسملا ديحتل يطايتحال خسنللا ةأدا ني عت 3.

```
route-policy BGP-Path-Selection
  set path-selection backup 1 advertise install
end-policy
!
```

```
RP/0/RP0/CPU0:RR#show bgp vpnv4 unicast rd 1:1 10.1.1.1/32
```

```
BGP routing table entry for 10.1.1.1/32, Route Distinguisher: 1:1
```

```
Versions:
```

```
Process          bRIB/RIB  SendTblVer
```

```
Speaker          5         5
```

```
Last Modified: Sep 17 14:20:36.907 for 00:01:55
```

```
Paths: (5 available, best #1)
```

```
Advertised to update-groups (with more than one peer):
```

```
0.2 0.3
```

```
Path #1: Received by speaker 0
```

```
Advertised to update-groups (with more than one peer):
```

```
0.2 0.3
```

```
Local, (Received from a RR-client)
```

```
10.0.0.1 (metric 2) from 10.0.0.1 (10.0.0.1)
```

```
Received Label 24012
```

```
Origin incomplete, metric 0, localpref 100, valid, internal, best, group-best, multipath,
```

```
import-candidate, imported
```

```
Received Path ID 0, Local Path ID 1, version 5
```

```
Extended community: RT:65000:1
```

```
Source AFI: VPNv4 Unicast, Source VRF: one, Source Route Distinguisher: 1:1
```

```
Path #2: Received by speaker 0
```

```
Advertised to update-groups (with more than one peer):
```

```
0.3
```

```
Local, (Received from a RR-client)
```

```
10.0.0.2 (metric 2) from 10.0.0.2 (10.0.0.2)
```

```
Received Label 24012
```

```
Origin incomplete, metric 0, localpref 100, valid, internal, multipath, backup, add-path,
```

```
import-candidate, imported
```

```
Received Path ID 0, Local Path ID 2, version 5
```

```
Extended community: RT:65000:1
```

```
Source AFI: VPNv4 Unicast, Source VRF: one, Source Route Distinguisher: 1:1
```

```
Path #3: Received by speaker 0
```

```
Not advertised to any peer
```

```
Local, (Received from a RR-client)
```

```
10.0.0.3 (metric 2) from 10.0.0.3 (10.0.0.3)
```

```
Received Label 24012
```

```
Origin incomplete, metric 0, localpref 100, valid, internal, import-candidate, imported
```

```
Received Path ID 0, Local Path ID 0, version 0
```

```
Extended community: RT:65000:1
```

```
Source AFI: VPNv4 Unicast, Source VRF: one, Source Route Distinguisher: 1:1
```

```
Path #4: Received by speaker 0
```

```
Not advertised to any peer
```

```
Local, (Received from a RR-client)
```

```
10.0.0.4 (metric 2) from 10.0.0.4 (10.0.0.4)
```

```
Received Label 24013
```

```
Origin incomplete, metric 0, localpref 100, valid, internal, import-candidate, imported
```

```
Received Path ID 0, Local Path ID 0, version 0
```

```
Extended community: RT:65000:1
```

```
Source AFI: VPNv4 Unicast, Source VRF: one, Source Route Distinguisher: 1:1
```

```
Path #5: Received by speaker 0
```

```
Not advertised to any peer
```

```
Local, (Received from a RR-client)
 10.0.0.5 (metric 2) from 10.0.0.5 (10.0.0.5)
   Received Label 24014
   Origin incomplete, metric 0, localpref 100, valid, internal, multipath, import-candidate,
imported
   Received Path ID 1, Local Path ID 0, version 0
   Extended community: RT:65000:1
   Source AFI: VPNv4 Unicast, Source VRF: one, Source Route Distinguisher: 1:1
```

```
RP/0/RP0/CPU0:RR#show route vrf one 10.1.1.1/32
```

```
Routing entry for 10.1.1.1/32
  Known via "bgp 65000", distance 200, metric 0
  Number of pic paths 1 , type internal
  Installed Sep 17 14:23:42.997 for 00:00:59
  Routing Descriptor Blocks
    10.0.0.1, from 10.0.0.1, BGP multi path
      Nexthop in Vrf: "default", Table: "default", IPv4 Unicast, Table Id: 0xe0000000
      Route metric is 0
    10.0.0.2, from 10.0.0.2, BGP backup path
      Nexthop in Vrf: "default", Table: "default", IPv4 Unicast, Table Id: 0xe0000000
      Route metric is 0
    10.0.0.3, from 10.0.0.3, BGP multi path
      Nexthop in Vrf: "default", Table: "default", IPv4 Unicast, Table Id: 0xe0000000
      Route metric is 0
    10.0.0.5, from 10.0.0.5, BGP multi path
      Nexthop in Vrf: "default", Table: "default", IPv4 Unicast, Table Id: 0xe0000000
      Route metric is 0
  No advertising protos.
```

```
RP/0/RP0/CPU0:RR#show cef vrf one 10.1.1.1/32
```

```
10.1.1.1/32, version 185, internal 0x5000001 0x30 (ptr 0xd96a770) [1], 0x0 (0xe3662a8), 0xa08
(0xf4e10a8)
  Updated Sep 17 14:23:42.999
  Prefix Len 32, traffic index 0, precedence n/a, priority 3
  via 10.0.0.1/32, 3 dependencies, recursive, bgp-multipath [flags 0x6080]
    path-idx 0 NHID 0x0 [0xdab2bc0 0x0], Internal 0xd6a2730
    recursion-via-/32
    next hop VRF - 'default', table - 0xe0000000
    next hop 10.0.0.1/32 via 24003/0/21
      next hop 10.1.101.1/32 Gi0/0/0/0 labels imposed {ImplNull 24012}
  via 10.0.0.2/32, 2 dependencies, recursive, backup [flags 0x6100]
    path-idx 1 NHID 0x0 [0xdab2e48 0x0]
    recursion-via-/32
    next hop VRF - 'default', table - 0xe0000000
    next hop 10.0.0.2/32 via 24001/0/21
      next hop 10.2.101.2/32 Gi0/0/0/4 labels imposed {ImplNull 24012}
  via 10.0.0.3/32, 3 dependencies, recursive, bgp-multipath [flags 0x6080]
    path-idx 2 NHID 0x0 [0xdab2060 0x0], Internal 0xd6a2550
    recursion-via-/32
    next hop VRF - 'default', table - 0xe0000000
    next hop 10.0.0.3/32 via 24007/0/21
      next hop 10.3.101.3/32 Gi0/0/0/6 labels imposed {ImplNull 24012}
  via 10.0.0.5/32, 3 dependencies, recursive, bgp-multipath [flags 0x6080]
    path-idx 3 NHID 0x0 [0xdab2368 0x0], Internal 0xd6a2190
    recursion-via-/32
    next hop VRF - 'default', table - 0xe0000000
    next hop 10.0.0.5/32 via 24005/0/21
      next hop 10.5.101.5/32 Gi0/0/0/1 labels imposed {ImplNull 24014}
```

اهن نل عمل تاراسملا نم ققحت

```
RP/0/RP0/CPU0:PE6#show bgp vpnv4 unicast rd 1:1 10.1.1.1/32
```

BGP routing table entry for 10.1.1.1/32, Route Distinguisher: 1:1

Versions:

```
Process          bRIB/RIB  SendTblVer
Speaker          105      105
```

Last Modified: Sep 17 14:23:43.649 for 00:02:16

Paths: (2 available, best #1)

Not advertised to any peer

Path #1: Received by speaker 0

Not advertised to any peer

Local

10.0.0.1 (metric 3) from 10.0.0.101 (10.0.0.1)

Received Label 24012

Origin incomplete, metric 0, localpref 100, valid, internal, best, group-best, import-candidate, imported

Received Path ID 1, Local Path ID 1, version 105

Extended community: RT:65000:1

Originator: 10.0.0.1, Cluster list: 10.0.0.101

Source AFI: VPNv4 Unicast, Source VRF: one, Source Route Distinguisher: 1:1

Path #2: Received by speaker 0

Not advertised to any peer

Local

10.0.0.2 (metric 3) from 10.0.0.101 (10.0.0.2)

Received Label 24012

Origin incomplete, metric 0, localpref 100, valid, internal, import-candidate, imported

Received Path ID 2, Local Path ID 0, version 0

Extended community: RT:65000:1

Originator: 10.0.0.2, Cluster list: 10.0.0.101

Source AFI: VPNv4 Unicast, Source VRF: one, Source Route Distinguisher: 1:1

إذ. يطايتحالال خسنللا راسم نع نالعالإا متي. يطايتحالال خسنللا راسم تيطبثت مت:ةم تاخاللا
هذه 1. و 2.

4. تانالعالإا لكل راسملا دي دحت تانالعالإا ني عت

```
route-policy BGP-Path-Selection
  set path-selection all advertise
end-policy
!
```

RP/0/RP0/CPU0:RR#show bgp vpnv4 unicast rd 1:1 10.1.1.1/32

BGP routing table entry for 10.1.1.1/32, Route Distinguisher: 1:1

Versions:

```
Process          bRIB/RIB  SendTblVer
Speaker          5         5
```

Last Modified: Sep 17 14:28:58.907 for 00:04:04

Paths: (5 available, best #1)

Advertised to update-groups (with more than one peer):

0.2 0.3

Path #1: Received by speaker 0

Advertised to update-groups (with more than one peer):

0.2 0.3

Local, (Received from a RR-client)

10.0.0.1 (metric 2) from 10.0.0.1 (10.0.0.1)

Received Label 24012

Origin incomplete, metric 0, localpref 100, valid, internal, **best**, group-best, **multipath**, import-candidate, imported

Received Path ID 0, Local Path ID 1, version 5

Extended community: RT:65000:1

Source AFI: VPNv4 Unicast, Source VRF: one, Source Route Distinguisher: 1:1

Path #2: Received by speaker 0

Advertised to update-groups (with more than one peer):

```

0.2
Local, (Received from a RR-client)
  10.0.0.2 (metric 2) from 10.0.0.2 (10.0.0.2)
    Received Label 24012
    Origin incomplete, metric 0, localpref 100, valid, internal, multipath, add-path, import-
candidate, imported
    Received Path ID 0, Local Path ID 4, version 5
    Extended community: RT:65000:1
    Source AFI: VPNv4 Unicast, Source VRF: one, Source Route Distinguisher: 1:1
Path #3: Received by speaker 0
Advertised to update-groups (with more than one peer):
  0.2
Local, (Received from a RR-client)
  10.0.0.3 (metric 2) from 10.0.0.3 (10.0.0.3)
    Received Label 24012
    Origin incomplete, metric 0, localpref 100, valid, internal, add-path, import-candidate,
imported
    Received Path ID 0, Local Path ID 2, version 5
    Extended community: RT:65000:1
    Source AFI: VPNv4 Unicast, Source VRF: one, Source Route Distinguisher: 1:1
Path #4: Received by speaker 0
Advertised to update-groups (with more than one peer):
  0.2
Local, (Received from a RR-client)
  10.0.0.4 (metric 2) from 10.0.0.4 (10.0.0.4)
    Received Label 24013
    Origin incomplete, metric 0, localpref 100, valid, internal, add-path, import-candidate,
imported
    Received Path ID 0, Local Path ID 3, version 5
    Extended community: RT:65000:1
    Source AFI: VPNv4 Unicast, Source VRF: one, Source Route Distinguisher: 1:1
Path #5: Received by speaker 0
Advertised to update-groups (with more than one peer):
  0.2
Local, (Received from a RR-client)
  10.0.0.5 (metric 2) from 10.0.0.5 (10.0.0.5)
    Received Label 24014
    Origin incomplete, metric 0, localpref 100, valid, internal, multipath, add-path, import-
candidate, imported
    Received Path ID 1, Local Path ID 5, version 5
    Extended community: RT:65000:1
    Source AFI: VPNv4 Unicast, Source VRF: one, Source Route Distinguisher: 1:1

```

```
RP/0/RP0/CPU0:RR#show route vrf one 10.1.1.1/32
```

```
Routing entry for 10.1.1.1/32
```

```
Known via "bgp 65000", distance 200, metric 0, type internal
```

```
Installed Sep 17 14:28:59.169 for 00:04:52
```

```
Routing Descriptor Blocks
```

```
  10.0.0.1, from 10.0.0.1, BGP multi path
```

```
    Nexthop in Vrf: "default", Table: "default", IPv4 Unicast, Table Id: 0xe0000000
    Route metric is 0
```

```
  10.0.0.2, from 10.0.0.2, BGP multi path
```

```
    Nexthop in Vrf: "default", Table: "default", IPv4 Unicast, Table Id: 0xe0000000
    Route metric is 0
```

```
  10.0.0.5, from 10.0.0.5, BGP multi path
```

```
    Nexthop in Vrf: "default", Table: "default", IPv4 Unicast, Table Id: 0xe0000000
    Route metric is 0
```

```
No advertising protos.
```

```
RP/0/RP0/CPU0:RR#show cef vrf one 10.1.1.1/32
```

```
10.1.1.1/32, version 201, internal 0x5000001 0x30 (ptr 0xd96a770) [1], 0x0 (0xe3662a8), 0xa08
(0xf696158)
```

```
Updated Sep 17 14:28:59.175
```

```

Prefix Len 32, traffic index 0, precedence n/a, priority 3
via 10.0.0.1/32, 3 dependencies, recursive, bgp-multipath [flags 0x6080]
  path-idx 0 NHID 0x0 [0xdab2bc0 0x0]
  recursion-via-/32
  next hop VRF - 'default', table - 0xe0000000
  next hop 10.0.0.1/32 via 24003/0/21
    next hop 10.1.101.1/32 Gi0/0/0/0    labels imposed {ImplNull 24012}
via 10.0.0.2/32, 3 dependencies, recursive, bgp-multipath [flags 0x6080]
  path-idx 1 NHID 0x0 [0xdab2e48 0x0]
  recursion-via-/32
  next hop VRF - 'default', table - 0xe0000000
  next hop 10.0.0.2/32 via 24001/0/21
    next hop 10.2.101.2/32 Gi0/0/0/4    labels imposed {ImplNull 24012}
via 10.0.0.5/32, 3 dependencies, recursive, bgp-multipath [flags 0x6080]
  path-idx 2 NHID 0x0 [0xdab2368 0x0]
  recursion-via-/32
  next hop VRF - 'default', table - 0xe0000000
  next hop 10.0.0.5/32 via 24005/0/21
    next hop 10.5.101.5/32 Gi0/0/0/1    labels imposed {ImplNull 24014}

```

اهنن نل عمل ااراسم لا نم ققحت

```
RP/0/RP0/CPU0:PE6#show bgp vpnv4 unicast rd 1:1 10.1.1.1/32
```

BGP routing table entry for 10.1.1.1/32, Route Distinguisher: 1:1

Versions:

Process	BRIB/RIB	SendTblVer
Speaker	125	125

Last Modified: Sep 17 14:29:00.649 for 00:02:21

Paths: (5 available, best #1)

Not advertised to any peer

Path #1: Received by speaker 0

Not advertised to any peer

Local

10.0.0.1 (metric 3) from 10.0.0.101 (10.0.0.1)

Received Label 24012

Origin incomplete, metric 0, localpref 100, valid, internal, best, group-best, import-candidate, imported

Received Path ID 1, Local Path ID 1, version 125

Extended community: RT:65000:1

Originator: 10.0.0.1, Cluster list: 10.0.0.101

Source AFI: VPNv4 Unicast, Source VRF: one, Source Route Distinguisher: 1:1

Path #2: Received by speaker 0

Not advertised to any peer

Local

10.0.0.3 (metric 3) from 10.0.0.101 (10.0.0.3)

Received Label 24012

Origin incomplete, metric 0, localpref 100, valid, internal, import-candidate, imported

Received Path ID 2, Local Path ID 0, version 0

Extended community: RT:65000:1

Originator: 10.0.0.3, Cluster list: 10.0.0.101

Source AFI: VPNv4 Unicast, Source VRF: one, Source Route Distinguisher: 1:1

Path #3: Received by speaker 0

Not advertised to any peer

Local

10.0.0.4 (metric 3) from 10.0.0.101 (10.0.0.4)

Received Label 24013

Origin incomplete, metric 0, localpref 100, valid, internal, import-candidate, imported

Received Path ID 3, Local Path ID 0, version 0

Extended community: RT:65000:1

Originator: 10.0.0.4, Cluster list: 10.0.0.101

Source AFI: VPNv4 Unicast, Source VRF: one, Source Route Distinguisher: 1:1

Path #4: Received by speaker 0

Not advertised to any peer

Local

10.0.0.2 (metric 3) from 10.0.0.101 (10.0.0.2)

Received Label 24012

Origin incomplete, metric 0, localpref 100, valid, internal, import-candidate, imported

Received Path ID 4, Local Path ID 0, version 0

Extended community: RT:65000:1

Originator: 10.0.0.2, Cluster list: 10.0.0.101

Source AFI: VPNv4 Unicast, Source VRF: one, Source Route Distinguisher: 1:1

Path #5: Received by speaker 0

Not advertised to any peer

Local

10.0.0.5 (metric 3) from 10.0.0.101 (10.0.0.5)

Received Label 24014

Origin incomplete, metric 0, localpref 100, valid, internal, import-candidate, imported

Received Path ID 5, Local Path ID 0, version 0

Extended community: RT:65000:1

Originator: 10.0.0.5, Cluster list: 10.0.0.101

Source AFI: VPNv4 Unicast, Source VRF: one, Source Route Distinguisher: 1:1

(5) تاراسم لاي مج نعالع ال ا متي . ي طاي تح ال ا خ سن ل ا راس م تي ب ث ت متي مل : ة مت ا خ ال

راسم لاي ديحت ل راسم لاض ف ا ني ع ت 5.

```
route-policy BGP-Path-Selection
```

```
  set path-selection best-path
```

```
end-policy
```

```
!
```

```
RP/0/RP0/CPU0:RR#show bgp vpnv4 unicast rd 1:1 10.1.1.1/32
```

```
BGP routing table entry for 10.1.1.1/32, Route Distinguisher: 1:1
```

```
Versions: Process          bRIB/RIB  SendTblVer
```

```
  Speaker              5          5
```

```
Last Modified: Sep 17 15:34:15.907 for 00:00:09
```

```
Paths: (5 available, best #1)
```

```
  Advertised to update-groups (with more than one peer):
```

```
    0.2 0.3
```

```
  Path #1: Received by speaker 0
```

```
  Advertised to update-groups (with more than one peer):
```

```
    0.2 0.3
```

```
Local, (Received from a RR-client)
```

```
  10.0.0.1 (metric 2) from 10.0.0.1 (10.0.0.1)
```

```
    Received Label 24012
```

```
    Origin incomplete, metric 0, localpref 100, valid, internal, best, group-best, multipath,  
import-candidate, imported
```

```
    Received Path ID 0, Local Path ID 1, version 5
```

```
    Extended community: RT:65000:1
```

```
    Source AFI: VPNv4 Unicast, Source VRF: one, Source Route Distinguisher: 1:1
```

```
  Path #2: Received by speaker 0
```

```
  Not advertised to any peer
```

```
Local, (Received from a RR-client)
```

```
  10.0.0.2 (metric 2) from 10.0.0.2 (10.0.0.2)
```

```
    Received Label 24012
```

```
    Origin incomplete, metric 0, localpref 100, valid, internal, multipath, import-candidate,  
imported
```

```
    Received Path ID 0, Local Path ID 0, version 0
```

```
    Extended community: RT:65000:1
```

```
    Source AFI: VPNv4 Unicast, Source VRF: one, Source Route Distinguisher: 1:1
```

```
  Path #3: Received by speaker 0
```

```
  Not advertised to any peer
```

```
Local, (Received from a RR-client)
```

```

10.0.0.3 (metric 2) from 10.0.0.3 (10.0.0.3)
  Received Label 24012
  Origin incomplete, metric 0, localpref 100, valid, internal, multipath, import-candidate,
imported
  Received Path ID 0, Local Path ID 0, version 0
  Extended community: RT:65000:1
  Source AFI: VPNv4 Unicast, Source VRF: one, Source Route Distinguisher: 1:1
Path #4: Received by speaker 0
Not advertised to any peer
Local, (Received from a RR-client)
  10.0.0.4 (metric 2) from 10.0.0.4 (10.0.0.4)
  Received Label 24013
  Origin incomplete, metric 0, localpref 100, valid, internal, import-candidate, imported
  Received Path ID 0, Local Path ID 0, version 0
  Extended community: RT:65000:1
  Source AFI: VPNv4 Unicast, Source VRF: one, Source Route Distinguisher: 1:1
Path #5: Received by speaker 0
Not advertised to any peer
Local, (Received from a RR-client)
  10.0.0.5 (metric 2) from 10.0.0.5 (10.0.0.5)
  Received Label 24014
  Origin incomplete, metric 0, localpref 100, valid, internal, import-candidate, imported
  Received Path ID 1, Local Path ID 0, version 0
  Extended community: RT:65000:1
  Source AFI: VPNv4 Unicast, Source VRF: one, Source Route Distinguisher: 1:1

```

RP/0/RP0/CPU0:RR#**show route vrf one 10.1.1.1/32**

```

Routing entry for 10.1.1.1/32
Known via "bgp 65000", distance 200, metric 0, type internal
Installed Sep 17 15:34:16.311 for 00:00:28
Routing Descriptor Blocks
  10.0.0.1, from 10.0.0.1, BGP multi path
    Nexthop in Vrf: "default", Table: "default", IPv4 Unicast, Table Id: 0xe0000000
    Route metric is 0
  10.0.0.2, from 10.0.0.2, BGP multi path
    Nexthop in Vrf: "default", Table: "default", IPv4 Unicast, Table Id: 0xe0000000
    Route metric is 0
  10.0.0.3, from 10.0.0.3, BGP multi path
    Nexthop in Vrf: "default", Table: "default", IPv4 Unicast, Table Id: 0xe0000000
    Route metric is 0
No advertising protos.

```

RP/0/RP0/CPU0:RR#**show cef vrf one 10.1.1.1/32**

```

10.1.1.1/32, version 215, internal 0x5000001 0x30 (ptr 0xd96a770) [1], 0x0 (0xe3662a8), 0xa08
(0xf696100)
Updated Sep 17 15:34:16.313
Prefix Len 32, traffic index 0, precedence n/a, priority 3
via 10.0.0.1/32, 3 dependencies, recursive, bgp-multipath [flags 0x6080]
  path-idx 0 NHID 0x0 [0xdab2bc0 0x0]
  recursion-via-/32
  next hop VRF - 'default', table - 0xe0000000
  next hop 10.0.0.1/32 via 24003/0/21
    next hop 10.1.101.1/32 Gi0/0/0/0 labels imposed {ImplNull 24012}
via 10.0.0.2/32, 3 dependencies, recursive, bgp-multipath [flags 0x6080]
  path-idx 1 NHID 0x0 [0xdab2e48 0x0]
  recursion-via-/32
  next hop VRF - 'default', table - 0xe0000000
  next hop 10.0.0.2/32 via 24001/0/21
    next hop 10.2.101.2/32 Gi0/0/0/4 labels imposed {ImplNull 24012}
via 10.0.0.3/32, 3 dependencies, recursive, bgp-multipath [flags 0x6080]
  path-idx 2 NHID 0x0 [0xdab2060 0x0]
  recursion-via-/32
  next hop VRF - 'default', table - 0xe0000000

```

```
next hop 10.0.0.3/32 via 24007/0/21
```

```
next hop 10.3.101.3/32 Gi0/0/0/6 labels imposed {ImplNull 24012}
```

نع نالعالإم تي .طقف تاراسملا ددعتم تاراسملا وراسم لصفأ تي بثت م تي :ةمخالل
هع نالع م وأ تبثم وأ دحم يطايتحإ حسن راسم دجوي ال .طقف لصفأال راسملا

6. راسملا دي دحتل تاراسملا ددعتم نالعالإ ني عت

ةبولطم ةيساسأ ةملك وه نالعالإ

```
route-policy BGP-Path-Selection
  set path-selection multipath advertise
end-policy
```

نيوانعلا ةلئاعل BGP ل تاراسملا ددعتم ني كمت كانه نو كي نأ بجي ،كلذ لمعي يكلو
ةددملا

دحاو VRF يف IPv4 unicast ل ررم ددعتملا تنكم ،انه

```
router bgp 65000
  vrf one
  rd 1:1
  address-family ipv4 unicast
    maximum-paths ibgp 3
  additional-paths selection route-policy BGP-Path-Selection
  redistribute connected
```

```
RP/0/RP0/CPU0:RR#show bgp vpnv4 unicast rd 1:1 10.1.1.1/32
```

BGP routing table entry for 10.1.1.1/32, Route Distinguisher: 1:1

Versions:

```
Process          bRIB/RIB  SendTblVer
Speaker          5         5
```

Last Modified: Sep 17 15:40:15.907 for 00:00:28

Paths: (5 available, best #1)

Advertised to update-groups (with more than one peer):

```
0.2 0.3
```

Path #1: Received by speaker 0

Advertised to update-groups (with more than one peer):

```
0.2 0.3
```

Local, (Received from a RR-client)

```
10.0.0.1 (metric 2) from 10.0.0.1 (10.0.0.1)
```

```
Received Label 24012
```

```
Origin incomplete, metric 0, localpref 100, valid, internal, best, group-best, multipath,
```

import-candidate, imported

```
Received Path ID 0, Local Path ID 1, version 5
```

```
Extended community: RT:65000:1
```

```
Source AFI: VPNv4 Unicast, Source VRF: one, Source Route Distinguisher: 1:1
```

Path #2: Received by speaker 0

Advertised to update-groups (with more than one peer):

```
0.3
```

Local, (Received from a RR-client)

```
10.0.0.2 (metric 2) from 10.0.0.2 (10.0.0.2)
```

```
Received Label 24012
```

```
Origin incomplete, metric 0, localpref 100, valid, internal, multipath, add-path, import-  
candidate, imported
```

```
Received Path ID 0, Local Path ID 3, version 5
```

```
Extended community: RT:65000:1
```

```
Source AFI: VPNv4 Unicast, Source VRF: one, Source Route Distinguisher: 1:1
```

Path #3: Received by speaker 0

Not advertised to any peer
Local, (Received from a RR-client)
10.0.0.3 (metric 2) from 10.0.0.3 (10.0.0.3)
Received Label 24012
Origin incomplete, metric 0, localpref 100, valid, internal, import-candidate, imported
Received Path ID 0, Local Path ID 0, version 0
Extended community: RT:65000:1
Source AFI: VPNv4 Unicast, Source VRF: one, Source Route Distinguisher: 1:1

Path #4: Received by speaker 0

Advertised to update-groups (with more than one peer):

0.3

Local, (Received from a RR-client)
10.0.0.4 (metric 2) from 10.0.0.4 (10.0.0.4)
Received Label 24013
Origin incomplete, metric 0, localpref 100, valid, internal, **multipath**, add-path, import-candidate, imported
Received Path ID 0, Local Path ID 2, version 5
Extended community: RT:65000:1
Source AFI: VPNv4 Unicast, Source VRF: one, Source Route Distinguisher: 1:1

Path #5: Received by speaker 0

Not advertised to any peer

Local, (Received from a RR-client)
10.0.0.5 (metric 2) from 10.0.0.5 (10.0.0.5)
Received Label 24014
Origin incomplete, metric 0, localpref 100, valid, internal, import-candidate, imported
Received Path ID 1, Local Path ID 0, version 0
Extended community: RT:65000:1
Source AFI: VPNv4 Unicast, Source VRF: one, Source Route Distinguisher: 1:1

RP/0/RP0/CPU0:RR#**show route vrf one 10.1.1.1/32**

Routing entry for 10.1.1.1/32

Known via "bgp 65000", distance 200, metric 0, type internal

Installed Sep 17 15:40:16.152 for 00:01:11

Routing Descriptor Blocks

10.0.0.1, from 10.0.0.1, **BGP multi path**

Nexthop in Vrf: "default", Table: "default", IPv4 Unicast, Table Id: 0xe0000000

Route metric is 0

10.0.0.2, from 10.0.0.2, **BGP multi path**

Nexthop in Vrf: "default", Table: "default", IPv4 Unicast, Table Id: 0xe0000000

Route metric is 0

10.0.0.4, from 10.0.0.4, **BGP multi path**

Nexthop in Vrf: "default", Table: "default", IPv4 Unicast, Table Id: 0xe0000000

Route metric is 0

No advertising protos.

RP/0/RP0/CPU0:RR#**show cef vrf one 10.1.1.1/32**

10.1.1.1/32, version 229, internal 0x5000001 0x30 (ptr 0xd96a770) [1], 0x0 (0xe3662a8), 0xa08 (0xf6961b0)

Updated Sep 17 15:40:16.156

Prefix Len 32, traffic index 0, precedence n/a, priority 3

via 10.0.0.1/32, 3 dependencies, recursive, **bgp-multipath** [flags 0x6080]

path-idx 0 NHID 0x0 [0xdab2bc0 0x0]

recursion-via-/32

next hop VRF - 'default', table - 0xe0000000

next hop 10.0.0.1/32 via 24003/0/21

next hop 10.1.101.1/32 Gi0/0/0/0 labels imposed {ImplNull 24012}

via 10.0.0.2/32, 3 dependencies, recursive, **bgp-multipath** [flags 0x6080]

path-idx 1 NHID 0x0 [0xdab2e48 0x0]

recursion-via-/32

next hop VRF - 'default', table - 0xe0000000

next hop 10.0.0.2/32 via 24001/0/21

next hop 10.2.101.2/32 Gi0/0/0/4 labels imposed {ImplNull 24012}

via 10.0.0.4/32, 3 dependencies, recursive, **bgp-multipath** [flags 0x6080]

```

path-idx 2 NHID 0x0 [0xdab2c98 0x0]
recursion-via-/32
next hop VRF - 'default', table - 0xe0000000
next hop 10.0.0.4/32 via 24000/0/21
  next hop 10.4.101.4/32 Gi0/0/0/7   labels imposed {ImplNull 24013}

```

اهن نل عم ل تاراسم ل نم ق قحت:

```
RP/0/RP0/CPU0:PE6#show bgp vpnv4 unicast rd 1:1 10.1.1.1/32
```

BGP routing table entry for 10.1.1.1/32, Route Distinguisher: 1:1

Versions:

```

Process          bRIB/RIB  SendTblVer
Speaker          153      153

```

Last Modified: Sep 17 15:40:17.649 for 00:02:08

Paths: (3 available, best #1)

Not advertised to any peer

Path #1: Received by speaker 0

Not advertised to any peer

Local

10.0.0.1 (metric 3) from 10.0.0.101 (10.0.0.1)

Received Label 24012

Origin incomplete, metric 0, localpref 100, valid, internal, best, group-best, import-candidate, imported

Received Path ID 1, Local Path ID 1, version 153

Extended community: RT:65000:1

Originator: 10.0.0.1, Cluster list: 10.0.0.101

Source AFI: VPNv4 Unicast, Source VRF: one, Source Route Distinguisher: 1:1

Path #2: Received by speaker 0

Not advertised to any peer

Local

10.0.0.4 (metric 3) from 10.0.0.101 (10.0.0.4)

Received Label 24013

Origin incomplete, metric 0, localpref 100, valid, internal, import-candidate, imported

Received Path ID 2, Local Path ID 0, version 0

Extended community: RT:65000:1

Originator: 10.0.0.4, Cluster list: 10.0.0.101

Source AFI: VPNv4 Unicast, Source VRF: one, Source Route Distinguisher: 1:1

Path #3: Received by speaker 0

Not advertised to any peer

Local

10.0.0.2 (metric 3) from 10.0.0.101 (10.0.0.2)

Received Label 24012

Origin incomplete, metric 0, localpref 100, valid, internal, import-candidate, imported

Received Path ID 3, Local Path ID 0, version 0

Extended community: RT:65000:1

Originator: 10.0.0.2, Cluster list: 10.0.0.101

Source AFI: VPNv4 Unicast, Source VRF: one, Source Route Distinguisher: 1:1

- ةددم تاراسم مادختساب VPNv4 تاراسم مي لعت متي.
- RIB في ةتبت ةثال ل ةددم تاراسم ل.
- ةثال ل ةددم تاراسم ل ن نال ع ل متي.
- ي طايحت ح ل خسن راسم دجوي ال.

خسن دجوي ال. اهن نال ع ل او RIB في تاراسم ل ةددم تاراسم ل تي بت متي: ةم تال ح ل ن نل عم و ا بت و ا دحم ي طايحت ح ل.

7. ةي امح-تاراسم ل ددم تي بت 1 ةي طايحت ح ل خسن ل دي دحت-راسم ني عت

```
route-policy BGP-Path-Selection
```

```
  set path-selection backup 1 install multipath-protect
```

end-policy

RP/0/RP0/CPU0:RR#show bgp vpnv4 unicast rd 1:1 10.1.1.1/32

BGP routing table entry for 10.1.1.1/32, Route Distinguisher: 1:1

Versions:

Process	bRIB/RIB	SendTblVer
Speaker	5	5

Last Modified: Sep 17 15:46:17.907 for 00:04:59

Paths: (5 available, best #1)

Advertised to update-groups (with more than one peer):
0.2 0.3

Path #1: Received by speaker 0

Advertised to update-groups (with more than one peer):
0.2 0.3

Local, (Received from a RR-client)

10.0.0.1 (metric 2) from 10.0.0.1 (10.0.0.1)

Received Label 24012

Origin incomplete, metric 0, localpref 100, valid, internal, **best**, group-best, **multipath**,
import-candidate, imported

Received Path ID 0, Local Path ID 1, version 5

Extended community: RT:65000:1

Source AFI: VPNv4 Unicast, Source VRF: one, Source Route Distinguisher: 1:1

Path #2: Received by speaker 0

Not advertised to any peer

Local, (Received from a RR-client)

10.0.0.2 (metric 2) from 10.0.0.2 (10.0.0.2)

Received Label 24012

Origin incomplete, metric 0, localpref 100, valid, internal, **multipath**, **backup**, add-path,
import-candidate, imported

Received Path ID 0, Local Path ID 2, version 5

Extended community: RT:65000:1

Source AFI: VPNv4 Unicast, Source VRF: one, Source Route Distinguisher: 1:1

Path #3: Received by speaker 0

Not advertised to any peer

Local, (Received from a RR-client)

10.0.0.3 (metric 2) from 10.0.0.3 (10.0.0.3)

Received Label 24012

Origin incomplete, metric 0, localpref 100, valid, internal, **backup(protect multipath)**,
add-path, import-candidate, imported

Received Path ID 0, Local Path ID 3, version 5

Extended community: RT:65000:1

Source AFI: VPNv4 Unicast, Source VRF: one, Source Route Distinguisher: 1:1

Path #4: Received by speaker 0

Not advertised to any peer

Local, (Received from a RR-client)

10.0.0.4 (metric 2) from 10.0.0.4 (10.0.0.4)

Received Label 24013

Origin incomplete, metric 0, localpref 100, valid, internal, **multipath**, import-candidate,
imported

Received Path ID 0, Local Path ID 0, version 0

Extended community: RT:65000:1

Source AFI: VPNv4 Unicast, Source VRF: one, Source Route Distinguisher: 1:1

Path #5: Received by speaker 0

Not advertised to any peer

Local, (Received from a RR-client)

10.0.0.5 (metric 2) from 10.0.0.5 (10.0.0.5)

Received Label 24014

Origin incomplete, metric 0, localpref 100, valid, internal, import-candidate, imported

Received Path ID 1, Local Path ID 0, version 0

Extended community: RT:65000:1

Source AFI: VPNv4 Unicast, Source VRF: one, Source Route Distinguisher: 1:1

RP/0/RP0/CPU0:RR#show route vrf one 10.1.1.1/32

Routing entry for 10.1.1.1/32

Known via "bgp 65000", distance 200, metric 0

Number of pic paths 1 , type internal

Installed Sep 17 15:46:17.904 for 00:05:14

Routing Descriptor Blocks

10.0.0.1, from 10.0.0.1, **BGP multi path**

Nexthop in Vrf: "default", Table: "default", IPv4 Unicast, Table Id: 0xe0000000

Route metric is 0

10.0.0.2, from 10.0.0.2, **BGP multi path**

Nexthop in Vrf: "default", Table: "default", IPv4 Unicast, Table Id: 0xe0000000

Route metric is 0

10.0.0.3, from 10.0.0.3, **BGP backup path**

Nexthop in Vrf: "default", Table: "default", IPv4 Unicast, Table Id: 0xe0000000

Route metric is 0

10.0.0.4, from 10.0.0.4, **BGP multi path**

Nexthop in Vrf: "default", Table: "default", IPv4 Unicast, Table Id: 0xe0000000

Route metric is 0

No advertising protos.

RP/0/RP0/CPU0:RR#show cef vrf one 10.1.1.1/32

10.1.1.1/32, version 249, internal 0x5000001 0x30 (ptr 0xd96a770) [1], 0x0 (0xe3662a8), 0xa08 (0xf4e10a8)

Updated Sep 17 15:46:17.907

Prefix Len 32, traffic index 0, precedence n/a, priority 3

via 10.0.0.1/32, 3 dependencies, recursive, **bgp-multipath** [flags 0x6080]

path-idx 0 NHID 0x0 [0xdab2bc0 0x0], Internal 0xd6a2190

recursion-via-/32

next hop VRF - 'default', table - 0xe0000000

next hop 10.0.0.1/32 via 24003/0/21

next hop 10.1.101.1/32 Gi0/0/0/0 labels imposed {ImplNull 24012}

via 10.0.0.2/32, 3 dependencies, recursive, **bgp-multipath** [flags 0x6080]

path-idx 1 NHID 0x0 [0xdab2e48 0x0], Internal 0xd6a2550

recursion-via-/32

next hop VRF - 'default', table - 0xe0000000

next hop 10.0.0.2/32 via 24001/0/21

next hop 10.2.101.2/32 Gi0/0/0/4 labels imposed {ImplNull 24012}

via 10.0.0.3/32, 2 dependencies, recursive, **backup** [flags 0x6100]

path-idx 2 NHID 0x0 [0xdab2060 0x0]

recursion-via-/32

next hop VRF - 'default', table - 0xe0000000

next hop 10.0.0.3/32 via 24007/0/21

next hop 10.3.101.3/32 Gi0/0/0/6 labels imposed {ImplNull 24012}

via 10.0.0.4/32, 3 dependencies, recursive, **bgp-multipath** [flags 0x6080]

path-idx 3 NHID 0x0 [0xdab2c98 0x0], Internal 0xd6a2730

recursion-via-/32

next hop VRF - 'default', table - 0xe0000000

next hop 10.0.0.4/32 via 24000/0/21

next hop 10.4.101.4/32 Gi0/0/0/7 labels imposed {ImplNull 24013}

اهن نل عمل تاراسم نم ققحت

RP/0/RP0/CPU0:PE6#show bgp vpnv4 unicast rd 1:1 10.1.1.1/32

BGP routing table entry for 10.1.1.1/32, Route Distinguisher: 1:1

Versions:

Process bRIB/RIB SendTblVer

Speaker 163 163

Last Modified: Sep 17 15:46:18.649 for 00:07:36

Paths: (1 available, best #1)

Not advertised to any peer

Path #1: Received by speaker 0

Not advertised to any peer

Local

10.0.0.1 (metric 3) from 10.0.0.101 (10.0.0.1)

Received Label 24012

Origin incomplete, metric 0, localpref 100, valid, internal, best, group-best, import-candidate, imported

Received Path ID 1, Local Path ID 1, version 163

Extended community: RT:65000:1

Originator: 10.0.0.1, Cluster list: 10.0.0.101

Source AFI: VPNv4 Unicast, Source VRF: one, Source Route Distinguisher: 1:1

ناك اذا، لاثم لاي بس ىلع .(تاراسم لاددعتم ةيامح) يطايتح |خسن راسم كانه نوكي ال دق
كانه نوكي سف ،طقف ني راسم مالتس |متو هنيوكت مت 2 BGP راسم لى صق أل دحل كانه
(تاراسم لاددعتم ةيامح) يطايتح |خسن راسم دجوي الو تاراسم لاددعتم ني راسم

يطايتح |خسن راسم ك رخآ راسم تي بثت مت .RIB يفة تبثم ةددعتم ل تاراسم ل لك :ةم تاخ
طقف لصف أل راسم ل نعالع ال متي .(تاراسم لاددعتم ةيامح) يطايتح |خسن راسم

8. تاراسم لاددعتم تي بثت 1 يطايتح |ال خسن ل راسم لاددعتم تانال ع |ني عت ةيامح ل

```
route-policy BGP-Path-Selection
```

```
set path-selection backup 1 install multipath-protect advertise
```

```
end-policy
```

```
RP/0/RP0/CPU0:RR#show bgp vpnv4 unicast rd 1:1 10.1.1.1/32
```

BGP routing table entry for 10.1.1.1/32, Route Distinguisher: 1:1

Versions:

Process	bRIB/RIB	SendTblVer
Speaker	5	5

Last Modified: Sep 17 16:03:00.907 for 00:01:19

Paths: (5 available, best #1)

Advertised to update-groups (with more than one peer):

0.2 0.3

Path #1: Received by speaker 0

Advertised to update-groups (with more than one peer):

0.2 0.3

Local, (Received from a RR-client)

10.0.0.1 (metric 2) from 10.0.0.1 (10.0.0.1)

Received Label 24012

Origin incomplete, metric 0, localpref 100, valid, internal, **best**, group-best, **multipath**, import-candidate, imported

Received Path ID 0, Local Path ID 1, version 5

Extended community: RT:65000:1

Source AFI: VPNv4 Unicast, Source VRF: one, Source Route Distinguisher: 1:1

Path #2: Received by speaker 0

Advertised to update-groups (with more than one peer):

0.3

Local, (Received from a RR-client)

10.0.0.2 (metric 2) from 10.0.0.2 (10.0.0.2)

Received Label 24012

Origin incomplete, metric 0, localpref 100, valid, internal, **multipath**, **backup**, add-path, import-candidate, imported

Received Path ID 0, Local Path ID 2, version 5

Extended community: RT:65000:1

Source AFI: VPNv4 Unicast, Source VRF: one, Source Route Distinguisher: 1:1

Path #3: Received by speaker 0

Not advertised to any peer

Local, (Received from a RR-client)

10.0.0.3 (metric 2) from 10.0.0.3 (10.0.0.3)

```
Received Label 24012
Origin incomplete, metric 0, localpref 100, valid, internal, multipath, import-candidate,
imported
Received Path ID 0, Local Path ID 0, version 0
Extended community: RT:65000:1
Source AFI: VPNv4 Unicast, Source VRF: one, Source Route Distinguisher: 1:1
Path #4: Received by speaker 0
Not advertised to any peer
Local, (Received from a RR-client)
10.0.0.4 (metric 2) from 10.0.0.4 (10.0.0.4)
Received Label 24013
Origin incomplete, metric 0, localpref 100, valid, internal, backup(protect multipath),
add-path, import-candidate, imported
Received Path ID 0, Local Path ID 3, version 5
Extended community: RT:65000:1
Source AFI: VPNv4 Unicast, Source VRF: one, Source Route Distinguisher: 1:1
Path #5: Received by speaker 0
Not advertised to any peer
Local, (Received from a RR-client)
10.0.0.5 (metric 2) from 10.0.0.5 (10.0.0.5)
Received Label 24014
Origin incomplete, metric 0, localpref 100, valid, internal, import-candidate, imported
Received Path ID 1, Local Path ID 0, version 0
Extended community: RT:65000:1
Source AFI: VPNv4 Unicast, Source VRF: one, Source Route Distinguisher: 1:1
```

RP/0/RP0/CPU0:RR#**show route vrf one 10.1.1.1/32**

```
Routing entry for 10.1.1.1/32
Known via "bgp 65000", distance 200, metric 0
Number of pic paths 1 , type internal
Installed Sep 17 16:03:01.199 for 00:05:13
Routing Descriptor Blocks
10.0.0.1, from 10.0.0.1, BGP multi path
  Nexthop in Vrf: "default", Table: "default", IPv4 Unicast, Table Id: 0xe0000000
  Route metric is 0
10.0.0.2, from 10.0.0.2, BGP multi path
  Nexthop in Vrf: "default", Table: "default", IPv4 Unicast, Table Id: 0xe0000000
  Route metric is 0
10.0.0.3, from 10.0.0.3, BGP multi path
  Nexthop in Vrf: "default", Table: "default", IPv4 Unicast, Table Id: 0xe0000000
  Route metric is 0
10.0.0.4, from 10.0.0.4, BGP backup path
  Nexthop in Vrf: "default", Table: "default", IPv4 Unicast, Table Id: 0xe0000000
  Route metric is 0
No advertising protos.
```

RP/0/RP0/CPU0:RR#**show cef vrf one 10.1.1.1/32**

```
10.1.1.1/32, version 281, internal 0x5000001 0x30 (ptr 0xd96a770) [1], 0x0 (0xe3662a8), 0xa08
(0xf4e1108)
Updated Sep 17 16:03:01.206
Prefix Len 32, traffic index 0, precedence n/a, priority 3
via 10.0.0.1/32, 3 dependencies, recursive, bgp-multipath [flags 0x6080]
  path-idx 0 NHID 0x0 [0xdab2bc0 0x0], Internal 0xd6a2190
  recursion-via-/32
  next hop VRF - 'default', table - 0xe0000000
  next hop 10.0.0.1/32 via 24003/0/21
    next hop 10.1.101.1/32 Gi0/0/0/0 labels imposed {ImplNull 24012}
via 10.0.0.2/32, 3 dependencies, recursive, bgp-multipath [flags 0x6080]
  path-idx 1 NHID 0x0 [0xdab2e48 0x0], Internal 0xd6a2550
  recursion-via-/32
  next hop VRF - 'default', table - 0xe0000000
  next hop 10.0.0.2/32 via 24001/0/21
    next hop 10.2.101.2/32 Gi0/0/0/4 labels imposed {ImplNull 24012}
```

```

via 10.0.0.3/32, 3 dependencies, recursive, bgp-multipath [flags 0x6080]
  path-idx 2 NHID 0x0 [0xdab2060 0x0], Internal 0xd6a2910
  recursion-via-/32
  next hop VRF - 'default', table - 0xe0000000
  next hop 10.0.0.3/32 via 24007/0/21
    next hop 10.3.101.3/32 Gi0/0/0/6 labels imposed {ImplNull 24012}
via 10.0.0.4/32, 2 dependencies, recursive, backup [flags 0x6100]
  path-idx 3 NHID 0x0 [0xdab2c98 0x0]
  recursion-via-/32
  next hop VRF - 'default', table - 0xe0000000
  next hop 10.0.0.4/32 via 24000/0/21
    next hop 10.4.101.4/32 Gi0/0/0/7 labels imposed {ImplNull 24013}

```

اهن ع نل عمل تاراسم ل ن م ق قحت:

```
RP/0/RP0/CPU0:PE6#show bgp vpnv4 unicast rd 1:1 10.1.1.1/32
```

BGP routing table entry for 10.1.1.1/32, Route Distinguisher: 1:1

Versions:

Process	bRIB/RIB	SendTblVer
Speaker	181	181

Last Modified: Sep 17 16:03:02.649 for 00:07:39

Paths: (2 available, best #1)

Not advertised to any peer

Path #1: Received by speaker 0

Not advertised to any peer

Local

10.0.0.1 (metric 3) from 10.0.0.101 (10.0.0.1)

Received Label 24012

Origin incomplete, metric 0, localpref 100, valid, internal, best, group-best, import-candidate, imported

Received Path ID 1, Local Path ID 1, version 181

Extended community: RT:65000:1

Originator: 10.0.0.1, Cluster list: 10.0.0.101

Source AFI: VPNv4 Unicast, Source VRF: one, Source Route Distinguisher: 1:1

Path #2: Received by speaker 0

Not advertised to any peer

Local

10.0.0.2 (metric 3) from 10.0.0.101 (10.0.0.2)

Received Label 24012

Origin incomplete, metric 0, localpref 100, valid, internal, import-candidate, imported

Received Path ID 2, Local Path ID 0, version 0

Extended community: RT:65000:1

Originator: 10.0.0.2, Cluster list: 10.0.0.101

Source AFI: VPNv4 Unicast, Source VRF: one, Source Route Distinguisher: 1:1

- تاراسم ل ةدعتم تاراسم ةثالث كانه.
- يطاي تحال خسن ل راسم وه اذه. دحاو "تاراسم ل ددعتم ةيامح) يطاي تحا خسن" راسم كانه ل و دج يف تبت م ل RIB/CEF.
- ددحم ريغ سم اخل ل راسم ل.
- يطاي تحال خسن ل راسم و ل ضف ال راسم ل ن ع ن ال عال م تي.

ن انك اذا، ل اثم ل ل ي بس ي ل ع. (تاراسم ل ددعتم ةيامح) يطاي تحا خسن راسم كانه نو كي ال دق كانه نو كي سف، طقف ني راسم م ال تس ا م تو ه ني وكت م ت BGP 2 راسم ل ي صق ال ا دحل كانه (تاراسم ل ددعتم ةيامح) يطاي تحا خسن راسم دجوي الو تاراسم ل ي ددعتم ني راسم ل.

يطاي تحال خسن ل) تاراسم ل ةدعتم تاراسم ل دحا وه اذه هن ع نل عمل يطاي تحال خسن ل راسم ل (BGP ل و دج يف زي م ل).

اهن ع نل عمل تاراسم ل ل ي صق ال ا دحل عم اذه

RP/0/RP0/CPU0:RR#show bgp vpnv4 unicast rd 1:1 10.1.1.1/32

BGP routing table entry for 10.1.1.1/32, Route Distinguisher: 1:1

Versions:

Process	bRIB/RIB	SendTblVer
Speaker	5	5

Last Modified: Sep 17 16:15:48.907 for 00:00:44

Paths: (5 available, best #1)

Advertised to update-groups (with more than one peer):

0.2 0.3

Path #1: Received by speaker 0

Advertised to update-groups (with more than one peer):

0.2 0.3

Local, (Received from a RR-client)

10.0.0.1 (metric 2) from 10.0.0.1 (10.0.0.1)

Received Label 24012

Origin incomplete, metric 0, localpref 100, valid, internal, **best**, group-best, import-candidate, imported

Received Path ID 0, Local Path ID 1, version 5

Extended community: RT:65000:1

Source AFI: VPNv4 Unicast, Source VRF: one, Source Route Distinguisher: 1:1

Path #2: Received by speaker 0

Advertised to update-groups (with more than one peer):

0.2

Local, (Received from a RR-client)

10.0.0.2 (metric 2) from 10.0.0.2 (10.0.0.2)

Received Label 24012

Origin incomplete, metric 0, localpref 100, valid, internal, **backup**, add-path, import-candidate, imported

Received Path ID 0, Local Path ID 2, version 5

Extended community: RT:65000:1

Source AFI: VPNv4 Unicast, Source VRF: one, Source Route Distinguisher: 1:1

Path #3: Received by speaker 0

Not advertised to any peer

Local, (Received from a RR-client)

10.0.0.3 (metric 2) from 10.0.0.3 (10.0.0.3)

Received Label 24012

Origin incomplete, metric 0, localpref 100, valid, internal, import-candidate, imported

Received Path ID 0, Local Path ID 0, version 0

Extended community: RT:65000:1

Source AFI: VPNv4 Unicast, Source VRF: one, Source Route Distinguisher: 1:1

Path #4: Received by speaker 0

Not advertised to any peer

Local, (Received from a RR-client)

10.0.0.4 (metric 2) from 10.0.0.4 (10.0.0.4)

Received Label 24013

Origin incomplete, metric 0, localpref 100, valid, internal, import-candidate, imported

Received Path ID 0, Local Path ID 0, version 0

Extended community: RT:65000:1

Source AFI: VPNv4 Unicast, Source VRF: one, Source Route Distinguisher: 1:1

Path #5: Received by speaker 0

Not advertised to any peer

Local, (Received from a RR-client)

10.0.0.5 (metric 2) from 10.0.0.5 (10.0.0.5)

Received Label 24014

Origin incomplete, metric 0, localpref 100, valid, internal, import-candidate, imported

Received Path ID 1, Local Path ID 0, version 0

Extended community: RT:65000:1

Source AFI: VPNv4 Unicast, Source VRF: one, Source Route Distinguisher: 1:1

RP/0/RP0/CPU0:RR#show route vrf one 10.1.1.1/32

Routing entry for 10.1.1.1/32

```
Known via "bgp 65000", distance 200, metric 0
Number of pic paths 1 , type internal
Installed Sep 17 16:15:48.900 for 00:01:28
Routing Descriptor Blocks
 10.0.0.1, from 10.0.0.1
   Nexthop in Vrf: "default", Table: "default", IPv4 Unicast, Table Id: 0xe0000000
   Route metric is 0
 10.0.0.2, from 10.0.0.2, BGP backup path
   Nexthop in Vrf: "default", Table: "default", IPv4 Unicast, Table Id: 0xe0000000
   Route metric is 0
No advertising protos.
```

RP/0/RP0/CPU0:RR#show cef vrf one 10.1.1.1/32

```
10.1.1.1/32, version 297, internal 0x5000001 0x30 (ptr 0xd96a770) [1], 0x0 (0xe3662a8), 0xa08
(0xf6960a8)
Updated Sep 17 16:15:48.903
Prefix Len 32, traffic index 0, precedence n/a, priority 3
via 10.0.0.1/32, 3 dependencies, recursive [flags 0x6000]
 path-idx 0 NHID 0x0 [0xdab2bc0 0x0], Internal 0xd6a2190
 recursion-via-/32
 next hop VRF - 'default', table - 0xe0000000
 next hop 10.0.0.1/32 via 24003/0/21
   next hop 10.1.101.1/32 Gi0/0/0/0 labels imposed {ImplNull 24012}
via 10.0.0.2/32, 2 dependencies, recursive, backup [flags 0x6100]
 path-idx 1 NHID 0x0 [0xdab2e48 0x0]
 recursion-via-/32
 next hop VRF - 'default', table - 0xe0000000
 next hop 10.0.0.2/32 via 24001/0/21
   next hop 10.2.101.2/32 Gi0/0/0/4 labels imposed {ImplNull 24012}
```

اهن نل عمل تاراسملا نم ققحت

RP/0/RP0/CPU0:PE6#show bgp vpnv4 unicast rd 1:1 10.1.1.1/32

BGP routing table entry for 10.1.1.1/32, Route Distinguisher: 1:1

Versions:

Process	bRIB/RIB	SendTblVer
Speaker	189	189

Last Modified: Sep 17 16:15:50.649 for 00:02:10

Paths: (2 available, best #1)

Not advertised to any peer

Path #1: Received by speaker 0

Not advertised to any peer

Local

10.0.0.1 (metric 3) from 10.0.0.101 (10.0.0.1)

Received Label 24012

Origin incomplete, metric 0, localpref 100, valid, internal, best, group-best, import-candidate, imported

Received Path ID 1, Local Path ID 1, version 189

Extended community: RT:65000:1

Originator: 10.0.0.1, Cluster list: 10.0.0.101

Source AFI: VPNv4 Unicast, Source VRF: one, Source Route Distinguisher: 1:1

Path #2: Received by speaker 0

Not advertised to any peer

Local

10.0.0.2 (metric 3) from 10.0.0.101 (10.0.0.2)

Received Label 24012

Origin incomplete, metric 0, localpref 100, valid, internal, import-candidate, imported

Received Path ID 2, Local Path ID 0, version 0

Extended community: RT:65000:1

Originator: 10.0.0.2, Cluster list: 10.0.0.101

Source AFI: VPNv4 Unicast, Source VRF: one, Source Route Distinguisher: 1:1


- RR ىل ع ECMP لوكوتورب دجوي ال
- RIB/CEF لودج ي ف هتېبثت مت .يطايتحالال خسنلاراسم وه راسم لصفأ ي ناث
- .يطايتحالال خسنلاراسمو لصفأالاراسملا نع نالعالا متي
- .(تاراسملا ددعتم ةيماح) .يطايتحالال خسن راسم دجوي ال

.يطايتحالال خسن راسمك رخآ راسم تېبثت مت .RIB ي ف ةتېبثت م ددعتملا تاراسملا لك :ةمتاخلا .يطايتحالال خسنلاراسمو لصفأالاراسملا نع نالعالا متي

9. راسم دي دحت ةعومجم لصفأال تانالعال ني عت

- .نالعالال عم طقف ةعومجم لصفأال مادختسا نكمي
- ةوطخ لكل لكدكو (يتاذلا ماظنلا) AS لكل راسم لصفأال وه لصفأال ةعومجملا دي دحت ةيلات
- .ةفلتخم ةلق تسم ةمظنا نم ةئدابلا أشنت

PE4 نكلو، 1 ةروصلال ي ف اهسفن تاهجوملا دجوت .ةلاجالا هذهل فلتخم طاطخم مادختسا متي AS 65000 ي ف رخآال تاهجوملا عيمج لازت ال .AS 65005 ي ف PE5 و AS 65004 ي ف نالال



2 ةروصلال

PE5 و RR ني و PE4 و RR ني ب eBGP لمع ةسلج نالال دجوت هنا ينعني اذهو

```
route-policy BGP-Path-Selection
  set path-selection group-best advertise
end-policy
```

```
RP/0/RP0/CPU0:RR#show bgp vpnv4 unicast rd 1:1 10.1.1.1/32
```

```
BGP routing table entry for 10.1.1.1/32, Route Distinguisher: 1:1
Versions:
Process          bRIB/RIB  SendTblVer
Speaker          5         5
Local Label: 24010
```

Last Modified: Sep 21 06:06:29.117 for 00:02:18

Paths: (5 available, best #1)

Advertised to update-groups (with more than one peer):

0.3 0.4

Path #1: Received by speaker 0

Advertised to update-groups (with more than one peer):

0.3 0.4

Local, (Received from a RR-client)

10.0.0.1 (metric 2) from 10.0.0.1 (10.0.0.1)

Received Label 24014

Origin incomplete, metric 0, localpref 100, valid, internal, **best**, **group-best**, **multipath**,
import-candidate, imported

Received Path ID 1, Local Path ID 1, version 5

Extended community: RT:65000:1

Source AFI: VPNv4 Unicast, Source VRF: one, Source Route Distinguisher: 1:1

Path #2: Received by speaker 0

Not advertised to any peer

Local, (Received from a RR-client)

10.0.0.2 (metric 2) from 10.0.0.2 (10.0.0.2)

Received Label 24014

Origin incomplete, metric 0, localpref 100, valid, internal, **multipath**, import-candidate,
imported

Received Path ID 1, Local Path ID 0, version 0

Extended community: RT:65000:1

Source AFI: VPNv4 Unicast, Source VRF: one, Source Route Distinguisher: 1:1

Path #3: Received by speaker 0

Not advertised to any peer

Local, (Received from a RR-client)

10.0.0.3 (metric 2) from 10.0.0.3 (10.0.0.3)

Received Label 24014

Origin incomplete, metric 0, localpref 100, valid, internal, **multipath**, import-candidate,
imported

Received Path ID 1, Local Path ID 0, version 0

Extended community: RT:65000:1

Source AFI: VPNv4 Unicast, Source VRF: one, Source Route Distinguisher: 1:1

Path #4: Received by speaker 0

Advertised to update-groups (with more than one peer):

0.4

65004

10.4.101.4 from 10.4.101.4 (10.0.0.4)

Received Label 24015

Origin incomplete, metric 0, localpref 100, valid, external, **group-best**, add-path, import-
candidate, imported

Received Path ID 0, Local Path ID 2, version 5

Extended community: RT:65000:1

Source AFI: VPNv4 Unicast, Source VRF: one, Source Route Distinguisher: 1:1

Path #5: Received by speaker 0

Advertised to update-groups (with more than one peer):

0.4

65005

10.5.101.5 from 10.5.101.5 (10.0.0.5)

Received Label 24014

Origin incomplete, metric 0, localpref 100, valid, external, **group-best**, add-path, import-
candidate, imported

Received Path ID 0, Local Path ID 3, version 5

Extended community: RT:65000:1

Source AFI: VPNv4 Unicast, Source VRF: one, Source Route Distinguisher: 1:1

RP/0/RP0/CPU0:RR#show route vrf one 10.1.1.1/32

Routing entry for 10.1.1.1/32

Known via "bgp 65000", distance 200, metric 0, type internal

Installed Sep 20 19:59:07.762 for 10:00:40

Routing Descriptor Blocks

```
10.0.0.1, from 10.0.0.1, BGP multi path
  Nexthop in Vrf: "default", Table: "default", IPv4 Unicast, Table Id: 0xe0000000
  Route metric is 0
10.0.0.2, from 10.0.0.2, BGP multi path
  Nexthop in Vrf: "default", Table: "default", IPv4 Unicast, Table Id: 0xe0000000
  Route metric is 0
10.0.0.3, from 10.0.0.3, BGP multi path
  Nexthop in Vrf: "default", Table: "default", IPv4 Unicast, Table Id: 0xe0000000
  Route metric is 0
No advertising protos.
```

```
RP/0/RP0/CPU0:RR#show cef vrf one 10.1.1.1/32
```

```
10.1.1.1/32, version 114, internal 0x1000001 0x30 (ptr 0xd96a338) [1], 0x0 (0xe366530), 0xa08
(0xf69e0a8)
```

```
Updated Sep 20 19:59:07.765
```

```
Prefix Len 32, traffic index 0, precedence n/a, priority 3
```

```
via 10.0.0.1/32, 3 dependencies, recursive, bgp-multipath [flags 0x6080]
```

```
path-idx 0 NHID 0x0 [0xdab1b98 0x0]
```

```
recursion-via-/32
```

```
next hop VRF - 'default', table - 0xe0000000
```

```
next hop 10.0.0.1/32 via 24008/0/21
```

```
local label 24010
```

```
next hop 10.1.101.1/32 Gi0/0/0/0 labels imposed {ImplNull 24014}
```

```
via 10.0.0.2/32, 3 dependencies, recursive, bgp-multipath [flags 0x6080]
```

```
path-idx 1 NHID 0x0 [0xdab30d0 0x0]
```

```
recursion-via-/32
```

```
next hop VRF - 'default', table - 0xe0000000
```

```
next hop 10.0.0.2/32 via 24000/0/21
```

```
local label 24010
```

```
next hop 10.2.101.2/32 Gi0/0/0/4 labels imposed {ImplNull 24014}
```

```
via 10.0.0.3/32, 3 dependencies, recursive, bgp-multipath [flags 0x6080]
```

```
path-idx 2 NHID 0x0 [0xdab2918 0x0]
```

```
recursion-via-/32
```

```
next hop VRF - 'default', table - 0xe0000000
```

```
next hop 10.0.0.3/32 via 24002/0/21
```

```
local label 24010
```

```
next hop 10.3.101.3/32 Gi0/0/0/6 labels imposed {ImplNull 24014}
```

CEF و RIB لودج يف ةتبثم ECMP تاراسم ةثالث ىلع يوتحي RR لازي ال

```
RP/0/RP0/CPU0:PE6#show bgp vpnv4 unicast rd 1:1 10.1.1.1/32
```

```
BGP routing table entry for 10.1.1.1/32, Route Distinguisher: 1:1
```

```
Versions:
```

```
Process          bRIB/RIB  SendTblVer
```

```
Speaker          47        47
```

```
Last Modified: Sep 20 19:59:07.588 for 09:59:44
```

```
Paths: (3 available, best #1)
```

```
Not advertised to any peer
```

```
Path #1: Received by speaker 0
```

```
Not advertised to any peer
```

```
Local
```

```
10.0.0.3 (metric 5) from 10.0.0.101 (10.0.0.3)
```

```
Received Label 24014
```

```
Origin incomplete, metric 0, localpref 100, valid, internal, best, group-best, import-
candidate, imported
```

```
Received Path ID 1, Local Path ID 1, version 47
```

```
Extended community: RT:65000:1
```

```
Originator: 10.0.0.3, Cluster list: 10.0.0.101
```

```
Source AFI: VPNv4 Unicast, Source VRF: one, Source Route Distinguisher: 1:1
```

```
Path #2: Received by speaker 0
```

```
Not advertised to any peer
```

```
65004
```

```

10.4.101.4 (metric 3) from 10.0.0.101 (10.0.0.101)
  Received Label 24010
  Origin incomplete, metric 0, localpref 100, valid, internal, group-best, import-candidate,
imported
  Received Path ID 2, Local Path ID 0, version 0
  Extended community: RT:65000:1
  Source AFI: VPNv4 Unicast, Source VRF: one, Source Route Distinguisher: 1:1
Path #3: Received by speaker 0
Not advertised to any peer
65005
10.5.101.5 (metric 2) from 10.0.0.101 (10.0.0.101)
  Received Label 24010
  Origin incomplete, metric 0, localpref 100, valid, internal, group-best, import-candidate,
imported
  Received Path ID 3, Local Path ID 0, version 0
  Extended community: RT:65000:1
  Source AFI: VPNv4 Unicast, Source VRF: one, Source Route Distinguisher: 1:1

```

AS نم اهل ابلقت سا متي يتلا ةثالثل ا تاراسم الم نم ةعومج ملل راسم ل ضفأ نع RR نلعي
 هلا بقت سا متي ذل ا تاعومج ملل راسم ل ضفأ نع اضيأ RR نلعي، راسم الم اذ ه بناج يلاو 65000.
 راسم و AS 65004 راسم و AS 65005.

نع نالعال متي. ك فلتخم راج اهل ةثالثل ا تاراسم الم نأل ةعومج ل ضفأ تاراسم ةثالثل كانه
 تاراسم الم ةدعت تاراسم الم نع نالعال متي ال. تاراسم الم هذ عي مج.

تاعومج ملل تاراسم ل ضفأ عي مج نع نالعال متي: ةمخالل

10. ددعت نالعال تي بثت 1 راسم الم دي دحتل يطايتحالل خسننل ةي لمع ني عت 10. نالعال-protect-تاراسم الم

Cisco IOS®-XR 7.3.1. نم اءب طقف رايخال اذ رفوتي

Multipath Protect-Advertising ةديج ةي اساساً ةم لك كانه، Cisco IOS®-XR 7.3.1 عم ءدبلل

لبق. يطايتحالل خسننل راسم بناج تاراسم الم ةدعت ةي امجال راسم نع نالعال ابل حمسي اذ هو
 هنع نالعال متي مل نكلو تاراسم الم ةدعت ةي امجال راسم تي بثت مت، Cisco IOS®-XR 7.3.1.
 (8. ةلال رظنا)

```

route-policy BGP-Path-Selection
  set path-selection backup 1 install multipath-protect advertise multipath-protect-advertise
end-policy
!
```

```
RP/0/RP0/CPU0:RR#show bgp vpnv4 unicast rd 1:1 10.1.1.1/32
```

```

BGP routing table entry for 10.1.1.1/32, Route Distinguisher: 1:1
Versions:
  Process          bRIB/RIB   SendTblVer
  Speaker          5          5
Last Modified: Sep 17 16:43:05.907 for 00:01:14
Paths: (5 available, best #1)
  Advertised to update-groups (with more than one peer):
    0.2 0.3
  Path #1: Received by speaker 0
  Advertised to update-groups (with more than one peer):
    0.2 0.3
  Local, (Received from a RR-client)
    10.0.0.1 (metric 2) from 10.0.0.1 (10.0.0.1)

```

```

Received Label 24012
Origin incomplete, metric 0, localpref 100, valid, internal, best, group-best, multipath,
import-candidate, imported
Received Path ID 0, Local Path ID 1, version 5
Extended community: RT:65000:1
Source AFI: VPNv4 Unicast, Source VRF: one, Source Route Distinguisher: 1:1
Path #2: Received by speaker 0
Advertised to update-groups (with more than one peer):
0.3
Local, (Received from a RR-client)
10.0.0.2 (metric 2) from 10.0.0.2 (10.0.0.2)
Received Label 24012
Origin incomplete, metric 0, localpref 100, valid, internal, multipath, backup, add-path,
import-candidate, imported
Received Path ID 0, Local Path ID 2, version 5
Extended community: RT:65000:1
Source AFI: VPNv4 Unicast, Source VRF: one, Source Route Distinguisher: 1:1
Path #3: Received by speaker 0
Not advertised to any peer
Local, (Received from a RR-client)
10.0.0.3 (metric 2) from 10.0.0.3 (10.0.0.3)
Received Label 24012
Origin incomplete, metric 0, localpref 100, valid, internal, multipath, import-candidate,
imported
Received Path ID 0, Local Path ID 0, version 0
Extended community: RT:65000:1
Source AFI: VPNv4 Unicast, Source VRF: one, Source Route Distinguisher: 1:1
Path #4: Received by speaker 0
Advertised to update-groups (with more than one peer):
0.3
Local, (Received from a RR-client)
10.0.0.4 (metric 2) from 10.0.0.4 (10.0.0.4)
Received Label 24013
Origin incomplete, metric 0, localpref 100, valid, internal, backup(protect multipath),
add-path, import-candidate, imported
Received Path ID 0, Local Path ID 3, version 5
Extended community: RT:65000:1
Source AFI: VPNv4 Unicast, Source VRF: one, Source Route Distinguisher: 1:1
Path #5: Received by speaker 0
Not advertised to any peer
Local, (Received from a RR-client)
10.0.0.5 (metric 2) from 10.0.0.5 (10.0.0.5)
Received Label 24014
Origin incomplete, metric 0, localpref 100, valid, internal, import-candidate, imported
Received Path ID 1, Local Path ID 0, version 0
Extended community: RT:65000:1
Source AFI: VPNv4 Unicast, Source VRF: one, Source Route Distinguisher: 1:1

```

RP/0/RP0/CPU0:RR#**show route vrf one 10.1.1.1**

Routing entry for 10.1.1.1/32

Known via "bgp 65000", distance 200, metric 0

Number of pic paths 1 , type internal

Installed Sep 17 16:43:05.562 for 00:01:45

Routing Descriptor Blocks

10.0.0.1, from 10.0.0.1, **BGP multi path**

Nexthop in Vrf: "default", Table: "default", IPv4 Unicast, Table Id: 0xe0000000

Route metric is 0

10.0.0.2, from 10.0.0.2, **BGP multi path**

Nexthop in Vrf: "default", Table: "default", IPv4 Unicast, Table Id: 0xe0000000

Route metric is 0

10.0.0.3, from 10.0.0.3, **BGP multi path**

Nexthop in Vrf: "default", Table: "default", IPv4 Unicast, Table Id: 0xe0000000

Route metric is 0

```
10.0.0.4, from 10.0.0.4, BGP backup path
  Nexthop in Vrf: "default", Table: "default", IPv4 Unicast, Table Id: 0xe0000000
  Route metric is 0
No advertising protos.
```

```
RP/0/RP0/CPU0:RR#show cef vrf one 10.1.1.1
```

```
10.1.1.1/32, version 323, internal 0x5000001 0x30 (ptr 0xd96a770) [1], 0x0 (0xe3662a8), 0xa08 (0xf4e1168)
```

```
Updated Sep 17 16:43:05.567
```

```
Prefix Len 32, traffic index 0, precedence n/a, priority 3
  via 10.0.0.1/32, 3 dependencies, recursive, bgp-multipath [flags 0x6080]
    path-idx 0 NHID 0x0 [0xdab2bc0 0x0], Internal 0xd6a2190
    recursion-via-/32
    next hop VRF - 'default', table - 0xe0000000
    next hop 10.0.0.1/32 via 24003/0/21
      next hop 10.1.101.1/32 Gi0/0/0/0 labels imposed {ImplNull 24012}
  via 10.0.0.2/32, 3 dependencies, recursive, bgp-multipath [flags 0x6080]
    path-idx 1 NHID 0x0 [0xdab2e48 0x0], Internal 0xd6a2730
    recursion-via-/32
    next hop VRF - 'default', table - 0xe0000000
    next hop 10.0.0.2/32 via 24001/0/21
      next hop 10.2.101.2/32 Gi0/0/0/4 labels imposed {ImplNull 24012}
  via 10.0.0.3/32, 3 dependencies, recursive, bgp-multipath [flags 0x6080]
    path-idx 2 NHID 0x0 [0xdab2060 0x0], Internal 0xd6a2910
    recursion-via-/32
    next hop VRF - 'default', table - 0xe0000000
    next hop 10.0.0.3/32 via 24007/0/21
      next hop 10.3.101.3/32 Gi0/0/0/6 labels imposed {ImplNull 24012}
  via 10.0.0.4/32, 2 dependencies, recursive, backup [flags 0x6100]
    path-idx 3 NHID 0x0 [0xdab2c98 0x0]
    recursion-via-/32
    next hop VRF - 'default', table - 0xe0000000
    next hop 10.0.0.4/32 via 24000/0/21
      next hop 10.4.101.4/32 Gi0/0/0/7 labels imposed {ImplNull 24013}
```

اهن نل عمل تاراسملا نم ققحت:

```
RP/0/RP0/CPU0:PE6#show bgp vpnv4 unicast rd 1:1 10.1.1.1/32
```

```
BGP routing table entry for 10.1.1.1/32, Route Distinguisher: 1:1
```

```
Versions:
```

```
Process          bRIB/RIB  SendTblVer
Speaker          207      207
```

```
Last Modified: Sep 17 16:43:06.649 for 00:02:31
```

```
Paths: (3 available, best #1)
```

```
Not advertised to any peer
```

```
Path #1: Received by speaker 0
```

```
Not advertised to any peer
```

```
Local
```

```
10.0.0.1 (metric 3) from 10.0.0.101 (10.0.0.1)
```

```
Received Label 24012
```

```
Origin incomplete, metric 0, localpref 100, valid, internal, best, group-best, import-candidate, imported
```

```
Received Path ID 1, Local Path ID 1, version 207
```

```
Extended community: RT:65000:1
```

```
Originator: 10.0.0.1, Cluster list: 10.0.0.101
```

```
Source AFI: VPNv4 Unicast, Source VRF: one, Source Route Distinguisher: 1:1
```

```
Path #2: Received by speaker 0
```

```
Not advertised to any peer
```

```
Local
```

```
10.0.0.2 (metric 3) from 10.0.0.101 (10.0.0.2)
```

```
Received Label 24012
```

```
Origin incomplete, metric 0, localpref 100, valid, internal, import-candidate, imported
```

```

Received Path ID 2, Local Path ID 0, version 0
Extended community: RT:65000:1
Originator: 10.0.0.2, Cluster list: 10.0.0.101
Source AFI: VPNv4 Unicast, Source VRF: one, Source Route Distinguisher: 1:1
Path #3: Received by speaker 0
Not advertised to any peer
Local
  10.0.0.4 (metric 3) from 10.0.0.101 (10.0.0.4)
    Received Label 24013
    Origin incomplete, metric 0, localpref 100, valid, internal, import-candidate, imported
    Received Path ID 3, Local Path ID 0, version 0
    Extended community: RT:65000:1
    Originator: 10.0.0.4, Cluster list: 10.0.0.101
    Source AFI: VPNv4 Unicast, Source VRF: one, Source Route Distinguisher: 1:1

```

راسم ةيماح (يطايتحال خسننل - رخآ راسم .RIB في ةتبت م ةددعت مل تاراسم لك : ةم تاخا
لضفأا راسم لن نالعال م تي .يطايتحال خسنن راسم ك هتيتبت م ت - (تاراسم لاددعت م
(تاراسم لاددعت م ةيماح)) يطايتحال خسنن راسم و يطايتحال خسنن راسم و

11. تاراسم لاددعت م نالعال راسم لاددعت مل تاراسم لاددعت م ناو نني عت ةيماح

Cisco IOS®-XR 7.3.1. نم اءب طقف رايلال اذه رفوتي

```

route-policy BGP-Path-Selection
  set path-selection multipath advertise multipath-protect
end-policy
!

```

```
RP/0/RP0/CPU0:RR#show bgp vpnv4 unicast rd 1:1 10.1.1.1/32
```

```

BGP routing table entry for 10.1.1.1/32, Route Distinguisher: 1:1
Versions:
  Process          bRIB/RIB  SendTblVer
  Speaker          5         5
Last Modified: Sep 18 06:12:25.907 for 00:00:12
Paths: (5 available, best #1)
  Advertised to update-groups (with more than one peer):
    0.2 0.3
  Path #1: Received by speaker 0
  Advertised to update-groups (with more than one peer):
    0.2 0.3
  Local, (Received from a RR-client)
    10.0.0.1 (metric 2) from 10.0.0.1 (10.0.0.1)
      Received Label 24012
      Origin incomplete, metric 0, localpref 100, valid, internal, best, group-best, multipath,
import-candidate, imported
      Received Path ID 0, Local Path ID 1, version 5
      Extended community: RT:65000:1
      Source AFI: VPNv4 Unicast, Source VRF: one, Source Route Distinguisher: 1:1
  Path #2: Received by speaker 0
  Advertised to update-groups (with more than one peer):
    0.3
  Local, (Received from a RR-client)
    10.0.0.2 (metric 2) from 10.0.0.2 (10.0.0.2)
      Received Label 24012
      Origin incomplete, metric 0, localpref 100, valid, internal, multipath, add-path, import-
candidate, imported
      Received Path ID 0, Local Path ID 3, version 5
      Extended community: RT:65000:1
      Source AFI: VPNv4 Unicast, Source VRF: one, Source Route Distinguisher: 1:1

```

Path #3: Received by speaker 0
Not advertised to any peer
Local, (Received from a RR-client)
10.0.0.3 (metric 2) from 10.0.0.3 (10.0.0.3)
Received Label 24012
Origin incomplete, metric 0, localpref 100, valid, internal, **backup(protect multipath)**,
add-path, import-candidate, imported
Received Path ID 0, Local Path ID 4, version 5
Extended community: RT:65000:1
Source AFI: VPNv4 Unicast, Source VRF: one, Source Route Distinguisher: 1:1

Path #4: Received by speaker 0
Advertised to update-groups (with more than one peer):
0.3
Local, (Received from a RR-client)
10.0.0.4 (metric 2) from 10.0.0.4 (10.0.0.4)
Received Label 24013
Origin incomplete, metric 0, localpref 100, valid, internal, **multipath**, add-path, import-
candidate, imported
Received Path ID 0, Local Path ID 2, version 5
Extended community: RT:65000:1
Source AFI: VPNv4 Unicast, Source VRF: one, Source Route Distinguisher: 1:1

Path #5: Received by speaker 0
Not advertised to any peer
Local, (Received from a RR-client)
10.0.0.5 (metric 2) from 10.0.0.5 (10.0.0.5)
Received Label 24014
Origin incomplete, metric 0, localpref 100, valid, internal, import-candidate, imported
Received Path ID 1, Local Path ID 0, version 0
Extended community: RT:65000:1
Source AFI: VPNv4 Unicast, Source VRF: one, Source Route Distinguisher: 1:1

RP/0/RP0/CPU0:RR#**show route vrf one 10.1.1.1/32**

Routing entry for 10.1.1.1/32
Known via "bgp 65000", distance 200, metric 0
Number of pic paths 1 , type internal
Installed Sep 18 06:12:26.137 for 00:05:23
Routing Descriptor Blocks
10.0.0.1, from 10.0.0.1, **BGP multi path**
Nexthop in Vrf: "default", Table: "default", IPv4 Unicast, Table Id: 0xe0000000
Route metric is 0
10.0.0.2, from 10.0.0.2, **BGP multi path**
Nexthop in Vrf: "default", Table: "default", IPv4 Unicast, Table Id: 0xe0000000
Route metric is 0
10.0.0.3, from 10.0.0.3, **BGP backup path**
Nexthop in Vrf: "default", Table: "default", IPv4 Unicast, Table Id: 0xe0000000
Route metric is 0
10.0.0.4, from 10.0.0.4, **BGP multi path**
Nexthop in Vrf: "default", Table: "default", IPv4 Unicast, Table Id: 0xe0000000
Route metric is 0
No advertising protos.

RP/0/RP0/CPU0:RR#**show cef vrf one 10.1.1.1/32**

10.1.1.1/32, version 345, internal 0x5000001 0x30 (ptr 0xd96a770) [1], 0x0 (0xe3662a8), 0xa08
(0xf4e1108)
Updated Sep 18 06:12:26.140
Prefix Len 32, traffic index 0, precedence n/a, priority 3
via 10.0.0.1/32, 3 dependencies, recursive, **bgp-multipath** [flags 0x6080]
path-idx 0 NHID 0x0 [0xdab2bc0 0x0], Internal 0xd6a2190
recursion-via-/32
next hop VRF - 'default', table - 0xe0000000
next hop 10.0.0.1/32 via 24003/0/21
next hop 10.1.101.1/32 Gi0/0/0/0 labels imposed {ImplNull 24012}
via 10.0.0.2/32, 3 dependencies, recursive, **bgp-multipath** [flags 0x6080]

```

path-idx 1 NHID 0x0 [0xdab2e48 0x0], Internal 0xd6a2730
recursion-via-/32
next hop VRF - 'default', table - 0xe0000000
next hop 10.0.0.2/32 via 24001/0/21
  next hop 10.2.101.2/32 Gi0/0/0/4    labels imposed {ImplNull 24012}
via 10.0.0.3/32, 2 dependencies, recursive, backup [flags 0x6100]
path-idx 2 NHID 0x0 [0xdab2060 0x0]
recursion-via-/32
next hop VRF - 'default', table - 0xe0000000
next hop 10.0.0.3/32 via 24007/0/21
  next hop 10.3.101.3/32 Gi0/0/0/6    labels imposed {ImplNull 24012}
via 10.0.0.4/32, 3 dependencies, recursive, bgp-multipath [flags 0x6080]
path-idx 3 NHID 0x0 [0xdab2c98 0x0], Internal 0xd6a2550
recursion-via-/32
next hop VRF - 'default', table - 0xe0000000
next hop 10.0.0.4/32 via 24000/0/21
  next hop 10.4.101.4/32 Gi0/0/0/7    labels imposed {ImplNull 24013}

```

اهن ع نل عمل ا تاراسم ل ن م ق قحت

```
RP/0/RP0/CPU0:PE6#show bgp vpnv4 unicast rd 1:1 10.1.1.1/32
```

BGP routing table entry for 10.1.1.1/32, Route Distinguisher: 1:1

Versions:

Process	BRIB/RIB	SendTblVer
Speaker	221	221

Last Modified: Sep 18 06:12:27.649 for 00:01:38

Paths: (3 available, best #1)

Not advertised to any peer

Path #1: Received by speaker 0

Not advertised to any peer

Local

10.0.0.1 (metric 3) from 10.0.0.101 (10.0.0.1)

Received Label 24012

Origin incomplete, metric 0, localpref 100, valid, internal, best, group-best, import-candidate, imported

Received Path ID 1, Local Path ID 1, version 221

Extended community: RT:65000:1

Originator: 10.0.0.1, Cluster list: 10.0.0.101

Source AFI: VPNv4 Unicast, Source VRF: one, Source Route Distinguisher: 1:1

Path #2: Received by speaker 0

Not advertised to any peer

Local

10.0.0.4 (metric 3) from 10.0.0.101 (10.0.0.4)

Received Label 24013

Origin incomplete, metric 0, localpref 100, valid, internal, import-candidate, imported

Received Path ID 2, Local Path ID 0, version 0

Extended community: RT:65000:1

Originator: 10.0.0.4, Cluster list: 10.0.0.101

Source AFI: VPNv4 Unicast, Source VRF: one, Source Route Distinguisher: 1:1

Path #3: Received by speaker 0

Not advertised to any peer

Local

10.0.0.2 (metric 3) from 10.0.0.101 (10.0.0.2)

Received Label 24012

Origin incomplete, metric 0, localpref 100, valid, internal, import-candidate, imported

Received Path ID 3, Local Path ID 0, version 0

Extended community: RT:65000:1

Originator: 10.0.0.2, Cluster list: 10.0.0.101

Source AFI: VPNv4 Unicast, Source VRF: one, Source Route Distinguisher: 1:1

- ةيامح) يطايتح |خسنك هميلعت متي. يطايتحال |خسنل راسم وه ثلثال راسم ل
RIB. ي يطايتح |خسن راسمك هتبتتو BGP ي (ةدعتم ل تاراسم ل

- تاراسم لة ددعت م تاراسم ل او راسم ل ض ف ا ن ع ن ال ع ل ا م ت ي .
- (ة ددعت م ل تاراسم ل ا ة ي ام ح) ي ط ا ي ت ح ال ا خ س ن ل ا " راسم ل ن ع ن ال ع ل ا م ت ي م ل ."

12. ة ي ام ح ل تاراسم ل ا ددعت م راسم ل ا د ي ح ت ل تاراسم ل ا ددعت م ن ال ع | ن ي ي ع ت . ن ال ع | - تاراسم ل ا ددعت م

تاراسم ل ا ب ن ا ج ب ن ع ن ال ع ل ا و تاراسم ل ا ددعت م ي م ح م ل ا راسم ل ا ت ي ب ت ب ح م س ي ا ذ و ة ددعت م ل ا .

```
route-policy BGP-Path-Selection
```

```
  set path-selection multipath advertise multipath-protect multipath-protect-advertise
end-policy
```

```
RP/0/RP0/CPU0:RR#show bgp vpnv4 unicast rd 1:1 10.1.1.1/32
```

```
BGP routing table entry for 10.1.1.1/32, Route Distinguisher: 1:1
```

```
Versions:
```

```
  Process          bRIB/RIB  SendTblVer
  Speaker          5         5
```

```
Last Modified: Sep 18 06:22:22.907 for 00:03:12
```

```
Paths: (5 available, best #1)
```

```
  Advertised to update-groups (with more than one peer):
    0.2 0.3
```

```
  Path #1: Received by speaker 0
```

```
  Advertised to update-groups (with more than one peer):
    0.2 0.3
```

```
  Local, (Received from a RR-client)
```

```
    10.0.0.1 (metric 2) from 10.0.0.1 (10.0.0.1)
```

```
      Received Label 24012
```

```
      Origin incomplete, metric 0, localpref 100, valid, internal, best, group-best, multipath,
import-candidate, imported
```

```
      Received Path ID 0, Local Path ID 1, version 5
```

```
      Extended community: RT:65000:1
```

```
      Source AFI: VPNv4 Unicast, Source VRF: one, Source Route Distinguisher: 1:1
```

```
  Path #2: Received by speaker 0
```

```
  Advertised to update-groups (with more than one peer):
    0.2
```

```
  Local, (Received from a RR-client)
```

```
    10.0.0.2 (metric 2) from 10.0.0.2 (10.0.0.2)
```

```
      Received Label 24012
```

```
      Origin incomplete, metric 0, localpref 100, valid, internal, backup(protect multipath),
add-path, import-candidate, imported
```

```
      Received Path ID 0, Local Path ID 4, version 5
```

```
      Extended community: RT:65000:1
```

```
      Source AFI: VPNv4 Unicast, Source VRF: one, Source Route Distinguisher: 1:1
```

```
  Path #3: Received by speaker 0
```

```
  Not advertised to any peer
```

```
  Local, (Received from a RR-client)
```

```
    10.0.0.3 (metric 2) from 10.0.0.3 (10.0.0.3)
```

```
      Received Label 24012
```

```
      Origin incomplete, metric 0, localpref 100, valid, internal, import-candidate, imported
```

```
      Received Path ID 0, Local Path ID 0, version 0
```

```
      Extended community: RT:65000:1
```

```
      Source AFI: VPNv4 Unicast, Source VRF: one, Source Route Distinguisher: 1:1
```

```
  Path #4: Received by speaker 0
```

```
  Advertised to update-groups (with more than one peer):
    0.2
```

```
  Local, (Received from a RR-client)
```

```
    10.0.0.4 (metric 2) from 10.0.0.4 (10.0.0.4)
```

```
Received Label 24013
Origin incomplete, metric 0, localpref 100, valid, internal, multipath, add-path, import-
candidate, imported
Received Path ID 0, Local Path ID 2, version 5
Extended community: RT:65000:1
Source AFI: VPNv4 Unicast, Source VRF: one, Source Route Distinguisher: 1:1
Path #5: Received by speaker 0
Advertised to update-groups (with more than one peer):
0.2
Local, (Received from a RR-client)
10.0.0.5 (metric 2) from 10.0.0.5 (10.0.0.5)
Received Label 24014
Origin incomplete, metric 0, localpref 100, valid, internal, multipath, add-path, import-
candidate, imported
Received Path ID 1, Local Path ID 3, version 5
Extended community: RT:65000:1
Source AFI: VPNv4 Unicast, Source VRF: one, Source Route Distinguisher: 1:1
```

RP/0/RP0/CPU0:RR#**show route vrf one 10.1.1.1/32**

```
Routing entry for 10.1.1.1/32
Known via "bgp 65000", distance 200, metric 0
Number of pic paths 1 , type internal
Installed Sep 18 06:22:23.059 for 00:03:34
Routing Descriptor Blocks
10.0.0.1, from 10.0.0.1, BGP multi path
  Nexthop in Vrf: "default", Table: "default", IPv4 Unicast, Table Id: 0xe0000000
  Route metric is 0
10.0.0.2, from 10.0.0.2, BGP backup path
  Nexthop in Vrf: "default", Table: "default", IPv4 Unicast, Table Id: 0xe0000000
  Route metric is 0
10.0.0.4, from 10.0.0.4, BGP multi path
  Nexthop in Vrf: "default", Table: "default", IPv4 Unicast, Table Id: 0xe0000000
  Route metric is 0
10.0.0.5, from 10.0.0.5, BGP multi path
  Nexthop in Vrf: "default", Table: "default", IPv4 Unicast, Table Id: 0xe0000000
  Route metric is 0
No advertising protos.
```

RP/0/RP0/CPU0:RR#**show cef vrf one 10.1.1.1/32**

```
10.1.1.1/32, version 367, internal 0x5000001 0x30 (ptr 0xd96a770) [1], 0x0 (0xe3662a8), 0xa08
(0xf4e11c8)
Updated Sep 18 06:22:23.062
Prefix Len 32, traffic index 0, precedence n/a, priority 3
via 10.0.0.1/32, 3 dependencies, recursive, bgp-multipath [flags 0x6080]
  path-idx 0 NHID 0x0 [0xdab2bc0 0x0], Internal 0xd6a2190
  recursion-via-/32
  next hop VRF - 'default', table - 0xe0000000
  next hop 10.0.0.1/32 via 24003/0/21
    next hop 10.1.101.1/32 Gi0/0/0/0 labels imposed {ImplNull 24012}
via 10.0.0.2/32, 2 dependencies, recursive, backup [flags 0x6100]
  path-idx 1 NHID 0x0 [0xdab2e48 0x0]
  recursion-via-/32
  next hop VRF - 'default', table - 0xe0000000
  next hop 10.0.0.2/32 via 24001/0/21
    next hop 10.2.101.2/32 Gi0/0/0/4 labels imposed {ImplNull 24012}
via 10.0.0.4/32, 3 dependencies, recursive, bgp-multipath [flags 0x6080]
  path-idx 2 NHID 0x0 [0xdab2c98 0x0], Internal 0xd6a2550
  recursion-via-/32
  next hop VRF - 'default', table - 0xe0000000
  next hop 10.0.0.4/32 via 24000/0/21
    next hop 10.4.101.4/32 Gi0/0/0/7 labels imposed {ImplNull 24013}
via 10.0.0.5/32, 3 dependencies, recursive, bgp-multipath [flags 0x6080]
  path-idx 3 NHID 0x0 [0xdab2368 0x0], Internal 0xd6a2910
```

```
recursion-via-/32
next hop VRF - 'default', table - 0xe0000000
next hop 10.0.0.5/32 via 24005/0/21
  next hop 10.5.101.5/32 Gi0/0/0/1 labels imposed {ImplNull 24014}
```

اهن نل عمل تاراسم ل ن م ق قحت:

```
RP/0/RP0/CPU0:PE6#show bgp vpnv4 unicast rd 1:1 10.1.1.1/32
```

BGP routing table entry for 10.1.1.1/32, Route Distinguisher: 1:1

```
Process          bRIB/RIB  SendTblVer
Speaker          235      235
Last Modified: Sep 18 06:22:24.649 for 00:03:59
Paths: (4 available, best #1)
Not advertised to any peer
Path #1: Received by speaker 0
Not advertised to any peer
Local
  10.0.0.1 (metric 3) from 10.0.0.101 (10.0.0.1)
    Received Label 24012
    Origin incomplete, metric 0, localpref 100, valid, internal, best, group-best, import-
candidate, imported
    Received Path ID 1, Local Path ID 1, version 235
    Extended community: RT:65000:1
    Originator: 10.0.0.1, Cluster list: 10.0.0.101
    Source AFI: VPNv4 Unicast, Source VRF: one, Source Route Distinguisher: 1:1
Path #2: Received by speaker 0
Not advertised to any peer
Local
  10.0.0.4 (metric 3) from 10.0.0.101 (10.0.0.4)
    Received Label 24013
    Origin incomplete, metric 0, localpref 100, valid, internal, import-candidate, imported
    Received Path ID 2, Local Path ID 0, version 0
    Extended community: RT:65000:1
    Originator: 10.0.0.4, Cluster list: 10.0.0.101
    Source AFI: VPNv4 Unicast, Source VRF: one, Source Route Distinguisher: 1:1
Path #3: Received by speaker 0
Not advertised to any peer
Local
  10.0.0.5 (metric 3) from 10.0.0.101 (10.0.0.5)
    Received Label 24014
    Origin incomplete, metric 0, localpref 100, valid, internal, import-candidate, imported
    Received Path ID 3, Local Path ID 0, version 0
    Extended community: RT:65000:1
    Originator: 10.0.0.5, Cluster list: 10.0.0.101
    Source AFI: VPNv4 Unicast, Source VRF: one, Source Route Distinguisher: 1:1
Path #4: Received by speaker 0
Not advertised to any peer
Local
  10.0.0.2 (metric 3) from 10.0.0.101 (10.0.0.2)
    Received Label 24012
    Origin incomplete, metric 0, localpref 100, valid, internal, import-candidate, imported
    Received Path ID 4, Local Path ID 0, version 0
    Extended community: RT:65000:1
    Originator: 10.0.0.2, Cluster list: 10.0.0.101
    Source AFI: VPNv4 Unicast, Source VRF: one, Source Route Distinguisher: 1:1
```

زارق ل:

- BGP لوك وورب يف ةثالث ل تاراسم ل ةفاك ل ل ع تاراسم ل ددعت م ةم ال ع عضو م تي .
- RIB/CEF لودج يف ECMP تاراسم م 3 تي بثت م ت .
- ةي طايحت ل ةخسن " ةم ال ع عضو م تي طايحت ل خسن ل راسم وه ين ل ل راسم ل .

يُطابق حاليًا خسن راسمك اهتبيثتو (BGP) دودجالا ةباوب لوكوتورب ي (ةددعتملا تاراسملا ريب/CEF لودج ي

- يطابق حاليًا خسنل "تاراسمو تاراسملا ةددعتم تاراسملاو راسم لصفأ نع نالعال متي (ةددعتملا تاراسملا ةيامح)".

Cisco IOS®-XR 7.3.1 عم لجالا وه امك ديديج راسم ديديجت كولس

اذه ريغمت مت، Cisco IOS®-XR 7.3.1 نم ارباعتا

- طقف نيوانع ةومجم لكل اذه ناك، Cisco IOS®-XR 7.3.1 لبق. نكمم راج لك راسم ديديجت
- دحاو راسم جهن يفة ةومجملا ةددعتم راسم ديديجت لمجج حامسلا متي
- هب اهلابقتسا متي يذلا بيترتلاب BGP تاراسم ضرع نكمي

نكمم راج لك راسم ديديجت

راسملا جهن يفاتملا راسملا ديديجت وه اذه

```
RP/0/RP0/CPU0:RR(config-rpl)#set path-selection ?
all          BGP all paths
backup       BGP backup path
best-path    BGP best path
group-best   BGP group best path
multipath    BGP multipath
```

يضا رتفالالا وه راسم لصفأ

نيوانعال ةلئاع يوتسم يلع موعدم اذهو

نيوكتلالاتم:

```
router bgp 65000
address-family ipv4 unicast
!
address-family vpnv4 unicast
additional-paths receive
additional-paths send
  additional-paths selection route-policy BGP-Path-Selection
!
neighbor 10.0.0.1
remote-as 65000
update-source Loopback0
address-family ipv4 unicast
  route-reflector-client
!
address-family vpnv4 unicast
  route-reflector-client
!
!
vrf one
rd 1:1
address-family ipv4 unicast
  maximum-paths ibgp 2
  additional-paths selection route-policy BGP-Path-Selection
  redistribute connected
!
```

!
!

راسملا ةسايس يف راسملا ديدحت تاراخي ضعب معد متي، Cisco IOS®-XR 7.3.1 عم ادبلل يتلا تاراسملا بقلعتي اميف ةقد رثكأ مكحت ىلإ يدؤي اذهو. رواجملا ىوتسملا ىلع اضيأ لصفأ نع BGP توص ربكم نلعي دق، لاثملا لىبس ىلع. BGP ناريجل اهنع نالعالا متي يمحيو ةددعتملا تاراسملا نع نلعي هنكلو، دحاو BGP راج ىلإ دحاو يطايتحإ خسن راسم وراسم رخأ راج ىلإ تاراسملا ددعتملا راسملا

ك:انه، رواجلا ىوتسم ىلعو

```
RP/0/RP0/CPU0:RR(config-rpl)#if destination ?
in                               Member of a set
  is-all                          Check for additional paths selected by all path-selection
  is-backup-path                  Checks for backup path
is-best-external                 Checks for best external route
  is-best-path                    Checks for best path
  is-multi-path                   Checks for multiple paths
  is-multipath-protect            Checks for multipath-protect path
longer-than                      Prefix-length greater than the route's prefix length
or-longer                        Prefix-length equal to or greater than the route's prefix length
```

ك، لذل عمو. BGP maximum-path رمأ نيوكت مت اذا تاراسملا ددعتم وه راسم لصفأ: ريذحت، متي يف، تاراسملا ددعتم وه راسملا جهن يف هنيوكت مت يذلا ديجولا طرشل ناك اذا ىلع دمتعي! لصفأ راسملا دعت ال يتلا طقف تاراسملا ةددعتم تاراسملا نع نالعالا، ةددعتملا تاراسملا نع نالعالا يغبني ناك اذا ه نالعالا نم نكلو، BGP ميمصت اضيأ لصفأ راسملا نع نالعالا بجيف

Cisco IOS®-XR 7.3.1 عم اثيديح is-all و is-multipath-protect ل اخدا متي

دحاو راسم جهن يف ةعومجملا ةددعتم راسم ديدحت تارابعب حامسلا متي

يف ددعتملا راسملا ديدحت تارابع ىلع لوصحلا كنكمي، Cisco IOS®-XR 7.3.1 نم ارابتعا هب احومسم اذه نكي مل، Cisco IOS®-XR 7.3.1 لبق. ةدحاو ةئدابب ةقلعتم ةدحاو راسم ةسايس عقتوم ريغ BGP راسم كولس ىلإ يدؤي نا ه نأش نمو.

ةئداب ل ك يف ال وأ دحاو راسم نم رثكأ ديدحت ىلإ رظنلا متي

ي:لي ام معد متي ال، Cisco IOS®-XR 7.3.1 لبق، لاثملا لىبس ىلع

```
route-policy add-path-to-ibgp
set weight 65000
  set path-selection backup 1 install
set metric-type type-1
set extcommunity rt RT BUSINESS additive
  set path-selection all advertise
set rib-metric 100
end-policy
```

ت.ئدابلا سفن ىلع اهقيبطت متي ةدحاو راسم ةسايس يف راسم ديدحت ناتلمج كيدل

راسملا ديدحت تارابع نا وه بلسلا. Cisco IOS®-XR 7.3.1 لبق يلي ام معد متي، كذل عمو (...، عمم، ةهجو) ديدحت تاذا تارابع مادختسا مت اذا هنأل، ةفلتخملا تئدابلل يه ةفلتخملا

1: لاثم

```

route-policy ADDPATH
  if destination in TRAFFIC_1 then
    set path-selection backup 1 install
  endif
  if destination in TRAFFIC_2 then
    set path-selection multipath advertise
  endif
end-policy

```

نيت لمج في نوكت) ة فل تخم ل ائ د اب ل اب قل ع ت ت ة و مج م ل ا س م دي د ح ت ا ر ا ب ع ن ا ل دي ج ا ذ ه و (ل م ج ت ن ا ك ا ذ ا ن ي ت ف ل ت خ م

2: ل ا ث م

```

route-policy ADDPATH-2
  if community matches-any COMM_ADD-PATH then
    set path-selection backup 1 install multipath-protect advertise
  else
    set path-selection best-path
  endif
end-policy

```

ي في ه و) ة فل تخم ل ا ئ د اب ل اب قل ع ت ت ة و مج م ل ا س م ل ا دي د ح ت ا ر ا ب ع ن ا ل ا ر ط ن دي ج ا ذ ه و (if ة ر ا ب ع ن م ن ي ف ل ت خ م ن ي ا ن ج

ا ذ ه م ع د م ت ي ، Cisco IOS®-XR 7.3.1 ن م ا د ب

ة د ح ا و ر ا س م دي د ح ت ة ر ا ب ع ن م ر ث ك ا ي ل ع ي و ت ح ي ر a س م ل ا ج ه ن ي ل ع ل ا ث م ا ذ ه

```

route-policy BGP-Path-Selection
  set path-selection multipath advertise
  set path-selection backup 1 install multipath-protect advertise multipath-protect-advertise
end-policy
!

```

ر a س م ي ا ر ا ي ت خ ا ن ك م ي . ر و ا ج م ل ا ا ذ ه ل ا ه ن ع ن ا ل ع ا ل ا م ت ي ي ت ل ا ت a ر a س م ل a ر a ج ل ل ك ل ر a س م ل a ج ه ن د د ح ي ن . ن ي و a ن ع ل a ة ل ا ئ ا ع ي و ت س م ي ل ع ل ع ف ل a ب ا ه ي ل ع ة م a ل ع ع و م ت ي ت l a T a R a S M l a ن م ط ق ف

ر a س م ل a دي د ح ت ك ي د ل ، ن ي و a ن ع ل a ة ل a ئ a ع ي و ت س م ي ل ع

```

RP/0/RP0/CPU0:RR(config-rpl)#set path-selection ?
all          BGP all paths
backup       BGP backup path
best-path    BGP best path
group-best   BGP group best path
multipath    BGP multipath

```

ك ا ن ه ، ر a و a ج l a ي و ت س م ي ل ع و

```

RP/0/RP0/CPU0:RR(config-rpl)#if destination ?
in           Member of a set
is-all       Check for additional paths selected by all path-selection
is-backup-path Checks for backup path
is-best-external Checks for best external route
is-best-path Checks for best path
is-multi-path Checks for multiple paths
is-multipath-protect Checks for multipath-protect path

```

longer-than
or-longer

Prefix-length greater than the route's prefix length
Prefix-length equal to or greater than the route's prefix length

كذلك، **BGP maximum-path** رقمًا نيوكوت مت إذا تاراسملا ددعتم وه راسم لضفأ: ريذحت،
م تي ف، تاراسملا ددعتم وه راسملا جهن يف هنيوكوت مت يذلا ديحول طرشل ناك إذا
يلع دمتعي! لضفأ راسملا دعت ال يتل طقف تاراسملا ددعتم تاراسملا نع نالعال
، ددعتم تاراسملا نع نالعال يغبني ناك إذا هنا لم تجملا نم نكلو، BGP مي م صت
اضيا لضفأ راسملا نع نالعال بجي ف.

Cisco IOS®-XR 7.3.1 عم اتي دح **is-all** و **is-multipath-protect** ل اخدا متي

راسملا دي دحت عاضوا نم اچي زم راسملا دي دحت **ةمالع** نوكت نأ نكمي، ةقيرطال هذه مادختساب
ةددعتم ةي امحلا، تاراسملا ددعتم، يطايت حال خسنلا، لك، لاثملا ل بس يلع) كي يدل يتل
ال (اذك هو، تاراسملا).

راسملا دي دحت ةمالع ل ا ادانتسا **نالعال** يف رواجملا جهنلا مكحتي

اعم ددعتم راسملا او يطايت حال خسنلا نيوكوت نكمي، لاثملا ل بس يلع: تامالعال عزج
فني وانعال ةلئاع يوتسم يلع راسملا جهن يف

```
route-policy BGP-Path-Selection
  set path-selection multipath advertise (1)
  set path-selection backup 1 install multipath-protect advertise multipath-protect-advertise
(2)
end-policy
!
```

Cisco IOS®-XR 7.3.1 نم اءب اتي دح همعد متي ام امه هالعال ني ت دراوال راسملا دي دحت اتعومجم
م يل لي ام كي يدل، لاثملا ل يف انوكم لازي ام **Maximum-Path IBGP 3** دوجو عم

- ةددعتم تاراسملا عي مچو راسم لضفأ نع نالعال حيتي
 - (ةددعتم تاراسملا ةي امح) يطايت حال خسنلا راسم و راسم لضفأ نع نالعال اب حامسلا
- اونوكي نأ ام (2) وأ (1) نأ ينعني اذهو. Cisco IOS®-XR 7.3.1 ل بق ةنكمم ةعومجملا هذه نكت مل
ذي فننتل زيح يف

ةجيتنلاليه هذهو:

```
RP/0/RP0/CPU0:RR#show bgp vpnv4 unicast rd 1:1 10.1.1.1/32
```

```
BGP routing table entry for 10.1.1.1/32, Route Distinguisher: 1:1
```

```
Versions:
```

```
Process          bRIB/RIB  SendTblVer
Speaker          5         5
```

```
Last Modified: Sep 18 06:59:27.907 for 00:00:28
```

```
Paths: (5 available, best #1)
```

```
Advertised to update-groups (with more than one peer):
```

```
0.2 0.3
```

```
Path #1: Received by speaker 0
```

```
Advertised to update-groups (with more than one peer):
```

```
0.2 0.3
```

```
Local, (Received from a RR-client)
```

```
10.0.0.1 (metric 2) from 10.0.0.1 (10.0.0.1)
```

```
Received Label 24012
```

```
Origin incomplete, metric 0, localpref 100, valid, internal, best, group-best, multipath,
```

```
import-candidate, imported
```

```
Received Path ID 0, Local Path ID 1, version 5
```

```

Extended community: RT:65000:1
Source AFI: VPNv4 Unicast, Source VRF: one, Source Route Distinguisher: 1:1
Path #2: Received by speaker 0
Advertised to update-groups (with more than one peer):
0.2
Local, (Received from a RR-client)
10.0.0.2 (metric 2) from 10.0.0.2 (10.0.0.2)
Received Label 24012
Origin incomplete, metric 0, localpref 100, valid, internal, multipath, backup, add-path,
import-candidate, imported
Received Path ID 0, Local Path ID 2, version 5
Extended community: RT:65000:1
Source AFI: VPNv4 Unicast, Source VRF: one, Source Route Distinguisher: 1:1
Path #3: Received by speaker 0
Advertised to update-groups (with more than one peer):
0.2
Local, (Received from a RR-client)
10.0.0.3 (metric 2) from 10.0.0.3 (10.0.0.3)
Received Label 24012
Origin incomplete, metric 0, localpref 100, valid, internal, backup(protect multipath),
add-path, import-candidate, imported
Received Path ID 0, Local Path ID 3, version 5
Extended community: RT:65000:1
Source AFI: VPNv4 Unicast, Source VRF: one, Source Route Distinguisher: 1:1
Path #4: Received by speaker 0
Advertised to update-groups (with more than one peer):
0.2
Local, (Received from a RR-client)
10.0.0.4 (metric 2) from 10.0.0.4 (10.0.0.4)
Received Label 24013
Origin incomplete, metric 0, localpref 100, valid, internal, multipath, add-path, import-
candidate, imported
Received Path ID 0, Local Path ID 4, version 5
Extended community: RT:65000:1
Source AFI: VPNv4 Unicast, Source VRF: one, Source Route Distinguisher: 1:1
Path #5: Received by speaker 0
Not advertised to any peer
Local, (Received from a RR-client)
10.0.0.5 (metric 2) from 10.0.0.5 (10.0.0.5)
Received Label 24014
Origin incomplete, metric 0, localpref 100, valid, internal, import-candidate, imported
Received Path ID 1, Local Path ID 0, version 0
Extended community: RT:65000:1
Source AFI: VPNv4 Unicast, Source VRF: one, Source Route Distinguisher: 1:1

```

RP/0/RP0/CPU0:RR#**show route vrf one 10.1.1.1/32**

Routing entry for 10.1.1.1/32

Known via "bgp 65000", distance 200, metric 0

Number of pic paths 1 , type internal

Installed Sep 18 06:59:27.833 for 00:01:59

Routing Descriptor Blocks

10.0.0.1, from 10.0.0.1, **BGP multi path**

Nexthop in Vrf: "default", Table: "default", IPv4 Unicast, Table Id: 0xe0000000

Route metric is 0

10.0.0.2, from 10.0.0.2, **BGP multi path**

Nexthop in Vrf: "default", Table: "default", IPv4 Unicast, Table Id: 0xe0000000

Route metric is 0

10.0.0.3, from 10.0.0.3, **BGP backup path**

Nexthop in Vrf: "default", Table: "default", IPv4 Unicast, Table Id: 0xe0000000

Route metric is 0

10.0.0.4, from 10.0.0.4, **BGP multi path**

Nexthop in Vrf: "default", Table: "default", IPv4 Unicast, Table Id: 0xe0000000

Route metric is 0

No advertising protos.

RP/0/RP0/CPU0:RR#show cef vrf one 10.1.1.1/32

10.1.1.1/32, version 409, internal 0x5000001 0x30 (ptr 0xd96a770) [1], 0x0 (0xe3662a8), 0xa08 (0xf4e1168)

Updated Sep 18 06:59:27.836

Prefix Len 32, traffic index 0, precedence n/a, priority 3

via 10.0.0.1/32, 3 dependencies, recursive, **bgp-multipath** [flags 0x6080]

path-idx 0 NHID 0x0 [0xdab2bc0 0x0], Internal 0xd6a2190

recursion-via-/32

next hop VRF - 'default', table - 0xe0000000

next hop 10.0.0.1/32 via 24003/0/21

next hop 10.1.101.1/32 Gi0/0/0/0 labels imposed {ImplNull 24012}

via 10.0.0.2/32, 3 dependencies, recursive, **bgp-multipath** [flags 0x6080]

path-idx 1 NHID 0x0 [0xdab2e48 0x0], Internal 0xd6a2550

recursion-via-/32

next hop VRF - 'default', table - 0xe0000000

next hop 10.0.0.2/32 via 24001/0/21

next hop 10.2.101.2/32 Gi0/0/0/4 labels imposed {ImplNull 24012}

via 10.0.0.3/32, 2 dependencies, recursive, **backup** [flags 0x6100]

path-idx 2 NHID 0x0 [0xdab2060 0x0]

recursion-via-/32

next hop VRF - 'default', table - 0xe0000000

next hop 10.0.0.3/32 via 24007/0/21

next hop 10.3.101.3/32 Gi0/0/0/6 labels imposed {ImplNull 24012}

via 10.0.0.4/32, 3 dependencies, recursive, **bgp-multipath** [flags 0x6080]

path-idx 3 NHID 0x0 [0xdab2c98 0x0], Internal 0xd6a2370

recursion-via-/32

next hop VRF - 'default', table - 0xe0000000

next hop 10.0.0.4/32 via 24000/0/21

next hop 10.4.101.4/32 Gi0/0/0/7 labels imposed {ImplNull 24013}

اهن نل عمل تاراسم نم ققحت:

RP/0/RP0/CPU0:PE6#show bgp vpnv4 unicast rd 1:1 10.1.1.1/32

BGP routing table entry for 10.1.1.1/32, Route Distinguisher: 1:1

Versions:

Process bRIB/RIB SendTblVer

Speaker 271 271

Last Modified: Sep 18 06:59:28.649 for 00:01:53

Paths: (4 available, best #1)

Not advertised to any peer

Path #1: Received by speaker 0

Not advertised to any peer

Local

10.0.0.1 (metric 3) from 10.0.0.101 (10.0.0.1)

Received Label 24012

Origin incomplete, metric 0, localpref 100, valid, internal, best, group-best, import-candidate, imported

Received Path ID 1, Local Path ID 1, version 271

Extended community: RT:65000:1

Originator: 10.0.0.1, Cluster list: 10.0.0.101

Source AFI: VPNv4 Unicast, Source VRF: one, Source Route Distinguisher: 1:1

Path #2: Received by speaker 0

Not advertised to any peer

Local

10.0.0.2 (metric 3) from 10.0.0.101 (10.0.0.2)

Received Label 24012

Origin incomplete, metric 0, localpref 100, valid, internal, import-candidate, imported

Received Path ID 2, Local Path ID 0, version 0

Extended community: RT:65000:1

Originator: 10.0.0.2, Cluster list: 10.0.0.101

```

Source AFI: VPNv4 Unicast, Source VRF: one, Source Route Distinguisher: 1:1
Path #3: Received by speaker 0
Not advertised to any peer
Local
  10.0.0.3 (metric 3) from 10.0.0.101 (10.0.0.3)
    Received Label 24012
    Origin incomplete, metric 0, localpref 100, valid, internal, import-candidate, imported
    Received Path ID 3, Local Path ID 0, version 0
    Extended community: RT:65000:1
    Originator: 10.0.0.3, Cluster list: 10.0.0.101
    Source AFI: VPNv4 Unicast, Source VRF: one, Source Route Distinguisher: 1:1
Path #4: Received by speaker 0
Not advertised to any peer
Local
  10.0.0.4 (metric 3) from 10.0.0.101 (10.0.0.4)
    Received Label 24013
    Origin incomplete, metric 0, localpref 100, valid, internal, import-candidate, imported
    Received Path ID 4, Local Path ID 0, version 0
    Extended community: RT:65000:1
    Originator: 10.0.0.4, Cluster list: 10.0.0.101
    Source AFI: VPNv4 Unicast, Source VRF: one, Source Route Distinguisher: 1:1

```

(راسم لصفأ) ةيساسأل اي طاي تحال خسنل تاراسم نع ناريجل دأل نالعال نأل نكم يو
 .ي طاي تحال خسنل تاراسم وأ راسم لصفأ ل اذانتسا

IS-Multi-path. مادختساب يرأل ةرواجم ل ةزهأل دأل ةددعتم تاراسم ل نع نالعال نكم يو

(ةلئال-ناونعال يوتسم يلع راسم ل جهن عم مدختسي) رواجم ل راسم ل جهن يلع لاثم

```

route-policy BGP-neighbor-1
  if community matches-any COMM-LIST-1 then
    if destination is-best-path or destination is-backup-path then
      pass
    else
      drop
    endif
  elseif community matches-any COMM-LIST-2 then
    if destination is-multi-path or destination is-multipath-protect then
      pass
    else
      drop
    endif
  else
    drop
  endif
end-policy
!

```

ةللال BGP تاراسم ل RR ل ناك اذ:

```
RP/0/RP0/CPU0:RR#show bgp vpnv4 unicast rd 1:1 10.1.1.1/32
```

```

BGP routing table entry for 10.1.1.1/32, Route Distinguisher: 1:1
Versions:
  Process          bRIB/RIB  SendTblVer
  Speaker          5         5
Last Modified: Sep 18 07:14:32.907 for 00:06:53
Paths: (5 available, best #1)
  Advertised to update-groups (with more than one peer):
    0.3
  Advertised to peers (in unique update groups):

```

```

10.0.0.6      10.0.0.5
Path #1: Received by speaker 0
Advertised to update-groups (with more than one peer):
  0.3
Advertised to peers (in unique update groups):
  10.0.0.6      10.0.0.5
Local, (Received from a RR-client)
  10.0.0.1 (metric 2) from 10.0.0.1 (10.0.0.1)
    Received Label 24012
    Origin incomplete, metric 0, localpref 100, valid, internal, best, group-best, multipath,
import-candidate, imported
    Received Path ID 0, Local Path ID 1, version 5
    Extended community: RT:65000:1
    Source AFI: VPNv4 Unicast, Source VRF: one, Source Route Distinguisher: 1:1
Path #2: Received by speaker 0
Advertised to peers (in unique update groups):
  10.0.0.6      10.0.0.5
Local, (Received from a RR-client)
  10.0.0.2 (metric 2) from 10.0.0.2 (10.0.0.2)
    Received Label 24012
    Origin incomplete, metric 0, localpref 100, valid, internal, multipath, backup, add-path,
import-candidate, imported
    Received Path ID 0, Local Path ID 2, version 5
    Extended community: RT:65000:1
    Source AFI: VPNv4 Unicast, Source VRF: one, Source Route Distinguisher: 1:1
Path #3: Received by speaker 0
Advertised to peers (in unique update groups):
  10.0.0.5
Local, (Received from a RR-client)
  10.0.0.3 (metric 2) from 10.0.0.3 (10.0.0.3)
    Received Label 24012
    Origin incomplete, metric 0, localpref 100, valid, internal, multipath, add-path, import-
candidate, imported
    Received Path ID 0, Local Path ID 4, version 5
    Extended community: RT:65000:1
    Source AFI: VPNv4 Unicast, Source VRF: one, Source Route Distinguisher: 1:1
Path #4: Received by speaker 0
Advertised to peers (in unique update groups):
  10.0.0.5
Local, (Received from a RR-client)
  10.0.0.4 (metric 2) from 10.0.0.4 (10.0.0.4)
    Received Label 24013
    Origin incomplete, metric 0, localpref 100, valid, internal, backup(protect multipath),
add-path, import-candidate, imported
    Received Path ID 0, Local Path ID 3, version 5
    Extended community: RT:65000:1
    Source AFI: VPNv4 Unicast, Source VRF: one, Source Route Distinguisher: 1:1
Path #5: Received by speaker 0
Not advertised to any peer
Local, (Received from a RR-client)
  10.0.0.5 (metric 2) from 10.0.0.5 (10.0.0.5)
    Received Label 24014
    Origin incomplete, metric 0, localpref 100, valid, internal, import-candidate, imported
    Received Path ID 1, Local Path ID 0, version 0
    Extended community: RT:65000:1
    Source AFI: VPNv4 Unicast, Source VRF: one, Source Route Distinguisher: 1:1

```

وهو، راسملا ةسايس - رواجملا راسملا لولال لولال راسملا مث

```

if destination is-best-path or destination is-backup-path then
  pass

```

تاراسملا هذه رواجملا PE6 ىقلتى

RP/0/RP0/CPU0:PE6#show bgp vpnv4 unicast rd 1:1 10.1.1.1/32

BGP routing table entry for 10.1.1.1/32, Route Distinguisher: 1:1

Versions:

Process	bRIB/RIB	SendTblVer
Speaker	283	283

Last Modified: Sep 18 07:14:33.649 for 00:07:21

Paths: (2 available, best #1)

Not advertised to any peer

Path #1: Received by speaker 0

Not advertised to any peer

Local

10.0.0.1 (metric 3) from 10.0.0.101 (10.0.0.1)

Received Label 24012

Origin incomplete, metric 0, localpref 100, valid, internal, best, group-best, import-candidate, imported

Received Path ID 1, Local Path ID 1, version 283

Extended community: RT:65000:1

Originator: 10.0.0.1, Cluster list: 10.0.0.101

Source AFI: VPNv4 Unicast, Source VRF: one, Source Route Distinguisher: 1:1

Path #2: Received by speaker 0

Not advertised to any peer

Local

10.0.0.2 (metric 3) from 10.0.0.101 (10.0.0.2)

Received Label 24012

Origin incomplete, metric 0, localpref 100, valid, internal, import-candidate, imported

Received Path ID 2, Local Path ID 0, version 0

Extended community: RT:65000:1

Originator: 10.0.0.2, Cluster list: 10.0.0.101

Source AFI: VPNv4 Unicast, Source VRF: one, Source Route Distinguisher: 1:1

RR. ىل ع يطايت حال ا خ سن ل راس م و راس م ل ض ف ا م ه ن ا راس م ل ن ا ذ ه

ي ل ل ا ل ا ك ي ه و ، ر و ا ج م ل راس م ل ة س ا ي س ن م ي ن ا ث ل ا ع ز ج ل ل ة ب س ن ل ا ب

```
if destination is-multi-path or destination is-multipath-protect
then
pass
```

ت ا راس م ل ه ذ ه ر و ا ج م ل ا PE6 ي ق ل ت ي

RP/0/RP0/CPU0:PE6#show bgp vpnv4 unicast rd 1:1 10.1.1.1/32

BGP routing table entry for 10.1.1.1/32, Route Distinguisher: 1:1

Versions:

Process	bRIB/RIB	SendTblVer
Speaker	299	299

Last Modified: Sep 18 07:31:09.649 for 00:02:29

Paths: (3 available, best #1)

Not advertised to any peer

Path #1: Received by speaker 0

Not advertised to any peer

Local

10.0.0.2 (metric 3) from 10.0.0.101 (10.0.0.2)

Received Label 24012

Origin incomplete, metric 0, localpref 100, valid, internal, best, group-best, import-candidate, imported

Received Path ID 2, Local Path ID 1, version 299

Extended community: RT:65000:1

Originator: 10.0.0.2, Cluster list: 10.0.0.101

Source AFI: VPNv4 Unicast, Source VRF: one, Source Route Distinguisher: 1:1

Path #2: Received by speaker 0

Not advertised to any peer

Local

10.0.0.4 (metric 3) from 10.0.0.101 (10.0.0.4)

Received Label 24013

Origin incomplete, metric 0, localpref 100, valid, internal, import-candidate, imported

Received Path ID 3, Local Path ID 0, version 0

Extended community: RT:65000:1

Originator: 10.0.0.4, Cluster list: 10.0.0.101

Source AFI: VPNv4 Unicast, Source VRF: one, Source Route Distinguisher: 1:1

Path #3: Received by speaker 0

Not advertised to any peer

Local

10.0.0.3 (metric 3) from 10.0.0.101 (10.0.0.3)

Received Label 24012

Origin incomplete, metric 0, localpref 100, valid, internal, import-candidate, imported

Received Path ID 4, Local Path ID 0, version 0

Extended community: RT:65000:1

Originator: 10.0.0.3, Cluster list: 10.0.0.101

Source AFI: VPNv4 Unicast, Source VRF: one, Source Route Distinguisher: 1:1

خسننلا راسم و (!راسم لضفأ نمضتت ال نكلو) تاراسملا ددعتم تاراسملا يه تاراسملا هذه (ددعتملا تاراسملا ةيامح) يطايتحالا

هب اهلابقتسا متي يذلا بيترتلاب BGP تاراسم راهظا

يمجععمل بيترتلاب BGP تاراسم رهظت

BGP تاراسم ةيؤرل - Cisco IOS®-XR 7.3.1 يف هميدقت مت- ديدج رمأ مادختسا نكمي هب اهلابقتسا مت يذلا بيترتلاب

```
show bgp <afi> rd <rd> <path_details> <age-order>
```

ددعتم ةمالع عضو متي .تاراسملا ددعتم تملع تاراسملا تناك امل يري نأ ديفم رمأ اذه يوصق تاراسمك RIB يف اهتيبثت متي واقباس اهيققلت مت يتلا تاراسملا يلع تاراسملا يلع ةتبثملا تاراسملا BGP Multipath ةيساسالا ةملكلا **show route** رمألا ضرعي .راسملا وحنلا اذه

ديدل رمألا مادختسا نكمي ،هيلي تاراسملا ددعتم ةمالع عضو مت يذلا راسملا نم ققحتلل يلعأ يف نوكت ثدحالا تاراسملا .تاراسملا عيمجالتسا هب مت يذلا بيترتلا نم ققحتلل تاجرملا

ي:لالتلا نيوكتلا مادختساب ،لاثملا ليلبس يلع

```
route-policy BGP-Path-Selection
```

```
set path-selection multipath advertise
```

```
set path-selection backup 1 install multipath-protect advertise multipath-protect-advertise
```

```
end-policy
```

```
!
```

صئاصخ يأ يلع تاراسملا يوتحت الو ،لضفألا راسملا ريرقت ةيلمع يف تاريغيغت دجوت ال راسم لضفأ يف رارقلا ذاختا ةيلمع يلع رثوت (يلحمل ليلضفتلا لثم)

اذه BGP راسم ديدحت يلع RR لمتش ي

BGP routing table entry for 10.1.1.1/32, Route Distinguisher: 1:1

Versions:

Process	bRIB/RIB	SendTblVer
Speaker	5	5

Last Modified: Sep 18 08:46:11.907 for 00:03:43

Paths: (5 available, best #1)

Advertised to update-groups (with more than one peer):
0.3

Advertised to peers (in unique update groups):
10.0.0.5

Path #1: Received by speaker 0

Advertised to update-groups (with more than one peer):
0.3

Advertised to peers (in unique update groups):
10.0.0.5

Local, (Received from a RR-client)

10.0.0.1 (metric 2) from 10.0.0.1 (10.0.0.1)

Received Label 24012

Origin incomplete, metric 0, localpref 100, valid, internal, **best**, group-best, **multipath**,

import-candidate, imported

Received Path ID 0, Local Path ID 1, version 5

Extended community: RT:65000:1

Source AFI: VPNv4 Unicast, Source VRF: one, Source Route Distinguisher: 1:1

Path #2: Received by speaker 0

Advertised to peers (in unique update groups):
10.0.0.5

Local, (Received from a RR-client)

10.0.0.2 (metric 2) from 10.0.0.2 (10.0.0.2)

Received Label 24012

Origin incomplete, metric 0, localpref 100, valid, internal, **multipath**, **backup**, add-path,

import-candidate, imported

Received Path ID 0, Local Path ID 2, version 5

Extended community: RT:65000:1

Source AFI: VPNv4 Unicast, Source VRF: one, Source Route Distinguisher: 1:1

Path #3: Received by speaker 0

Advertised to peers (in unique update groups):
10.0.0.5 10.0.0.6

Local, (Received from a RR-client)

10.0.0.3 (metric 2) from 10.0.0.3 (10.0.0.3)

Received Label 24012

Origin incomplete, metric 0, localpref 100, valid, internal, **multipath**, add-path, import-candidate, imported

Received Path ID 0, Local Path ID 3, version 5

Extended community: RT:65000:1

Source AFI: VPNv4 Unicast, Source VRF: one, Source Route Distinguisher: 1:1

Path #4: Received by speaker 0

Advertised to peers (in unique update groups):
10.0.0.5 10.0.0.6

Local, (Received from a RR-client)

10.0.0.4 (metric 2) from 10.0.0.4 (10.0.0.4)

Received Label 24013

Origin incomplete, metric 0, localpref 100, valid, internal, **backup(protect multipath)**, add-path, import-candidate, imported

Received Path ID 0, Local Path ID 4, version 5

Extended community: RT:65000:1

Source AFI: VPNv4 Unicast, Source VRF: one, Source Route Distinguisher: 1:1

Path #5: Received by speaker 0

Not advertised to any peer

Local, (Received from a RR-client)

10.0.0.5 (metric 2) from 10.0.0.5 (10.0.0.5)

Received Label 24014

Origin incomplete, metric 0, localpref 100, valid, internal, import-candidate, imported

Received Path ID 1, Local Path ID 0, version 0

Extended community: RT:65000:1

Source AFI: VPNv4 Unicast, Source VRF: one, Source Route Distinguisher: 1:1

خسننلا راسم وه 10.0.0.2 نم راسملا اذامل؟ راسم لضفأ وه 10.0.0.1 نم راسملا اذامل
خسننلا وه 10.0.0.4 نم راسملا اذامل؟ تاراسملا ددعتم 10.0.0.3 نم راسملا اذامل؟ يطاي تحالال
لضفأ راسملا سيل 10.0.0.5 نم راسملا اذامل؟ (ددعتم تاراسملا ةيماح) يطاي تحالال
(ددعتم تاراسملا ةيماح) يطاي تحالال خسننلا راسم الو ددعتم راسملا سيلو

نوكت ثدحالال تاراسملا. ةياهنلا يف رمعلال بيترت عم هسفن رمألا مادختساب اذه ةيؤركنكمي
تاجخملال لعل يف

```
RP/0/RP0/CPU0:RR#show bgp vpnv4 unicast rd 1:1 10.1.1.1/32 age-order
```

BGP routing table entry for 10.1.1.1/32, Route Distinguisher: 1:1

Versions:

Process bRIB/RIB SendTblVer

Speaker 5 5

Flags: 0x240692b2+0x00010000; multipath; backup available;

Last Modified: Sep 18 07:31:07.907 for 00:23:23

Paths: (5 available, best #3)

Advertised to update-groups (with more than one peer):

0.3

Advertised to peers (in unique update groups):

10.0.0.5

Path #1: Received by speaker 0

Flags: 0x2000000084060205, import: 0x96

Advertised to peers (in unique update groups):

10.0.0.6 10.0.0.5

Local, (Received from a RR-client)

10.0.0.4 (metric 2) from 10.0.0.4 (10.0.0.4), if-handle 0x00000000

Received Label 24013

Origin incomplete, metric 0, localpref 100, valid, internal, **backup(protect multipath)**,

add-path, import-candidate, imported

Received Path ID 0, Local Path ID 3, version 5

Extended community: RT:65000:1

Source AFI: VPNv4 Unicast, Source VRF: one, Source Route Distinguisher: 1:1

Path #2: Received by speaker 0

Flags: 0x2000000084020205, import: 0x96

Not advertised to any peer

Local, (Received from a RR-client)

10.0.0.5 (metric 2) from 10.0.0.5 (10.0.0.5), if-handle 0x00000000

Received Label 24014

Origin incomplete, metric 0, localpref 100, valid, internal, import-candidate, imported

Received Path ID 1, Local Path ID 0, version 0

Extended community: RT:65000:1

Source AFI: VPNv4 Unicast, Source VRF: one, Source Route Distinguisher: 1:1

Path #3: Received by speaker 0

Flags: 0x2000000085070205, import: 0x9f

Advertised to update-groups (with more than one peer):

0.3

Advertised to peers (in unique update groups):

10.0.0.5

Local, (Received from a RR-client)

10.0.0.1 (metric 2) from 10.0.0.1 (10.0.0.1), if-handle 0x00000000

Received Label 24012

Origin incomplete, metric 0, localpref 100, valid, internal, **best**, group-best, multipath,

import-candidate, imported

Received Path ID 0, Local Path ID 1, version 5

Extended community: RT:65000:1

Source AFI: VPNv4 Unicast, Source VRF: one, Source Route Distinguisher: 1:1

Path #4: Received by speaker 0

Flags: 0x2000000084070205, import: 0x96

Advertised to peers (in unique update groups):

```

10.0.0.6      10.0.0.5
Local, (Received from a RR-client)
  10.0.0.3 (metric 2) from 10.0.0.3 (10.0.0.3), if-handle 0x00000000
    Received Label 24012
    Origin incomplete, metric 0, localpref 100, valid, internal, multipath, add-path, import-
candidate, imported
    Received Path ID 0, Local Path ID 4, version 5
    Extended community: RT:65000:1
    Source AFI: VPNv4 Unicast, Source VRF: one, Source Route Distinguisher: 1:1
Path #5: Received by speaker 0
Flags: 0x2000000084070205, import: 0x96
Advertised to peers (in unique update groups):
  10.0.0.6      10.0.0.5
Local, (Received from a RR-client)
  10.0.0.2 (metric 2) from 10.0.0.2 (10.0.0.2), if-handle 0x00000000
    Received Label 24012
    Origin incomplete, metric 0, localpref 100, valid, internal, multipath, backup, add-path,
import-candidate, imported
    Received Path ID 0, Local Path ID 2, version 5
    Extended community: RT:65000:1
    Source AFI: VPNv4 Unicast, Source VRF: one, Source Route Distinguisher: 1:1

```

إذا لم نم ققحت لل **bestpath-compare** في أساس الة لكل ال عم **show bgp** رم أو ما دخت س إ كن كم ي
(راسم لكل ب ب س ل ا ض رع م تي) راسم ل ض ف أ وه راسم ل س ي ل

```
RP/0/RP0/CPU0:RR#show bgp vpnv4 unicast rd 1:1 10.1.1.1/32 bestpath-compare
```

```

BGP routing table entry for 10.1.1.1/32, Route Distinguisher: 1:1
Versions:
  Process          bRIB/RIB  SendTblVer
  Speaker          5         5
    Flags: 0x240692b2+0x00010000; multipath; backup available;
Last Modified: Sep 18 07:31:07.907 for 00:44:59
Paths: (5 available, best #1)
  Advertised to update-groups (with more than one peer):
    0.3
  Advertised to peers (in unique update groups):
    10.0.0.5
  Path #1: Received by speaker 0
  Flags: 0x2000000085070205, import: 0x9f
  Advertised to update-groups (with more than one peer):
    0.3
  Advertised to peers (in unique update groups):
    10.0.0.5
Local, (Received from a RR-client)
  10.0.0.1 (metric 2) from 10.0.0.1 (10.0.0.1), if-handle 0x00000000
    Received Label 24012
    Origin incomplete, metric 0, localpref 100, valid, internal, best, group-best, multipath,
import-candidate, imported
    Received Path ID 0, Local Path ID 1, version 5
    Extended community: RT:65000:1
    best of local AS, Overall best
    Source AFI: VPNv4 Unicast, Source VRF: one, Source Route Distinguisher: 1:1
Path #2: Received by speaker 0
Flags: 0x2000000084070205, import: 0x96
Advertised to peers (in unique update groups):
  10.0.0.6      10.0.0.5
Local, (Received from a RR-client)
  10.0.0.2 (metric 2) from 10.0.0.2 (10.0.0.2), if-handle 0x00000000
    Received Label 24012
    Origin incomplete, metric 0, localpref 100, valid, internal, multipath, backup, add-path,
import-candidate, imported
    Received Path ID 0, Local Path ID 2, version 5

```

```

Extended community: RT:65000:1
iBGP multi-path
Source AFI: VPNv4 Unicast, Source VRF: one, Source Route Distinguisher: 1:1
Path #3: Received by speaker 0
Flags: 0x2000000084070205, import: 0x96
Advertised to peers (in unique update groups):
10.0.0.6      10.0.0.5
Local, (Received from a RR-client)
10.0.0.3 (metric 2) from 10.0.0.3 (10.0.0.3), if-handle 0x00000000
Received Label 24012
Origin incomplete, metric 0, localpref 100, valid, internal, multipath, add-path, import-
candidate, imported
Received Path ID 0, Local Path ID 4, version 5
Extended community: RT:65000:1
iBGP multi-path
Source AFI: VPNv4 Unicast, Source VRF: one, Source Route Distinguisher: 1:1
Path #4: Received by speaker 0
Flags: 0x2000000084060205, import: 0x96
Advertised to peers (in unique update groups):
10.0.0.6      10.0.0.5
Local, (Received from a RR-client)
10.0.0.4 (metric 2) from 10.0.0.4 (10.0.0.4), if-handle 0x00000000
Received Label 24013
Origin incomplete, metric 0, localpref 100, valid, internal, backup(protect multipath),
add-path, import-candidate, imported
Received Path ID 0, Local Path ID 3, version 5
Extended community: RT:65000:1
Higher router ID than best path (path #1)
Source AFI: VPNv4 Unicast, Source VRF: one, Source Route Distinguisher: 1:1
Path #5: Received by speaker 0
Flags: 0x2000000084020205, import: 0x96
Not advertised to any peer
Local, (Received from a RR-client)
10.0.0.5 (metric 2) from 10.0.0.5 (10.0.0.5), if-handle 0x00000000
Received Label 24014
Origin incomplete, metric 0, localpref 100, valid, internal, import-candidate, imported
Received Path ID 1, Local Path ID 0, version 0
Extended community: RT:65000:1
Higher router ID than best path (path #1)
Source AFI: VPNv4 Unicast, Source VRF: one, Source Route Distinguisher: 1:1

```

لضفا رأي تخارارق نإف، تاراسم ال نيب ةي واستم BGP تاراسم يف تامس ال مظعم نأ امب
 BGP 10.0.0.1 توص ربكم يلي امي ف. BGP توص ربكم نم هجوم فرعم لقا يلى لقتنا راسم
 ربكم نم هجوم فرعم لقا يثا يلاتلابو، راسم لضا يثا وه يطايتحال خسن ال راسم
 BGP 10.0.0.2 انه توص

دعب اهتبيثت مت اهان ال تاراسم ال ةدعتم تاراسم تسيل 10.0.0.5 و 10.0.0.4 نم تاراسم ال
 10.0.0.3 و 10.0.0.2 و 10.0.0.1 نم تاراسم ال

(ةدعتم ال تاراسم ال ةي امح) يطايتحال خسن ال لباقم يطايتحال خسن ال راسم

```

route-policy BGP-Path-Selection
  set path-selection multipath advertise
  set path-selection backup 1 install multipath-protect advertise multipath-protect-advertise
end-policy
!
```

Maximum-path ibgp 3. نيوكت مت

راسم لبق ةدعتم ال تاراسم ال مالتسإ مت، انه. راسم لضا يثا وه يطايتحال خسن ال
 يطايتحال خسن راسم وه رخاؤ تاراسم ال ةدعتم تاراسم ةثالث كانه، اذا. ةي طاييتحال خسن ال

RP/0/RP0/CPU0:RR#show bgp vpnv4 unicast rd 1:1 10.1.1.1/32 age-order

BGP routing table entry for 10.1.1.1/32, Route Distinguisher: 1:1

Versions:

```
Process          bRIB/RIB  SendTblVer
Speaker          5         5
```

Flags: 0x240692b2+0x00010000; multipath; backup available;

Last Modified: Sep 18 08:51:17.907 for 00:07:11

Paths: (5 available, best #3)

Advertised to update-groups (with more than one peer):

0.3

Advertised to peers (in unique update groups):

10.0.0.5

Path #1: Received by speaker 0

Flags: 0x2000000084020205, import: 0x96

Not advertised to any peer

Local, (Received from a RR-client)

10.0.0.4 (metric 2) from 10.0.0.4 (10.0.0.4), if-handle 0x00000000

Received Label 24013

Origin incomplete, metric 0, localpref 100, valid, internal, import-candidate, imported

Received Path ID 0, Local Path ID 0, version 0

Extended community: RT:65000:1

Source AFI: VPNv4 Unicast, Source VRF: one, Source Route Distinguisher: 1:1

Path #2: Received by speaker 0

Flags: 0x2000000084060205, import: 0x96

Advertised to peers (in unique update groups):

10.0.0.5

Local, (Received from a RR-client)

10.0.0.2 (metric 2) from 10.0.0.2 (10.0.0.2), if-handle 0x00000000

Received Label 24012

Origin incomplete, metric 0, localpref 100, valid, internal, **backup**, add-path, import-candidate, imported

Received Path ID 0, Local Path ID 2, version 5

Extended community: RT:65000:1

Source AFI: VPNv4 Unicast, Source VRF: one, Source Route Distinguisher: 1:1

Path #3: Received by speaker 0

Flags: 0x2000000085070205, import: 0x9f

Advertised to update-groups (with more than one peer):

0.3

Advertised to peers (in unique update groups):

10.0.0.5

Local, (Received from a RR-client)

10.0.0.1 (metric 2) from 10.0.0.1 (10.0.0.1), if-handle 0x00000000

Received Label 24012

Origin incomplete, metric 0, localpref 100, valid, internal, **best**, group-best, multipath, import-candidate, imported

Received Path ID 0, Local Path ID 1, version 5

Extended community: RT:65000:1

Source AFI: VPNv4 Unicast, Source VRF: one, Source Route Distinguisher: 1:1

Path #4: Received by speaker 0

Flags: 0x2000000084070205, import: 0x96

Advertised to peers (in unique update groups):

10.0.0.6

Local, (Received from a RR-client)

10.0.0.5 (metric 2) from 10.0.0.5 (10.0.0.5), if-handle 0x00000000

Received Label 24014

Origin incomplete, metric 0, localpref 100, valid, internal, **multipath**, add-path, import-candidate, imported

Received Path ID 1, Local Path ID 3, version 5

Extended community: RT:65000:1

Source AFI: VPNv4 Unicast, Source VRF: one, Source Route Distinguisher: 1:1

Path #5: Received by speaker 0

Flags: 0x2000000084070205, import: 0x96
Advertised to peers (in unique update groups):
10.0.0.5 10.0.0.6
Local, (Received from a RR-client)
10.0.0.3 (metric 2) from 10.0.0.3 (10.0.0.3), if-handle 0x00000000
Received Label 24012
Origin incomplete, metric 0, localpref 100, valid, internal, **multipath**, add-path, import-candidate, imported
Received Path ID 0, Local Path ID 4, version 5
Extended community: RT:65000:1
Source AFI: VPNv4 Unicast, Source VRF: one, Source Route Distinguisher: 1:1

كيدل نآلا 10.0.0.5 راجلا قلغأ:

RP/0/RP0/CPU0:RR#show bgp vpnv4 unicast rd 1:1 10.1.1.1/32 age-order

BGP routing table entry for 10.1.1.1/32, Route Distinguisher: 1:1

Versions:

Process	BRIB/RIB	SendTblVer
Speaker	7	7

Flags: 0x2406b2b2+0x00010000; **multipath**; backup available;

Last Modified: Sep 18 09:05:07.907 for 00:00:23

Paths: (4 available, best #3)

Advertised to update-groups (with more than one peer):
0.3

Path #1: Received by speaker 0

Flags: 0x2000000084060205, import: 0x96

Advertised to peers (in unique update groups):

10.0.0.6

Local, (Received from a RR-client)

10.0.0.4 (metric 2) from 10.0.0.4 (10.0.0.4), if-handle 0x00000000

Received Label 24013

Origin incomplete, metric 0, localpref 100, valid, internal, **backup(protect multipath)**, add-path, import-candidate, imported

Received Path ID 0, Local Path ID 5, version 7

Extended community: RT:65000:1

Source AFI: VPNv4 Unicast, Source VRF: one, Source Route Distinguisher: 1:1

Path #2: Received by speaker 0

Flags: 0x2000000084070205, import: 0x96

Advertised to peers (in unique update groups):

10.0.0.6

Local, (Received from a RR-client)

10.0.0.2 (metric 2) from 10.0.0.2 (10.0.0.2), if-handle 0x00000000

Received Label 24012

Origin incomplete, metric 0, localpref 100, valid, internal, **multipath, backup**, add-path, import-candidate, imported

Received Path ID 0, Local Path ID 2, version 7

Extended community: RT:65000:1

Source AFI: VPNv4 Unicast, Source VRF: one, Source Route Distinguisher: 1:1

Path #3: Received by speaker 0

Flags: 0x2000000085070205, import: 0x9f

Advertised to update-groups (with more than one peer):

0.3

Local, (Received from a RR-client)

10.0.0.1 (metric 2) from 10.0.0.1 (10.0.0.1), if-handle 0x00000000

Received Label 24012

Origin incomplete, metric 0, localpref 100, valid, internal, **best**, group-best, **multipath**, import-candidate, imported

Received Path ID 0, Local Path ID 1, version 5

Extended community: RT:65000:1

Source AFI: VPNv4 Unicast, Source VRF: one, Source Route Distinguisher: 1:1

Path #4: Received by speaker 0

Flags: 0x2000000084070205, import: 0x96

Advertised to peers (in unique update groups):
10.0.0.6

Local, (Received from a RR-client)

10.0.0.3 (metric 2) from 10.0.0.3 (10.0.0.3), if-handle 0x00000000

Received Label 24012

Origin incomplete, metric 0, localpref 100, valid, internal, **multipath**, add-path, import-candidate, imported

Received Path ID 0, Local Path ID 4, version 5

Extended community: RT:65000:1

Source AFI: VPNv4 Unicast, Source VRF: one, Source Route Distinguisher: 1:1

• 10.0.0.5 ن م راسم ال يفتخا

• اضي أ تاراسم ال ددعت م نآل ه نكلو، اي طايتح | 10.0.0.2 ن م راسم ال لازي ال

• خسن راسم نآل كيدل، تاراسم ال ددعت م راسم اضي أ وه ي طايتح ال خسن ال راسم نآل
10.0.0.4 ن م راسم ال وه اذه. (تاراسم ال ددعت م ةي امح) ي طايتح |

10.0.0.5 رواجم ال قالغ اءاغ ل اب مق

```
RP/0/RP0/CPU0:RR#show bgp vpnv4 unicast rd 1:1 10.1.1.1/32 age-order
```

BGP routing table entry for 10.1.1.1/32, Route Distinguisher: 1:1

Versions:

Process	bRIB/RIB	SendTblVer
Speaker	10	10

Flags: 0x2406b2b2+0x00010000; multipath; backup available;

Last Modified: Sep 18 09:08:42.907 for 00:00:00

Paths: (5 available, best #4)

Advertised to update-groups (with more than one peer):

0.3

Advertised to peers (in unique update groups):

10.0.0.5

Path #1: Received by speaker 0

Flags: 0x2000000084020205, import: 0x96

Not advertised to any peer

Local, (Received from a RR-client)

10.0.0.5 (metric 2) from 10.0.0.5 (10.0.0.5), if-handle 0x00000000

Received Label 24014

Origin incomplete, metric 0, localpref 100, valid, internal, import-candidate, imported

Received Path ID 1, Local Path ID 0, version 0

Extended community: RT:65000:1

Source AFI: VPNv4 Unicast, Source VRF: one, Source Route Distinguisher: 1:1

Path #2: Received by speaker 0

Flags: 0x2000000084060205, import: 0x96

Advertised to peers (in unique update groups):

10.0.0.5 10.0.0.6

Local, (Received from a RR-client)

10.0.0.4 (metric 2) from 10.0.0.4 (10.0.0.4), if-handle 0x00000000

Received Label 24013

Origin incomplete, metric 0, localpref 100, valid, internal, **backup(protect multipath)**, add-path, import-candidate, imported

Received Path ID 0, Local Path ID 5, version 7

Extended community: RT:65000:1

Source AFI: VPNv4 Unicast, Source VRF: one, Source Route Distinguisher: 1:1

Path #3: Received by speaker 0

Flags: 0x2000000084070205, import: 0x96

Advertised to peers (in unique update groups):

10.0.0.5 10.0.0.6

Local, (Received from a RR-client)

10.0.0.2 (metric 2) from 10.0.0.2 (10.0.0.2), if-handle 0x00000000

Received Label 24012

Origin incomplete, metric 0, localpref 100, valid, internal, **multipath, backup**, add-path, import-candidate, imported

```

Received Path ID 0, Local Path ID 2, version 10
Extended community: RT:65000:1
Source AFI: VPNv4 Unicast, Source VRF: one, Source Route Distinguisher: 1:1
Path #4: Received by speaker 0
Flags: 0x2000000085070205, import: 0x9f
Advertised to update-groups (with more than one peer):
0.3
Advertised to peers (in unique update groups):
10.0.0.5
Local, (Received from a RR-client)
10.0.0.1 (metric 2) from 10.0.0.1 (10.0.0.1), if-handle 0x00000000
Received Label 24012
Origin incomplete, metric 0, localpref 100, valid, internal, best, group-best, multipath,
import-candidate, imported
Received Path ID 0, Local Path ID 1, version 5
Extended community: RT:65000:1
Source AFI: VPNv4 Unicast, Source VRF: one, Source Route Distinguisher: 1:1
Path #5: Received by speaker 0
Flags: 0x2000000084070205, import: 0x96
Advertised to peers (in unique update groups):
10.0.0.5      10.0.0.6
Local, (Received from a RR-client)
10.0.0.3 (metric 2) from 10.0.0.3 (10.0.0.3), if-handle 0x00000000
Received Label 24012
Origin incomplete, metric 0, localpref 100, valid, internal, multipath, add-path, import-
candidate, imported
Received Path ID 0, Local Path ID 4, version 5
Extended community: RT:65000:1
Source AFI: VPNv4 Unicast, Source VRF: one, Source Route Distinguisher: 1:1

```

نم راسم الة فاضا تم . لبق نم اهت يثبت مت يت الة ب الة تاراسم الة اى ش ريغت ي مل نم عون ي ا و ا تاراسم الة ددع تم راسم س ي ل ه ن ا . ث دح ا ه ن الة الة ي ف س ل ج ي ه ن ا . ط ق ف 10.0.0.5 ي ط ا ي ت ح الة خ س ن الة راسم

ريغت دع ب تاراسم الة ددع تم ريغ الة تاراسم الة ددع تم نم 10.0.0.5 نم راسم الة ريغت مت راسم الة ف الة ل

رارق الة

- نوكت تاراسم الة اى ددع ت ي ف ارود ه ب تاراسم الة ل ا ب ق ت س ا مت ي ي ذل ا ب ي ت ر ت ل ا ب ع ل ي . تاراسم الة ددع تم
- ي ط ا ي ت ح ا خ س ن راسم ك ا ن ه ن ا ك ا ذ ا ارود تاراسم الة م ا ل ت س ا ه ي ف مت ي ي ذل ا ب ي ت ر ت ل ا ب ع ل ي . ال م ا (تاراسم الة ددع تم ا ي م ا ح)
- ل ض ف ا ك ه ر ا ي ت خ ا مت ي راسم ي ا ي ف ارود ب ع ل ي ال تاراسم الة م ا ل ت س ا ه ب مت ي ي ذل ا ب ي ت ر ت ل ا ب ع ل ي . ي ط ا ي ت ح ا خ س ن راسم و ا راسم

IGP سايق بسح بلطال

(IGP) الة ل خ ا د ل ا ر ا ب ع ال ل و ك و ت و ر ب سايق ل ل ة د د ع ت م الة تاراسم الة ب ي ت ر ت ل ر ا ي خ ك ا ن ه

```

RP/0/RP0/CPU0:RR#conf t
RP/0/RP0/CPU0:RR(config)#router bgp 65000
RP/0/RP0/CPU0:RR(config-bgp)#vrf one
RP/0/RP0/CPU0:RR(config-bgp-vrf)#address-family ipv4 unicast
RP/0/RP0/CPU0:RR(config-bgp-vrf-af)#maximum-paths ibgp 3 unequal-cost ?
deterministic Deterministic Multipath selection primarily on IGP metric order
selective Allow multipaths only from marked neighbors
<cr>

```

```
RP/0/RP0/CPU0:RR(config-bgp-vrf-af)#maximum-paths ibgp 3 unequal-cost deterministic ?
selective Allow multipaths only from marked neighbors
<cr>
RP/0/RP0/CPU0:RR(config-bgp-vrf-af)#maximum-paths ibgp 3 unequal-cost deterministic
RP/0/RP0/CPU0:RR(config-bgp-vrf-af)#commit
RP/0/RP0/CPU0:RR(config-bgp-vrf-af)#end
RP/0/RP0/CPU0:RR#
```

راسم و طقف لضفألا راسملا يلع لصحت كنإف، وإو ةبولطم ةئفاكتمل ريغ ةفلكتلا
إلا جاتحت ةددعتملا تاراسملا نأل تاراسملا ددعتم راسم دجوي ال نكل ويطايتحال خسنلا
ةددعتم تاراسم اهرابتعا متي يتح ةيلخادلا ةرابعالا لوكتورب ةفلكت سفن

لوكتورب ةفلكت نيوكت متي . ططخملا في PE تاهجوم يلى RR نم IGP ةفلكت ريغت متي
يلى امك ةيلخادلا ةرابعالا

- RR يلى PE1 : 5
- RR يلى PE2 : 4
- RR يلى PE3 : 3
- RR يلى PE4 : 2
- RR يلى PE5 : 1

هذه كانه لازت ال

```
route-policy BGP-Path-Selection
  set path-selection multipath advertise
  set path-selection backup 1 install multipath-protect advertise multipath-protect-advertise
end-policy
!
```

(تاطابت رالا عيجم في اهسفن يه ةفلكتلا) IGP سايق تاريغت لبق

```
RP/0/RP0/CPU0:RR#show bgp vpnv4 unicast rd 1:1 10.1.1.1/32
```

```
BGP routing table entry for 10.1.1.1/32, Route Distinguisher: 1:1
Versions:
  Process          bRIB/RIB  SendTblVer
  Speaker          10        10
Last Modified: Sep 18 09:08:42.907 for 05:26:53
Paths: (5 available, best #1)
  Advertised to update-groups (with more than one peer):
    0.3
  Advertised to peers (in unique update groups):
    10.0.0.5
  Path #1: Received by speaker 0
  Advertised to update-groups (with more than one peer):
    0.3
  Advertised to peers (in unique update groups):
    10.0.0.5
  Local, (Received from a RR-client)
    10.0.0.1 (metric 2) from 10.0.0.1 (10.0.0.1)
      Received Label 24012
      Origin incomplete, metric 0, localpref 100, valid, internal, best, group-best, multipath,
import-candidate, imported
      Received Path ID 0, Local Path ID 1, version 5
      Extended community: RT:65000:1
      Source AFI: VPNv4 Unicast, Source VRF: one, Source Route Distinguisher: 1:1
  Path #2: Received by speaker 0
  Advertised to peers (in unique update groups):
    10.0.0.5      10.0.0.6
  Local, (Received from a RR-client)
```

```
10.0.0.2 (metric 2) from 10.0.0.2 (10.0.0.2)
  Received Label 24012
  Origin incomplete, metric 0, localpref 100, valid, internal, multipath, backup, add-path,
import-candidate, imported
  Received Path ID 0, Local Path ID 2, version 10
  Extended community: RT:65000:1
  Source AFI: VPNv4 Unicast, Source VRF: one, Source Route Distinguisher: 1:1
Path #3: Received by speaker 0
Advertised to peers (in unique update groups):
  10.0.0.5      10.0.0.6
Local, (Received from a RR-client)
10.0.0.3 (metric 2) from 10.0.0.3 (10.0.0.3)
  Received Label 24012
  Origin incomplete, metric 0, localpref 100, valid, internal, multipath, add-path, import-
candidate, imported
  Received Path ID 0, Local Path ID 4, version 5
  Extended community: RT:65000:1
  Source AFI: VPNv4 Unicast, Source VRF: one, Source Route Distinguisher: 1:1
Path #4: Received by speaker 0
Advertised to peers (in unique update groups):
  10.0.0.5      10.0.0.6
Local, (Received from a RR-client)
10.0.0.4 (metric 2) from 10.0.0.4 (10.0.0.4)
  Received Label 24013
  Origin incomplete, metric 0, localpref 100, valid, internal, backup(protect multipath),
add-path, import-candidate, imported
  Received Path ID 0, Local Path ID 5, version 7
  Extended community: RT:65000:1
  Source AFI: VPNv4 Unicast, Source VRF: one, Source Route Distinguisher: 1:1
Path #5: Received by speaker 0
Not advertised to any peer
Local, (Received from a RR-client)
10.0.0.5 (metric 2) from 10.0.0.5 (10.0.0.5)
  Received Label 24014
  Origin incomplete, metric 0, localpref 100, valid, internal, import-candidate, imported
  Received Path ID 1, Local Path ID 0, version 0
  Extended community: RT:65000:1
  Source AFI: VPNv4 Unicast, Source VRF: one, Source Route Distinguisher: 1:1
```

IGP سايقم رييغت دعب

```
RP/0/RP0/CPU0:RR#show bgp vpnv4 unicast rd 1:1 10.1.1.1/32 age-order
```

```
BGP routing table entry for 10.1.1.1/32, Route Distinguisher: 1:1
```

```
Versions:
```

```
Process          bRIB/RIB  SendTblVer
Speaker          14        14
```

```
Flags: 0x2486b2b2+0x00010000; multipath; backup available;
```

```
Last Modified: Sep 18 16:09:45.907 for 00:01:10
```

```
Paths: (5 available, best #2)
```

```
Advertised to update-groups (with more than one peer):
```

```
0.3
```

```
Path #1: Received by speaker 0
```

```
Flags: 0x2000000084020205, import: 0x94
```

```
Not advertised to any peer
```

```
Local, (Received from a RR-client)
```

```
10.0.0.1 (metric 6) from 10.0.0.1 (10.0.0.1), if-handle 0x00000000
```

```
Received Label 24012
```

```
Origin incomplete, metric 0, localpref 100, valid, internal, import-candidate, imported
```

```
Received Path ID 1, Local Path ID 0, version 0
```

```
Extended community: RT:65000:1
```

```
Source AFI: VPNv4 Unicast, Source VRF: one, Source Route Distinguisher: 1:1
```

```
Path #2: Received by speaker 0
```

```

Flags: 0x2000000085070205, import: 0x9f
Advertised to update-groups (with more than one peer):
  0.3
Local, (Received from a RR-client)
  10.0.0.5 (metric 2) from 10.0.0.5 (10.0.0.5), if-handle 0x00000000
  Received Label 24014
  Origin incomplete, metric 0, localpref 100, valid, internal, best, group-best, multipath,
import-candidate, imported
  Received Path ID 1, Local Path ID 1, version 11
  Extended community: RT:65000:1
  Source AFI: VPNv4 Unicast, Source VRF: one, Source Route Distinguisher: 1:1
Path #3: Received by speaker 0
Flags: 0x2000000084060205, import: 0x94
Advertised to update-groups (with more than one peer):
  0.3
Advertised to peers (in unique update groups):
  10.0.0.6
Local, (Received from a RR-client)
  10.0.0.2 (metric 5) from 10.0.0.2 (10.0.0.2), if-handle 0x00000000
  Received Label 24012
  Origin incomplete, metric 0, localpref 100, valid, internal, backup(protect multipath),
add-path, import-candidate, imported
  Received Path ID 1, Local Path ID 3, version 10
  Extended community: RT:65000:1
  Source AFI: VPNv4 Unicast, Source VRF: one, Source Route Distinguisher: 1:1
Path #4: Received by speaker 0
Flags: 0x2000000084070205, import: 0xd4
Advertised to update-groups (with more than one peer):
  0.3
Advertised to peers (in unique update groups):
  10.0.0.6
Local, (Received from a RR-client)
  10.0.0.4 (metric 3) from 10.0.0.4 (10.0.0.4), if-handle 0x00000000
  Received Label 24013
  Origin incomplete, metric 0, localpref 100, valid, internal, multipath, backup, add-path,
import-candidate, imported
  Received Path ID 1, Local Path ID 5, version 14
  Extended community: RT:65000:1
  Source AFI: VPNv4 Unicast, Source VRF: one, Source Route Distinguisher: 1:1
Path #5: Received by speaker 0
Flags: 0x2000000084070205, import: 0x94
Advertised to update-groups (with more than one peer):
  0.3
Advertised to peers (in unique update groups):
  10.0.0.6
Local, (Received from a RR-client)
  10.0.0.3 (metric 4) from 10.0.0.3 (10.0.0.3), if-handle 0x00000000
  Received Label 24012
  Origin incomplete, metric 0, localpref 100, valid, internal, multipath, add-path, import-
candidate, imported
  Received Path ID 1, Local Path ID 4, version 10
  Extended community: RT:65000:1
  Source AFI: VPNv4 Unicast, Source VRF: one, Source Route Distinguisher: 1:1

```

- (2 ڀرت م ل) IGP س ا ق م ض ا ف خ ن ا ب ب س ب 10.0.0.5 ن م ر ا س م ل و ه ن ا ل ر ا س م ل ض ف ا .
- و ه و ، IGP س ا ق ل ض ف ا ڀ ن ا ت ل ع ل ڀ و ت ح ڀ ڀ ذ ل ر ا س م ل ن ا ل و ه ڀ ط ا ڀ ت ح ا ل خ س ن ل ر ا س م
- (3 ڀرت م ل) 10.0.0.4 ن م ر ا س م ل .
- د ح ا و ر ا س م ل ق ب ڀ ل ل ذ ل ، ت ا ر ا س م ل د د ع ت م ڀ ط ا ڀ ت ح ا ل خ س ن ل ر ا س م ل و ه ن ا ل ر ا س م ل ن ا ا م ك
- (4 س ا ق ل) 10.0.0.3 ن م ر ا س م ل و ه ا ذ ه . ه ر ا ڀ ت خ ا م ت ڀ ل ت ا ر ا س م ل د د ع ت م
- (5 س ا ق ل) 10.0.0.2 ن م ر ا س م ل و ه (د د ع ت م ل ت ا ر ا س م ل ة ڀ ا م ح) ڀ ط ا ڀ ت ح ا ل خ س ن ل ر ا س م
- ڀ و ت ح ڀ ه ن ا ل ، ق ا ل ط ا ل ل ع ل (6 ڀرت م ل) 10.0.0.1 ن م ر ا س م ل ل ع ل ة م ا ل ع و م ت ڀ م ل ، ا ر ڀ خ ا و
- س ا ق م ا و س ا ل ع ل .

ةمچرتل هذه لوج

ةللأل تاي نقتل نمة ومة مادختساب دن تسمل اذة Cisco تمةرت
ملاعلاء انء عمة ف نمة دختسمل معد ى وتحم مة دقتل ةرشة لل و
امك ةققة نوك ت نل ةللأل ةمچرت لصف أن ةظحال مة چرئ. ةصاخل مة تة لل ب
Cisco ةلخت. فرتحم مچرت مة دققة لل ةل
ىل ةل
(رفوتم طبارل) ىل ةل ةل