

# Stealthwatch Flow Collector 4200

First Ship Date: 5/2017

Final Ship Date: Currently Shipping

The Stealthwatch Flow Collector 4200 has the following general configuration. Your model may look slightly different.

## Front View



## Back View



1. Reserved ports
2. CIMC management port
3. Stealthwatch management port
4. Monitoring port

## Specifications

UCS Platform	UCSC-C22-M4S
Maximum Flows per Second (fps)	120,000 fps *
Network/NIC	<p>Reserved ports: 2; 10 GB SFP+</p> <p>CIMC management port: 1; 100/1000 copper</p> <p>Stealthwatch management port: 1; 100/1000 copper</p> <p>Monitoring port: 1; 100/1000 copper</p> <p><b>Note:</b> You can configure a monitoring port to be a dedicated interface (ingress only) for receiving NetFlow traffic.</p>
Processor	2.40 GHz E5-2680 v4

Memory	32 GB DDR4 (16x) - 512GB total
Flow Storage	4 TB, RAID 6, Redundant
Addressable Storage	7.2TB
RAID Cache	4 GB
Rack Units	1U
Weight	37.9 pounds (17.2 kg)
Dimensions	<b>Height:</b> 1.7 inches (4.3 cm) <b>Width:</b> 16.9 inches (42.9 cm) <b>Depth:</b> 29.8 inches (75.8 cm)
Power	Redundant 770W AC 50/60 Auto Ranging (100v to 240V)
Humidity (Relative)	<b>Operating:</b> 10% to 90% <b>Storage:</b> 5% to 93%
Altitude	<b>Operating:</b> 0 feet to 10,000 feet (0 meters to 3,048 meters) <b>Storage:</b> 0 feet to 40,000 feet (0 meters to 12,192 meters)
Heat Dissipation	1741.13 BTU per hour maximum (estimated)
Temperature	<b>Operating:</b> 41° F to 95° F (5° C to 35° C) Derate the maximum temperature by 1°C for every 305 meters of altitude above sea level. <b>Storage:</b> -40° F to 149° F (-40° C to 65° C)

\* These numbers are generated in our test environments using average customer data. There are several factors that may affect your specific performance, such as number of hosts, average size of flows, and more. While we do our best to represent the data as fairly and accurately as possible, your environment may experience different limits.