



STEALTHWATCH® MANAGEMENT CONSOLE 1010

First Ship Date: 3/2015
Final Ship Date: Currently Shipping

The StealthWatch Management Console (SMC) 1010 has the following general configuration. Your model may look slightly different.

Front



Back



Management Port

Specifications

Hardware Platform	Hardware Generation
R630	13G
Rack Units (Mountable)	Weight
1U	41 pounds (18.6 kg)
Shipping Dimensions	Shipping Weight
Height: 11 inches (27.9 cm) Width: 24 inches (61 cm) Depth: 36 inches (91.4 cm)	65 pounds (29.5 kg)
Dimensions	Network
Height: 1.68 inches (4.3 cm) Width: 18.99 inches (48.24 cm) with rack latches 17.08 inches (43.4 cm) without rack latches Depth: 29.25 inches (74.3 cm) with power supply and bezel 27.25 inches (69.2 cm) without power supplies and bezel	Management Port: 1; 10/100/1000 copper
- continued -	

Humidity (Relative)	Altitude
Operating: 10% to 80% (non-condensing) with 78.8° F (26° C) maximum dew point Storage: 5% to 95% (non-condensing) with 91° F (33° C) maximum dew point	Operating: -50 feet to 10,000 feet (-15.2 meters to 3,048 meters) Storage: -50 feet to 35,000 feet (-15.2 meters to 10,668 meters)
Power	Heat Dissipation
Redundant 750 W AC, 50/60 Hz Auto Ranging (100V to 240V)	2,891 BTU per hour maximum
Storage	Temperature
1 TB (RAID-6 Redundant)	Operating: 50° F to 95° F (10° C to 35° C) at 10% to 80% relative humidity, with 78.8° F (26° C) maximum dew point Note: For altitudes above 2,952 feet, the maximum allowable dry bulb temperature is derated at 1° F (-17° C) per 550 feet (1.67 m). Storage: -40° F to 149° F (-40° C to 65° C) with a maximum temperature gradation of 68°F (20°C) per hour
Vibration	Shock
Operating Maximum: 0.26 Grms at 5-350 Hz in all orientations Storage Maximum: 1.87 Grms at 10-500 Hz for 15 minutes (all six sides tested)	Operating Maximum: One shock pulse in the positive z-axis of 31 G for 2.6 ms in all operation orientations Storage Maximum: Six consecutively executed shock pulse in the positive and negative x, y, and z axes (one pulse on each side of the system of 71 G for up to 2 minutes.
Rails	Regulatory
Sliding Ready Rails	FCC (U.S. only) Class A VCCI Class A DOC (Canada) Class A UL 1950 CE Mark (EN 55022 Class A, EN 55024, EN 61000-3-2, EN 61000-3-3, EN 60950) Please call for a complete list.




Americas Headquarters
 Cisco Systems, Inc.
 San Jose, CA

Asia Pacific Headquarters
 Cisco Systems (USA) Pte. Ltd.
 Singapore

Europe Headquarters
 Cisco Systems International BV Amsterdam,
 The Netherlands

Cisco has more than 200 offices worldwide. Addresses, phone numbers, and fax numbers are listed on the Cisco Website at www.cisco.com/go/offices.

 Cisco and the Cisco logo are trademarks or registered trademarks of Cisco and/or its affiliates in the U.S. and other countries. To view a list of Cisco trademarks, go to this URL: www.cisco.com/go/trademarks. Third party trademarks mentioned are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (1110R)