

Stealthwatch Management Console 2200

First Ship Date: 5/2017

Final Ship Date: Currently Shipping

The Stealthwatch Management Console (SMC) 2200 has the following general configuration. Your model may look slightly different.

Front View



Back View



1. Reserved ports
2. CIMC management port
3. Stealthwatch management port

Specifications

UCS Platform	UCSC-C220-M4S
Network/NIC	Reserved ports: 2; fiber - 10 GB SFP+ CIMC management port: 1; 100/1000 copper Stealthwatch management port: 1; 100/1000 copper
Processor	2.40 GHz E5-2680 v4
Memory	32G DDR4 (16x) - 512GB total
Data Storage	4 TB, RAID6, Redundant
Addressable Storage	7.2 TB
RAID Cache	4 GB

Rack Units	1U
Weight	37.9 pounds (17.2 kg)
Dimensions	Height: 1.7 inches (4.3 cm) Width: 16.9 inches (42.9 cm) Depth: 29.8 inches (75.8 cm)
Power	Redundant 770W AC 50/60 Auto Ranging (100v to 240V)
Humidity (Relative)	Operating: 10% to 90% Storage: 5% to 93%
Altitude	Operating: 0 feet to 10,000 feet (0 meters to 3,048 meters) Storage: 0 feet to 40,000 feet (0 meters to 12,192 meters)
Heat Dissipation	1741.13 BTU per hour maximum (estimated)
Temperature	Operating: 41° F to 95° F (5° C to 35° C) Derate the maximum temperature by 1°C for every 305 meters of altitude above sea level. Storage: -40° F to 149° F (-40° C to 65° C)