

Cisco HyperFlex Express for HX240c M6, HX240c M6 All Flash, and HX240c M6 All NVMe Nodes

Fast path to hybrid cloud: high-capacity clusters
for storage-intensive applications

April 2022

Contents

Simplicity you can build on	3
Cisco HyperFlex Express HX240c M6 Node family	4
Hybrid configurations	5
Features and benefits	5
Product specifications	7
Ordering information	9
Cisco Unified Computing Services	9
Cisco environmental sustainability	10
Cisco Capital	10
How to buy	10
For more information	10
Document history	11

Today's applications live across a complex, multidomain world—from enterprise data centers and private and public clouds, to campus, branch, and edge locations. Cisco HyperFlex™ systems with Intel® Xeon® Scalable processors make it easy to modernize and simplify deployments and operations. Engineered with Cisco Unified Computing System™ (Cisco UCS®) technology, and managed through the Cisco Intersight™ cloud-operations platform, Cisco HyperFlex systems deliver flexible scale-out infrastructure that can rapidly adapt to changing business demands.

We have created Cisco HyperFlex Express to simplify the onboarding process, especially for new customers, to get products on site quickly. Cisco HyperFlex Express delivers “high-velocity transactions” with simplified ordering and fast delivery. With HyperFlex Express, we have taken our most popular Cisco HyperFlex node configurations, added a few simple and important options, priced them attractively to deliver optimal value, and reduced transaction times to help keep your plans on track.

Simplicity you can build on

With hybrid Small-Form-Factor (SFF) and Large-Form-Factor (LFF), or all-flash-memory storage configurations and cloud-based management, Cisco HyperFlex Express HX240c M6 systems are deployed as a preintegrated cluster with a unified pool of resources that you can quickly provision, adapt, scale, and manage to efficiently power your applications and your business (Figure 1). Based on Intel Xeon Scalable processors, these servers have faster processors, more cores, and faster and larger-capacity memory than previous-generation servers. In addition, they are ready for Intel Optane™ persistent memory (PMem) which can be used as both storage and system memory, increasing your virtual server configuration options and flexibility for applications.




Figure 1.
Cisco HyperFlex systems product family

Cisco HyperFlex Express HX240c M6 Node family

The Cisco HyperFlex Express HX240c M6 Node family delivers high disk capacity (up to 28 drives) in a 2-socket, 2RU package ideal for storage-intensive applications. Physically, the system is delivered as a cluster of three or more Cisco HyperFlex Express HX240c M6 Nodes, HX240c M6 All NVMe Nodes, HX240c M6 All Flash Nodes, or HX240c M6 LFF Nodes. The nodes are integrated into a single system by a pair of Cisco UCS 6300 or 6400 series fabric interconnects, creating clusters that deliver the performance and storage capacity needed by workloads. All nodes use Intel Xeon Scalable processors and next-generation DDR4 memory and offer 12-Gbps SAS throughput.

Hybrid configurations

The HX240c M6 Node family can be deployed with various Cisco UCS B-series blade servers and C-series rack servers to create a hybrid cluster. Incorporating Intel Xeon Scalable processors, these Cisco HyperFlex HX-series nodes offer an improved price-to-performance ratio that ranks them among the best values in the industry. Cloud-based management makes it easy for you to scale your cluster to support more workloads and deliver the performance, bandwidth, and low latency that your users and applications need.

Features and benefits

Table 1. Summary of features and benefits of Cisco HyperFlex HX240c M6, HX240c M6 All Flash, and HX240c M6 All NVMe Nodes.

Feature	Benefit		
Memory	<ul style="list-style-type: none"> • High memory capacity • Up to 8 TB memory (32 x 256 GB DDR4 DIMMs¹) or • Up to 12 TB memory (16 x 256 GB DDR4 DIMMs) and 16 x 512 GB Intel Optane persistent memory modules (PMem) 		
Intel Xeon Scalable processors	<ul style="list-style-type: none"> • High performance • 10-nanometer (nm) processor technology • Massive processing power • Top-of-the-line memory-channel performance • Improved scalability and intercore data flow • Intel Automated Vector Extensions 2 (AVX2) 	<ul style="list-style-type: none"> • Agility • Supports highly dense virtual machine deployments • Offers flexible virtualization technology that optimizes performance for virtualized environments, including processor support for migration and direct I/O 	<ul style="list-style-type: none"> • Efficiency and security • Low-power, high-speed DDR4 memory technology • Automated energy efficiency reduces energy costs by automatically putting the processor and memory in the lowest available power state while delivering the performance required • Hardware-assisted security advancements
Unified network fabric	<ul style="list-style-type: none"> • Low-latency, lossless, 2 x 100 Gigabit Ethernet connections • Wire-once deployment model, eliminating the need to install adapters and re-cable racks and switches when changing I/O configurations • Fewer interface cards, cables, and upstream network ports to purchase, power, configure, and maintain 		
Expansion	<ul style="list-style-type: none"> • Support for up to 8 PCIe slots • Flexibility, increased performance, and compatibility with industry standards • High I/O bandwidth, increased flexibility, and backward compatibility with support for PCIe 2.0 		
Virtualization optimization	<ul style="list-style-type: none"> • I/O virtualization and Intel Xeon Scalable processor features, extending the network directly to virtual machines • Consistent and scalable operational model • Increased security and efficiency with reduced complexity • Capability to move virtual machine security features and policies from rack to rack or rack to blade 		

Feature	Benefit	
Cloud-based management	<p>Cisco Intersight simplifies operations across on-premises data centers, edge sites, and public clouds.</p> <ul style="list-style-type: none"> • Use a software-as-a-service platform that bridges applications with infrastructure • Gain instant access to clusters regardless of where they are deployed • Correlate visibility and management across bare-metal servers, hypervisors, Kubernetes, and serverless and application components • Transform operations with artificial intelligence to reach needed scale and velocity • Collaborate and work smarter and faster by automating lifecycle workflows • Support compliance and governance with extensible, open capabilities that natively integrate with third-party platforms and tools • Proactively respond to impending issues with a recommendation engine that determines when capacity needs to be scaled 	<p>Additional management capabilities include:</p> <ul style="list-style-type: none"> • Support for the VMware vSphere plug-in • Support for the Cisco HyperFlex Connect interface with an HTML 5 presentation layer accessible on desktop and laptop computers and mobile devices
Storage	<ul style="list-style-type: none"> • Support for all-flash, hybrid (HDD and SSD memory), or all-NVMe configurations • Deliver high-capacity configurations for the Cisco HyperFlex HX Data Platform capacity layer 	
Enterprise data protection	<ul style="list-style-type: none"> • Pointer-based snapshot capabilities • Native snapshots for iSCSI LUNs, including a consistency group for snapshot operations, instantaneous snapshot creation, and RESTful APIs for snapshot creation and third-party backup use • Snapshot integration with MEDITECH BridgeHead for electronic health records and databases • Near-instant cloning • Inline deduplication and compression • Native replication for disaster recovery • N:1 replication for data-center clusters with fabric interconnects and more than 4 nodes, as well as a flexible retention policy for local and remote point-in-time copies • Data-at-rest encryption using self-encrypting drives and enterprise key management integration 	
Security	<ul style="list-style-type: none"> • Locking bezel option to protect against unauthorized access to disk drives • Trusted Platform Module (TPM), a chip (microcontroller) that can securely store artifacts, including passwords, certificates, and encryption keys, which are used to authenticate the platform (node) • Supports TPM 2.0 	
Software	<ul style="list-style-type: none"> • Cisco HyperFlex HX Data Platform Software (software subscription, data-center license) • VMware vSphere 6.7 or 7 software preinstalled 	

Product specifications

Table 2. Common specifications for Cisco HyperFlex Express HX240c M6, HX240c M6 All Flash, and HX240c M6 All NVMe Nodes

Feature	Common specifications across the HX240c M6 Node family	
Chassis	<ul style="list-style-type: none"> • 2RU of rack space per node 	
Processors	<ul style="list-style-type: none"> • One or two 3rd Gen Intel Xeon Scalable processors (Ice Lake) • A 2-CPU configuration is required when using NVMe caching drives or All NVMe systems 	
Interconnect	<ul style="list-style-type: none"> • 3 Intel UPI channels per processor, each capable of 11.2 gigatransfers per second (GTPS) 	
Chip set	<ul style="list-style-type: none"> • Intel C621A series 	
Memory	<ul style="list-style-type: none"> • Capability to use 16-, 32-, 64-, 128-, or 256-GB DIMMs • 16 slots for RDIMMs, LRDIMMs per node • Advanced Error-Correcting Code (ECC) • Independent channel mode • Lockstep channel mode 	
Storage	<ul style="list-style-type: none"> • All-flash-memory, all-NVMe, or hybrid storage configurations (combination of Hard-Disk Drives [HDDs], and solid-state-disks [SSDs]) • Cisco 12-Gbps Modular SAS Host Bus Adapter (HBA) with internal SAS connectivity M.2 SATA SSD drive for boot 	
PCIe	<ul style="list-style-type: none"> • Up to 8 PCIe slots 	
Expansion slots	<ul style="list-style-type: none"> • Up to 6 full-height, full-length slots • 2 slots capable of Graphics Processing Unit (GPU) support for enhanced Virtual Desktop Infrastructure (VDI) capabilities 	<ul style="list-style-type: none"> • 3 full-height, full-length slots • 3 full-height, 3/4-length slots
Modular LAN on Motherboard (mLOM) slot	<ul style="list-style-type: none"> • Up to 256 I/O devices programmable on demand for hypervisor and virtual machine support 	
Network	<ul style="list-style-type: none"> • Dual 10-, 25- or 100-Gbps Ethernet ports per node 	
Cisco Integrated Management Controller (IMC)	<ul style="list-style-type: none"> • Integrated Baseboard Management Controller (BMC) • IPMI 2.0 compliant for management and control • 1 x 10/100/1000 Ethernet out-of-band management interface • Command-Line Interface (CLI) and web GUI management tool for automated, lights-out management • Keyboard, Video, and Mouse (KVM) console 	
Advanced reliability, availability, and serviceability (RAS) features	<ul style="list-style-type: none"> • Highly available and self-healing architecture • Robust reporting and analytics • Hot-swappable, front-accessible drives • Dual-redundant fans and hot-swappable, redundant power supplies for enterprise-class reliability and a convenient latching lid for easy access to internal server • Tool-free CPU insertion, enabling processor upgrades and replacements with less risk of damage • Tool-free access to all serviceable items, and color-coded indicators to guide users to hot-pluggable and serviceable items • Nondisruptive rolling upgrades • Cisco Smart Call Home and onsite 24-hours-a-day, 7-days-a-week (24 x 7) support options 	

Feature	Common specifications across the HX240c M6 Node family
Front-panel connector	<ul style="list-style-type: none"> • 1 KVM console connector per node (supplies 2 USB connectors, 1 VGA connector, and 1 serial connector)
Front-panel locator LED	<ul style="list-style-type: none"> • Helps direct administrators to specific servers in large data center environments
Additional rear connectors	<ul style="list-style-type: none"> • 1 Gigabit Ethernet management port • 2 x 10 Gigabit Ethernet ports • 1 RS-232 serial port (RJ45 connector) • 1 Video Graphics Array (VGA) video port (DB15 connector) • 2 USB 3.0 ports
Power and cooling	<ul style="list-style-type: none"> • One or two hot-pluggable power supplies • Second power supply provides 1+1 redundancy • 1050W, 1600W, or 2300W • 6 hot-swappable fans
Rail-kit options	<ul style="list-style-type: none"> • Cisco ball-bearing rail kit with optional reversible cable-management arm • Cisco friction rail kit with optional reversible cable-management arm
Software	<ul style="list-style-type: none"> • Cisco HyperFlex HX Data Platform Software (software subscription, Data Center license)

Table 3. Individual model specifications for Cisco HyperFlex Express HX240c M6, HX240c M6 All Flash, and HX240c M6 All NVMe Nodes

Feature	Storage
HX240c M6 All NVMe	<ul style="list-style-type: none"> • 3.8-TB or 7.6-TB NVMe (data) • 375G Intel Optane (cache)
HX240c M6 All Flash	<ul style="list-style-type: none"> • 3.8-TB or 7.6-TB SATA (data) • 1.6-TB NVMe (cache)
HX240c M6 Hybrid (SFF)	<ul style="list-style-type: none"> • 2.4-TB 10K rpm HDD (data) • 1.6-TB SAS HDD (cache)

Ordering information

Table 4. Predefined options for Cisco HyperFlex Express ordering

Drive type	HX240c M6 Hybrid	HX240c All-Flash	HX240c All NVMe
Server	<ul style="list-style-type: none"> • HX240C-M6SX 	<ul style="list-style-type: none"> • HXAF240C-M6SX 	<ul style="list-style-type: none"> • HXAF240C-M6SN
CPU options	<ul style="list-style-type: none"> • HX-CPU-I6348 • HX-CPU-I5320 • HX-CPU-I4314 	<ul style="list-style-type: none"> • HX-CPU-I6348 • HX-CPU-I5320 • HX-CPU-I4314 	<ul style="list-style-type: none"> • HX-CPU-I6348 • HX-CPU-I5320 • HX-CPU-I4314
Memory	<ul style="list-style-type: none"> • HX-MR-X64G2RW 	<ul style="list-style-type: none"> • HX-MR-X64G2RW 	<ul style="list-style-type: none"> • HX-MR-X64G2RW
Drives			
Housekeeping	<ul style="list-style-type: none"> • HX-SD240GM1X-EV 	<ul style="list-style-type: none"> • HX-SD240GM1X-EV 	<ul style="list-style-type: none"> • HX-NVME2H-I1000
Boot	<ul style="list-style-type: none"> • HX-M2-240GB 	<ul style="list-style-type: none"> • HX-M2-240GB 	<ul style="list-style-type: none"> • HX-M2-240GB
Cache	<ul style="list-style-type: none"> • HX-SD16TK3X-EP 	<ul style="list-style-type: none"> • HX-NVMEM6-W1600 	<ul style="list-style-type: none"> • HX-NVMEXPB-I375
Data options	<ul style="list-style-type: none"> • HX-HD24TB10K4KN 	<ul style="list-style-type: none"> • HX-SD38T61X-EV • HX-SD76T61X-EV 	<ul style="list-style-type: none"> • HX-NVMEI4-I3840 • HX-NVMEI4-I7680
MLOM/VIC	<ul style="list-style-type: none"> • HX-M-V25-04 	<ul style="list-style-type: none"> • HX-M-V25-04 	<ul style="list-style-type: none"> • HX-M-V25-04

For a complete list of part numbers, refer to specification sheet.

Cisco Unified Computing Services

Cisco and our industry-leading partners deliver services that accelerate your transition to Cisco HyperFlex systems. Cisco Unified Computing Services can help you create an agile infrastructure, accelerate time-to-value, reduce costs and risks, and maintain availability during deployment and migration. After you have deployed your system, our services can help you improve performance, availability, and resiliency as your business needs evolve and help you further mitigate risk.

Cisco environmental sustainability

Information about Cisco's environmental sustainability policies and initiatives for our products, solutions, operations, and extended operations or supply chain is provided in the "Environment Sustainability" section of Cisco's [Corporate Social Responsibility](#) (CSR) Report.

Reference links to information about key environmental sustainability topics (mentioned in the "Environment Sustainability" section of the CSR Report) are provided in the following table:

Sustainability topic	Reference
Information on product material content laws and regulations	Materials
Information on electronic waste laws and regulations, including products, batteries, and packaging	WEEE compliance

Cisco makes the packaging data available for informational purposes only. It may not reflect the most current legal developments, and Cisco does not represent, warrant, or guarantee that it is complete, accurate, or up to date. This information is subject to change without notice.

Cisco Capital

Flexible payment solutions to help you achieve your objectives

Cisco Capital makes it easier to get the right technology to achieve your objectives, enable business transformation and help you stay competitive. We can help you reduce the total cost of ownership, conserve capital, and accelerate growth. In more than 100 countries, our flexible payment solutions can help you acquire hardware, software, services and complementary third-party equipment in easy, predictable payments. [Learn more](#).

How to buy

To view buying options and speak with a Cisco sales representative, go to <https://www.cisco.com/c/en/us/buy.html>

For more information

For more information about Cisco HyperFlex systems, refer to <https://www.cisco.com/site/us/en/products/computing/hyperconverged-infrastructure/index.html>.

Document history

New or revised topic	Described in	Date
Initial release	Spec sheet	March 2022

Americas Headquarters
Cisco Systems, Inc.
San Jose, CA

Asia Pacific Headquarters
Cisco Systems (USA) Pte. Ltd.
Singapore

Europe Headquarters
Cisco Systems International BV Amsterdam,
The Netherlands

Cisco has more than 200 offices worldwide. Addresses, phone numbers, and fax numbers are listed on the Cisco Website at <https://www.cisco.com/go/offices>.

Cisco and the Cisco logo are trademarks or registered trademarks of Cisco and/or its affiliates in the U.S. and other countries. To view a list of Cisco trademarks, go to this URL: <https://www.cisco.com/go/trademarks>. Third-party trademarks mentioned are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (1110R)