

Cisco Catalyst IE3200 Rugged Series

Contents

Product overview	3
Features and benefits	4
Products overview	4
Product specifications	5
Ordering information	15
Warranty	15
Cisco environmental sustainability	16
Cisco Services	16
Cisco Capital	16
Document history	17

Features and benefits

Table 1. Features and benefits

Feature	Benefit
Robust industrial design	<ul style="list-style-type: none"> • Built for harsh environments and temperature ranges (-40°C to +75°C) • Fanless, convection-cooled with no moving parts for extended durability • Hardened for vibration, shock and surge, and electrical noise immunity • Complies with multi-industry specifications for automation, ITS, and substation environments • Improves uptime, performance, and safety of industrial systems and equipment • Covers a wide range of Power over Ethernet (PoE) application requirements • Alarm I/O for monitoring and signaling to external equipment
Full Gigabit Ethernet interfaces	<ul style="list-style-type: none"> • Provides secure access for new high-speed applications in the industrial space • Packs up to 10 ports of GE - 2x1 Gigabit Small Form-Factor Pluggable (SFP) uplinks, plus 8x1 Gigabit copper RJ45 downlink ports (with PoE+ or non PoE) in a small form-factor base system • Connects high-speed wireless access points (802.11n, 802.11ac, 802.11ax) • Enables High-Definition (HD) IP cameras and Programmable Logic Controllers (PLC) • Delivers multiple rings and redundant ring topologies for new network configurations • Extends geographical scalability where longer-distance connectivity is required
High-density industrial Power over Ethernet (PoE)	<ul style="list-style-type: none"> • Supports up to 8 PoE/PoE+ ports [Power budget - 240W] • Controls costs by limiting wiring, distribution panels, and circuit breakers • Reduces equipment needs, thus requiring less space and reducing heat dissipation • Enables ready-to-use PoE devices, such as IP phones, cameras, and wireless access points
User-friendly GUI, called WebUI	<ul style="list-style-type: none"> • Allows easy configuration and monitoring • Eliminates the need for more complex terminal emulation programs • Reduces the cost of deployment
SwapDrive, a zero-configuration replacement	<ul style="list-style-type: none"> • True zero-configuration and simple switch replacement in the event of a failure • No networking expertise required • Helps ensure fast recovery
IPv6 Ready Logo	<ul style="list-style-type: none"> • IPv6 Ready Logo Certified

Products overview

Table 2. Product feature sets

Product family	Platforms supported	Cisco IOS Software image (feature sets) supported
IE3000	IE3200	Network Essentials (default)

Product specifications

Table 3 highlights the hardware configuration for Cisco Catalyst IE3200 Rugged Series switches.

Table 3. IE3200 Hardware configurations

Product number*	Total ports	10/100/1000 RJ45 Copper ports	100/1000 SFP ports	Software license (Default)	PoE/PoE(+) budget
IE-3200-8T2S-E	10	8	2	Network Essentials	N.A.
IE-3200-8P2S-E	10	8	2	Network Essentials	240W

Table 4 highlights the hardware specifications for Cisco Catalyst IE3200 Rugged Series switches.

Table 4. IE3200 Hardware specifications

Hardware specification	Cisco IE-3200-8T2S-E	Cisco IE-3200-8P2S-E
PoE power budget	Not applicable	240W ¹
Removable storage	USB ^{2,3} , SD card ²	USB ^{2,3} , SD card ²
Alarms	2 alarms in, 1 alarm out	2 alarms in, 1 alarm out
Console ports	1 RS-232 (via RJ-45), 1 USB Mini Type B	1 RS-232 (via RJ-45), 1 USB Mini Type B
Power inputs	Dual DC power inputs	Dual DC power inputs

¹In order to achieve the 240W power budget, the minimum power requirements as specified in Table 7 for the switch need to be considered when selecting a power supply.

²The USB and SD card are optional and are not shipped by default with the switch.

³USB 2.0 to load system images and set configurations

Table 5 highlights the physical configuration for Cisco Catalyst IE3200 Rugged Series switches.

Table 5. IE3200 physical configurations

Physical specifications	Cisco IE-3200-8T2S-E	Cisco IE-3200-8P2S-E
Dimensions (H x W x D)	6 in. X 3.6 in. X 5.3 in. 15.2 cm. x 9.1 cm. x 13.5 cm	6.0 in. X 3.6 in. X 5.3 in. 15.2 cm. x 9.1 cm. x 13.5 cm
Weight	3.8 lbs 1.7 kg	3.8 lbs 1.7 kg
Mounting	DIN rail	DIN rail




Figure 2.
Cisco Catalyst IE3200 dimensions

Table 6 highlights the performance and scalability features for Cisco Catalyst IE3200 Rugged Series switches.

Table 6. IE3200 performance and scalability features

Features	Cisco IE-3200-8T2S-E	Cisco IE-3200-8P2S-E
Forwarding rate	Line rate for all ports and all packet sizes	Line rate for all ports and all packet sizes
Number of queues	8	8
Unicast MAC addresses	8K	16K
Internet Group Management Protocol (IGMP) multicast groups	1K	1K
No. of VLANs	256	256
Spanning Tree Protocol (STP) instances	128	128
Access Control Entries (PACL/VACL/RACL)	3K	3K
DRAM	2 GB	2 GB
Flash (User Accessible)	1.5 GB	1.5 GB
SD card capacity¹	4 GB	4 GB
Jumbo Frames	8996 bytes	8996 bytes

¹The SD card is optional and is not shipped by default with the switch.

Table 7 highlights the power specifications for Cisco Catalyst IE3200 Rugged Series switches.

Table 7. IE3200 power specifications

Features	Cisco IE-3200-8T2S-E	Cisco IE-3200-8P2S-E
Input voltage range	Redundant DC input voltage: 9.6 to 60VDC	Redundant DC input voltage: 9.6 to 60VDC 48VDC is required for PoE and 54VDC is required for PoE+
Maximum Input current	2.4A	5.5A
Power consumption¹	23W	32W

¹Power consumption for non PoE supported model is measured at 12V and for the PoE supported model is measured at 54V. Power consumption does not include PoE power.

Table 8 highlights the power supply options for Cisco Catalyst IE3200 Rugged Series switches.

Table 8. Power supply options

Product Number	Wattage	Rated nominal input operating range	PoE/PoE+ support ¹	More Details
PWR-IE50W-AC=	50W	AC 100-240V/1.25A 50-60Hz or DC 125-250V/1.25A	No	Click here for more details on these DIN Rail power supplies
PWR-IE50W-AC-IEC=	50W	AC 90-264V	No	
PWR-IE50W-AC-L= ²	50W	AC 100-240V/1.2A 50-60Hz	No	
PWR-IE65W-PC-AC=	65W	AC 100-240V/1.4A 50-60Hz or DC 125-250V/1.0A	Yes	
PWR-IE65W-PC-DC=	65W	DC 24-48VDC/4.5A	Yes	
PWR-IE170W-PC-AC=	170W	AC 100-240V/2.3A 50-60Hz or DC 125-250V/2.1A	Yes	
PWR-IE170W-PC-DC=	170W	DC 12-54VDC/23A	Yes	
PWR-IE240W-PCAC-L= ²	240W	AC 100-240V/3.5A 50-60Hz	Yes	
PWR-IE480W-PCAC-L= ²	480W	AC 100-240V/6.0A 50-60Hz	Yes	

¹The entire power budget for the switch and PoE ports needs to stay within the power supply wattage.

²The power supplies are not certified for smart grid and hazardous locations. These power supplies are IP20 rated.

Table 9 highlights the supported software features for Cisco Catalyst IE3200 Rugged Series switches.

Table 9. Key supported software features

Network Essentials License (Perpetual)	Features
Layer 2 switching	IEEE 802.1, 802.3 standard, NTP, UDLD, CDP, LLDP, unicast MAC filter, PAgP, LACP, VTPv2, VTPv3, EtherChannel, Q-in-Q tunneling, voice VLAN, PVST+, MSTP, and RSTP
Multicast	IGMPv1, v2, v3 snooping, IGMP filtering, IGMP querier
Management	WebUI, MIB, SmartPort, SNMP, syslog, DHCP server, SPAN session, RSPAN, FSPAN, Express setup, NETCONF, RESTCONF
Security	Port security, 802.1x, Dynamic Host Configuration Protocol (DHCP) snooping, dynamic ARP inspection, IP source guard, guest VLAN, MAC authentication bypass, 802.1x multidomain authentication, storm control - unicast, multicast, broadcast, SCP, SSH, SNMPv3, TACACS+, RADIUS server/client, MAC address notification, BPDU guard, SUDI 2099 (Secure Unique Device identifier), Access Lists (ACL/RACL/VACL), MACsec-128, FIPS 140-2
Quality of Service (QoS)	Ingress policing, rate limit, egress queuing and shaping, auto QoS
IPv6	IPv6 host support, SNMP over IPv6, HTTP/HTTP(s) over IPv6, Syslog over IPv6, DHCPv6 relay source, DHCPv6 bulk lease query (RFC 5460), IPv6 stateless Auto Config, SCP/SSH, Radius, TACACS+, NTP over IPv6, IPV6 ND cache expire, IPv6 support for TFTP, IPv6 DNS transport, IPv6 QoS, IPv6 FHS RA Guard, IPv6 FHS DHCPv6 Guard
Layer 3 routing	Inter-VLAN routing, static routing
Industrial Ethernet	CIP Ethernet/IP, IEEE 1588 PTP v2 (default and power), PROFINET
Redundancy	Resilient Ethernet Protocol (REP) ring, PROFINET-Media Redundancy Protocol (MRP), REP Preferred, Fast REP
Utility	Dying gasp, SCADA protocol classification - GOOSE messaging, MODBUS TCP/IP
Automation	YANG, NETCONF, RESTCONF

Table 10 highlights the details on Cisco Catalyst Center Essentials License for Cisco Catalyst IE3200 Rugged Series switches.

Table 10. Cisco IE3200 Cisco Catalyst Center Essentials License

Feature	Description
Element Management	Discovery, topology, inventory, software image management
Assurance	Health Dashboards - Network, Client, Basic Switch and Wired Client Health Monitoring
Automation	Cisco Network Plug-and-Play application
Software Defined Access	SD-Access Extended Node, REP Ring workflow for Extended Nodes

Cisco Catalyst Center licenses for Industrial Ethernet switches are add-on/optional and not mandatory, and need to be purchased separately. These do not include Network Tier features.

Table 11 highlights the compliance specifications for Cisco Catalyst IE3200 Rugged Series switches.

Table 11. Compliance specifications¹

Descriptions	Specifications
Industrial Automation Control System	IEC 62443-4-1 IEC 62443-4-2
Electromagnetic emissions	FCC 47 CFR Part 15 subpart B Class A EN 55032/CISPR 32 Class A VCCI Class A AS/NZS CISPR 32 Class A CISPR 11 Class A ICES 003 Class A CNS 13438 Class A KN 32 Class A EN 300 386
Electromagnetic immunity	CISPR 24 EN 55024 KN 35 EN 61000-4-2 Electro Static Discharge (air - 15kV, contact - 8kV) EN 61000-4-3 Radiated RF (10V/m UTP, 20V/m STP) EN 61000-4-4 Electromagnetic Fast Transients (4kV) EN 61000-4-5 Surge (2KV/1KV Power, 4KV STP) EN 61000-4-6 Conducted RF (10Vrms UTP) EN 61000-4-10 Damped Oscillatory Magnetic Field (100 A/m) EN 61000-4-16 Conducted CM Disturbances (30V, Cont/300V, 1 sec) EN 61000-4-17 Ripple Immunity DC Power (10%) EN 61000-4-18 Damped Oscillatory Wave (2.5kV, 1MHz) EN-61000-4-29 DC Voltage Dips and interruptions EN 61000-4-8 Power Frequency Magnetic Field (1000A/m)
Industry standards	EN 61000-6-2 Industrial Immunity EN 61000-6-4 Industrial Emissions EN 61000-6-1 Light Industrial Immunity EN 61326-1 Measurement, Control and Laboratory Equipment IEEE 1613 Electric Power Stations Communications Networking EN/IEC 61850-3 Electric Substations Communications Networking ODVA Industrial EtherNet/IP

Descriptions	Specifications
	NEMA TS 2-2016 AREMA C & S section 11, 19 IP30
Marine I	DNC Certification according to class guideline DNV-CG-0339 Additional Standards: IEC 60945, IACS UR E10 Marine DNV GL - Ships; High speed and light craft
Safety standards and certifications	Information technology equipment: UL/CSA 60950-1, IEC 60950-1 CB with all country deviations UL/CSA 62368-1, IEC 62368-1 CB with all country deviations Industrial floor (control equipment): UL/CSA 61010-2-201 CB report and certificate to IEC/EN 61010-2-201 Hazardous locations: UL121201 (Class I, Div 2, groups A-D) CSA 213 (Class I, Div 2, groups A-D) UL/CSA 60079-0, -15 (Class I, Zone 2, Gc/IIC) IEC 60079-0, -15 IECEx test report (Class I, Zone 2, Gc/IIC) EN 60079-0, -15 ATEX certificate (Class I, Zone 2, Gc/IIC) Cabinet enclosure required
Operating environment	Operating temperature: -40°C to +70°C (40 LFM vented enclosure) -40°C to +60°C (sealed enclosure) -40°C to +75°C (Min. 200 LFM fan or blower-equipped enclosure) +85°C (type tested for 16 hours) Altitude: Up to 15,000 feet
Storage environment	Temperature: -40°C to +85°C Altitude: 15,000 feet IEC 60068-2-14
Humidity	Relative humidity of 5% to 95% non-condensing IEC 60068-2-78 IEC 60068-2-30
Shock and vibration	IEC 60068-2-27 (operational shock, 50G, 3ms, half sine) IEC 60068-2-27 (non-operational shock, 65-80G, 9ms, trapezoidal) MIL-STD-810, Method 514.4 IEC 60068-2-6 (vibration-sinusoidal, 5Hz-150Hz)

Descriptions	Specifications
Corrosion	IEC 60068-2-52 (salt fog) IEC 60068-2-60 (flowing mixed gas)
Railway	EN50125-1: 2014 EN50125-3: 2003 EN50121-4 Railway – Signaling and Telecommunications Apparatus EN50155- Railway applications – Rolling stock
Warranty	Five-year limited hardware warranty on all IE3200 product IDs and all Industrial Ethernet (IE) power supplies. See more information under the Warranty section

¹For more detailed information on safety approved power/thermal ratings refer the Hardware Installation Guide.

Table 12 highlights Mean-Time-Between-Failures (MTBF) for Cisco Catalyst IE3200 Rugged Series switches.

Table 12. MTBF information

Parameter	Cisco IE-3200-8T2S-E	Cisco IE-3200-8P2S-E
Rated MTBF (hours)	641,150	613,125

Table 13 highlights information about management and standards for Cisco Catalyst IE3200 Rugged Series switches.

Table 13. Management and standards

Descriptions	Specifications	
IEEE standards	IEEE 802.1D MAC Bridges, STP IEEE 802.1p Layer2 COS prioritization IEEE 802.1q VLAN IEEE 802.1s Multiple Spanning-Trees IEEE 802.1w Rapid Spanning-Tree IEEE 802.1x Port Access Authentication IEEE 802.1AB LLDP IEEE 1588v2 PTP Precision Time Protocol	IEEE 802.3ad Link Aggregation (LACP) IEEE 802.3ah 100BASE-X SMF/MMF only IEEE 802.3x full duplex on 10BASE-T IEEE 802.3 10BASE-T specification IEEE 802.3u 100BASE-TX specification IEEE 802.3ab 1000BASE-T specification IEEE 802.3z 1000BASE-X specification IEEE 802.3af Power over Ethernet IEEE 802.3at Power over Ethernet plus
RFC compliance	RFC 768: UDP RFC 783: TFTP RFC 791: IPv4 protocol RFC 792: ICMP RFC 793: TCP RFC 826: ARP RFC 854: Telnet	RFC 1492: TACACS+ RFC 1493: Bridge MIB Objects RFC 1534: DHCP and BOOTP interoperation RFC 1542: Bootstrap Protocol RFC 1643: Ethernet Interface MIB RFC 1757: RMON RFC 2068: HTTP

Descriptions	Specifications	
	RFC 959: FTP RFC 1157: SNMPv1 RFC 1901,1902-1907 SNMPv2 RFC 2273-2275: SNMPv3 RFC 2571: SNMP Management RFC 1166: IP Addresses RFC 1256: ICMP Router Discovery RFC 1305: NTP RFC 951: BootP	RFC 2131, 2132: DHCP RFC 2236: IGMP v2 RFC 3376: IGMP v3 RFC 2474: DiffServ Precedence RFC 3046: DHCP Relay Agent Information Option RFC 3580: 802.1x RADIUS RFC 4250-4252 SSH Protocol RFC 5460: DHCPv6 bulk lease query
SNMP MIB objects	802.1X MIB CISCO-DHCP-SNOOPING-MIB CISCO-UDLD-MIB CISCO-ENVMON-MIB CISCO-PRIVATE-VLAN-MIB CISCO-PAE-MIB Cisco-Port-QoS-MIB CISCO-ERR-DISABLE-MIB CISCO- PROCESS-MIB LLDP-MIB CiscoMAC Notification-MIB CISCO-CONFIG-COPY-MIB LLDP-MED-MIB Bridge-MIB CISCO-CAR-MIB CISCO-LAG-MIB CISCO-SYSLOG-MIB CISCO-FTP-CLIENT-MIB CISCO-VLAN-IFTABLE-RELATIONSHIP-MIB CISCO-VLAN-MEMBERSHIP-MIB Cisco-REP-MIB CISCO-PORT-STORM-CONTROL-MIB CISCO-CDP-MIB CISCO-IP-STAT-MIB CISCO-LICENSE-MGMT-MIB CISCO-STP-EXTN-MIB CISCO-VTP-MIB IEEE8023-LAG-MIB	CISCO-IF-EXTENSION-MIB CISCO-IMAGE-MIB CISCO-MEMORY-POOL-MIB CISCO-PING-MIB SNMP-TARGET-EXT-MIB IF_MIB ENTITY-MIB LLDP-EXT-PNO-MIB NOTIFICATION-LOG-MIB OLD-CISCO-CPU-MIB ETHERLIKE-MIB OLD-CISCO-SYSTEM-MIB OLD-CISCO-MEMORY-MIB RMON-MIB SNMP-COMMUNITY-MIB SNMP-FRAMEWORK-MIB SNMP-PROXY-MIB SNMP-MPD-MIB SNMP-NOTIFICATION-MIB SNMP-TARGET-MIB SNMP-USM-MIB CISCO-DATACOLLECTION-MIB CISCO-CABLE-DIAG-MIB CISCO -PORT-SECURITY-MIB BULK_FILE_MIB NAC-NAD-MIB CISCO-ENTITY-ALARM-MIB SNMP-VIEW-BASED-ACM-MIB

Descriptions	Specifications	
	SMON-MIB	CISCO-MAC-AUTH-BYPASS-MIB
	CISCO-ACCESS-ENVMON-MIB	CISCO-AUTH-FRAMEWORK-MIB
	CISCO-CALLHOME-MIB	CISCO-BRIDGE-Ext-MIB
	CISCO-CONFIG-MAN-MIB	SNMPv2-MIB
	CISCO-FLASH-MIB	CISCO-ENTITY-VENDORTYPE-OID-MIB
	CISCO-ENTITY-SENSOR-MIB	CISCO-PRODUCTS-MIB
	IP-MIB	IP-FORWARD-MIB
	CISCO-PAGP-MIB	

Table 14 highlights information about supported SFPs for Cisco Catalyst IE3200 Rugged Series switches.

Table 14. SFP Support

Part Number	Specifications	SFP type	Temperature range ¹	Maximum distance	Cable type	Dom support
GLC-FE-100FX-RGD	100BASE-FX	FE	IND	2 km	Multimode Fiber (MMF)	No
GLC-FE-100LX-RGD	100BASE-LX10	FE	IND	10 km	Single-Mode Fiber (SMF)	No
GLC-FE-100FX	100BASE-FX	FE	COM	2 km	MMF	No
GLC-FE-100LX	100BASE-LX10	FE	COM	10 km	SMF	No
GLC-FE-100EX	100BASE-EX	FE	COM	40 km	SMF	No
GLC-FE-100ZX	100BASE-ZX	FE	COM	80 km	SMF	No
GLC-FE-100BX-U	100BASE-BX10	FE	COM	10 km	SMF	No
GLC-FE-100BX-D	100BASE-BX10	FE	COM	10 km	SMF	No
GLC-SX-MM-RGD	1000BASE-SX	GE	IND	220-550 m	MMF	Yes
GLC-LX-SM-RGD	1000BASE-LX/LH	GE	IND	550 m/10 km	MMF/SMF	Yes
GLC-ZX-SM-RGD	1000BASE-ZX	GE	IND	70 km	SMF	Yes
SFP-GE-S	1000BASE-SX	GE	EXT	220-550 m	MMF	Yes
SFP-GE-L	1000BASE-LX/LH	GE	EXT	550 m/10 km	MMF/SMF	Yes
SFP-GE-Z	1000BASE-ZX	GE	EXT	70 km	SMF	Yes
GLC-BX-U	1000BASE-BX10	GE	COM	10 km	SMF	Yes
GLC-BX-D	1000BASE-BX10	GE	COM	10 km	SMF	Yes
GLC-SX-MM	1000BASE-SX	GE	COM	220-550 m	MMF	Yes

Part Number	Specifications	SFP type	Temperature range ¹	Maximum distance	Cable type	Dom support
GLC-LH-SM	1000BASE-LX/LH	GE	COM	550 m/10 km	MMF/SMF	Yes
GLC-ZX-SM	1000BASE-ZX	GE	COM	70 km	SMF	Yes
GLC-EX-SMD	1000BASE-EX	GE	COM	40 km	SMF	Yes
GLC-TE	1000BASE-T	GE	EXT	100 m	Cat5e	No
GLC-BX40-U-I=	1000BASE-BX40	GE	IND	40km	SMF	Yes
GLC-BX40-D-I=	1000BASE-BX40	GE	IND	40km	SMF	Yes
GLC-BX40-DA-I=	1000BASE-BX40	GE	IND	40km	SMF	Yes
GLC-BX80-U-I=	1000BASE-BX80	GE	IND	80km	SMF	Yes
GLC-BX80-D-I=	1000BASE-BX80	GE	IND	80km	SMF	Yes
GLC-SX-MMD=	1000BASE-SX	GE	EXT	550m	MMF	Yes
GLC-LH-SMD=	1000BASE-LX/LH	GE	EXT	550m/10km	MMF/SMF	Yes
GLC-ZX-SMD=	1000BASE-ZX	GE	EXT	70km	SMF	Yes
GLC-T-RGD=	1000BASE-T	GE	IND	100m	Copper	NA
GLC-BX-U-I=	1000BASE-BX	GE	IND	10km	SMF	Yes
GLC-BX-D-I=	1000BASE-BX	GE	IND	10km	SMF	Yes
CWDM-SFP-1470	1000BASE-CWDM	10GE	COM	80km	SMF	Yes
CWDM-SFP-1610	1000BASE-CWDM	10GE	COM	80km	SMF	Yes
CWDM-SFP-1530	1000BASE-CWDM	10GE	COM	80km	SMF	Yes
CWDM-SFP-1490	1000BASE-CWDM	10GE	COM	80km	SMF	Yes
DWDM-SFP-3033	1000BASE-DWDM	10GE	COM	80km	SMF	Yes
DWDM-SFP-3112	1000BASE-DWDM	10GE	COM	80km	SMF	Yes

¹If non-industrial SFPs (EXT, COM) are used, the switch operating temperature must be derated.

Ordering information

Table 15 lists the ordering information for fixed system and memory that are commonly used with the Cisco Catalyst IE3200 switches.

Table 15. Ordering information

Part number	Product description
IE-3200-8T2S-E	Catalyst IE3200 w/ 8 GE Copper and 2 GE SFP, Fixed System, Network Essentials
IE-3200-8P2S-E	Catalyst IE3200 w/ 8 GE PoE/PoE+ and 2 GE SFP, Fixed System, Network Essentials
SD-IE-4GB=	Industrial Ethernet (IE) 4-GB SD memory card for IE
STK-RACK-DINRAIL=	19" DIN Rail mount kit
IE3200-DNA-E¹	Cisco Catalyst Center Essentials license for IE3200 Series
IE3200-DNA-E-3Y	IE 3200 Cisco Catalyst Center Essentials, 3 Year Term license
IE3200-DNA-E-5Y	IE 3200 Cisco Catalyst Center Essentials, 5 Year Term license
IE3200-DNA-E-7Y	IE 3200 Cisco Catalyst Center Essentials, 7 Year Term license
LIC-MRP-MGR-XE=	MRP Ring Manager License
LIC-MRP-CLIENT-XE=	MRP Ring Client License

¹MRP Feature Licenses are not required from release IOS XE 17.7.1 onwards. Please refer to the IOS XE 17.7.1 [Release Notes](#).

¹Cisco Catalyst Center Advantage license is not required for IE3200 to be in Extended Node Mode.

Warranty

Five-year limited HW warranty on all IE3200 PIDs and all IE Power Supplies (see table 8 above). See link below for more details on warranty <https://www.cisco.com/c/en/us/products/warranties/warranty-doc-c99-740591.html>.

Cisco environmental sustainability

Information about Cisco’s environmental sustainability policies and initiatives for our products, solutions, operations, and extended operations or supply chain is provided in the “Environment Sustainability” section of Cisco’s [Corporate Social Responsibility](#) (CSR) Report.

Reference links to information about key environmental sustainability topics (mentioned in the “Environment Sustainability” section of the CSR Report) are provided in the following table:

Sustainability topic	Reference
Information on product material content laws and regulations	Materials
Information on electronic waste laws and regulations, including products, batteries, and packaging	WEEE compliance

Reference links to product-specific environmental sustainability information that is mentioned in relevant sections of this data sheet are provided in the following table:

Sustainability Topic	Reference
Power	
Power specifications and consumption	Table 7. IE3200 power specifications
Environmental Characteristics	
Operating temperature, industry standards, EMC emissions	Table 11. Compliance specifications
Material	
Unit Weight	Table 5. IE3200 physical configurations

Cisco makes the packaging data available for informational purposes only. It may not reflect the most current legal developments, and Cisco does not represent, warrant, or guarantee that it is complete, accurate, or up to date. This information is subject to change without notice.

Cisco Services

<https://www.cisco.com/web/services/>.

Cisco Capital

Flexible payment solutions to help you achieve your objectives

Cisco Capital makes it easier to get the right technology to achieve your objectives, enable business transformation and help you stay competitive. We can help you reduce the total cost of ownership, conserve capital, and accelerate growth. In more than 100 countries, our flexible payment solutions can help you acquire hardware, software, services and complementary third-party equipment in easy, predictable payments.

[Learn more.](#)

Document history

New or Revised Topic	Described In	Date
DNA name change to Catalyst Center, Temperature Range change for Blower Cabinet, Addition of UL60101	Entire Datasheet, Compliance Specification	October 19, 2023
Updated AREMA Certification, DNV GL, Railway certifications, EN61000 Power Frequency Magnetic Field, Extended Node,	Table 11 , Table 10	December 19, 2022
Updated IPv6 Ready Logo, removed IPv6 VRF aware BGP feature, updated DNA License information, BGP MIB removal, updated SFP support, Cisco Environmental Sustainability information	Table 1 , 9 , 10 , 13 , 14 , Cisco Environmental Sustainability	October 29, 2021
Added IEC 60068-2-6 (vibration-sinusoidal, 5Hz-150Hz)	Table 11	November 18, 2020
Added measures in metric system; updated name of standard: EN 61000-4-10 Damped Oscillatory Magnetic Field (100 A/m) and removed "test in progress" from IEEE 1613 & EN/IEC 61850-3	Table 5 and Table 11	October 06, 2020
Revised: PoE/PoE+ budget language clarification	Overview and Table 1	December 17, 2019
Added Hardware configurations; updated hardware specifications; updated power specifications	Table 3 , Table 4 , Table 7	December 17, 2019
Added PWR-IE50W-AC-IEC= to Power Supply Options; Added details on IPv6 support and PROFINET support on key supported software features	Table 8 and Table 9	December 17, 2019
Added new part numbers on SFP support	Table 14	December 17, 2019
Fixed descriptions on product description in ordering information	Table 15	December 17, 2019

Americas Headquarters
Cisco Systems, Inc.
San Jose, CA

Asia Pacific Headquarters
Cisco Systems (USA) Pte. Ltd.
Singapore

Europe Headquarters
Cisco Systems International BV Amsterdam,
The Netherlands

Cisco has more than 200 offices worldwide. Addresses, phone numbers, and fax numbers are listed on the Cisco Website at <https://www.cisco.com/go/offices>.

Cisco and the Cisco logo are trademarks or registered trademarks of Cisco and/or its affiliates in the U.S. and other countries. To view a list of Cisco trademarks, go to this URL: <https://www.cisco.com/go/trademarks>. Third-party trademarks mentioned are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (1110R)