

Cisco Nexus 6001 Switch

Product Overview

In today's data centers, virtualization deployments have become commonplace, and this trend is increasing rapidly with the availability of 10 Gigabit Ethernet servers at attraction prices. The combination of increased adoption of these servers and applications with higher bandwidth requirements is increasing the need for dense 10 and 40 Gigabit Ethernet switching. Moreover, data center architecture is evolving as customers seek to build large-scale nonblocking fabrics to accommodate different applications.

The Cisco Nexus[®] 6001 Switch is part of a robust fabric that can scale significantly to meet data center growth, delivering architectural flexibility that enables any data center to be a more agile, cost-effective, and efficient environment. The Cisco Nexus 6001 Switch is an important component of the Cisco[®] Unified Data Center architecture, complementing existing Cisco Nexus switches. The Cisco Nexus 6001 is an energy-efficient switch that offers high port density in one rack unit (1RU), supports 10 and 40 Gigabit Ethernet and Fibre Channel over Ethernet (FCoE), provides integrated Layer 2 and 3 features at wire speed, and offers low latency of approximately 1 microsecond for any packet size. With a choice of front-to-back (port-side exhaust) and back-to-front (port-side intake) airflow options, the switch is designed for a broad range of traditional data center and large-scale virtualized cloud deployments.

The Cisco Nexus 6001 Switch runs the industry-leading Cisco NX-OS Software operating system, providing customers with features and capabilities that are widely deployed around the world. Cisco NX-OS Software is a purpose-built data center operating system designed for performance, resiliency, scalability, manageability, and programmability. It meets Ethernet and storage networking requirements, providing a robust and comprehensive feature set that can meet the demanding requirements of virtualization and automation in present and future data centers. The Cisco enhanced fabric solution allows the transparent integration of the virtual and physical devices on a unified network. In addition, the comprehensive Cisco NX-OS service set can be used to create unique innovations for customized solutions.

The Cisco Nexus 6001 Switch comes in these configurations:

- Cisco Nexus 6001P: The Cisco Nexus 6001P (Figure 1) is a 1RU, 10- and 40- Gigabit Ethernet switch offering wire-speed performance for up to sixty-four 10 Gigabit Ethernet ports (using Quad Small Form-Factor Pluggable [QSFP] breakout cables) for Ethernet and FCoE traffic, with an overall throughput of 1.28 terabits per second (Tbps). The Cisco Nexus 6001P offers 48 fixed 1/10 Gigabit Ethernet Enhanced Small Form-Factor Pluggable (SFP+) ports and four 40 Gigabit Ethernet QSFP+ ports. Each 40 Gigabit Ethernet port can be split into four 10 Gigabit Ethernet ports using a QSFP+ breakout cable. The Cisco Nexus 6001P delivers low port-to-port latency of approximately 1 microsecond and low jitter independent of packet size using cut-through switching architecture and with features enabled.

Figure 1. Cisco Nexus 6001P Switch



- **Cisco Nexus 6001T:** The Cisco Nexus 6001T (Figure 2) is a 1RU 10 and 40 Gigabit Ethernet switch offering wire-speed performance for up to sixty-four 10 Gigabit Ethernet ports (using Quad Small Form-Factor Pluggable [QSFP] breakout cables) for Ethernet and FCoE traffic. It has an overall throughput of 1.28 terabits per second (Tbps). The Cisco Nexus 6001T offers 48 fixed 1/10G BASE-T and four 40 Gigabit Ethernet QSFP+ ports. Each 40 Gigabit Ethernet port can be split into four 10 Gigabit Ethernet ports using a QSFP breakout cable. The Cisco Nexus 6001T delivers low port-to-port latency of approximately 3.3 microsecond and low jitter independent of packet size using cut-through switching architecture and with features enabled. QSFP interface supports 1 microsecond latency. The hardware of 6001T is capable of supporting FCoE over 10G BASE-T interface. The Cisco Nexus 6001T can be deployed in multiple scenarios - direct-attach 10 and 40 Gigabit Ethernet server-access and high-density fabric extender aggregation deployments, leaf and spine designs, and compact aggregation - to build scalable Cisco Unified Fabric across a diverse set of physical and virtual server environments in the data center.

Figure 2. Cisco Nexus 6001T Switch



The Cisco Nexus 6001 Switch is well-suited to meet the challenging demands of virtualized and cloud-based deployments. The switch is designed with the Cisco high-performance application-specific integrated circuit (ASIC) and is excellent for integrating and connecting a virtual environment to the high-performance servers in a data center. The Nexus 6001 switch is excellent for top-of-rack (ToR) deployments such as direct-attach 10 Gigabit Ethernet server-access and fabric extender aggregation deployments and leaf and spine designs to build scalable Cisco Unified Fabric in data centers. This platform can be deployed in the middle of the row (MoR, in server racks) or at the end of the row (EoR, in network racks) in a data center.

Features and Benefits

The following are some of the primary features of the Cisco Nexus 6001 Switch:

- **Optimization for virtualization and cloud deployments:** Today, high-performance servers deployed in the cloud can support many more virtual machines and workloads than ever before. The requirement to deploy new servers on demand puts additional strain on the network fabric. The Cisco Nexus 6001 Switch addresses this challenge by providing scalability and performance, making it an excellent platform for meeting current and future needs.
- **Density and resilience:** Built for today's data centers, the switches are designed just like the servers they support. Ports and power connections are at the rear, close to server ports, helping keep cable lengths as short as possible and delivering to rack servers benefits traditionally offered only on blade servers. Hot-swappable power and fan modules can be accessed from the front panel, where status lights offer an at-a-glance view of switch operation. Front-to-back or back-to-front cooling is consistent with server designs, supporting efficient data center hot- and cold-aisle designs. Serviceability is enhanced with all customer-replaceable units accessible from the front panel.
- **Energy efficiency:** The Cisco Nexus 6001 Switch helps data centers operate within their space, power, and cooling parameters while reducing their carbon footprints. The switch power supplies are also capable of maintaining 90 percent efficiency at load conditions of as low as 25 percent utilization. This capability allows the switch to make efficient use of power while still being appropriately sized to support the conditions of a full system load.

- **Low latency:** The Cisco Nexus 6001 with cut-through switching supports approximately 1 microsecond of port-to-port latency for any packet size with features enabled.
- **Intelligent Cisco Switched Port Analyzer (SPAN) and Encapsulated SPAN (ERSPAN):** SPAN and ERSPAN can be used for troubleshooting and robust monitoring of traffic. The SPAN and ERSPAN capabilities in the Cisco Nexus 6001 Switch are nondisruptive, with only extra bandwidth capacity used for SPAN and ERSPAN traffic. Enhancements include more efficient allocation of bandwidth to SPAN and ERSPAN traffic whereby any fabric bandwidth not used for data traffic can be allocated to SPAN or ERSPAN traffic. The switch can support up to 31 line-rate SPAN and ERSPAN sessions.
- **Flexible buffer management:** The Cisco Nexus 6001 Switch supports a 25-MB packet buffer shared by every 3 ports of 40 Gigabit Ethernet or every 12 ports of 10 Gigabit Ethernet. The flexible buffer management capability on the Cisco Nexus 6001 Switch allows dynamic tuning of the shared and dedicated buffer size in the event of congestion.
- **Multicast enhancements:** The Cisco Nexus 6001 Switch supports line-rate Layer 2 and 3 multicast throughput for all frame sizes. It offers optimized multicast replication through the fabric and at the egress point. Support is provided for 32,000 multicast routes and for Internet Group Management Protocol (IGMP) snooping tables in hardware. Multicast enhancements include flow-based hashing for multicast traffic over a PortChannel and enhanced Bidirectional Protocol-Independent Multicast (Bidir-PIM) support. The switch also supports IP-based forwarding for IGMP snooping.

Applications

The Cisco Nexus 6001 Switch supports a number of application scenarios, making it a versatile data center option.

Fabric Extender Architecture: High-Density Fabric Extender Aggregator

Cisco Fabric Extender Technology (FEX Technology) enables you to build a single, modular fabric that extends from Cisco Nexus switches, to Cisco Unified Computing System™ (Cisco UCS®) servers, to adapters (Cisco Adapter FEX), and to virtual machines (Cisco Data Center VM-FEX). The Cisco FEX technology is based on the emerging standard IEEE 802.1br. Designing the network using Cisco FEX technology provides flexibility, reduced cabling infrastructure, and a single point of management, helping customers scale their networks. When Nexus 6001 Switches are part of a fabric that includes Cisco Nexus 2200 platforms, use the Cisco Nexus 2200 platform fabric extenders in single or dual connected mode using enhanced virtual port channel (vPC+) technology to two upstream Cisco Nexus 6001 Switches. Servers or end hosts can connect to single or dual Cisco Nexus 2200 platform fabric extenders using network interface card (NIC) teaming when the parent Cisco Nexus 6001 has vPC+ enabled.

Following are some common fabric extender Cisco Nexus 2000 and 6000 Series deployment options:

- Rack servers with 100 Megabit Ethernet, Gigabit Ethernet, or 10 Gigabit Ethernet NICs; the fabric extender can be physically located at the top of the rack, and the Cisco Nexus 6000 Series Switch can reside in the middle or at the end of the row, or the fabric extender and the Cisco Nexus 6000 Series Switch can both reside in the middle or at the end of the row
- Mixed Gigabit Ethernet and 10 Gigabit Ethernet environments in which rack servers are running at either speed in the same rack or in adjacent racks
- 10 Gigabit Ethernet and FCoE deployments using servers with converged network adapters (CNAs) for unified fabric environments with the Cisco Nexus 2232PP 10GE Fabric Extender

- 1/10GBASE-T server connectivity with ease of migration from 1 to 10GBASE-T and effective reuse of structured cabling
- Gigabit Ethernet and 10 Gigabit Ethernet blade servers with pass-through blades
- Low-latency, high-performance computing environments
- Virtualized access

In addition to these options, the Cisco Nexus 6001 Switch provides unique value as a high-density fabric extender aggregation platform. For example, the Cisco Nexus 6001 Switch can be used in conjunction with the Cisco Nexus 2248PQ, 2232PP, and 2248TP Fabric Extenders as a high-density switching system, consolidating 10 Gigabit Ethernet connections in a single management plane. In addition, a variety of blade fabric extender options can be aggregated into a Cisco Nexus 6001 Switch using 10 Gigabit Ethernet, providing a single point of management for blade server deployments.

Table 1 lists the fabric extenders that are supported with the Cisco Nexus 6001. Please refer to the Cisco Nexus 2200 platform data sheets and release notes for more information about the products.

Table 1. Supported Fabric Extenders

| Fabric Extender | Description |
|----------------------|--|
| Cisco Nexus 2224TP | 24x 100/1000BASE-T host interfaces and 2x 10 Gigabit Ethernet fabric interfaces (SFP+) |
| Cisco Nexus 2248TP | 48x 100/1000BASE-T host interfaces and 4x 10 Gigabit Ethernet fabric interfaces (SFP+) |
| Cisco Nexus 2248TP-E | 48x 100/1000BASE-T host interfaces and 4x 10 Gigabit Ethernet fabric interfaces (SFP+; 32 MB shared buffer) |
| Cisco Nexus 2232PP | 32x 1/10 Gigabit Ethernet and FCoE host interfaces (SFP+) and 8x 10 Gigabit Ethernet and FCoE fabric interfaces (SFP+) |
| Cisco Nexus 2248PQ | 48x 1/10GE SFP+ host interface and 4x 40G (16 x 10G SFP+) network interfaces |
| Cisco Nexus 2232TM | 32x 1/10GBASE-T host interfaces and 8x 10 Gigabit Ethernet (SFP+) uplink modules |
| Cisco Nexus 2232TM-E | 32x 1/10GBASE-T host interfaces and 8x 10 Gigabit Ethernet (SFP+) uplink modules (lower power consumption and improved bit error rate [BER]) |
| Cisco Nexus B22HP | 16x 1/10GBASE-KR internal host interfaces and 8x 10 Gigabit Ethernet fabric interfaces (SFP+; network interfaces) |
| Cisco Nexus B22F | 16x 10GBASE-KR internal host interfaces and 8x 10 Gigabit Ethernet fabric interfaces (SFP+; network interfaces) |
| Cisco Nexus B22DELL | 16x 10GBASE-KR internal host interfaces and 8x 10 Gigabit Ethernet fabric interfaces (SFP+) Network Interfaces |
| Cisco Nexus B22IBM | Fourteen 1 and 10 Gigabit Ethernet BASE-KR internal host interfaces and eight 10 Gigabit Ethernet fabric (SFP+) network interfaces |

Large-Scale Fabric (Layer 2 and 3): Leaf and Spine Architecture

Data center designs are evolving, with customers seeking to build large-scale nonblocking fabrics to accommodate different applications, creating patterns of heavy east-west and north-south traffic. The Cisco Nexus 6001 is well suited as a leaf or spine node in a Layer 2 or 3 fabric design. Leaf and spine layer designs using high-density and low-latency switches lead to flatter network architecture, allowing connections scaling from hundreds to more than 10,000 servers with high bidirectional bandwidth, and helping ensure low-latency fabric with a low hop count. The spine switches create a nonblocking, low-latency fabric, forwarding packets between leafs. The leaf switches provide connectivity to servers. Use of a highly meshed architecture helps ensure the highest possible network availability with little impact on customer traffic in the event of a failure. The Cisco Nexus 6001 can be deployed as a Layer 2 or Layer 3 spine or leaf switch, providing a high degree of design flexibility.

Multihop FCoE

Cisco Unified Fabric combines data center and storage networks to deliver a single high-performance, highly available, and scalable network. With the Cisco Nexus 6001, Cisco can support end-to-end data center convergence, from the server to storage, by delivering multihop FCoE capability in the data center. The FCoE capability complements the existing FCoE function on the Cisco Nexus 5500 switch platform. With this broad selection of standards-based FCoE switches, Cisco provides unified fabric support to both the access and core network layers, supporting all storage traffic (FCoE, Small Computer System Interface over IP [iSCSI], and network-attached storage [NAS]) over simplified infrastructure based on lossless 10 and 40 Gigabit Ethernet. The Cisco Nexus 6000 Series Switches are the industry's first to provide 40-Gbps FCoE support, surpassing the 16-Gbps Fibre Channel capability.

High-Performance Computing

The Cisco Nexus 6001 can be deployed as a high-density Small Form-Factor (SFF) access-layer switch to consolidate a large number of 10 Gigabit Ethernet servers in deployments that call for only a small number of hops from the server to the upstream network to reduce latency. The Cisco Nexus 6001 has a high density of 10 Gigabit Ethernet ports per rack unit, approximately 1 microsecond of latency port to port for any packet size, integrated line-rate Layer 2 and 3 features, scalability, and integrated data analytics with programmability. It addresses the needs of high-performance computing (HPC) and high-frequency trading (HFT) environments, for which InfiniBand solutions lack management visibility and high performance of bulk data transfers across traditional applications.

The capability of the Cisco Nexus 6001 to function in all these capacities helps protect investments in the data center with a deployment model in which additional features can be enabled as they are needed.

Cisco NX-OS Software Overview

Cisco NX-OS Software is a purpose-built data center operating system designed for performance, resiliency, scalability, manageability, and programmability. Cisco NX-OS meets Ethernet and storage networking requirements, providing a robust and comprehensive feature set that can meet the demanding requirements of virtualization and automation in present and future data centers. Cisco's enhanced fabric solution allows the transparent integration of the virtual and physical devices on a unified network. In addition, users can use the comprehensive Cisco NX-OS service set to create unique innovations for customized solutions. With its MIBs, native XML interface, and command-line interface (CLI) like that of Cisco IOS® Software, Cisco NX-OS provides drastically simplified management for the devices in which it runs.

For a complete list of all the features and benefits of Cisco NX-OS Software, please see http://www.cisco.com/en/US/prod/collateral/iosswrel/ps9494/ps9372/data_sheet_c78-652063.html.

Cisco NX-OS Software Packaging for Cisco Nexus 6001 Switch

The software packaging for the Cisco Nexus 6001 Switch offers flexibility and a comprehensive feature set while being consistent with Cisco Nexus access switches. The default system software has a comprehensive Layer 2 feature set with comprehensive security and management features. To enable Layer 3 IP unicast and multicast routing functions, additional licenses need to be installed.

Table 2 lists the software packaging and licensing available.

Table 2. Software Packaging and Licensing

| License | Chassis Based or Port Based | Part Number | Supported Features and Platforms |
|--|-----------------------------|-----------------|---|
| Cisco Nexus 6000 FCoE NPV License | Chassis | N6K-FNPV-SSK9 | FCoE Network Port Virtualization (NPV) features supported on Cisco Nexus 6000 |
| Cisco Nexus 6001 Storage Protocols Services License, 16 Ports | Port | N6001-16P-SSK9 | Fibre Channel and FCoE and FCoE NPV features supported on any 16 ports of Cisco Nexus 6001 |
| Cisco Nexus 6001 Storage Protocols Services License, 64 Ports | Port | N6001-64P-SSK9 | Fibre Channel and FCoE and FCoE NPV features supported on any 64 ports of Cisco Nexus 6001 |
| Cisco Nexus 6000 Layer 3 Base Software License | Chassis | N6K-BAS1K9 | Unlimited static routes and maximum of 256 dynamic routes: <ul style="list-style-type: none"> • Static routes • Routing Information Protocol Version 2 (RIPv2) • Open Shortest Path First Version 2 (OSPFv2) and OSPFv3 • Enhanced Interior Gateway Routing Protocol (EIGRP) Stub • Hot-Standby Router Protocol (HSRP) • Virtual Router Redundancy Protocol (VRRP) • IGMP v2 and v3 • PIMv2 (sparse mode) • Virtual Routing and Forwarding (VRF) Lite • Routed access control list (ACL) • Network Address Translation (NAT) |
| Cisco Nexus 6001 Layer 3 Enterprise Software License | Chassis | N6001-LAN1K9 | N6001-LAN1K9 includes the following features in addition to the ones provided by the N6K-BAS1K9 license: <ul style="list-style-type: none"> • Border Gateway Protocol (BGP) • Policy-based routing (PBR) • Full EIGRP • PIMv2 (all modes) • Layer 3 Intermediate System-to-Intermediate System (IS-IS) • Unicast Reverse-Path Forwarding (uRPF) • Multicast Source Discovery Protocol (MSDP) • Sampled NetFlow |
| Cisco Nexus 6000 VM-FEX Software License | Chassis | N6K-VMFEXK9 | Cisco Data Center VM-FEX supported on Cisco Nexus 6000 Series |
| Cisco Nexus 6001 Enhanced Layer 2 Software License | Chassis | N6001-EL2-SSK9 | Cisco FabricPath supported on Cisco Nexus 6001 |
| Cisco Data Center Network Manager (DCNM) SAN Software License | Chassis | DCNM-SAN-N61-K9 | Cisco DCNM for SAN Advanced Edition for Cisco Nexus 6001 |
| Cisco DCNM LAN Software License | Chassis | DCNM-LAN-N61-K9 | Cisco DCNM for LAN Advanced Edition for Cisco Nexus 6001 |

Cisco ONE Software

Licenses can be purchased individually for each feature as shown in Table 2 or through [Cisco ONE™ Software for Data Center Networking](#) which is available for the Cisco Nexus 6001 Switch.

Cisco ONE Software provides a new way for customers to purchase, consume, and use our infrastructure software. It offers a simplified consumption model focused on common customer scenarios for the data center, WAN, and LAN.

Cisco ONE Software and services provide customers with four main benefits:

- Software suites that address typical customer use scenarios at an attractive price
- Investment protection of software purchases through software services-enabled license portability
- Access to ongoing innovation and new technology with Cisco Software Support Service (SWSS)
- Flexible licensing models to smoothly distribute the customer's software spending over time

For ordering information for Cisco ONE Software for the Cisco Nexus 6001 Switch, please [click here](#).

Cisco Prime Data Center Network Manager

Cisco Prime™ DCNM provides LAN and SAN management capabilities for the Cisco Nexus and Cisco MDS 9500 Families. Cisco Prime DCNM provides a GUI that reduces OpEx compared to traditional CLI methods and allows efficient operation control, monitoring, provisioning, and troubleshooting for your Cisco NX-OS devices. The main features include:

- Unified fabric visibility and topology display with VMware vSphere integration shows connectivity from the virtual machine to the VMware ESX host and to the switch and the storage array.
- Event aggregation and filtering helps you quickly find the information you need and identify network problems.
- Deployment wizards and user-modifiable templates help implement best practices.
- RBAC secures devices and provides appropriate delegation.
- Integrated domain dashboards, health monitoring, reporting, change tracking, and user auditing provides comprehensive management capabilities.
- Trend monitoring of ports and traffic allow you to optimize your existing resources and anticipate new resource requirements.

Specifications

Table 3 lists the specifications for the Cisco Nexus 6001. Please check software release notes for feature support information.

Table 3. Product Specifications

| Performance |
|---|
| <ul style="list-style-type: none">• Cisco Nexus 6001: Layer 2 and 3 hardware forwarding at 1.28 Tbps• Support for up to 256,000 combined entries of MAC addresses and APR entries• Low-latency of approximately 1 microsecond using cut-through forwarding for predictable, consistent traffic latency regardless of packet size, traffic pattern, or features enabled on 40 and 10 Gigabit Ethernet interfaces• 25-MB buffer per 3x 40 Gigabit Ethernet QSFP interfaces• Line-rate traffic throughput on all ports |
| Interfaces |
| <ul style="list-style-type: none">• Cisco Nexus 6001P: 48 fixed 1/10 Gigabit Ethernet SFP+ and 4 fixed 40 Gigabit Ethernet QSFP+ ports, with 10 and 40 Gigabit Ethernet FCoE support on all respective ports• Cisco Nexus 6001T: 48 fixed 1/10 Gigabit BASE-T and 4 fixed 40 Gigabit Ethernet QSFP+ ports, with 10 and 40 Gigabit Ethernet FCoE support on all respective ports• 40 Gigabit Ethernet ports can be converted to 10 Gigabit Ethernet interfaces through QSFP+breakout cable• Fabric extension through the Cisco Nexus 2200 |

Layer 2 Features

- Layer 2 switch ports and VLAN trunks
- IEEE 802.1Q VLAN encapsulation
- Support for up to 4000 VLANs
- Support for up to 4000 ACL entries
- Rapid Per-VLAN Spanning Tree Plus (PVRST+) (IEEE 802.1w compatible)
- Multiple Spanning Tree Protocol (MSTP) (IEEE 802.1s): 64 instances
- Spanning Tree PortFast
- Spanning Tree root guard
- Spanning Tree Bridge Assurance
- Cisco EtherChannel technology (up to 16 ports per EtherChannel)
- Cisco vPC technology
- vPC configuration synchronization
- vPC Shutdown
- Link Aggregation Control Protocol (LACP): IEEE 802.3ad
- Advanced port channel hashing based on Layer 2, 3, and 4 information
- Jumbo frames on all ports (up to 9216 bytes)
- Pause frames (IEEE 802.3x)
- Storm control (unicast, multicast, and broadcast)
- Private VLANs
- Private VLAN over trunks (isolated and promiscuous)
- Private VLANs over vPC and EtherChannels
- VLAN remapping
- Cisco FabricPath
- EvPC and vPC+ with Cisco FabricPath
- Cisco Adapter FEX
- Cisco Data Center VM-FEX
- Support for up to 24 fabric extenders (Layer 2) with each switch

Layer 3 Features

- Layer 3 interfaces: Routed ports, switch virtual interface (SVI), port channels, subinterfaces, and port channel subinterfaces
- Support for up to 32,000 IPv4 and 8000 IPv6 host prefixes
- Support for up to 8000 multicast routes (IPv4)
- Support for up to 8000 IGMP snooping groups
- Support for 4000 VRF entries
- Support for up to 4096 VLANs
- Equal-Cost Multipathing (ECMP) up to 64 ways
- 4000 flexible ACL entries
- Routing protocols: Static, RIPv2, EIGRP, OSPFv2, BGP and IS-IS
- IPv6 routing protocols: Static, OPFv3, BGPv6, and EIGRPv6
- IPv6 VRF-lite
- BFD support: OSPFv2, BGPv4, EIGRP, VRFs
- Policy Based Routing (IPv4 and IPv6)
- HSRP and VRRP
- IPdirect Broadcast
- vPC+ Routing Protocol Peering
- ACL: Routed ACL with Layer 3 and 4 options to match ingress and egress ACL
- Multicast: PIMv2 sparse mode, Source-Specific Multicast (SSM), Bidir-PIM, MSDP, IGMPv2 and v3, and Multicast VLAN Registration (MVR)
- VRF: VRF-lite (IP VPN); VRF-aware unicast; and BGP-, OSPF-, RIP-, and VRF-aware multicast
- Unicast Reverse Path Forwarding (uRFP) with ACL; strict and loose modes
- Jumbo frame support (up to 9216 bytes)
- Support for up to 24 fabric extenders on each Cisco Nexus 6001

Quality of Service (QoS)

- Layer 2 IEEE 802.1p (class of service [CoS])
- 8 unicast queues and 8 multicast queues per port
- Per-port QoS configuration
- CoS trust
- Port-based CoS assignment
- Modular QoS CLI (MQC) compliance: IPv4 and IPv6
- ACL-based QoS classification (Layers 2, 3, and 4)
- Flexible TCAM Carving
- MAC/ARP Hardware Carving
- MQC CoS marking
- Per-port virtual output queuing
- CoS-based egress queuing
- Egress strict-priority queuing
- Egress port-based scheduling: Weighted Round-Robin (WRR)
- Control Plan Policing (CoPP): IPv4 and IPv6

Security

- Ingress ACLs (standard and extended) on Ethernet and virtual Ethernet ports
- Standard and extended Layer 2 ACLs: MAC addresses, protocol type, etc.
- Standard and extended Layer 3 and 4 ACLs: IPv4 and IPv6, Internet Control Message Protocol (ICMP and ICMPv6), TCP, User Datagram Protocol (UDP), etc.
- Ingress Policing
- VLAN-based ACLs (VACLs)
- Port-based ACLs (PACLs)
- Named ACLs
- Optimized ACL distribution
- ACLs on virtual terminals (VTYs)
- ACL logging (IPv4 only)
- Dynamic Host Configuration Protocol (DHCP) snooping with Option 82
- Dynamic Address Resolution Protocol (ARP) Inspection
- IP source guard
- DHCP relay - up to 32 destinations
- Ethernet Port Security
- IPv6 RACL, PACL, and VACL
- iSCSI TLV

High-Availability Features

- ISSU for Layer 2
- Hot-swappable field-replaceable power supplies and fan modules
- N+1 and N+N power redundancy
- N:1 fan module redundancy
- N+1 fan module redundancy

Management

- Switch management using 10/100/1000-Mbps management or console ports
- CLI-based console to provide detailed out-of-band management
- In-band switch management
- Port-based locator and beacon LEDs
- Configuration synchronization
- Configuration rollback
- Secure Shell Version 2 (SSHv2)
- Telnet
- Authentication, authorization, and accounting (AAA)
- AAA with RBAC
- RADIUS
- TACACS+
- Syslog (8 servers)

- Embedded packet analyzer
- SNMPv1, v2, and v3 (IPv4 and IPv6)
- Enhanced SNMP MIB support
- XML (NETCONF) support
- Remote monitoring (RMON)
- Advanced Encryption Standard (AES) for management traffic
- Unified username and passwords across CLI and SNMP
- Microsoft Challenge Handshake Authentication Protocol (MS-CHAP)
- Digital certificates for management between switch and RADIUS server
- Cisco Discovery Protocol Versions 1 and 2
- RBAC
- SPAN on physical, port channel and VLAN
- ERSPAN
- Ingress and egress packet counters per interface
- Network Time Protocol (NTP)
- Cisco Generic Online Diagnostics (GOLD)
- Comprehensive bootup diagnostic tests
- Embedded Event Manager
- Cisco Call Home
- Cisco Smart Call Home
- Default Interface
- Cisco Fabric Manager
- Cisco DCNM
- CiscoWorks LAN Management Solution (LMS)

Data Center Bridging

- CEE- and IEEE-compliant priority flow control (PFC; per-priority Pause frame support)
- PFC link distance support: 300m
- CEE-compliant Data Center Bridging Exchange (DCBX) Protocol
- CEE- and IEEE-compliant enhanced transmission selection

FCoE Features (Require Storage Services License)

- T11 standards-compliant FCoE (FC-BB-5)
- T11 FCoE Initialization Protocol (FIP) (FC-BB-5)
- Any 10 or 40 Gigabit Ethernet port configurable as FCoE
- SAN administration separate from LAN administration
- Fibre Channel forwarding (FCF)
- Fibre Channel enhanced port types: VE, and VF
- Direct attachment of FCoE targets
- Fabric Device Management Interface (FDMI)
- Fibre Channel ID (FCID) persistence
- Distributed device alias services
- In-order delivery
- Port tracking
- Cisco FCoE_NPV technology
- N-port identifier virtualization (NPIV)
- Fabric services: Name server, registered state change notification (RSCN), login services, and name-server zoning
- Per-VSAN fabric services
- Cisco Fabric Services
- Distributed device alias services
- Host-to-switch and switch-to-switch FC-SP authentication
- Fabric Shortest Path First (FSPF)
- Standard zoning
- Enhanced zoning
- Cisco Fabric Analyzer
- Cisco Data Center Network Manager - SAN
- Storage Management Initiative Specification (SMI-S)
- Boot from SAN over vPC and Enhanced vPC (EvPC)

- FCP
- VSAN trunking
- Fabric Device Management Interface (FDMI)
- Fibre Channel ID (FCID) persistence
- Distributed device alias services
- In-order delivery
- Port tracking
- Cisco NPV technology
- Fabric binding for Fibre Channel
- Port security
- Fibre Channel traceroute
- Fibre Channel ping
- Fibre Channel debugging

SNMP MIBs

Generic MIBs

- SNMPv2-SMI
- CISCO-SMI
- SNMPv2-TM
- SNMPv2-TC
- IANA-ADDRESS-FAMILY-NUMBERS-MIB
- IANAifType-MIB
- IANAiprouteprotocol-MIB
- HCNUM-TC
- CISCO-TC
- SNMPv2-MIB
- SNMP-COMMUNITY-MIB
- SNMP-FRAMEWORK-MIB
- SNMP-NOTIFICATION-MIB
- SNMP-TARGET-MIB
- SNMP-USER-BASED-SM-MIB
- SNMP-VIEW-BASED-ACM-MIB
- CISCO-SNMP-VACM-EXT-MIB

Layer 3 MIBs

- UDP-MIB
- TCP-MIB
- OSPF-MIB
- BGP4-MIB
- CISCO-HSRP-MIB

Ethernet MIBs

- CISCO-VLAN-MEMBERSHIP-MIB
- CISCO-Virtual-Interface-MIB
- CISCO-VTP-MIB

Configuration MIBs

- ENTITY-MIB
- IF-MIB
- CISCO-ENTITY-EXT-MIB
- CISCO-ENTITY-FRU-CONTROL-MIB
- CISCO-ENTITY-SENSOR-MIB
- CISCO-FLASH-MIB
- CISCO-SYSTEM-MIB
- CISCO-SYSTEM-EXT-MIB
- CISCO-IP-IF-MIB
- CISCO-IF-EXTENSION-MIB
- CISCO-SERVER-INTERFACE-MIB
- CISCO-NTP-MIB

- CISCO-IMAGE-MIB
- CISCO-IMAGE-CHECK-MIB
- CISCO-IMAGE-UPGRADE-MIB
- CISCO-CONFIG-COPY-MIB
- CISCO-ENTITY-VENDORTYPE-OID-MIB
- CISCO-BRIDGE-MIB

Monitoring MIBs

- DIFFSERV-DSCP-TC
- NOTIFICATION-LOG-MIB
- DIFFSERV-MIB
- CISCO-CALLHOME-MIB
- CISCO-SYSLOG-EXT-MIB
- CISCO-PROCESS-MIB
- RMON-MIB
- CISCO-RMON-CONFIG-MIB
- CISCO-HC-ALARM-MIB
- LLDP-MIB

Security MIBs

- CISCO-AAA-SERVER-MIB
- CISCO-AAA-SERVER-EXT-MIB
- CISCO-COMMON-ROLES-MIB
- CISCO-COMMON-MGMT-MIB
- CISCO-RADIUS-MIB
- CISCO-SECURE-SHELL-MIB
- TCP/IP MIBs
- INET-ADDRESS-MIB
- TCP-MIB
- CISCO-TCP-MIB
- UDP-MIB
- IP-MIB
- CISCO-IP-PROTOCOL-FILTER-MIB
- CISCO-DNS-CLIENT-MIB
- CISCO-PORTSECURITY-MIB

Miscellaneous MIBs

- START-MIB
- CISCO-LICENSE-MGR-MIB
- CISCO-FEATURE-CONTROL-MIB
- CISCO-CDP-MIB
- CISCO-RF-MIB
- CISCO-ETHERNET-FABRIC-EXTENDER-MIB
- CISCO-BRIDGE-MIB
- CISCO-FCOE-MIB
- CISCO-PORTCHANNEL-MIB
- CISCO-ZS-MIB

| Standards |
|---|
| Industry Standards <ul style="list-style-type: none"> • IEEE 802.1D: Spanning Tree Protocol • IEEE 802.1p: CoS prioritization • IEEE 802.1Q: VLAN tagging • IEEE 802.1Qaz: Enhanced transmission selection • IEEE 802.1Qbb: Per-priority Pause • IEEE 802.1s: Multiple VLAN instances of Spanning Tree Protocol • IEEE 802.1w: Rapid reconfiguration of Spanning Tree Protocol • IEEE 802.3: Ethernet • IEEE 802.3ad: LACP with fast timers • IEEE 802.3ae: 10 Gigabit Ethernet • SFF 8431 SFP+ CX1 support • RMON |

Power Supply

Table 4 lists the power supply properties of the Cisco Nexus 6001.

Table 4. Power Supply Properties

| AC Power Supply Properties | Cisco Nexus 6001 |
|--|-------------------|
| Typical operating power | 750W |
| Maximum power | 1100W |
| Input voltage | 94 to 240 VAC |
| Frequency | 47 to 63 Hz |
| Efficiency | 94% (at 50% load) |
| RoHS compliance | Yes |
| Hot swappable | Yes |
| Front-to-back air flow power supply (Port side exhaust) | Yes |
| Back-to-front air flow power supply (Port side intake airflow) | Yes |

Environment

Table 5 lists the environment properties of the Cisco Nexus 6001.

Table 5. Environment Properties

| Property | Cisco Nexus 6001 |
|------------------------------------|---|
| Physical (height x width x depth) | 1.75 x 17.3 x 30 in. (4.4 x 43.9 x 76.2 cm) |
| Operating temperature | 32 to 104°F (0 to 40°C) |
| Nonoperating (storage) temperature | -40 to 158°F (-40 to 70°C) |
| Humidity | 5 to 95% (noncondensing) |
| Altitude | 0 to 10,000 ft (0 to 3000m) |
| Weight | 32 lbs |

For the latest software release information and recommendations, please see the product bulletin at <http://www.cisco.com/go/nexus6000>.

Regulatory Standards Compliance

Table 6 summarizes regulatory standards compliance for the Cisco Nexus 6001.

Table 6. Regulatory Standards Compliance: Safety and EMC

| Specification | Description |
|------------------------------|---|
| Regulatory compliance | Products should comply with CE Markings according to directives 2004/108/EC and 2006/95/EC. |
| Safety | <ul style="list-style-type: none"> • UL 60950-1 Second Edition • CAN/CSA-C22.2 No. 60950-1 Second Edition • EN 60950-1 Second Edition • IEC 60950-1 Second Edition • AS/NZS 60950-1 • GB4943 |
| EMC: Emissions | <ul style="list-style-type: none"> • 47CFR Part 15 (CFR 47) Class A • AS/NZS CISPR22 Class A • CISPR22 Class A • EN55022 Class A • ICES003 Class A • VCCI Class A • EN61000-3-2 • EN61000-3-3 • KN22 Class A • CNS13438 Class A |
| EMC: Immunity | <ul style="list-style-type: none"> • EN55024 • CISPR24 • EN300386 • KN 61000-4 series |
| RoHS | The product is RoHS 6 compliant with exceptions for leaded ball grid array (BGA) balls and lead press-fit connectors. |

Cisco Nexus 6001 Transceiver and Cabling Options

The Cisco Nexus 6001 supports a wide variety of 1, 10, and 40 Gigabit Ethernet connectivity options. Table 7 lists the transceivers supported for 1 and 10 Gigabit Ethernet connectivity, and Table 8 lists the 40 Gigabit Ethernet QSFP+ transceivers supported.

Table 7. Cisco Nexus 6001 1 and 10 Gigabit Ethernet SFP+ Transceiver Support Matrix

| Cisco SFP | Description |
|-------------------------------|---|
| FET-10G | 10-Gbps SFP+ module for Cisco Nexus 2000 Series to Cisco Nexus 5000 Series connectivity |
| Cisco SFP-10G-SR | 10GBASE-SR SFP+ module (multimode fiber [MMF]) |
| Cisco SFP-10G-LR | 10GBASE-LR SFP+ module (single-mode fiber [SMF]) |
| Cisco SFP-10G-ER | 10GBASE-ER-SFP+ module (SMF) |
| Cisco SFP-H10GB-CU1M | 10GBASE-CU SFP+ cable 1m (Twinax cable) |
| SFP-H10GB-CU1.5M | 10GBASE CU SFP+ cable, 1.5 Meter, passive (Twinax cable) |
| SFP-H10GB-CU2M | 10GBASE CU SFP+ cable, 2 Meter, passive (Twinax cable) |
| SFP-H10GB-CU2.5M | 10GBASE CU SFP+ cable, 2.5 Meter, passive (Twinax cable) |
| Cisco SFP-H10GB-CU3M | 10GBASE-CU SFP+ cable 3m (Twinax cable) |
| Cisco SFP-H10GB-CU5M | 10GBASE-CU SFP+ cable 5m (Twinax cable) |
| Cisco SFP-H10GB-ACU7M | 10GBASE-CU SFP+ cable 7m (active Twinax cable) |
| Cisco SFP-H10GB-ACU10M | 10GBASE-CU SFP+ cable 10m (active Twinax cable) |
| SFP-10G-AOC1M | Cisco 10GBASE-AOC SFP+ Cable 1 Meter |

| Cisco SFP | Description |
|-------------------------|---|
| SFP-10G-AOC2M | Cisco 10GBASE-AOC SFP+ Cable 2 Meter |
| SFP-10G-AOC3M | Cisco 10GBASE-AOC SFP+ Cable 3 Meter |
| SFP-10G-AOC5M | Cisco 10GBASE-AOC SFP+ Cable 5 Meter |
| SFP-10G-AOC7M | Cisco 10GBASE-AOC SFP+ Cable 7 Meter |
| SFP-10G-AOC10M | Cisco 10GBASE-AOC SFP+ Cable 10 Meter |
| Cisco GLC-T | 1000BASE-T SFP |
| GLC-ZX-SM | 1000BASE-ZX SFP transceiver module for SMF, 1550-nm wavelength, dual LC/PC connector |
| Cisco GLC-SX-MM | Gigabit Ethernet SFP, LC connector SX transceiver (MMF) |
| Cisco GLC-SX-MMD | Gigabit Ethernet SFP, LC connector SX transceiver (MMF), extended temperature range and digital optical monitoring (DOM) |
| Cisco GLC-LH-SM | Gigabit Ethernet SFP, LC connector LX/LH transceiver (SMF) |
| Cisco GLC-LH-SMD | Gigabit Ethernet SFP, LC connector LX/LH transceiver (SMF), extended temperature range and digital optical monitoring (DOM) |
| Cisco SFP-GE-T | 1000BASE-T SFP, extended temperature range |
| Cisco SFP-GE-S | Gigabit Ethernet SFP, LC connector SX transceiver (MMF), extended temperature range and digital optical monitoring (DOM) |
| Cisco SFP-GE-L | Gigabit Ethernet SFP, LC connector LX/LH transceiver (SMF), extended temperature range and DOM |

Table 8. Cisco Nexus 6001 40 Gigabit Ethernet QSFP+ Transceiver Support Matrix

| Cisco QSFP++ | Description |
|--------------------------|---|
| QSFP-40G-SR4 | 40GBASE-SR4 QSFP module, (multi-mode fiber, MMF at 100m) |
| QSFP-40G-CSR4 | 40GBASE Extended CSR4 QSFP module, (multi-mode fiber, MMF at 300m) |
| QSFP-40G-LR4 | 40G Base Extended LR4 QSFP module, LC connector 10Km |
| QSFP-4X10G-LR-S | QSFP 4x10G Transceiver Module, SM MPO, 10KM, Enterprise-Class (6001P only) |
| QSFP-40G-SR-BD | Cisco QSFP40G BiDi Short-reach Transceiver |
| QSFP-4SFP10G-CU1M | Cisco 40GBASE-CR4 QSFP+ to 4 10GBASE-CU SFP+ passive direct-attach copper transceiver assembly, 1 meter |
| QSFP-4SFP10G-CU3M | Cisco 40GBASE-CR4 QSFP+ to 4 10GBASE-CU SFP+ passive direct-attach copper transceiver assembly, 3 meter |
| QSFP-4SFP10G-CU5M | Cisco 40GBASE-CR4 QSFP+ to 4 10GBASE-CU SFP+ passive direct-attach copper transceiver assembly, 5 meter |
| QSFP-4x10G-AC7M | Cisco 40GBASE-CR4 QSFP+ to 4 10GBASE-CU SFP+ direct-attach breakout cable, 7-meter, active |
| QSFP-4x10G-AC10M | Cisco 40GBASE-CR4 QSFP+ to 4 10GBASE-CU SFP+ direct-attach breakout cable, 10-meter, active |
| QSFP-H40G-CU1M | Cisco 40GBASE-CR4 QSFP+ direct-attach copper cable, 1-meter, passive |
| QSFP-H40G-CU3M | Cisco 40GBASE-CR4 QSFP+ direct-attach copper cable, 3-meter, passive |
| QSFP-H40G-CU5M | Cisco 40GBASE-CR4 QSFP+ direct-attach copper cable, 5-meter, passive |
| QSFP-H40G-ACU7M | Cisco 40GBASE-CR4 QSFP+ direct-attach copper cable, 7-meter, active |
| QSFP-H40G-ACU10M | Cisco 40GBASE-CR4 QSFP+ direct-attach copper cable, 10-meter, active |
| QSFP-4X10G-AOC1M | Cisco 40GBase-AOC QSFP to 4 SFP+ Active Optical breakout Cable, 1-meter |
| QSFP-4X10G-AOC2M | Cisco 40GBase-AOC QSFP to 4 SFP+ Active Optical breakout Cable, 2-meter |
| QSFP-4X10G-AOC3M | Cisco 40GBase-AOC QSFP to 4 SFP+ Active Optical breakout Cable, 3-meter |
| QSFP-4X10G-AOC5M | Cisco 40GBase-AOC QSFP to 4 SFP+ Active Optical breakout Cable, 5-meter |
| QSFP-4X10G-AOC7M | Cisco 40GBase-AOC QSFP to 4 SFP+ Active Optical breakout Cable, 7-meter |
| QSFP-4X10G-AOC10M | Cisco 40GBase-AOC QSFP to 4 SFP+ Active Optical breakout Cable, 10-meter |
| QSFP-H40G-AOC1M | Cisco 40GBase-AOC QSFP direct-attach Active Optical Cable, 1-meter |
| QSFP-H40G-AOC2M | Cisco 40GBase-AOC QSFP direct-attach Active Optical Cable, 2-meter |
| QSFP-H40G-AOC3M | Cisco 40GBase-AOC QSFP direct-attach Active Optical Cable, 3-meter |

| Cisco QSFP++ | Description |
|-------------------------|---|
| QSFP-H40G-AOC5M | Cisco 40GBase-AOC QSFP direct-attach Active Optical Cable, 5-meter |
| QSFP-H40G-AOC7M | Cisco 40GBase-AOC QSFP direct-attach Active Optical Cable, 7-meter |
| QSFP-H40G-AOC10M | Cisco 40GBase-AOC QSFP direct-attach Active Optical Cable, 10-meter |

The platform supports an innovative Twinax copper cabling solution that connects to standard QSFP connectors for in-rack use, and optical cabling for longer cable runs (Table 9).

For in-rack or adjacent-rack cabling, the Cisco Nexus 6001 supports QSFP+ direct-attach 40 Gigabit Ethernet copper cables, an innovative solution that integrates transceivers with Twinax cables into an energy-efficient, low-cost, and low-latency solution. QSFP+ direct-attach 40 Gigabit Twinax copper cables use only 1.5 watt (W) of power per transceiver and introduce approximately 0.1 microsecond of latency per link.

For longer cable runs, the Cisco Nexus 6001 supports multimode, short-reach optical QSFP+ transceivers. These optical transceivers use approximately 1.5W per transceiver and have a latency of approximately 0.1 microsecond.

Table 9. Cisco Nexus 6001 Cabling Support Matrix

| Connector (Media) | Cable | Distance | Maximum Power Consumption | Transceiver Latency |
|------------------------|------------------------|----------------|---------------------------|--------------------------------|
| QSFP CU copper | Twinax | 1m 3m 5m | Approximately 1.5W | Approximately 0.25 microsecond |
| QSFP ACU copper | Active Twinax | 7m 10m | Approximately 1.5W | Approximately 0.1 microsecond |
| QSFP SR4 MMF | MMF (OM3) MMF (OM4) | 100m 150m | Approximately 1.5W | Approximately 0.1 microsecond |
| QSFP CSR4 MMF | MMF (OM3) MMF (OM4) | 300m 400m | Approximately 1.5W | Approximately 0.1 microsecond |
| QSFP LR4 SMF | SMF | 10 km | Approximately 3.5W | Approximately 0.1 microsecond |

Ordering Information

Table 10 presents ordering information for the Cisco Nexus 6001 platform. Note that you can order the Cisco Nexus 2200 Series Fabric Extenders either separately or along with the Cisco Nexus 6001 platform.

Table 10. Ordering Information

| Part Number | Description |
|---------------------------|---|
| Chassis | |
| N6K-C6001-64P | Cisco Nexus 6001 1 RU Switch, Fixed 48P of 10G SFP+ and 4P QSFP; 2 PS, 3 Fans |
| N6K-C6001-64T | Cisco Nexus 6001 1 RU Switch, Fixed 48P of 10G BaseT and 4P QSFP; 2 PS, 3 Fans |
| Fan Modules | |
| N6K-C6001-FAN-F= | Cisco Nexus 6001 Fan Module, Front-to-Back (Port Side Exhaust) Airflow, spare |
| N6K-C6001-FAN-B= | Cisco Nexus 6001 Fan Module, Back-to-Front (Port Side Intake) Airflow, spare |
| Power Supplies | |
| N55-PAC-1100W= | Cisco Nexus 6001 PSU module, 100-240VAC 1100W, Front-to-Back (Port Side Exhaust) Airflow, Spare |
| N55-PAC-1100W-B= | Cisco Nexus 6001 PSU module, 100-240VAC 1100W, Back-to-Front (Port Side Intake) Airflow, Spare |
| N55-PDC-1100W= | Cisco Nexus 6001 PSU Front-to-Back Airflow module spare, D/C, - 40 to -72VDC, 1100W |
| NXA-PAC-1100W(=) | Cisco Nexus 6001 Platinum PSU Front-to-Back Airflow module spare, A/C, 100-240V, 1100W |
| NXA-PAC-1100W-B(=) | Cisco Nexus 6001 Platinum PSU Back-to-Front Airflow module spare, A/C, 100-240V, 1100W |

| Part Number | Description |
|--------------------------|---|
| Software | |
| N6KUK9-602N1.2 | Nexus 6000 Base OS Software Rel 6.0(2)N1(2) |
| N6KUK9-602N1.2= | Nexus 6000 Base OS Software Rel 6.0(2)N1(2), spare |
| N6KUK9-602N1.2a | Nexus 6000 Base OS Software Rel 6.0(2)N1(2a) |
| N6KUK9-602N1.2a= | Nexus 6000 Base OS Software Rel 6.0(2)N1(2a), spare |
| N6KUK9-602N2.1 | Nexus 6000 Base OS Software Rel 6.0(2)N2(1) |
| N6KUK9-602N2.1= | Nexus 6000 Base OS Software Rel 6.0(2)N2(1), spare |
| N6KUK9-700N1.1 | Nexus 6000 Base OS Software Rel 7.0(0)N1(1) |
| N6KUK9-700N1.1 | Nexus 6000 Base OS Software Rel 7.0(0)N1(1), spare |
| Cables and Optics | |
| QSFP-40G-SR4 | 40GBASE-SR4 QSFP module, (multi-mode fiber, MMF at 100m) |
| QSFP-40G-CSR4 | 40GBASE Extended CSR4 QSFP module, (multi-mode fiber, MMF at 300m) |
| QSFP-40G-LR4 | Cisco 40GBASE-LR4 QSFP+ transceiver module for SMF, duplex LC connector |
| QSFP-40G-SR-BD | Cisco QSFP40G BiDi Short-reach Transceiver |
| QSFP-4SFP10G-CU1M | Cisco 40GBASE-CR4 QSFP+ to 4 10GBASE-CU SFP+ passive direct-attach copper transceiver assembly, 1 meter |
| QSFP-4SFP10G-CU3M | Cisco 40GBASE-CR4 QSFP+ to 4 10GBASE-CU SFP+ passive direct-attach copper transceiver assembly, 3 meter |
| QSFP-4SFP10G-CU5M | Cisco 40GBASE-CR4 QSFP+ to 4 10GBASE-CU SFP+ passive direct-attach copper transceiver assembly, 5 meter |
| QSFP-4x10G-AC7M | Cisco 40GBASE-CR4 QSFP+ to 4 10GBASE-CU SFP+ direct-attach breakout cable, 7-meter, active |
| QSFP-4x10G-AC10M | Cisco 40GBASE-CR4 QSFP+ to 4 10GBASE-CU SFP+ direct-attach breakout cable, 10-meter, active |
| QSFP-H40G-CU1M | Cisco 40GBASE-CR4 QSFP+ direct-attach copper cable, 1-meter, passive |
| QSFP-H40G-CU3M | Cisco 40GBASE-CR4 QSFP+ direct-attach copper cable, 3-meter, passive |
| QSFP-H40G-CU5M | Cisco 40GBASE-CR4 QSFP+ direct-attach copper cable, 5-meter, passive |
| QSFP-H40G-ACU7M | Cisco 40GBASE-CR4 QSFP+ direct-attach copper cable, 7-meter, active |
| QSFP-H40G-ACU10M | Cisco 40GBASE-CR4 QSFP+ direct-attach copper cable, 10-meter, active |
| QSFP-4X10G-AOC1M | Cisco 40GBase-AOC QSFP to 4 SFP+ Active Optical breakout Cable, 1-meter |
| QSFP-4X10G-AOC2M | Cisco 40GBase-AOC QSFP to 4 SFP+ Active Optical breakout Cable, 2-meter |
| QSFP-4X10G-AOC3M | Cisco 40GBase-AOC QSFP to 4 SFP+ Active Optical breakout Cable, 3-meter |
| QSFP-4X10G-AOC5M | Cisco 40GBase-AOC QSFP to 4 SFP+ Active Optical breakout Cable, 5-meter |
| QSFP-4X10G-AOC7M | Cisco 40GBase-AOC QSFP to 4 SFP+ Active Optical breakout Cable, 7-meter |
| QSFP-4X10G-AOC10M | Cisco 40GBase-AOC QSFP to 4 SFP+ Active Optical breakout Cable, 10-meter |
| QSFP-H40G-AOC1M | Cisco 40GBase-AOC QSFP direct-attach Active Optical Cable, 1-meter |
| QSFP-H40G-AOC2M | Cisco 40GBase-AOC QSFP direct-attach Active Optical Cable, 2-meter |
| QSFP-H40G-AOC3M | Cisco 40GBase-AOC QSFP direct-attach Active Optical Cable, 3-meter |
| QSFP-H40G-AOC5M | Cisco 40GBase-AOC QSFP direct-attach Active Optical Cable, 5-meter |
| QSFP-H40G-AOC7M | Cisco 40GBase-AOC QSFP direct-attach Active Optical Cable, 7-meter |
| QSFP-H40G-AOC10M | Cisco 40GBase-AOC QSFP direct-attach Active Optical Cable, 10-meter |
| Power Cords | |
| CAB-250V-10A-AR | AC Power Cord - 250V, 10A - Argentina (2.5 meter) |
| CAB-9K10A-AU | Power Cord, 250VAC 10A 3112 Plug, Australia (2.5 meter) |
| CAB-250V-10A-BR | AC Power Cord - 250V, 10A - Brazil (2.1 meter) |
| CAB-250V-10A-CN | AC Power Cord - 250V, 10A - PRC (2.5 meter) |

| Part Number | Description |
|---------------------------|---|
| CAB-9K10A-EU | Power Cord, 250VAC 10A CEE 7/7 Plug, EU (2.5 meter) |
| CAB-IND-10A | 10A Power cable for India (2.5 meter) |
| CAB-250V-10A-IS | AC Power Cord - 250V, 10A - Israel (2.5 meter) |
| CAB-9K10A-IT | Power Cord, 250VAC 10A CEI 23-16/VII Plug, Italy (2.5 meter) |
| CAB-250V-10A-ID | AC Power Cord - 250V, 10A, South Africa (2.5 meter) |
| CAB-9K10A-SW | Power Cord, 250VAC 10A MP232 Plug, SWITZ (2.5 meter) |
| CAB-9K10A-UK | Power Cord, 250VAC 10A BS1363 Plug (13 A fuse), UK (2.5 meter) |
| CAB-9K12A-NA | Power Cord, 125VAC 13A NEMA 5-15 Plug, North America (2.5 meter) |
| CAB-AC-250V/13A | North America, NEMA L6-20 250V/20A plug-IEC320/C13 receptacle (2.0 meter) |
| CAB-N5K6A-NA | Power Cord, 200/240V 6A North America (2.5 meter) |
| CAB-C13-CBN | Cabinet Jumper Power Cord, 250 VAC 10A, C14-C13 Connectors (0.7 meter) |
| CAB-C13-C14-2M | Power Cord Jumper, C13-C14 Connectors, 2 Meter Length (2 meter) |
| CAB-C13-C14-AC | Power cord, C13 to C14 (recessed receptacle), 10A (3 meter) |
| Accessory Kit | |
| N6K-C6001-ACC-KIT= | Cisco Nexus 6001 Chassis Accessory Kit, spare |

Warranty

The Cisco Nexus 6001 has a 1-year limited hardware warranty. The warranty includes hardware replacement with a 10-day turnaround from receipt of a return materials authorization (RMA).

Service and Support

Cisco offers a wide range of services to help accelerate your success in deploying and optimizing the Cisco Nexus 6001 in your data center. The innovative Cisco Services are delivered through a unique combination of people, processes, tools, and partners and are focused on helping you increase operation efficiency and improve your data center network. Cisco Advanced Services uses an architecture-led approach to help you align your data center infrastructure with your business goals and achieve long-term value. Cisco SMARTnet[®] Service helps you resolve mission-critical problems with direct access at any time to Cisco network experts and award-winning resources. With this service, you can take advantage of the Cisco Smart Call Home service capability, which offers proactive diagnostics and real-time alerts on your Cisco Nexus 6001 Switch. Spanning the entire network lifecycle, Cisco Services offerings help increase investment protection, optimize network operations, support migration operations, and strengthen your IT expertise.

Cisco Capital Financing to Help You Achieve Your Objectives

Cisco Capital[®] financing can help you acquire the technology you need to achieve your objectives and stay competitive. We can help you reduce capital expenditures (CapEx), accelerate your growth, and optimize your investment dollars and ROI. Cisco Capital financing gives you flexibility in acquiring hardware, software, services, and complementary third-party equipment. And there's just one predictable payment. Cisco Capital financing is available in more than 100 countries. [Learn more.](#)

More Information

- Cisco Nexus 6000 Series Switches: <http://www.cisco.com/go/nexus6000>
- Cisco Nexus 2000 Series Fabric Extenders: <http://www.cisco.com/go/nexus2000>
- Cisco NX-OS Software: <http://www.cisco.com/go/nxos>




Americas Headquarters
Cisco Systems, Inc.
San Jose, CA

Asia Pacific Headquarters
Cisco Systems (USA) Pte. Ltd.
Singapore

Europe Headquarters
Cisco Systems International BV Amsterdam,
The Netherlands

Cisco has more than 200 offices worldwide. Addresses, phone numbers, and fax numbers are listed on the Cisco Website at www.cisco.com/go/offices.

 Cisco and the Cisco logo are trademarks or registered trademarks of Cisco and/or its affiliates in the U.S. and other countries. To view a list of Cisco trademarks, go to this URL: www.cisco.com/go/trademarks. Third party trademarks mentioned are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (1110R)