

# Troubleshoot CUIC User Collection Permissions

## Contents

[Introduction](#)

[CUIC User Collection Permissions](#)

[Check Permissions in CUIC Web Page](#)

[Check Permissions in CUIC Database](#)

## Introduction

This document describes troubleshoot process for user permissions in Cisco Unified Intelligence Center (CUIC) server.

## CUIC User Collection Permissions

A typical CUIC issue is that a particular user cannot see collections or value lists to which the user has permissions.

### Check Permissions in CUIC Web Page

In this example, a user **cuicu1** has execute permission for Tech collection. Check the permissions configured for the user.

The screenshot shows the CUIC web interface with two main panels: 'Assigned Group Permissions' and 'Assigned User Permissions'.

**Assigned Group Permissions:** Shows 'Collections' selected under 'Permissions For'. A dropdown menu shows 'Collections'. A search bar is present. A list box contains items: Agents.ALL Agents, Agents.Sales, and Agents.Tech, with Agents.Tech selected.

**Assigned User Permissions:** Shows a 'User List' with the following details:

User Name
ADMINISTRATOR\administrator
<b>ADMINISTRATOR\cuicu1</b> (highlighted)
ADMINISTRATOR\cuicu2
CUIC\agentproxy
CUIC\ayankovs
CUIC\ccmadmin

**User permissions for selected item:** Shows the permissions for ADMINISTRATOR\cuicu1:

User name	Exec	Write
ADMINISTRATOR\cuicu1	✓	
* CUIC\ccmadmin	✓	✓

\* indicates the owner of the selected item.

The same user **cui1cu1** belongs to a group **admin\_custom** that has permission to **Sales** collection.

The screenshot shows the 'Assigned Group Permissions' interface. On the left, under 'Permissions For:' is a dropdown set to 'Collections' and a search bar. Below it is a tree view of collections: 'Agents.ALL Agents' expanded, showing 'Agents.Sales' (selected) and 'Agents.Tech'. A 'Set Permissions' button is below the tree. To the right is a list of 'All Groups' with a search bar. 'admin\_custom' is selected. Below that is a list of 'All Users for the selected group' with 'ADMINISTRATOR\cui1cu1' selected. A note at the bottom says '\* indicates the default group.'

As a result, when the user runs a report there are two collections available in the list: **Sales** and **Tech**.

The screenshot shows the 'Choose Filter' dialog. It includes a 'Parameters' section, a 'Date and Time\*' section with a date range from 'Today' to '11:59:59 PM', a 'Time Range' section with options for 'All Day' or 'Custom' and specific times, and an 'Agent Names\*' section where 'Sales' and 'Tech' are listed under 'Available' and none are listed under 'Selected'. A 'Run' button is at the bottom right.

## Check Permissions in CUIC Database

The same information can be verified from the database.

### Step 1. Get user groups.

```
admin:run sql SELECT gm.memberid,u.name,gm.groupid,g.name FROM cuic_data:cuicgroupmember gm \
INNER JOIN cuic_data:cuicuser u ON u.id==gm.memberid INNER JOIN cuic_data:cuicgroup g ON
g.id==gm.groupid WHERE u.name LIKE '%cuicul%'

memberid name groupid name
=====
=====

F7DB93871000015C000001E0A302F8E ADMINISTRATOR\cuicul 22222222222222222222222222222222AAAA AllUsers
F7DB93871000015C000001E0A302F8E ADMINISTRATOR\cuicul 7CA0F8121000015C000003DE0A302F8E
admin_custom
```

The combined permissions list for this user is consists of three entires: 1st for the user itself, 2nd and 3rd for the group the user **admin\_custom** belongs to. These values are used in the next queries.

```
admin:run sql SELECT gm.memberid,u.name,gm.groupid,g.name FROM cuic_data:cuicgroupmember gm \
INNER JOIN cuic_data:cuicuser u ON u.id==gm.memberid INNER JOIN cuic_data:cuicgroup g ON
g.id==gm.groupid WHERE u.name LIKE '%cuicul%'

memberid name groupid name
=====
=====

F7DB93871000015C000001E0A302F8E ADMINISTRATOR\cuicul 22222222222222222222222222222222AAAA AllUsers
F7DB93871000015C000001E0A302F8E ADMINISTRATOR\cuicul 7CA0F8121000015C000003DE0A302F8E
admin_custom
```

### Step 2. Get all permissions for this user and his groups for the collections.

```
admin:run sql SELECT ca.usergroupid user_or_groupid,ca.collectionid,c.name collection FROM
cuic_data:cuiccollectionauth ca \
INNER JOIN cuic_data:cuiccollection c ON c.id==ca.collectionid \
WHERE ca.usergroupid IN
('F7DB93871000015C000001E0A302F8E','22222222222222222222222222222222AAAA','7CA0F8121000015C000003DE
0A302F8E')

user_or_groupid collectionid collection
=====
=====

F7DB93871000015C000001E0A302F8E EA6464501000015D000007A0A302F8E Tech
7CA0F8121000015C000003DE0A302F8E EA6420C11000015D00000750A302F8E Sales
```

The list of collections from the output in the step 2 should match the list the user can see in the CUIC web page. Also the output from the database must be the same on all of the nodes in CUIC cluster.

In case an inconsistency in permissions is found please contact Cisco TAC support.