Password Recovery Procedure for the ASA Security Services Modules AIP–SSM and CSC–SSM

Document ID: 82109

Contents

Introduction Prerequisites Requirements Related Products Conventions Step-by-Step Procedure Sample Procedure Related Information Introduction

This document describes how to recover a password on a Cisco ASA 5500 Series Content Security and Control Security Services Module (CSC–SSM) or the Advanced Inspection and Prevention Security Services Module (AIP–SSM) without the need to re–image the device.

Prerequisites

Requirements

A list of additional files that you need for the recovery procedure is required. This includes an explanation of how and where to get the files and any processing that needs to happen before the recovery procedure begins.

Cisco ASA 8.x and later software provides a mechanism to reset the passwords of the SSM modules (CSC or AIP) without the need to re–image the device.

Note: The CSC and AIP modules must run version 6.0 in order for the feature to work. There is no option for password recovery in version 5.0 for the AIP–SSM or CSC–SSM, because this feature is not introduced until version 6.0.

Related Products

This password recovery procedure can be used for any of these products:

- Advanced Inspection and Prevention Security Services Module (AIP–SSM)
- Content Security and Control Security Services Module (CSC-SSM)

Conventions

Refer to Cisco Technical Tips Conventions for more information on document conventions.

Step-by-Step Procedure

This step is necessary in order to complete the password recovery.

Issue the **hw–module module <module_num> password–reset** command from the Cisco ASA CLI. For the AIP module, this command sets the configuration register in ROMMON to cause a boot of the password reset image and then power cycles the module. For the CSC module, this command sends the **session 1 do reset–password** command to the module.

ciscoasa(config)#hw-module module 1 password-reset
Reset the password on module in slot 1? [confirm]

Sample Procedure

This procedure shows how to recover the password with the Cisco Adaptive Security Device Manager (ASDM).

📫 Cisco ASDM						
file yew Icols tielp			Search		Find -	ahaha
Gowmand Line Interface Show Commands Ignored by ASDM on Device	? Help					cisco
Home Pig Device In Incoroute	1	Interface Statu				10
General 125 Password Reset		Interface	IP Address/Mask	Line	Link	Kbps
Host Nam Preferences ASA Vess ASDM Java Console ASDM Vession: 5.3(0)72 Device Type: ASA 5521	m 30s	inside outside testin/2	10.0 54.22/24 10.0 55.22/24 10.0 56.2/24	0 up 0 up	G up G up G up	1 0 0
Firewal Mode: Routed Context Mode: Single Total Memory: 1024 MB	,	Select an interfa	ce to view input and output K	Upps-		
-VPN Status		Traffic Status				
IKE Tunnels: 0 WebVPN Tunnels: 0 SVC Tur	nnels: 0	-Connections Per	Second Usage			
- System Resources Status CPU - CPU Urage (percent) 100		3 · · · · · · · · · · · · · · · · · · ·				
31.8. 50		16:49:17	16:51:02	16:	52:47	16:54:11
165422 164917 165102 185	2.47 1854:11	UDP: 0	and the second	Totał 0		
	10:34:11		Traffic Usage (Kbps)			
Memory - Memory Usage (MB)		3.635.063				
220148 512		0 16:49:17	16.51.02	16:	52:47	16:54:11
Undest ASDM Syslog Messages	I see a second					009×
ASDM logging is d	sabled.To enable ASDM logg	ing with informational le ble Logging	rvel, dick the button below.			
		tes	er 2	🖬 👪	8/11	/04 3:54:22 PM UT0

1. For the AIP-SSM, click Tools on the main menu, and select IPS Password Reset.

2. For the CSC–SSM, click Tools on the main menu, and select CSC Password Reset.

Commend Line Interface Schwid Commands [gaored by ASDM on Device. Beelantication Schwid Commands [gaored by ASDM on Device. 9 dod Add 9 dod Content Security M Freewall Dathboard 9 dod Content Mode: CSC Dessended Reset Add Benory 266 KB 9 dod Content Mode: CSC Dessended Reset Web/PM Turnel:: 0 9 dod Subcod Benory CSC Dessended Reset Web/PM Turnel:: 0 9 dod Subcod Benory Content Security Free Social Usage 9 dod Subcod Benory Subsch Turneli:: 0 9 dod <th>🖆 Cisco ASDM</th> <th></th> <th></th> <th></th> <th>0</th> <th></th> <th></th> <th>land -</th> <th></th>	🖆 Cisco ASDM				0			land -	
Add Packet Trace Pig Toporoute Pig Toporoute To		Command Line Interface		Search Search Forward ? Hep				cisco	
ASDM logging is disabled. To enable ASDM logging with informational level, click the button below. Enable Logging	🗣 Add 👔 	Packet Tracer Pbp Traceroute File Management Upgrade Software Upgrade Software Upgrade Image from CCO Upland ASDM Assistant Guide System Belood CSC Passeord Reset Administrator's Alerts Preferences ASDM Java Console	Content Sec	ice Upines Ud Oh Om 47s ice Type: ASA 5510 eed Mode: Single al Memoy: 256 MB mele: 0 SVC Tunnels:	Interface inside outside Select an inter Connections P Connections P Connections P T7:18-45 UDP -founded Interfa Ast,663 17:18-45	IP Addess Mask 10.11.11.1/24 192.169.1.6/24 face to view input and out or Second Usage Please TCP: TCP: Please Please Please	e mat.	O up	7270126

Related Information

- Cisco ASA 5500 Series Adaptive Security Appliances Support
- Cisco ASA Advanced Inspection and Prevention (AIP) Module
- Cisco ASA Content Security and Control (CSC) Security Services Module
- Technical Support & Documentation Cisco Systems

Contacts & Feedback | Help | Site Map

© 2013 – 2014 Cisco Systems, Inc. All rights reserved. Terms & Conditions | Privacy Statement | Cookie Policy | Trademarks of Cisco Systems, Inc.

Updated: Jun 25, 2007

Document ID: 82109