



Supported Packages and System Requirements

- [Memory Requirements, on page 1](#)
- [Hardware Supported, on page 1](#)
- [Determining the Software Version, on page 1](#)

Memory Requirements



Note Memory is not configurable for the Cisco Remote PHY Shelf 7200 Software 1.3.

Table 1: Memory Recommendations for the Cisco Remote PHY Shelf 7200 Software 1.3

Feature Set	Cisco RPHY Processor	Software Image	Fixed Memory	Runs From
FCC	LS1043A	HA-SHELF-V1-3.itb	2GB	Bootflash:
RPD LC	LS1088	HA-SHELF-V1-3.itb	8GB	Bootflash:

Hardware Supported

For information about the supported hardware on Cisco Remote PHY Shelf 7200 Software 1.3 and its maintenance releases, see:

http://www.cisco.com/c/en/us/td/docs/cable/cbr/installation/guide/b_cbr_how_and_what_to_order.html.

Determining the Software Version

To determine the version of the Cisco Remote PHY Shelf 7200 Software 1.3 running on your Cisco Remote PHY Shelf 7200 device from FCC, LC, eRPD, and CMTS, log in and enter the **show version** EXEC command:

```
HA-Shelf-FCC#show version
```

```
Cisco HA-Shelf Software, version v1.3, build by HA-Shelf-release, on 2020-12-15 09:36:33
Branch information:
FCC branch: (HEAD detached at HA-SHELF_V1_3_20201215)
OpenRPD branch: (HEAD detached at HA-SHELF_V1_3_20201215)
```

```
Slot-1#show version
Cisco HA-Shelf Software, version v1.3, build by HA-Shelf-release, on 2020-12-15 09:36:34
Branch information:
Linecard branch: (HEAD detached at HA-SHELF_V1_3_20201215)
OpenRPD branch: (HEAD detached at HA-SHELF_V1_3_20201215)
```

```
eRPD-5/1#show version
Cisco HA-Shelf Software, version v1.3, build by HA-Shelf-release, on 2020-12-15 09:36:34
Branch information:
Linecard branch: (HEAD detached at HA-SHELF_V1_3_20201215)
OpenRPD branch: (HEAD detached at HA-SHELF_V1_3_20201215)
```

```
GMM#show cable rpd badb.ad17.60c1 sw-version
Load for five secs: 22%/4%; one minute: 26%; five minutes: 26%
Time source is NTP, 15:58:23.873 CST Mon Dec 21 2020
```

```
RPD ID          SwVersion
badb.ad17.60c1 v1.3
```