



Tech Support

- [Tech Support and System Logs, on page 1](#)
- [Downloading System Logs, on page 2](#)
- [Streaming System Logs to External Analyzer, on page 2](#)

Tech Support and System Logs

Nexus Dashboard Orchestrator system logging is automatically enabled when you first deploy the Orchestrator cluster and captures the events and faults that occur in the environment.

You can choose to download the logs at any time or stream them to an external log analyzer, such as Splunk, if you want to use additional tools to quickly parse, view, and respond to important events without a delay.

Starting with Release 3.3(1), the tech support logs are split into two parts:

- Original database backup files containing the same information as in prior releases
- JSON-based database backup for ease of readability

Within each backup archive, you will find the following contents:

- `x.x.x.x`—one or more files in `x.x.x.x` format for container logs available at the time of the backup.
- `msc-backup-<date>_temp`—Original database backup containing the same information as previous releases.
- `msc-db-json-<date>_temp`—Backup contents in JSON format.

For example:


```
msc_anpEpgRels.json
msc_anpExtEpgRels.json
msc_asyncExecutionStatus.json
msc_audit.json
msc_backup-versions.json
msc_backupRecords.json
msc_ca-cert.json
msc_cloudSecStatus.json
msc_consistency.json
...
```

Downloading System Logs

This section describes how to generate a troubleshooting report and infrastructure logs file for all the schemas, sites, tenants, and users that are managed by Nexus Dashboard Orchestrator.

Step 1 Log in to your Nexus Dashboard Orchestrator GUI.

Step 2 Open the **System Logs** screen.



- In the main menu, select **Operations** > **Tech Support**.
- In the top right corner of the **System Logs** frame, click the edit button.

Step 3 Click **Download** download the logs.

An archive will be downloaded to your system. Containing all the information as described in the first section of this chapter.

Streaming System Logs to External Analyzer

Nexus Dashboard Orchestrator allows you to send the Orchestrator logs to an external log analyzer tool in real time. By streaming any events as they are generated, you can use the additional tools to quickly parse, view, and respond to important events without a delay.

This section describes how to enable Nexus Dashboard Orchestrator to stream its logs to an external analyzer tool, such as Splunk or syslog.

Before you begin

- This release supports only Splunk and `syslog` as external log analyzer.
- This release supports `syslog` only for Nexus Dashboard Orchestrator in Nexus Dashboard deployments.
- This release supports up to 5 external servers.

- If using Splunk, set up and configure the log analyzer service provider.


For detailed instructions on how to configure an external log analyzer, consult its documentation.

- If using Splunk, obtain an authentication token for the service provider.

Obtaining an authentication token for Splunk service is detailed in the Splunk documentation, but in short, you can get the authentication token by logging into the Splunk server, selecting **Settings > Data Inputs > HTTP Event Collector**, and clicking **New Token**.


Step 1 Log in to your Nexus Dashboard Orchestrator GUI.

Step 2 Open the **System Logs** screen.



- In the main menu, select **Operations > Tech Support**.
- In the top right corner of the **System Logs** frame, click the edit button.

Step 3 In the **System Logs** window, enable external streaming and add a server.



- Enable the **External Streaming** knob.
- Choose whether you want to stream **All Logs** or just the **Audit Logs**.

c) Click **Add Server** to add an external log analyzer server.

Step 4 Add a Splunk server.

If you do not plan to use Splunk service, skip this step.

The screenshot shows a configuration form for adding a server. The form has the following fields and elements:

- Select Service:** A dropdown menu with 'splunk' selected. A blue callout bubble with the number '1' points to the dropdown arrow.
- Protocol:** Two buttons, 'HTTP' (selected) and 'HTTPS'. A blue callout bubble with the number '2' points to the 'HTTPS' button.
- * Host:** A text input field containing '10.30.11.69'. A blue callout bubble with the number '3' points to the input field.
- * Port:** A text input field containing '8088'.
- * Token:** A text input field containing '2824ec94-fbce-4111-954f-e8df0c9cfcb5'.
- Checkmark icon:** A small checkmark icon in the top right corner, with a blue callout bubble containing the number '4' pointing to it.

a) Choose `splunk` for the server type.

b) Choose the protocol.

c) Provide the server name or IP address, port, and the authentication token you obtained from the Splunk service.

Obtaining an authentication token for Splunk service is detailed in the Splunk documentation, but in short, you can get the authentication token by logging into the Splunk server, selecting **Settings > Data Inputs > HTTP Event Collector**, and clicking **New Token**.

d) Click the checkmark icon to finish adding the server.

Step 5 Add a `syslog` server.

If you do not plan to use `syslog`, skip this step.

The screenshot shows a configuration form for adding a logging server. It includes the following fields and controls:

- Select Service:** A dropdown menu with 'syslog' selected. A blue callout '1' points to the dropdown arrow.
- Protocol:** Two radio buttons, 'TCP' (selected) and 'UDP'. A blue callout '2' points to the 'UDP' button.
- * Host:** A text input field containing '10.195.223.220'. A vertical blue line and callout '3' are positioned to the right of this field.
- * Port:** A text input field containing '514'.
- Severity:** A dropdown menu with 'Warning' selected. A blue callout '4' points to a checkmark icon in the top right corner of the form.

- Choose `syslog` for the server type.
- Choose the protocol.
- Provide the server name or IP address, port number, and the severity level of the log messages to stream.
- Click the checkmark icon to finish adding the server.

Step 6 Repeat the steps if you want to add multiple servers.

This release supports up to 5 external servers.

Step 7 Click **Save** to save the changes.

The screenshot shows the 'System Logs' configuration page. It includes the following elements:

- System Logs:** A header with a close button (X).
- Download Logs:** A 'Download' button.
- External Streaming:** A toggle switch that is currently turned off.
- Select Logs:** Two buttons, 'All Logs' (selected) and 'Audit Logs'.
- * Logging Servers:** A table listing configured servers.

Server Type	Protocol	Host	Port	
splunk	http	10.30.11.69	8088	✖
syslog	tcp	10.195.223.220	514	✖
- + Add Server:** A button to add a new server.
- SAVE:** A button to save the changes.

