



EEM Library Debug Command Extensions

Last Updated: November 17, 2011

- [cli_debug, page 1](#)
- [smtp_debug, page 1](#)

cli_debug

Prints a command-line interface (CLI) debug statement to syslog. This Tcl command extension is used to print a CLI debug statement to syslog if the **debug event manager tcl cli_library** Cisco IOS CLI command is in effect.

Syntax

```
cli_debug spec_string debug_string
```

Arguments

spec_string	(Mandatory) The spec_string argument is used to indicate the type of debug statement.
debug_string	(Mandatory) The debug_string argument is used to indicate the debugging text.

Result String

None

Set _cerrno

No

smtp_debug



Americas Headquarters:
Cisco Systems, Inc., 170 West Tasman Drive, San Jose, CA 95134-1706 USA

Prints a Simple Mail Transfer Protocol (SMTP) debug statement to syslog. This Tcl command extension prints a SMTP debug statement to syslog if the **debug event manager tcl smtp_library** Cisco IOS command-line interface (CLI) command is in effect.

Syntax

```
smtp_debug spec_string debug_string
```

Arguments

spec_string	(Mandatory) The spec_string argument is used to indicate the type of debug statement.
debug_string	(Mandatory) The debug_string argument is used to indicate the debugging text.

Result String

None

Set_cerrno

No

© 2011 Cisco Systems, Inc. All rights reserved.