



NAT Optimized SIP Media Path Without SDP

The NAT Optimized SIP Media Path Without SDP feature provides the ability to optimize the media path taken by a SIP VoIP session when NAT is used. NAT forces the VoIP traffic to take at least one extra hop in the network, which usually results in several additional hops being added to the path between two IP hosts.

The Message Digest 5 (MD5) algorithm is supported.

- [Information About the NAT Optimized SIP Media Path Without SDP Feature, on page 1](#)
- [How to Configure NAT Optimized SIP Media Path Without SDP, on page 2](#)
- [Configuration Examples for NAT Optimized SIP Media Path Without SDP, on page 3](#)
- [Additional References, on page 4](#)
- [Feature Information for NAT Optimized SIP Media Path Without SDP, on page 5](#)

Information About the NAT Optimized SIP Media Path Without SDP Feature

Benefits of NAT Optimized SIP Media Path Without SDP

- The media path can be shortened, decreasing voice delay.
- More control of voice policy is possible because the media path is closer to the customer domain and not deep within the service provider cloud.
- Processes all packets sent through the NAT-enabled router, even those without the Session Description Protocol (SDP).

NAT Optimized SIP Media Path Without SDP Feature Design

Cisco IOS NAT will add the relevant translation information per SIP session within the SIP protocol messages. The SIP Application Layer Gateway support within Cisco IOS NAT will extract this translation information from the SIP packets and create NAT table entries.

The “piggybacking” of NAT translation information within the SIP call flows, the design of how users interact with the application when they talk to it, will allow the media path of a SIP VoIP session between two calling parties to take the optimized routing path between each other.

How to Configure NAT Optimized SIP Media Path Without SDP

Configuring a NAT Optimized SIP Media Path Without SDP Messages Including MD5 Authentication

Perform this task to configure messages with a NAT optimized SIP Media path including MD5 authentication.

SUMMARY STEPS

1. **enable**
2. **configure terminal**
3. **ip nat piggyback-support sip-alg all-messages router *router-id* [md5-authentication *md5-authentication-key*]**

DETAILED STEPS

	Command or Action	Purpose
Step 1	enable Example: Router> enable	Enables privileged EXEC mode. <ul style="list-style-type: none"> • Enter your password if prompted.
Step 2	configure terminal Example: Router# configure terminal	Enters global configuration mode.
Step 3	ip nat piggyback-support sip-alg all-messages router <i>router-id</i> [md5-authentication <i>md5-authentication-key</i>] Example: Router(config)# ip nat piggyback-support sip-alg all-messages router 100 md5-authentication md5-key	Enables messages with a NAT optimized SIP Media path including MD5 authentication.

Configuring a NAT Optimized SIP Media Path Without SDP Messages

Perform this task to configure SDP messages with a NAT optimized SIP Media path without MD5 authentication.

SUMMARY STEPS

1. **enable**
2. **configure terminal**
3. **ip nat piggyback-support sip-alg all-messages router *router-id***

DETAILED STEPS

	Command or Action	Purpose
Step 1	enable Example: <pre>Router> enable</pre>	Enables privileged EXEC mode. <ul style="list-style-type: none"> • Enter your password if prompted.
Step 2	configure terminal Example: <pre>Router# configure terminal</pre>	Enters global configuration mode.
Step 3	ip nat piggyback-support sip-alg all-messages router <i>router-id</i> Example: <pre>Router(config)# ip nat piggyback-support sip-alg all-messages router 100</pre>	Enables messages with a NAT optimized SIP Media path without MD5 authentication.

Configuration Examples for NAT Optimized SIP Media Path Without SDP

Configuring a NAT Optimized SIP Media Path Without SDP Including MD5 Authentication Example

The following example shows how to configure a NAT optimized SIP media path without SDP including MD5 authentication:

```
ip nat piggyback-support sip-alg all-messages router 100 md5-authentication md5-key
```

Configuring a NAT Optimized SIP Media Path Without SDP or MD5 Authentication Example

The following example shows how to configure a NAT optimized SIP media path without SDP or MD5 authentication:

```
ip nat piggyback-support sip-alg all-messages router 100
```

Additional References

Related Documents

Related Topic	Document Title
Cisco IOS commands	Cisco IOS Master Commands List, All Releases
NAT commands: complete command syntax, command mode command history, defaults, usage guidelines, and examples	Cisco IOS IP Addressing Services Command Reference
Application-level gateways	<i>Using Application Level Gateways with NAT</i> module
IP access list sequence numbering	IP Access List Sequence Numbering document
NAT-on-a-Stick technology note	Network Address Translation on a Stick technology note
NAT maintenance	<i>Monitoring and Maintaining NAT</i> module
RADIUS attributes overview	<i>RADIUS Attributes Overview and RADIUS IETF Attributes</i> module
Using HSRP and stateful NAT for high availability	<i>Configuring NAT for High Availability</i> module
Using NAT with MPLS VPNs	<i>Integrating NAT with MPLS VPNs</i> module

Standards and RFCs

Standard/RFC	Title
RFC 1597	Internet Assigned Numbers Authority
RFC 1631	The IP Network Address Translation (NAT)
RFC 1918	Address Allocation for Private Internets
RFC 2663	IP Network Address Translation (NAT) Terminology and Considerations
RFC 3022	Traditional IP Network Address Translation (Traditional NAT)

Technical Assistance

Description	Link
The Cisco Support and Documentation website provides online resources to download documentation, software, and tools. Use these resources to install and configure the software and to troubleshoot and resolve technical issues with Cisco products and technologies. Access to most tools on the Cisco Support and Documentation website requires a Cisco.com user ID and password.	http://www.cisco.com/cisco/web/support/index.html

Feature Information for NAT Optimized SIP Media Path Without SDP

The following table provides release information about the feature or features described in this module. This table lists only the software release that introduced support for a given feature in a given software release train. Unless noted otherwise, subsequent releases of that software release train also support that feature.

Use Cisco Feature Navigator to find information about platform support and Cisco software image support. To access Cisco Feature Navigator, go to www.cisco.com/go/cfn. An account on Cisco.com is not required.

Table 1: Feature Information for NAT Optimized SIP Media Path Without SDP

Feature Name	Releases	Feature Information
NAT Optimized SIP Media Path Without SDP	12.4(2)T	The NAT Optimized SIP Media Path Without SDP feature provides the ability to optimize the media path taken by a SIP VoIP session when NAT is used. NAT forces the VoIP traffic to take at least one extra hop in the network, which usually results in several additional hops being added to the path between two IP hosts.

