

OSPFv3 Demand Circuit Ignore

This feature enables you to prevent an interface from accepting demand-circuit requests from other devices by specifying the ignore keyword in the **ipv6 ospf demand-circuit** command.

- Finding Feature Information, page 1
- Information About OSPFv3 Demand Circuit Ignore, page 1
- How to Configure OSPFv3 Demand Circuit Ignore, page 2
- Configuration Examples for OSPFv3 Demand Circuit Ignore, page 3
- Additional References for OSPFv3 Demand Circuit Ignore, page 3
- Feature Information for OSPFv3 Demand Circuit Ignore, page 4

Finding Feature Information

Your software release may not support all the features documented in this module. For the latest caveats and feature information, see Bug Search Tool and the release notes for your platform and software release. To find information about the features documented in this module, and to see a list of the releases in which each feature is supported, see the feature information table.

Use Cisco Feature Navigator to find information about platform support and Cisco software image support. To access Cisco Feature Navigator, go to www.cisco.com/go/cfn. An account on Cisco.com is not required.

Information About OSPFv3 Demand Circuit Ignore

Demand Circuit Ignore Support

Demand Circuit Ignore Support enables you to prevent an interface from accepting demand-circuit requests from other devices by specifying the ignore keyword in the **ipv6 ospf demand-circuit** command. Demand circuit ignore instructs the router not to accept Demand Circuit (DC) negotiation and is a useful configuration option on the point-to-multipoint interface of the Hub router.

1

How to Configure OSPFv3 Demand Circuit Ignore

Configuring Demand Circuit Ignore Support for OSPFv3

SUMMARY STEPS

- 1. enable
- 2. configure terminal
- **3.** interface type number
- 4. Enter one of the following commands:
 - ipv6 ospf demand-circuit ignore
 - ospfv3 demand-circuit ignore
- 5. end
- 6. show ospfv3 process-id [area-id] [address-family] [vrf {vrf-name |* }] interface [type number] [brief]

	Command or Action	Purpose	
Step 1	enable	Enables privileged EXEC mode.	
	Example:	• Enter your password if prompted.	
	Device> enable		
Step 2	configure terminal	Enters global configuration mode.	
	Example:		
	Device# configure terminal		
Step 3	interface type number	Configures an interface type and number and enters interface configuration mode.	
	Example:	-	
	Device(config) # interface GigabitEthernet 0/1/0		
Step 4	Enter one of the following commands:	Prevents an interface from accepting demand-circu	
	 ipv6 ospf demand-circuit ignore 	requests from other devices.	
	 ospfv3 demand-circuit ignore 		

DETAILED STEPS

	Command or Action	Purpose
	Example: Device(config-if)# ipv6 ospf demand-circuit ignore	
	Example: Device (config-if) # ospfv3 demand-circuit ignore	
Step 5	end	Returns to privileged EXEC mode.
	Example:	
	<pre>Device(config-if) # end</pre>	
Step 6	<pre>show ospfv3 process-id [area-id] [address-family] [vrf {vrf-name * }] interface [type number] [brief]</pre>	(Optional) Displays OSPFv3-related interface information.
	Example:	
	Device# show ospfv3 interface GigabitEthernet 0/1/0	

Configuration Examples for OSPFv3 Demand Circuit Ignore

Example: Demand Circuit Ignore Support for OSPFv3

The following example shows how to configure demand circuit ignore support for OSPFv3:

```
interface Serial0/0
ip address 6.1.1.1 255.255.255.0
ipv6 enable
ospfv3 network point-to-multipoint
ospfv3 demand-circuit ignore
ospfv3 1 ipv6 area 0
```

Additional References for OSPFv3 Demand Circuit Ignore

The following sections provide references related to the OSPFv3 Demand Circuit Ignore feature.

Related Documents

Related Topic	Document Title	
OSPF configuration tasks	"Configuring OSPF"	

Related Topic	Document Title	
OSPF commands	Cisco IOS IP Routing: OSPF Command Reference	
Cisco IOS commands	Cisco IOS Master Command List, All Releases	

Technical Assistance

Description	Link
The Cisco Support and Documentation website provides online resources to download documentation, software, and tools. Use these resources to install and configure the software and to troubleshoot and resolve technical issues with Cisco products and technologies. Access to most tools on the Cisco Support and Documentation website requires a Cisco.com user ID and password.	

Feature Information for OSPFv3 Demand Circuit Ignore

The following table provides release information about the feature or features described in this module. This table lists only the software release that introduced support for a given feature in a given software release train. Unless noted otherwise, subsequent releases of that software release train also support that feature.

Use Cisco Feature Navigator to find information about platform support and Cisco software image support. To access Cisco Feature Navigator, go to www.cisco.com/go/cfn. An account on Cisco.com is not required.

Feature Name	Releases	Feature Information
OSPFv3 Demand Circuit Ignore	Cisco IOS XE Release 3.8	The OSPFv3 Demand Circuit Ignore feature enables you to prevent an interface from accepting demand-circuit requests from other devices by specifying the ignore keyword in the ipv6 ospf demand-circuit command. The following commands were introduced or modified: • ipv6 ospf demand-circuit • ospfv3 demand-circuit

Table 1: Feature Information for OSPFv3 Demand Circuit Ignore