



IPv6 Commands: ipv6 mo to ipv6 ospf da

- [ipv6 mobile home-agent \(global configuration\)](#), on page 4
- [ipv6 mobile home-agent \(interface configuration\)](#), on page 5
- [ipv6 mobile router](#), on page 7
- [ipv6 mobile router-service roam](#), on page 8
- [ipv6 mode host unicast](#), on page 9
- [ipv6 mtu](#), on page 10
- [ipv6 multicast aaa account receive](#), on page 12
- [ipv6 multicast boundary](#), on page 13
- [ipv6 multicast group-range](#), on page 15
- [ipv6 multicast limit](#), on page 17
- [ipv6 multicast limit cost](#), on page 19
- [ipv6 multicast limit rate](#), on page 21
- [ipv6 multicast multipath](#), on page 22
- [ipv6 multicast pim-passive-enable](#), on page 23
- [ipv6 multicast-routing](#), on page 24
- [ipv6 multicast rpf](#), on page 26
- [ipv6 nat](#), on page 28
- [ipv6 nat max-entries](#), on page 29
- [ipv6 nat prefix](#), on page 30
- [ipv6 nat prefix v4-mapped](#), on page 32
- [ipv6 nat translation](#), on page 33
- [ipv6 nat v4v6 pool](#), on page 35
- [ipv6 nat v4v6 source](#), on page 37
- [ipv6 nat v6v4 pool](#), on page 39
- [ipv6 nat v6v4 source](#), on page 41
- [ipv6 nd advertisement-interval](#), on page 44
- [ipv6 nd autoconfig default-router](#), on page 45
- [ipv6 nd autoconfig prefix](#), on page 46
- [ipv6 nd cache expire](#), on page 47
- [ipv6 nd cache interface-limit \(global\)](#), on page 48
- [ipv6 nd cache interface-limit \(interface\)](#), on page 49
- [ipv6 nd dad attempts](#), on page 51
- [ipv6 nd dad-proxy](#), on page 55

- [ipv6 nd dad time](#), on page 56
- [ipv6 nd host mode strict](#), on page 57
- [ipv6 nd inspection](#), on page 58
- [ipv6 nd inspection policy](#), on page 60
- [ipv6 nd managed-config-flag](#), on page 62
- [ipv6 nd na glean](#), on page 64
- [ipv6 nd ns-interval](#), on page 65
- [ipv6 nd nud retry](#), on page 67
- [ipv6 nd other-config-flag](#), on page 69
- [ipv6 nd prefix](#), on page 71
- [ipv6 nd prefix framed-ipv6-prefix](#), on page 75
- [ipv6 nd prefix-advertisement](#), on page 76
- [ipv6 nd ra dns server](#), on page 78
- [ipv6 nd ra interval](#), on page 79
- [ipv6 nd ra lifetime](#), on page 81
- [ipv6 nd ra solicited unicast](#), on page 82
- [ipv6 nd ra suppress](#), on page 83
- [ipv6 nd rguard](#), on page 85
- [ipv6 nd rguard attach-policy](#), on page 86
- [ipv6 nd rguard policy](#), on page 88
- [ipv6 nd reachable-time](#), on page 90
- [ipv6 nd resolution data limit](#), on page 92
- [ipv6 nd route-owner](#), on page 93
- [ipv6 nd router-preference](#), on page 94
- [ipv6 nd secured certificate-db](#), on page 96
- [ipv6 nd secured full-secure](#), on page 97
- [ipv6 nd secured full-secure \(interface\)](#), on page 98
- [ipv6 nd secured key-length](#), on page 99
- [ipv6 nd secured sec-level](#), on page 100
- [ipv6 nd secured timestamp](#), on page 101
- [ipv6 nd secured timestamp-db](#), on page 102
- [ipv6 nd secured trustanchor](#), on page 103
- [ipv6 nd secured trustpoint](#), on page 104
- [ipv6 nd suppress attach-policy](#), on page 105
- [ipv6 nd suppress policy](#), on page 107
- [ipv6 neighbor](#), on page 108
- [ipv6 neighbor binding](#), on page 110
- [ipv6 neighbor binding down-lifetime](#), on page 112
- [ipv6 neighbor binding interface](#), on page 113
- [ipv6 neighbor binding logging](#), on page 115
- [ipv6 neighbor binding max-entries](#), on page 116
- [ipv6 neighbor binding stale-lifetime](#), on page 118
- [ipv6 neighbor binding vlan](#), on page 119
- [ipv6 neighbor tracking](#), on page 121
- [ipv6 next-hop-self eigrp](#), on page 122
- [ipv6 nhrp authentication](#), on page 124

- [ipv6 nhrp cache non-authoritative](#), on page 125
- [ipv6 nhrp holdtime](#), on page 126
- [ipv6 nhrp interest](#), on page 127
- [ipv6 nhrp map](#), on page 128
- [ipv6 nhrp map multicast](#), on page 130
- [ipv6 nhrp map multicast dynamic](#), on page 131
- [ipv6 nhrp max-send](#), on page 133
- [ipv6 nhrp multicast](#), on page 135
- [ipv6 nhrp network-id](#), on page 136
- [ipv6 nhrp nhs](#), on page 137
- [ipv6 nhrp record](#), on page 139
- [ipv6 nhrp redirect](#), on page 140
- [ipv6 nhrp registration](#), on page 141
- [ipv6 nhrp resolution refresh base](#), on page 143
- [ipv6 nhrp responder](#), on page 145
- [ipv6 nhrp send-routed](#), on page 146
- [ipv6 nhrp server-only](#), on page 147
- [ipv6 nhrp shortcut](#), on page 148
- [ipv6 nhrp trigger-svc](#), on page 149
- [ipv6 nhrp use](#), on page 150
- [ipv6 ospf area](#), on page 152
- [ipv6 ospf authentication](#), on page 154
- [ipv6 ospf bfd](#), on page 156
- [ipv6 ospf cost](#), on page 158
- [ipv6 ospf database-filter all out](#), on page 161

ipv6 mobile home-agent (global configuration)

To enter home agent configuration mode, use the **ipv6 mobile home-agent** command in global configuration mode. To reset to the default settings of the command, use the **no** form of this command.

ipv6 mobile home-agent
no ipv6 mobile home-agent

Syntax Description This command has no arguments or keywords.

Command Default Mobile IPv6 home agent is disabled.

Command Modes
 Global configuration

Release	Modification
12.3(14)T	This command was introduced.

Usage Guidelines Use the **ipv6 mobile home-agent** command to enter home agent configuration mode. Once in home agent configuration mode, you can configure binding parameters using the **binding** command. Once an interface is configured to provide the home-agent service, the **ipv6 mobile home-agent** global configuration command automatically appears in the global configuration.

The home agent service needs to be started on each interface using the **ipv6 mobile home-agent** command in interface configuration mode. The **ipv6 mobile home-agent** command in global configuration mode does not start home agent service on an interface.

Examples In the following example, the user enters home agent configuration mode:

```
Router(config)# ipv6 mobile home-agent
Router(config-ha)#
```

Command	Description
binding	Configures binding options for the Mobile IPv6 home agent feature in home agent configuration mode.
ipv6 mobile home-agent (interface configuration)	Initializes and starts the Mobile IPv6 home agent on a specific interface.
show ipv6 mobile globals	Displays global Mobile IPv6 parameters.

ipv6 mobile home-agent (interface configuration)

To initialize and start the Mobile IPv6 home agent on a specific interface, use the **ipv6 mobile home-agent** command in interface configuration mode. To discard bindings and any interface parameter settings, and to terminate home agent operation on a specific interface, use the **no** form of this command.

ipv6 mobile home-agent [**preference** *preference-value*]
no ipv6 mobile home-agent

Syntax Description	<p>preference <i>preference-value</i></p>	(Optional) Configures the Mobile IPv6 home agent preference value on a specified interface. The <i>preference-value</i> argument is an integer to be configured for preference in the home agent information option. The range is from 0 to 65535. The default preference value is 0.
---------------------------	--	---

Command Default Mobile IPv6 home agent is disabled. The default preference value is 0.

Command Modes Interface configuration

Command History	Release	Modification
	12.3(14)T	This command was introduced.

Usage Guidelines Before you enable the **ipv6 mobile home-agent** (interface configuration) command on an interface, you should configure common parameters using the **binding** command. Once an interface is configured to run the home agent feature, the **ipv6 mobile home-agent** command in global configuration mode automatically appears in the global configuration.

Once enabled, the **ipv6 mobile home-agent**(interface configuration) command cannot be disabled if there is a home agent configured on at least one of the interfaces. If there is no home agent service on any interfaces, the **no** form of the command disables home agent capability from the router.

To configure the home agent preference value, use the optional **preference** *preference-value* keyword and argument. A preference value is a 16-bit signed integer used by the home agent sending a router advertisement. The preference value orders the addresses returned to the mobile node in the home agent addresses field of a home agent address discovery reply message. The higher the preference value, the more preferable is the home agent.

If a preference value is not included in a router advertisement, the default value is 0. Values greater than 0 indicate a home agent more preferable than this default value.

Examples

In the following example, the user initializes and starts Mobile IPv6 agent on Ethernet interface 2:

```
Router(config)# interface Ethernet 2
Router(config-if)# ipv6 mobile home-agent
```

In the following example, the home agent preference value is set to 10:

```
Router(config-if)# ipv6 mobile home-agent preference 10
```

Related Commands

Command	Description
binding	Configures binding options for the Mobile IPv6 home agent feature in home agent configuration mode.
ipv6 mobile home-agent (global configuration)	Enters home agent configuration mode.
show ipv6 mobile globals	Displays global Mobile IPv6 parameters.

ipv6 mobile router

To enable IPv6 network mobility (NEMO) functionality on a router and place the router in IPv6 mobile router configuration mode, use the **ipv6 mobile router** command in global configuration mode. To disable NEMO functionality on the router, use the **no** form of the command.

ipv6 mobile router
no ipv6 mobile router

Syntax Description This command has no arguments or keywords.

Command Default NEMO functionality is not enabled.

Command Modes Global configuration (config)

Release	Modification
12.4(20)T	This command was introduced.

Usage Guidelines The mobile router is a router that operates as a mobile node. The mobile router can roam from its home network and still provide connectivity for devices on its networks. The mobile networks are locally attached to the router.

Examples In the following example, the mobile router is enabled:

```
Router(config)# ipv6 mobile router
```

ipv6 mobile router-service roam

To enable the IPv6 mobile router interface to roam, use the **ipv6 mobile router-service roam** command in interface configuration mode. To disable roaming, use the **no** form of this command.

ipv6 mobile router-service roam [**bandwidth-efficient** | **cost-efficient** | **priority** *value*]
no ipv6 mobile router-service roam

Syntax Description

bandwidth-efficient	(Optional) Enables the mobile router to use the largest configured lifetime value.
cost-efficient	(Optional) Prevents a binding update unless a dialup link is up and a valid care-of address is available.
priority <i>value</i>	(Optional) Priority value that is compared among multiple configured interfaces to select the interface in which to send the registration request. When multiple interfaces have highest priority, the highest bandwidth is the preferred choice. When multiple interfaces have the same bandwidth, the interface with the highest IPv6 address is preferred. The range is from 0 to 255; the default is 100. Lower values equate to a higher priority.

Command Default

Roaming is not enabled.

Command Modes

Interface configuration (config-if)

Command History

Release	Modification
12.4(20)T	This command was introduced.

Usage Guidelines

The mobile router discovers home agents and foreign agents by receiving agent advertisements.

The **bandwidth-efficient** keyword enables the mobile router to use the largest configured lifetime value, even when the home agent recommends a shorter lifetime in a binding refresh advice message. This option can be used when the bandwidth is expensive.

Examples

The following example shows how to enable roaming for the IPv6 mobile router interface:

```
Router(config-if)# ipv6 mobile router-service roam
```

Related Commands

Command	Description
show ipv6 mobile router	Displays configuration information and monitoring statistics about the IPv6 mobile router.

ipv6 mode host unicast

To disable IPv6 routing services and inhibit forwarding on an interface in the network, use the **ipv6 mode host unicast** command in interface configuration mode.

ipv6 mode host unicast
no ipv6 mode host unicast

Syntax Description

This command has no arguments or keywords

Command Default

Command Modes

Interface configuration (config-if)

Command History

Release	Modification
Prior to Cisco IOS 15.4(2)S	This command was introduced.
Cisco IOS 15.4(2)S	This command was deprecated.

Usage Guidelines

Ensure that the routing services on interfaces that forward IPv6 traffic is enabled.

Examples

The following example shows to configure how a specific route entries change when many parameters is monitored:

```
Device> enable
Device# configure terminal
Device(config)# interface Serial10/0
Device(config-if)# ipv6 mode host unicast
```

Related Commands

Command	Description

ipv6 mtu

To set the maximum transmission unit (MTU) size of IPv6 packets transmitted on an interface, use the **ipv6 mtu** command in interface configuration mode. To restore the default MTU size, use the **no** form of this command.

ipv6 mtu *bytes*
no ipv6 mtu *bytes*

Syntax Description

<i>bytes</i>	MTU in bytes.
--------------	---------------

Command Default

The default MTU value depends on the interface medium, but the minimum for any interface is 1280 bytes.

Command Modes

Interface configuration (config-if)

Command History

Release	Modification
Cisco IOS 12.2(2)T	This command was introduced.
Cisco IOS 12.0(21)ST	This command was integrated into Cisco IOS Release 12.0(21)ST.
Cisco IOS 12.0(22)S	This command was integrated into Cisco IOS Release 12.0(22)S.
Cisco IOS 12.2(14)S	This command was integrated into Cisco IOS Release 12.2(14)S.
Cisco IOS 12.2(28)SB	This command was integrated into Cisco IOS Release 12.2(28)SB.
Cisco IOS 12.2(25)SG	This command was integrated into Cisco IOS Release 12.2(25)SG.
Cisco IOS 12.2(33)SRA	This command was integrated into Cisco IOS Release 12.2(33)SRA.
Cisco IOS 12.2(33)SXH	This command was integrated into Cisco IOS Release 12.2(33)SXH.
Cisco IOS XE 3.10S	This command was modified. The range for <i>bytes</i> argument was extended to 9676 for loopback interfaces.

Usage Guidelines

If a nondefault value is configured for an interface, an MTU option is included in router advertisements. IPv6 routers do not fragment forwarded IPv6 packets. Traffic originating from IPv6 routers may be fragmented. All devices on a physical medium must have the same protocol MTU in order to operate. In addition to the “IPv6 MTU value” (set by using the **ipv6 mtu** command), interfaces also have a nonprotocol-specific “MTU value”.



Note The MTU value configured by using the **ipv6 mtu** interface configuration command must not be less than 1280 bytes.

The MTU value configured depends on the type of interface. On a loopback interface, the MTU size can be a maximum of 9676 bytes.

Examples

The following example sets the maximum IPv6 packet size for serial interface 0/1 to 2000 bytes:

```
Device(config)# interface serial 0/1  
Device(config-if)# ipv6 mtu 2000
```

Related Commands

Command	Description
show ipv6 interface	Displays the usability status of interfaces configured for IPv6.

ipv6 multicast aaa account receive

To enable authentication, authorization, and accounting (AAA) accounting on specified groups or channels, use the **ipv6 multicast aaa account receive** command in interface configuration mode. To disable AAA accounting, use the **no** form of this command.

ipv6 multicast aaa account receive *access-list-name* [**throttle** *throttle-number*]
no ipv6 multicast aaa account receive

Syntax Description	
<i>access-list-name</i>	Access list to specify which groups or channels are to have AAA accounting enabled.
throttle	(Optional) Limits the number of records sent during channel surfing. No record is sent if a channel is viewed for less than a specified, configurable period of time.
<i>throttle-number</i>	(Optional) Throttle or surfing interval, in seconds.

Command Default No AAA accounting is performed on any groups or channels.

Command Modes Interface configuration

Command History	Release	Modification
	12.4(4)T	This command was introduced.

Usage Guidelines



Note Including information about IPv6 addresses in accounting and authorization records transmitted between the router and the RADIUS or TACACS+ server is supported. However, there is no support for using IPv6 to communicate with that server. The server must have an IPv4 address.

Use the **ipv6 multicast aaa account receive** command to enable AAA accounting on specific groups or channels and to set throttle interval limits on records sent during channel surfing.

Examples

The following example enables AAA accounting using an access list named list1:

```
Router(config-if)# ipv6 multicast aaa account receive list1
```

Related Commands	Command	Description
	aaa accounting multicast default	Enables AAA accounting of IPv6 multicast services for billing or security purposes when you use RADIUS.

ipv6 multicast boundary

To configure an IPv6 multicast boundary on the interface for a specified scope, use the **ipv6 multicast boundary** command in interface configuration mode. To disable this feature, use the **no** form of this command.

```

ipv6 multicast boundary block source
no ipv6 multicast boundary block source
ipv6 multicast boundary scope scope-value
no ipv6 multicast boundary scope scope-value

```

Syntax Description	block source	Blocks the source of all incoming multicast traffic on an interface.
	scope <i>scope-value</i>	Specifies the boundary for a particular scope. The scope value can be one of the following: <ul style="list-style-type: none"> • Link-local address • Subnet-local address • Admin-local address • Site-local address • Organization-local • Virtual Private Network (VPN) • Scope number, which is from 2 through 15

Command Default Multicast boundary is not configured on the interface.

Command Modes Interface configuration (config-if)

Command History	Release	Modification
	Cisco IOS 12.3(14)T	This command was introduced.
	Cisco IOS 12.2(18)SXE	This command was integrated into Cisco IOS Release 12.2(18)SXE.
	Cisco IOS XE 3.13S	This command was modified. The block and source keywords were added.

Usage Guidelines Use the **ipv6 multicast boundary block source** command to block all incoming multicast traffic on an interface. However, this command allows the multicast traffic to flow out on the interface and allows any reserved multicast packets to flow in on the interface. This command is primarily used at first-hop routers to prevent local hosts from functioning as multicast sources.

If the **ipv6 multicast boundary scope** command is configured for a particular scope on the Reverse Path Forwarding (RPF) interface, then packets are not accepted on that interface for groups that belong to scopes that are less than or equal to the one that is configured. Protocol Independent Multicast (PIM) join/prune messages for those groups are not sent on the RPF interface. The effect of the scope is verified by checking

the output of the **show ipv6 mrib route** command. The output does not show the RPF interface with Accept flag.

If the **ipv6 multicast boundary scope** command is configured for a particular scope on an interface in the outgoing interface list, packets are not forwarded for groups that belong to scopes that are less than or equal to the one configured.

Protocol Independent Multicast (PIM) join/prune (J/P) messages are not processed when it is received on the interface for groups that belong to scopes that are less than or equal to the one configured. Registers and bootstrap router (BSR) messages are also filtered on the boundary.

Examples

The following example shows how to block the source of all incoming multicast traffic on the interface:

```
Device> enable
Device# configure terminal
Device(config)# int GigabitEthernet0/0/0
Device(config-if)# ipv6 multicast boundary block source
```

The following example sets the scope value to be a scope number of 6:

```
ipv6 multicast boundary scope 6
```

Related Commands

Command	Description
ipv6 pim bsr candidate bsr	Configures a router to be a candidate BSR.
ipv6 pim bsr candidate rp	Configures the candidate RP to send PIM RP advertisements to the BSR.
show ipv6 mrib route	Displays the MRIB route information.

ipv6 multicast group-range

To disable multicast protocol actions and traffic forwarding for unauthorized groups or channels on all the interfaces in a router, use the **ipv6 multicast group-range** command in global configuration mode. To return to the command's default settings, use the **no** form of this command.

```
ipv6 multicast [vrf vrf-name] group-range [access-list-name]
no ipv6 multicast [vrf vrf-name] group-range [access-list-name]
```

Syntax Description		
	vrf <i>vrf-name</i>	(Optional) Specifies a virtual routing and forwarding (VRF) configuration.
	<i>access-list-name</i>	(Optional) Name of an access list that contains authenticated subscriber groups and authorized channels that can send traffic to the router.

Command Default Multicast is enabled for groups and channels permitted by a specified access list and disabled for groups and channels denied by a specified access list.

Command Modes Global configuration (config)

Command History	Release	Modification
	12.4(4)T	This command was introduced.
	15.0(1)M	This command was integrated into Cisco IOS Release 15.0(1)M.
	12.2(33)SRE	This command was modified. It was integrated into Cisco IOS Release 12.2(33)SRE.
	Cisco IOS XE Release 2.6	This command was introduced on Cisco ASR 1000 series routers.
	15.1(4)M	The vrf <i>vrf-name</i> keyword and argument were added.

Usage Guidelines The **ipv6 multicast group-range** command provides an access control mechanism for IPv6 multicast edge routing. The access list specified by the *access-list-name* argument specifies the multicast groups or channels that are to be permitted or denied. For denied groups or channels, the router ignores protocol traffic and actions (for example, no Multicast Listener Discovery (MLD) states are created, no mroute states are created, no Protocol Independent Multicast (PIM) joins are forwarded), and drops data traffic on all interfaces in the system, thus disabling multicast for denied groups or channels.

Using the **ipv6 multicast group-range** global configuration command is equivalent to configuring the MLD access control and multicast boundary commands on all interfaces in the system. However, the **ipv6 multicast group-range** command can be overridden on selected interfaces by using the following interface configuration commands:

- **ipv6 mld access-group** *access-list-name*
- **ipv6 multicast boundary scope** *scope-value*

Because the **no ipv6 multicast group-range** command returns the router to its default configuration, existing multicast deployments are not broken.

Examples

The following example ensures that the router disables multicast for groups or channels denied by an access list named list2:

```
Router(config)# ipv6 multicast group-range list2
```

The following example shows that the command in the previous example is overridden on an interface specified by int2:

```
Router(config)# interface int2
Router(config-if)# ipv6 mld access-group int-list2
```

On int2, MLD states are created for groups or channels permitted by int-list2 but are not created for groups or channels denied by int-list2. On all other interfaces, the access-list named list2 is used for access control.

In this example, list2 can be specified to deny all or most multicast groups or channels, and int-list2 can be specified to permit authorized groups or channels only for interface int2.

Related Commands

Command	Description
ipv6 mld access-group	Performs IPv6 multicast receiver access control.
ipv6 multicast boundary scope	Configures a multicast boundary on the interface for a specified scope.

ipv6 multicast limit

To configure per-interface multicast route (mroute) state limiters in IPv6, use the **ipv6 multicast limit** command in interface configuration mode. To remove the limit imposed by a per-interface mroute state limiter, use the **no** form of this command.

```
ipv6 multicast limit [{connected | rpf | out}] limit-acl max [threshold threshold-value]
no ipv6 multicast limit [{connected | rpf | out}] limit-acl max [threshold threshold-value]
```

Syntax Description		
connected	(Optional) Limits mroute states created for an Access Control List (ACL)-classified set of multicast traffic on an incoming (Reverse Path Forwarding [RPF]) interface that is directly connected to a multicast source by counting each time that an mroute permitted by the ACL is created or deleted.	
rpf	(Optional) Limits the number of mroute states created for an ACL-classified set of multicast traffic on an incoming (RPF) interface by counting each time an mroute permitted by the ACL is created or deleted.	
out	(Optional) Limits mroute outgoing interface list membership on an outgoing interface for an ACL-classified set of multicast traffic by counting each time that an mroute list member permitted by the ACL is added or removed.	
<i>limit-acl</i>	Name identifying the ACL that defines the set of multicast traffic to be applied to a per-interface mroute state limiter.	
<i>max</i>	Maximum number of mroutes permitted by the per interface mroute state limiter. The range is from 0 to 2147483647.	
threshold	(Optional) The mCAC threshold percentage.	
<i>threshold-value</i>	(Optional) The specified percentage. The threshold notification default is 0%, meaning that threshold notification is disabled.	

Command Default No per-interface mroute state limiters are configured. Threshold notification is set to 0%; that is, it is disabled.

Command Modes Interface configuration (config-if)

Command History	Release	Modification
	12.2(33)SRE	This command was introduced.
	Cisco IOS XE Release 2.6	This command was introduced on Cisco ASR 1000 series routers.

Usage Guidelines Use the **ipv6 multicast limit** command to configure mroute state limiters on an interface.

For the required *limit-acl* argument, specify the ACL that defines the IPv6 multicast traffic to be limited on an interface. A standard or extended ACL can be specified.

The **ipv6 multicast limit cost** command complements the per-interface **ipv6 multicast limit** command. Once the *limit-acl* argument is matched in the **ipv6 multicast limit** command, the *access-list* argument in the **ipv6**

multicast limit cost command is checked to see which cost to apply to limited groups. If no cost match is found, the default cost is 1.

The threshold notification for mCAC limit feature notifies the user when actual simultaneous multicast channel numbers exceeds or fall below a specified threshold percentage.

Examples

The following example configures the interface limit on the source router's outgoing interface Ethernet 1/3:

```
interface Ethernet1/3
ipv6 address FE80::40:1:3 link-local
ipv6 address 2001:0DB8:1:1:3/64
ipv6 multicast limit out acl1 10
```

Related Commands

Command	Description
ipv6 multicast limit cost	Applies a cost to mroutes that match per-interface mroute state limiters in IPv6.
ipv6 multicast limit rate	Configures the maximum allowed state on the source router.

ipv6 multicast limit cost

To apply a cost to mroutes that match per-interface mroute state limiters in IPv6, use the **ipv6 multicast limit cost** command in global configuration mode. To restore the default cost for mroutes being limited by per-interface mroute state limiters, use the **no** form of this command.

ipv6 multicast [*vrf vrf-name*] **limit cost** *access-list* *cost-multiplier*
no ipv6 multicast [*vrf vrf-name*] **limit cost** *access-list* *cost-multiplier*

Syntax Description		
vrf <i>vrf-name</i>	(Optional) Specifies a virtual routing and forwarding (VRF) configuration.	
<i>access-list</i>	Access Control List (ACL) name that defines the mroutes for which to apply a cost.	
<i>cost-multiplier</i>	Cost value applied to mroutes that match the corresponding ACL. The range is from 0 to 2147483647.	

Command Default If the **ipv6 multicast limit cost** command is not configured or if an mroute that is being limited by a per-interface mroute state limiter does not match any of the ACLs applied to **ipv6 multicast limit cost** command configurations, a cost of 1 is applied to the mroutes being limited.

Command Modes

Global configuration (config)

Command History

Release	Modification
12.2(33)SRE	This command was introduced.
Cisco IOS XE Release 2.6	This command was introduced on Cisco ASR 1000 series routers.
15.1(4)M	The vrf vrf-name keyword and argument were added.

Usage Guidelines

Use the **ipv6 multicast limit cost** command to apply a cost to mroutes that match per-interface mroute state limiters (configured with the **ipv6 multicast limit** command in interface configuration mode). This command is primarily used to provide bandwidth-based Call Admission Control (CAC) in network environments where multicast flows utilize different amounts of bandwidth. Accordingly, when this command is configured, the configuration is usually referred to as a bandwidth-based multicast CAC policy.

The **ipv6 multicast limit cost** command complements the per-interface **ipv6 multicast limit** command. Once the *limit-acl* argument is matched in the **ipv6 multicast limit** command, the *access-list* argument in the **ipv6 multicast limit cost** command is checked to see which cost to apply to limited groups. If no cost match is found, the default cost is 1.

Examples

The following example configures the global limit on the source router.

```
Router(config)# ipv6 multicast limit cost costlist1 2
```

Related Commands

Command	Description
ipv6 multicast limit	Configures per-interface mroute state limiters in IPv6.

ipv6 multicast limit rate

To configure the maximum allowed state globally on the source router, use the **ipv6 multicast limit rate** command in global configuration mode. To remove the rate value, use the **no** form of this command.

```
ipv6 multicast limit rate rate-value
no ipv6 multicast limit rate rate-value
```

Syntax Description	<i>rate-value</i> The maximum allowed state on the source router. The range is from 0 through 100.
---------------------------	--

Command Default The maximum state is 1.

Command Modes Global configuration (config)

Command History	Release	Modification
	Cisco IOS XE Release 2.6	This command was introduced.

Usage Guidelines The ipv6 multicast rate limit command is set to a maximum state of 1 message per second. If the default is set to 0, the syslog notification rate limiter is disabled.

Examples The following example configures the maximum state on the source router:

```
ipv6 multicast limit rate 2
```

Related Commands	Command	Description
	ipv6 multicast limit	Configures per-interface mroute state limiters in IPv6.

ipv6 multicast multipath

To enable load splitting of IPv6 multicast traffic across multiple equal-cost paths, use the **ipv6 multicast multipath** command in global configuration mode. To disable this function, use the **no** form of this command.

ipv6 multicast [**vrf** *vrf-name*] **multipath**
no ipv6 multicast [**vrf** *vrf-name*] **multipath**

Syntax Description

vrf <i>vrf-name</i>	(Optional) Specifies a virtual routing and forwarding (VRF) configuration.
----------------------------	--

Command Default

This command is enabled.

Command Modes

Global configuration

Command History

Release	Modification
12.3(7)T	This command was introduced.
12.2(25)S	This command was integrated into Cisco IOS Release 12.2(25)S.
15.1(4)M	The vrf <i>vrf-name</i> keyword and argument were added.

Usage Guidelines

The **ipv6 multicast multipath** command is enabled by default. In the default scenario, the reverse path forwarding (RPF) neighbor is selected randomly from the available equal-cost RPF neighbors, resulting in the load splitting of traffic from different sources among the available equal cost paths. All traffic from a single source is still received from a single neighbor.

When the **no ipv6 multicast multipath** command is configured, the RPF neighbor with the highest IPv6 address is chosen for all sources with the same prefix, even when there are other available equal-cost paths.

Because the **ipv6 multicast multipath** command changes the way an RPF neighbor is selected, it must be configured consistently on all routers in a redundant topology to avoid looping.

Examples

The following example enables load splitting of IPv6 traffic:

```
Router(config)# ipv6 multicast multipath
```

Related Commands

Command	Description
show ipv6 rpf	Checks RPF information for a given unicast host address and prefix.

ipv6 multicast pim-passive-enable

To enable the Protocol Independent Multicast (PIM) passive feature on an IPv6 router, use the **ipv6 multicast pim-passive-enable** command in global configuration mode. To disable this feature, use the **no** form of this command.

```
ipv6 multicast pim-passive-enable
no ipv6 multicast pim-passive-enable
```

Syntax Description This command has no arguments or keywords.

Command Default PIM passive mode is not enabled on the router.

Command Modes Global configuration (config)

Release	Modification
Cisco IOS XE Release 2.6	This command was introduced.

Usage Guidelines Use the **ipv6 multicast pim-passive-enable** command to configure IPv6 PIM passive mode on a router. Once PIM passive mode is configured globally, use the **ipv6 pim passive** command in interface configuration mode to configure PIM passive mode on a specific interface.

Examples The following example configures IPv6 PIM passive mode on a router:

```
Router(config)# ipv6 multicast pim-passive-enable
```

Command	Description
ipv6 pim passive	Configures PIM passive mode on a specific interface.

ipv6 multicast-routing

To enable multicast routing using Protocol Independent Multicast (PIM) and Multicast Listener Discovery (MLD) on all IPv6-enabled interfaces of the router and to enable multicast forwarding, use the **ipv6 multicast-routing** command in global configuration mode. To stop multicast routing and forwarding, use the **no** form of this command.

```
ipv6 multicast-routing [vrf vrf-name]
no ipv6 multicast-routing
```

Syntax Description

vrf <i>vrf-name</i>	(Optional) Specifies a virtual routing and forwarding (VRF) configuration.
----------------------------	--

Command Default

Multicast routing is not enabled.

Command Modes

Global configuration

Command History

Release	Modification
12.3(2)T	This command was introduced.
12.2(18)S	This command was integrated into Cisco IOS Release 12.2(18)S.
12.0(26)S	This command was integrated into Cisco IOS Release 12.0(26)S.
12.2(25)SG	This command was integrated into Cisco IOS Release 12.2(25)SG.
12.2(33)SRA	This command was integrated into Cisco IOS Release 12.2(33)SRA.
12.2(33)SXH	This command was integrated into Cisco IOS Release 12.2(33)SXH.
15.1(4)M	This command was modified. The vrf vrf-name keyword and argument were added.
15.0(1)SY	This command was integrated into Cisco IOS Release 15.0(1)SY.
15.0(2)SE	This command was integrated into Cisco IOS Release 15.0(2)SE.
15.1(1)SY	This command was integrated into Cisco IOS Release 15.1(1)SY.
15.4(1)S	This command was implemented on the Cisco ASR 901 series routers.

Usage Guidelines

Use the **ipv6 multicast-routing** command to enable multicast forwarding. This command also enables Protocol Independent Multicast (PIM) and Multicast Listener Discovery (MLD) on all IPv6-enabled interfaces of the router being configured.

You can configure individual interfaces before you enable multicast so that you can then explicitly disable PIM and MLD protocol processing on those interfaces, as needed. Use the **no ipv6 pim** or the **no ipv6 mld router** command to disable IPv6 PIM or MLD router-side processing, respectively.

For the Cisco Catalyst 6500 and Cisco 7600 series routers, you must enable the **ipv6 multicast-routing** command to use IPv6 multicast routing. The **ipv6 multicast-routing** command need not be enabled for IPv6 unicast-routing to function.

Examples

The following example enables multicast routing and turns on PIM and MLD on all interfaces:

```
ipv6 multicast-routing
```

Related Commands

Command	Description
ipv6 pim rp-address	Configures the address of a PIM RP for a particular group range.
no ipv6 pim	Turns off IPv6 PIM on a specified interface.
no ipv6 mld router	Disables MLD router-side processing on a specified interface.

ipv6 multicast rpf

To enable IPv6 multicast reverse path forwarding (RPF) check to use Border Gateway Protocol (BGP) unicast routes in the Routing Information Base (RIB), use the **ipv6 multicast rpf** command in global configuration mode. To disable this function, use the **no** form of this command.

```
ipv6 multicast [vrf vrf-name] rpf {backoff initial-delay max-delay | use-bgp}
no ipv6 multicast [vrf vrf-name] rpf {backoff initial-delay max-delay | use-bgp}
```

Syntax Description

vrf <i>vrf-name</i>	(Optional) Specifies a virtual routing and forwarding (VRF) configuration.
backoff	Specifies the backoff delay after a unicast routing change.
<i>initial-delay</i>	Initial RPF backoff delay, in milliseconds (ms). The range is from 200 to 65535.
<i>max-delay</i>	Maximum RPF backoff delay, in ms. The range is from 200 to 65535.
use-bgp	Specifies to use BGP routes for multicast RPF lookups.

Command Default

The multicast RPF check does not use BGP unicast routes.

Command Modes

Global configuration (config)

Command History

Release	Modification
12.4(2)T	This command was introduced.
12.2(28)SB	This command was integrated into Cisco IOS Release 12.2(28)SB.
12.2(33)SRA	This command was integrated into Cisco IOS Release 12.2(33)SRA.
12.2(33)SX13	This command was integrated into Cisco IOS Release 12.2(33)SX13.
15.0(1)M	This command was modified in a release earlier than Cisco IOS Release 15.0(1)M. The backoff keyword and <i>initial-delay max-delay</i> arguments were added.
Cisco IOS XE Release 2.1	This command was integrated into Cisco IOS XE Release 2.1 and implemented on the Cisco ASR 1000 Series Aggregation Services Routers.
15.1(4)M	The vrf <i>vrf-name</i> keyword and argument were added.

Usage Guidelines

When the **ipv6 multicast rpf** command is configured, multicast RPF check uses BGP unicast routes in the RIB. This is not done by default.

Examples

The following example shows how to enable the multicast RPF check function:

```
Router# configure terminal
Router(config)# ipv6 multicast rpf use-bgp
```

Related Commands

Command	Description
ipv6 multicast limit	Configure per-interface multicast route (mroute) state limiters in IPv6.
ipv6 multicast multipath	Enables load splitting of IPv6 multicast traffic across multiple equal-cost paths.

ipv6 nat

To designate that traffic originating from or destined for the interface is subject to Network Address Translation--Protocol Translation (NAT-PT), use the **ipv6 nat** command in interface configuration mode. To prevent the interface from being able to translate, use the **no** form of this command.

ipv6 nat
no ipv6 nat

Syntax Description This command has no keywords or arguments.

Command Default Traffic leaving or arriving at this interface is not subject to NAT-PT.

Command Modes
 Interface configuration

Command History	Release	Modification
	12.2(13)T	This command was introduced.

Usage Guidelines The **ipv6 nat** command is usually specified on at least one IPv4 interface and one IPv6 interface at the networking device where you intend to use NAT-PT.

Examples

The following example assigns the IPv4 address 192.168.30.1 to Fast Ethernet interface 1/0 and the IPv6 address 2001:0DB8:0:1::1 to Fast Ethernet interface 2/0. IPv6 routing is globally enabled and both interfaces are configured to run IPv6 and enable NAT-PT translations.

```
interface fastethernet 1/0
 ip address 192.168.30.1 255.255.255.0
 ipv6 nat
!
interface fastethernet 2/0
 ipv6 address 2001:0DB8:0:1::1/64
 ipv6 nat
```

Related Commands

Command	Description
ipv6 address link-local	Configures an IPv6 link-local address for an interface and enables IPv6 processing on the interface.
ipv6 address eui-64	Configures an IPv6 address for an interface and enables IPv6 processing on an interface using an EUI-64 interface ID in the low-order 64 bits of the address.
show ipv6 interface	Displays the usability status of interfaces configured for IPv6.
show ipv6 nat translations	Displays active NAT-PT translations.

ipv6 nat max-entries

To specify the maximum number of Network Address Translation--Protocol Translation (NAT-PT) translation entries stored by the router, use the **ipv6 nat max-entries** command in global configuration mode. To restore the default number of NAT-PT entries, use the **no** form of this command.

ipv6 nat max-entries *number*
no ipv6 nat max-entries

Syntax Description	<i>number</i> (Optional) Specifies the maximum number (1-2147483647) of NAT-PT translation entries. Default is unlimited.
---------------------------	---

Command Default Unlimited number of NAT-PT entries.

Command Modes Global configuration

Command History	Release	Modification
	12.2(13)T	This command was introduced.

Usage Guidelines Use the **ipv6 nat max-entries** command to set the maximum number of NAT-PT translation entries stored by the router when the router memory is limited, or the actual number of translations is important.

Examples The following example sets the maximum number of NAT-PT translation entries to 1000:

```
ipv6 nat max-entries 1000
```

Related Commands	Command	Description
	clear ipv6 nat translation	Clears dynamic NAT-PT translations from the translation table.
	show ipv6 nat translations	Displays active NAT-PT translations.

ipv6 nat prefix

To assign an IPv6 prefix where matching IPv6 packets will be translated using Network Address Translation--Protocol Translation (NAT-PT), use the **ipv6 nat prefix** command in global configuration or interface configuration mode. To prevent the IPv6 prefix from being used by NAT-PT, use the **no** form of this command.

ipv6 nat prefix *ipv6-prefix/prefix-length*
no ipv6 nat prefix *ipv6-prefix/prefix-length*

Syntax Description

<i>ipv6-prefix</i>	The IPv6 network used as the NAT-PT prefix. This argument must be in the form documented in RFC 2373 where the address is specified in hexadecimal using 16-bit values between colons.
<i>/ prefix-length</i>	The length of the IPv6 prefix. A decimal value that indicates how many of the high-order contiguous bits of the address comprise the prefix (the network portion of the address). The only prefix length supported is 96. A slash mark must precede the decimal value.

Command Default

No IPv6 prefixes are used by NAT-PT.

Command Modes

Global configuration
 Interface configuration

Command History

Release	Modification
12.2(13)T	This command was introduced.

Usage Guidelines

The **ipv6 nat prefix** command is used to specify an IPv6 address prefix against which the destination prefix in an IPv6 packet is matched. If the match is successful, NAT-PT will translate the IPv6 packet to an IPv4 packet using the configured mapping rules.

Use the **ipv6 nat prefix** command in global configuration mode to assign a global NAT-PT NAT-PT prefix, or in interface configuration mode to assign a different NAT-PT prefix for each interface. Using a different NAT-PT prefix on several interfaces allows the NAT-PT router to support an IPv6 network with multiple exit points to IPv4 networks.

Examples

The following example assigns the IPv6 prefix 2001:0DB8:1::/96 as the global NAT-PT prefix:

```
ipv6 nat prefix 2001:0DB8:1::/96
```

The following example assigns the IPv6 prefix 2001:0DB8:2::/96 as the NAT-PT prefix for the Fast Ethernet interface 1/0, and the IPv6 prefix 2001:0DB8:4::/96 as the NAT-PT prefix for the Fast Ethernet interface 2/0:

```
interface fastethernet 1/0
  ipv6 address 2001:0DB8:2:1::1/64
  ipv6 nat prefix 2001:0DB8:2::/96
!
```

```
interface fastethernet 2/0
  ipv6 address 2001:0DB8:4:1::1/64
  ipv6 nat prefix 2001:0DB8:4::/96
```

Related Commands

Command	Description
ipv6 address link-local	Configures an IPv6 link-local address for an interface and enables IPv6 processing on the interface.
ipv6 address eui-64	Configures an IPv6 address for an interface and enables IPv6 processing on an interface using an EUI-64 interface ID in the low-order 64 bits of the address.
show ipv6 interface	Displays the usability status of interfaces configured for IPv6.
show ipv6 nat translations	Displays active NAT-PT translations.

ipv6 nat prefix v4-mapped

To enable customers to send traffic from their IPv6 network to an IPv4 network without configuring IPv6 destination address mapping, use the **ipv6 nat prefix v4-mapped** command in global configuration or interface configuration mode. To disable this feature, use the **no** form of this command.

```
ipv6 nat prefix ipv6-prefix v4-mapped {access-list-nameipv6-prefix}
no ipv6 nat prefix ipv6-prefix v4-mapped {access-list-nameipv6-prefix}
```

Syntax Description		
	<i>ipv6-prefix</i>	IPv6 prefix for Network Address Translation--Protocol Translation (NAT-PT).
	<i>access-list-name</i>	Name of an IPv6 access list. Names cannot contain a space or quotation mark, or begin with a numeric.

Command Default This command is not enabled.

Command Modes

- Global configuration
- Interface configuration

Command History	Release	Modification
	12.3(14)T	This command was introduced.

Usage Guidelines The IPv6 target address of a packet arriving at an interface is checked to discover if it has a NAT-PT prefix that was configured with the **ipv6 nat prefix v4-mapped** command. If the prefix does match, then an access-list check is performed to discover if the source address matches the access list or prefix list. If the prefix does not match, the packet is dropped.

If the prefix matches, source address translation is performed. If a rule has been configured for the source address translation, the last 32 bits of the destination IPv6 address is used as the IPv4 destination and a flow entry is created.

Examples

In the following example, the access list permits any IPv6 source address with the prefix 2001::/96 to go to the destination with a 2000::/96 prefix. The destination is then translated to the last 32 bit of its IPv6 address; for example: source address = 2001::1, destination address = 2000::192.168.1.1. The destination then becomes 192.168.1.1 in the IPv4 network:

```
ipv6 nat prefix 2000::/96 v4-mapped v4map_acl
ipv6 access-list v4map_acl
 permit ipv6 2001::/96 2000::/96
```


ipv6 nat translation

To change the amount of time after which Network Address Translation--Protocol Translation (NAT-PT) translations time out, use the **ipv6 nat translation** command in global configuration mode. To disable the timeout, use the **no** form of this command.

```

ipv6 nat translation {timeout | udp-timeout | dns-timeout | tcp-timeout | finrst-timeout | icmp-timeout
| syn-timeout} {seconds | never}
no ipv6 nat translation {timeout | udp-timeout | dns-timeout | tcp-timeout | finrst-timeout |
icmp-timeout | syn-timeout}

```

Syntax Description

timeout	Specifies that the timeout value applies to dynamic translations. Default is 86400 seconds (24 hours).
udp-timeout	Specifies that the timeout value applies to the User Datagram Protocol (UDP) port. Default is 300 seconds (5 minutes).
dns-timeout	Specifies that the timeout value applies to connections to the Domain Naming System (DNS). Default is 60 seconds.
tcp-timeout	Specifies that the timeout value applies to the TCP port. Default is 86400 seconds (24 hours).
finrst-timeout	Specifies that the timeout value applies to Finish and Reset TCP packets, which terminate a connection. Default is 60 seconds.
icmp-timeout	Specifies the timeout value for Internet Control Message Protocol (ICMP) flows. Default is 60 seconds.
syn-timeout	Specifies that the timeout value applies when a TCP SYN (request to synchronize sequence numbers used when opening a connection) flag is received but the flag is not followed by data belonging to the same TCP session.
<i>seconds</i>	Number of seconds after which the specified translation timer expires. The default is 0.
never	Specifies that the dynamic translation timer never expires.

Command Default

timeout : 86400 seconds (24 hours)**udp-timeout**: 300 seconds (5 minutes)**dns-timeout**: 60 seconds (1 minute)**tcp-timeout**: 86400 seconds (24 hours)**finrst-timeout**:60 seconds (1 minute)**icmp-timeout**: 60 seconds (1 minute)

Command Modes

Global configuration

Command History

Release	Modification
12.2(13)T	This command was introduced.

Usage Guidelines

Dynamic translations time out after a period of time without any translations. The default timeout period is 24 hours. When port translation is configured, there is finer control over translation entry timeouts because

each entry contains more context about the traffic that is using it. Non-DNS UDP translations time out after 5 minutes, and DNS times out in 1 minute. TCP translations time out in 24 hours, unless an RST or FIN flag is seen on the stream, in which case they will time out in 1 minute.

Examples

The following example causes UDP port translation entries to time out after 10 minutes:

```
ipv6 nat translation udp-timeout 600
```

Related Commands

Command	Description
clear ipv6 nat translation	Clears dynamic NAT-PT translations from the translation table.
show ipv6 nat translations	Displays active NAT-PT translations.

ipv6 nat v4v6 pool

To define a pool of IPv6 addresses for Network Address Translation--Protocol Translation (NAT-PT), use the **ipv6 nat v4v6 pool** command in global configuration mode. To remove one or more addresses from the pool, use the **no** form of this command.

```
ipv6 nat v4v6 pool name start-ipv6 end-ipv6 prefix-length prefix-length
no ipv6 nat v4v6 pool name start-ipv6 end-ipv6 prefix-length prefix-length
```

Syntax Description		
	<i>name</i>	Name of the pool.
	<i>start-ipv6</i>	Starting IPv6 address that defines the range of IPv6 addresses in the address pool.
	<i>end-ipv6</i>	Ending IPv6 address that defines the range of IPv6 addresses in the address pool.
	prefix-length <i>prefix-length</i>	Number that indicates how many bits of the address indicate the network. Specify the subnet of the network to which the pool addresses belong.

Command Default No pool of addresses is defined.

Command Modes Global configuration

Command History	Release	Modification
	12.2(13)T	This command was introduced.

Usage Guidelines This command defines a pool of IPv6 addresses using start address, end address, and prefix length. The pool is used when NAT-PT needs a dynamic mapping of an IPv6 address to translate an IPv4 address.

Examples

The following example configures a dynamic NAT-PT mapping to translate IPv4 addresses to IPv6 addresses using a pool of IPv6 addresses named v6pool. The packets to be translated by NAT-PT are filtered using an access list named pt-list2. One static NAT-PT mapping is configured to access a Domain Naming System (DNS) server. Ethernet interface 3/1 is an IPv6-only host and Ethernet interface 3/3 is an IPv4-only host.

```
interface Ethernet3/1
  ipv6 address 2001:0DB8:AABB:1::9/64
  ipv6 enable
  ipv6 nat
  !
interface Ethernet3/3
  ip address 192.168.30.9 255.255.255.0
  ipv6 nat
  !
ipv6 nat v4v6 source list pt-list2 pool v6pool
ipv6 nat v4v6 pool v6pool 2001:0DB8:EEFF::1 2001:0DB8:EEFF::2 prefix-length 128
ipv6 nat v6v4 source 2001:0DB8:AABB:1::1 10.21.8.0
ipv6 nat prefix 2001:0DB8:EEFF::/96
```

```
!  
access-list pt-list2 permit 192.168.30.0 0.0.0.255
```

Related Commands

Command	Description
clear ipv6 nat translations	Clears dynamic NAT-PT translations from the translation table.
show ipv6 nat translations	Displays active NAT-PT translations.

ipv6 nat v4v6 source

To configure IPv4 to IPv6 address translation using Network Address Translation--Protocol Translation (NAT-PT), use the **ipv6 nat v4v6 source** command in global configuration mode. To remove the static translation or remove the dynamic association to a pool, use the **no** form of this command.

```
ipv6 nat v4v6 source {list {access-list-numbername} pool name | ipv4-address ipv6-address}
no ipv6 nat v4v6 source {list {access-list-numbername} pool name | ipv4-address ipv6-address}
```

Syntax Description

list <i>access-list-number</i>	Standard IP access list number. Packets with source addresses that pass the access list are dynamically translated using global addresses from the named pool.
list <i>name</i>	Name of a standard IP access list. Packets with source addresses that pass the access list are dynamically translated using global addresses from the named pool.
pool <i>name</i>	Name of the pool from which global IP addresses are allocated dynamically.
<i>ipv4-address</i>	Sets up a single static translation. This argument establishes the local IP address assigned to a host on the inside network. The address could be randomly chosen, allocated from RFC 1918, or obsolete.
<i>ipv6-address</i>	Sets up a single static translation. This argument establishes the globally unique IP address of an inside host as it appears to the outside world.

Command Default

No NAT-PT translation of IPv4 to IPv6 addresses occurs.

Command Modes

Global configuration

Command History

Release	Modification
12.2(13)T	This command was introduced.

Usage Guidelines

This command has two forms: dynamic and static address translation. The form with an IPv6 access list establishes dynamic translation. Packets from IPv4 addresses that match the standard access list are translated using IPv6 addresses allocated from the pool named with the **ipv6 nat v4v6 pool** command. The access list is used to specify which traffic is to be translated.

Alternatively, the syntax form using the *ipv4-address* and *ipv6-address* arguments establishes a single static translation.

Examples

The following example configures a dynamic NAT-PT mapping to translate IPv4 addresses to IPv6 addresses using a pool of IPv6 addresses named v6pool. The packets to be translated by NAT-PT are filtered using an access list named pt-list2. Ethernet interface 3/1 is an IPv6-only host and Ethernet interface 3/3 is an IPv4-only host.

```
interface Ethernet3/1
  ipv6 address 2001:0DB8:AABB:1::9/64
  ipv6 enable
```

```

ipv6 nat
!
interface Ethernet3/3
 ip address 192.168.30.9 255.255.255.0
  ipv6 nat
  !
 ipv6 nat v4v6 source list pt-list2 pool v6pool
 ipv6 nat v4v6 pool v6pool 2001:0DB8:EEFF::1 2001:0DB8:EEFF::2 prefix-length 128
 ipv6 nat prefix 3ffe:c00:yyyy::/96
  !
 access-list pt-list2 permit 192.168.30.0 0.0.0.255

```

The following example shows a static translation where the IPv4 address 192.168.30.1 is translated into the IPv6 address 2001:0DB8:EEFF::2:

```

ipv6 nat v4v6 source 192.168.30.1 2001:0DB8:EEFF::2

```

Related Commands

Command	Description
clear ipv6 nat translation	Clears dynamic NAT-PT translations from the translation state table.
ipv6 nat v4v6 pool	Defines a pool of IPv6 addresses for NAT-PT.
ipv6 nat v6v4 source	Enables NAT-PT for an IPv6 source address.
show ipv6 nat translations	Displays active NAT-PT translations.

ipv6 nat v6v4 pool

To define a pool of IPv4 addresses for Network Address Translation--Protocol Translation (NAT-PT), use the **ipv6 nat v6v4 pool** global configuration command. To remove one or more addresses from the pool, use the **no** form of this command.

```
ipv6 nat v6v4 pool name start-ipv4 end-ipv4 prefix-length prefix-length
no ipv6 nat v6v4 pool name start-ipv4 end-ipv4 prefix-length prefix-length
```

Syntax Description		
	<i>name</i>	Name of the pool.
	<i>start-ipv4</i>	Starting IPv4 address that defines the range of IPv4 addresses in the address pool.
	<i>end-ipv4</i>	Ending IPv4 address that defines the range of IPv4 addresses in the address pool.
	prefix-length <i>prefix-length</i>	Number that indicates how many bits of the address indicate the network. Specify the subnet of the network to which the pool addresses belong.

Command Default No pool of addresses is defined.

Command Modes Global configuration

Command History	Release	Modification
	12.2(13)T	This command was introduced.

Usage Guidelines This command defines a pool of IPv4 addresses using start address, end address, and prefix length. The pool is used when NAT-PT needs a dynamic mapping of IPv4 addresses to translate IPv6 addresses.

Examples

The following example configures a dynamic NAT-PT mapping to translate IPv6 addresses to IPv4 addresses using a pool of IPv4 addresses named v4pool. The packets to be translated by NAT-PT are filtered using an IPv6 access list named pt-list1. One static NAT-PT mapping is configured to access a Domain Naming System (DNS) server. Ethernet interface 3/1 is an IPv6-only host and Ethernet interface 3/3 is an IPv4-only host.

```
interface Ethernet3/1
  ipv6 address 2001:0DB8:AABB:1::9/64
  ipv6 enable
  ipv6 nat
  !
interface Ethernet3/3
  ip address 192.168.30.9 255.255.255.0
  ipv6 nat
  !
ipv6 nat v4v6 source 192.168.30.1 2001:0DB8:EEFF::2
ipv6 nat v6v4 source list pt-list1 pool v4pool
ipv6 nat v6v4 pool v4pool 10.21.8.1 10.21.8.10 prefix-length 24
ipv6 nat prefix 2001:0DB8:EEFF::/96
```

```
!  
ipv6 access-list pt-list1  
  permit ipv6 2001:0DB8:AABB:1::/64 any
```

Related Commands

Command	Description
clear ipv6 nat translations	Clears dynamic NAT-PT translations from the translation table.
show ipv6 nat translations	Displays active NAT-PT translations.

ipv6 nat v6v4 source

To configure IPv6 to IPv4 address translation using Network Address Translation--Protocol Translation (NAT-PT), use the **ipv6 nat v6v4 source** command in global configuration mode. To remove the static translation or remove the dynamic association to a pool, use the **no** form of this command.

```

ipv6 nat v6v4 source {list access-list-name pool name | route-map map-name pool name |
ipv6-address ipv4-address} [overload]
no ipv6 nat v6v4 source {list access-list-name pool name | route-map map-name pool name |
ipv6-address ipv4-address} [overload]
  
```

Syntax Description

list <i>access-list-name</i>	IPv6 access list name. Packets with source addresses that pass the access list are translated using global addresses from the named pool.
route-map <i>map-name</i>	Sets up a single static translation. This keyword and argument combination establishes the globally unique IP address assigned to a host on the outside network by its owner. It was allocated from globally routable network space.
pool <i>name</i>	Name of the pool from which global IP addresses are allocated dynamically.
<i>ipv6-address</i>	Sets up a single static translation. This argument establishes the globally unique IP address of an inside host as it appears to the outside world.
<i>ipv4-address</i>	Sets up a single static translation. This argument establishes the local IP address assigned to a host on the inside network. The address could be randomly chosen, allocated from RFC 1918, or obsolete.
overload	Enables multiplexing of IPv6 addresses to a single IPv4 address for TCP, UDP, and ICMP.

Command Default

No NAT-PT translation of IPv6 to IPv4 addresses occurs.

Command Modes

Global configuration

Command History

Release	Modification
12.2(13)T	This command was introduced.
12.3(2)T	The overload keyword was added to support Port Address Translation (PAT), or Overload, multiplexing multiple IPv6 addresses to a single IPv4 address or to an IPv4 address pool.

Usage Guidelines

Dynamic and Static Address Translation

This command has two forms: dynamic and static address translation. The form with an IPv6 access list establishes dynamic translation. Packets from IPv6 addresses that match the IPv6 access list are translated using IPv4 addresses allocated from the pool named with the **ipv6 nat v6v4 pool** command. The access list is used to specify which traffic is to be translated.

Alternatively, the syntax form using the *ipv6-address* and *ipv4-address* arguments establishes a single static translation.

Port Address Translation

When used for PAT, the command can be used for a single IPv4 interface or for a pool of IPv4 interfaces.

Examples

Dynamic Mapping to a Pool of IPv4 Addresses Example

The following example configures a dynamic NAT-PT mapping to translate IPv6 addresses to IPv4 addresses using a pool of IPv4 addresses named v4pool. The packets to be translated by NAT-PT are filtered using an IPv6 access list named pt-list1. Ethernet interface 3/1 is an IPv6-only host and Ethernet interface 3/3 is an IPv4-only host.

```
interface Ethernet3/1
  ipv6 address ffe:aaaa:bbbb:1::9/64
  ipv6 enable
  ipv6 nat
  !
interface Ethernet3/3
  ip address 192.168.30.9 255.255.255.0
  ipv6 nat
  !
ipv6 nat v6v4 source list pt-list1 pool v4pool
ipv6 nat v6v4 pool v4pool 10.21.8.1 10.21.8.10 prefix-length 24
ipv6 nat prefix 3ffe:c00:::/96
  !
ipv6 access-list pt-list1
  permit ipv6 3ffe:aaaa:bbbb:1::/64 any
```

Static Translation for a Single Address Example

The following example shows a static translation where the IPv6 address 3ffe:aaaa:bbbb:1::1 is translated into the IPv4 address 10.21.8.10:

```
ipv6 nat v6v4 source 3ffe:aaaa:bbbb:1::1 10.21.8.10
```

Port Address Translation to a Single Address Example

```
ipv6 nat v6v4 pool v6pool 10.1.1.1 10.1.1.10 subnetmask 255.255.255.0
ipv6 nat v6v4 source list v6list interface e1 overload
ipv6 accesslist v6list
  permit 3000::/64 any
```

Related Commands

Command	Description
clear ipv6 nat translation	Clears dynamic NAT-PT translations from the translation state table.
debug ipv6 nat	Diaplays debugging messages for NAT-PT.
ipv6 nat v6v4 pool	Defines a pool of IPv4 addresses for NAT-PT.

Command	Description
ipv6 nat v4v6 source	Enables NAT-PT for an IPv4 source address.
show ipv6 nat translations	Displays active NAT-PT translations.

ipv6 nd advertisement-interval

To configure the advertisement interval option in router advertisements (RAs), use the **ipv6 nd advertisement-interval** in interface configuration mode. To reset the interval to the default value, use the **no** form of this command.

ipv6 nd advertisement-interval
no ipv6 nd advertisement-interval

Syntax Description This command has no arguments or keywords.

Command Default Advertisement interval option is not sent.

Command Modes Interface configuration

Release	Modification
12.3(14)T	This command was introduced.
15.2(2)S	This command was implemented on the Cisco ASR 901 Series Aggregation Services devices.

Usage Guidelines Use the **ipv6 nd advertisement-interval** command to indicate to a visiting mobile node the interval at which that node may expect to receive RAs. The node may use this information in its movement detection algorithm.

Examples The following example enables the advertisement interval option to be sent in RAs:

```
Device(config-if)# ipv6 nd advertisement-interval
```

Command	Description
ipv6 mobile home-agent (interface configuration)	Initializes and starts the Mobile IPv6 home agent on a specific interface.
ipv6 nd ra-interval	Configures the interval between Mobile IPv6 RA transmissions on an interface.

ipv6 nd autoconfig default-router

To allow Neighbor Discovery to install a default route to the Neighbor Discovery-derived default router, use the **ipv6 nd autoconfig default-router** command in interface configuration mode. To remove the default route configured through interface configuration mode from the interface, use the **no** form of this command.

ipv6 nd autoconfig default-router
no ipv6 nd autoconfig default-router

Syntax Description This command has no arguments or keywords.

Command Default This command is enabled in host mode.

Command Modes Interface configuration (config-if)#

Command History	Release	Modification
	15.2(1)T	This command was introduced.

Usage Guidelines If the **ipv6 nd autoconfig default-router** command is configured on a router, Neighbor Discovery installs a default route to the Neighbor Discovery-derived default router. Using this command sends a router solicitation (RS) message to solicit a router advertisement (RA), thus eliminating any delay in waiting for the next periodic RA.

Examples

```
Device(config-if)# ipv6 nd autoconfig default router
```

Related Commands	Command	Description
	ipv6 nd autoconfig prefix	Uses Neighbor Discovery to install all valid on-link prefixes from RAs received on the interface.
	ipv6 nd route-owner	Inserts Neighbor Discovery-learned routes into the routing table with "ND" status and enables ND autoconfiguration behavior.

ipv6 nd autoconfig prefix

To use Neighbor Discovery to install all valid on-link prefixes from router advertisements (RAs) received on the interface, use the **ipv6 nd autoconfig prefix** command in interface configuration mode. To remove the prefix from the RIB, use the **no** form of the command.

```
ipv6 nd autoconfig prefix
no ipv6 nd autoconfig prefix
```

Syntax Description This command has no arguments or keywords.

Command Default This command is not enabled.

Command Modes Interface configuration (config-if)#

Command History	Release	Modification
	15.2(1)T	This command was introduced.

Usage Guidelines Using the **ipv6 nd autoconfig prefix command** sends a router solicitation (RS) message to solicit a router advertisement (RA), thus eliminating any delay in waiting for the next periodic RA. The router receives a prefix from a neighboring router, and installs the prefix in the RIB.

Use of the **ipv6 nd autoconfig prefix command** allows Neighbor Discovery to install all valid on-link prefixes from RAs received on the interface. The prefixes are installed as Neighbor Discovery-owned static routes in same manner as a Neighbor Discovery default route. If both **ipv6 address autoconfig** and **ipv6 nd autoconfig prefix** are both configured, then the handling of /64 autoconfiguration and on-link prefixes will be unchanged. All other valid Neighbor Discovery prefixes will be installed as static routes.

Examples Device (config-if) # **ipv6 nd autoconfig default-router**

Related Commands	Command	Description
	ipv6 nd autoconfig default-router	Allows Neighbor Discovery to install a default route to the Neighbor Discovery-derived default router.
	ipv6 nd route-owner	Inserts Neighbor Discovery-learned routes into the routing table with "ND" status and enables ND autoconfiguration behavior.

ipv6 nd cache expire

To configure the length of time before an IPv6 neighbor discovery (ND) cache entry expires, use the **ipv6 nd cache expire** command in interface configuration mode. To remove this configuration, use the **no** form of this command.

```
ipv6 nd cache expire expire-time-in-seconds [refresh]
no ipv6 nd cache expire expire-time-in-seconds [refresh]
```

Syntax Description	
<i>expire-time-in-seconds</i>	The time range is from 1 through 65536 seconds. The default is 14400 seconds, or 4 hours.
refresh	(Optional) Automatically refreshes the ND cache entry.

Command Default This expiration time is 14400 seconds (4 hours)

Command Modes Interface configuration (config-if)

Command History	Release	Modification
	12.2(33)SXI7	This command was introduced.
	Cisco IOS XE Release 3.2SE	This command was integrated into Cisco IOS XE Release 3.2SE.

Usage Guidelines By default, an ND cache entry is expired and deleted if it remains in the STALE state for 14,400 seconds, or 4 hours. The **ipv6 nd cache expire** command allows the user to vary the expiry time and to trigger autorefresh of an expired entry before the entry is deleted.

When the **refresh** keyword is used, an ND cache entry is autorefreshed. The entry moves into the DELAY state and the neighbor unreachability detection (NUD) process occurs, in which the entry transitions from the DELAY state to the PROBE state after 5 seconds. When the entry reaches the PROBE state, a neighbor solicitation (NS) is sent and then retransmitted as per the configuration.

Examples

The following example shows that the ND cache entry is configured to expire in 7200 seconds, or 2 hours:

```
Router(config-if)# ipv6 nd cache expire 7200
```

ipv6 nd cache interface-limit (global)

To configure a neighbor discovery cache limit on all interfaces on the device, use the **ipv6 nd cache interface-limit** command in global configuration mode. To remove the neighbor discovery from all interfaces on the device, use the **no** form of this command.

```
ipv6 nd cache interface-limit size [log rate]
no ipv6 nd cache interface-limit size [log rate]
```

Syntax Description	
<i>size</i>	Cache size.
log rate	(Optional) Adjustable logging rate, in seconds. The valid values are 0 and 1.

Command Default Default logging rate for the device is one entry every second.

Command Modes Global configuration (config)

Command History	Release	Modification
	Cisco IOS XE Release 2.6	This command was introduced.
	15.1(3)T	This command was integrated into Cisco IOS Release 15.1(3)T.
	15.1(1)SY	This command was integrated into Cisco IOS Release 15.1(1)SY.
	15.3(1)S	This command was integrated into Cisco IOS Release 15.3(1)S.

Usage Guidelines The **ipv6 nd cache interface-limit** command in global configuration mode imposes a common per-interface cache size limit on all interfaces on the device.

Issuing the **no** or default form of the command will remove the neighbor discovery limit from every interface on the device that was configured using global configuration mode. It will not remove the neighbor discovery limit from any interface configured using the **ipv6 nd cache interface-limit** command in interface configuration mode.

The default (and maximum) logging rate for the device is one entry every second.

Examples

The following example shows how to set a common per-interface cache size limit of 4 seconds on all interfaces on the device:

```
Device(config)#
ipv6 nd cache interface-limit 4
```

Related Commands	Command	Description
	ipv6 nd cache interface-limit (interface)	Configures a neighbor discovery cache limit on a specified interface on the device.

ipv6 nd cache interface-limit (interface)

To configure a neighbor discovery cache limit on a specified interface on the , use the **ipv6 nd cache interface-limit** command in interface configuration mode. To remove the neighbor discovery limit configured through interface configuration mode from the interface, use the **no** form of this command.

```
ipv6 nd cache interface-limit size [log rate]
no ipv6 nd cache interface-limit size [log rate]
```

Syntax Description	<i>size</i>	Cache size.
	log rate	(Optional) Adjustable logging rate, in seconds. The valid values are 0 and 1.

Command Default Default logging rate for the device is one entry every second.

Command Modes Interface configuration (config-if)

Command History	Release	Modification
	Cisco IOS XE Release 2.6	This command was introduced.
	15.1(3)T	This command was integrated into Cisco IOS Release 15.1(3)T.
	15.1(1)SY	This command was integrated into Cisco IOS Release 15.1(1)SY.

Usage Guidelines The **ipv6 nd cache interface-limit** command in interface configuration mode allows you to configure a per-interface neighbor discovery limit on the associated interface. The limit configured by this command overrides any limit configured using the **ipv6 nd cache interface-limit** command in global configuration mode.

Issuing the **no** or default form of the command removes the neighbor discovery limit configured using interface configuration mode from the interface. Then, if the **ipv6 nd cache interface-limit** command in global configuration mode has been issued, the neighbor discovery limit on the interface reverts to that specified by global configuration. If the globally configured limit is smaller than the interface limit, then excess entries are removed. If the **ipv6 nd cache interface-limit** command in global configuration mode has not been issued, then no limit is set on the interface.

The number of entries in the neighbor discovery cache is limited on an interface basis. Once the limit is reached, no new entries are allowed.

Examples

The following example shows how to set the number of entries in a neighbor discovery cache (on an interface basis) to 1:

```
Device(config-if)# ipv6 nd cache interface-limit 1
```

Related Commands

Command	Description
ipv6 nd cache interface-limit (global)	Configures a neighbor discovery cache limit on all interfaces on the devices.

ipv6 nd dad attempts

To configure the number of consecutive neighbor solicitation messages that are sent on an interface while duplicate address detection is performed on the unicast IPv6 addresses of the interface, use the **ipv6 nd dad attempts** command in interface configuration mode. To return the number of messages to the default value, use the **no** form of this command.

ipv6 nd dad attempts *value*
no ipv6 nd dad attempts *value*

Syntax Description

<i>value</i>	The number of neighbor solicitation messages. The acceptable range is from 0 to 600. Configuring a value of 0 disables duplicate address detection processing on the specified interface; a value of 1 configures a single transmission without follow-up transmissions. Default is one message.
--------------	--

Command Default

Duplicate address detection on unicast IPv6 addresses with the sending of one neighbor solicitation message is enabled.

Command Modes

Interface configuration

Command History

Release	Modification
12.2(4)T	This command was introduced.
12.0(21)ST	This command was integrated into Cisco IOS Release 12.0(21)ST.
12.0(22)S	This command was integrated into Cisco IOS Release 12.0(22)S.
12.2(14)S	This command was integrated into Cisco IOS Release 12.2(14)S.
12.2(28)SB	This command was integrated into Cisco IOS Release 12.2(28)SB.
12.2(33)SRA	This command was integrated into Cisco IOS Release 12.2(33)SRA.
12.2(33)SXH	This command was integrated into Cisco IOS Release 12.2(33)SXH.
15.2(2)SNG	This command was implemented on the Cisco ASR 901 Series Aggregation Services devices.
15.2(2)SA2	This command was implemented on the Cisco ME 2600X Series Ethernet Access Switches.

Usage Guidelines

Duplicate address detection verifies the uniqueness of new unicast IPv6 addresses before the addresses are assigned to interfaces (the new addresses remain in a tentative state while duplicate address detection is performed). Duplicate address detection uses neighbor solicitation messages to verify the uniqueness of unicast IPv6 addresses.

The DupAddrDetectTransmits node configuration variable (as specified in RFC 2462, IPv6 Stateless Address Autoconfiguration) is used to automatically determine the number of consecutive neighbor solicitation messages that are sent on an interface while duplicate address detection is performed on a tentative unicast IPv6 address.

The interval between duplicate address detection, neighbor solicitation messages (the duplicate address detection timeout interval) is specified by the neighbor discovery-related variable RetransTimer (as specified

in RFC 2461, Neighbor Discovery for IP Version 6 [IPv6]), which is used to determine the time between retransmissions of neighbor solicitation messages to a neighbor when resolving the address or when probing the reachability of a neighbor. This is the same management variable used to specify the interval for neighbor solicitation messages during address resolution and neighbor unreachability detection. Use the **ipv6 nd ns-interval** command to configure the interval between neighbor solicitation messages that are sent during duplicate address detection.

Duplicate address detection is suspended on interfaces that are administratively "down." While an interface is administratively "down," the unicast IPv6 addresses assigned to the interface are set to a pending state. Duplicate address detection is automatically restarted on an interface when the interface returns to being administratively "up."



Note An interface returning to administratively "up" restarts duplicate address detection for all of the unicast IPv6 addresses on the interface. While duplicate address detection is performed on the link-local address of an interface, the state for the other IPv6 addresses is still set to TENTATIVE. When duplicate address detection is completed on the link-local address, duplicate address detection is performed on the remaining IPv6 addresses.

When duplicate address detection identifies a duplicate address, the state of the address is set to DUPLICATE and the address is not used. If the duplicate address is the link-local address of the interface, the processing of IPv6 packets is disabled on the interface and an error message similar to the following is issued:

```
%IPV6-4-DUPLICATE: Duplicate address FE80::1 on Ethernet0
```

If the duplicate address is a global address of the interface, the address is not used and an error message similar to the following is issued:

```
%IPV6-4-DUPLICATE: Duplicate address 3000::4 on Ethernet0
```

All configuration commands associated with the duplicate address remain as configured while the state of the address is set to DUPLICATE.

If the link-local address for an interface changes, duplicate address detection is performed on the new link-local address and all of the other IPv6 address associated with the interface are regenerated (duplicate address detection is performed only on the new link-local address).

Duplicate address detection is performed on all multicast-enabled IPv6 interfaces, including the following interface types:

- ATM permanent virtual circuit (PVC)
- Cisco High-Level Data Link Control (HDLC)
- Ethernet, Fast Ethernet, and Gigabit Ethernet
- FDDI
- Frame Relay PVC
- Point-to-point links
- PPP

Examples

The following example configures five consecutive neighbor solicitation messages to be sent on Ethernet interface 0 while duplicate address detection is being performed on the tentative unicast IPv6 address of the interface. The example also disables duplicate address detection processing on Ethernet interface 1.

```
Device(config)# interface ethernet 0
Device(config-if)# ipv6 nd dad attempts 5
Device(config)# interface ethernet 1
Device(config-if)# ipv6 nd dad attempts 0
```



Note Configuring a value of 0 with the **ipv6 nd dad attempts** command disables duplicate address detection processing on the specified interface; a value of 1 configures a single transmission without follow-up transmissions. The default is one message.

To display the state (OK, TENTATIVE, or DUPLICATE) of the unicast IPv6 address configured for an interface, to verify whether duplicate address detection is enabled on the interface, and to verify the number of consecutive duplicate address detection, neighbor solicitation messages that are being sent on the interface, enter the **show ipv6 interface** command:

```
Device# show ipv6 interface
Ethernet0 is up, line protocol is up
IPv6 is stalled, link-local address is FE80::1 [TENTATIVE]
Global unicast address(es):
  2000::1, subnet is 2000::/64 [TENTATIVE]
  3000::1, subnet is 3000::/64 [TENTATIVE]
Joined group address(es):
  FF02::1
  FF02::2
  FF02::1:FF00:1
MTU is 1500 bytes
ICMP error messages limited to one every 100 milliseconds
ICMP redirects are enabled
ND DAD is enabled, number of DAD attempts: 1
ND reachable time is 30000 milliseconds
ND advertised reachable time is 0 milliseconds
ND advertised retransmit interval is 0 milliseconds
ND router advertisements are sent every 200 seconds
ND router advertisements live for 1800 seconds
Hosts use stateless autoconfig for addresses.
Ethernet1 is up, line protocol is up
IPv6 is stalled, link-local address is FE80::2
Global unicast address(es):
  2000::2, subnet is 2000::/64
  3000::3, subnet is 3000::/64
Joined group address(es):
  FF02::1
  FF02::2
  FF02::1:FF00:1
MTU is 1500 bytes
ICMP error messages limited to one every 100 milliseconds
ICMP redirects are enabled
ND DAD is disabled, number of DAD attempts: 0
ND reachable time is 30000 milliseconds
ND advertised reachable time is 0 milliseconds
ND advertised retransmit interval is 0 milliseconds
ND router advertisements are sent every 200 seconds
```

ND router advertisements live for 1800 seconds
Hosts use stateless autoconfig for addresses.

Related Commands

Command	Description
ipv6 nd ns-interval	Configures the interval between IPv6 neighbor solicitation transmissions on an interface.
show ipv6 interface	Displays the usability status of interfaces configured for IPv6.

ipv6 nd dad-proxy

To enable the IPv6 Neighbor Discovery (ND) Duplicate Address Detection (DAD) Proxy feature, use the **ipv6 nd dad-proxy** command in global configuration mode or interface configuration mode.

```
ipv6 nd dad-proxy
noipv6 nd dad-proxy
```

Command Default

The IPv6 ND DAD Proxy feature is disabled.

Command Modes

Global configuration (config)

Command History

Release	Modification
15.1(2)SG	This command was introduced.

Usage Guidelines

Use the **ipv6 nd dad-proxy** command to enable the IPv6 ND DAD Proxy feature on a device or an interface.

On devices where the IPv6 ND Multicast Suppress feature is not available on the device platform, you use the **ipv6 nd dad-proxy** command in global configuration mode to configure the feature on the device.

The following example shows how to configure IPv6 ND DAD proxy on a device:

```
Device(config)# ipv6 nd dad-proxy
```

ipv6 nd dad time

To configure the neighbor solicitation (NS) retransmit interval for duplicate address detection (DAD) separately from the NS retransmit interval for address resolution, use the **ipv6 nd dad time** command in global configuration or interface configuration mode. To remove the NS retransmit interval for DAD, use the **no** form of this command.

ipv6 nd dad time *milliseconds*
no ipv6 nd dad time

Syntax Description

<i>milliseconds</i>	The interval between IPv6 neighbor solicit transmissions for DAD. The range is from 1000 to 3600000 milliseconds.
---------------------	---

Command Default

Default NS retransmit interval: 1000 msec (1 second)

Command Modes

Global configuration (config)
 Interface configuration (config-if)

Command History

Release	Modification
Cisco IOS XE Release 3S	This command was introduced.

Usage Guidelines

The **ipv6 nd dad time** command allows you to configure the NS retransmit interval for DAD separately from the NS retransmit interval for address resolution. This command also allows you to set the behavior globally for the whole router or on a per-interface basis.

Examples

The following example shows how to increase the default NS retransmit interval on an interface for address resolution to 3 seconds but keep the DAD NS retransmit interval at the default value of 1 second:

```
Router(config-if)# ipv6 nd ns-interval 3000
Router(config-if)# ipv6 nd dad time 1000
```

Related Commands

Command	Description
ipv6 nd ns-interval	Configures the interval between IPv6 neighbor solicitation retransmissions for address resolution on an interface.
show ipv6 interface	Displays the usability status of interfaces configured for IPv6.

ipv6 nd host mode strict

To enable the conformant, or strict, IPv6 host mode, use the **ipv6 nd host mode strict** command in global configuration mode. To reenable conformant, or loose, IPv6 host mode, use the **no** form of this command.

ipv6 nd host mode strict

Syntax Description This command has no arguments or keywords.

Command Default Nonconformant, or loose, IPv6 host mode is enabled.

Command Modes Global configuration (config)

Command History	Release	Modification
	15.0(2)SE	This command was introduced.

Usage Guidelines The default IPv6 host mode type is loose, or nonconformant. To enable IPv6 strict, or conformant, host mode, use the **ipv6 nd host mode strict** command. You can change between the two IPv6 host modes using the **no** form of this command.

The **ipv6 nd host mode strict** command selects the type of IPv6 host mode behavior and enters interface configuration mode. However, the **ipv6 nd host mode strict** command is ignored if you have configured IPv6 routing with the **ipv6 unicast-routing** command. In this situation, the default IPv6 host mode type, loose, is used.

Examples

The following example shows how to configure the device as a strict IPv6 host and enables IPv6 address autoconfiguration on Ethernet interface 0/0:

```
Device(config)# ipv6 nd host mode strict
Device(config-if)# interface ethernet0/0
Device(config-if)# ipv6 address autoconfig
```

The following example shows how to configure the device as a strict IPv6 host and configures a static IPv6 address on Ethernet interface 0/0:

```
Device(config)# ipv6 nd host mode strict
Device(config-if)# interface ethernet0/0
Device(config-if)# ipv6 address 2001::1/64
```

Related Commands	Command	Description
	ipv6 unicast-routing	Enables the forwarding of IPv6 unicast datagrams.

ipv6 nd inspection

To apply the Neighbor Discovery Protocol (NDP) Inspection feature, use the **ipv6 nd inspection** command in interface configuration mode. To remove the NDP Inspection feature, use the **no** form of this command.

```

ipv6 nd inspection [attach-policy [policy-name] | vlan {add | except | none | remove
| all} vlan vlan-id ]]
no ipv6 nd inspection

```

Syntax Description

attach-policy	(Optional) Attaches an NDP Inspection policy.
<i>policy-name</i>	(Optional) The NDP Inspection policy name.
vlan	(Optional) Applies the ND Inspection feature to a VLAN on the interface.
add	(Optional) Adds a VLAN to be inspected.
except	(Optional) Inspects all VLANs except the one specified.
none	(Optional) Specifies that no VLANs are inspected.
remove	(Optional) Removes the specified VLAN from NDP inspection.
all	(Optional) Inspects NDP traffic from all VLANs on the port.
<i>vlan-id</i>	(Optional) A specific VLAN on the interface. More than one VLAN can be specified. The VLAN number that can be used is from 1 to 4094.

Command Default

All NDP messages are inspected. Secure Neighbor Discovery (SeND) options are ignored. Neighbors are probed based on the criteria defined in the Neighbor Tracking feature. Per-port IPv6 address limit enforcement is disabled. Layer 2 header source MAC address validations are disabled. Per-port rate limiting of the NDP messages in software is disabled.

Command Modes

Interface configuration (config-if)

Command History

Release	Modification
12.2(50)SY	This command was introduced.
15.0(2)SE	This command was integrated into Cisco IOS Release 15.0(2)SY. The limited-broadcast keyword was deprecated.
Cisco IOS XE Release 3.2SE	This command was integrated into Cisco IOS XE Release 3.2SE. The limited-broadcast keyword was deprecated.

Usage Guidelines

The **ipv6 nd inspection** command applies the NDP Inspection feature on a specified interface. If you enable the optional **attach-policy** or **vlan** keywords, NDP traffic is inspected by policy or by VLAN. If no VLANs

are specified, NDP traffic from all VLANs on the port is inspected (which is equivalent to using the **vlan all** keywords).

If no policy is specified in this command, the default criteria are as follows:

- All NDP messages are inspected.
- SeND options are ignored.
- Neighbors are probed based on the criteria defined in neighbor tracking feature.
- Per-port IPv6 address limit enforcement is disabled.
- Layer 2 header source MAC address validations are disabled.
- Per-port rate limiting of the NDP messages in software is disabled.

If a VLAN is specified, its parameter is either a single VLAN number from 1 to 4094 or a range of VLANs described by two VLAN numbers, the lesser one first, separated by a dash (for example, **vlan 1-100,200,300-400**). Do not enter any spaces between comma-separated VLAN parameters or in dash-specified ranges.

Examples

The following example enables NDP inspection on a specified interface:

```
Router(config-if)# ipv6 nd inspection
```

ipv6 nd inspection policy

To define the neighbor discovery (ND) inspection policy name and enter ND inspection policy configuration mode, use the **ipv6 nd inspection** command in ND inspection configuration mode. To remove the ND inspection policy, use the **no** form of this command.

```
ipv6 nd inspection policy policy-name
no ipv6 nd inspection policy policy-name
```

Syntax Description	<i>policy-name</i>	The ND inspection policy name.
---------------------------	--------------------	--------------------------------

Command Default No ND inspection policies are configured.

Command Modes ND inspection configuration (config-nd-inspection)

Command History	Release	Modification
	12.2(50)SY	This command was introduced.
	15.0(2)SE	This command was integrated into Cisco IOS Release 15.0(2)SE.
	Cisco IOS XE Release 3.2SE	This command was integrated into Cisco IOS XE Release 3.2SE.

Usage Guidelines The **ipv6 nd inspection policy** command defines the ND inspection policy name and enters ND inspection policy configuration mode. Once you are in ND inspection policy configuration mode, you can use any of the following commands:

- **device-role**
- **drop-unsecure**
- **limit address-count**
- **sec-level minimum**
- **tracking**
- **trusted-port**
- **validate source-mac**

Examples

The following example defines an ND policy name as policy1:

```
Router(config)# ipv6 nd inspection policy policy1
Router(config-nd-inspection)#
```

Related Commands

Command	Description
device-role	Specifies the role of the device attached to the port.
drop-unsecure	Drops messages with no or invalid options or an invalid signature.
limit address-count	Limits the number of IPv6 addresses allowed to be used on the port.
sec-level minimum	Specifies the minimum security level parameter value when CGA options are used.
tracking	Overrides the default tracking policy on a port.
trusted-port	Configures a port to become a trusted port.
validate source-mac	Checks the source MAC address against the link-layer address.

ipv6 nd managed-config-flag

To set the "managed address configuration flag" in IPv6 router advertisements, use the **ipv6 nd managed-config-flag** command in interface configuration mode. To clear the flag from IPv6 router advertisements, use the **no** form of this command.

ipv6 nd managed-config-flag
no ipv6 nd managed-config-flag

Syntax Description This command has no arguments or keywords.

Command Default The "managed address configuration flag" flag is not set in IPv6 router advertisements.

Command Modes
 Interface configuration

Release	Modification
12.2(2)T	This command was introduced.
12.0(21)ST	This command was integrated into Cisco IOS Release 12.0(21)ST.
12.0(22)S	This command was integrated into Cisco IOS Release 12.0(22)S.
12.2(14)S	This command was integrated into Cisco IOS Release 12.2(14)S.
12.2(28)SB	This command was integrated into Cisco IOS Release 12.2(28)SB.
12.2(25)SG	This command was integrated into Cisco IOS Release 12.2(25)SG.
12.2(33)SRA	This command was integrated into Cisco IOS Release 12.2(33)SRA.
12.2(33)SXH	This command was integrated into Cisco IOS Release 12.2(33)SXH.

Usage Guidelines Setting the "managed address configuration flag" flag in IPv6 router advertisements indicates to attached hosts whether they should use stateful autoconfiguration to obtain addresses. If the flag is set, the attached hosts should use stateful autoconfiguration to obtain addresses. If the flag is not set, the attached hosts should not use stateful autoconfiguration to obtain addresses.

Hosts may use stateful and stateless address autoconfiguration simultaneously.

Examples The following example configures the "managed address configuration flag" flag in IPv6 router advertisements on Ethernet interface 0/0:

```
Router(config)# interface ethernet 0/0
Router(config-if)# ipv6 nd managed-config-flag
```

Command	Description
ipv6 nd prefix-advertisement	Configures which IPv6 prefixes are included in IPv6 router advertisements

Command	Description
show ipv6 interface	Displays the usability status of interfaces configured for IPv6.

ipv6 nd na glean

To configure neighbor discovery (ND) to glean an entry from an unsolicited neighbor advertisement (NA), use the **ipv6 nd na glean** command in interface configuration mode. To disable this feature, use the **no** form of this command.

```
ipv6 nd na glean
no ipv6 nd na glean
```

Syntax Description This command has no arguments or keywords.

Command Default The router ignores an unsolicited NA.

Command Modes Interface configuration (config-if)

Release	Modification
12.2(33)SXI7	This command was introduced.
Cisco IOS XE Release 3.2SE	This command was integrated into Cisco IOS XE Release 3.2SE.

Usage Guidelines IPv6 nodes may choose to emit a multicast unsolicited NA packet following the successful completion of duplicate address detection (DAD). By default, these unsolicited NA packets are ignored by other IPv6 nodes. The **ipv6 nd na glean** command configures the router to create an ND entry on receipt of an unsolicited NA packet (assuming no such entry already exists and the NA has the link-layer address option). Use of this command allows a router to populate its ND cache with an entry for a neighbor in advance of any data traffic exchange with the neighbor.

Examples The following example configures ND to glean an entry from an unsolicited neighbor advertisement:

```
Router(config-if)# ipv6 nd na glean
```


ipv6 nd ns-interval

To configure the interval between IPv6 neighbor solicitation (NS) retransmissions on an interface, use the **ipv6 nd ns-interval** command in interface configuration mode. To restore the default interval, use the **no** form of this command.

ipv6 nd ns-interval *milliseconds*
no ipv6 nd ns-interval

Syntax Description

<i>milliseconds</i>	The interval between IPv6 neighbor solicit transmissions for address resolution. The acceptable range is from 1000 to 3600000 milliseconds.
---------------------	---

Command Default

0 milliseconds (unspecified) is advertised in router advertisements and the value 1000 is used for the neighbor discovery activity of the router itself.

Command Modes

Interface configuration (config-if)

Command History

Release	Modification
12.2(2)T	This command was introduced.
12.0(21)ST	This command was integrated into Cisco IOS Release 12.0(21)ST.
12.0(22)S	This command was integrated into Cisco IOS Release 12.0(22)S.
12.2(14)S	This command was integrated into Cisco IOS Release 12.2(14)S.
12.2(28)SB	This command was integrated into Cisco IOS Release 12.2(28)SB.
12.2(25)SG	This command was integrated into Cisco IOS Release 12.2(25)SG.
12.2(33)SRA	This command was integrated into Cisco IOS Release 12.2(33)SRA.
12.2(33)SXH	This command was integrated into Cisco IOS Release 12.2(33)SXH.
15.2(2)SA2	This command was implemented on the Cisco ME 2600X Series Ethernet Access Switches.

Usage Guidelines

By default, using the **ipv6 nd ns-interval** command changes the NS retransmission interval for both address resolution and duplicate address detection (DAD). To specify a different NS retransmission interval for DAD, use the **ipv6 nd dad time** command.

This value will be included in all IPv6 router advertisements sent out this interface. Very short intervals are not recommended in normal IPv6 operation. When a nondefault value is configured, the configured time is both advertised and used by the router itself.

Examples

The following example configures an IPv6 neighbor solicit transmission interval of 9000 milliseconds for Ethernet interface 0/0:

```
Router(config)# interface ethernet 0/0
Router(config-if)# ipv6 nd ns-interval 9000
```

Related Commands

Command	Description
ipv6 nd dad time	Configures the NS retransmit interval for DAD separately from the NS retransmit interval for address resolution.
show ipv6 interface	Displays the usability status of interfaces configured for IPv6.

ipv6 nd nud retry

To configure the number of times neighbor unreachability detection (NUD) resends neighbor solicitations (NSs), use the **ipv6 nd nud retry** command in interface configuration mode. To disable this feature, use the **no** form of this command.

ipv6 nd nud retry *base interval max-attempts*
no ipv6 nd nud retry *base interval max-attempts*

Syntax Description		
	<i>base</i>	The base NUD value.
	<i>interval</i>	The time interval, in milliseconds, between retries.
	<i>max-attempts</i>	The maximum number of retry attempts, depending on the base value.

Command Default Three NS packets are sent 1 second apart.

Command Modes Interface configuration (config-if)

Command History	Release	Modification
	12.2(33)SXI7	This command was introduced.
	Cisco IOS XE Release 3.2SE	This command was integrated into Cisco IOS XE Release 3.2SE.

Usage Guidelines When a router runs NUD to re-resolve the ND entry for a neighbor, it sends three NS packets 1 second apart. In certain situations (for example, spanning-tree events, high traffic, the end host being reloaded), three NS packets sent at an interval of 1 second may not be sufficient. To help maintain the neighbor cache in such situations, use the **ipv6 nd nud retry** command to configure exponential timers for NS retransmits.

The maximum number of retry attempts is configured using the *max-attempts* argument. The retransmit interval is calculated with the following formula:

tm

- *t* = Time interval
- *m* = Base (1, 2, or 3)
- *n* = Current NS number (where the first NS is 0)

The **ipv6 nd nud retry** command affects only the retransmit rate for NUD, not for initial resolution, which uses the default of three NS packets sent 1 second apart.

Examples

The following example provides a fixed interval of 1 second and three retransmits:

```
Router(config-if)# ipv6 nd nud retry 1 1000 3
```

The following example provides a retransmit interval of 1, 2, 4, and 8:

```
Router(config-if)# ipv6 nd nud retry 2 1000 4
```

The following example provides the retransmit intervals of 1, 3, 9, 27, 81:

```
Router(config-if)# ipv6 nd nud retry 3 1000 5
```

ipv6 nd other-config-flag

To set the "other stateful configuration" flag in IPv6 router advertisements, use the **ipv6 nd other-config-flag** command in interface configuration mode. To clear the flag from IPv6 router advertisements, use the **no** form of this command.

ipv6 nd other-config-flag
no ipv6 nd other-config-flag

Syntax Description This command has no arguments or keywords.

Command Default The "other stateful configuration" flag is not set in IPv6 router advertisements.

Command Modes Interface configuration

Release	Modification
12.2(2)T	This command was introduced.
12.0(21)ST	This command was integrated into Cisco IOS Release 12.0(21)ST.
12.0(22)S	This command was integrated into Cisco IOS Release 12.0(22)S.
12.2(14)S	This command was integrated into Cisco IOS Release 12.2(14)S.
12.2(18)SXE	This command was integrated into Cisco IOS Release 12.2(18)SXE.
12.2(28)SB	This command was integrated into Cisco IOS Release 12.2(28)SB.
12.2(25)SG	This command was integrated into Cisco IOS Release 12.2(25)SG.
12.2(33)SRE	This command was modified. It was integrated into Cisco IOS Release 12.2(33)SRE.

Usage Guidelines The setting of the "other stateful configuration" flag in IPv6 router advertisements indicates to attached hosts how they can obtain autoconfiguration information other than addresses. If the flag is set, the attached hosts should use stateful autoconfiguration to obtain the other (nonaddress) information.



Note If the "managed address configuration" flag is set using the **ipv6 nd managed-config-flag** command, then an attached host can use stateful autoconfiguration to obtain the other (nonaddress) information regardless of the setting of the "other stateful configuration" flag.

Examples

The following example configures the "other stateful configuration" flag in IPv6 router advertisements on Ethernet interface 0/0:

```
Router(config)# interface ethernet 0/0
Router(config-if)# ipv6 nd other-config-flag
```

Related Commands

Command	Description
ipv6 nd managed-config-flag	Sets the "managed address configuration" flag in IPv6 router advertisements.
show ipv6 interface	Displays the usability status of interfaces configured for IPv6.

ipv6 nd prefix

To configure IPv6 prefixes that are included in IPv6 Neighbor Discovery (ND) router advertisements, use the **ipv6 nd prefix** command in interface configuration mode. To remove the prefixes, use the **no** form of this command.

```
ipv6 nd prefix {ipv6-prefix/prefix-length | default} [{no-advertise | [valid-lifetime preferred-lifetime
[{off-link | no-rtr-address | no-autoconfig | no-onlink}]]}]
at valid-date | preferred-date [{off-link | no-rtr-address | no-autoconfig}]
no ipv6 nd prefix {ipv6-prefix/prefix-length | default}
```

Syntax Description

<i>ipv6-prefix</i>	Specifies the IPv6 network number to include in router advertisements (RA). This argument must be in the form documented in RFC 2373 where the address is specified in hexadecimal format using 16-bit values between colons.
<i>/ prefix-length</i>	Specifies the length of the IPv6 prefix. A decimal value that indicates how many of the high-order contiguous bits of the address comprise the prefix (the network portion of the address). A slash mark must precede the decimal value.
default	Specifies that the default values are used.
no-advertise	(Optional) Specifies that the prefix is not advertised.
<i>valid-lifetime</i>	(Optional) Specifies the amount of time (in seconds) that the specified IPv6 prefix is advertised as being valid. The range is from 0 to 4294967295.
<i>preferred-lifetime</i>	(Optional) Specifies the amount of time (in seconds) that the specified IPv6 prefix is advertised as being preferred. The range is from 0 to 4294967295.
off-link	(Optional) Configures the specified prefix as off-link. The prefix will be advertised with the L-bit clear. The prefix will not be inserted into the routing table as a Connected prefix. If the prefix is already present in the routing table as a Connected prefix (for example, because the prefix was also configured using the ipv6 address command), then it will be removed.
no-rtr-address	(Optional) Indicates that the router will not send the full router address in prefix advertisements and will not set the R bit.
no-autoconfig	(Optional) Indicates to hosts on the local link that the specified prefix cannot be used for IPv6 autoconfiguration. The prefix will be advertised with the A-bit clear.
no-onlink	(Optional) Configures the specified prefix as not on-link. The prefix will be advertised with the L-bit clear.

at <i>valid-date</i>	(Optional) Specifies the date and time at which the lifetime and preference expire. The prefix is valid until this specified date and time are reached. Date is expressed in the form <i>date-valid-expire month-valid-expire year-valid-expire hh:mm-valid-expire</i> .
<i>preferred-date</i>	(Optional) Specifies the preferred expire date. Dates is expressed in the form <i>date-prefer-expire month-prefer-expire year-valid-expire hh:mm-prefer-expire</i> .

Command Default

All prefixes configured on interfaces that originate IPv6 router advertisements are advertised with a valid lifetime of 2,592,000 seconds (30 days) and a preferred lifetime of 604,800 seconds (7 days).

Note that by default:

- All prefixes will be inserted in the routing table as Connected prefixes
- All prefixes will be advertised as on-link (for example, the L-bit will be set in the advertisement)
- All prefixes will be advertised as an autoconfiguration prefix (for example, the A-bit will be set in the advertisement)

Command Modes

Interface configuration (config-if)

Command History

Release	Modification
12.2(13)T	This command was introduced. This command replaces the ipv6 nd prefix-advertisement command.
12.2(14)S	This command was integrated into Cisco IOS Release 12.2(14)S.
12.3(11)T	This command was modified. The no-rtr-address keyword was added.
12.2(28)SB	This command was integrated into Cisco IOS Release 12.2(28)SB.
12.2(33)SRA	This command was integrated into Cisco IOS Release 12.2(33)SRA.
12.2(33)SXH	This command was integrated into Cisco IOS Release 12.2(33)SXH.
12.2(32.08.01)REC154	This command was modified. The no-onlink keyword was added.
15.2(2)SA2	This command was implemented on the Cisco ME 2600X Series Ethernet Access Switches.

Usage Guidelines

This command allows control over the individual parameters per prefix, including whether the prefix should be advertised or not.

By default, prefixes configured as addresses on an interface using the **ipv6 address** command and additional prefixes configured using the **ipv6 nd prefix** command are advertised in router advertisements. If you configure prefixes for advertisement using the **ipv6 nd prefix** command, then only these prefixes are advertised.

If you configure the ND prefix using the **ipv6 nd prefix** command, both the interface IPv6 address and ND prefix is advertised.

Default Parameters

The **default** keyword can be used to set default parameters for all prefixes.

Prefix Lifetime and Expiration

A date can be set to specify the expiration of a prefix. The valid and preferred lifetimes are counted down in real time. When the expiration date is reached, the prefix will no longer be advertised.

On-Link

When on-link is “on” (by default), the specified prefix is assigned to the link. Nodes sending traffic to such addresses that contain the specified prefix consider the destination to be locally reachable on the link.

Autoconfiguration

When autoconfiguration is “on” (by default), it indicates to hosts on the local link that the specified prefix can be used for IPv6 autoconfiguration.

The configuration options affect the L-bit and A-bit settings associated with the prefix in the IPv6 ND Router Advertisement, and presence of the prefix in the routing table, as follows:

- Default L=1 A=1 In Routing Table
- no-onlink L=0 A=1 In Routing Table
- no-autoconfig L=1 A=0 In Routing Table
- no-onlink no-autoconfig L=0 A=0 In Routing Table
- off-link L=0 A=1 Not in Routing Table
- off-link no-autoconfig L=0 A=0 Not in Routing Table

Examples

The following example includes the IPv6 prefix 2001:0DB8::/35 in router advertisements sent out Ethernet interface 0/0 with a valid lifetime of 1000 seconds and a preferred lifetime of 900 seconds:

```
Device(config)# interface ethernet 0/0
Device(config-if)# ipv6 nd prefix 2001:0DB8::/35 1000 900
```

The following example advertises the prefix with the L-bit clear, so that the prefix is retained in the IPv6 routing table:

```
Device(config)# interface ethernet 0/0
Device(config-if)# ipv6 address 2001::1/64
Device(config-if)# ipv6 nd prefix 2001::/64 3600 3600 no-onlink
```

Related Commands

Command	Description
ipv6 address eui-64	Configures an IPv6 address and enables IPv6 processing on an interface using an EUI-64 interface ID in the low-order 64 bits of the address.
ipv6 address link-local	Configures an IPv6 link-local address for an interface and enables IPv6 processing on the interface.

Command	Description
ipv6 mobile home-agent (interface configuration)	Initializes and starts the IPv6 Mobile home agent on a specific interface.
ipv6 nd managed-config-flag	Sets the "managed address configuration" flag in IPv6 router advertisements.
show ipv6 interface	Displays the usability status of interfaces configured for IPv6.

ipv6 nd prefix framed-ipv6-prefix

To add the prefix in a received RADIUS framed IPv6 prefix attribute to the interface's neighbor discovery prefix queue, use the **ipv6 nd prefix framed-ipv6-prefix** command in interface configuration mode. To disable this feature, use the **no** form of this command.

```
ipv6 nd prefix framed-ipv6-prefix
no ipv6 nd prefix framed-ipv6-prefix
```

Syntax Description This command has no arguments or keywords.

Command Default Prefix is sent in the router advertisements (RAs).

Command Modes Interface configuration

Release	Modification
12.3(14)T	This command was introduced.
12.2(18)SXE	This command was integrated into Cisco IOS Release 12.2(18)SXE.
12.2(33)SRA	This command was integrated into Cisco IOS Release 12.2(33)SRA.

Usage Guidelines Use the **ipv6 nd prefix framed-ipv6-prefix** command to add the prefix in a received RADIUS framed IPv6 prefix attribute to the interface's neighbor discovery prefix queue and include it in RAs sent on the interface's link. By default, the prefix is sent in RAs. If the prefix in the attribute should be used by other applications such as the Dynamic Host Configuration Protocol (DHCP) for IPv6 server, administrators can disable the default behavior with the **no** form of the command.

Examples The following example adds the prefix in a received RADIUS framed IPv6 prefix attribute to the interface's neighbor discovery prefix queue:

```
ipv6 nd prefix framed-ipv6-prefix
```

ipv6 nd prefix-advertisement



Note Effective with Cisco IOS Release 12.2(13)T, the **ipv6 nd prefix-advertisement** command is replaced by the **ipv6 nd prefix** command. See the **ipv6 nd prefix** command for more information.

To configure which IPv6 prefixes are included in IPv6 router advertisements, use the **ipv6 nd prefix-advertisement** command in interface configuration mode. To remove the prefixes, use the **no** form of this command.

ipv6 nd prefix-advertisement *ipv6-prefix/prefix-length valid-lifetime preferred-lifetime* [[onlink](#)]
[[autoconfig](#)]
no ipv6 nd prefix-advertisement *ipv6-prefix/prefix-length*

Syntax Description

<i>ipv6-prefix</i>	The IPv6 network number to include in router advertisements. This argument must be in the form documented in RFC 2373 where the address is specified in hexadecimal using 16-bit values between colons.
<i>/ prefix-length</i>	The length of the IPv6 prefix. A decimal value that indicates how many of the high-order contiguous bits of the address comprise the prefix (the network portion of the address). A slash mark must precede the decimal value.
<i>valid-lifetime</i>	The amount of time (in seconds) that the specified IPv6 prefix is advertised as being valid.
<i>preferred-lifetime</i>	The amount of time (in seconds) that the specified IPv6 prefix is advertised as being preferred.
onlink	(Optional) Indicates that the specified prefix is assigned to the link. Nodes sending traffic to such addresses that contain the specified prefix consider the destination to be locally reachable on the link.
autoconfig	(Optional) Indicates to hosts on the local link that the specified prefix can be used for IPv6 autoconfiguration.

Command Default

All prefixes configured on interfaces that originate IPv6 router advertisements are advertised with a valid lifetime of 2592000 seconds (30 days) and a preferred lifetime of 604800 seconds (7 days), and with both the "onlink" and "autoconfig" flags set.

Command Modes

Interface configuration

Command History

Release	Modification
12.2(2)T	This command was introduced.
12.0(21)ST	This command was integrated into Cisco IOS Release 12.0(21)ST.

Release	Modification
12.0(22)S	This command was integrated into Cisco IOS Release 12.0(22)S.
12.2(13)T	This command was replaced by the ipv6 nd prefix command.
12.2(25)SG	This command was integrated into Cisco IOS Release 12.2(25)SG.

Usage Guidelines

By default, prefixes configured on an interface using the **ipv6 address** command are advertised with "onlink" and "autoconfiguration" flags set. If you configure prefixes for advertisement using the **ipv6 nd prefix-advertisement** command, then only these prefixes are advertised.

Examples

The following example includes the IPv6 prefix 2001:0DB8::/35 in router advertisements sent out Ethernet interface 0/0 with a valid lifetime of 1000 seconds, a preferred lifetime of 900 seconds, and both the "onlink" and "autoconfig" flags set:

```
Router(config)# interface ethernet 0/0
Router(config-if)# ipv6 nd prefix-advertisement 2001:0DB8::/35 1000 900 onlink autoconfig
```

Related Commands

Command	Description
ipv6 address link-local	Configures an IPv6 link-local address for an interface and enables IPv6 processing on the interface.
ipv6 address eui-64	Configures an IPv6 address and enables IPv6 processing on an interface using an EUI-64 interface ID in the low-order 64 bits of the address.
ipv6 nd managed-config-flag	Sets the "managed address configuration" flag in IPv6 router advertisements.
show ipv6 interface	Displays the usability status of interfaces configured for IPv6.

ipv6 nd ra dns server

To configure the IPv6 router advertisement of DNS server addresses on an interface, use the **ipv6 nd ra dns server** command in interface configuration mode. To remove the IPv6 router advertisement of DNS server addresses, use the **no** form of this command.

```

ipv6 nd ra dns server ipv6-address
seconds
no ipv6 nd ra dns server ipv6-address

```

Syntax Description

seconds The amount of time (in seconds) that the Domain Naming System (DNS) server is advertised in an IPv6 router advertisement (RA). The range is from 200 to 4294967295.

Command Default

The DNS server is not advertised in an IPv6 RA.

Command Modes

Interface configuration (config-if)

Command History

Release	Modification
Cisco IOS XE Release 3.9S	This command was introduced.

Usage Guidelines

You can use the **ipv6 nd ra dns server** command to configure up to eight DNS server addresses in an RA. If you configure a *seconds* value of zero, the DNS server will no longer be used.

Example

The following example configures a DNS server with an IPv6 address of 2001:DB8:1::1 to be advertised in an RA with a lifetime of 600 seconds:

```

Router(config)# interface ethernet 0/0
Router(config-if)# ipv6 nd ra dns server 2001:DB8:1::1 600

```

Related Commands

Command	Description
ipv6 nd ra interval	Configures the interval between IPv6 router advertisement transmissions on an interface.
show ipv6 interface	Displays the usability status of interfaces configured for IPv6.

ipv6 nd ra interval

To configure the interval between IPv6 router advertisement (RA) transmissions on an interface, use the **ipv6 nd ra interval** command in interface configuration mode. To restore the default interval, use the **no** form of this command.

ipv6 nd ra interval {*maximum-secs* [*minimum-secs*] | **msec** *maximum-ms* [*minimum-ms*]}
no ipv6 nd ra interval

Syntax Description

<i>maximum-secs</i>	Maximum interval between IPv6 RA transmissions, in seconds. The range is from 4 to 1800.
<i>minimum-secs</i>	(Optional) Minimum interval between IPv6 RA transmissions, in seconds. The range is from 3 to 150.
msec	Specifies that the intervals are in milliseconds.
<i>maximum-ms</i>	Maximum interval between IPv6 RA transmissions, in milliseconds. The range is from 70 to 1800000.
<i>minimum-ms</i>	(Optional) Minimum interval between IPv6 RA transmissions, in milliseconds. The smallest possible RA interval is 30 milliseconds. The range is from 30 to 53.

Command Default

The default interval between IPv6 RA transmissions is 200 seconds.

Command Modes

Interface configuration (config-if)

Command History

Release	Modification
12.4(2)T	This command was introduced. This command replaces the ipv6 nd ra-interval command.
12.2(25)SG	This command was integrated into Cisco IOS Release 12.2(25)SG.
12.2(33)SRA	This command was integrated into Cisco IOS Release 12.2(33)SRA.
12.2(33)SXH	This command was integrated into Cisco IOS Release 12.2(33)SXH.
12.2(33)SB	This command was integrated into Cisco IOS Release 12.2(33)SB.
15.2(2)SA2	This command was implemented on Cisco ME 2600X Series Ethernet Access Switches.

Usage Guidelines

The interval between transmissions should be less than or equal to the IPv6 router advertisement lifetime if you configure the route as a default router by using the **ipv6 nd ra lifetime** command. To prevent synchronization with other IPv6 nodes, the actual interval used is randomly selected from a value between the minimum and maximum values.

Users can explicitly configure a minimum RA interval. The minimum RA interval may never be more than 75 percent of the maximum RA interval and never less than 3 seconds (if specified in seconds). If the minimum RA interval is not configured, it is calculated as 75 percent of the maximum RA interval.

If the user specifies the time in milliseconds, then the minimum RA interval is 30 milliseconds. This limit allows configuration of very short RA intervals for Mobile IPv6.

The maximum and minimum RA intervals govern only unsolicited RA messages. Solicited RA messages are transmitted as router solicitation (RS) on the interface. However, if multiple RS messages are received every second, there is a minimum delay of 3 seconds between the RA messages. This limits the number of solicited RA messages transmitted from the interface.

Examples

The following example configures an IPv6 router advertisement interval of 201 seconds for Ethernet interface 0/0:

```
Device(config)# interface ethernet 0/0
Device(config-if)# ipv6 nd ra interval 201
```

The following examples shows a maximum RA interval of 200 seconds and a minimum RA interval of 50 seconds:

```
Device(config-if)# ipv6 nd ra interval 200 50
```

The following examples shows a maximum RA interval of 100 milliseconds and a minimum RA interval of 30 milliseconds, which is the smallest value allowed:

```
Device(config-if)# ipv6 nd ra interval msec 100 30
```

Related Commands

Command	Description
ipv6 mobile home-agent (interface configuration)	Initializes and starts the Mobile IPv6 home agent on a specific interface.
ipv6 nd advertisement-interval	Configures the advertisement interval option to be sent in RAs.
ipv6 nd ra lifetime	Configures the router lifetime value in IPv6 router advertisements on an interface.
show ipv6 interface	Displays the usability status of interfaces configured for IPv6.

ipv6 nd ra lifetime

To configure the router lifetime value in IPv6 router advertisements on an interface, use the **ipv6 nd ra lifetime** command in interface configuration mode. To restore the default lifetime, use the **no** form of this command.

ipv6 nd ra lifetime *seconds*
no ipv6 nd ra lifetime

Syntax Description

<i>seconds</i>	The validity of this router as a default router on this interface (in seconds).
----------------	---

Command Default

The default lifetime value is 1800 seconds.

Command Modes

Interface configuration

Command History

Release	Modification
12.4(2)T	This command was introduced. This command replaces the ipv6 nd ra-lifetime command.
12.2(25)SG	This command was integrated into Cisco IOS Release 12.2(25)SG.
12.2(33)SRA	This command was integrated into Cisco IOS Release 12.2(33)SRA.
12.2(33)SXH	This command was integrated into Cisco IOS Release 12.2(33)SXH.
12.2(33)SB	This command was integrated into Cisco IOS Release 12.2(33)SB.
15.2(2)SA2	This command was implemented on the Cisco ME 2600X Series Ethernet Access Switches.

Usage Guidelines

The "router lifetime" value is included in all IPv6 router advertisements sent out the interface. The value indicates the usefulness of the router as a default router on this interface. Setting the value to 0 indicates that the router should not be considered a default router on this interface. The "router lifetime" value can be set to a non zero value to indicate that it should be considered a default router on this interface. The non zero value for the "router lifetime" value should not be less than the router advertisement interval.

Examples

The following example configures an IPv6 router advertisement lifetime of 1801 seconds for Ethernet interface 0/0:

```
Router(config)# interface ethernet 0/0
Router(config-if)# ipv6 nd ra lifetime 1801
```

Related Commands

Command	Description
ipv6 nd ra interval	Configures the interval between IPv6 router advertisement transmissions on an interface.
show ipv6 interface	Displays the usability status of interfaces configured for IPv6.

ipv6 nd ra solicited unicast

To configure unified solicited Router Advertisement response method on an interface, use the **ipv6 nd ra solicited unicast** command in interface configuration mode. To remove solicited Router Advertisement response, use the **no** form of this command.

ipv6 nd ra solicited unicast
noipv6 nd ra solicited unicast

Syntax Description There are no keywords or arguments for this command.

Command Default The solicited Router Advertisement response is not configured.

Command Modes Interface configuration

Release	Modification
15.4(2)T	This command was introduced.
15.4(2)S	This command was integrated into Cisco IOS Release 15.4(2)S.
15.2(1)SY1	This command was integrated into Cisco IOS Release 15.2(1)SY1.

Usage Guidelines Large networks with a high concentration of mobile devices might experience like battery depletion, when solicited Router Advertisement messages are multicast . Use the **ipv6 nd ra solicited unicast** to unicast solicited Router Advertisement messages extend battery life of mobile device in the network.

Examples The following example configures an IPv6 router advertisement lifetime of 1801 seconds for Ethernet interface 0/0:

```
Router(config)# interface ethernet 0/0
Router(config-if)# ipv6 nd ra solicited unicast
```

Command	Description
ipv6 nd ra interval	Configures the interval between IPv6 router advertisement transmissions on an interface.
show ipv6 interface	Displays the usability status of interfaces configured for IPv6.

ipv6 nd ra suppress

To suppress IPv6 router advertisement transmissions on a LAN interface, use the **ipv6 nd ra suppress** command in interface configuration mode. To reenble the sending of IPv6 router advertisement transmissions on a LAN interface, use the **no** form of this command.

```
ipv6 nd ra suppress [all]
no ipv6 nd ra suppress
```

Syntax Description

all	(Optional) Suppresses all router advertisements (RAs) on an interface.
------------	--

Command Default

IPv6 router advertisements are automatically sent on Ethernet and FDDI interfaces if IPv6 unicast routing is enabled on the interfaces. IPv6 router advertisements are not sent on other types of interfaces.

Command Modes

Interface configuration

Command History

Release	Modification
12.4(2)T	This command was introduced. This command replaces the ipv6 nd suppress-ra command.
12.2(25)SG	This command was integrated into Cisco IOS Release 12.2(25)SG.
12.2(33)SRA	This command was integrated into Cisco IOS Release 12.2(33)SRA.
12.2(33)SXH	This command was integrated into Cisco IOS Release 12.2(33)SXH.
12.2(33)SB	This command was integrated into Cisco IOS Release 12.2(33)SB.
Cisco IOS XE Release 2.1	This command was integrated into Cisco IOS XE Release 2.1.
15.2(2)SA2	This command was implemented on the Cisco ME 2600X Series Ethernet Access Switches.

Usage Guidelines

The **ipv6 nd ra suppress** command only suppresses periodic unsolicited RAs. It does not suppress RAs sent in response to a router solicitation. To suppress all RAs, including those sent in response to a router solicitation, use the **ipv6 nd ra suppress** command with the **all** keyword.

Use the **no ipv6 nd ra suppress** command to enable the sending of IPv6 RA transmissions on non-LAN interface types (for example, serial or tunnel interfaces).

Examples

The following example suppresses IPv6 router advertisements on Ethernet interface 0/0:

```
Router(config)# interface ethernet 0/0
Router(config-if)# ipv6 nd ra suppress
```

The following example enables the sending of IPv6 router advertisements on serial interface 0/1:

ipv6 nd ra suppress

```
Router(config)# interface serial 0/1  
Router(config-if)# no ipv6 nd ra suppress
```

Related Commands

Command	Description
show ipv6 interface	Displays the usability status of interfaces configured for IPv6.

ipv6 nd raguard

To apply the router advertisements (RA) guard feature, use the **ipv6 nd raguard** command in interface configuration mode.

```
ipv6 nd raguard
no ipv6 nd raguard
```

Syntax Description This command has no arguments or keywords.

Command Default An RA guard policy is not configured.

Command Modes Interface configuration (config-if)

Release	Modification
12.2(33)SXI4	This command was introduced.
12.2(54)SG	This command was modified. Support for Cisco IOS Release 12.2(54)SG was added.

Usage Guidelines The **ipv6 nd raguard** command enables the RA guard feature. If the RA does not match with the configured option, the packet is dropped.

Examples The following example applies the RA guard:

```
Router(config-if)# ipv6 nd raguard
```

ipv6 nd rguard attach-policy

To apply the IPv6 router advertisement (RA) guard feature on a specified interface, use the **ipv6 nd rguard attach-policy** command in interface configuration mode.

```
ipv6 nd rguard attach-policy [policy-name [vlan {add | except | none | remove | all} vlan [vlan1,
vlan2, vlan3...]]]
```

Syntax Description

<i>policy-name</i>	(Optional) IPv6 RA guard policy name.
vlan	(Optional) Applies the IPv6 RA guard feature to a VLAN on the interface.
add	Adds a VLAN to be inspected.
except	All VLANs are inspected except the one specified.
none	No VLANs are inspected.
remove	Removes the specified VLAN from RA guard inspection.
all	ND traffic from all VLANs on the port is inspected.
<i>vlan</i>	(Optional) A specific VLAN on the interface. More than one VLAN can be specified (<i>vlan1</i> , <i>vlan2</i> , <i>vlan3</i> ...). The range of available VLAN numbers is from 1 through 4094.

Command Default

An IPv6 RA guard policy is not configured.

Command Modes

Interface configuration (config-if)

Command History

Release	Modification
12.2(50)SY	This command was introduced.
15.2(4)S	This command was integrated into Cisco IOS Release 15.2(4)S.
15.0(2)SE	This command was integrated into Cisco IOS Release 15.0(2)SE.
Cisco IOS XE Release 3.2SE	This command was integrated into Cisco IOS XE Release 3.2SE.

Usage Guidelines

If no policy is specified using the *policy-name* argument, the port device role is set to host and all inbound router traffic (for example, RA and redirect messages) is blocked.

If no VLAN is specified (which is equal to entering the **vlan all** keywords after the *policy-name* argument), RA guard traffic from all VLANs on the port is analyzed.

If specified, the VLAN parameter is either a single VLAN number from 1 through 4094 or a range of VLANs described by two VLAN numbers, the lesser one first, separated by a dash. Do not enter any spaces between comma-separated vlan parameters or in dash-specified ranges; for example, vlan 1-100,200,300-400.

Examples

In the following example, the IPv6 RA guard feature is applied on GigabitEthernet interface 0/0:

```
Device(config)# interface GigabitEthernet 0/0
Device(config-if)# ipv6 nd rguard attach-policy
```

ipv6 nd rguard policy

To define the router advertisement (RA) guard policy name and enter RA guard policy configuration mode, use the **ipv6 nd rguard policy** command in global configuration mode.

ipv6 nd rguardpolicy *policy-name*

Syntax Description

<i>policy-name</i>	IPv6 RA guard policy name.
--------------------	----------------------------

Command Default

An RA guard policy is not configured.

Command Modes

Global configuration (config)#

Command History

Release	Modification
12.2(50)SY	This command was introduced.
15.2(4)S	This command was integrated into Cisco IOS Release 15.2(4)S.
15.0(2)SE	This command was integrated into Cisco IOS Release 15.0(2)SE.
Cisco IOS XE Release 3.2SE	This command was integrated into Cisco IOS XE Release 3.2SE.

Usage Guidelines

Use the **ipv6 nd rguard policy** command to configure RA guard globally on a router. Once the device is in ND inspection policy configuration mode, you can use any of the following commands:

- **device-role**
- **drop-unsecure**
- **limit address-count**
- **sec-level minimum**
- **trusted-port**
- **validate source-mac**

After IPv6 RA guard is configured globally, you can use the **ipv6 nd rguard attach-policy** command to enable IPv6 RA guard on a specific interface.

Examples

The following example shows how to define the RA guard policy name as `policy1` and place the device in policy configuration mode:

```
Device(config)# ipv6 nd rguard policy policy1
Device(config-ra-guard)#
```


Related Commands*Table 1:*

Command	Description
device-role	Specifies the role of the device attached to the port.
drop-unsecure	Drops messages with no or invalid options or an invalid signature.
ipv6 nd rguard attach-policy	Applies the IPv6 RA guard feature on a specified interface.
limit address-count	Limits the number of IPv6 addresses allowed to be used on the port.
sec-level minimum	Specifies the minimum security level parameter value when CGA options are used.
trusted-port	Configures a port to become a trusted port.
validate source-mac	Checks the source MAC address against the link layer address.

ipv6 nd reachable-time

To configure the amount of time that a remote IPv6 node is considered reachable after some reachability confirmation event has occurred, use the **ipv6 nd reachable-time** command in interface configuration mode. To restore the default time, use the **no** form of this command.

ipv6 nd reachable-time *milliseconds*
no ipv6 nd reachable-time

Syntax Description

<i>milliseconds</i>	The amount of time that a remote IPv6 node is considered reachable (in milliseconds).
---------------------	---

Command Default

0 milliseconds (unspecified) is advertised in router advertisements and the value 30000 (30 seconds) is used for the neighbor discovery activity of the router itself.

Command Modes

Interface configuration

Command History

Release	Modification
12.2(2)T	This command was introduced.
12.0(21)ST	This command was integrated into Cisco IOS Release 12.0(21)ST.
12.0(22)S	This command was integrated into Cisco IOS Release 12.0(22)S.
12.2(14)S	This command was integrated into Cisco IOS Release 12.2(14)S.
12.2(28)SB	This command was integrated into Cisco IOS Release 12.2(28)SB.
12.2(25)SG	This command was integrated into Cisco IOS Release 12.2(25)SG.
12.2(33)SRA	This command was integrated into Cisco IOS Release 12.2(33)SRA.
12.2(33)SXH	This command was integrated into Cisco IOS Release 12.2(33)SXH.
15.2(2)SA2	This command was implemented on the Cisco ME 2600X Series Ethernet Access Switches.

Usage Guidelines

The configured time enables the router to detect unavailable neighbors. Shorter configured times enable the router to detect unavailable neighbors more quickly; however, shorter times consume more IPv6 network bandwidth and processing resources in all IPv6 network devices. Very short configured times are not recommended in normal IPv6 operation.

The configured time is included in all router advertisements sent out of an interface so that nodes on the same link use the same time value. A value of 0 means indicates that the configured time is unspecified by this router.

Examples

The following example configures an IPv6 reachable time of 1,700,000 milliseconds for Ethernet interface 0/0:

```
Router(config)# interface ethernet 0/0
Router(config-if)# ipv6 nd reachable-time 1700000
```

Related Commands

Command	Description
show ipv6 interface	Displays the usability status of interfaces configured for IPv6.

ipv6 nd resolution data limit

To configure the number of data packets queued pending Neighbor Discovery resolution, use the **ipv6 nd resolution data limit** command in global configuration mode.

ipv6 nd resolution data limit *number-of-packets*
no ipv6 nd resolution data limit *number-of-packets*

Syntax Description

<i>number-of-packets</i>	The number of queued data packets. The range is from 16 to 2048 packets.
--------------------------	--

Command Default

Queue limit is 16 packets.

Command Modes

Global configuration

Command History

Release	Modification
Cisco IOS XE Release 2.6	This command was introduced.

Usage Guidelines

The **ipv6 nd resolution data limit** command allows the customer to configure the number of data packets queued pending Neighbor Discovery resolution. IPv6 Neighbor Discovery queues a data packet that initiates resolution for an unresolved destination. Neighbor Discovery will only queue one packet per destination. Neighbor Discovery also enforces a global (per-router) limit on the number of packets queued. Once the global queue limit is reached, further packets to unresolved destinations are discarded. The minimum (and default) value is 16 packets, and the maximum value is 2048.

In most situations, the default value of 16 queued packets pending Neighbor Discovery resolution is sufficient. However, in some high-scalability scenarios in which the router needs to initiate communication with a very large number of neighbors almost simultaneously, then the value may be insufficient. This may lead to loss of the initial packet sent to some neighbors. In most applications, the initial packet is retransmitted, so initial packet loss generally is not a cause for concern. (Note that dropping the initial packet to an unresolved destination is normal in IPv4.) However, there may be some high-scale configurations where loss of the initial packet is inconvenient. In these cases, the customer can use the **ipv6 nd resolution data limit** command to prevent the initial packet loss by increasing the unresolved packet queue size.

Examples

The following example configures the global number of data packets held awaiting resolution to be 32:

```
Router(config)# ipv6 nd resolution data limit 32
```

ipv6 nd route-owner

To insert Neighbor Discovery-learned routes into the routing table with "ND" status and to enable ND autoconfiguration behavior, use the **ipv6 nd route-owner** command. To remove this information from the routing table, use the **no** form of this command.

ipv6 ndroute-owner

Syntax Description

This command has no arguments or keywords.

Command Default

The status of Neighbor Discovery-learned routes is "Static."

Command Modes

Global configuration (config)#

Command History

Release	Modification
15.2(1)T	This command was introduced.

Usage Guidelines

The **ipv6 nd route-owner** command inserts routes learned by Neighbor Discovery into the routing table with a status of "ND" rather than "Static" or "Connected."

This global command also enables you to use the **ipv6 nd autoconfig default** or **ipv6 nd autoconfig prefix** commands in interface configuration mode. If the **ipv6 nd route-owner** command is not issued, then the **ipv6 nd autoconfig default** and **ipv6 nd autoconfig prefix** commands are accepted by the router but will not work.

Examples

```
Device (config)# ipv6 nd route-owner
```

Related Commands

Command	Description
ipv6 nd autoconfig default	Allows Neighbor Discovery to install a default route to the Neighbor Discovery-derived default router.
ipv6 nd autoconfig prefix	Uses Neighbor Discovery to install all valid on-link prefixes from RAs received on the interface.

ipv6 nd router-preference

To configure a default router preference (DRP) for the router on a specific interface, use the **ipv6 nd router-preference** command in interface configuration mode. To return to the default DRP, use the **no** form of this command.

```
ipv6 nd router-preference {high | medium | low}
no ipv6 nd router-preference
```

Syntax Description

high	Preference for the router specified on an interface is high.
medium	Preference for the router specified on an interface is medium.
low	Preference for the router specified on an interface is low.

Command Default

Router advertisements (RAs) are sent with the **medium** preference.

Command Modes

Interface configuration

Command History

Release	Modification
12.4(2)T	This command was introduced.
12.2(33)SXH	This command was integrated into Cisco IOS Release 12.2(33)SXH.
12.2(33)SB	This command was integrated into Cisco IOS Release 12.2(33)SB.
Cisco IOS XE Release 2.1	This command was integrated into Cisco IOS XE Release 2.1.
Cisco IOS XE Release 3.2SE	This command was integrated into Cisco IOS XE Release 3.2SE.

Usage Guidelines

RA messages are sent with the DRP configured by the **ipv6 nd router-preference** command. If no DRP is configured, RAs are sent with a medium preference.

A DRP is useful when, for example, two routers on a link may provide equivalent, but not equal-cost, routing, and policy may dictate that hosts should prefer one of the routers.

Examples

The following example configures a DRP of high for the router on gigabit Ethernet interface 0/1:

```
Router(config)# interface Gigabit ethernet 0/1
Router(config-if)# ipv6 nd router-preference high
```

Related Commands

Command	Description
ipv6 nd ra interval	Configures the interval between IPv6 router advertisement transmissions on an interface.

Command	Description
show ipv6 interface	Displays the usability status of interfaces configured for IPv6.

ipv6 nd secured certificate-db

To configure the maximum number of entries in an IPv6 Secure Neighbor Discovery (SeND) certificate database, use the **ipv6 nd secured certificate-db** command in global configuration mode. To disable any maximum number of entries set for a SeND certificate database, use the **no** form of this command.

ipv6 nd secured certificate-db max-entries *max-entries-value*
no ipv6 nd secured certificate-db max-entries

Syntax Description	max-entries <i>max-entries-value</i>	Specifies the maximum number of entries in the certificate database. The range is from 1 to 1000.
---------------------------	---	---

Command Default No SeND certificate database is configured.

Command Modes Global configuration (config)

Command History	Release	Modification
	12.4(24)T	This command was introduced.

Usage Guidelines This command allows you to set up a maximum size for the certificate database (DB), to protect against denial of service (DoS) certificate flooding. When the limit is reached, new certificates are dropped.

The certificate DB is relevant on a router in host mode only, because it stores certificates received from routers.

Examples The following example configures a SeND certificate database with a maximum number of 500 entries:

```
Router(config)# ipv6 nd secured certificate-db max-entries 500
```

Related Commands	Command	Description
	ipv6 nd secured full-secure (global configuration)	Enables SeND security mode on a router.
	ipv6 nd secured full-secure (interface configuration)	Enables SeND security mode on a specified interface.
	ipv6 nd secured key-length	Configures SeND key-length options.
	ipv6 nd secured timestamp	Configures the SeND time stamp.
	ipv6 nd secured timestamp-db	Configures the maximum number of entries that did not reach the destination in a SeND time-stamp database.

ipv6 nd secured full-secure

To enable the secure mode for IPv6 Secure Neighbor Discovery (SeND) on a router, use the **ipv6 nd secured full-secure** command in global configuration mode. To disable SeND security mode, use the **no** form of this command.

ipv6 nd secured full-secure
no ipv6 nd secured full-secure

Syntax Description

This command has no arguments or keywords.

Command Default

Non-SeND neighbor discovery messages are accepted by the router.

Command Modes

Global configuration (config)

Command History

Release	Modification
12.4(24)T	This command was introduced.

Usage Guidelines

The **ipv6 nd secured full-secure** command in global configuration mode allows you to configure the router to accept or reject non-SeND neighbor discovery messages. If this command is enabled, non-SeND messages are rejected by the specified router.

Examples

The following example enables SeND security mode on a router:

```
Router(config)# ipv6 nd secured full-secure
```

Related Commands

Command	Description
ipv6 nd secured full-secure (interface configuration)	Enables SeND security mode on a specified interface.

ipv6 nd secured full-secure (interface)

To enable the secure mode for IPv6 Secure Neighbor Discovery (SeND) on a specified interface, use the **ipv6 nd secured full-secure** command in interface configuration mode. To provide the co-existence mode for secure and nonsecure neighbor discovery messages on an interface, use the **no** form of this command.

ipv6 nd secured full-secure
no ipv6 nd secured full-secure

Syntax Description This command has no arguments or keywords.

Command Default Non-SeND messages are accepted by the interface.

Command Modes Interface configuration (config-if)

Command History	Release	Modification
	12.4(24)T	This command was introduced.

Usage Guidelines The **ipv6 nd secured full-secure** command in interface configuration mode allows you to configure a specified interface to accept or reject non-SeND neighbor discovery messages. If this command is enabled, non-SeND messages are rejected by the interface. If this command is not enabled, secure and nonsecure neighbor discovery messages can coexist on the same interface.

Examples The following example enables SeND security mode on an interface:

```
Router(config)# interface Ethernet0/0
Router(config-if)# ipv6 nd secured full-secure
```

Related Commands	Command	Description
	ipv6 nd secured full-secure (global configuration)	Enables SeND security mode on a specified router.

ipv6 nd secured key-length

To configure IPv6 Secure Neighbor Discovery (SeND) key-length options, use the **ipv6 nd secured key-length** command in global configuration mode. To disable the key length, use the **no** form of this command.

ipv6 nd secured key-length [[{**minimum** | **maximum**}] *value*
no ipv6 nd secured key-length

Syntax Description	
minimum <i>value</i>	(Optional) Sets the minimum key-length value, which should be at least 384 bits. The range is from 384 to 2048 bits, and the default key-length value is 1024 bits.
maximum <i>value</i>	(Optional) Sets the maximum key-length value. The range is from 384 to 2048 bits, and the default key-length value is 1024 bits.

Command Default The key length is 1024 bits.

Command Modes Global configuration (config)

Command History	Release	Modification
	12.4(24)T	This command was introduced.

Usage Guidelines When used by SeND, the key length is checked against the key-length value, as set in the **ipv6 nd secured key-length** command. When packets are received from a neighbor with a key length that is out of the configured boundaries, the packets are treated as unsecure.

Examples The following example sets the minimum key-length value to 512 bits and the maximum value to 1024 bits:

```
Router(config)# ipv6 nd secured key-length minimum 512
Router(config)# ipv6 nd secured key-length maximum 1024
```

Related Commands	Command	Description
	ipv6 nd secured certificate-db	Configures the maximum number of entries in a SeND certificate database.
	ipv6 nd secured full-secure (global configuration)	Enables SeND security mode on a specified router.
	ipv6 nd secured full-secure (interface configuration)	Enables SeND security mode on a specified interface.
	ipv6 nd secured timestamp	Configures the SeND time stamp.
	ipv6 nd secured timestamp-db	Configures the maximum number of entries in a SeND time-stamp database.

ipv6 nd secured sec-level

To configure the minimum security value that IPv6 Secure Neighbor Discovery (SeND) will accept from its peer, use the **ipv6 nd secured sec-level** command in global configuration mode. To disable the security level, use the **no** form of this command.

ipv6 nd secured sec-level [**minimum value**]
no ipv6 nd secured sec-level

Syntax Description

minimum <i>value</i>	(Optional) Sets the minimum security level, which is a value from 0 through 7. The default security level is 1.
----------------------	---

Command Default

The default security level is 1.

Command Modes

Global configuration (config)

Command History

Release	Modification
12.4(24)T	This command was introduced.

Usage Guidelines

The **ipv6 nd secured sec-level** command allows the user to configure the minimum security value the router will accept from its peer.

Examples

The following example sets the minimum security level to 2:

```
Router(config)# ipv6 nd secured sec-level 2
```

Related Commands

Command	Description
ipv6 nd secured certificate-db	Configures the maximum number of entries in a SeND certificate database.
ipv6 nd secured full-secure (global configuration)	Enables SeND security mode on a specified router.
ipv6 nd secured full-secure (interface configuration)	Enables SeND security mode on a specified interface.
ipv6 nd secured key-length	Configures SeND key-length options.
ipv6 nd secured timestamp	Configures the SeND time stamp.
ipv6 nd secured timestamp-db	Configures the maximum number of unreachable entries in a SeND time-stamp database.

ipv6 nd secured timestamp

To configure the IPv6 Secure Neighbor Discovery (SeND) time stamp, use the **ipv6 nd secured timestamp** command in interface configuration mode. To return to the default settings, use the **no** form of this command.

```
ipv6 nd secured timestamp {delta value | fuzz value}
no ipv6 nd secured timestamp
```

Syntax Description	Parameter	Description
	delta <i>value</i>	Specifies the maximum time difference accepted between the sender and the receiver. Default value is 300 seconds.
	fuzz <i>value</i>	Specifies the maximum age of the message, when the delta is taken into consideration; that is, the amount of time, in seconds, that a packet can arrive after the delta value before being rejected. Default value is 1 second.

Command Default Default time-stamp values are used.

Command Modes Interface configuration (config-if)

Command History	Release	Modification
	12.4(24)T	This command was introduced.

Usage Guidelines The **ipv6 nd secured timestamp** command configures the amount of time the router waits before it accepts or rejects packets it has received.

Examples The following example configures the SeND time stamp to be 600 seconds:

```
Router(config)# interface Ethernet0/0
Router(config-if)# ipv6 nd secured timestamp delta 600
```

Related Commands	Command	Description
	ipv6 nd secured certificate-db	Configures the maximum number of entries in a SeND certificate database.
	ipv6 nd secured full-secure (global configuration)	Enables SeND security mode on a specified router.
	ipv6 nd secured full-secure (interface configuration)	Enables SeND security mode on a specified interface.
	ipv6 nd secured key-length	Configures SeND key-length options.
	ipv6 nd secured timestamp-db	Configures the maximum number of unreachable entries in a SeND time-stamp database.

ipv6 nd secured timestamp-db

To configure the maximum number of unreachable entries in an IPv6 Secure Neighbor Discovery (SeND) time-stamp database, use the **ipv6 nd secured timestamp-db** command in global configuration mode. To return to the default settings, use the **no** form of this command.

ipv6 nd secured timestamp-db max-entries *max-entries-value*
no ipv6 nd secured timestamp-db max-entries

Syntax Description	max-entries <i>max-entries-value</i>	Specifies the maximum number of entries in the certificate database. The range is from 1 to 1000.
---------------------------	---	---

Command Default No time-stamp database is configured.

Command Modes Global configuration (config)

Command History	Release	Modification
	12.4(24)T	This command was introduced.

Examples The following example configures the time-stamp database on a router:

```
Router(config)# ipv6 nd secured timestamp-db max-entries 345
```

Related Commands	Command	Description
	ipv6 nd secured certificate-db	Configures the maximum number of entries in a SeND certificate database.
	ipv6 nd secured full-secure (global configuration)	Enables SeND security mode on a specified router.
	ipv6 nd secured full-secure (interface configuration)	Enables SeND security mode on a specified interface.
	ipv6 nd secured key-length	Configures SeND key-length options.
	ipv6 nd secured timestamp	Configures the SeND time stamp.

ipv6 nd secured trustanchor

To specify an IPv6 Secure Neighbor Discovery (SeND) trusted anchor on an interface, use the **ipv6 nd secured trustanchor** command in interface configuration mode. To remove a trusted anchor, use the **no** form of this command.

```
ipv6 nd secured trustanchor trustanchor-name
no ipv6 nd secured trustanchor trustanchor-name
```

Syntax Description	<i>trustanchor-name</i>	The name to be found in the certificate of the trustpoint.
---------------------------	-------------------------	--

Command Default No trusted anchor is defined.

Command Modes Interface configuration (config-if)

Command History	Release	Modification
	12.4(24)T	This command was introduced.

Usage Guidelines The **ipv6 nd secured trustanchor** command is used to select the certificate authority (CA) you want to authenticate. The trusted anchors configured by this command act as as references to the trustpoints configured.

A crypto Public Key Infrastructure (PKI) trustpoint can be a self-signed root CA or a subordinate CA. The *trustpoint-name* argument refers to the name to be found in the certificate of the trustpoint.

The **ipv6 nd secured trustanchor** and **ipv6 nd secured trustpoint** commands both generate an entry in the SeND configuration database that points to the trustpoint provided. More than one trustpoint can be provided for each command, and the same trustpoint can be used in both commands.

Examples

The following example specifies trusted anchor anchor1 on Ethernet interface 0/0:

```
Router(config)# interface Ethernet0/0
Router(config-if)# ipv6 nd secured trustanchor anchor1
```

Related Commands	Command	Description
	crypto pki trustpoint	Declares the trustpoint that your router should use.
	ipv6 nd secured trustpoint	Specifies which trustpoint should be used for selecting the certificate to advertise.

ipv6 nd secured trustpoint

To specify which trustpoint should be used in the ipv6 Secure Neighbor Discovery (SeND) protocol for selecting the certificate to advertise, use the **ipv6 nd secured trustpoint** command in interface configuration mode. To disable the trustpoint, use the **no** form of this command.

ipv6 nd secured trustpoint *trustpoint-name*
no ipv6 nd secured trustpoint *trustpoint-name*

Syntax Description

<i>trustpoint-name</i>	The name to be found in the certificate of the trustpoint.
------------------------	--

Command Default

SeND is not enabled on a specified interface.

Command Modes

Interface configuration (config-if)

Command History

Release	Modification
12.4(24)T	This command was introduced.

Usage Guidelines

The **ipv6 nd secured trustpoint** command enables SeND on an interface and specifies which trustpoint should be used. The trustpoint points to the Rivest, Shamir, and Adelman (RSA) key pair and the trusted anchor (which is the certificate authority [CA] signing your certificate).

The **ipv6 nd secured trustpoint** and **ipv6 nd secured trustanchor** commands both generate an entry in the SeND configuration database that points to the trustpoint provided. More than one trustpoint can be provided for each command, and the same trustpoint can be used in both commands. However, the trustpoint provided in the **ipv6 nd secured trustpoint** command must include a router certificate and the signing CA certificate. It may also include the certificate chain up to the root certificate provided by a CA that hosts (connected to the router) will trust.

The trustpoint provided in the **ipv6 nd secured trustanchor** command must only include a CA certificate.

Examples

The following example specifies trusted anchor anchor1 on Ethernet interface 0/0:

```
Router(config)# interface Ethernet0/0
Router(config-if)# ipv6 nd secured trustpoint trustpoint1
```

Related Commands

Command	Description
crypto pki trustpoint	Declares the trustpoint that your router should use.
ipv6 nd secured trustanchor	Specifies a trusted anchor on an interface.

ipv6 nd suppress attach-policy

To apply the IPv6 neighbor discovery (ND) suppress feature on a specified interface, use the **ipv6 nd suppress attach-policy** command in interface configuration mode.

ipv6 nd suppress attach-policy [*policy-name* **vlan** {**add** | **except** | **none** | **remove** | **all**} *vlan* [*vlan1*, *vlan2*, *vlan3*...]]

Syntax Description

<i>policy-name</i>	(Optional) IPv6 ND suppress policy name.
vlan	(Optional) Applies the IPv6 ND suppress feature to a VLAN on the interface.
add	Adds a VLAN to be inspected.
except	All VLANs are inspected except the one specified.
none	No VLANs are inspected.
remove	Removes the specified VLAN from IPv6 ND suppression.
all	ND traffic from all VLANs on the port is inspected.
<i>vlan</i>	(Optional) A specific VLAN on the interface. More than one VLAN can be specified (<i>vlan1</i> , <i>vlan2</i> , <i>vlan3</i> ...). The range of available VLAN numbers is from 1 through 4094.

Command Default

An IPv6 ND suppress policy is not configured.

Command Modes

Interface configuration (config-if)

Command History

Release	Modification
15.3(1)S	This command was introduced.
Cisco IOS XE Release 3.2SE	This command was integrated into Cisco IOS XE Release 3.2SE.

Usage Guidelines

If no VLAN is specified (which is equal to entering the **vlan all** keywords after the *policy-name* argument), RA guard traffic from all VLANs on the port is analyzed.

If specified, the VLAN parameter is either a single VLAN number from 1 through 4094 or a range of VLANs described by two VLAN numbers, the lesser one first, separated by a dash. Do not enter any spaces between comma-separated vlan parameters or in dash-specified ranges; for example, `vlan 1-100,200,300-400`.

Examples

In the following example, the IPv6 ND suppress feature is applied on Ethernet interface 0/0:

```
Device(config)# interface Ethernet 0/0
Device(config-if)# ipv6 nd suppress attach-policy
```

Related Commands

Command	Description
ipv6 nd suppress policy	Enables IPv6 ND multicast suppress and enter ND suppress policy configuration mode

ipv6 nd suppress policy

To enable IPv6 Neighbor Discovery (ND) multicast suppress and enter ND suppress policy configuration mode, use the **ipv6 nd suppress policy** command in global configuration mode.

ipv6 nd suppress policy *policy-name*

Syntax Description	<i>policy-name</i>	IPv6 ND suppress policy name.
---------------------------	--------------------	-------------------------------

Command Default An ND suppress policy is not configured.

Command Modes Global configuration (config)

Command History	Release	Modification
	15.3(1)S	This command was introduced.
	Cisco IOS XE Release 3.2SE	This command was integrated into Cisco IOS XE Release 3.2SE.

Usage Guidelines Use the **ipv6 nd suppress policy** command to configure NA suppress globally on a device. After IPv6 ND suppress is configured globally, you can use the **ipv6 nd suppress attach-policy** command to enable IPv6 ND suppress on a specific interface.

Examples The following example shows how to define the ND suppress policy name as policy1 and place the device in policy configuration mode:

```
Device(config)# ipv6 nd suppress policy policy1
Device(config-nd-suppress)#
```

Related Commands	Command	Description
	ipv6 nd suppress attach-policy	Applies the IPv6 ND suppress feature on a specified interface.

ipv6 neighbor

To configure a static entry in the IPv6 neighbor discovery cache, use the **ipv6 neighbor** command in global configuration mode. To remove a static IPv6 entry from the IPv6 neighbor discovery cache, use the **no** form of this command.

ipv6 neighbor *ipv6-address interface-type interface-number hardware-address*
no ipv6 neighbor *ipv6-address interface-type interface-number*

Syntax Description

<i>ipv6-address</i>	The IPv6 address that corresponds to the local data-link address. This argument must be in the form documented in RFC 2373 where the address is specified in hexadecimal using 16-bit values between colons.
<i>interface-type</i>	The specified interface type. For supported interface types, use the question mark (?) online help function.
<i>interface-number</i>	The specified interface number.
<i>hardware-address</i>	The local data-link address (a 48-bit address).

Command Default

Static entries are not configured in the IPv6 neighbor discovery cache.

Command Modes

Global configuration

Command History

Release	Modification
12.2(8)T	This command was introduced.
12.0(21)ST	This command was integrated into Cisco IOS Release 12.0(21)ST.
12.0(22)S	This command was integrated into Cisco IOS Release 12.0(22)S.
12.2(14)S	This command was integrated into Cisco IOS Release 12.2(14)S.
12.2(28)SB	This command was integrated into Cisco IOS Release 12.2(28)SB.
12.2(33)SRA	This command was integrated into Cisco IOS Release 12.2(33)SRA.
12.2(33)SXH	This command was integrated into Cisco IOS Release 12.2(33)SXH.
15.2(2)SA2	This command was implemented on the Cisco ME 2600X Series Ethernet Access Switches.

Usage Guidelines

The **ipv6 neighbor** command is similar to the **arp** (global) command.

If an entry for the specified IPv6 address already exists in the neighbor discovery cache--learned through the IPv6 neighbor discovery process--the entry is automatically converted to a static entry.

Use the **show ipv6 neighbors** command to view static entries in the IPv6 neighbor discovery cache. A static entry in the IPv6 neighbor discovery cache can have one of the following states:

- INCMP (Incomplete)--The interface for this entry is down.
- REACH (Reachable)--The interface for this entry is up.



Note Reachability detection is not applied to static entries in the IPv6 neighbor discovery cache; therefore, the descriptions for the INCMP and REACH states are different for dynamic and static cache entries. See the **show ipv6 neighbors** command for descriptions of the INCMP and REACH states for dynamic cache entries.

The **clear ipv6 neighbors** command deletes all entries in the IPv6 neighbor discovery cache, except static entries. The **no ipv6 neighbor** command deletes a specified static entry from the neighbor discovery cache; the command does not remove dynamic entries--learned from the IPv6 neighbor discovery process--from the cache. Disabling IPv6 on an interface by using the **no ipv6 enable** command or the **no ipv6 unnumbered** command deletes all IPv6 neighbor discovery cache entries configured for that interface, except static entries (the state of the entry changes to INCMP).

Static entries in the IPv6 neighbor discovery cache are not modified by the neighbor discovery process.



Note Static entries for IPv6 neighbors can be configured only on IPv6-enabled LAN and ATM LAN Emulation interfaces.

Examples

The following example configures a static entry in the IPv6 neighbor discovery cache for a neighbor with the IPv6 address 2001:0DB8::45A and link-layer address 0002.7D1A.9472 on Ethernet interface 1:

```
Router(config)# ipv6 neighbor 2001:0DB8::45A ethernet1 0002.7D1A.9472
```

Related Commands

Command	Description
arp (global)	Adds a permanent entry in the ARP cache.
clear ipv6 neighbors	Deletes all entries in the IPv6 neighbor discovery cache, except static entries.
no ipv6 enable	Disables IPv6 processing on an interface that has not been configured with an explicit IPv6 address.
no ipv6 unnumbered	Disables IPv6 on an unnumbered interface.
show ipv6 neighbors	Displays IPv6 neighbor discovery cache information.

ipv6 neighbor binding

To change the defaults of neighbor binding entries in a binding table, use the **ipv6 neighbor binding** command in global configuration mode. To return the networking device to its default, use the **no** form of this command.

ipv6 neighbor binding [{**reachable-lifetime** *value* | **stale-lifetime** *value*}]
no ipv6 neighbor binding

Syntax Description

reachable-lifetime <i>value</i>	(Optional) The maximum time, in seconds, an entry is considered reachable without getting a proof of reachability (direct reachability through tracking, or indirect reachability through Neighbor Discovery protocol [NDP] inspection). After that, the entry is moved to stale. The range is from 1 through 3600 seconds, and the default is 300 seconds (or 5 minutes).
stale-lifetime <i>value</i>	(Optional) The maximum time, in seconds, a stale entry is kept in the binding table before the entry is deleted or proof is received that the entry is reachable. <ul style="list-style-type: none"> The default is 24 hours (86,400 seconds).
down-lifetime <i>value</i>	(Optional) The maximum time, in seconds, an entry learned from a down interface is kept in the binding table before the entry is deleted or proof is received that the entry is reachable. <ul style="list-style-type: none"> The default is 24 hours (86,400 seconds).

Command Default

Reachable lifetime: 300 seconds Stale lifetime: 24 hours Down lifetime: 24 hours

Command Modes

Global configuration (config)

Command History

Release	Modification
12.2(50)SY	This command was introduced.

Usage Guidelines

Use the **ipv6 neighbor binding** command to configure information about individual entries in a binding table. If no keywords or arguments are configured, the IPv6 neighbor binding entry defaults are used.

If the **tracking reachable-lifetime** command is configured, it overrides **ipv6 neighbor binding reachable-lifetime** configuration. If the **tracking stale-lifetime** command is configured, it overrides **ipv6 neighbor binding stale-lifetime** configuration.

Examples

The following example shows how to change the reachable lifetime for binding entries to 100 seconds:

```
Router(config)# ipv6 neighbor binding reachable-entries 100
```

Related Commands

Command	Description
ipv6 neighbor tracking	Tracks entries in the binding table.

Command	Description
tracking	Overrides the default tracking policy on a port.

ipv6 neighbor binding down-lifetime

To change the default of a neighbor binding entry's down lifetime, use the **ipv6 neighbor binding down-lifetime** command in global configuration mode. To return the networking device to its default, use the **no** form of this command.

```
ipv6 neighbor binding down-lifetime {value | infinite}
no ipv6 neighbor binding down-lifetime
```

Syntax Description

<i>value</i>	The maximum time, in minutes, an entry learned from a down interface is kept in the table before deletion. The range is from 1 to 3600 minutes. <ul style="list-style-type: none"> The default is 24 hours (86,400 seconds).
<i>infinite</i>	Keeps an entry in the binding table for an infinite amount of time.

Command Default

A neighbor binding entry is down for 24 hours before it is deleted from the binding table.

Command Modes

Global configuration (config)

Command History

Release	Modification
12.2(50)SY	This command was introduced.

Usage Guidelines

Use the **ipv6 neighbor binding down-lifetime** command to change the amount of time a neighbor binding is down before that binding is removed from the binding table.

Examples

The following example shows how to change a binding entry's down lifetime to 2 minutes before it is deleted from the binding table:

```
Router(config)# ipv6 neighbor binding down-lifetime 2
```

Related Commands

Command	Description
ipv6 neighbor tracking	Tracks entries in the binding table.

ipv6 neighbor binding interface

To add a static entry to the binding table database for an interface, use the **ipv6 neighbor binding interface** command in global configuration mode. To remove the static entry, use the **no** form of this command.

ipv6 neighbor binding *IPv6-address* **interface** *type number* [{*hardware-address*}] **tracking** [{**disable** | **enable** | **retry-interval** *seconds*}] [**reachable-lifetime** *seconds*]
no ipv6 neighbor binding interface *type number*

Syntax Description		
	<i>IPv6-address</i>	IPv6 address of the static entry.
	<i>hardware-address</i>	(Optional) Hardware address.
	tracking	(Optional) Verifies a static entry's reachability directly.
	disable	(Optional) Disables tracking for a particular static entry.
	enable	(Optional) Enables tracking for a particular static entry.
	retry-interval <i>seconds</i>	(Optional) Verifies a static entry's reachability, in seconds, at the configured interval. The range is from 1 to 3600, and the default is 300.
	reachable-lifetime <i>seconds</i>	(Optional) Specifies the maximum time, in seconds, an entry is considered reachable without getting a proof of reachability (direct reachability through tracking, or indirect reachability through Neighbor Discovery Protocol [NDP] inspection). After that, the entry is moved to stale. The range is from 1 to 3600 seconds, and the default is 300 seconds.

Command Default Static entries are not added to the binding table database for an interface.

Command Modes Global configuration (config)

Command History	Release	Modification
	Cisco IOS XE Release 3.9S	This command was introduced.

Usage Guidelines The **ipv6 neighbor binding interface** command is used to control the content of the binding table. Use this command to add a static entry in the binding table database. The binding table manager is responsible for aging out entries and directly verifying their reachability by probing them (if the **tracking** keyword is enabled). Use of the **tracking** keyword overrides any general behavior provided globally by the **ipv6 neighbor tracking** command for this static entry. The **disable** keyword disables tracking for this static entry. The **reachable-lifetime** keyword defines the maximum time (300 seconds) that the entry will be kept once it is determined not to be reachable (or stale).

Examples The following example shows how to change the reachable lifetime for binding entries to 100 seconds:

```
Router(config)# ipv6 neighbor binding 2001:DB8:0:ABCD::1 interface GigabitEthernet 0/0/1
reachable-lifetime 100
```

Related Commands

Command	Description
ipv6 neighbor binding max-entries	Specifies the maximum number of entries that are allowed to be inserted in the cache.
ipv6 neighbor tracking	Tracks entries in the binding table.

ipv6 neighbor binding logging

To enable the logging of binding table main events, use the **ipv6 neighbor binding logging** command in global configuration mode. To disable this function, use the **no** form of this command.

ipv6 neighbor binding logging
no ipv6 neighbor binding logging

Syntax Description This command has no arguments or keywords.

Command Default Binding table events are not logged.

Command Modes Global configuration (config)

Release	Modification
12.2(50)SY	This command was introduced.
15.0(2)SE	This command was integrated into Cisco IOS Release 15.0(2)SE.
15.3(1)S	This command was integrated into Cisco IOS Release 15.3(1)S.
Cisco IOS XE Release 3.2SE	This command was integrated into Cisco IOS XE Release 3.2SE.

Usage Guidelines The **ipv6 neighbor binding logging** command enables the logging of the following binding table events:

- An entry is inserted into the binding table.
- A binding table entry was updated.
- A binding table entry was deleted from the binding table.
- A binding table entry was not inserted into the binding table, possibly because of a collision with an existing entry, or because the maximum number of entries has been reached.

Examples

The following example shows how to enable binding table event logging:

```
Router(config)# ipv6 neighbor binding logging
```

Command	Description
ipv6 neighbor binding vlan	Adds a static entry to the binding table database.
ipv6 neighbor tracking	Tracks entries in the binding table.
ipv6 snooping logging packet drop	Configures IPv6 snooping security logging.

ipv6 neighbor binding max-entries

To specify the maximum number of entries that are allowed to be inserted in the binding table cache, use the **ipv6 neighbor binding max-entries** command in global configuration mode. To return to the default, use the **no** form of this command.

ipv6 neighbor binding max-entries *entries* [{**vlan-limit** *number* | **interface-limit** *number* | **mac-limit** *number*}]

no ipv6 neighbor binding max-entries *entries* [{**vlan-limit** | **mac-limit**}]

Syntax Description

<i>entries</i>	Number of entries that can be inserted into the cache.
vlan-limit <i>number</i>	(Optional) Specifies a neighbor binding limit per number of VLANs.
interface-limit <i>number</i>	(Optional) Specifies a neighbor binding limit per interface.
mac-limit <i>number</i>	(Optional) Specifies a neighbor binding limit per number of Media Access Control (MAC) addresses.

Command Default

This command is disabled.

Command Modes

Global configuration (config)

Command History

Release	Modification
12.2(50)SY	This command was introduced.
15.0(2)SE	This command was integrated into Cisco IOS Release 15.0(2)SE.
15.3(1)S	This command was integrated into Cisco IOS Release 15.3(1)S.
Cisco IOS XE Release 3.2SE	This command was integrated into Cisco IOS XE Release 3.2SE.

Usage Guidelines

The **ipv6 neighbor binding max-entries** command is used to control the content of the binding table. This command specifies the maximum number of entries that are allowed to be inserted in the binding table cache. Once this limit is reached, new entries are refused, and the Neighbor Discovery Protocol (NDP) traffic source with the new entry is dropped.

If the maximum number of entries specified is lower than the current number of entries in the database, no entries are cleared, and the new threshold is reached after normal cache attrition.

The maximum number of entries can be set globally per VLAN, interface, or MAC addresses.

Examples

The following example shows how to specify globally the maximum number of entries inserted into the cache:

```
Router(config)# ipv6 neighbor binding max-entries 100
```

Related Commands

Command	Description
ipv6 neighbor binding vlan	Adds a static entry to the binding table database.
ipv6 neighbor tracking	Tracks entries in the binding table.

ipv6 neighbor binding stale-lifetime

To set the length of time a stale entry is kept in the binding table, use the **ipv6 neighbor binding stale-lifetime** command in global configuration mode. To return to the default setting, use the **no** form of this command.

ipv6 neighbor binding stale-lifetime {*value* | **infinite**}
no ipv6 neighbor binding

Syntax Description

<i>value</i>	The maximum time, in minutes, a stale entry is kept in the table before it is deleted or some proof of reachability is seen. The range is from 1 to 3600 minutes, and the default is 24 hours (or 1440 minutes).
infinite	Keeps an entry in the binding table for an infinite amount of time.

Command Default

Stale lifetime: 1440 minutes (24 hours)

Command Modes

Global configuration (config)

Command History

Release	Modification
12.2(50)SY	This command was introduced.

Usage Guidelines

Use the **ipv6 neighbor binding stale-lifetime** command to configure the length of time a stale entry is kept in the binding table before it is removed.

Examples

The following example shows how to change the stale lifetime for a binding entry to 720 minutes (or 12 hours):

```
Router(config)# ipv6 neighbor binding stale lifetime 720
```

Related Commands

Command	Description
ipv6 neighbor binding	Changes the defaults of neighbor binding entries in a binding table.

ipv6 neighbor binding vlan

To add a static entry to the binding table database, use the **ipv6 neighbor binding vlan** command in global configuration mode. To remove the static entry, use the **no** form of this command.

```
ipv6 neighbor binding vlan vlan-id {interface type number ipv6-address mac-address} [{tracking
[disable | enable | retry-interval value]}] reachable-lifetime value}]
no ipv6 neighbor binding vlan vlan-id
```

Syntax Description		
	<i>vlan-id</i>	ID of the specified VLAN.
	interface <i>type number</i>	Adds static entries by the specified interface type and number.
	<i>ipv6-address</i>	IPv6 address of the static entry.
	<i>mac-address</i>	Media Access Control (MAC) address of the static entry.
	tracking	(Optional) Verifies a static entry's reachability directly.
	disable	(Optional) Disables tracking for a particular static entry.
	enable	(Optional) Enables tracking for a particular static entry.
	retry-interval <i>value</i>	(Optional) Verifies a static entry's reachability, in seconds, at the configured interval. The range is from 1 to 3600, and the default is 300.
	reachable-lifetime <i>value</i>	(Optional) Specifies the maximum time, in seconds, an entry is considered reachable without getting a proof of reachability (direct reachability through tracking, or indirect reachability through Neighbor Discovery Protocol [NDP] inspection). After that, the entry is moved to stale. The range is from 1 to 3600 seconds, and the default is 300 seconds.

Command Default Retry interval: 300 seconds
 Reachable lifetime: 300 seconds

Command Modes Global configuration (config)

Command History	Release	Modification
	12.2(50)SY	This command was introduced.
	15.0(2)SE	This command was integrated into Cisco IOS Release 15.0(2)SE.
	15.3(1)S	This command was integrated into Cisco IOS Release 15.3(1)S.
	Cisco IOS XE Release 3.2SE	This command was integrated into Cisco IOS XE Release 3.2SE.

Usage Guidelines

The **ipv6 neighbor binding vlan** command is used to control the content of the binding table. Use this command to add a static entry in the binding table database. The binding table manager is responsible for aging out entries and verifying their reachability directly by probing them (if the **tracking** keyword is enabled). Use of the **tracking** keyword overrides any general behavior provided globally by the **ipv6 neighbor tracking** command for this static entry. The **disable** keyword disables tracking for this static entry. The **stale-lifetime** keyword defines the maximum time the entry will be kept once it is determined to be not reachable (or stale).

Examples

The following example shows how to change the reachable lifetime for binding entries to 100 seconds:

```
Router(config)# ipv6 neighbor binding vlan reachable-lifetime 100
```

Related Commands

Command	Description
ipv6 neighbor binding max-entries	Specifies the maximum number of entries that are allowed to be inserted in the cache.
ipv6 neighbor tracking	Tracks entries in the binding table.

ipv6 neighbor tracking

To track entries in the binding table, use the **ipv6 neighbor tracking** command in global configuration mode. To disable entry tracking, use the **no** form of this command.

ipv6 neighbor tracking [**retry-interval** *value*]
no ipv6 neighbor tracking [**retry-interval** *value*]

Syntax Description	retry-interval <i>value</i> (Optional) Verifies a static entry's reachability at the configured interval time, in seconds, between two probings. The range is from 1 to 3600, and the default is 300.
---------------------------	--

Command Default Entries in the binding table are not tracked.

Command Modes Global configuration (config)

Command History	Release	Modification
	12.2(50)SY	This command was introduced.
	15.0(2)SE	This command was integrated into Cisco IOS Release 15.0(2)SE.
	15.3(1)S	This command was integrated into Cisco IOS Release 15.3(1)S.
	Cisco IOS XE Release 3.2SE	This command was integrated into Cisco IOS XE Release 3.2SE.

Usage Guidelines The **ipv6 neighbor tracking** command enables the tracking of entries in the binding table. Entry reachability is tested at every interval configured by the optional **retry-interval** keyword (or every 300 seconds, which is the default retry interval) using the neighbor unreachability detection (NUD) mechanism used for directly tracking neighbor reachability.

Reachability can also be established indirectly by using Neighbor Discovery Protocol (NDP) inspection up to the VERIFY_MAX_RETRIES value (the default is 10 seconds). When there is no response, entries are considered stale and are deleted after the stale lifetime value is reached (the default is 1440 minutes).

When the **ipv6 neighbor tracking** command is disabled, entries are considered stale after the reachable lifetime value is met (the default is 300 seconds) and deleted after the stale lifetime value is met.

To change the default values of neighbor binding entries in a binding table, use the **ipv6 neighbor binding** command.

Examples

The following example shows how to track entries in a binding table:

```
Router(config)# ipv6 neighbor tracking
```

Related Commands	Command	Description
	ipv6 neighbor binding	Changes the defaults of neighbor binding entries in a binding table.

ipv6 next-hop-self eigrp

To instruct a device configured with the Enhanced Interior Gateway Routing Protocol (EIGRP) that the IPv6 next hop is the local outbound interface address, use the **ipv6 next-hop-self eigrp** command in interface configuration mode. To instruct EIGRP to use the received next hop instead of the local outbound interface, use the **no** form of this command.

ipv6 next-hop-self eigrp *as-number*
no ipv6 next-hop-self eigrp *as-number* [{**no-ecmp-mode**}]

Syntax Description

<i>as-number</i>	Autonomous system number.
no-ecmp-mode	(Optional) Evaluates all paths to a network before advertising the paths out of an interface.

Command Default

The IPv6 next-hop-self state is enabled.

Command Modes

Interface configuration (config-if)

Command History

Release	Modification
12.4(6)T	This command was introduced.
12.2(33)SRB	This command was integrated into Cisco IOS Release 12.2(33)SRB.
12.2(33)SXH	This command was integrated into Cisco IOS Release 12.2(33)SXH.
Cisco IOS XE Release 2.1	This command was integrated into Cisco IOS XE Release 2.1.
15.2(1)S	This command was integrated into Cisco IOS Release 15.2(1)S. The no-ecmp-mode keyword was added.
Cisco IOS XE Release 3.5S	This command was modified. The no-ecmp-mode keyword was added.
15.2(3)T	This command was modified. The no-ecmp-mode keyword was added.

Usage Guidelines

EIGRP, by default, sets the next-hop value to the local outbound interface address for routes that it is advertising, even when advertising those routes back out of the same interface on which they were learned. To change this default, use the **no ipv6 next-hop-self eigrp** command to instruct EIGRP to use the received next-hop value when advertising these routes. Some exceptions to this guideline are as follows:

- If your topology does not require spoke-to-spoke dynamic tunnels, you need not configure the **no ipv6 next-hop-self eigrp** command.
- If your topology requires spoke-to-spoke dynamic tunnels, you must use process switching on the tunnel interface on spoke devices. Otherwise, you will need to use a different routing protocol over Dynamic Multipoint VPN (DMVPN).

The **no-ecmp-mode** option is an enhancement to the **no ipv6 next-hop-self eigrp** command. When this option is enabled, all routes to a network in the EIGRP table are evaluated to check whether routes advertised from an interface were learned on the same interface. If a route advertised by an interface was learned on the same

interface, the **no ipv6 next-hop-self eigrp** configuration is honored and the received next hop is used to advertise this route. Disabling the IPv6 next-hop self functionality is primarily useful in DMVPN spoke-to-spoke topologies.

Examples

The following example shows how to change the default IPv6 next-hop value by disabling the **ipv6 next-hop-self** functionality and configuring EIGRP to use the received next-hop value to advertise routes:

```
Device(config)# interface serial 0
Device(config-if)# no ipv6 next-hop-self eigrp 1 no-ecmp-mode
```

Related Commands

Command	Description
next-hop-self	Instructs an EIGRP device that the IPv6 next hop is the local outbound interface.
ip next-hop-self eigrp	Enables EIGRP to advertise routes with the local outbound interface address as the next hop.

ipv6 nhrp authentication

To configure the authentication string for an interface using the Next Hop Resolution Protocol (NHRP), use the **ip nhrp authentication** command in interface configuration mode. To remove the authentication string, use the **no** form of this command.

ipv6 nhrp authentication *string*
no ipv6 nhrp authentication [*string*]

Syntax Description

<i>string</i>	Authentication string configured for the source and destination stations that controls whether NHRP stations allow intercommunication. The string can be up to eight characters long.
---------------	---

Command Default

No authentication string is configured. Cisco IOS software adds no authentication option to NHRP packets it generates.

Command Modes

Interface configuration (config-if)

Command History

Release	Modification
12.4(20)T	This command was introduced.

Usage Guidelines

All routers configured with NHRP within one logical nonbroadcast multiaccess (NBMA) network must share the same authentication string.

Examples

In the following example, the authentication string named `examplexx` must be configured in all devices using NHRP on the interface before NHRP communication occurs:

```
ip nhrp authentication examplexx
```

ipv6 nhrp cache non-authoritative

To make a hub non-authoritative to respond to resolution requests, use the **ipv6 nhrp cache non-authoritative** command.

To make a hub authoritative to respond to resolution requests, use the **no** form of the command.

ipv6 nhrp cache non-authoritative

no ipv6 nhrp cache non-authoritative

Command Default

By default this command is configured and the hub is non-authoritative to respond to resolution requests.

Command Modes

Interface configuration

Command History

Release	Modification
IOS XE Release 16.8.1	Command introduced.

Example

```
interface tunnel0
 no ipv6 nhrp cache non-authoritative
```

ipv6 nhrp holdtime

To change the number of seconds that Next Hop Resolution Protocol (NHRP) nonbroadcast multiaccess (NBMA) addresses are advertised as valid in authoritative NHRP responses, use the **ipv6 nhrp holdtime** command in interface configuration mode. To restore the default value, use the **no** form of this command.

ipv6 nhrp holdtime *seconds*
no ipv6 nhrp holdtime [*seconds*]

Syntax Description

<i>seconds</i>	Time, in seconds, that NBMA addresses are advertised as valid in positive authoritative NHRP responses.
----------------	---

Command Default

7200 seconds (2 hours)

Command Modes

Interface configuration (config-if)

Command History

Release	Modification
12.4(20)T	This command was introduced.

Usage Guidelines

The **ipv6 nhrp holdtime** command affects authoritative responses only. The advertised holding time is the length of time the Cisco IOS software tells other routers to keep information that it is providing in authoritative NHRP responses. The cached IPv6-to-NBMA address mapping entries are discarded after the holding time expires.

The NHRP cache can contain static and dynamic entries. The static entries never expire. Dynamic entries expire regardless of whether they are authoritative or nonauthoritative.

Examples

In the following example, NHRP NBMA addresses are advertised as valid in positive authoritative NHRP responses for 1 hour:

```
ipv6 nhrp holdtime 3600
```

ipv6 nhrp interest

To control which IPv6 packets can trigger sending a Next Hop Resolution Protocol (NHRP) request packet, use the **ipv6 nhrp interest** command in interface configuration mode. To restore the default value, use the **no** form of this command.

```
ipv6 nhrp interest ipv6-access-list
no ipv6 nhrp interest [ipv6-access-list]
```

Syntax Description

<i>ipv6-access-list</i>	IPv6 access list number in the range from 1 to 199.
-------------------------	---

Command Default

All non-NHRP packets can trigger NHRP requests.

Command Modes

Interface configuration (config-if)

Command History

Release	Modification
12.4(20)T	This command was introduced.

Usage Guidelines

Use the **ipv6 nhrp interest** command with the **ipv6 access-list** command to control which IPv6 packets trigger NHRP requests.

Examples

In the following example, the IPv6 packets specified by the IPv6 access list named list2 will trigger NHRP requests:

```
Router(config)# ipv6 access-list list2
permit any any
Router(config-if)# ipv6 nhrp interest list2
```

Related Commands

Command	Description
ipv6 access-list	Defines an IPv6 access list.

ipv6 nhrp map

To statically configure the IPv6-to-nonbroadcast multiaccess (NBMA) address mapping of IPv6 destinations connected to an NBMA network, use the **ipv6 nhrp map** command in interface configuration mode. To remove the static entry from Next Hop Resolution Protocol (NHRP) cache, use the **no** form of this command.

ipv6 nhrp map *ipv6-address nbma-address* [**preference** *pref*]

no ipv6 nhrp map *ipv6-address nbma-address* [**preference** *pref*]

Syntax Description

<i>ipv6-address</i>	IPv6 address of the destination reachable through the NBMA network. This address is mapped to the NBMA address.
<i>nbma-address</i>	An IPv4 or IPv6 NBMA address that is directly reachable through the NBMA network. The address format varies depending on the medium you are using. For example, ATM has a network service access point (NSAP) address, Ethernet has a MAC address, and Switched Multimegabit Data Service (SMDS) has an E.164 address.
preference <i>pref</i>	(Optional) Assigns a preference for the IP-to-NBMA address mapping. The preference must be in the range 1 to 255.

Command Default

No static IPv6-to-NBMA cache entries exist.

Command Modes

Interface configuration (config-if)

Command History

Release	Modification
12.4(20)T	This command was introduced.
15.2(1)T	This command was modified. The <i>nbma-address</i> argument was enhanced to support IPv4 and IPv6 addresses.
Cisco IOS XE Release 16.8.1	This command was modified. Option to assign a preference for IP-to-NBMA address mapping was added.

Usage Guidelines

The **ipv6 nhrp map** command accepts IPv6 prefixes in the form of **prefix/ prefix-length**, as shown in the following example:

```
ipv6 nhrp map abcd::abcd/128 172.16.1.1
```

Because the NBMA supports IPv4 addresses, only IPv4 destinations are accepted in the **ipv6 nhrp map** command. IPv6 prefixes can be mapped to IPv4 addresses.

You will probably need to configure at least one static mapping in order to reach the next hop server. Repeat this command to statically configure multiple IPv6-to-NBMA address mappings.

Examples

In the following example, this station in a multipoint tunnel network is statically configured to be served by two next hop servers 2001:0DB8:3333:4::5 and 2001:0DB8:4444:5::6. The NBMA address for 2001:0DB8:3333:4::5 is statically configured to be 2001:0DB8:5555:5::6 and the NBMA address for 2001:0DB8:4444:5::6 is 2001:0DB8:8888:7::6.

```
interface tunnel 0
  ipv6 nhrp nhs 2001:0DB8:3333:4::5
  ipv6 nhrp nhs 2001:0DB8:4444:5::6
  ipv6 nhrp map 2001:0DB8:3333:4::5 10.1.1.1 preference 3
  ipv6 nhrp map 2001:0DB8:4444:5::6 10.2.2.2 preference 9
```

ipv6 nhrp map multicast

To map destination IPv6 addresses to IPv4 nonbroadcast multiaccess (NBMA) addresses, use the **ipv6 nhrp map multicast** command in interface configuration mode. To remove the destination IPv6 addresses, use the **no** form of this command.

```
ipv6 nhrp map multicast {ipv4-nbma-addressipv6-nbma-address}
no ipv6 nhrp map multicast {ipv4-nbma-addressipv6-nbma-address}
```

Syntax Description	
<i>ipv4-nbma-address</i>	IPv4 NBMA address (IPv6 over IPv4 transport) that is directly reachable through the NBMA network.
<i>ipv6-nbma-address</i>	IPv6 NBMA address that is directly reachable through the NBMA network.

Command Default No NBMA addresses are configured as destinations for broadcast or multicast packets.

Command Modes Interface configuration (config-if)

Command History	Release	Modification
	12.4(20)T	This command was introduced.
	15.2(1)T	This command was modified. Support was extended to IPv6 NBMA addresses.

Usage Guidelines The **ipv6 nhrp map multicast** command works only with tunnel interfaces.

The command is useful for supporting broadcasts over a tunnel network when the underlying network does not support IPv4 multicasts. If the underlying network supports IPv4 multicasts, you should use the **tunnel destination** command to configure a multicast destination for the transmission of tunnel broadcasts or multicasts.

When multiple NBMA addresses are configured, the system replicates the broadcast packet for each address.

Examples In the following example, an IPv6 address is mapped to the IPv4 address 10.11.11.99:

```
ipv6 nhrp map 2001:0DB8::99/128 10.11.11.99
ipv6 nhrp map multicast 10.11.11.99
```

Related Commands	Command	Description
	tunnel destination	Specifies the destination for a tunnel interface.

ipv6 nhrp map multicast dynamic

To allow Next Hop Resolution Protocol (NHRP) to automatically add routers to the multicast NHRP mappings, use the **ipv6 nhrp map multicast dynamic** command in interface configuration mode. To disable this functionality, use the **no** form of this command

ipv6 nhrp map multicast dynamic
no ipv6 nhrp map multicast dynamic

Syntax Description

This command has no arguments or keywords.

Command Default

Routers are not automatically added to the multicast NHRP mapping.

Command Modes

Interface configuration (config-if)

Command History

Release	Modification
12.4(20)T	This command was introduced.

Usage Guidelines

Use the **ipv6 nhrp map multicast dynamic** command when spoke routers need to initiate multipoint generic routing encapsulation (GRE) and IP security (IPsec) tunnels and register their unicast NHRP mappings. This command is needed to enable dynamic routing protocols to work over the Multipoint GRE and IPsec tunnels because IGP routing protocols use multicast packets. This command prevents the hub router from needing a separate configuration line for a multicast mapping for each spoke router.

Examples

The following example shows how to enable the **ipv6 nhrp map multicast dynamic** command on the hub router:

```
crypto ipsec profile cisco-ipsec
 set transform-set cisco-ts
!
interface Tunnel0
 bandwidth 100000
 ip address 10.1.1.99 255.255.255.0
 no ip redirects
 ip nhrp map multicast dynamic
 delay 50000
 ipv6 address 2001:0DB8::99/100
 ipv6 address FE80::0B:0B:0B:8F link-local
 ipv6 enable
 ipv6 eigrp 1
 no ipv6 split-horizon eigrp 1
 no ipv6 next-hop-self eigrp 1
 ipv6 nhrp map multicast dynamic
 ipv6 nhrp network-id 99
 tunnel source Ethernet0/0
 tunnel mode gre multipoint
 tunnel protection ipsec profile cisco-ipsec
```

Related Commands

Command	Description
ipv6 nhrp network-id	Enables NHRP on an interface.

ipv6 nhrp max-send

To change the maximum frequency at which Next Hop Resolution Protocol (NHRP) packets can be sent, use the **ipv6 nhrp max-send** command in interface configuration mode. To restore this frequency to the default value, use the **no** form of this command.

```
ipv6 nhrp max-send pkt-count every seconds
no ipv6 nhrp max-send
```

Syntax Description

<i>pkt-count</i>	Number of packets that can be sent in the range from 1 to 65535. Default is 100 packets.
every <i>seconds</i>	Specifies the time (in seconds) in the range from 10 to 65535. Default is 10 seconds.

Command Default

Maximum frequency default settings are used.

Command Modes

Interface configuration (config-if)

Command History

Release	Modification
12.4(20)T	This command was introduced.

Usage Guidelines

The software maintains a per-interface quota of NHRP packets that can be sent. NHRP traffic, whether locally generated or forwarded, cannot be sent at a rate that exceeds this quota. The quota is replenished at the rate specified by the *seconds* argument:

- The user needs to consider the number of spoke routers being handled by this hub and how often they send NHRP registration requests. To support this load you would need:

Number of spokes / registration timeout * *max-send-interval*

- Example:

500 spokes with 100-second registration timeout

Max send value = 500/100*10 = 50

- The maximum number of spoke-spoke tunnels that are expected to be up at any one time across the whole DMVPN network.

spoke-spoke tunnels/NHRP holdtime * *max-send-interval*

This formula covers spoke-spoke tunnel creation and the refreshing of spoke-spoke tunnels that are used for longer periods of time:

- Example

2000 spoke-spoke tunnels with 250-second hold timeout

Max send value = 2000/250*10 = 80

Then add these together and multiply this by 1.5 to 2.0 to give a buffer:

- Example

Max send = (50 + 80) * 2 = 260

- The max-send interval can be used to keep the long-term average number of NHRP messages allowed to be sent constant, but to allow greater peaks:

- Example

400 messages in 10 seconds

In this case, it could peak at approximately 200 messages in the first second of the 10-second interval, but still keep to a 40-messages-per-second average over the 10-second interval:

4000 messages in 100 seconds

In this case, it could peak at approximately 2000 messages in the first second of the 100-second interval, but it would still be held to 40-messages-per-second average over the 100-second interval. In the second case, it could handle a higher peak rate, but risk a longer period of time when no messages can be sent if it used up its quota for the interval.

By default, the maximum rate at which the software sends NHRP packets is five packets per 10 seconds. The software maintains a per-interface quota of NHRP packets (whether generated locally or forwarded) that can be sent.

Examples

In the following example, only one NHRP packet can be sent from serial interface 0 each minute:

```
interface serial 0
  ipv6 nhrp max-send 1 every 60
```

Related Commands

Command	Description
ipv6 nhrp interest	Controls which IP packets can trigger sending an NHRP request.
ipv6 nhrp use	Configures the software so that NHRP is deferred until the system has attempted to send data traffic to a particular destination multiple times.

ipv6 nhrp multicast

To configure multicast batch size and batch interval, use the **ipv6 nhrp multicast** command in interface configuration mode. To remove the multicast batch size and batch interval configuration, use the **no** form of this command.

```
ipv6 nhrp multicast [batch-size num][batch-interval milliseconds]
```

```
no ipv6 nhrp multicast [batch-size num][batch-interval milliseconds]
```

Syntax Description

batch-size *num* Specifies the batch size of multicast replication.

batch-interval *milliseconds* Specifies the interval for batch multicast replication.

Command Default

The default multicast batch-size is 250. The default multicast batch-interval is 10 milliseconds.

Command Modes

Interface configuration

Command History

Release	Modification
IOS XE Release 16.8.1	Command introduced.

Example

The following example shows the multicast batch-size configured to 12 and the batch-interval configured to 10 milliseconds for a tunnel interface.

```
interface tunnel0
  ipv6 nhrp multicast batch-size 12 batch-interval 10
```

ipv6 nhrp network-id

To enable the Next Hop Resolution Protocol (NHRP) on an interface, use the **ipv6 nhrp network-id** command in interface configuration mode. To disable NHRP on the interface, use the **no** form of this command..

ipv6 nhrp network-id *network-id*
no ipv6 nhrp network-id *network-id*

Syntax Description

<i>network-id</i>	Globally unique, 32-bit network identifier from a nonbroadcast multiaccess (NBMA) network. The range is from 1 to 4294967295.
-------------------	---

Command Default

NHRP is disabled on the interface.

Command Modes

Interface configuration (config-if)

Command History

Release	Modification
12.4(20)T	This command was introduced.

Usage Guidelines

In general, all NHRP stations within one logical NBMA network must be configured with the same network identifier.

Examples

The following example shows how to enable NHRP on the interface:

```
Router(config-if)# ipv6 nhrp network-id 99
```

Related Commands

Command	Description
ipv6 nhrp map multicast dynamic	Allows NHRP to automatically add routers to the multicast NHRP mappings.

ipv6 nhrp nhs

To specify the IPv6 prefix of one or more Next Hop Resolution Protocol (NHRP) servers, use the **ipv6 nhrp nhs** command in interface configuration mode. To remove the prefix address, use the **no** form of this command.

```

ipv6 nhrp nhs { ipv6-nhs-address [ scope { global } ] [ nbma { nbma-address fqdn-string } ]
[ multicast ] [ priority value ] [ cluster value ] | cluster value max-connections value | dynamic
[ scope { global } ] nbma { nbma-address fqdn-string } [ multicast ] [ priority value ] [ cluster
value ] | fallback seconds }
no ipv6 nhrp nhs { ipv6-nhs-address [ scope { global } ] [ nbma { nbma-address fqdn-string } ]
[ multicast ] [ priority value ] [ cluster value ] | cluster value max-connections value | dynamic [ scope
{ global } ] nbma { nbma-address fqdn-string } [ multicast ] [ priority value ] [ cluster value ] | fallback
seconds }

```

Syntax Description

<i>ipv6-nhs-address</i>	IPv6 prefix of the next hop server being specified.
nbma	(Optional) Specifies nonbroadcast multiple access (NBMA) values.
<i>nbma-address</i>	(Optional) IPv4 or IPv6 NBMA address.
<i>fqdn-string</i>	(Optional) Next hop address (NHS) fully qualified domain name (FQDN) string.
multicast	(Optional) Specifies to use NBMA mapping for broadcasts and multicasts.
priority <i>value</i>	(Optional) Assigns a priority to hubs to control the order in which spokes select hubs to establish tunnels. The range is from 0 to 255, where 0 is the highest and 255 is the lowest priority.
cluster <i>value</i>	(Optional) Specifies NHS groups. The range is from 0 to 10, where 0 is the highest and 10 is the lowest value. The default value is 0.
max-connections <i>value</i>	Specifies the number of NHS elements from each NHS group that need to be active. The range is from 0 to 255.
dynamic	Configures the spoke to learn the NHS protocol address dynamically.
fallback <i>seconds</i>	Specifies the duration, in seconds, for which the spoke must wait before falling back to an NHS of higher priority upon recovery.
scope <i>global</i>	Defines the scope for the NHS address. The default behaviour is to register with both global unicast and link local address. If the scope is set to <i>global</i> , the registration is limited to global unicast address only.

Command Default

No next hop servers are explicitly configured, so normal network layer routing decisions are used to forward NHRP traffic.

Command Modes

Interface configuration (config-if)

Command History

Release	Modification
12.4(20)T	This command was introduced.
15.1(2)T	This command was modified. The <i>net-address</i> argument was removed and the nbma , <i>nbma-address</i> , <i>fqdn-string</i> , multicast , priority value , cluster value , max-connections value , dynamic , and fallback seconds keywords and arguments were added.
15.2(1)T	This command was modified. The <i>nbma-address</i> argument was modified to support IPv4 addresses.

Usage Guidelines

Use the **ipv6 nhrp nhs** command to specify the IPv6 prefix of a next hop server and the networks it serves. Normally, NHRP consults the network layer forwarding table to determine how to forward NHRP packets. When next hop servers are configured, these next hop IPv6 prefixes override the forwarding path that would otherwise be used for NHRP traffic.

For any next hop server that is configured, you can specify multiple networks by repeating this command with the same *nhs-address* argument, but with different IPv6 network addresses.

Examples

The following example shows how to register a hub to a spoke using NBMA and FQDN:

```
Router# configure terminal
Router(config)# interface tunnel 1
Router(config-if)# ipv6 nhrp nhs 2001:0DB8:3333:4::5 nbma examplehub.example1.com
```

The following example shows how to configure the desired **max-connections** value:

```
Router# configure terminal
Router(config)# interface tunnel 1
Router(config-if)# ipv6 nhrp nhs cluster 5 max-connections 100
```

The following example shows how to configure the NHS fallback time:

```
Router# configure terminal
Router(config)# interface tunnel 1
Router(config-if)# ipv6 nhrp nhs fallback 25
```

The following example shows how to configure NHS priority and group values:

```
Router# configure terminal
Router(config)# interface tunnel 1
Router(config-if)# ipv6 nhrp nhs 2001:0DB8:3333:4::5 priority 1 cluster 2
```

Related Commands

Command	Description
ipv6 nhrp map	Statically configures the IP-to-NBMA address mapping of IPv6 destinations connected to an NBMA network.
show ipv6 nhrp	Displays NHRP mapping information.

ipv6 nhrp record

To reenable the use of forward record and reverse record options in Next Hop Resolution Protocol (NHRP) request and reply packets, use the **ipv6 nhrp record** command in interface configuration mode. To suppress the use of such options, use the **no** form of this command.

ipv6 nhrp record
no ipv6 nhrp record

Syntax Description

This command has no arguments or keywords.

Command Default

Forward record and reverse record options are used in NHRP request and reply packets.

Command Modes

Interface configuration (config-if)

Command History

Release	Modification
12.4(20)T	This command was introduced.

Usage Guidelines

Forward record and reverse record options provide loop detection and are enabled by default. Using the **no** form of this command disables this method of loop detection. For another method of loop detection, see the **ipv6 nhrp responder** command.

Examples

The following example suppresses forward record and reverse record options:

```
no ipv6 nhrp record
```

Related Commands

Command	Description
ipv6 nhrp responder	Designates the primary IP address of which interface the next hop server will use in NHRP reply packets when the NHRP requester uses the Responder Address option.

ipv6 nhrp redirect

To enable Next Hop Resolution Protocol (NHRP) redirect, use the **ipv6 nhrp redirect** command in interface configuration mode. To remove the NHRP redirect, use the **no** form of this command.

ipv6 nhrp redirect [*timeout seconds*]
no ipv6 nhrp redirect [*timeout seconds*]

Syntax Description

timeout <i>seconds</i>	(Optional) Indicates the interval, in seconds, that the NHRP redirects are sent for the same nonbroadcast multiaccess (NBMA) source and destination combination. The range is from 2 to 30 seconds.
-------------------------------	---

Command Default

NHRP redirect is disabled.

Command Modes

Interface configuration (config-if)

Command History

Release	Modification
12.4(20)T	This command was introduced.

Usage Guidelines

The NHRP redirect message is an indication that the current path to the destination is not optimal. The receiver of the message should find a better path to the destination.

This command generates an NHRP redirect traffic indication message if the incoming and outgoing interface is part of the same dynamic multipoint VPN (DMVPN) network. The NHRP shortcut switching feature depends on receiving the NHRP redirect message. NHRP shortcut switching does not trigger an NHRP resolution request on its own. It triggers an NHRP resolution request only after receiving an NHRP redirect message.

Most of the traffic would follow a spoke-hub-spoke path. NHRP redirect is generally required to be configured on all the DMVPN nodes in the event the traffic follows a spoke-spoke-hub-spoke path.

Do not configure this command if the DMVPN network is configured for full-mesh. In a full-mesh configuration, the spokes are populated with a full routing table, with the next hop being the other spokes.

Examples

The following example shows how to enable NHRP redirects on the interface:

```
ipv6 nhrp redirect
```

Related Commands

Command	Description
ipv6 nhrp shortcut	Enables NHRP shortcut switching.

ipv6 nhrp registration

To enable the client to set the unique flag in the Next Hop Resolution Protocol (NHRP) request and reply packets, use the **ipv6 nhrp registration** command in interface configuration mode. To reenable this functionality, use the **no** form of this command.

```
ipv6 nhrp registration [{timeout seconds | no-unique | req-def-map}]
no ipv6 nhrp registration [{timeout seconds | no-unique | req-def-map}]
```

Syntax Description	timeout seconds	(Optional) Specifies the time between periodic registration messages:
		<ul style="list-style-type: none"> <i>seconds</i> --Number of seconds. The range is from 1 through the value of the NHRP hold timer. If the timeout keyword is not specified, NHRP registration messages are sent every number of seconds equal to one-third the value of the NHRP hold timer.
	no-unique	(Optional) Enables the client to not set the unique flag in the NHRP request and reply packets.
	req-def-map	(Optional) Enables the client to request default maps in registration.

Command Default The default settings are used.

Command Modes Interface configuration (config-if)

Command History	Release	Modification
	12.4(20)T	This command was introduced.
	Cisco IOS XE Release 16.10.1	The req-def-map keyword was added.

Usage Guidelines If the unique flag is set in the NHRP registration request packet, a next hop server (NHS) must reject any registration attempts for the same private address using a different nonbroadcast multiaccess (NBMA) address. If a client receives a new IP address—for example, via DHCP—and tries to register before the cache entry on the NHS times out, the NHS must reject it.

By configuring the **ip nhrp registration** command and **no-unique** keyword, the unique flag is not set, and the NHS can override the old registration information.

This command and keyword combination is useful in an environment where client IPv6 addresses can change frequently such as a dial environment.

By configuring the **ip nhrp registration** command and the **req-def-map** keyword, the NHRP client requests for default map from the server via registration message.

Examples

The following example configures the client not to set the unique flag in the NHRP registration packet:

```
interface FastEthernet 0/0
  ipv6 nhrp registration no-unique
```

The following example shows that the registration timeout is set to 120 seconds, and the delay is set to 5 seconds:

```
interface FastEthernet 0/0
  ipv6 nhrp registration 120 5
```

The following example configures the client to enable requesting default maps in registration packet:

```
interface FastEthernet 0/0
  ip nhrp registration req-def-map
```

Related Commands

Command	Description
ipv6 nhrp holdtime	Changes the number of seconds that NHRP NBMA addresses are advertised as valid in authoritative NHRP responses

ipv6 nhrp resolution refresh base

The default NHRP resolution requests follow the routed path to the destination spoke (exit point out the DMVPN cloud). For the first resolution request, this routed path is via the hub(s) all the way to the destination spoke. Owing to the on-demand route created as a result of the resolution process, for a resolution request sent for refreshing on-demand spoke-spoke routes and tunnels the routed path is the direct path between the spokes. This revalidates the direct spoke-spoke path like a keepalive and also reduces the load on the hub.

You can use this command to make the requests follow the base routed path via the hub(s), and do not take the on-demand path/route that was learnt for the prefix/next hop.

ipv6 nhrp resolution refresh base *number*
no ipv6 nhrp resolution refresh base

Syntax Description

refresh	Displays resolution refresh-related configuration options.
base	Configures the base routed path for routing resolution requests for refresh. This excludes the on-demand/shortcut routed path for routing resolution requests for refreshes.
<i>number</i>	(Optional) Specifies which refresh goes through the base path.

Command Default

The default settings are used.

Command Modes

Interface configuration (config-if)

Command History

Release	Modification
Cisco IOS XE 17.4 Release	The refresh and base keywords were introduced to the ipv6 nhrp resolution refresh base command.

Usage Guidelines

Use **ipv6 nhrp resolution refresh base *number*** on the tunnel interface on the spoke when it is intended that the resolution requests follow the base routed path via the hub(s) and don't take the on-demand path/route that was learnt for the prefix/next hop. When configured, it should be configured symmetrically at both ends, else, it leads to asymmetric behavior.

Examples

The following example displays what the *number* denotes:

- When the value is n=1, every refresh goes through the base path.
- When the value is n=2, every second refresh goes through the base path, while other values still follow the default behaviour.

```
ipv6 nhrp resolution refresh base 1
```

Related Commands

Command	Description
ipv6 nhrp send-routed	This command is enabled by default and is used to forward the resolution requests via the routed path.

Command	Description
no ipv6 nhrp send-routed	This command causes NHRP control packets to be sent over the routed path to the destination/next hop. This is enabled by default.

ipv6 nhrp responder

To designate the primary IPv6 address the next hop server that an interface will use in Next Hop Resolution Protocol (NHRP) reply packets when the NHRP requestor uses the Responder Address option, use the **ipv6 nhrp responder** command in interface configuration mode. To remove the designation, use the **no** form of this command.

```
ipv6 nhrp responder interface-type interface-number
no ipv6 nhrp responder [interface-type] [interface-number]
```

Syntax Description		
<i>interface-type</i>	Interface type whose primary IPv6 address is used when a next hop server complies with a Responder Address option (for example, serial or tunnel).	
<i>interface-number</i>	Interface number whose primary IPv6 address is used when a next hop server complies with a Responder Address option.	

Command Default The next hop server uses the IPv6 address of the interface where the NHRP request was received.

Command Modes Interface configuration (config-if)

Command History	Release	Modification
	12.4(20)T	This command was introduced.

Usage Guidelines If an NHRP requestor wants to know which next hop server generates an NHRP reply packet, it can request that information through the Responder Address option. The next hop server that generates the NHRP reply packet then complies by inserting its own IPv6 address in the Responder Address option of the NHRP reply. The next hop server uses the primary IPv6 address of the specified interface.

If an NHRP reply packet being forwarded by a next hop server contains the IPv6 address of that next hop server, the next hop server generates an Error Indication of type "NHRP Loop Detected" and discards the reply packet.

Examples

In the following example, any NHRP requests for the Responder Address will cause this router acting as a next hop server to supply the primary IPv6 address of serial interface 0 in the NHRP reply packet:

```
ipv6 nhrp responder serial 0
```

ipv6 nhrp send-routed

To forward the resolution requests via the routed path, use **ipv6 nhrp send-routed** command in interface configuration mode. To disable this feature, use the **no** form of this command.

ipv6 nhrp send-routed
no ipv6 nhrp send-routed

Command Default Enabled

Command Modes Interface configuration

Command History	Release	Modification
	16.9	This command was introduced.

Usage Guidelines With **ipv6 nhrp send-routed** configured, the control packets take the routed path instead of nhs priority path. Without send-routed, the nhs priority configuration takes effect. The path taken by the control packets can be verified using **show ipv6 nhrp traffic** command.

For all non-registration packets, the first NHRP resolution request takes the route installed by the IGP initially and then is forwarded along the routed path, for subsequent requests. The routed path can be the NHRP route or NHOs.

If the routed path fails for some reasons, tunnel falls back to the NHS path.

Examples

The following is an example of tunnel interface when the tunnel interface is disabled:

```
interface Tunnel0
  ipv6 address 2001::2/64
  ipv6 enable
  ipv6 nhrp authentication test
  ipv6 nhrp map 3001::2/64 10.1.1.2
  ipv6 nhrp network-id 100
  no ipv6 nhrp send-routed
  tunnel source Ethernet0/0
  tunnel mode gre multipoint
```

ipv6 nhrp server-only

To configure the interface to operate in Next Hop Resolution Protocol (NHRP) server-only mode, use the **ipv6 nhrp server-only** command in interface configuration mode. To disable this feature, use the **no** form of this command.

```
ipv6 nhrp server-only [non-caching]
no ipv6 nhrp server-only
```

Syntax Description	non-caching (Optional) Specifies that the router will not cache NHRP information received on this interface.
---------------------------	---

Command Default The interface does not operate in NHRP server-only mode.

Command Modes Interface configuration (config-if)

Command History	Release	Modification
	12.4(20)T	This command was introduced.

Usage Guidelines When the interface is operating in NHRP server-only mode, the interface does not originate NHRP requests or set up an NHRP shortcut Switched Virtual Circuit (SVC).

Examples The following example shows that the interface is configured to operate in server-only mode:

```
ipv6 nhrp server-only
```

ipv6 nhrp shortcut

To enable Next Hop Resolution Protocol (NHRP) shortcut switching, use the **ipv6 nhrp shortcut** command in interface configuration mode. To remove shortcut switching from NHRP, use the **no** form of this command.

ipv6 nhrp shortcut
no ipv6 nhrp shortcut

Syntax Description This command has no arguments or keywords.

Command Default NHRP shortcut switching is disabled.

Command Modes Interface configuration (config-if)#

Release	Modification
12.4(20)T	This command was introduced.

Usage Guidelines Do not configure this command if the dynamic multipoint VPN (DMVPN) network is configured for full-mesh. In a full-mesh configuration, the spokes are populated with a full routing table, with the next hop being the other spokes.

Examples The following example shows how to configure an NHRP shortcut on an interface:

```
Router(config-if)# ipv6 nhrp shortcut
```

Command	Description
ipv6 nhrp redirect	Enables NHRP redirect.

ipv6 nhrp trigger-svc

To configure when the Next Hop Resolution Protocol (NHRP) will set up and tear down a switched virtual circuit (SVC) based on aggregate traffic rates, use the **ipv6 nhrp trigger-svc** command in interface configuration mode. To restore the default thresholds, use the **no** form of this command.

ipv6 nhrp trigger-svc *trigger-threshold* *teardown-threshold*
no ipv6 nhrp trigger-svc

Syntax Description		
<i>trigger-threshold</i>		Average traffic rate calculated during the load interval, at or above which NHRP will set up an SVC for a destination. The default value is 1 kb/s.
<i>teardown-threshold</i>		Average traffic rate calculated during the load interval, at or below which NHRP will tear down the SVC to the destination. The default value is 0 kb/s.

Command Default The SVC default settings are used.

Command Modes Interface configuration (config-if)

Command History	Release	Modification
	12.4(20)T	This command was introduced.

Usage Guidelines The two thresholds are measured during a sampling interval of 30 seconds, by default.

Examples In the following example, the triggering and teardown thresholds are set to 100 kb/s and 5 kb/s, respectively:

```
ipv6 nhrp trigger-svc 100 5
```

ipv6 nhrp use

To configure the software so that the Next Hop Resolution Protocol (NHRP) is deferred until the system has attempted to send data traffic to a particular destination multiple times, use the **ipv6 nhrp use** command in interface configuration mode. To restore the default value, use the **no** form of this command.

```
ipv6 nhrp use usage-count
no ipv6 nhrp use usage-count
```

Syntax Description

<i>usage-count</i>	Packet count in the range from 1 to 65535. Default is 1.
--------------------	--

Command Default

The first time a data packet is sent to a destination for which the system determines NHRP can be used, an NHRP request is sent.

Command Modes

Interface configuration (config-if)

Command History

Release	Modification
12.4(20)T	This command was introduced.

Usage Guidelines

When the software attempts to send a data packet to a destination for which it has determined that NHRP address resolution can be used, an NHRP request for that destination normally is sent immediately. Configuring the *usage-count* argument causes the system to wait until the configured number of data packets have been sent to a particular destination before it attempts NHRP. The *usage-count* argument for a particular destination is measured over 1-minute intervals (the NHRP cache expiration interval).

The usage count applies *per destination*. So if the *usage-count* argument is configured to be 3, and four data packets are sent toward 2001:0DB8:3333:4::5 and one packet toward 2001:0DB8:5555:5::6, then an NHRP request is generated for 2001:0DB8:3333:4::5 only.

If the system continues to need to forward data packets to a particular destination, but no NHRP response has been received, retransmission of NHRP requests is performed. This retransmission occurs only if data traffic continues to be sent to a destination.

The **ipv6 nhrp interest** command controls *which* packets cause NHRP address resolution to take place; the **ipv6 nhrp use** command controls *how readily* the system attempts such address resolution.

Examples

In the following example, if in the first minute five packets are sent to the first destination and five packets are sent to a second destination, then a single NHRP request is generated for the second destination.

If in the second minute the same traffic is generated and no NHRP responses have been received, then the system resends its request for the second destination.

```
ipv6 nhrp use 5
```

Related Commands

Command	Description
ipv6 nhrp interest	Controls which IPv6 packets can trigger sending an NHRP request.
ipv6 nhrp max-send	Changes the maximum frequency at which NHRP packets can be sent.

ipv6 ospf area

To enable Open Shortest Path First version 3 (OSPFv3) on an interface, use the **ip v6 ospf area** command in interface configuration mode. To disable OSPFv3 routing for interfaces defined, use the **no** form of this command.

```
ipv6 ospf process-id area area-id [instance instance-id]  
no ipv6 ospf process-id area area-id [instance instance-id]
```

Syntax Description

<i>process-id</i>	Internal identification. It is locally assigned and can be any positive integer. The number used here is the number assigned administratively when enabling the OSPFv3 routing process.
<i>area-id</i>	Area that is to be associated with the OSPFv3 interface.
instance <i>instance-id</i>	(Optional) Instance identifier.

Command Default

OSPFv3 is not enabled.

Command Modes

Interface configuration

Command History

Release	Modification
12.0(24)S	This command was introduced.
12.2(15)T	This command was integrated into Cisco IOS Release 12.2(15)T.
12.2(18)S	This command was integrated into Cisco IOS Release 12.2(18)S.
12.2(28)SB	This command was integrated into Cisco IOS Release 12.2(28)SB.
12.2(25)SG	This command was integrated into Cisco IOS Release 12.2(25)SG.
12.2(33)SRA	This command was integrated into Cisco IOS Release 12.2(33)SRA.
12.2(33)SXH	This command was integrated into Cisco IOS Release 12.2(33)SXH.
Cisco IOS XE Release 2.1	This command was integrated into Cisco IOS XE Release 2.1.
15.1(3)S	Use of the ospfv3 areacmd can affect the ipv6 ospf area command.
Cisco IOS XE Release 3.4S	Use of the ospfv3 areacmd can affect the ipv6 ospf area command.
15.2(1)T	Use of the ospfv3 areacmd can affect the ipv6 ospf area command.
15.1(1)SY	This command was integrated into Cisco IOS Release 15.1(1)SY.
15.2(2)SNG	This command was implemented on the Cisco ASR 901 Series Aggregation Services devices.

Usage Guidelines

If the **ospfv3 areacmd** command is configured with the *process-id* argument, it overwrites the **ipv6 ospf area** configuration if OSPFv3 was attached to the interface using the **ipv6 ospf area** command.

Before you enable OSPFv3 on an interface using the **ipv6 ospf area** command, you must enable IPv6 on the interface, and you must enable IPv6 routing.

An OSPFv3 instance (also known as an OSPFv3 process) can be considered a logical device running OSPFv3 in a physical device. Use the instance ID to control selection of other devices as your neighbors. You become neighbors only with devices that have the same instance ID.

In IPv6, users can configure many addresses on an interface. In OSPFv3, all addresses on an interface are included by default. Users cannot select some addresses to be imported into OSPFv3; either all addresses on an interface are imported, or no addresses on an interface are imported.

There is no limit to the number of **ipv6 ospf area** commands you can use on the device. You must have at least two interfaces configured for OSPFv3 to run.

Examples

The following example enables OSPFv3 on an interface:

```
ipv6 unicast-routing
interface ethernet0/1
  ipv6 enable
  ipv6 ospf 1 area 0
ipv6 unicast-routing
interface ethernet0/2
  ipv6 enable
  ipv6 ospf 120 area 1.4.20.9 instance 2
```

Related Commands

Command	Description
ipv6 router ospf	Enables OSPFv3 router configuration mode.
ospfv3 area	Enables an OSPFv3 instance with the IPv4 or IPv6 address family.
router ospfv3	Enables OSPFv3 router configuration mode for the IPv4 or IPv6 address family.

ipv6 ospf authentication

To specify the authentication type for an Open Shortest Path First version 3 (OSPFv3) interface, use the **ipv6 ospf authentication** command in interface configuration mode. To remove the authentication type for an interface, use the **no** form of this command.

```
ipv6 ospf authentication {null | ipsec spi spi authentication-algorithm [key-encryption-type] [key]}
no ipv6 ospf authentication ipsec spi spi
```

Syntax Description

ipsec	Specifies IP Security (IPsec).
spi spi	Specifies the security policy index (SPI) value. The <i>spi</i> value must be a number from 256 to 4294967295, which is entered as a decimal.
<i>authentication-algorithm</i>	Encryption authentication algorithm to be used. The values can be one of the following: <ul style="list-style-type: none"> • md5 —Enables message digest 5 (MD5) authentication. • sha1 —Enables Secure Hash Algorithm 1 (SHA-1) authentication.
<i>key-encryption-type</i>	(Optional) One of two values can be entered: <ul style="list-style-type: none"> • 0 —The key is not encrypted. • 7 —The key is encrypted.
<i>key</i>	Number used in the calculation of the message digest. When MD5 authentication is used, the key must be 32 hexadecimal digits (16 bytes) long. When SHA-1 authentication is used, the key must be 40 hexadecimal digits (20 bytes) long.
null	Overrides area authentication.

Command Default

No authentication.

Command Modes

Interface configuration (config-if)

Command History

Release	Modification
12.3(4)T	This command was introduced.
12.4(4)T	This command was modified. The sha1 keyword was added.
15.1(3)S	This command was modified. Use of the ospfv3 authentication command can affect the ipv6 ospf authentication command.
Cisco IOS XE Release 3.4S	This command was modified. Use of the ospfv3 authentication command can affect the ipv6 ospf authentication command.

Release	Modification
15.2(1)T	This command was modified. Use of the ospfv3 authentication command can affect the ipv6 ospf authentication command.
15.0(2)SE	This command was integrated into Cisco IOS Release 15.0(2)SE.

Usage Guidelines

You need to ensure that the same policy (the SPI and the key) is configured on all of the interfaces on the link. SPI values may automatically be used by other client applications, such as tunnels.

The policy database is common to all client applications on a device. This means that two IPsec clients, such as OSPFv3 and a tunnel, cannot use the same SPI. Additionally, an SPI can be used only in one policy.

The **null** keyword is used to override existing area authentication. If area authentication is not configured, then it is not necessary to configure the interface with the **ipv6 ospf authentication null** command.

Beginning with Cisco IOS Release 12.4(4)T, the **sha1** keyword can be used to choose SHA-1 authentication instead of entering the **md5** keyword to use MD5 authentication. The SHA-1 algorithm is considered to be somewhat more secure than the MD5 algorithm, and it requires a 40-hexadecimal-digit (20-byte) key rather than the 32-hexadecimal-digit (16-byte) key that is required for MD5 authentication.

Examples

The following example shows how to enable MD5 authentication and then override area authentication:

```
Router(config-if)# ipv6 ospf authentication ipsec spi 500 md5 1234567890abcdef1234567890abcdef
Router(config-if)# ipv6 ospf authentication null
```

The following example shows how to enable SHA-1 authentication on the interface:

```
Router(config)# interface Ethernet0/0
Router(config)# ipv6 enable
Router(config-if)# ipv6 ospf authentication ipsec spi 500 sha1
1234567890123456789012345678901234567890
```

Related Commands

Command	Description
ipv6 router ospf	Enables OSPF router configuration mode.
ospfv3 authentication	Specifies the authentication type for an OSPFv3 instance.
router ospfv3	Enables OSPFv3 router configuration mode for the IPv4 or IPv6 address family.

ipv6 ospf bfd

To enable Bidirectional Forwarding Detection (BFD) on a specific interface configured for Open Shortest Path First version 3 (OSPFv3), use the **ipv6 ospf bfd** command in interface configuration mode. To remove the **ospf bfd** command, use the **no** form of this command.

```
ipv6 ospf bfd [disable]
no ipv6 ospf bfd
```

Syntax Description

disable	(Optional) Disables BFD for OSPFv3 on a specified interface.
----------------	--

Command Default

When the **disable** keyword is not used, the default behavior is to enable BFD support for OSPFv3 on the interface.

Command Modes

Interface configuration

Command History

Release	Modification
Cisco IOS XE Release 2.1	This command was introduced.
12.2(33)SRE	This command was modified. It was integrated into Cisco IOS Release 12.2(33)SRE.
15.1(3)S	Use of the ospfv3 bfd command can affect the ipv6 ospf bfd command.
Cisco IOS XE Release 3.4S	Use of the ospfv3 bfd command can affect the ipv6 ospf bfd command.
15.2(1)T	Use of the ospfv3 bfd command can affect the ipv6 ospf bfd command.

Usage Guidelines

Enter the **ipv6 ospf bfd** command to configure an OSPFv3 interface to use BFD for failure detection. If you have used the **bfd all-interfaces** command in router configuration mode to globally configure all OSPFv3 interfaces for an OSPFv3 process to use BFD, you can enter the **ipv6 ospf bfd** command in interface configuration mode with the **disable** keyword to disable BFD for a specific OSPFv3 interface.

Examples

In the following example, the interface associated with OSPFv3, Fast Ethernet interface 3/0, is configured for BFD:

```
Router> enable
Router# configure terminal
Router(config)# interface fastethernet 3/0
Router(config-if)# ipv6 ospf bfd
Router(config-if)# end
```

Related Commands

Command	Description
bfd all-interfaces	Enables BFD for all interfaces for a BFD peer.
ospfv3 bfd	Enables BFD on an interface.

Command	Description
router ospfv3	Enables OSPFv3 router configuration mode for the IPv4 or IPv6 address family.

ipv6 ospf cost

To explicitly specify the cost of sending a packet on an Open Shortest Path First version 3 (OSPFv3) interface, use the **ipv6 ospf cost** command in interface configuration mode. To reset the interface cost to the default value, use the **no** form of this command.

ipv6 ospf cost *interface-cost* | *dynamic* [**weight** {**throughput percent** | **resources percent** | **latency percent** | **L2-factor percent**} | [**hysteresis** | **threshold threshold-value**]]

no ipv6 ospf cost

Syntax Description

<i>interface-cost</i>	Unsigned integer value expressed as the link-state metric. It can be a value in the range from 1 to 65535.
<i>dynamic</i>	Default value on VMI interfaces.
weight	(Optional) Amount of impact a variable has on the dynamic cost.
throughput percent	Throughput weight of the Layer 2 link, expressed as a percentage. The percent value can be in the range from 0 to 100. The default value is 100.
resources percent	Resources weight (such as battery life) of the router at the Layer 2 link, expressed as a percentage. The percent value can be in the range from 0 to 100. The default value is 100.
latency percent	Latency weight of the Layer 2 link, expressed as a percentage. The percent value can be in the range from 0 to 100. The default value is 100.
L2-factor percent	Quality weight of the Layer 2 link expressed as a percentage. The percent value can be in the range from 0 to 100. The default value is 100.
hysteresis	(Optional) Value used to dampen cost changes.
threshold threshold-value	(Optional) Cost change threshold at which hysteresis will be implemented. The threshold range is from 0 to 64K, and the default threshold value is 10K.

Command Default

Default cost is based on the bandwidth.

Default cost on VMI interfaces is dynamic.

Command Modes

Interface configuration (config-if)

Command History

Release	Modification
12.0(24)S	This command was introduced.
12.2(15)T	This command was integrated into Cisco IOS Release 12.2(15)T.
12.2(18)S	This command was integrated into Cisco IOS Release 12.2(18)S.
12.2(28)SB	This command was integrated into Cisco IOS Release 12.2(28)SB.

Release	Modification
12.2(33)SRA	This command was integrated into Cisco IOS Release 12.2(33)SRA.
12.2(33)SXH	This command was integrated into Cisco IOS Release 12.2(33)SXH.
12.4(15)XF	The following keywords and arguments were added to support Virtual Multipoint Interfaces (VMI) and Mobile Adhoc Networking: <ul style="list-style-type: none"> • <i>dynamic</i> argument • weight, resources percent, latency percent, and L2-factor percent keywords and arguments.
12.4(15)T	This command was integrated into Cisco IOS Release 12.4(15)T.
12.2(33)SXH	This command was integrated into Cisco IOS Release 12.2(33)SXH.
15.1(3)S	Use of the ospfv3 cost command can affect the ipv6 ospf cost command.
Cisco IOS XE Release 3.4S	Use of the ospfv3 cost command can affect the ipv6 ospf cost command.
15.2(1)T	Use of the ospfv3 cost command can affect the ipv6 ospf cost command.

Using this formula, the default path costs were calculated as noted in the following list. If these values do not suit your network, you can use your own method of calculating path costs.

- 56-kbps serial link-Default cost is 1785.
- 64-kbps serial link-Default cost is 1562.
- T1 (1.544-Mbps serial link)-Default cost is 64.
- E1 (2.048-Mbps serial link)-Default cost is 48.
- Ethernet-Default cost is 10.
- 16-Mbps Token Ring-Default cost is 6.
- FDDI-Default cost is 1.
- X25-Default cost is 5208.
- Asynchronous-Default cost is 10,000.
- ATM- Default cost is 1. The dynamic cost is calculated using the following formula:

$$L2L3API$$

Where the metric calculations are:

S1 = ipv6 ospf dynamic weight throughput

S2 = ipv6 ospf dynamic weight resources

S3 = ipv6 ospf dynamic weight latency

S4 = ipv6 ospf dynamic weight L2 factor

OC = standard cost of a non-VMI route

Throughput = (current-data-rate)/(maximum-data-rate)

Router-dynamic cost= OC + (S1) + (S2) + (S3) + (S4)

For a dynamic cost to have the same cost as a default cost, all parameters must equal zero.

Each Layer 2 feedback can contribute a cost in the range of 0 to 65535. To tune down this cost range, use the optional **weight** keyword in conjunction with the **throughput**, **resources**, **latency**, or **L2-factor** keyword. Each of these weights has a default value of 100% and can be configured in the range from 0 to 100. When 0 is configured for a specific weight, that weight does not contribute to the OSPFv3 cost.

Because cost components can change rapidly, you may need to dampen the amount of changes in order to reduce network-wide churn. Use the optional **hysteresis** keyword with the **threshold**threshold-value keyword and argument to set a cost change threshold. Any cost change below this threshold is ignored.

Examples

The following example sets the interface cost value to 65:

```
ipv6 ospf cost 65
```

The following example sets the interface cost value for a VMI interface:

```
interface vmi 0
ipv6 ospf cost dynamic hysteresis threshold 30
ipv6 ospf cost dynamic weight throughput 75
ipv6 ospf cost dynamic weight resources 70
ipv6 ospf cost dynamic weight latency 80
ipv6 ospf cost dynamic weight L2-factor 10
```

Related Commands

Command	Description
interface vmi	Creates a virtual multipoint interface that can be configured and applied dynamically.
ipv6 ospf neighbor	Configures OSPFv3 routers interconnecting to nonbroadcast networks.
ospfv3 cost	Explicitly specifies the cost of sending a packet on an interface.
router ospfv3	Enables OSPFv3 router configuration mode for the IPv4 or IPv6 address family.

ipv6 ospf database-filter all out

To filter outgoing link-state advertisements (LSAs) to an Open Shortest Path First version 3 (OSPFv3) interface, use the **ip v6 ospf database-filter all out** command in interface configuration mode. To restore the forwarding of LSAs to the interface, use the **no** form of this command.

ipv6 ospf database-filter all out
no ipv6 ospf database-filter all out

Syntax Description This command has no arguments or keywords.

Command Default All outgoing LSAs are flooded to the interface.

Command Modes Interface configuration

Release	Modification
12.0(24)S	This command was introduced.
12.2(15)T	This command was integrated into Cisco IOS Release 12.2(15)T.
12.2(18)S	This command was integrated into Cisco IOS Release 12.2(18)S.
12.2(28)SB	This command was integrated into Cisco IOS Release 12.2(28)SB.
12.2(33)SRA	This command was integrated into Cisco IOS Release 12.2(33)SRA.
12.2(33)SXH	This command was integrated into Cisco IOS Release 12.2(33)SXH.
15.1(3)S	Use of the ospfv3 database-filter command can affect the ipv6 ospf database-filter all out command.
Cisco IOS XE Release 3.4S	Use of the ospfv3 database-filter command can affect the ipv6 ospf database-filter all out command.
15.2(1)T	Use of the ospfv3 database-filter command can affect the ipv6 ospf database-filter all out command.

Usage Guidelines This command performs the same function that the **neighbor database-filter** command performs on a neighbor basis.

Examples The following example prevents flooding of OSPFv3 LSAs to broadcast, nonbroadcast, or point-to-point networks reachable through Ethernet interface 0:

```
interface ethernet 0
  ipv6 ospf database-filter all out
```

Related Commands

ospfv3 database-filter	Filters outgoing LSAs to an OSPFv3 interface
-------------------------------	--

router ospfv3	Enables OSPFv3 router configuration mode for the IPv4 or IPv6 address family.
---------------	---