



## **Cisco IOS NetFlow Command Reference**

### **Americas Headquarters**

Cisco Systems, Inc.  
170 West Tasman Drive  
San Jose, CA 95134-1706  
USA  
<http://www.cisco.com>  
Tel: 408 526-4000  
800 553-NETS (6387)  
Fax: 408 527-0883





## CONTENTS

---

### CHAPTER 1

<b>backup (NetFlow SCTP) through ip route-cache flow</b>	<b>1</b>
backup (NetFlow SCTP)	3
cache	6
cache-timeout	8
clear fm netflow counters	11
clear ip flow stats	12
clear mls nde flow counters	14
clear mls netflow	15
debug mpls netflow	19
enabled (aggregation cache)	21
export destination	23
export destination sctp (NetFlow aggregation cache)	26
export template	29
export version	32
flow hardware mpls-vpn ip	35
flow-sampler	37
flow-sampler-map	40
ip flow	43
ip flow layer2-switched	46
ip flow-aggregation cache	48
ip flow-cache entries	52
ip flow-cache mpls label-positions	55
ip flow-cache timeout	58
ip flow-capture	60
ip flow-egress input-interface	67
ip flow-export destination	69
ip flow-export destination sctp	73
ip flow-export hardware version	75

- ip flow-export interface-names 77
- ip flow-export source 79
- ip flow-export template 82
- ip flow-export version 85
- ip flow-export version (Supervisor Engine 2) 89
- ip flow-export version (Supervisor Engine 720) 91
- ip flow-top-talkers 93
- ip multicast netflow 96
- ip multicast netflow output-counters 99
- ip multicast netflow rpf-failure 101
- ip route-cache flow 103

---

**CHAPTER 2**

- mask (IPv4) through top 105**
  - mask (IPv4) 107
  - mask 111
  - match (NetFlow) 113
  - mls aging fast 120
  - mls aging long 122
  - mls aging normal 123
  - mls exclude acl-deny 124
  - mls flow 125
  - mls ip nat netflow-frag-l4-zero 127
  - mls nde flow 128
  - mls nde interface 130
  - mls nde sender 132
  - mls netflow 134
  - mls netflow interface 136
  - mls netflow maximum-flows 137
  - mls netflow sampling 139
  - mls netflow usage notify 141
  - mls sampling 143
  - mode (flow sampler configuration) 146
  - mpls netflow egress 149
  - netflow-sampler 151
  - platform netflow rp sampling scale 155

reliability (NetFlow SCTP) 157

show flow-sampler 159

show fm nat netflow data 161

show fm netflow 163

show ip cache flow 165

show ip cache flow aggregation 172

show ip cache verbose flow 180

show ip cache verbose flow aggregation 192

show ip flow export 200

show ip flow top 211

show ip flow top-talkers 212

show mls ip non-static 233

show mls ip routes 235

show mls ip static 237

show mls nde 239

show mls netflow 241

show mls netflow ip 246

show mls netflow ipv6 252

show mls netflow ip dynamic 256

show mls netflow ip routes 258

show mls netflow ip sw-installed 260

show mls netflow ipx 262

show mls sampling 264

sort-by 265

top 268





## backup (NetFlow SCTP) through ip route-cache flow

---

- [backup \(NetFlow SCTP\), page 3](#)
- [cache, page 6](#)
- [cache-timeout, page 8](#)
- [clear fm netflow counters, page 11](#)
- [clear ip flow stats, page 12](#)
- [clear mls nde flow counters, page 14](#)
- [clear mls netflow, page 15](#)
- [debug mpls netflow, page 19](#)
- [enabled \(aggregation cache\), page 21](#)
- [export destination, page 23](#)
- [export destination sctp \(NetFlow aggregation cache\), page 26](#)
- [export template, page 29](#)
- [export version, page 32](#)
- [flow hardware mpls-vpn ip, page 35](#)
- [flow-sampler, page 37](#)
- [flow-sampler-map, page 40](#)
- [ip flow, page 43](#)
- [ip flow layer2-switched, page 46](#)
- [ip flow-aggregation cache, page 48](#)
- [ip flow-cache entries, page 52](#)
- [ip flow-cache mpls label-positions, page 55](#)
- [ip flow-cache timeout, page 58](#)
- [ip flow-capture, page 60](#)

- [ip flow-egress input-interface](#), page 67
- [ip flow-export destination](#), page 69
- [ip flow-export destination sctp](#), page 73
- [ip flow-export hardware version](#), page 75
- [ip flow-export interface-names](#), page 77
- [ip flow-export source](#), page 79
- [ip flow-export template](#), page 82
- [ip flow-export version](#), page 85
- [ip flow-export version \(Supervisor Engine 2\)](#), page 89
- [ip flow-export version \(Supervisor Engine 720\)](#), page 91
- [ip flow-top-talkers](#), page 93
- [ip multicast netflow](#), page 96
- [ip multicast netflow output-counters](#), page 99
- [ip multicast netflow rpf-failure](#), page 101
- [ip route-cache flow](#), page 103



# backup (NetFlow SCTP)

To configure a backup destination for the reliable export of NetFlow accounting information in NetFlow cache entries, use the **backup** command in NetFlow ip flow export stream control transmission protocol (SCTP) configuration mode. To remove a destination for the reliable export of NetFlow accounting information, use the no form of this command.

**backup** {destination {*ip-address* | *hostname*} *sctp-port* | **fail-over** *time* | **mode** {**fail-over** | **redundant**} | **restore-time** *time*}

**no backup** {destination {*ip-address* | *hostname*} *sctp-port* | **fail-over** | **mode** {**fail-over** | **redundant**} | **restore-time**}

## Syntax Description

<i>ip-address</i>   <i>hostname</i>	IP address or hostname of the workstation to which you want to send the NetFlow information.
<i>port</i>	Specifies the number of the stream control transmission protocol (SCTP) port on which the workstation is listening for the exported NetFlow datagrams.
<b>fail-over</b> <i>time</i>	(Optional) Specifies the length of time that the primary export destination must be unavailable before SCTP starts using the backup export destination. The default fail-over time for sctp to start using a backup export destination is 25 milliseconds (msec). Range: 0 to 3600 msec.
<b>mode</b> { <b>fail-over</b>   <b>redundant</b> }	(Optional) Specifies the mode that SCTP will use to establish a connection to the backup export destination: <ul style="list-style-type: none"> <li>• <b>fail-over</b> --Opens an association with the backup export destination when the primary export destination becomes unavailable</li> <li>• <b>redundant</b> --Maintains a permanent association with the backup export destination.</li> </ul>
<b>restore-time</b> <i>time</i>	(Optional) Specifies the length of time that the primary export destination must be available after an outage before SCTP reverts back to it. This is applicable only when SCTP is using the backup export destination. Range: 0 to 3600 seconds.

## Command Default

Backup destinations for the reliable export of NetFlow information are not configured.

**Command Modes**

NetFlow ip flow export SCTP (config-flow-export-sctp)

**Usage Guidelines**

When you configure a backup export destination for SCTP messages are sent to the destination if the primary export destination becomes unavailable. When connectivity with the primary export destination has been lost and a backup export destination is configured, SCTP begins using the backup export destination. The default period of time that SCTP waits until it starts using the backup export destination is 25 sec. You can configure a different with the **fail-overtime** command.

**Note**

SCTP retransmits messages that have not been acknowledged three times. The router will initiate fail-over after three retransmissions of the same message are not acknowledged by the primary collector.

The router sends periodic SCTP heart beat messages to the SCTP export destinations that you have configured. The router uses the SCTP heart-beat message acknowledgments from the export destinations to monitor the status of each export destination. This allows an application, such as NetFlow, to be quickly informed when connectivity to an export destination is lost.

You can configure SCTP backup in fail-over or redundant mode. When the router is configured with SCTP backup in fail-over mode the router waits to activate the association with the backup export destination until the router has not received acknowledgments for the SCTP heart beat messages from the primary export destination for the time specified by the **fail-overtime** command. When the router is configured with SCTP backup in redundant mode, the router activates the association with the backup export destination immediately instead of waiting for the primary export destination to fail. The router will not start sending SCTP messages to a backup export destination in redundant mode until the router has not received acknowledgements for the SCTP heart beat messages from the primary export destination for the time specified by the **fail-overtime** command. Fail-over mode is the preferred method when the backup export destination is on the end of an expensive lower-bandwidth link such as ISDN.

During the time that SCTP is using the backup export destination, SCTP continues to try to restore the association with the primary export destination. SCTP makes this attempt until connectivity is restored or the primary SCTP export destination is removed from the configuration.

When connectivity to the primary export destination is available again, the router waits for a period of time before reverting to using it as the primary destination. You use the **restore-timetime** command to configure the value of the period of time that SCTP waits until reverting. The default period of time that SCTP waits is 25 msec.

Under either fail-over mode, any records which have been queued between loss of connectivity with the primary destination and, the establishing of the association with the backup export destination might be lost. A count of how many records were lost can be viewed through the use of the **show ip flow export sctp verbose** command.

To avoid a flapping SCTP association with an export destination (the SCTP association going up and down in quick succession), the time period configured with the **restore-timetime** command should be greater than the period of a typical connectivity problem. For example, your router is configured to use IP fast convergence for its routing table and you have a LAN interface that is going up and down repeatedly (flapping). This causes the IP route to the primary export destination to be added to and removed from the routing table (route flapping) every 2000 msec (2 sec) you need to configure the restore time for a value greater than 2000 msec.

The backup connection uses stream 0 for sending templates, options templates, and option records. The data stream(s) inherit the reliability settings of the primary export destination.

**Command History**

Release	Modification
12.4(4)T	This command was introduced.

**Examples**

The following example shows how to configure the networking device to use SCTP as the transport protocol for transmissions to multiple export destinations in redundant mode. The router activates the association with the backup export destination immediately instead of waiting until the primary export destination fails. The router starts sending SCTP messages to the backup export destination over the preexisting association after it fails to receive acknowledgments for its SCTP heart-beat messages from the primary export destination for 1500 msec. The router waits 3000 msec after the primary export destination is reachable again before resuming the association with the primary export destination.

```
Router(config)# ip flow-export destination 172.16.10.2 78 sctp
Router(config-flow-export-sctp) # backup destination 172.16.10.3 78
Router(config-flow-export-sctp) # backup mode redundant
Router(config-flow-export-sctp) # backup fail-over 1500
Router(config-flow-export-sctp) # backup restore-time 3000
```

The following example shows how to configure the networking device to use SCTP as the transport protocol to multiple export destinations in fail-over mode. The router activates the association with the backup export destination and starts sending SCTP messages to the backup export destination after it fails to receive acknowledgments for its SCTP heart beat messages from the primary export destination for 1500 msec. The router waits 3000 sec after the primary export destination is reachable again before resuming the association with the primary export destination. The SCTP association with the backup export destination is closed after the router resumes sending SCTP messages to the primary export destination.

```
Router(config)# ip flow-export destination 172.16.10.2 78 sctp
Router(config-flow-export-sctp) # backup destination 172.16.10.3 78
Router(config-flow-export-sctp) # backup mode fail-over
Router(config-flow-export-sctp) # backup fail-over 1500
Router(config-flow-export-sctp) # backup restore-time 3000
```

**Related Commands**

Command	Description
<b>ip flow-export destination sctp</b>	Enables the reliable export of NetFlow accounting information in NetFlow cache entries.
<b>reliability</b>	Specifies the level of reliability for the reliable export of NetFlow accounting information in NetFlow cache entries.
<b>show ip flow export</b>	Displays the status and the statistics for NetFlow accounting data export.

# cache

To configure operational parameters for NetFlow accounting aggregation caches, use the **cache** command in NetFlow aggregation cache configuration mode. To disable the NetFlow aggregation cache operational parameters for NetFlow accounting, use the **no** form of this command.

**cache** {**entries** *number*| **timeout** {**active** *minutes*| **inactive** *seconds*}}

**no cache** {**entries**| **timeout** {**active**| **inactive**}}

## Syntax Description

<b>entries</b> <i>number</i>	(Optional) The number of cached entries allowed in the aggregation cache. The range is from 1024 to 524288. The default is 4096.  <b>Note</b> For the Cisco ASR 1000 Series Aggregation Services Router, the range is 1024 to 2000000 (2 million). The default is 4096.
<b>timeout</b>	(Optional) Configures aggregation cache time-outs.
<b>active</b> <i>minutes</i>	(Optional) The number of minutes that an active entry will stay in the aggregation cache before it is exported and removed. The range is from 1 to 60 minutes. The default is 30 minutes.
<b>inactive</b> <i>seconds</i>	(Optional) The number of seconds that an inactive entry will stay in the aggregation cache before it times out. The range is from 10 to 600 seconds. The default is 15 seconds.

## Command Default

The operational parameters for NetFlow accounting aggregation caches are not configured.

## Command Modes

NetFlow aggregation cache configuration (config-flow-cache)

## Command History

Release	Modification
12.0(3)T	This command was introduced.
12.2(14)S	This command was integrated into Cisco IOS Release 12.2(14)S.
12.3(7)T	This command function was modified to support cache entries for IPv6.
12.2(28)SB	This command was integrated into Cisco IOS Release 12.2(28)SB.
12.2(18)SXF	This command was integrated into Cisco IOS Release 12.2(18)SXF.

Release	Modification
12.2(33)SRA	This command was integrated into Cisco IOS Release 12.2(33)SRA.

**Usage Guidelines**

You must have NetFlow accounting configured on your router before you can use this command. .

**Examples**

The following example shows how to set the NetFlow aggregation cache entry limits and timeout values for the NetFlow protocol-port aggregation cache:

```
Router(config)#
ip flow-aggregation cache protocol-port
Router(config-flow-cache)#
cache entries 2046
Router(config-flow-cache)#
cache timeout inactive 199
Router(config-flow-cache)#
cache timeout active 45
Router(config-flow-cache)#
enabled
```

**Related Commands**

Command	Description
<b>enabled (aggregation cache)</b>	Enables a NetFlow accounting aggregation cache.
<b>export destination (aggregation cache)</b>	Enables the exporting of NetFlow accounting information from NetFlow aggregation caches.
<b>ip flow-aggregation cache</b>	Enables NetFlow accounting aggregation cache schemes.
<b>mask (IPv4)</b>	Specifies the source or destination prefix mask for a NetFlow accounting prefix aggregation cache.
<b>show ip cache flow</b>	Displays a summary of the NetFlow accounting statistics.
<b>show ip cache flow aggregation</b>	Displays the NetFlow accounting aggregation cache statistics.
<b>show ip cache verbose flow</b>	Displays a detailed summary of the NetFlow accounting statistics.
<b>show ip flow interface</b>	Displays NetFlow accounting configuration for interfaces.

# cache-timeout

To specify the length of time for which the list of NetFlow top talkers (unaggregated top flows) is retained, use the **cache-timeout** command in NetFlow top talkers configuration mode. To return the timeout parameters for the list of top talkers to the default of 5 seconds, use the **no** form of this command.

**cache-timeout** *milliseconds*

**no cache-timeout**

## Syntax Description

<i>milliseconds</i>	Length in milliseconds for which the list of top talkers is retained. The range is from 1 to 3,600,000 (1 millisecond to one hour). The default is 5000 (5 seconds).
---------------------	--

## Command Default

The default time for which the list of top talkers is retained is 5 seconds.

## Command Modes

NetFlow top talkers configuration

## Command History

Release	Modification
12.2(25)S	This command was introduced.
12.3(11)T	This feature was integrated into Cisco IOS Release 12.3(11)T.
12.2(27)SBC	This command was integrated into Cisco IOS Release 12.2(27)SBC.
12.2(33)SRA	This command was integrated into Cisco IOS Release 12.2(33)SRA.
12.2SX	This command is supported in the Cisco IOS Release 12.2SX train. Support in a specific 12.2SX release of this train depends on your feature set, platform, and platform hardware.

## Usage Guidelines

### Configuring NetFlow top talkers

You must enable NetFlow on at least one interface in the router; and configure NetFlow top talkers before you can use the **show ip flow top-talkers** command to display the traffic statistics for the unaggregated top flows in the network. NetFlow top talkers also requires that you configure the **sort-by** and **top** commands. Optionally, the **match** command can be configured to specify additional matching criteria.

### Cache Timeout

The cache timeout starts after the list of top talkers is requested by entering the **show ip flow top-talkers** command or through the netflow MIB.

A long timeout period limits the system resources that are used by NetFlow top talkers. However, the list of top talkers is calculated only once during the timeout period. If a request to display the top talkers is made more than once during the timeout period, the same results are displayed for each request, and the list of top talkers is not recalculated until the timeout period expires.

A short timeout period ensures that the latest list of top talkers is retrieved; however too short a period can have undesired effects:

- The list of top talkers is lost when the timeout period expires. You should configure a timeout period for at least as long as it takes the network management system (NMS) to retrieve all the required NetFlow top talkers.
- The list of top talkers is updated every time the top talkers information is requested, possibly causing unnecessary usage of system resources.

A good method to ensure that the latest information is displayed, while also conserving system resources, is to configure a large value for the timeout period, but recalculate the list of top talkers by changing the parameters of the **cache-timeout**, **top**, or **sort-by** command prior to entering the **show ip flow top-talkers** command to display the top talkers. Changing the parameters of the **cache-timeout**, **top**, or **sort-by** command causes the list of top talkers to be recalculated upon receipt of the next command line interface (CLI) or MIB request.

**Examples**

In the following example, the list of top talkers is configured to be retained for 2 seconds (2000 milliseconds). There is a maximum of 4 top talkers, and the sort criterion is configured to sort the list of top talkers by the total number of bytes in each top talker.

```
Router(config)# ip flow-top-talkers
Router(config-flow-top-talkers)# cache-timeout 2000
Router(config-flow-top-talkers)# top 4
Router(config-flow-top-talkers)# sort-by bytes
```

The following example shows the output of the **show ip flow top talkers** command using the configuration from the previous example:

```
Router# show ip flow top-talkers

SrcIf      SrcIPAddress  DstIf      DstIPAddress  Pr SrcP DstP Bytes
Et0/0.1    10.10.18.1    Et1/0.1    172.16.10.232  11 00A1 00A1 349K
Et0/0.1    10.10.19.1    Et1/0.1    172.16.10.2    11 00A2 00A2 349K
Et0/0.1    172.30.216.196 Et1/0.1    172.16.10.2    06 0077 0077 328K
Et0/0.1    10.162.37.71 Et1/0.1    172.16.10.2    06 0050 0050 303K
4 of 4 top talkers shown. 11 flows processed
```

**Related Commands**

Command	Description
<b>ip flow-top-talkers</b>	Enters the configuration mode for the NetFlow MIB and top talkers (heaviest traffic patterns and most-used applications in the network) feature.
<b>match (NetFlow)</b>	Specifies match criteria for the NetFlow MIB and top talkers (heaviest traffic patterns and most-used applications in the network) feature.

Command	Description
<b>show ip flow top-talkers</b>	Displays the statistics for the top talkers (heaviest traffic patterns and most-used applications in the network).
<b>sort-by</b>	Specifies the sorting criterion for top talkers (heaviest traffic patterns and most-used applications in the network) to be displayed for the NetFlow MIB and top talkers feature.
<b>top</b>	Specifies the maximum number of top talkers (heaviest traffic patterns and most-used applications in the network) to be displayed for the NetFlow MIB and top talkers feature.
<b>show ip cache flow</b>	Displays a summary of the NetFlow accounting statistics.
<b>show ip cache verbose flow</b>	Displays a detailed summary of the NetFlow accounting statistics.
<b>show ip flow interface</b>	Displays NetFlow accounting configuration for interfaces.



# clear fm netflow counters

To clear the NetFlow counters, use the **clear fm netflow counters** command in privileged EXEC mode.

**clear fm netflow counters**

**Syntax Description** This command has no arguments or keywords.

**Command Default** This command has no default settings.

**Command Modes** Privileged EXEC

<b>Command History</b>	<b>Release</b>	<b>Modification</b>
	12.2(18)SXD	Support for this command was introduced on the Supervisor Engine 720.
	12.2(33)SRA	This command was integrated into Cisco IOS Release 12.2(33)SRA.

**Usage Guidelines** This command is not supported on systems that are configured with a Supervisor Engine 2.

**Examples** This example shows how to clear the NetFlow counters:

```
Router# clear fm netflow counters
Router#
```

# clear ip flow stats

To clear the NetFlow accounting statistics, use the **clear ip flow stats** command in privileged EXEC mode.

**clear ip flow stats [nbar]**

## Syntax Description

<b>nbar</b>	(Optional) Clears Network Based Application Recognition (NBAR) NetFlow statistics.
-------------	--

## Command Modes

Privileged EXEC (#)

## Command History

Release	Modification
11.1CA	This command was introduced.
12.2(14)S	This command was integrated into Cisco IOS Release 12.2(14)S.
12.2(14)SX	Support for this command was introduced on the Supervisor Engine 720.
12.2(17d)SXB	Support for this command on the Supervisor Engine 2 was extended to the 12.2(17d)SXB release.
12.2(27)SBC	This command was integrated into Cisco IOS Release 12.2(27)SBC.
12.2(18)SXF	This command was integrated into Cisco IOS Release 12.2(18)SXF.
12.2(33)SRA	This command was integrated into Cisco IOS Release 12.2(33)SRA.
12.2(18)ZYA2	This command was modified. The <b>nbar</b> keyword was added.

## Usage Guidelines

You must have NetFlow accounting configured on your router before you can use this command.

The **show ip cache flow** command displays the NetFlow accounting statistics. Use the **clear ip flow stats** command to clear the NetFlow accounting statistics.

## Examples

The following example shows how to clear the NetFlow accounting statistics on the router:

```
Router# clear ip flow stats
```

**Related Commands**

<b>Command</b>	<b>Description</b>
<b>show ip cache flow</b>	Displays a summary of the NetFlow accounting statistics.
<b>show ip cache verbose flow</b>	Displays a detailed summary of the NetFlow accounting statistics.
<b>show ip flow interface</b>	Displays NetFlow accounting configuration for interfaces.
<b>show ip interface</b>	Displays the usability status of interfaces configured for IP.

# clear mls nde flow counters

To clear the NDE counters, use the **clearmlsndeflowcounters** command.

**clear mls nde flow counters**

**Syntax Description** This command has no keywords or arguments.

**Command Default** This command has no default settings.

**Command Modes** Privileged EXEC

## Command History

Release	Modification
12.2(14)SX	Support for this command was introduced on the Supervisor Engine 720.
12.2(17d)SXB	Support for this command on the Supervisor Engine 2 was extended to the 12.2 SX release.
12.2(33)SRA	This command was integrated into Cisco IOS Release 12.2(33)SRA.

## Examples

This example shows how to reset the NDE counters:

```
Router#
clear mls nde flow counters
Router#
```

## Related Commands

Command	Description
show mls nde	Displays information about the NDE hardware-switched flow.

# clear mls netflow

To clear the MLS NetFlow-shortcut entries, use the **clearmlsnetflow** command.

**clear mls netflow ip** [**destination** *ip-addr* [**source** *ip-addr-spec*]] [**dynamic**| **sw-installed** [**non-static**| **static**]] [**module** *mod*]

**clear mls netflow ipv6** [**destination** *ipv6-addr* [**slash** *ipv6-prefix*] [**source** *ipv6-addr* [**slash** *ipv6-prefix*]]] [**flow** {**tcp**| **udp**}] [{**destination**| **source**} *port-num*] [**dynamic**| **sw-installed** [**non-static**| **static**]] [**module** *mod*]

**clear mls netflow mpls** [**top-label** *entry*] [**dynamic**| **sw-installed** [**non-static**| **static**]] [**module** *mod*]

**clear mls ipx** [[**module** *mod*] [**destination** *ipx-network* [*ipx-node* ]]] [**source** *ipx-network*] [**macs** *mac-addr*] [**macd** *mac-addr*] [**interface** *interface-num*]] [**all**]]

## Syntax Description

<b>ip</b>	Clears IP MLS entries.
<b>destination</b> <i>ip-addr</i>	(Optional) Specifies a destination full IP address or a subnet address. See the “Usage Guidelines” section for formatting guidelines.
<b>source</b> <i>ip-addr</i>	(Optional) Specifies a source full IP address or a subnet address. See the “Usage Guidelines” section for formatting guidelines.
<b>dynamic</b>	(Optional) Clears NetFlow-statistics entries that are created in the hardware.
<b>sw-installed non-static</b>	(Optional) Clears software-installed nonstatic entries.
<b>sw-installed static</b>	(Optional) Clears software-installed static entries.
<b>module</b> <i>mod</i>	(Optional) Specifies a module number.
<b>ipv6</b>	Clears IP version 6 software-installed entries.
<b>destination</b> <i>ipv6-addr</i>	(Optional) Specifies a destination full IPv6 address or a subnet address. See the “Usage Guidelines” section for formatting guidelines.
<i>/ ipv6-prefix</i>	(Optional) IPv6 prefix; valid values are from 0 to 128.
<b>source</b> <i>iv6p-addr</i>	(Optional) Specifies a source full IPv6 address or a subnet address. See the “Usage Guidelines” section for formatting guidelines.
<b>flow tcp</b>	(Optional) Clears TCP flow information.

<b>flow udp</b>	(Optional) Clears UDP flow information.
<i>destination port-num</i>	(Optional) Specifies a destination port number.
<i>sourceport-num</i>	(Optional) Specifies a source port number.
<b>mpls</b>	Clears MPLS software-installed entries.
<b>top-label</b> <i>entry</i>	(Optional) Clears top-label entries; valid values are from 1 to 4294967295.
<b>ipx</b>	Clears IPX MLS entries.
<b>destination</b> <i>ipx-network</i>	(Optional) Specifies the destination IPX address. See the “Usage Guidelines” section for formatting guidelines.
<i>ipx-node</i>	(Optional) IPX node address. See the “Usage Guidelines” section for formatting guidelines.
<b>source</b> <i>ipx-network</i>	(Optional) Specifies the source IPX address. See the “Usage Guidelines” section for formatting guidelines.
<b>macs</b> <i>mac-addr</i>	(Optional) Specifies the source MAC addresses to consider when searching for entries to purge.
<b>macd</b> <i>mac-addr</i>	(Optional) Specifies the destination MAC addresses to consider when searching for entries to purge.
<b>interface</b> <i>interface-num</i>	(Optional) Clears entries that are associated with the specified VLAN or interface.
<b>all</b>	(Optional) Clears all entries.

**Command Default** This command has no default settings.

**Command Modes** Privileged EXEC

#### Command History

Release	Modification
12.2(14)SX	Support for this command was introduced on the Supervisor Engine 720.

Release	Modification
12.2(17a)SX	This command was changed as follows: <ul style="list-style-type: none"> <li>• Replaced the <b>routes</b> keyword with <b>sw-installed</b>.</li> <li>• Replaced the <b>statistics</b> keyword with <b>dynamic</b>.</li> <li>• Changed the syntax from <b>clearmls [ip   ipv6   mpls]</b> to <b>clearmlsnetflow [ip   ipv6   mpls]</b></li> </ul>
12.2(17d)SXB	Support for this command on the Supervisor Engine 2 was extended to the 12.2 SX release.
12.2(18)SXF	This command was changed as follows: <ul style="list-style-type: none"> <li>• Removed support for the <b>any</b> keyword.</li> <li>• Added the <i>ipv6-prefix</i> argument.</li> </ul>
12.2(33)SRA	This command was integrated into Cisco IOS Release 12.2(33)SRA.

### Usage Guidelines

The **destination***ipx-network*, *ipx-node*, and **source***ipx-network* keywords and arguments are supported on Cisco 7600 series routers that are configured with a Supervisor Engine 2 only.

When entering the IPX address syntax, use the following format:

- IPX network address--1..FFFFFFFE
- IPX node address--x.x.x where x is 0..FFFF
- IPX address--ipx\_net.ipx\_node (for example, 3.0034.1245.AB45, A43.0000.0000.0001)

Entering any combination of input parameters narrows the search of entries to be cleared. The **destination** or **sourceport-num** keyword and argument should be specified as one of the following: telnet, FTP, WWW, SMTP, X, or DNS.

Up to 16 routers can be included explicitly as MLS-RPs.

Use the following syntax to specify an IP subnet address:

- *ip-subnet-addr* or *ipv6-subnet-addr*--Short subnet address format. The trailing decimal number 00 in an IP or IPv6 address YY.YY.YY.00 specifies the boundary for an IP or IPv6 subnet address. For example, 172.22.36.00 indicates a 24-bit subnet address (subnet mask 172.22.36.00/255.255.255.0), and 173.24.00.00 indicates a 16-bit subnet address (subnet mask 173.24.00.00/255.255.0.0). However, this format can identify only a subnet address of 8, 16, or 24 bits.
- *ip-addr/subnet-mask* or *ipv6-addr/subnet-mask*--Long subnet address format. For example, 172.22.252.00/255.255.252.00 indicates a 22-bit subnet address. This format can specify a subnet address of any bit number. To provide more flexibility, the *ip-addr* or *ipv6-addr* is a full host address, such as 172.22.253.1/255.255.252.00.
- *ip-addr/maskbits* or *ipv6-addr/maskbits*--Simplified long subnet address format. The mask bits specify the number of bits of the network masks. For example, 172.22.252.00/22 indicates a 22-bit subnet

address. The *ip-addr* or *ipv6-addr* is a full host address, such as 193.22.253.1/22, which has the same subnet address as the *ip-subnet-addr* or *ipv6-subnet-addr*.

If you do not use the **all** keyword, you must specify at least one of the other four keywords (**source**, **destination**, **flow**, or **interface**) and its arguments.

A 0 value for the **destination** or **sourceport-num** keyword and argument clears all entries. Unspecified options are treated as wildcards, and all entries are cleared.

## Examples

This example shows how to clear all the entries that are associated with a specific module (2) and that have a specific destination IP address (173.11.50.89):

```
Router#
clear mls netflow ip destination 173.11.50.89 module 2
Router#
```

This example shows how to clear the IPv6 software-installed entries:

```
Router#
clear mls netflow ipv6
Router#
```

This example shows how to clear the statistical information:

```
Router#
clear mls netflow dynamic
Router#
```

## Related Commands

Command	Description
<b>show mls netflow ip</b>	Displays information about the hardware NetFlow IP.
<b>show mls netflow ipv6</b>	Displays information about the hardware NetFlow IPv6 configuration.



## debug mpls netflow

To display debug messages for MPLS egress NetFlow accounting, use the **debug mpls netflow** command in privileged EXEC mode. To disable debugging output, use the **no** form of this command.

**debug mpls netflow**

**no debug mpls netflow**

**Syntax Description** This command has no arguments or keywords.

**Command Modes** Privileged EXEC (#)

### Command History

Release	Modification
12.0(10)ST	This command was introduced.
12.1(5)T	This command was integrated into Cisco IOS Release 12.1(5)T.
12.0(22)S	This command was integrated into Cisco IOS Release 12.0(22)S.
12.2(28)SB	This command was integrated into Cisco IOS Release 12.2(28)SB.
12.2(33)SRA	This command was integrated into Cisco IOS Release 12.2(33)SRA.
12.2(33)SX14	This command was integrated into Cisco IOS Release 12.2(33)SX14.

### Examples

Here is sample output from the **debug mpls netflow** command:

```
Router# debug mpls netflow
MPLS Egress NetFlow debugging is on
Router#
Router#
Router#
4d00h:Egress flow:entry created, dest 3.3.3.3/32, src 34.0.0.1/8
Router#
Router#
4d00h:Egress flow:entry created, dest 3.3.3.3/32, src 42.42.42.42/32
Router# conf t
Enter configuration commands, one per line. End with CNTL/Z.
Router(config)# int eth1/4
Router(config-if)# no mpls netflow egress
Router(config-if)#
4d00h:MPLS output feature change, trigger TFIB scan
4d00h:tfib_scanner_walk, prefix 5.5.5.5/32, rewrite flow flag 0
4d00h:tfib_scanner_walk, prefix 2.0.0.0/8, rewrite flow flag 0
4d00h:tfib_scanner_walk, prefix 3.3.3.3/32, rewrite flow flag 0
4d00h:tfib_scanner_walk, prefix 40.40.40.40/32, rewrite flow flag 0
4d00h:tfib_scanner_walk, prefix 50.50.50.50/32, rewrite flow flag 0
4d00h:tfib_scanner_walk, prefix 100.100.100.100/32, rewrite flow flag 0
4d00h:tfib_scanner_walk, prefix 180.1.1.0/24, rewrite flow flag 0
4d00h:tfib_scanner_walk, prefix 190.1.1.0/24, rewrite flow flag 1
```

```

4d00h:tfib_scanner_walk, prefix 2.0.0.0/8, rewrite flow flag 1
4d00h:tfib_scanner_walk, prefix 4.4.4.4/32, rewrite flow flag 1
4d00h:tfib_scanner_walk, prefix 40.40.40.40/32, rewrite flow flag 0
4d00h:tfib_scanner_walk, prefix 50.50.50.50/32, rewrite flow flag 0
4d00h:tfib_scanner_walk, prefix 177.1.1.0/24, rewrite flow flag 1
4d00h:tfib_scanner_walk, prefix 180.1.1.0/24, rewrite flow flag 0
4d00h:tfib_scanner_walk, prefix 190.1.1.0/24, rewrite flow flag 1
Router(config-if)#
Router(config-if)# mpls netflow egress
Router(config-if)#
4d00h:Interface refcount with output feature enabled = 2
4d00h:MPLS output feature change, trigger TFIB scan
4d00h:tfib_scanner_walk, prefix 5.5.5.5/32, rewrite flow flag 0
4d00h:tfib_scanner_walk, prefix 2.0.0.0/8, rewrite flow flag 1
4d00h:tfib_scanner_walk, prefix 3.3.3.3/32, rewrite flow flag 1
4d00h:tfib_scanner_walk, prefix 40.40.40.40/32, rewrite flow flag 0
4d00h:tfib_scanner_walk, prefix 50.50.50.50/32, rewrite flow flag 0
4d00h:tfib_scanner_walk, prefix 100.100.100.100/32, rewrite flow flag 1
4d00h:tfib_scanner_walk, prefix 180.1.1.0/24, rewrite flow flag 1
4d00h:tfib_scanner_walk, prefix 190.1.1.0/24, rewrite flow flag 1
4d00h:tfib_scanner_walk, prefix 2.0.0.0/8, rewrite flow flag 1
4d00h:tfib_scanner_walk, prefix 4.4.4.4/32, rewrite flow flag 1
4d00h:tfib_scanner_walk, prefix 40.40.40.40/32, rewrite flow flag 0
4d00h:tfib_scanner_walk, prefix 50.50.50.50/32, rewrite flow flag 0
4d00h:tfib_scanner_walk, prefix 177.1.1.0/24, rewrite flow flag 1
4d00h:tfib_scanner_walk, prefix 180.1.1.0/24, rewrite flow flag 1
4d00h:tfib_scanner_walk, prefix 190.1.1.0/24, rewrite flow flag 1
4d00h:Egress flow:entry created, dest 3.3.3.3/32, src 42.42.42.42/32
Router(config-if)#
Router(config-if)# end
Router# show run int eth1/4
Building configuration...
Current configuration:
!
interface Ethernet1/4
 ip vrf forwarding vpn1
 ip address 180.1.1.1 255.255.255.0
 no ip directed-broadcast
 mpls netflow egress
end
Router#
Router#
4d00h:%SYS-5-CONFIG_I:Configured from console by console
Router#

```



**Note** Flow flag 1 prefixes are reachable through this interface; therefore, MPLS egress NetFlow accounting is applied to all packets going out the destination prefix. Flow flag 0 prefixes are not reachable through this interface; therefore, MPLS egress NetFlow accounting is not applied to any packets going out the destination prefix.

**Related Commands**

Command	Description
show debug	Displays active debug output.

## enabled (aggregation cache)

To enable a NetFlow accounting aggregation cache, use the **enabled** command in NetFlow aggregation cache configuration mode. To disable a NetFlow accounting aggregation cache, use the **no** form of this command.

**enabled**

**no enabled**

**Syntax Description** This command has no arguments or keywords.

**Command Default** No aggregation cache is enabled.

**Command Modes** NetFlow aggregation cache configuration

Command History	Release	Modification
	12.0(3)T	This command was introduced.
	12.2(14)S	This command was integrated into Cisco IOS Release 12.2(14)S.
	12.2(27)SBC	This command was integrated into Cisco IOS Release 12.2(27)SBC.
	12.2(18)SXF	This command was integrated into Cisco IOS Release 12.2(18)SXF.
	12.2(33)SRA	This command was integrated into Cisco IOS Release 12.2(33)SRA.

**Usage Guidelines** You must have NetFlow accounting configured on your router before you can use this command.

**Examples** The following example shows how to enable a NetFlow protocol-port aggregation cache:

```
Router(config)# ip flow-aggregation cache protocol-port
```

```
Router(config-flow-cache) # enabled
```

The following example shows how to disable a NetFlow protocol-port aggregation cache:

```
Router(config)# ip flow-aggregation cache protocol-port
```

```
Router(config-flow-cache) # no
enabled
```

**Related Commands**

Command	Description
<b>cache</b>	Defines operational parameters for NetFlow accounting aggregation caches.
<b>export destination (aggregation cache)</b>	Enables the exporting of NetFlow accounting information from NetFlow aggregation caches.
<b>ip flow-aggregation cache</b>	Enables NetFlow accounting aggregation cache schemes.
<b>mask (IPv4)</b>	Specifies the source or destination prefix mask for a NetFlow accounting prefix aggregation cache.
<b>show ip cache flow aggregation</b>	Displays the NetFlow accounting aggregation cache statistics.
<b>show ip cache flow</b>	Displays a summary of the NetFlow accounting statistics.
<b>show ip cache verbose flow</b>	Displays a detailed summary of the NetFlow accounting statistics.
<b>show ip flow interface</b>	Displays NetFlow accounting configuration for interfaces.

# export destination

To enable the exporting of NetFlow accounting information from NetFlow aggregation caches, use the **export destination** command in NetFlow aggregation cache configuration mode. To disable the export of NetFlow accounting information from NetFlow aggregation caches, use the **no** form of this command.

**export destination** {*hostname*| *ip-address*} *port* [**vrf** *vrf-name*] [**udp**]

**no export destination** {*hostname*| *ip-address*} *port* [**vrf** *vrf-name*] [**udp**]

## Syntax Description

<i>ip-address</i>   <i>hostname</i>	IP address or hostname of the workstation to which you want to send the NetFlow information
<i>port</i>	Specifies the number of the user datagram protocol (UDP) port on which the workstation is listening for the exported NetFlow datagrams.
<b>vrf</b> <i>vrf-name</i>	(Optional) The <b>vrf</b> keyword specifies that the export data packets are to be sent to the named Virtual Private Network (VPN) routing forwarding instance (VRF) for routing to the destination, instead of to the global routing table.  <b>Note</b> The <i>vrf-name</i> argument is the name of the VRF
<b>udp</b>	(Optional) Specifies UDP as the transport protocol. UDP is the default transport protocol.

## Command Default

Export of NetFlow information from NetFlow aggregation caches is disabled.

## Command Modes

NetFlow aggregation cache configuration (config-flow-cache)

## Command History

Release	Modification
12.0(3)T	This command was introduced.
12.2T	This command was modified to enable multiple NetFlow export destinations to be used.
12.3(1)	Support for the NetFlow v9 Export Format feature was added.
12.2(14)S	This command was integrated into Cisco IOS Release 12.2(14)S, and support for the Multiple Export Destinations feature was added.

Release	Modification
12.2(27)SBC	This command was integrated into Cisco IOS Release 12.2(27)SBC.
12.2(18)SXF	This command was integrated into Cisco IOS Release 12.2(18)SXF.
12.2(33)SRA	This command was integrated into Cisco IOS Release 12.2(33)SRA.

**Usage Guidelines**

If the version of Cisco IOS that you have installed on your networking device supports the NetFlow Multiple Export Destinations feature, you can configure your networking device to export NetFlow data to a maximum of 2 export destinations (collectors) per cache (main and aggregation caches), using any combination of UDP and SCTP as the transport protocol for the destinations. A destination is identified by a unique combination of hostname or IP address and port number or port type.



**Note**

UDP is the default transport protocol used by the **export destination** command. In some Cisco IOS releases you can configure SCTP as the transport protocol if you need reliability and additional redundancy. Refer to the **export destination sctp** command for more information.

The table below shows examples of the 2 permitted NetFlow export destinations for each cache.

**Table 1: Examples of Permitted Multiple NetFlow Export Destinations for Each Cache**

First Export Destination	Second Export Destination
<b>ip flow-export</b> 10.25.89.32 100 udp	<b>ip flow-export</b> 10.25.89.32 285 udp
<b>ip flow-export</b> 10.25.89.32 100 udp	<b>ip flow-export</b> 172.16.89.32 100 udp
<b>ip flow-export</b> 10.25.89.32 100 udp	<b>ip flow-export</b> 172.16.89.32 285 udp
<b>ip flow-export</b> 10.25.89.32 100 udp	<b>ip flow-export</b> 10.25.89.32 100 sctp
<b>ip flow-export</b> 10.25.89.32 100 sctp	<b>ip flow-export</b> 10.25.89.32 285 sctp
<b>ip flow-export</b> 10.25.89.32 100 sctp	<b>ip flow-export</b> 172.16.89.32 100 sctp
<b>ip flow-export</b> 10.25.89.32 100 sctp	<b>ip flow-export</b> 172.16.89.32 285 sctp

The most common use of the multiple-destination feature is to send the NetFlow cache entries to two different destinations for redundancy. Therefore, in most cases the second destination IP address is not the same as the first IP address. The port numbers can be the same when you are configuring two unique destination IP addresses. If you want to configure both instances of the command to use the same destination IP address, you must use unique port numbers. You receive a warning message when you configure the two instances of the command with the same IP address. The warning message is, “%Warning: Second destination address is the same as previous address <ip-address>”.

**VRF Destinations for Exporting NetFlow Data**

Before Cisco IOS Releases 12.4(4)T and 12.2(18)SXH, only one routing option existed for NetFlow export data packets. NetFlow sent all export data packets to the global routing table for routing to the export destinations you specified.

Cisco IOS 12.4(4)T, 12.2(18)SXH, and later releases provide an additional routing option for NetFlow export data packets. You can send NetFlow data export packets to a Virtual Private Network (VPN) routing/forwarding instance (VRF) for routing to the destinations that you specify.

To send NetFlow data export packets to a VRF for routing to a destination, you enter the optional **vrfvrf-name** keyword and argument with the **ip flow-export destination ip-addressport** command. To configure the global routing table option, enter this command without the optional **vrfvrf-name** keyword and argument.

**Examples**

The following example shows how to configure two export destinations for a NetFlow accounting protocol-port aggregation cache scheme:

```
Router(config)#
ip flow-aggregation cache protocol-port
Router(config-flow-cache) # export destination 10.41.41.1 9992
Router(config-flow-cache) # export destination 172.16.89.1 9992
Router(config-flow-cache) # enabled
```

The following example shows how to configure the networking device for exporting from the NetFlow **source-prefix-tos** aggregation cache to an export destination that is reachable in VRF group1:

```
Router(config)#
ip flow-aggregation cache source-prefix-tos
Router(config-flow-cache) #
  export destination 172.16.10.2 78 vrf group1
Router(config-flow-cache) #
enabled
```

**Related Commands**

Command	Description
<b>export template</b>	Configures template options for the export of NetFlow accounting information in NetFlow aggregation cache entries
<b>export version</b>	Specifies the export version format for the exporting of NetFlow accounting information in NetFlow aggregation cache entries
<b>show ip flow export</b>	Displays the status and the statistics for NetFlow accounting data export.

## export destination sctp (NetFlow aggregation cache)

To enable the reliable export of NetFlow accounting information from NetFlow aggregation caches, use the **export destination sctp** command in NetFlow aggregation cache configuration mode. To disable the reliable export of NetFlow accounting information from NetFlow aggregation caches, use the **no** form of this command.

**export destination** {*ip-address*|*hostname*} *port* [**vrf** *vrf-name*] **sctp**

**no export destination** {*ip-address*|*hostname*} *port* [**vrf** *vrf-name*] **sctp**

### Syntax Description

<i>ip-address</i>   <i>hostname</i>	IP address or hostname of the workstation to which you want to send the NetFlow information.
<i>port</i>	Specifies the number of the stream control transmission protocol (SCTP) port on which the workstation is listening for the exported NetFlow datagrams.
<b>vrf</b> <i>vrf-name</i>	(Optional) The <b>vrf</b> keyword specifies that the export data packets are to be sent to the named Virtual Private Network (VPN) routing forwarding instance (VRF) for routing to the destination, instead of to the global routing table.  <b>Note</b> The <i>vrf-name</i> argument is the name of the VRF

### Command Default

Reliable export of NetFlow information from NetFlow aggregation caches is disabled.

### Command Modes

NetFlow aggregation cache configuration (config-flow-cache)

### Command History

Release	Modification
12.4(4)T	This command was introduced.
12.2(33)SRA	This command was integrated into Cisco IOS Release 12.2(33)SRA.

### Usage Guidelines

#### NetFlow Reliable Export Using SCTP

SCTP can be used as an alternative to UDP when you need a more robust and flexible transport protocol than UDP. SCTP is a reliable message-oriented transport layer protocol, which allows data to be transmitted between two end-points in a reliable, partially reliable, or unreliable manner.



An SCTP session consists of an association (connection) between two end-points (peers), which can contain one or more logical channels called streams. The default mode of transmission for a stream is to guarantee reliable ordered delivery of messages using a selective-acknowledgment scheme. SCTP buffers messages until their receipt has been acknowledged by the receiving end-point. SCTP has a congestion control mechanism which limits how much memory is consumed by the SCTP stack, in packet buffering.

**VRF Destinations for Exporting NetFlow Data**

Before Cisco IOS Release 12.4(4)T, one routing option existed for NetFlow export data packets. NetFlow sent all export data packets to the global routing table for routing to the destinations you specified.

Cisco IOS 12.4(4)T and later releases provide an additional routing option for NetFlow export data packets. You can send NetFlow data export packets to a Virtual Private Network (VPN) routing/forwarding instance (VRF) for routing to the destinations that you specify.

To send NetFlow data export packets to a VRF for routing to a destination, you enter the optional **vrfvrf-name** keyword and argument with the **export destination ip-addressport** command. To configure the global routing table option, enter this command without the optional **vrfvrf-name** keyword and argument.

**Examples**

The following example shows how to configure the networking device to use SCTP as the transport protocol when exporting NetFlow data from a NetFlow AS aggregation cache to a host:

```
Router(config)#
ip flow-aggregation cache as
Router(config
-flow-cache
)# export destination 172.16.10.2 78 sctp
Router(config
-flow-cache
)# enabled
```

The following example shows how to configure the networking device to use SCTP as the transport protocol when exporting NetFlow data from a NetFlow AS aggregation cache to a host that is reachable in VRF group1:

```
Router(config)#
ip flow-aggregation cache as
Router(config
-flow-cache
)# export destination 172.16.10.2 78 vrf group1 sctp
Router(config
-flow-cache
)# enabled
```

**Related Commands**

Command	Description
<b>backup</b>	Configures a backup destination for the reliable export of NetFlow accounting information in NetFlow cache entries
<b>export destination</b>	Enables the export of NetFlow accounting information in NetFlow aggregation cache entries to a remote device such as a server running an application that analyzes NetFlow data.
<b>export template</b>	Configures template options for the export of NetFlow accounting information in NetFlow aggregation cache entries

Command	Description
<b>export version</b>	Specifies the export version format for the exporting of NetFlow accounting information in NetFlow aggregation cache entries
<b>reliability</b>	Specifies the level of reliability for the reliable export of NetFlow accounting information in NetFlow cache entries.
<b>show ip flow export</b>	Displays the status and the statistics for NetFlow accounting data export.

# export template

To configure template options for the export of NetFlow accounting information from NetFlow aggregation caches, use the **export template** command in NetFlow aggregation cache configuration mode. To return to the default behavior, use the noform of this command.

## Configure template only

**export template** {refresh-rate *packets*| timeout-rate *minutes*}

**no export template** {refresh-rate| timeout-rate}

## Configure template options

**ip export template options** {export-stats| refresh-rate *packets*| timeout-rate *minutes*| sampler}

**no export template options** {export-stats| refresh-rate| timeout-rate| sampler}

### Syntax Description

<b>template</b>	Enables the <b>refresh-rate</b> and <b>timeout-rate</b> keywords for the configuring of Version 9 export templates.
<b>refresh-rate</b> <i>packets</i>	(Optional) Specifies the number of export packets that are sent before the options and flow templates are resent. Range: 1 to 600 packets. The default is 20 packets.  <b>Note</b> This applies to the <b>export template refresh-rate packets</b> command.
<b>timeout-rate</b> <i>minutes</i>	(Optional) Specifies the interval (in minutes) that the router waits after sending the templates (flow and options) before sending them again. Range: 1 to 3600 minutes. The default is 30 minutes.  <b>Note</b> This applies to the <b>export template timeout-rate minutes</b> command.
<b>options</b>	(Optional) Enables the <b>export-stats</b> , <b>refresh-rate</b> , <b>sampler</b> and <b>timeout-rate</b> keywords for configuring Version 9 export options.
<b>export-stats</b>	(Optional) Enables the export of statistics including the total number of flows exported and the total number of packets exported.

<b>sampler</b>	(Optional) When Version 9 export is configured, this keyword enables the export of an option containing a random-sampler configuration, including the sampler ID, sampling mode, and sampling interval for each configured random sampler.  <b>Note</b> You must have a flow sampler map configured before you can configure the sampler keyword for the <b>export template options</b> command.
<b>refresh-rate</b> <i>packets</i>	(Optional) Specifies the number of packets that are sent before the configured options records are resent. Range: 1 to 600 packets. The default is 20 packets.  <b>Note</b> This applies to the <b>export template options refresh-rate</b> <i>packets</i> command.
<b>timeout-rate</b> <i>minutes</i>	(Optional) Specifies the interval (in minutes) that the router will wait after sending the options records before they are sent again. Range: 1 to 3600 minutes. The default is 30 minutes.  <b>Note</b> This applies to the <b>export template options timeout-rate</b> <i>minutes</i> command.

**Command Default**

The default parameters as noted in the Syntax Description table are used.

**Command Modes**

NetFlow aggregation cache configuration (config-flow-cache)

**Command History**

<b>Release</b>	<b>Modification</b>
12.3(2)T	This command was introduced.
12.2(27)SBC	This command was integrated into Cisco IOS Release 12.2(27)SBC.
12.2(18)SXF	This command was integrated into Cisco IOS Release 12.2(18)SXF.
12.2(33)SRA	This command was integrated into Cisco IOS Release 12.2(33)SRA.

**Usage Guidelines**

The **export template options export-stats** command requires that the NetFlow Version 9 export format be already configured on the router.

The **export template options sampler** command requires that the NetFlow Version 9 export format and a flow sampler map be already configured on the router.

**Examples**

The following example shows how to configure a NetFlow accounting protocol-port aggregation cache so that the networking device sends the export statistics (total flows and packets exported) as options data:

```
Router(config)#
ip flow-aggregation cache protocol-port
Router(config-flow-cache)# export template options export-stats
Router(config-flow-cache)# enabled
```

The following example shows how to configure a NetFlow accounting protocol-port aggregation cache to wait until 100 export packets have been sent, or 60 minutes have passed since the last time the templates were sent (whichever comes first) before the templates are resent to the destination host:

```
Router(config)#
ip flow-aggregation cache protocol-port
Router(config-flow-cache)# export template refresh-rate 100
Router(config-flow-cache)# export template timeout-rate 60
Router(config-flow-cache)# enabled
```

The following example shows how to configure a NetFlow accounting protocol-port aggregation cache to enable the export of information about NetFlow random samplers:

```
Router(config)#
ip flow-aggregation cache protocol-port
Router(config-flow-cache)# export template option sampler
Router(config-flow-cache)# enabled
```



**Tip**

You must have a **flow-sampler** map configured before you can configure the sampler keyword for the **ip flow-export template options** command.

**Related Commands**

Command	Description
<b>export destination</b>	Enables the export of NetFlow accounting information in NetFlow aggregation cache entries to a remote device such as a server running an application that analyzes NetFlow data.
<b>export version</b>	Specifies the export version format for the exporting of NetFlow accounting information in NetFlow aggregation cache entries
<b>show ip flow export</b>	Displays the status and the statistics for NetFlow accounting data export.

## export version

To specify the version of the export format of NetFlow accounting information from NetFlow aggregation caches, use the **export version** command in NetFlow aggregation cache configuration mode. To return to the default behavior, use the **no** form of this command.

**export version** {8|9}

**no export version**

### Syntax Description

<b>version</b> {8 9}	Version of the format for NetFlow data export.
----------------------	--

### Command Default

Version 9 is the default format for the exporting of NetFlow accounting information from NetFlow aggregation caches.

### Command Modes

NetFlow aggregation cache configuration (config-flow-cache)

### Command History

Release	Modification
12.0(3)T	This command was introduced.
12.4(4)T	The <b>sctp</b> keyword was added.
12.2(33)SRA	This command was integrated into Cisco IOS Release 12.2(33)SRA.

### Usage Guidelines

NetFlow aggregation caches export data in UDP datagrams using either the Version 9 or Version 8 export format.

The table below describes how to determine the most appropriate export format for your requirements.

**Table 2: Selecting a NetFlow Export Format**

Export Format	Select When...
Version 9	<p>You need a flexible and extensible format, which provides the versatility needed for support of new fields and record types.</p> <p>This format accommodates new NetFlow-supported technologies such as Multicast, IPv6 NetFlow, Egress NetFlow, NetFlow Layer 2 and security exports, Multiprotocol Label Switching (MPLS), and Border Gateway Protocol (BGP) next hop.</p> <p>Version 9 export format enables you to use the same version for main and aggregation caches, and because the format is extensible you can use the same export format with future features.</p>
Version 8	<p>Version 8 export format is available only for export from aggregation caches.</p> <p>Use Version 8 when your NetFlow Collection Engine (NFC) does not support Version 9.</p>

The **export version** command supports two export data formats: Version 8, and Version 9. Version 8 should be used only when it is the only NetFlow data export format version that is supported by the application that you are using to analyze the exported NetFlow data. Version 9 is the only flexible export format version.

The NetFlow Version 9 Export Format feature was introduced in Cisco IOS Release 12.0(24)S and was integrated into Cisco IOS Release 12.3(1) and Cisco IOS Release 12.2(18)S.

NetFlow Version 9 is a flexible and extensible means for transferring NetFlow records from a network node to a collector. NetFlow Version 9 has definable record types and is self-describing for easier NetFlow Collection Engine configuration.

Third-party business partners who produce applications that provide NetFlow Collection Engine or display services for NetFlow do not need to recompile their applications each time a new NetFlow technology is added. Instead, with the NetFlow Version 9 Export Format feature, they can use an external data file that documents the known template formats and field types.

NetFlow Version 9 has the following characteristics:

- Record formats are defined by templates.
- Template descriptions are communicated from the router to the NetFlow Collection Engine.
- Flow records are sent from the router to the NetFlow Collection Engine with minimal template information so that the NetFlow Collection Engine can relate the records to the appropriate template.

Version 9 is independent of the underlying transport (UDP, TCP, SCTP, and so on).



**Note** In order for the BGP information to be populated in the main cache, you must have either a NetFlow export destination configured or a NetFlow aggregation configured.



**Note** The AS values for the **peer-as** and the **origin-as** keywords are captured only if you have configured an export destination with the **ip flow-export destination** command.



**Note** The AS values for the **peer-as** and the **origin-as** keywords are captured only if you have configured an export destination with the **ip flow-export destination** command.

For more information on the available export data formats, see the *Cisco IOS NetFlow Configuration Guide*, Release 12.4T. For more information on the Version 9 data format, see the [Cisco IOS NetFlow Version 9 Export Format Feature Guide](#).

## Examples

The following example shows how to configure version 9 as the export format for a NetFlow accounting protocol-port aggregation cache scheme:

```
Router(config)#
ip flow-aggregation cache protocol-port
Router(config-flow-cache)# export version 9
Router(config-flow-cache)# enabled
```

## Related Commands

Command	Description
<b>export destination</b>	Enables the export of NetFlow accounting information in NetFlow aggregation cache entries to a remote device such as a server running an application that analyzes NetFlow data.
<b>export template</b>	Configures template options for the export of NetFlow accounting information in NetFlow aggregation cache entries
<b>show ip flow export</b>	Displays the status and the statistics for NetFlow accounting data export.



# flow hardware mpls-vpn ip

To ensure the creation and export of hardware NetFlow cache entries for traffic entering the router on the last MPLS hop of an IPv4 MPLS VPN network, use the flow **hardware mpls-vpn ip** command in global configuration mode. To disable the creation and export of hardware NetFlow cache entries for this traffic, use the **no** form of this command.

**flow hardware mpls-vpn ip** *vrf-id*  
**no flow hardware mpls-vpn ip** *vrf-id*

### Syntax Description

<i>vrf-id</i>	The name of a VRF that you have previously configured.
---------------	--

### Command Default

Creation and export of hardware NetFlow cache entries for traffic entering the router on the last MPLS hop of an IPv4 MPLS VPN network is not enabled.

### Command Modes

Global configuration

### Command History

Release	Modification
12.2(33)SRB	This command was introduced.
12.2SX	This command is supported in the Cisco IOS Release 12.2SX train. Support in a specific 12.2SX release of this train depends on your feature set, platform, and platform hardware.

### Usage Guidelines

#### NetFlow Aggregation

If you want to include IPV4 MPLS VPN traffic in a NetFlow aggregation scheme on your router, you must configure the **flow hardware mpls-vpn ip** command.

#### NetFlow Sampling

If you want to include IPV4 MPLS VPN traffic in the traffic that is analyzed using NetFlow sampling on your router, you must configure the **flow hardware mpls-vpn ip** command.

### Examples

The following example configures NDE for VRF vpn1:

```
Router(config)# flow hardware mpls-vpn ip vpn1
```

**Related Commands**

Command	Description
show mls netflow ip	Displays information about the hardware NetFlow IP flows.

# flow-sampler

To apply a flow sampler map for random sampled NetFlow accounting to an interface, use the **flow-sampler** command in interface configuration mode. To remove a flow sampler map for random sampled NetFlow accounting from an interface, use the **no** form of this command.

**flow-sampler** *sampler-map-name* [egress]

**no flow-sampler** *sampler-map-name* [egress]

## Syntax Description

<i>sampler-map-name</i>	Name of the flow sampler map to apply to the interface.
<b>egress</b>	(Optional) Specifies that the sampler map is to be applied to egress traffic.

## Command Default

Flow sampler maps for NetFlow accounting are not applied to interfaces by default.

## Command Modes

Interface configuration Subinterface configuration

## Command History

Release	Modification
12.3(2)T	This command was introduced.
12.2(18)S	This command was integrated into Cisco IOS Release 12.2(18)S.
12.0(26)S	This command was integrated into Cisco IOS Release 12.0(26)S.
12.3(11)T	NetFlow egress support was added.
12.2(27)SBC	This command was integrated into Cisco IOS Release 12.2(27)SBC.
12.2(18)SXF	This command was integrated into Cisco IOS Release 12.2(18)SXF.
12.2(33)SRA	This command was integrated into Cisco IOS Release 12.2(33)SRA.

## Usage Guidelines

You must create and enable the random sampler NetFlow map for random sampled NetFlow accounting using the **flow-sampler-map** and **mode** commands before you can use the **flow-sampler** command to apply the random sampler NetFlow map to an interface.

Random sampled NetFlow accounting cannot be run concurrently with (ingress) NetFlow accounting, egress NetFlow accounting, or NetFlow accounting with input filter sampling on the same interface, or subinterface.

You must disable ingress NetFlow accounting, egress NetFlow accounting, or NetFlow accounting with input filter sampling on the interface, or subinterface, if you want to enable random sampled NetFlow accounting on the interface, or subinterface.

You must enable either Cisco Express Forwarding (CEF) or distributed CEF (dCEF) before using this command.

**Tip**

If you disable CEF or DCEF globally using the **no ip cef [distributed]** command the **flow-sampler sampler-map-name** command is removed from any interfaces that you previously configured for random sampled NetFlow accounting. You must reenter the **flow-sampler sampler-map-name** command after you reenable CEF or dCEF to reactivate random sampled NetFlow accounting.

**Tip**

If your router is running Cisco IOS release 12.2(14)S or a later release, or Cisco IOS Release 12.2(15)T or a later release, NetFlow accounting might be enabled through the use of the **ip flow ingress** command instead of the **ip route-cache flow** command. If your router has NetFlow accounting enabled through the use of **ip flow ingress** command you must disable NetFlow accounting, using the **no** form of this command, before you apply a random sampler map for random sampled NetFlow accounting on an interface otherwise the full, un-sampled traffic will continue to be seen.

**Examples**

The following example shows how to create and enable a random sampler map for random sampled (ingress) NetFlow accounting with CEF switching on Ethernet interface 0/0:

```
Router(config)# ip cef
Router(config)# flow-sampler-map my-map
Router(config-sampler)# mode random one-out-of 100
Router(config-sampler)# interface ethernet 0/0
Router(config-if)# no ip route-cache flow
Router(config-if)# ip
route-cache cef
Router(config-if)# flow-sampler my-map
```

The following example shows how to create and enable a random sampler map for random sampled egress NetFlow accounting with CEF switching on Ethernet interface 1/0:

```
Router(config)# ip cef
Router(config)# flow-sampler-map my-map
Router(config-sampler)# mode random one-out-of 100
Router(config-sampler)# interface ethernet 1/0
Router(config-if)# no
ip flow egress
Router(config-if)# ip
route-cache cef
Router(config-if)# flow-sampler my-map egress
```

The following output from the **show flow-sampler** command verifies that random sampled NetFlow accounting is active:

```
Router# show flow-sampler

Sampler : my-map, id : 1, packets matched : 7, mode : random sampling mode
sampling interval is : 100
```

**Related Commands**

<b>Command</b>	<b>Description</b>
<b>flow-sampler-map</b>	Defines a flow sampler map for random sampled NetFlow accounting.
<b>mode (flow sampler configuration)</b>	Specifies a packet interval for NetFlow accounting random sampling mode and enables the flow sampler map.
<b>netflow-sampler</b>	Enables NetFlow accounting with input filter sampling.
<b>show flow-sampler</b>	Displays the status of random sampled NetFlow (including mode, packet interval, and number of packets matched for each flow sampler).
<b>show ip cache flow</b>	Displays a summary of the NetFlow accounting statistics.
<b>show ip cache verbose flow</b>	Displays a detailed summary of the NetFlow accounting statistics.
<b>show ip flow interface</b>	Displays NetFlow accounting configuration for interfaces.

# flow-sampler-map

To define a flow sampler map for random sampled NetFlow accounting, use the **flow-sampler-map** command in global configuration mode. To remove a flow sampler map for random sampled NetFlow accounting, use the **no** form of this command.

**flow-sampler-map** *sampler-map-name*

**no flow-sampler-map** *sampler-map-name*

## Syntax Description

<i>sampler-map-name</i>	Name of the flow sampler map to be defined for random sampled NetFlow accounting.
-------------------------	---

## Command Default

No flow sampler maps for random sampled NetFlow accounting are defined.

## Command Modes

Global configuration

## Command History

Release	Modification
12.3(2)T	This command was introduced.
12.2(18)S	This command was integrated into Cisco IOS Release 12.2(18)S.
12.0(26)S	This command was integrated into Cisco IOS Release 12.0(26)S.
12.2(27)SBC	This command was integrated into Cisco IOS Release 12.2(27)SBC.
12.2(18)SXF	This command was integrated into Cisco IOS Release 12.2(18)SXF.
12.2(33)SRA	This command was integrated into Cisco IOS Release 12.2(33)SRA.

## Usage Guidelines

Random sampled NetFlow accounting does not start sampling traffic until (1) the random sampler map is activated through the use of the **mode** command and (2) the sampler map has been applied to an interface through the use of the **flow-sampler** command.

Random Sampled NetFlow accounting cannot be run concurrently with (ingress) NetFlow accounting, egress NetFlow accounting, or NetFlow accounting with input filter sampling on the same interface, or subinterface. You must disable (ingress) NetFlow accounting, egress NetFlow accounting, or NetFlow accounting with input filter sampling on the interface or subinterface, if you want to enable random sampled NetFlow accounting on that interface or subinterface.

You must enable either Cisco Express Forwarding (CEF) or distributed CEF (dCEF) before using this command.



**Tip**

If you disable dCEF globally using the **no ip cef [distributed]** command, the **flow-sampler sampler-map-name** command is removed from any interfaces that you previously configured for random sampled NetFlow accounting. You must reenter the **flow-sampler sampler-map-name** command after you reenables CEF or dCEF to reactivate random sampled NetFlow accounting.



**Tip**

If your router is running Cisco IOS release 12.2(14)S or a later release, or Cisco IOS Release 12.2(15)T or a later release, NetFlow accounting might be enabled through the use of the **ip flow ingress** command instead of the **ip route-cache flow** command. If your router has NetFlow accounting enabled through the use of **ip flow ingress** command you must disable NetFlow accounting, using the **no** form of this command, before you apply a random sampler map for random sampled NetFlow accounting on an interface otherwise the full, un-sampled traffic will continue to be seen.

**Examples**

The following example shows how to create and enable a random sampler map for random sampled (ingress) NetFlow accounting with CEF switching on Ethernet interface 0/0:

```
Router(config)# ip cef
Router(config)# flow-sampler-map my-map
Router(config-sampler)# mode random one-out-of 100
Router(config-sampler)# interface ethernet 0/0
Router(config-if)# no ip route-cache flow
Router(config-if)# ip
    route-cache cef
Router(config-if)# flow-sampler my-map
```

The following example shows how to create and enable a random sampler map for random sampled egress NetFlow accounting with CEF switching on Ethernet interface 1/0:

```
Router(config)# ip cef
Router(config)# flow-sampler-map my-map
Router(config-sampler)# mode random one-out-of 100
Router(config-sampler)# interface ethernet 1/0
Router(config-if)# no
    ip flow egress
Router(config-if)# ip
    route-cache cef
Router(config-if)# flow-sampler my-map egress
```

The following output from the **show flow-sampler** command verifies that random sampled NetFlow accounting is active:

```
Router# show flow-sampler

Sampler : my-map, id : 1, packets matched : 7, mode : random sampling mode
sampling interval is : 100
```

**Related Commands**

Command	Description
<b>flow-sampler-map</b>	Defines a flow sampler map for random sampled NetFlow accounting.

Command	Description
<b>mode (flow sampler configuration)</b>	Specifies a packet interval for NetFlow accounting random sampling mode and enables the flow sampler map.
<b>netflow-sampler</b>	Enables NetFlow accounting with input filter sampling.
<b>show flow-sampler</b>	Displays the status of random sampled NetFlow (including mode, packet interval, and number of packets matched for each flow sampler).
<b>show ip cache flow</b>	Displays a summary of the NetFlow accounting statistics.
<b>show ip cache verbose flow</b>	Displays a detailed summary of the NetFlow accounting statistics.
<b>show ip flow interface</b>	Displays NetFlow accounting configuration for interfaces.



# ip flow

To enable NetFlow accounting for inbound (received) or outbound (transmitted) network traffic, use the **ip flow** command in interface or subinterface configuration mode. To disable NetFlow accounting, use the **no** form of this command.

```
ip flow {ingress| egress}
no ip flow {ingress| egress}
```

## Syntax Description

<b>ingress</b>	Enables NetFlow accounting for traffic that is received on an interface.  <b>Note</b> This is also known as ingress NetFlow accounting.
<b>egress</b>	Enables NetFlow accounting for traffic that is transmitted on an interface.  <b>Note</b> This is also known as egress NetFlow accounting.

## Command Default

NetFlow accounting is disabled.

## Command Modes

Interface configuration (config-if) Subinterface configuration (config-sub-if)

## Command History

Release	Modification
12.2(14)S	This command was introduced.
12.2(25)S	Output of the <b>show running configuration</b> command was modified so that the <b>ip route-cache flow</b> command as well as the <b>ip flow ingress</b> command will appear when either command is configured.
12.2(15)T	This command was integrated into Cisco IOS Release 12.2(15)T.
12.3(11)T	The egress keyword was added.
12.2(28)SBB	This command was integrated into Cisco IOS Release 12.2(27)SBB and implemented for the Cisco 10000 series routers.
12.2(27)SBC	This command was integrated into Cisco IOS Release 12.2(27)SBC.
12.2(31)SB2	This command was integrated into Cisco IOS Release 12.2(31)SB2.
12.2(18)SXE	Support for this command was introduced on the Supervisor Engine 720.

Release	Modification
12.2(18)SXF	This command was integrated into Cisco IOS Release 12.2(18)SXF. This command was changed to allow you to dynamically create NetFlow entries on a 7600.
12.2(33)SRA	This command was integrated into Cisco IOS Release 12.2(33)SRA.

## Usage Guidelines

### Cisco 7600 Series Platforms

The **ip flow ingress** command is supported on the Supervisor Engine 720 in PFC3B and PFC3BXL mode.

The **ip flow ingress** command is supported on the Supervisor Engine 2 with a PFC2.

In Release 12.2(18)SXF and later releases, to create a NetFlow entry, you need to enter the **ip flow ingress** command. In releases prior to Release 12.2(18)SXF, the NetFlow entries are created automatically.

### Other Platforms

Use this command on an interface or subinterface to enable NetFlow accounting for traffic.

You must enable CEF or dCEF globally on the networking device, and on the interface or subinterface that you want to enable NetFlow accounting on before you enable either ingress or egress NetFlow accounting.

## Examples

The following example shows how to configure ingress NetFlow accounting for traffic that is received on FastEthernet interface 0/0:

```
Router(config)# interface fastethernet0/0
Router(config-if)# ip flow ingress
```

The following example shows how to configure egress NetFlow accounting for traffic that is transmitted on FastEthernet interface 0/0:

```
Router(config)# interface fastethernet0/0
Router(config-if)# ip flow egress
```

## Related Commands

Command	Description
<b>ip flow-egress input-interface</b>	Removes the NetFlow egress accounting flow key that specifies an output interface and adds a flow key that specifies an input interface for NetFlow egress accounting.
<b>ip flow-cache timeout</b>	Specifies NetFlow accounting flow cache parameters
<b>ip flow-cache entries</b>	Changes the number of entries maintained in the NetFlow accounting cache.
<b>show ip cache flow</b>	Displays a summary of the NetFlow accounting statistics.

Command	Description
<b>show ip cache verbose flow</b>	Displays a detailed summary of the NetFlow accounting statistics.
<b>show ip flow interface</b>	Displays NetFlow accounting configuration for interfaces.

## ip flow layer2-switched

To enable the creation of switched, bridged, and Layer 2 IP flows for a specific VLAN, use the **ip flow layer2-switched** command in global configuration mode. Use the **no** form of this command to return to the default settings.

**ip flow {ingress| export} layer2-switched vlan {num| vlanlist}**

**no ip flow {ingress| export} layer2-switched vlan {num| vlanlist}**

### Syntax Description

<b>ingress</b>	Enables the collection of switched, bridged, and IP flows in Layer 2.
<b>export</b>	Enables the export of switched, bridged, and IP flows in Layer 2.
<b>vlan</b> <i>num</i>   <i>vlanlist</i>	Specifies the VLAN or range of VLANs; valid values are from 1 to 4094. See the “Usage Guidelines” section for additional information.

### Command Default

The defaults are as follows:

- **ip flow ingress layer2switch** is disabled.
- **ip flow export layer2switched** is enabled.

### Command Modes

Global configuration (config)

### Command History

Release	Modification
12.2(18)SXE	Support for this command was introduced on the Supervisor Engine 720.
12.2(33)SRA	This command was integrated into Cisco IOS Release 12.2(33)SRA.
12.2SX	This command is supported in the Cisco IOS Release 12.2SX train. Support in a specific 12.2SX release of this train depends on your feature set, platform, and platform hardware.

### Usage Guidelines

The **ip flow layer2-switched** command is supported on the Supervisor Engine 720 in PFC3B and PFC3BXL mode only.

The **ip flow layer2-switched** command is supported on the Supervisor Engine 2 with a PFC2.

Before using this command on Cisco 7600 series routers that are configured with a Supervisor Engine 720, you must ensure that a corresponding VLAN interface is available and has a valid IP address. This guideline does not apply to Cisco 7600 series routers that are configured with a Supervisor Engine 2.

You can enter one or multiple VLANs. The following examples are samples of valid VLAN lists: 1; 1,2,3; 1-3,7.

## Examples

This example shows how to enable the collection of Layer 2-switched flows on a specific VLAN:

```
Router(config)# ip flow ingress layer2-switched vlan 2
Router(config)#
```

This example shows how to enable export of Layer 2-switched flows on a range of VLANs:

```
Router(config)# ip flow export layer2-switched vlan 1-3,7
Router(config)#
```

This example shows how to disable the collection of Layer 2-switched flows on a specific VLAN:

```
Router(config)# no ip flow ingress layer2-switched vlan 2
Router(config)#
```

## ip flow-aggregation cache

To enable NetFlow accounting aggregation cache schemes, use the **ip flow-aggregation cache** command in global configuration mode. To disable NetFlow accounting aggregation cache schemes, use the **no** form of this command.

**ip flow-aggregation cache** {as| as-tos| bgp-nexthop-tos| destination-prefix| destination-prefix-tos| prefix| prefix-port| prefix-tos| protocol-port| protocol-port-tos| source-prefix| source-prefix-tos| exp-bgp-prefix}

**no ip flow-aggregation cache** {as| as-tos| bgp-nexthop-tos| destination-prefix| destination-prefix-tos| prefix| prefix-port| prefix-tos| protocol-port| protocol-port-tos| source-prefix| source-prefix-tos| exp-bgp-prefix}

### Syntax Description

<b>as</b>	Configures the autonomous system aggregation cache scheme.
<b>as-tos</b>	Configures the autonomous system type of service (ToS) aggregation cache scheme.
<b>bgp-nexthop-tos</b>	Configures the Border Gateway Protocol (BGP) next hop ToS aggregation cache scheme. <b>Note</b> This keyword is not supported on the Cisco ASR 1000 Series Aggregation Services Router.
<b>destination-prefix</b>	Configures the destination-prefix aggregation cache scheme.
<b>destination-prefix-tos</b>	Configures the destination prefix ToS aggregation cache scheme.
<b>prefix</b>	Configures the prefix aggregation cache scheme.
<b>prefix-port</b>	Configures the prefix port aggregation cache scheme.
<b>prefix-tos</b>	Configures the prefix ToS aggregation cache scheme.
<b>protocol-port</b>	Configures the protocol-port aggregation cache scheme.
<b>protocol-port-tos</b>	Configures the protocol-port ToS aggregation cache scheme.
<b>source-prefix</b>	Configures the source-prefix aggregation cache scheme.
<b>source-prefix-tos</b>	Configures the source-prefix ToS aggregation cache scheme.

<b>exp-bgp-prefix</b>	Configures the exp-bgp-prefix aggregation cache scheme.
-----------------------	---

**Command Default** This command is not enabled by default.

**Command Modes** Global configuration

<b>Release</b>	<b>Modification</b>
12.0(3)T	This command was introduced.
12.0(15)S	This command was modified to include the ToS aggregation scheme keywords.
12.2(2)T	This command was modified to enable multiple NetFlow export destinations.
12.2(14)S	This command was integrated into Cisco IOS Release 12.2(14)S.
12.3(1)	Support for the BGP Next Hop Support feature was added.
12.2(18)S	Support for the BGP Next Hop Support feature was added.
12.2(14)SX	Support for this command was introduced on the Supervisor Engine 720.
12.2(17d)SXB	Support for this command on the Supervisor Engine 2 was extended to Release 12.2(17d)SXB.
12.2(27)SBC	This command was integrated into Cisco IOS Release 12.2(27)SBC.
12.2(18)SXF	This command was integrated into Cisco IOS Release 12.2(18)SXF.
12.2(33)SRA	This command was integrated into Cisco IOS Release 12.2(33)SRA.
12.2(31)SB2	This command was integrated into Cisco IOS Release 12.2(31)SB2. The <b>exp-bgp-prefix</b> aggregation cache keyword was added.

**Usage Guidelines** You must have NetFlow accounting configured on your router before you can use this command. The **export destination** command supports a maximum of two concurrent export destinations.

The ToS aggregation cache scheme keywords enable NetFlow accounting aggregation cache schemes that include the ToS byte in their export records. The ToS byte is an 8-bit field in the IP header. The ToS byte specifies the quality of service for a datagram during its transmission through the Internet.

You can enable only one aggregation cache configuration scheme per command line. The following rules apply to configuring source and destination masks.

- The source mask can only be configured in the prefix, prefix-port, prefix-tos, source-prefix and source-prefix-tos aggregation modes.
- The destination mask can only be configured in the prefix, prefix-port, prefix-tos, destination-prefix and destination-prefix-tos aggregation modes.
- No masks can be configured in non-prefix aggregation modes

To enable aggregation (whether or not an aggregation cache is fully configured), you must enter the **enabled** command in aggregation cache configuration mode. (You can use the **no** form of this command to disable aggregation. The cache configuration remains unchanged even if aggregation is disabled.)

## Examples

The following example shows how to configure a NetFlow accounting autonomous system aggregation cache scheme:

```
Router(config)# ip flow-aggregation cache as
Router(config-flow-cache)# enabled
```

The following example shows how to configure a minimum prefix mask of 16 bits for the NetFlow accounting destination-prefix aggregation cache scheme:

```
Router(config)# ip flow-aggregation cache destination-prefix
Router(config-flow-cache)# mask destination minimum 16
Router(config-flow-cache)# enabled
```

The following example shows how to configure a minimum prefix mask of 16 bits for the NetFlow accounting source-prefix aggregation cache scheme:

```
Router(config)# ip flow-aggregation cache source-prefix
Router(config-flow-cache)# mask source minimum 16
Router(config-flow-cache)# enabled
```

The following example shows how to configure multiple export destinations for the NetFlow accounting autonomous system ToS aggregation cache scheme:

```
Router(config)# ip flow-aggregation cache as-tos
Router(config-flow-cache)# export destination 172.17.24.65 9991
Router(config-flow-cache)# export destination 172.16.10.2 9991
Router(config-flow-cache)# enabled
```

## Related Commands

Command	Description
<b>export destination (aggregation cache)</b>	Enables the exporting of NetFlow accounting information from NetFlow aggregation caches.
<b>enabled (aggregation cache)</b>	Enables the NetFlow aggregation cache.
<b>mask</b>	Specifies the source or destination prefix mask.
<b>show ip cache flow aggregation</b>	Displays a summary of the NetFlow accounting aggregation cache statistics.
<b>show ip cache flow</b>	Displays a summary of the NetFlow accounting statistics.



Command	Description
<b>show ip cache verbose flow</b>	Displays a detailed summary of the NetFlow accounting statistics.
<b>show ip flow interface</b>	Displays NetFlow accounting configuration for interfaces.

## ip flow-cache entries

To change the number of entries maintained in the NetFlow accounting cache, use the **ip flow-cache entries** command in global configuration mode. To return to the default number of entries, use the **no** form of this command.

**ip flow-cache entries** *number*

**no ip flow-cache entries**

### Syntax Description

<i>number</i>	<p>Number of entries to maintain in the NetFlow cache. The range is from 1024 to 524288. The default is 4096.</p> <p><b>Note</b> For the Cisco ASR 1000 Series Aggregation Services Router, the range is 1024 to 2000000 (2 million). The default is 200000.</p>
---------------	--

### Command Default

The default value of 4096 is used as the size of the NetFlow accounting cache.

### Command Modes

Global configuration (config)

### Command History

Release	Modification
12.0(3)T	This command was introduced.
12.2(14)S	This command was integrated into Cisco IOS Release 12.2(14)S.
12.2(14)SX	Support for this command was introduced on the Supervisor Engine 720.
12.2(17d)SXB	Support for this command on the Supervisor Engine 2 was extended to Release 12.2(17d)SXB.
12.2(27)SBC	This command was integrated into Cisco IOS Release 12.2(27)SBC.
12.2(18)SXF	This command was integrated into Cisco IOS Release 12.2(18)SXF.
12.2(33)SRA	This command was integrated into Cisco IOS Release 12.2(33)SRA.
12.2(31)SB2	This command was integrated into Cisco IOS Release 12.2(31)SB2.

### Usage Guidelines

You must have NetFlow accounting configured on your router before you can use this command.

Normally the default size of the NetFlow cache will meet your needs. However, you can increase or decrease the number of entries maintained in the cache to meet the needs of your flow traffic rates. For environments with a high amount of flow traffic (such as an internet core router), a larger value such as 131072 (128K) is recommended. To obtain information on your flow traffic, use the **show ip cache flow EXEC** command.

Each cache entry is approximately 64 bytes of storage. Assuming a cache with the default number of entries, approximately 4 MB of DRAM would be required. Each time a new flow is taken from the free flow queue, the number of free flows is checked. If only a few free flows remain, NetFlow attempts to age 30 flows using an accelerated timeout. If only one free flow remains, NetFlow automatically ages 30 flows regardless of their age. The intent is to ensure that free flow entries are always available.



**Caution**

We recommend that you not change the number of NetFlow cache entries. To return to the default number of NetFlow cache entries, use the **no ip flow-cache entries** global configuration command.

**Examples**

The following example shows how to increase the number of NetFlow cache entries to 131,072 (128K):

```
Router(config)# ip flow-cache entries 131072
%The change in number of entries will take effect after either the next reboot or when
netflow is turned off on all interfaces
```



**Tip**

You turn off NetFlow accounting on interfaces by removing the command that you enabled NetFlow accounting with. For example, if you enabled NetFlow accounting on an interface with the **ip flow ingress** command you turn off NetFlow accounting for the interface using the **no** form of the command **-no ip flow ingress**. Remember to turn NetFlow accounting back on for the interface after you have turned it off.

**Related Commands**

Command	Description
<b>ip flow-cache timeout</b>	Specifies NetFlow accounting flow cache parameters.
<b>ip flow egress</b>	Enables NetFlow egress accounting for traffic that the router is forwarding.
<b>ip flow-egress input-interface</b>	Removes the NetFlow egress accounting flow key that specifies an output interface and adds a flow key that specifies an input interface for NetFlow egress accounting.
<b>ip flow ingress</b>	Enables NetFlow (ingress) accounting for traffic arriving on an interface.
<b>show ip cache flow</b>	Displays a summary of the NetFlow accounting statistics.
<b>show ip cache verbose flow</b>	Displays a detailed summary of the NetFlow accounting statistics.

Command	Description
<b>show ip flow interface</b>	Displays NetFlow accounting configuration for interfaces.

# ip flow-cache mpls label-positions

To enable Multiprotocol Label Switching (MPLS)-Aware NetFlow, use the **ip flow-cache mpls label-positions** command in global configuration mode. To disable MPLS-aware NetFlow, use the **no** form of this command.

**ip flow-cache mpls label-positions** [*label-position-1*] [*label-position-2*] [*label-position-3*]]  
**[exp-bgp-prefix-fields] [no-ip-fields] [mpls-length]**

**no ip flow-cache mpls label-positions**

## Syntax Description

<i>label-position-1</i>	(Optional) Position of an MPLS label in the incoming label stack. Label positions are counted from the top of the stack, starting with 1.
<b>exp-bgp-prefix-fields</b>	<p>(Optional) Generates a MPLS Provider Edge (PE) PE-to-PE traffic matrix.</p> <p>The following IP-related flow fields are included:</p> <ul style="list-style-type: none"> <li>• Input interface</li> <li>• BGP Nexthop</li> <li>• MPLS Experimental (EXP) bits</li> </ul> <p>The MPLS label values will be set to zero on the Cisco 10000 in the display output of the <b>show ip cache verbose flow aggregation exp-bgp-prefix</b> command.</p>
<b>no-ip-fields</b>	<p>(Optional) Controls the capture and reporting of MPLS flow fields. If the <b>no-ip-fields</b> keyword is not specified, the following IP-related flow fields are included:</p> <ul style="list-style-type: none"> <li>• Source IP address</li> <li>• Destination IP address</li> <li>• Transport layer protocol</li> <li>• Source application port number</li> <li>• Destination application port number</li> <li>• IP type of service (ToS)</li> <li>• TCP flag</li> </ul> <p>If the <b>no-ip-fields</b> keyword is specified, the IP-related fields are reported with a value of 0.</p>

<b>mpls-length</b>	(Optional) Controls the reporting of packet length. If the <b>mpls-length</b> keyword is specified, the reported length represents the sum of the MPLS packet payload length and the MPLS label stack length. If the <b>mpls-length</b> keyword is not specified, only the length of the MPLS packet payload is reported.
--------------------	---

**Command Default** MPLS-Aware NetFlow is not enabled.

**Command Modes** Global configuration (config)

<b>Command History</b>	<b>Release</b>	<b>Modification</b>
	12.0(24)S	This command was introduced.
	12.0(25)S	The <b>no-ip-fields</b> and <b>mpls-length</b> keywords were added.
	12.3(8)T	This command was integrated into Cisco IOS Release 12.3(8)T.
	12.2(28)SB	This command was integrated into Cisco IOS Release 12.2(28)SB.
	12.2(31)SB2	This command was integrated into Cisco IOS Release 12.2(31)SB2. The <b>exp-bgp-prefix-fields</b> keyword was added.

**Usage Guidelines** You must have NetFlow accounting configured on your router before you can use this command.

Use this command to configure the MPLS-aware NetFlow feature on a label switch router (LSR) and to specify labels of interest in the incoming label stack. Label positions are counted from the top of the stack, starting with 1. The position of the top label is 1, the position of the second label is 2, and so forth.

With MPLS-aware NetFlow enabled on the router, NetFlow collects data for incoming IP packets and for incoming MPLS packets on all interfaces where NetFlow is enabled in full or in sampled mode.

**Caution**

When you enter the **ip flow-cache mpls label-positions** command on a Cisco 12000 series Internet router, NetFlow will stop collecting data for incoming IP packets on any Engine 4P line cards installed in the router on which NetFlow is enabled in full or in sampled mode. Engine 4P line cards in a Cisco 12000 series Internet router do not support NetFlow data collection of incoming IP packets and MPLS packets concurrently.

**Tip**

MPLS-aware NetFlow is enabled in global configuration mode. NetFlow is enabled per interface.

**Examples**

The following example shows how to configure MPLS-aware NetFlow to capture the first (top), third, and fifth label:

```
Router(config)# ip flow-cache mpls label-positions 1 3 5
```

The following example shows how to configure MPLS-aware NetFlow to capture only MPLS flow information (no IP-related flow fields) and the length that represents the sum of the MPLS packet payload length and the MPLS label stack length:

```
Router(config)# ip flow-cache mpls label-positions no-ip-fields mpls-length
```

The following example shows how to configure MPLS PE-to-PE Traffic Statistics for Netflow:

```
Router(config)# ip flow-cache mpls label-positions 1 2 exp-bgp-prefix-fields
```

**Related Commands**

Command	Description
<b>ip flow-cache entries</b>	Changes the number of entries maintained in the NetFlow accounting cache.
<b>ip flow-cache timeout</b>	Specifies NetFlow accounting flow cache parameters.
<b>ip flow egress</b>	Enables NetFlow egress accounting for traffic that the router is forwarding.
<b>ip flow-egress input-interface</b>	Removes the NetFlow egress accounting flow key that specifies an output interface and adds a flow key that specifies an input interface for NetFlow egress accounting.
<b>ip flow ingress</b>	Enables NetFlow (ingress) accounting for traffic arriving on an interface.
<b>show ip cache flow</b>	Displays a summary of the NetFlow accounting statistics.
<b>show ip cache verbose flow</b>	Displays a detailed summary of the NetFlow accounting statistics.
<b>show ip flow interface</b>	Displays NetFlow accounting configuration for interfaces.

## ip flow-cache timeout

To specify NetFlow accounting flow cache parameters, use the **ip flow-cache timeout** command in global configuration mode. To disable the flow cache parameters, use the **no** form of this command.

**ip flow-cache timeout** [**active** *minutes*] **inactive** *seconds*]

**no ip flow-cache timeout** [**active**] **inactive**]

### Syntax Description

<b>active</b>	Specifies the active flow timeout.
<i>minutes</i>	(Optional) The number of minutes that an active flow remains in the cache before it times out. The range is from 1 to 60. The default value is 30.
<b>inactive</b>	Specifies the inactive flow timeout.
<i>seconds</i>	(Optional) The number of seconds that an inactive flow remains in the cache before it times out. The range is from 10 to 600. The default value is 15.

### Command Default

The flow-cache timeout values are set to the default values.

### Command Modes

Global configuration

### Command History

Release	Modification
12.3(7)T	This command was introduced.
12.2(14)S	This command was integrated into Cisco IOS Release 12.2(14)S.
12.2(27)SBC	This command was integrated into Cisco IOS Release 12.2(27)SBC.
12.2(18)SXF	This command was integrated into Cisco IOS Release 12.2(18)SXF.
12.2(33)SRA	This command was integrated into Cisco IOS Release 12.2(33)SRA.

### Usage Guidelines

You must have NetFlow accounting configured on your router before you can use this command.

Use this command to specify active and inactive timeout parameters.



A flow is considered to be active if packets belonging to the flow are detected wherever the NetFlow statistics are being collected. A flow is considered to be inactive if no further packets are detected for the flow at the collection point for NetFlow statistics.

### Examples

In the following example, an active flow is allowed to remain in the cache for 20 minutes:

```
Router(config)# ip flow-cache timeout active 20
```

In the following example, an inactive flow is allowed to remain in the cache for 10 seconds before it times out and is removed:

```
Router(config)# ip flow-cache timeout inactive 10
```

### Related Commands

Command	Description
<b>ip flow egress</b>	Enables NetFlow (egress) accounting for traffic that the router is forwarding.
<b>ip flow ingress</b>	Enables NetFlow (ingress) accounting for traffic arriving on an interface.
<b>ip flow-cache entries</b>	Changes the number of entries maintained in the NetFlow accounting cache.
<b>ip flow-egress input-interface</b>	Removes the NetFlow egress accounting flow key that specifies an output interface and adds a flow key that specifies an input interface for NetFlow egress accounting.
<b>show ip cache flow</b>	Displays a summary of the NetFlow accounting statistics.
<b>show ip cache verbose flow</b>	Displays a detailed summary of the NetFlow accounting statistics.
<b>show ip flow interface</b>	Displays NetFlow accounting configuration for interfaces.

## ip flow-capture

To enable the capture of values from Layer 2 or additional Layer 3 fields in NetFlow traffic, use the **ip flow-capture** command in global configuration mode. To disable capturing Layer 2 or Layer 3 fields from NetFlow traffic, use the **no** form of this command.

**ip flow-capture** {fragment-offset| icmp| ip-id| mac-addresses| packet-length| ttl| vlan-id| nbar}

**no ip flow-capture** {fragment-offset| icmp| ip-id| mac-addresses| packet-length| ttl| vlan-id| nbar}

### Syntax Description

<b>fragment-offset</b>	Captures the value of the 13-bit IP fragment offset field from the first fragmented IP datagram in a flow.
<b>icmp</b>	Captures the value of the ICMP type and code fields from the first ICMP datagram in a flow.
<b>ip-id</b>	Captures the value of the IP-ID field from the first IP datagram in a flow.
<b>mac-addresses</b>	Captures the values of the source MAC addresses from ingress packets and the destination MAC addresses from egress packets from the first packet in a flow.  <b>Note</b> This command applies only to traffic that is received or transmitted over Ethernet interfaces.
<b>packet-length</b>	Captures the value of the packet length field from IP datagrams in a flow.
<b>ttl</b>	Captures the value of the time-to-live (TTL) field from IP datagrams in a flow.
<b>vlan-id</b>	Captures the value of the 802.1q or Inter-Switch Link (ISL) VLAN-ID field from VLAN-encapsulated frames in a flow when the frames are received or transmitted on trunk ports.
<b>nbar</b>	Exports Network Based Application Recognition (NBAR) information along with the NetFlow Version 9 record.

### Command Default

Values from Layer 2 and Layer 3 fields are not captured.

### Command Modes

Global configuration (config)

**Command History**

Release	Modification
12.3(14)T	This command was introduced.
12.4(2)T	The <b>fragment-offset</b> keyword was added.
12.2(33)SRA	This command was integrated into Cisco IOS Release 12.2(33)SRA.
12.2(18)ZYA2	This command was modified. The <b>nbar</b> keyword was added.

**Usage Guidelines**

You must enable NetFlow accounting on an interface or a subinterface using the **ip flow {ingress | egress}** command for the **ip flow-capture** command to take effect. You can enable NetFlow accounting before or after you have entered the **ip flow-capture** command in global configuration mode.

If you want to export the information captured by the **ip flow-capture** command, you must configure NetFlow export using the **ip flow-export destination** command, and you must configure NetFlow to use the Version 9 export format. Use the **ip flow-export version 9** command to configure the NetFlow Version 9 export format.

The fields captured by the **ip flow-capture** command are currently not available in the NetFlow MIB.



**Note**

You can capture the value from only one field at a time. Execute the command once for each value you want to capture.

**ip flow-capture fragment-offset**

IP fragmentation occurs when the size of an IP datagram exceeds the maximum transmission unit (MTU) of the Layer 2 frame type used by the next-hop network. For example, the IP MTU size of an ATM network is 4470 bytes. When a host needs to transmit an IP datagram that exceeds 4470 bytes on an ATM network, it must first fragment the datagram into two or more smaller IP datagrams.

An IP datagram sent by a host system such as a web server can also be fragmented by a router in the network if the router needs to transmit the IP datagram on a next-hop network that has an MTU that is smaller than the current size of the IP datagram. For example, if a router receives a 4470-byte IP datagram on an ATM interface and the next-hop network is a 100-Mbps Fast Ethernet network with an MTU of 1514, the router must fragment the IP datagram into three smaller IP datagrams (4470/1514). It is possible for an IP datagram to be fragmented two or more times on its path from the sending host to the destination host.

A fragmented IP datagram is reassembled by the destination host. The last fragment of an IP datagram is identified when the “more fragments” flag is set to 0. The length of a complete IP datagram is calculated by the receiving host by means of the fragment offset field and the length of the last fragment.

The **ip flow-capture fragment-offset** command captures the value of the IP fragment offset field from the first fragmented IP packet in the flow. If you are seeing several flows with the same value for the IP fragment offset field, it is possible that your network is being attacked by a host that is sending the same IP packets again and again.

**ip flow-capture icmp**

Internet Control Message Protocol (ICMP) is used for several purposes. One of the most common is the ping command. ICMP echo requests are sent by a host to a destination to verify that the destination is reachable by IP. If the destination is reachable, it should respond by sending an ICMP echo reply. Refer to RFC 792, *Darpa Internet Program Protocol Specification* ( <http://www.ietf.org/rfc/rfc0792.txt?number=792> ) for more information on ICMP.

ICMP packets have been used in many types of attacks on networks. Two of the most common attacks are the denial-of-service (DoS) attack and the “ping of death” attack.

- DoS attack--Any action or actions that prevent any part of a system from functioning in accordance with its intended purpose. This includes any action that causes unauthorized delay of service. Generally, DoS attacks do not destroy data or resources, but prevent access or use. In network operations, flooding a device with ping packets when the device has not been configured to block or ignore them might effect a denial of service.
- “ping of death”--An attack that sends an improperly large ping echo request packet with the intent of overflowing the input buffers of the destination machine and causing it to crash.

Finding out the types of ICMP traffic in your network can help you decide if your network is being attacked by ICMP packets.

The **ip flow-capture icmp** command captures the value of the ICMP type field and the ICMP code field from the first ICMP packet detected in a flow.

#### **ip flow-capture ip-id**

It is possible for a host to receive IP datagrams from two or more senders concurrently. It is also possible for a host to receive multiple IP datagrams from the same host for different applications concurrently. For example, a server might be transferring email and HTTP traffic from the same host concurrently. When a host is receiving multiple IP datagrams concurrently, it must be able to identify the fragments from each of the incoming datagrams to ensure that they do not get mixed up during the datagram reassembly process. The receiving host uses the IP header identification field and the source IP address of the IP datagram fragment to ensure that it rebuilds the IP datagrams correctly.

The **ip flow-capture ip-id** command captures the value of the IP header identification field from the first packet in the flow. The value in the IP header identification field is a sequence number assigned by the host that originally transmitted the IP datagram. All of the fragments of an IP datagram have the same identifier value. This ensures that the destination host can match the IP datagram to the fragment during the IP datagram reassembly process. The sending host is responsible for ensuring that each subsequent IP datagram it sends to the same destination host has a unique value for the IP header identification field.

If you are seeing several flows with the same value for the IP header identification field, it is possible that your network is being attacked by a host that is sending the same IP packets again and again.

#### **ip flow-capture packet-length**

The value in the packet length field in an IP datagram indicates the length of the IP datagram, excluding the IP header.

Use the **ip flow-capture packet-length** command to capture the value of the IP header packet length field for packets in the flow. The **ip flow-capture packet-length** command keeps track of the minimum and maximum values captured from the flow. The minimum and maximum packet length values are stored in separate fields. This data is updated when a packet with a packet length that is lower or higher than the currently stored value is received. For example, if the currently stored value for the minimum packet length is 1024 bytes and the next packet received has a packet length of 512 bytes, the 1024 is replaced by 512.

If you are seeing several IP datagrams in the flow with the same value for the packet-length field, it is possible that your network is being attacked by a host that is constantly sending the same IP packets again and again.

### ip flow-capture ttl

The TTL field is used to prevent the indefinite forwarding of IP datagrams. The TTL field contains a counter value set by the source host. Each router that processes this datagram decreases the TTL value by 1. When the TTL value reaches 0, the datagram is discarded.

There are two scenarios where an IP packet without a TTL field could live indefinitely in a network:

- The first scenario occurs when a host sends an IP datagram to an IP network that does not exist and the routers in the network have a gateway of last resort configured—that is, a gateway to which they forward IP datagrams for unknown destinations. Each router in the network receives the datagram and attempts to determine the best interface to use to forward it. Because the destination network is unknown, the best interface for the router to use to forward the datagram to the next hop is always the interface to which the gateway of last resort is assigned.
- The second scenario occurs when a wrong configuration in the network results in a routing loop. For example, if one router forwards an IP datagram to another router because it appears to be the correct next-hop router, then the receiving router sends it back because it believes that the correct next-hop router is the router that it received the IP datagram from in the first place.

The **ip flow-capture ttl** command keeps track of the TTL values captured from packets in the flow. The minimum and maximum TTL values are stored in separate fields. This data is updated when a packet with a TTL that is lower or higher than the currently stored value is received. For example if the currently stored value for the minimum TTL is 64 and the next packet received has a TTL of 12, the 64 is replaced by 12.

If you are seeing several flows with the same value for the TTL, it is possible that your network is being attacked by a host that is constantly sending the same IP packets again and again. Under normal circumstances, flows come from many sources, each a different distance away. Therefore you should see a variety of TTLs across all the flows that NetFlow is capturing.

### ip flow-capture mac-addresses



#### Note

---

This command applies only to the traffic that is received or transmitted over Ethernet interfaces.

---

The **ip flow-capture mac-addresses** command captures the MAC addresses of the incoming source and the outgoing destination from the first Layer 2 frame in the flow. If you discover that your network is attacked by Layer 3 traffic, use these addresses to identify the device that transmits the traffic received by the router and the next-hop or final destination device to which the router forwards the traffic.

### ip flow-capture vlan-id

A virtual LAN (VLAN) is a broadcast domain within a switched network. A broadcast domain is defined by the network boundaries within which a network propagates a broadcast frame generated by a station. Some switches can be configured to support single or multiple VLANs. Whenever a switch supports multiple VLANs, broadcasts within one VLAN never appear in another VLAN.

Each VLAN is also a separate Layer 3 network. A router or a multilayer switch must be used to interconnect the Layer 3 networks that are assigned to the VLANs. For example, a device on VLAN 2 with an IP address of 172.16.0.76 communicating with a device on VLAN 3 with an IP address of 172.17.0.34 must use a router as an intermediary device because they are on different Class B IP networks. This is accomplished by connecting a switch to a router and configuring the link between them as a VLAN trunk. In order for the link to be used as a VLAN trunk, the interfaces on the router and the switch must be configured for the same VLAN encapsulation type.

**Note**


---

When a router is configured to route traffic between VLANs, it is often referred to as an inter-VLAN router.

---

When a router or a switch needs to send traffic on a VLAN trunk, it must either tag the frames using the IEEE 802.1q protocol or encapsulate the frames using the Cisco Inter-Switch Link (ISL) protocol. The VLAN tag or encapsulation header must contain the correct VLAN ID to ensure that the device receiving the frames can process them properly. The device that receives the VLAN traffic examines the VLAN ID from each frame to find out how it should process the frame. For example, when a switch receives an IP broadcast datagram such as an Address Resolution Protocol (ARP) datagram with an 802.1q tagged VLAN ID of 6 from a router, it forwards the datagram to every interface that is assigned to VLAN 6 and any interfaces that are configured as VLAN trunks.

The **ip flow-capture vlan-id** command captures the VLAN ID number from the first frame in the flow it receives that has an 802.1q tag or that is encapsulated with ISL. When the received traffic in the flow is transmitted over an interface that is configured with either 802.1q or ISL trunking, the **ip flow-capture vlan-id** command captures the destination VLAN ID number from the 802.1q or ISL VLAN header from the first frame in the flow.

**Note**


---

The **ip flow-capture vlan-id** command does not capture the type of VLAN encapsulation in use. The receiving and transmitting interfaces can use different VLAN protocols. If only one of the interfaces is configured as a VLAN trunk, the VLAN ID field is blank for the other interface.

---

Your router configuration must meet the following criteria before NetFlow can capture the value in the VLAN-ID field:

- It must have at least one LAN interface that is configured with one or more subinterfaces.
- The subinterfaces where you want to receive VLAN traffic must have either 802.1q or ISL enabled.
- The subinterfaces that are configured to receive VLAN traffic must have the **ip flow ingress** command configured on them.

If you discover that your network is being attacked by Layer 3 traffic, you can use the VLAN-ID information to help you find out which VLAN the device that is sending the traffic is on. The information can also help you identify the VLAN to which the router is forwarding the traffic.

**ip flow-capture nbar**

The **ip flow-capture nbar** command captures the application IDs and subapplication IDs exported as part of the NetFlow Version 9 record. The application IDs are mapped to applications. By means of the **ip flow-export template options nbar** command, this mapping information is exported to the NetFlow data collector. To capture Network Based Application Recognition (NBAR) information, you must enable NetFlow Version 9.

**Note**


---

The subapplication ID value is always 0 in current release.

---

**Examples**

The following example shows how to configure NetFlow to capture the value of the IP fragment-offset field from the IP datagrams in the flow:

```
Router(config)# ip flow-capture fragment-offset
```

The following example shows how to configure NetFlow to capture the value of the ICMP type field and the value of the code field from the IP datagrams in the flow:

```
Router(config)# ip flow-capture icmp
```

The following example shows how to configure NetFlow to capture the value of the IP-ID field from the IP datagrams in the flow:

```
Router(config)# ip flow-capture ip-id
```

The following example shows how to configure NetFlow to capture the value of the packet length field from the IP datagrams in the flow:

```
Router(config)# ip flow-capture packet-length
```

The following example shows how to configure NetFlow to capture the TTL field from the IP datagrams in the flow:

```
Router(config)# ip flow-capture ttl
```

The following example shows how to configure NetFlow to capture the MAC addresses from the IP datagrams in the flow:

```
Router(config)# ip flow-capture mac-addresses
```

The following example shows how to configure NetFlow to capture the VLAN ID from the IP datagrams in the flow:

```
Router(config)# ip flow-capture vlan-id
```

The following example shows how to configure NetFlow to capture NBAR information:

```
Router(config)# ip flow-capture nbar
```

**Related Commands**

Command	Description
<b>ip flow-cache entries</b>	Changes the number of entries maintained in the NetFlow accounting cache.
<b>ip flow-cache timeout</b>	Specifies NetFlow accounting flow cache parameters.
<b>ip flow egress</b>	Enables NetFlow egress accounting for traffic that the router is forwarding.
<b>ip flow-egress input-interface</b>	Removes the NetFlow egress accounting flow key that specifies an output interface and adds a flow key that specifies an input interface for NetFlow egress accounting.
<b>ip flow-export template options nbar</b>	Exports application mapping information to the NetFlow data collector.

<b>Command</b>	<b>Description</b>
<b>ip flow ingress</b>	Enables NetFlow ingress accounting for traffic arriving on an interface.
<b>show ip cache flow</b>	Displays a summary of NetFlow accounting statistics.
<b>show ip cache verbose flow</b>	Displays a detailed summary of the NetFlow accounting statistics.
<b>show ip flow export</b>	Displays the status and the statistics for NetFlow accounting data export.
<b>show ip flow interface</b>	Displays the NetFlow accounting configuration for interfaces.



## ip flow-egress input-interface

To remove the NetFlow egress accounting flow key that specifies an output interface and to add a flow key that specifies an input interface for NetFlow egress accounting, use the **ip flow-egress input-interface** command in global configuration mode. To change the flow key back from an input interface to an output interface for NetFlow egress statistics, use the **no** form of this command.

**ip flow-egress input-interface**

**no ip flow-egress input-interface**

**Syntax Description** This command has no arguments or keywords.

**Command Default** By default NetFlow egress statistics use the output interface as part of the flow key.

**Command Modes** Global configuration

Command History	Release	Modification
	12.3(11)T	This command was introduced.
	12.2(33)SRA	This command was integrated into Cisco IOS Release 12.2(33)SRA.
	12.2SX	This command is supported in the Cisco IOS Release 12.2SX train. Support in a specific 12.2SX release of this train depends on your feature set, platform, and platform hardware.

**Usage Guidelines** You must have NetFlow egress accounting configured on your router before you can use this command.

When the NetFlow Egress Support feature is configured, by default it uses the output interface as part of the flow key. The **ip flow-egress input-interface** command changes the key for egress flows so that the ingress interface is used instead of the output interface. This command is used to create a new flow for each input interface.

**Examples** In the following example the key for NetFlow reporting of egress traffic is changed from the output interface to the input interface:

```
Router(config)# ip flow-egress input-interface
```

**Related Commands**

<b>Command</b>	<b>Description</b>
<b>ip flow ingress</b>	Enables NetFlow (ingress) accounting for traffic arriving on an interface.
<b>ip flow egress</b>	Enables NetFlow egress accounting for traffic that the router is forwarding.
<b>ip flow-cache timeout</b>	Specifies NetFlow accounting flow cache parameters.
<b>ip flow-cache entries</b>	Changes the number of entries maintained in the NetFlow accounting cache.
<b>show ip cache flow</b>	Displays a summary of the NetFlow accounting statistics.
<b>show ip cache verbose flow</b>	Displays a detailed summary of the NetFlow accounting statistics.
<b>show ip flow interface</b>	Displays NetFlow accounting configuration for interfaces.

# ip flow-export destination

To enable the export of NetFlow accounting information in NetFlow cache entries to a remote device such as a server running an application that analyzes NetFlow data, use the **ip flow-export destination** command in global configuration mode. To remove an export destination, use the no form of this command.

**ip flow-export destination** {hostname| ip-address} port [udp] [vrf vrf-name]

**no ip flow-export destination** {hostname| ip-address} port [udp] [vrf vrf-name]

## Syntax Description

<i>ip-address</i>   <i>hostname</i>	IP address or hostname of the workstation to which you want to send the NetFlow information
<i>port</i>	Specifies the number of the user datagram protocol (UDP) port on which the workstation is listening for the exported NetFlow datagrams.
<b>vrf</b> <i>vrf-name</i>	(Optional) The <b>vrf</b> keyword specifies that the export data packets are to be sent to the named Virtual Private Network (VPN) routing forwarding instance (VRF) for routing to the destination, instead of to the global routing table.  <b>Note</b> The <i>vrf-name</i> argument is the name of the VRF.
<b>udp</b>	(Optional) Specifies UDP as the transport protocol. UDP is the default transport protocol.

## Command Default

Export of NetFlow information is disabled.

## Command Modes

Global configuration (config)#

## Command History

Release	Modification
11.1 CA	This command was introduced.
12.0(24)S	This command was integrated into Cisco IOS Release 12.0(24)S.
12.2(14)S	This command was integrated into Cisco IOS Release 12.2(14)S, and support for the Multiple Export Destinations feature was added.
12.2(2)T	This command was modified to enable multiple NetFlow export destinations to be used.

Release	Modification
12.2(14)SX	This command was introduced on the Supervisor Engine 720.
12.2(17d)SXB	Support for this command on the Supervisor Engine 2 was extended to the 12.2 SX release.
12.2(18)SXD	This command was changed to allow you to configure multiple NetFlow export destinations to a router.
12.2(18)SXE	This command was changed to allow you to enter two destination IP addresses on the Supervisor Engine 720 only. See the “Usage Guidelines” section for more information.
12.2(27)SBC	This command was integrated into Cisco IOS Release 12.2(27)SBC.
12.4(4)T	The <b>vrf</b> keyword and <i>vrf name</i> argument were added.
12.2(33)SRA	This command was integrated into Cisco IOS Release 12.2(33)SRA.
Cisco IOS XE 2.6	This command was integrated into Cisco IOS Release XE 2.6.
12.2(33)SXI4	This command was integrated into Cisco IOS Release 12.2(33)SXI4. The <b>vrf</b> keyword and <i>vrf name</i> argument were added.

## Usage Guidelines

### Cisco Catalyst 6500 Series Switches

With a PFC3 and Release 12.2(18)SXE and later releases, you can enter multiple NetFlow export destinations on the Supervisor Engine 720 only.

### Multiple Export Destinations

If the version of Cisco IOS that you have installed on your networking device supports the NetFlow Multiple Export Destinations feature, you can configure your networking device to export NetFlow data to a maximum of 2 export destinations (collectors) per cache (main and aggregation caches), using any combination of UDP and SCTP as the transport protocol for the destinations. A destination is identified by a unique combination of hostname or IP address and port number or port type.



#### Note

UDP is the default transport protocol used by the **export destination** command. In some Cisco IOS releases you can configure SCTP as the transport protocol if you need reliability and additional redundancy. Refer to the **ip flow-export sctp** command for more information.

The table below shows examples of the 2 permitted NetFlow export destinations for each cache.

**Table 3: Examples of Permitted Multiple NetFlow Export Destinations for Each Cache**

First Export Destination	Second Export Destination
<b>ip flow-export</b> 10.25.89.32 100 udp	<b>ip flow-export</b> 10.25.89.32 285 udp

First Export Destination	Second Export Destination
<code>ip flow-export 10.25.89.32 100 udp</code>	<code>ip flow-export 172.16.89.32 100 udp</code>
<code>ip flow-export 10.25.89.32 100 udp</code>	<code>ip flow-export 172.16.89.32 285 udp</code>
<code>ip flow-export 10.25.89.32 100 udp</code>	<code>ip flow-export 10.25.89.32 100 sctp</code>
<code>ip flow-export 10.25.89.32 100 sctp</code>	<code>ip flow-export 10.25.89.32 285 sctp</code>
<code>ip flow-export 10.25.89.32 100 sctp</code>	<code>ip flow-export 172.16.89.32 100 sctp</code>
<code>ip flow-export 10.25.89.32 100 sctp</code>	<code>ip flow-export 172.16.89.32 285 sctp</code>

The most common use of the multiple-destination feature is to send the NetFlow cache entries to two different destinations for redundancy. Therefore, in most cases the second destination IP address is not the same as the first IP address. The port numbers can be the same when you are configuring two unique destination IP addresses. If you want to configure both instances of the command to use the same destination IP address, you must use unique port numbers. You receive a warning message when you configure the two instances of the command with the same IP address. The warning message is, “%Warning: Second destination address is the same as previous address <ip-address>”.

**VRF Destinations for Exporting NetFlow Data**

Before Cisco IOS Releases 12.4(4)T, 12.2(33)SX14, and Cisco IOS XE Release 2.6, only one routing option existed for NetFlow export data packets. NetFlow sent all export data packets to the global routing table for routing to the export destinations you specified.

Cisco IOS Release 12.4(4)T, Cisco IOS XE Release 2.6, Cisco IOS Release 12.2(33)SX14, and later releases provide an additional routing option for NetFlow export data packets. You can send NetFlow data export packets to a Virtual Private Network (VPN) routing/forwarding instance (VRF) for routing to the destinations that you specify.

To send NetFlow data export packets to a VRF for routing to a destination, you enter the optional **vrfrvf-name** keyword and argument with the **ip flow-export destination ip-addressport** command. To configure the global routing table option, enter this command without the optional **vrfrvf-name** keyword and argument.

**More Information on NetFlow Data Export**

For more information on NetFlow Data Export (NDE) on a Cisco Catalyst 6500 series switch, refer to the “Configuring NDE” chapter in the *Catalyst 6500 Series Switch Cisco IOS Software Configuration Guide* .

For more information on NetFlow Data Export (NDE) on a Cisco 7600 series router, refer to the “Configuring NDE” chapter in the *Cisco 7600 Series Cisco IOS Software Configuration Guide* .

For more information on NetFlow Data Export (NDE) on Cisco routers, refer to the “Configuring NetFlow and NetFlow Data Export” chapter in the *Cisco IOS NetFlow Configuration Guide* .

**Examples**

The following example shows how to configure the networking device to export the NetFlow cache entry to a single export destination system:

```
Router(config)# ip flow-export destination 10.42.42.1 9991
```

The following example shows how to configure the networking device to export the NetFlow cache entry to multiple destination systems:

```
Router(config)# ip flow-export destination 10.42.42.1 9991
Router(config)# ip flow-export destination 10.0.101.254 9991
```

The following example shows how to configure the networking device to export the NetFlow cache entry to two different UDP ports on the same destination system:

```
Router(config)# ip flow-export destination 10.42.42.1 9991
Router(config)# ip flow-export destination 10.42.42.1 9992
%Warning: Second destination address is the same as previous address 10.42.42.1
```

The following example shows how to configure the networking device to export NetFlow data to a export destination that is reachable in VRF group1:

```
Router(config)# ip flow-export destination 172.16.10.2 78 vrf group1
```

### Related Commands

Command	Description
ip flow-export interface-names	Enables the inclusion of the interface names for the flows during the export of NetFlow accounting information in NetFlow cache entries.
ip flow-export source	Specifies the interface from which NetFlow will derive the source IP address for the NetFlow export datagrams containing NetFlow accounting information from NetFlow cache entries.
ip flow-export template	Configures template options for the export of NetFlow accounting information in NetFlow cache entries
ip flow-export version	Specifies the export version format for the exporting of NetFlow accounting information in NetFlow cache entries
<b>show ip flow export</b>	Displays the status and the statistics for NetFlow accounting data export.

# ip flow-export destination sctp

To enable the reliable export of NetFlow accounting information in NetFlow cache entries, use the **ip flow-export destination sctp** command in global configuration mode. To disable the reliable export of information, use the noform of this command.

**ip flow-export destination** {*ip-address*| *hostname*} *port* [**vrf** *vrf-name*] **sctp**

**no ip flow-export destination** {*ip-address*| *hostname*} *port* [**vrf** *vrf-name*] **sctp**

## Syntax Description

<i>ip-address</i>   <i>hostname</i>	IP address or hostname of the workstation to which you want to send the NetFlow information.
<i>port</i>	Specifies the number of the stream control transmission protocol (SCTP) port on which the workstation is listening for the exported NetFlow datagrams.
<b>vrf</b> <i>vrf-name</i>	(Optional) The <b>vrf</b> keyword specifies that the export data packets are to be sent to the named Virtual Private Network (VPN) routing forwarding instance (VRF) for routing to the destination, instead of to the global routing table.  <b>Note</b> The <i>vrf-name</i> argument is the name of the VRF

**Command Default** Reliable export of NetFlow information is disabled.

**Command Modes** Global configuration (config)

Release	Modification
12.4(4)T	This command was introduced.

## Usage Guidelines

### NetFlow Reliable Export Using SCTP

SCTP can be used as an alternative to UDP when you need a more robust and flexible transport protocol than UDP. SCTP is a reliable message-oriented transport layer protocol, which allows data to be transmitted between two end-points in a reliable, partially reliable, or unreliable manner.

An SCTP session consists of an association (connection) between two end-points (peers), which can contain one or more logical channels called streams. The default mode of transmission for a stream is to guarantee reliable ordered delivery of messages using a selective-acknowledgment scheme. SCTP buffers messages

until their receipt has been acknowledged by the receiving end-point. SCTP has a congestion control mechanism which limits how much memory is consumed by the SCTP stack, in packet buffering.

### VRF Destinations for Exporting NetFlow Data

Before Cisco IOS Release 12.4(4)T, one routing option existed for NetFlow export data packets. NetFlow sent all export data packets to the global routing table for routing to the destinations you specified.

Cisco IOS 12.4(4)T and later releases provide an additional routing option for NetFlow export data packets. You can send NetFlow data export packets to a Virtual Private Network (VPN) routing/forwarding instance (VRF) for routing to the destinations that you specify.

To send NetFlow data export packets to a VRF for routing to a destination, you enter the optional **vrfvrf-name** keyword and argument with the **ip flow-export destination ip-addressport** command. To configure the global routing table option, enter this command without the optional **vrfvrf-name** keyword and argument.

### Examples

The following example shows how to configure the networking device to use SCTP as the transport protocol when exporting NetFlow data:

```
Router(config)# ip flow-export destination 172.16.10.2 78 sctp
```

The following example shows how to configure the networking device to use SCTP as the transport protocol when exporting NetFlow data to a host that is reachable in VRF group1:

```
Router(config)# ip flow-export destination 172.16.10.2 78 vrf group1 sctp
```

### Related Commands

Command	Description
<b>backup</b>	Configures a backup destination for the reliable export of NetFlow accounting information in NetFlow cache entries
<b>reliability</b>	Specifies the level of reliability for the reliable export of NetFlow accounting information in NetFlow cache entries.
<b>show ip flow export</b>	Displays the status and the statistics for NetFlow accounting data export.



# ip flow-export hardware version

To specify the NetFlow Data Export (NDE) version for hardware-switched flows, use the **ip flow-export hardware version** command in global configuration mode. To return to the default settings, use the no form of this command.

**ip flow-export hardware version** [5| 7]

**no ip flow-export hardware version**

## Syntax Description

5	Specifies that the export packet uses the version 5 format; see the “Usage Guidelines” section for additional information.
7	Specifies that the export packet uses the version 7 format; see the “Usage Guidelines” section for additional information.

## Command Default

Version 7

## Command Modes

Global configuration

## Command History

Release	Modification
12.2(18)SXD	Support for this command was introduced on the Supervisor Engine 720 and the Supervisor Engine 2.

## Usage Guidelines

The **ip flow-export hardware version** command is only supported on systems that have a version 2 Supervisor Engine.

## Examples

This example shows how to specify the NDE version for hardware-switched flows:

```
Router(config)#
 ip flow-export hardware version 5
Router(config)#
```

## Related Commands

Command	Description
<b>ip flow-export interface</b>	Enables the interface-based ingress NDE for hardware-switched flows.

Command	Description
<b>ip flow-export version (Supervisor Engine 2)</b>	Specifies the version for the export of information in NetFlow cache entries.
<b>show mls nde</b>	Displays information about the NDE hardware-switched flow.

# ip flow-export interface-names

To enable the inclusion of the interface names for the flows during the export of NetFlow accounting information in NetFlow cache entries, use the **ip flow-export interface-names** command in global configuration mode. To return to the default behavior, use the noform of this command.

**ip flow-export interface-names**  
**no ip flow-export interface-names**

**Syntax Description** There are no keywords or arguments for this command.

**Command Default** Inclusion the interface names for the flows during the export of NetFlow accounting information in NetFlow cache entries is disabled.

**Command Modes** Global configuration (config)

Command History	Release	Modification
	12.4(2)T	This command was introduced.

**Usage Guidelines** The **interface-names** keyword for the **ip flow-export** command configures NetFlow to include the interface names from the flows when it exports the NetFlow cache entry to a destination system.

Prior to the addition of the **interface-names** keyword you had to poll the SNMP MIB for this information and correlate IF-index entries to interface names. After you enable the **ip flow-export interface-names** command the information is included in the exported NetFlow cache entries.



**Note** Interface names are exported as options templates/records.

**Examples** The following example shows how to configure the networking device to include the interface names from the flows when it exports the NetFlow cache entry to a destination system:

```
Router(config)# ip flow-export interface-names
```

**Related Commands**

Command	Description
<b>ip flow-export destination</b>	Enables the export of NetFlow accounting information in NetFlow cache entries to a remote device such as a server running an application that analyzes NetFlow data.
<b>ip flow-export source</b>	Specifies the interface from which NetFlow will derive the source IP address for the NetFlow export datagrams containing NetFlow accounting information from NetFlow cache entries.
<b>ip flow-export template</b>	Configures template options for the export of NetFlow accounting information in NetFlow cache entries
<b>ip flow-export version</b>	Specifies the export version format for the exporting of NetFlow accounting information in NetFlow cache entries
<b>show ip flow export</b>	Displays the status and the statistics for NetFlow accounting data export.

# ip flow-export source

To specify the interface from which NetFlow will derive the source IP address for the NetFlow export datagrams containing NetFlow accounting information from NetFlow cache entries, use the **ip flow-export source** command in global configuration mode. To return to the default behavior, use the noform of this command.

**ip flow-export source interface** *type number*

**no ip flow-export source interface** *type number*

## Syntax Description

<b>interface</b> <i>type number</i>	Interface name followed by the interface type and number.
-------------------------------------	---

## Command Default

NetFlow uses the IP address of the interface that the datagram is transmitted over as the source IP address for the NetFlow datagrams.

## Command Modes

Global configuration (config)

## Command History

Release	Modification
11.1 CA	This command was introduced.
12.0(24)S	This command was integrated into Cisco IOS Release 12.0(24)S.
12.2(14)S	This command was integrated into Cisco IOS Release 12.2(14)S.
12.2(27)SBC	This command was integrated into Cisco IOS Release 12.2(27)SBC.
12.2(18)SXF	This command was integrated into Cisco IOS Release 12.2(18)SXF.
12.2(33)SRA	This command was integrated into Cisco IOS Release 12.2(33)SRA.
15.0(1)M	This command was integrated into a release earlier than Cisco IOS Release 15.0(1)M. The <b>interface</b> <i>type number</i> keyword and arguments were added.
12.2(33)SRC	This command was modified. The <b>interface</b> <i>type number</i> keyword and arguments were added.
12.2(33)SXI	This command was modified. The <b>interface</b> <i>type number</i> keyword and arguments were added.
Cisco IOS XE Release 2.1	This command was integrated into Cisco IOS XE Release 2.1.

## Usage Guidelines

After you configure NetFlow data export, use the **ip flow-export source** command to specify the interface that NetFlow will use to obtain the source IP address for the NetFlow datagrams that it sends to destination systems, such as a system running NFC Engine. This will override the default behavior (using the IP address of the interface that the datagram is transmitted over as the source IP address for the NetFlow datagrams).

Some of the benefits of using a consistent IP source address for the datagrams that NetFlow sends are:

- The source IP address of the datagrams exported by NetFlow is used by the destination system to determine which router the NetFlow data is arriving from. If your network has two or more paths that can be used to send NetFlow datagrams from the router to the destination system and you do not specify the source interface from which the source IP address is to be obtained, the router uses the IP address of the interface that the datagram is transmitted over as the source IP address of the datagram. In this situation the destination system might receive NetFlow datagrams from the same router, but with different source IP addresses. This causes the destination system to treat the NetFlow datagrams as if they were being sent from different routers unless you have configured the destination system to aggregate the NetFlow datagrams it receives from all of the possible source IP addresses in the router into a single NetFlow flow.
- If your router has multiple interfaces that can be used to transmit datagrams to the CNS NFC, and you do not configure the **ip flow-export source interface** command, you will have to add an entry for the IP address of each interface into any access lists that you create for permitting NetFlow traffic. It is easier to create and maintain access-lists for permitting NetFlow traffic from known sources and blocking it from unknown sources when you limit the source IP address for NetFlow datagrams to a single IP address for each router that is exporting NetFlow traffic.

You can use the IP address of a loopback interface as the source IP address for NetFlow traffic by entering the **ip flow-export source interface** *type[number | slot/port]* command (for example, **ip flow-export source interface loopback 0**). Doing so makes it more difficult for people who want to attack your network by spoofing the source IP address of your NetFlow-enabled routers to determine which IP address to use. This is because the IP addresses assigned to loopback interfaces are not as easy to discover as the IP addresses assigned to physical interfaces on the router. For example, it is easy to determine the IP address of a Fast Ethernet interface on a router that is connected to a LAN that has end user devices on it. You simply check the configuration of one of the devices for its IP default gateway address.

If the export destination is in a VRF, the **ip flow-export source** command specifies an interface, which is not an interface in the same VRF as the destination. Therefore, the code will automatically pick up an interface on the local router that is in the same VRF as the export-destination and hence ignore the configured export source.

## Examples

The following example shows how to configure NetFlow to use a loopback interface as the source interface for NetFlow traffic.



### Caution

The interface that you configure as the **ip flow-export source** interface must have an IP address configured and it must be up.

```
Router(config)# ip flow-export source loopback0
```

**Related Commands**

<b>Command</b>	<b>Description</b>
<b>ip flow-export destination</b>	Enables the export of NetFlow accounting information in NetFlow cache entries to a remote device such as a server running an application that analyzes NetFlow data.
<b>ip flow-export interface-names</b>	Enables the inclusion of the interface names for the flows during the export of NetFlow accounting information in NetFlow cache entries.
<b>ip flow-export template</b>	Configures template options for the export of NetFlow accounting information in NetFlow cache entries
<b>ip flow-export version</b>	Specifies the export version format for the exporting of NetFlow accounting information in NetFlow cache entries
<b>show ip flow export</b>	Displays the status and the statistics for NetFlow accounting data export.

## ip flow-export template

To configure template options for the export of NetFlow accounting information in NetFlow cache entries, use the **ip flow-export template** command in global configuration mode. To remove the configured refresh-rate and timeout-rate and to return to the default rate, use the noform of this command.

### Configure template only

**ip flow-export template** {refresh-rate *packets*| timeout-rate *minutes*}

**no ip flow-export template** {refresh-rate| timeout-rate}

### Configure template options

**ip flow-export template options** {export-stats| refresh-rate *packets*| timeout-rate *minutes*| sampler| nbar}

**no ip flow-export template options** {export-stats| refresh-rate| timeout-rate| sampler| nbar}

### Syntax Description

<b>template</b>	Enables the <b>refresh-rate</b> and <b>timeout-rate</b> keywords for the configuring of Version 9 export templates.
<b>refresh-rate</b> <i>packets</i>	Specifies the number of export packets that are sent before the options and flow templates are resent. Range: 1 to 600. Default: 20.
<b>timeout-rate</b> <i>minutes</i>	Specifies the interval (in minutes) that the router waits after sending the templates (flow and options) before sending them again. Range: 1 to 3600. Default: 30.
<b>options</b>	Enables the <b>export-stats</b> , <b>refresh-rate</b> , <b>sampler</b> and <b>timeout-rate</b> keywords for configuring Version 9 export options.
<b>export-stats</b>	Enables the export of statistics including the total number of flows exported and the total number of packets exported.
<b>sampler</b>	When Version 9 export is configured, this keyword enables the export of an option containing a random-sampler configuration, including the sampler ID, sampling mode, and sampling interval for each configured random sampler.  <b>Note</b> You must have a flow sampler map configured before you can configure the sampler keyword for the <b>ip flow-export template options</b> command.
<b>nbar</b>	Exports application mapping information to the NetFlow data collector.



**Command Default** The export template and export template options are not configured.

**Command Modes** Global configuration (config)

Release	Modification
12.3(2)T	This command was introduced.
12.2(27)SBC	This command was integrated into Cisco IOS Release 12.2(27)SBC.
12.2(18)SXF	This command was integrated into Cisco IOS Release 12.2(18)SXF.
12.2(33)SRA	This command was integrated into Cisco IOS Release 12.2(33)SRA.
12.2(18)ZYA2	This command was modified. The <b>nbar</b> keyword was added.

**Usage Guidelines**

The **ip flow-export template options export-stats** command requires that the NetFlow Version 9 export format be already configured on the router.

The **ip flow-export template options sampler** command requires that the NetFlow Version 9 export format and a flow sampler map be already configured on the router.

The **ip flow-export template options nbar** command exports application IDs to string mapping as options. It displays string values for application IDs to which they are mapped. To export the application mapping information, you must enable NetFlow Export Version 9 export format and have Network Based Application Recognition (NBAR) configured on the device.

**Examples** The following example shows how to configure NetFlow so that the networking device sends the export statistics (total flows and packets exported) as options data:

```
Router(config)# ip flow-export template options export-stats
```

The following example shows how to configure NetFlow to wait until 100 export packets have been sent or 60 minutes have passed since the last time the templates were sent (whichever comes first) before the templates are resent to the destination host:

```
Router(config)# ip flow-export template refresh-rate 100
Router(config)# ip flow-export template timeout-rate 60
```

The following example shows how to configure NetFlow to enable the export of information about NetFlow random samplers:

```
Router(config)# ip flow-export template options sampler
```

**Tip**

You must have a **flow-sampler** map configured before you can configure the sampler keyword for the **ip flow-export template options** command.

The following example shows how to configure NetFlow to enable the export of application mapping information:

```
Router(config)# ip flow-export template options nbar
```

**Related Commands**

Command	Description
<b>ip flow-export destination</b>	Enables the export of NetFlow accounting information in NetFlow cache entries to a remote device such as a server running an application that analyzes NetFlow data.
<b>ip flow-export interface-names</b>	Enables the inclusion of the interface names for the flows during the export of NetFlow accounting information in NetFlow cache entries.
<b>ip flow-export source</b>	Specifies the interface from which NetFlow will derive the source IP address for the NetFlow export datagrams containing NetFlow accounting information from NetFlow cache entries.
<b>ip flow-export version</b>	Specifies the export version format for the exporting of NetFlow accounting information in NetFlow cache entries
<b>show ip flow export</b>	Displays the status and the statistics for NetFlow accounting data export.

# ip flow-export version

To specify the export version format for the exporting of NetFlow accounting information in NetFlow cache entries, use the **ip flow-export version** command in global configuration mode. To return to the default behavior, use the noform of this command.

**ip flow-export version** {1|5|9} [origin-as|peer-as] [bgp-nexthop]}

**no ip flow-export version** {1|5|9} [origin-as|peer-as] [bgp-nexthop]}

## Syntax Description

<b>1</b>	Specifies that the export datagram uses the version 1 format. This is the default.
<b>5</b>	Specifies that the export datagram uses the version 5 format.
<b>9</b>	(Specifies that the export datagram uses the version 9 format.
<b>origin-as</b>	(Optional) Specifies that export statistics include the originating autonomous system (AS) for the source and destination.
<b>peer-as</b>	(Optional) Specifies that export statistics include the peer AS for the source and destination.
<b>bgp-nexthop</b>	(Optional) Specifies that export statistics include Border Gateway Protocol (BGP) next-hop-related information.

## Command Default

Version 1 is the default export format for the exporting of NetFlow accounting information in NetFlow cache entries.

## Command Modes

Global configuration (config)

## Command History

Release	Modification
11.1CA	This command was introduced.
12.0(24)S	This command was integrated into Cisco IOS Release 12.0(24)S, and the <b>9</b> keyword was added.
12.0(26)S	Support for the BGP Next Hop Support feature was added.

Release	Modification
12.2(14)S	This command was integrated into Cisco IOS Release 12.2(14)S.
12.3(1)	Support for the BGP Next Hop Support and NetFlow v9 Export Format features was added.
12.2(18)S	Support for the BGP Next Hop Support and NetFlow v9 Export Format features was added.
12.2(27)SBC	This command was integrated into Cisco IOS Release 12.2(27)SBC.
12.2(18)SXF	This command was integrated into Cisco IOS Release 12.2(18)SXF.
12.2(33)SRA	This command was integrated into Cisco IOS Release 12.2(33)SRA.

### Usage Guidelines

The **ip flow-export version** command supports three export data formats: Version 1, Version 5, and Version 9. Version 1 should be used only when it is the only NetFlow data export format version that is supported by the application that you are using to analyze the exported NetFlow data. Version 5 exports more fields than Version 1. Version 9 is the only flexible export format version.

The NetFlow Version 9 Export Format feature was introduced in Cisco IOS Release 12.0(24)S and was integrated into Cisco IOS Release 12.3(1) and Cisco IOS Release 12.2(18)S.

NetFlow Version 9 is a flexible and extensible means for transferring NetFlow records from a network node to a collector. NetFlow Version 9 has definable record types and is self-describing for easier NetFlow Collection Engine configuration.

Third-party business partners who produce applications that provide NetFlow Collection Engine or display services for NetFlow do not need to recompile their applications each time a new NetFlow technology is added. Instead, with the NetFlow Version 9 Export Format feature, they can use an external data file that documents the known template formats and field types.

NetFlow Version 9 has the following characteristics:

- Record formats are defined by templates.
- Template descriptions are communicated from the router to the NetFlow Collection (NFC) Engine.
- Flow records are sent from the router to the NetFlow Collection Engine with minimal template information so that the NetFlow Collection Engine can relate the records to the appropriate template.

Version 9 is independent of the underlying transport (UDP, TCP, SCTP, and so on).



#### Note

The values for the BGP next hop IP address captured by the **bgp-nexthop** command are exported to a NetFlow export destination only when the Version 9 export format is configured.



**Note** In order for the BGP information to be populated in the main cache, you must have either a NetFlow export destination configured or a NetFlow aggregation configured.



**Note** The AS values for the **peer-as** and the **origin-as** keywords are captured only if you have configured an export destination with the **ip flow-export destination** command.

For more information on the available export data formats, see the *Cisco IOS NetFlow Configuration Guide*, Release 12.4T. For more information on the Version 9 data format, see the [Cisco IOS NetFlow Version 9 Export Format Feature Guide](#).



**Caution** Entering the **ip flow-export version** or **no ip flow-export version** command on the Cisco 12000 series Internet routers, Cisco 6500 series routers, and Cisco 7600 series routers and specifying a format other than version 1 (in other words, entering the **ip flow-export version** or **no ip flow-export version** command and specifying the **5** keyword) causes packet forwarding to stop for a few seconds while NetFlow reloads the Route Processor and line card Cisco Express Forwarding tables. To avoid interruption of service to a live network, apply this command during a change window, or include it in the startup-config file to be executed during a router reboot.

**Examples**

The following example shows how to configure the networking device to use the NetFlow Version 9 format for the exported data and how to include the originating autonomous system (origin-as) with its corresponding next BGP hop (bgp-nexthop):

```
Router(config)# ip flow-export version 9 origin-as bgp-nexthop
```

**Related Commands**

Command	Description
ip flow-export destination	Enables the export of NetFlow accounting information in NetFlow cache entries to a remote device such as a server running an application that analyzes NetFlow data.
ip flow-export interface-names	Enables the inclusion of the interface names for the flows during the export of NetFlow accounting information in NetFlow cache entries.
ip flow-export source	Specifies the interface from which NetFlow will derive the source IP address for the NetFlow export datagrams containing NetFlow accounting information from NetFlow cache entries.
ip flow-export template	Configures template options for the export of NetFlow accounting information in NetFlow cache entries

Command	Description
<b>show ip flow export</b>	Displays the status and the statistics for NetFlow accounting data export.

## ip flow-export version (Supervisor Engine 2)

To specify the version for the export of information in NetFlow cache entries, use the **ip flow-export version** command in global configuration mode. To disable information exporting, use the no form of this command.

**ip flow-export version** {1| 5 [origin-as| peer-as]| 6 [origin-as| peer-as]}

**no ip flow-export version**

### Syntax Description

<b>1</b>	Specifies that the export packet uses the version 1 format; see the “Usage Guidelines” section for additional information.
<b>5</b>	Specifies that the export packet uses the version 5 format; see the “Usage Guidelines” section for additional information.
<b>origin-as</b>	(Optional) Specifies that export statistics include the origin autonomous system for the source and destination.
<b>peer-as</b>	(Optional) Specifies that export statistics include the peer autonomous system for the source and destination.
<b>6</b>	Specifies that the export packet uses the version 6 format; see the “Usage Guidelines” section for additional information.

### Command Default

Version 1

### Command Modes

Global configuration

### Command History

Release	Modification
12.2(17d)SXB	Support for this command on the Supervisor Engine 2 was extended to the 12.2 SX release.

### Usage Guidelines

This command documentation applies only to systems that have a version 2 Supervisor Engine.

NDE makes traffic statistics available for analysis by an external data collector. You can use NDE to monitor all Layer 3 switched and all routed IP unicast traffic. In the Cisco 7600 series router, both the Policy Feature Card (PFC) and the Multilayer Switch Feature Card (MSFC) maintain NetFlow caches that capture flow-based traffic statistics. The cache on the PFC captures statistics for Layer 3-switched flows. The cache on the MSFC captures statistics for routed flows.



**Note** NDE can use NDE version 1, 5, or 6 to export the statistics that are captured on the MSFC for routed traffic.

The number of records stored in the datagram is a variable from 1 to 24 for version 1. The number of records stored in the datagram is a variable between 1 and 30 for version 5.

For more information on NDE, refer to the “Configuring NDE” chapter in the Cisco 7600 Series Router Cisco IOS Software Configuration Guide.

### Examples

This example shows how to export the data using the version 5 format and include the peer autonomous system information:

```
Router# configure terminal
Router(config)# interface loopback0
Router(config-if)# ip address 4.0.0.1 255.0.0.0
Router(config-if)# exit
Router(config)# interface serial 5/0:0
Router(config-if)# ip unnumbered loopback0
Router(config-if)# no ip mroute-cache
Router(config-if)# encapsulation ppp
Router(config-if)# ip route-cache flow
Router(config-if)# exit
Router(config)# ip flow-export version 5 peer-as
Router(config)# exit
```

### Related Commands

Command	Description
<b>ip flow-export destination</b>	Exports the NetFlow cache entries to a specific destination.
<b>ip flow-export source</b>	Specifies the source interface IP address that is used in the NDE datagram.
<b>ip route-cache flow</b>	Enables NetFlow switching for IP routing.



# ip flow-export version (Supervisor Engine 720)

To specify the version for the export of information in NetFlow cache entries, use the **ip flow-export version** command in global configuration mode. To return to the default settings, use the no form of this command.

```
ip flow-export version {1| 5 [origin-as| peer-as]| 9 [bgp-nexthop| origin-as| peer-as]}
no ip flow-export version
```

### Syntax Description

<b>1</b>	Specifies that the export packet use the version 1 format; see the “Usage Guidelines” section for additional information.
<b>5</b>	Specifies that the export packet use the version 5 format; see the “Usage Guidelines” section for additional information.
<b>origin-as</b>	(Optional) Specifies that export statistics include the origin autonomous system for the source and destination.
<b>peer-as</b>	(Optional) Specifies that export statistics include the peer autonomous system for the source and destination.
<b>9</b>	Specifies that the export packet uses the version 9 format; see the “Usage Guidelines” section for additional information.
<b>bgp-nexthop</b>	(Optional) Specifies that export statistics include the BGP next hop for the source and destination.

**Command Default** Export of information in NetFlow cache entries is disabled.

**Command Modes** Global configuration

### Command History

Release	Modification
12.2(17d)SXB	This command was introduced on the Supervisor Engine 720.
12.2(18)SXF	Support was added for NetFlow version 9 export format on the Supervisor Engine 720.

Release	Modification
12.2(33)SRA	This command was integrated into Cisco IOS Release 12.2(33)SRA.

### Usage Guidelines

Version 5 and version 9 formats include the source and destination autonomous-system addresses and source and destination prefix masks. Also, version 9 includes BGP next-hop information.

The number of records stored in the datagram is a variable from 1 to 24 for version 1. The number of records stored in the datagram is a variable between 1 and 30 for version 5.

For more information on NDE, refer to the “Configuring NDE” chapter in the Cisco 7600 Series Router Cisco IOS Software Configuration Guide.



### Caution

Entering the **ip flow-export version** or **no ip flow-export version** command on the Cisco 12000 series Internet routers, Cisco 6500 series routers, and Cisco 7600 series routers and specifying a format other than version 1 (in other words, entering the **ip flow-export version** or **no ip flow-export version** command and specifying the **5** keyword) causes packet forwarding to stop for a few seconds while NetFlow reloads the Route Processor and line card Cisco Express Forwarding tables. To avoid interruption of service to a live network, apply this command during a change window, or include it in the startup-config file to be executed during a router reboot.

### Examples

This example shows how to export the data using the version 5 format:

```
Router(config)# ip flow-export version 5
```

### Related Commands

Command	Description
<b>ip flow-export version (Supervisor Engine 2)</b>	Specifies the version for the export of information in NetFlow cache entries.
<b>show mls nde</b>	Displays information about the NDE hardware-switched flow.

## ip flow-top-talkers

To configure NetFlow top talkers to capture traffic statistics for the unaggregated top flows of the heaviest traffic patterns and most-used applications in the network, use the **ip flow-top-talkers** command in global configuration mode. To disable NetFlow top talkers, use the **no** form of this command.

**ip flow-top-talkers**

**no ip flow-top-talkers**

**Syntax Description** This command has no arguments or keywords.

**Command Default** NetFlow top talkers is disabled by default.

**Command Modes** Global configuration

Command History	Release	Modification
	12.2(25)S	This command was introduced.
	12.3(11)T	This feature was integrated into Cisco IOS Release 12.3(11)T.
	12.2(27)SBC	This command was integrated into Cisco IOS Release 12.2(27)SBC.
	12.2(33)SRA	This command was integrated into Cisco IOS Release 12.2(33)SRA.
	12.2SX	This command is supported in the Cisco IOS Release 12.2SX train. Support in a specific 12.2SX release of this train depends on your feature set, platform, and platform hardware.

### Usage Guideline

#### Tip

The **ip flow-top-talkers** command does not appear in the configuration until you have configured the **topnumber** and **sort-by [bytes | packets]** commands.

#### Enabling NetFlow

You must enable NetFlow on at least one interface in the router; and configure NetFlow top talkers before you can use the **show ip flow top-talkers** command to display the traffic statistics for the unaggregated top flows in the network. NetFlow top talkers also requires that you configure the **sort-by** and **top** commands. Optionally, the **match** command can be configured to specify additional matching criteria.

#### Cache Timeout

The timeout period as specified by the **cache-timeout** command does not start until the **show ip flow top-talkers** command is entered. From that time, the same top talkers are displayed until the timeout period

expires. To recalculate a new list of top talkers before the timeout period expires, you can change the parameters of the **cache-timeout**, **top**, or **sort-by** command prior to entering the **show ip flow top-talkers** command.

A long timeout period for the **cache-timeout** command limits the system resources that are used by the NetFlow top talkers feature. However, the list of top talkers is calculated only once during the timeout period. If a request to display the top talkers is made more than once during the timeout period, the same results are displayed for each request, and the list of top talkers is not recalculated until the timeout period expires.

A short timeout period ensures that the latest list of top talkers is retrieved; however too short a period can have undesired effects:

- The list of top talkers is lost when the timeout period expires. You should configure a timeout period for at least as long as it takes the network management system (NMS) to retrieve all the required NetFlow top talkers.
- The list of top talkers is updated every time the top talkers information is requested, possibly causing unnecessary usage of system resources.

A good method to ensure that the latest information is displayed, while also conserving system resources, is to configure a large value for the timeout period, but cause the list of top talkers to be recalculated by changing the parameters of the **cache-timeout**, **top**, or **sort-by** command prior to entering the **show ip flow top-talkers** command to display the top talkers. Changing the parameters of the **cache-timeout**, **top**, or **sort-by** command causes the list of top talkers to be recalculated upon receipt of the next command line interface (CLI) or MIB request.

Use the **show ip flow top-talkers** command to display the list of unaggregated top flows.

## Examples

In the following example, a maximum of four top talkers is configured. The sort criterion is configured to sort the list of top talkers by the total number of bytes for each Top Talker.

```
Router(config)# ip flow-top-talkers
Router(config-flow-top-talkers)# top 4
Router(config-flow-top-talkers)# sort-by bytes
```

The following example shows the output of the **show ip flow top talkers** command with the configuration from the previous example:

```
Router# show ip flow top-talkers

SrcIf          SrcIPAddress      DstIf          DstIPAddress      Pr SrcP DstP Bytes
Et0/0.1        10.10.18.1        Et1/0.1        172.16.10.232    11 00A1 00A1 349K
Et0/0.1        10.10.19.1        Et1/0.1        172.16.10.2      11 00A2 00A2 349K
Et0/0.1        172.30.216.196    Et1/0.1        172.16.10.2      06 0077 0077 328K
Et0/0.1        10.162.37.71      Et1/0.1        172.16.10.2      06 0050 0050 303K
4 of 4 top talkers shown. 11 flows processed
```

## Related Commands

Command	Description
<b>cache-timeout</b>	Specifies the length of time for which the list of top talkers (heaviest traffic patterns and most-used applications in the network) for the NetFlow MIB and top talkers feature is retained.
<b>match (NetFlow)</b>	Specifies match criteria for the NetFlow MIB and top talkers (heaviest traffic patterns and most-used applications in the network) feature.

<b>Command</b>	<b>Description</b>
<b>show ip flow top-talkers</b>	Displays the statistics for the top talkers (heaviest traffic patterns and most-used applications in the network).
<b>sort-by</b>	Specifies the sorting criterion for top talkers (heaviest traffic patterns and most-used applications in the network) to be displayed for the NetFlow MIB and top talkers feature.
<b>top</b>	Specifies the maximum number of top talkers (heaviest traffic patterns and most-used applications in the network) to be displayed for the NetFlow MIB and top talkers feature.
<b>show ip cache flow</b>	Displays a summary of the NetFlow accounting statistics.
<b>show ip cache verbose flow</b>	Displays a detailed summary of the NetFlow accounting statistics.
<b>show ip flow interface</b>	Displays NetFlow accounting configuration for interfaces.

## ip multicast netflow

To configure multicast NetFlow accounting on an interface, use the **ip multicast netflow** command in interface configuration mode. To disable multicast NetFlow accounting, use the **no** form of this command.

**ip multicast netflow** {ingress| egress}

**no ip multicast netflow** {ingress| egress}

### Syntax Description

<b>ingress</b>	Enables multicast NetFlow (ingress) accounting.
<b>egress</b>	Enables multicast NetFlow (egress) accounting.

### Command Default

Multicast ingress NetFlow accounting is enabled.

Multicast egress NetFlow accounting is disabled.

### Command Modes

Interface configuration

### Command History

Release	Modification
12.3(1)	This command was introduced.
12.2(18)S	This command was integrated into Cisco IOS Release 12.2(18)S.
12.2(27)SBC	This command was integrated into Cisco IOS Release 12.2(27)SBC.
12.2(18)SXD	Support for this command was introduced on the Supervisor Engine 720.
12.2(18)SXF	This command was integrated into Cisco IOS Release 12.2(18)SXF.
12.2(33)SRA	This command was integrated into Cisco IOS Release 12.2(33)SRA.
12.2(31)SB2	This command was integrated into Cisco IOS Release 12.2(31)SB2.
12.4(11)T	In Cisco IOS Release 12.4(11)T this command was moved to global configuration mode and the <b>ingress</b> and <b>egress</b> keywords were replaced by the <b>output-counters</b> keyword. See the <b>ip multicast netflow output-counters</b> command.
12.4(12)	In Cisco IOS Release 12.4(12) this command was moved to global configuration mode and the <b>ingress</b> and <b>egress</b> keywords were replaced by the <b>output-counters</b> keyword. See the <b>ip multicast netflow output-counters</b> command.

Release	Modification
12.(33)SRB	In Cisco IOS Release 12.(33)SRB this command was moved to global configuration mode and the <b>ingress</b> and <b>egress</b> keywords were replaced by the <b>output-counters</b> keyword. See the <b>ip multicast netflow output-counters</b> command.
12.(33)SXH	In Cisco IOS Release 12.(33)SXH this command was moved to global configuration mode and the <b>ingress</b> and <b>egress</b> keywords were replaced by the <b>output-counters</b> keyword. See the <b>ip multicast netflow output-counters</b> command.
12.(33)SB	In Cisco IOS Release 12.(33)SB this command was moved to global configuration mode and the <b>ingress</b> and <b>egress</b> keywords were replaced by the <b>output-counters</b> keyword. See the <b>ip multicast netflow output-counters</b> command.

**Usage Guidelines**

You must have NetFlow accounting configured on your router before you can use this command.

**ip multicast netflow ingress**

NetFlow (ingress) accounting for multicast traffic is enabled by default. The **ip multicast netflow ingress** command does not appear in the configuration.

**ip multicast netflow egress**

You must enable multicast egress NetFlow accounting on all interfaces for which you want to count outgoing multicast streams.

To display the multicast entries, enter the **show mls netflow ip** command.

**Examples**

The following example shows how to enable multicast ingress NetFlow accounting on the ingress Ethernet 1/0 interface:

```
Router(config)# interface ethernet 1/0
Router(config-if)# ip multicast netflow ingress
```

The following example shows how to enable multicast egress NetFlow accounting on the egress Ethernet interface 0/0:

```
Router(config)# interface ethernet 0/0
Router(config-if)# ip multicast netflow egress
```

**Related Commands**

Command	Description
<b>ip multicast netflow rpf-failure</b>	Enables accounting for multicast data that fails the RPF check.
<b>show ip cache flow</b>	Displays a summary of the NetFlow statistics.
<b>show ip cache verbose flow</b>	Displays a detailed summary of the NetFlow statistics.

Command	Description
<b>show ip flow interface</b>	Displays NetFlow accounting configuration for interfaces.
<b>show ip mroute</b>	Displays the contents of the IP multicast routing (mroute) table.
<b>show mls netflow ip</b>	Displays information about the hardware NetFlow IP.



## ip multicast netflow output-counters

To enable NetFlow accounting for the number of bytes and packets of multicast traffic forwarded from an ingress flow, use the **ip multicast netflow output-counters** command in global configuration mode. To disable accounting for the number of bytes and packets forwarded, use the **no** form of this command.

**ip multicast netflow output-counters**

**no ip multicast netflow output-counters**

**Syntax Description** This command has no arguments or keywords.

**Command Default** Accounting for the number of bytes and packets of multicast traffic that is forwarded is disabled.

**Command Modes** Global configuration

Command History	Release	Modification
	12.3(1)	This command was introduced.
	12.2(18)S	This command was integrated into Cisco IOS Release 12.2(18)S.
	12.4(11)T	This command was integrated into Cisco IOS Release 12.4(11)T.
	12.4(12)	This command was integrated into Cisco IOS Release 12.4(12).
	12.2(33)SRB	This command was integrated into Cisco IOS Release 12.2(33)SRA.
	12.2(33)SXH	This command was integrated into Cisco IOS Release 12.2(33)SXH.
	12.2(33)SB	This command was integrated into Cisco IOS Release 12.2(33)SB.

**Usage Guidelines** You must have NetFlow accounting configured on your router before you can use this command.

**Examples** The following example shows how to enable NetFlow accounting for the number of bytes and packets of multicast traffic forwarded from an ingress flow:

```
Router# configure terminal
Router(config)# ip multicast netflow output-counters
Router(config)# end
```

**Related Commands**

<b>Command</b>	<b>Description</b>
<b>ip multicast netflow</b>	Configures multicast NetFlow accounting on an interface.
<b>show ip cache flow</b>	Displays a summary of the NetFlow accounting statistics.
<b>show ip cache verbose flow</b>	Displays a detailed summary of the NetFlow accounting statistics.
<b>show ip flow interface</b>	Displays NetFlow accounting configuration for interfaces.
<b>show ip mroute</b>	Displays the contents of the IP multicast routing (mroute) table.
<b>show ip rpf</b>	Displays how IP multicast routing does RPF.
<b>show ip rpf events</b>	Displays the last 15 triggered multicast RPF check events.

## ip multicast netflow rpf-failure

To enable NetFlow accounting for multicast data that fails the reverse path forwarding (RPF) check (meaning any IP packets that lack a verifiable IP source address), use the **ip multicast netflow rpf-failure** command in global configuration mode. To disable accounting for multicast data that fails the RPF check, use the **no** form of this command.

**ip multicast netflow rpf-failure**

**no ip multicast netflow rpf-failure**

**Syntax Description** This command has no arguments or keywords.

**Command Default** Accounting for multicast data that fails the RPF check is disabled.

**Command Modes** Global configuration

Command History	Release	Modification
	12.3(1)	This command was introduced.
	12.2(18)S	This command was integrated into Cisco IOS Release 12.2(18)S.
	12.2(27)SBC	This command was integrated into Cisco IOS Release 12.2(27)SBC.
	12.2(18)SXF	This command was integrated into Cisco IOS Release 12.2(18)SXF.
	12.2(33)SRA	This command was integrated into Cisco IOS Release 12.2(33)SRA.

**Usage Guidelines** You must have NetFlow accounting configured on your router before you can use this command.

**Examples** The following example shows how to enable accounting for multicast data that fails the RPF check:

```
Router# configure terminal
Router(config)# ip multicast netflow rpf-failure
Router(config)# end
```

### Related Commands

Command	Description
<b>ip multicast netflow</b>	Configures multicast NetFlow accounting on an interface.

Command	Description
<b>show ip cache flow</b>	Displays a summary of the NetFlow accounting statistics.
<b>show ip cache verbose flow</b>	Displays a detailed summary of the NetFlow accounting statistics.
<b>show ip flow interface</b>	Displays NetFlow accounting configuration for interfaces.
<b>show ip mroute</b>	Displays the contents of the IP multicast routing (mroute) table.
<b>show ip rpf</b>	Displays how IP multicast routing does RPF.
<b>show ip rpf events</b>	Displays the last 15 triggered multicast RPF check events.

## ip route-cache flow

Effective with Cisco IOS Releases 12.4(2)T and 12.2(18)SXD, the **ip route-cache flow** command is replaced by the **ip flow ingress** command. See the **ip flow ingress** command for more information.

To enable NetFlow (ingress) accounting for traffic arriving on an interface, use the **ip route-cache flow** command in interface configuration mode. To disable NetFlow (ingress) accounting for traffic arriving on an interface, use the **no** form of this command in interface configuration mode.

**ip route-cache flow**

**no route-cache flow**

**Syntax Description** This command has no arguments or keywords.

**Command Default** This command is not enabled by default.

**Command Modes** Interface configuration

### Command History

Release	Modification
11.1	This command was introduced.
12.4(2)T	The <b>ip route-cache flow</b> command is automatically remapped to the <b>ip flow-ingress</b> command.
12.2(14)S	This command was integrated into Cisco IOS Release 12.2(14)S.
12.2(25)S	The <b>ip route-cache flow</b> command is automatically remapped to the <b>ip flow-ingress</b> command.
12.2(14)SX	Support for this command was introduced on the Supervisor Engine 720.
12.2(27)SBC	This command was integrated into Cisco IOS Release 12.2(27)SBC.
12.2(17d)SXB	Support for this command on the Supervisor Engine 2 was extended to the 12.2 SX release.
12.2(18)SXD	The <b>ip route-cache flow</b> command is automatically remapped to the <b>ip flow-ingress</b> command.
12.2(18)SXF	This command was integrated into Cisco IOS Release 12.2(18)SXF.
12.2(33)SRA	This command was integrated into Cisco IOS Release 12.2(33)SRA.

**Usage Guidelines**

Use this command on an interface or subinterface to enable NetFlow (ingress) accounting for traffic that is being received by the router.

**Cisco IOS Release 12.2(25)S and 12.2(18)SXD**

When you enter the **ip route-cache flow** command to enable NetFlow (ingress) accounting on an interface in a router that is running Cisco IOS Release 12.2(25)S or later, or Cisco IOS Release 12.2(18)SXD or later, the command is automatically remapped to the **ip flow-ingress** command before it is added to the in the running configuration. Therefore you must use the **no ip flow ingress** command to disable NetFlow (ingress) accounting on the interface.

**Examples**

The following example shows how to enable NetFlow (ingress) accounting on Ethernet interface 0/0 using the **ip route-cache flow** command:

```
Router(config)# interface Ethernet0/0
Router(config-if)# ip
route-cache flow
```

The following example shows how to disable NetFlow (ingress) accounting on Ethernet interface 0/0 of a router that is running Cisco IOS Release 12.2(25)S or later using the **no ip flow ingress** command:

```
Router(config)# interface Ethernet0/0
Router(config-if)# no ip flow ingress
```

**Related Commands**

Command	Description
<b>show ip cache flow</b>	Displays a summary of the NetFlow accounting statistics.
<b>show ip cache verbose flow</b>	Displays a detailed summary of the NetFlow accounting statistics.
<b>ip flow ingress</b>	Enables NetFlow (ingress) accounting for traffic arriving on an interface.



## mask (IPv4) through top

---

- [mask \(IPv4\), page 107](#)
- [mask, page 111](#)
- [match \(NetFlow\), page 113](#)
- [mls aging fast, page 120](#)
- [mls aging long, page 122](#)
- [mls aging normal, page 123](#)
- [mls exclude acl-deny, page 124](#)
- [mls flow, page 125](#)
- [mls ip nat netflow-frag-l4-zero, page 127](#)
- [mls nde flow, page 128](#)
- [mls nde interface, page 130](#)
- [mls nde sender, page 132](#)
- [mls netflow, page 134](#)
- [mls netflow interface, page 136](#)
- [mls netflow maximum-flows, page 137](#)
- [mls netflow sampling, page 139](#)
- [mls netflow usage notify, page 141](#)
- [mls sampling, page 143](#)
- [mode \(flow sampler configuration\), page 146](#)
- [mpls netflow egress, page 149](#)
- [netflow-sampler, page 151](#)
- [platform netflow rp sampling scale, page 155](#)
- [reliability \(NetFlow SCTP\), page 157](#)
- [show flow-sampler, page 159](#)

- [show fm nat netflow data](#), page 161
- [show fm netflow](#), page 163
- [show ip cache flow](#), page 165
- [show ip cache flow aggregation](#), page 172
- [show ip cache verbose flow](#), page 180
- [show ip cache verbose flow aggregation](#), page 192
- [show ip flow export](#), page 200
- [show ip flow top](#), page 211
- [show ip flow top-talkers](#), page 212
- [show mls ip non-static](#), page 233
- [show mls ip routes](#), page 235
- [show mls ip static](#), page 237
- [show mls nde](#), page 239
- [show mls netflow](#), page 241
- [show mls netflow ip](#), page 246
- [show mls netflow ipv6](#), page 252
- [show mls netflow ip dynamic](#), page 256
- [show mls netflow ip routes](#), page 258
- [show mls netflow ip sw-installed](#), page 260
- [show mls netflow ipx](#), page 262
- [show mls sampling](#), page 264
- [sort-by](#), page 265
- [top](#), page 268



## mask (IPv4)

To specify the source or destination prefix mask for a NetFlow accounting prefix aggregation cache, use the **mask** command in aggregation cache configuration mode. To disable the source or destination mask, use the **no** form of this command.

**mask** [*destination*| *source*] **minimum** *value*

**no mask** [*destination*| *source*] **minimum** *value*

### Syntax Description

<b>destination</b>	Specifies the destination mask for a NetFlow accounting aggregation cache.
<b>source</b>	Specifies the source mask for a NetFlow accounting aggregation cache.
<b>minimum</b>	Configures the minimum value for the mask.
<i>value</i>	Specifies the value for the mask. Range is from 1 to 32.

### Command Default

The default value of the minimum source or destination mask is 0.

### Command Modes

NetFlow aggregation cache configuration

### Command History

Release	Modification
12.1(2)T	This command was introduced.
12.2(14)S	This command was integrated into Cisco IOS Release 12.2(14)S.
12.2(27)SBC	This command was integrated into Cisco IOS Release 12.2(27)SBC.
12.2(18)SXF	This command was integrated into Cisco IOS Release 12.2(18)SXF.
12.2(33)SRA	This command was integrated into Cisco IOS Release 12.2(33)SRA.

### Usage Guidelines

You must have NetFlow accounting configured on your router before you can use this command.

The NetFlow accounting minimum prefix mask allows you to set a minimum mask size for the traffic that will be added to the NetFlow aggregation cache. The source or destination IP address (depending on the type of aggregation cache that you are configuring) is ANDed with the larger of the two masks (the mask that you

enter with the **mask** command and the mask in the IP routing table) to determine if the traffic should be added to the aggregation cache that you are configuring.

To enable the minimum prefix mask for a particular aggregation cache, configure the desired minimum mask value using the NetFlow aggregation cache commands. The minimum mask value in the range of 1-32 is used by the router defines the granularity of the NetFlow data that is collected:

- For coarse NetFlow collection granularity, select a low minimum mask value.
- For fine NetFlow collection granularity, select a high minimum mask value.

Specifying the minimum value for the source or destination mask of a NetFlow accounting aggregation cache is permitted only for the following NetFlow aggregation cache types:

- Destination prefix aggregation (destination mask only)
- Destination prefix TOS aggregation (destination mask only)
- Prefix aggregation (source and destination mask)
- Prefix-port aggregation (source and destination mask)
- Prefix-TOS aggregation (source and destination mask)
- Source prefix aggregation (source mask only)
- Source prefix TOS aggregation (source mask only)

## Examples

### Examples

The following example shows how to configure the source-prefix aggregation cache:

```
Router(config)# ip flow-aggregation cache source-prefix
Router(config-flow-cache)# enable
```

The following output from the **show ip cache flow aggregation source-prefix** command shows that, with no minimum mask configured, nine flows are included in the NetFlow source prefix aggregation cache:

```
Router# show ip cache flow aggregation source-prefix
IP Flow Switching Cache, 278544 bytes
 9 active, 4087 inactive, 18 added
950 aged polls, 0 flow alloc failures
Active flows timeout in 30 minutes
Inactive flows timeout in 15 seconds
IP Sub Flow Cache, 21640 bytes
 9 active, 1015 inactive, 18 added, 18 added to flow
 0 alloc failures, 0 force free
 1 chunk, 1 chunk added
```

Src If	Src Prefix	Msk	AS	Flows	Pkts	B/Pk	Active
Et0/0.1	10.10.10.0	/24	0	4	668	762	179.9
Et0/0.1	10.10.10.0	/24	0	4	668	762	180.8
Et0/0.1	10.10.11.0	/24	0	4	668	1115	180.9
Et0/0.1	10.10.11.0	/24	0	4	668	1115	181.9
Et0/0.1	10.1.0.0	/16	0	4	668	1140	179.9
Et0/0.1	10.1.0.0	/16	0	4	668	1140	179.9
Et0/0.1	172.16.6.0	/24	0	1	6	52	138.4
Et0/0.1	172.16.1.0	/24	0	8	1338	1140	182.1
Et0/0.1	172.16.1.0	/24	0	8	1339	1140	181.0

```
Router#
```

The following example shows how to configure the source-prefix aggregation cache using a minimum source mask of 8:

```
Router(config)# ip flow-aggregation cache source-prefix
Router(config-flow-cache)# mask source minimum 8
Router(config-flow-cache)# enable
```

The following output from the **show ip cache flow aggregation source-prefix** command shows that with a minimum mask of 8 configured, only five flows from the same traffic used in the previous example are included in the NetFlow source prefix aggregation cache:

```
Router# show ip cache flow aggregation source-prefix
IP Flow Switching Cache, 278544 bytes
  5 active, 4091 inactive, 41 added
  3021 ager polls, 0 flow alloc failures
  Active flows timeout in 30 minutes
  Inactive flows timeout in 15 seconds
IP Sub Flow Cache, 21640 bytes
  5 active, 1019 inactive, 59 added, 59 added to flow
  0 alloc failures, 0 force free
  1 chunk, 7 chunks added
Minimum source mask is configured to /8
Src If      Src Prefix      Msk AS      Flows Pkts B/Pk  Active
Et0/0.1    10.0.0.0        /8  0          12   681  1007   64.8
Et0/0.1    172.16.6.0      /24 0           1     3    52    56.1
Et0/0.1    10.0.0.0        /8  0          12   683  1006   64.8
Et0/0.1    172.16.1.0     /24 0           8   450  1140   61.8
Et0/0.1    172.16.1.0     /24 0           8   448  1140   61.5
Router#
```

## Examples

The following example shows how to configure the destination-prefix aggregation cache:

```
Router(config)# ip flow-aggregation cache destination-prefix
Router(config-flow-cache)# enable
```

The following output from the **show ip cache flow aggregation destination-prefix** command shows that, with no minimum mask configured, only two flows are included in the NetFlow source prefix aggregation cache:

```
Router# show ip cache flow aggregation destination-prefix
IP Flow Switching Cache, 278544 bytes
  3 active, 4093 inactive, 3 added
  4841 ager polls, 0 flow alloc failures
  Active flows timeout in 30 minutes
  Inactive flows timeout in 15 seconds
IP Sub Flow Cache, 21640 bytes
  3 active, 1021 inactive, 9 added, 9 added to flow
  0 alloc failures, 0 force free
  1 chunk, 1 chunk added
Dst If      Dst Prefix      Msk AS      Flows Pkts B/Pk  Active
Et1/0.1    172.16.10.0     /24 0          120  6737  1059   371.0
Et1/0.1    172.16.10.0     /24 0          120  6739  1059   370.9
```

The following example shows how to configure the destination-prefix aggregation cache using a minimum source mask of 32:

```
Router(config)# ip flow-aggregation cache destination-prefix
Router(config-flow-cache)# mask source minimum 32
Router(config-flow-cache)# enable
```

The following output from the **show ip cache flow aggregation destination-prefix** command shows that, with a minimum mask of 32 configured, 20 flows from the same traffic used in the previous example are included in the NetFlow source prefix aggregation cache:

```
Router# show ip cache flow aggregation destination-prefix
```

```

IP Flow Switching Cache, 278544 bytes
 20 active, 4076 inactive, 23 added
4984 aged polls, 0 flow alloc failures
Active flows timeout in 30 minutes
Inactive flows timeout in 15 seconds
IP Sub Flow Cache, 21640 bytes
 20 active, 1004 inactive, 29 added, 29 added to flow
 0 alloc failures, 0 force free
 1 chunk, 2 chunks added
Minimum destination mask is configured to /32
Dst If      Dst Prefix      Msk AS      Flows  Pkts B/Pk  Active
Et1/0.1    172.16.10.12   /32 0         1     57 1140  60.6
Et1/0.1    172.16.10.12   /32 0         1     57 1140  60.6
Et1/0.1    172.16.10.14   /32 0         1     57 1140  60.6
Et1/0.1    172.16.10.9    /32 0         1     57 1140  60.6
Et1/0.1    172.16.10.11   /32 0         1     57 1140  60.6
Et1/0.1    172.16.10.10   /32 0         1     57 1140  60.6
Et1/0.1    172.16.10.11   /32 0         1     57 1140  60.6
Et1/0.1    172.16.10.10   /32 0         1     57 1140  60.6
Et1/0.1    172.16.10.5    /32 0         1     56 1040  59.5
Et1/0.1    172.16.10.4    /32 0         1     56  940  59.5
Et1/0.1    172.16.10.4    /32 0         1     56  940  59.5
Et1/0.1    172.16.10.7    /32 0         1     57 1140  60.6
Et1/0.1    172.16.10.7    /32 0         1     57 1140  60.6
Et1/0.1    172.16.10.1    /32 0         1     56  628  59.5
Et1/0.1    172.16.10.2    /32 0         1     56  640  59.5
Et1/0.1    172.16.10.17   /32 0         1     56 1140  59.5
Et1/0.1    172.16.10.17   /32 0         1     56 1140  59.5
Et1/0.1    172.16.10.18   /32 0         1     56 1140  59.5
Et1/0.1    172.16.10.19   /32 0         1     56 1140  59.5
Et1/0.1    172.16.10.18   /32 0         1     56 1140  59.5

```

## Related Commands

Command	Description
<b>cache</b>	Defines operational parameters for NetFlow accounting aggregation caches.
<b>enabled (aggregation cache)</b>	Enables a NetFlow accounting aggregation cache.
<b>export destination (aggregation cache)</b>	Enables the exporting of NetFlow accounting information from NetFlow aggregation caches.
<b>ip flow-aggregation cache</b>	Enables NetFlow accounting aggregation cache schemes.
<b>show ip cache flow aggregation</b>	Displays the NetFlow accounting aggregation cache statistics.
<b>show ip cache flow</b>	Displays a summary of the NetFlow accounting statistics.
<b>show ip cache verbose flow</b>	Displays a detailed summary of the NetFlow accounting statistics.
<b>show ip flow interface</b>	Displays NetFlow accounting configuration for interfaces.

# mask

To specify the destination or source mask, use the **mask** command in aggregation cache configuration mode. To disable the destination mask, use the **no** form of this command.

**mask** {*destination*| *source*} **minimum** *value*

**no mask destination minimum** *value*

## Syntax Description

<b>destination</b>	Specifies that the destination mask is to be used for determining the aggregation cache.
<b>source</b>	Specifies that the source mask is to be used for determining the aggregation cache.
<i>value</i>	Specifies the number of bits to record from the source or destination mask. Range is from 1 to 32.

## Command Default

The default value of the minimum mask is zero.

## Command Modes

Aggregation cache configuration

## Command History

Release	Modification
12.1(2)T	This command was introduced.
12.3(7)T	Support was added for IPv6 source and destination addresses to be used for cache aggregation.
12.2(30)S	This command was integrated into Cisco IOS Release 12.2(30)S.
12.2(33)SRA	This command was integrated into Cisco IOS Release 12.2(33)SRA.
12.2(33)SXH	This command was integrated into Cisco IOS Release 12.2(33)SXH.

## Usage Guidelines

This command is only available with router-based aggregation. Minimum masking capability is not available if router-based aggregation is not enabled.

## Examples

The following example shows how to configure the mask to use the destination-prefix as the aggregation cache scheme with a minimum mask value of 32:

```
Router(config)# ipv6 flow-aggregation cache destination-prefix  
Router(config-flow-cache)# mask destination minimum 32
```

## Related Commands

Command	Description
<b>ip flow-aggregation cache</b>	Enables aggregation cache configuration mode.
<b>ipv6 flow-aggregation cache</b>	Enables aggregation cache configuration mode for IPv6 traffic.
<b>show ip cache flow aggregation</b>	Displays the aggregation cache configuration.
<b>show ipv6 cache flow aggregation</b>	Displays the aggregation cache configuration for IPv6 NetFlow configurations.

## match (NetFlow)

To specify match criteria for the NetFlow top talkers (unaggregated top flows), use the **match** command in NetFlow top talkers configuration mode. To remove match criteria for NetFlow top talkers, use the **no** form of this command.

```
match {byte-range [max-byte-number min-byte-number| max max-byte-number| min min-byte-number]|
class-map map-name| destination [address ip-address [mask slash nn]]| as as-number| port [max-port-number
min-port-number| max max-port-number| min min-port-number]| direction [ingress| egress]| flow-sampler
flow-sampler-name| input-interface interface-type interface-number| nexthop-address ip-address [mask
slash nn]| output-interface interface-type interface-number| packet-range [max-packets min-packets| max
max-packets| min min-packets]| protocol [protocol-number| udp| tcp]| source [address ip-address [mask
slash nn]]| as as-number| port [max-port-number min-port-number| max max-port-number| min
min-port-number]| tos [tos-byte| dscp dscp| precedence precedence]}
```

```
no match {byte-range| class-map| destination [address| as] | port] | direction| flow-sampler| input-interface|
nexthop-address| output-interface| packet-range| protocol| source [address| as] | port] | tos}
```

### Syntax Description

<b>byte-range</b>	The match criterion is based on the size in bytes of the IP datagrams in the flows.
<i>max-byte-number min-byte-number</i>	Range of sizes for IP datagrams to be matched in bytes. Range: 1-4294967295.
<b>max</b> <i>max-byte-number</i>	Maximum size for IP datagrams to be matched in bytes. Range: 1-4294967295.
<b>min</b> <i>min-byte-number</i>	Minimum size for IP datagrams to be matched in bytes. Range: 1-4294967295.
<b>class-map</b>	The match criterion is based on a class map.
<i>map-name</i>	Name of the class map to be matched.
<b>destination address</b>	The match criterion is based on the destination IP address.
<i>ip-address</i>	The destination IP address to be matched.
<i>mask</i>	Address mask, in dotted decimal format.
<i>/nn</i>	Address mask as entered in classless interdomain routing (CIDR) format. An address mask of 255.255.255.0 is equivalent to a /24 mask in CIDR format.
<b>destination as</b>	The match criterion is based on the destination autonomous system.

<i>as-number</i>	Autonomous system number to be matched.
<b>destination port</b>	The match criterion is based on the destination port.
<i>max-port-number min-port-number</i>	Range of port numbers for IP datagrams to be matched. Range: 0-65535.
<b>max</b> <i>max-port-number</i>	Maximum port number for IP datagrams to be matched. Range: 0-65535.
<b>min</b> <i>min-port-number</i>	Minimum port number for IP datagrams to be matched. Range: 0-65535.
<b>direction</b>	Direction of the flow to be matched.
<b>ingress</b>	The match criterion is based on ingress flows.
<b>egress</b>	The match criterion is based on egress flows.
<b>flow-sampler</b>	The match criterion is based on Top Talker sampling.
<i>flow-sampler-name</i>	Name of the Top Talker sampler to be matched.
<b>input-interface</b>	The match criterion is based on the input interface.
<i>interface-type interface-number</i>	The input interface to be used
<b>nexthop address</b>	The match criterion is based on the next-hop IP address.
<i>ip-address</i>	The next-hop IP address to be matched.
<i>mask</i>	Address mask, in dotted decimal format.
<i>/nn</i>	Address mask as entered in classless interdomain routing (CIDR) format. An address mask of 255.255.255.0 is equivalent to a /24 mask in CIDR format.
<b>output-interface</b>	The match criterion is based on the output interface.
<i>interface-type interface-number</i>	The output interface to be used
<b>packet-range</b>	The match criterion is based on the number of IP datagrams in the flows.
<i>max-packets min-packets</i>	Range of number of packets in the flows to be matched. Range: 1-4294967295.



<b>max</b> <i>max-packet</i>	Maximum number of packets in the flows to be matched. Range: 1-4294967295.
<b>min</b> <i>min-packets</i>	Minimum number of packets in the flows to be matched. Range: 1-4294967295.
<b>protocol</b>	The match criterion is based on protocol.
<i>protocol-number</i>	Protocol number to be matched. Range: 0 to 255.
<b>tcp</b>	Protocol number to be matched as TCP.
<b>udp</b>	Protocol number to be matched as UDP.
<b>source address</b>	The match criterion is based on the source IP address.
<i>ip-address</i>	The source IP address to be matched.
<i>mask</i>	Address mask, in dotted decimal format.
<i>/nn</i>	Address mask as entered in classless interdomain routing (CIDR) format. An address mask of 255.255.255.0 is equivalent to a /24 mask in CIDR format.
<b>source as</b>	The match criterion is based on the source autonomous system.
<i>as-number</i>	Autonomous system number to be matched.
<b>source port</b>	The match criterion is based on the source port.
<i>max-port-number min-port-number</i>	Range of port numbers for IP datagrams to be matched. Range: 0-65535.
<b>max</b> <i>max-port-number</i>	Maximum port number for IP datagrams to be matched. Range: 0-65535.
<b>min</b> <i>min-port-number</i>	Minimum port number for IP datagrams to be matched. Range: 0-65535.
<b>tos</b>	The match criterion is based on type of service (ToS).
<i>tos-value</i>	ToS to be matched.
<b>dscp</b> <i>dscp-value</i>	Differentiated services code point (DSCP) value to be matched.
<b>precedence</b> <i>precedence-value</i>	Precedence value to be matched.

**Command Default**

No matching criteria are specified by default. All top talkers are displayed.

**Command Modes**

NetFlow top talkers configuration

**Command History**

Release	Modification
12.2(25)S	This command was introduced.
12.3(11)T	This command was integrated into Cisco IOS Release 12.3(11)T. The <b>direction</b> , <b>ingress</b> , and <b>egress</b> keywords were added.
12.2(27)SBC	This command was integrated into Cisco IOS Release 12.2(27)SBC
12.2(33)SRA	This command was integrated into Cisco IOS Release 12.2(33)SRA.
12.2SX	This command is supported in the Cisco IOS Release 12.2SX train. Support in a specific 12.2SX release of this train depends on your feature set, platform, and platform hardware.

**Usage Guidelines****Configuring NetFlow Top Talkers**

You must enable NetFlow on at least one interface in the router; and configure NetFlow top talkers before you can use the **show ip flow top-talkers** command to display the traffic statistics for the unaggregated top flows in the network. NetFlow top talkers also requires that you configure the **sort-by** and **top** commands.

**Specifying Match Criteria**

Use this command to specify match criteria for NetFlow top talkers. Using matching criteria is useful to restrict the list of top talkers.

If you are using a MIB and using simple network management protocol (SNMP) commands to configure this feature, refer to the table below for a mapping of the command-line interface (CLI) commands to the MIB SNMP commands:

**Table 4: Router CLI Commands and Equivalent SNMP Commands**

Router CLI Command	SNMP Command
<b>match source address</b> [ <i>ip-address</i> ][ <i>mask</i>   / <i>nn</i> ]	<b>cnfTopFlowsMatchSrcAddress</b> <i>ip-address</i> <b>cnfTopFlowsMatchSrcAddressType</b> <i>type</i> <a href="#">1</a> <b>cnfTopFlowsMatchSrcAddressMask</b> <i>mask</i>
<b>match destination address</b> [ <i>ip-address</i> ][ <i>mask</i>   / <i>nn</i> ]	<b>cnfTopFlowsMatchDstAddress</b> <i>ip-address</i> <b>cnfTopFlowsMatchDstAddressType</b> <i>type</i> <a href="#">1</a> <b>cnfTopFlowsMatchDstAddressMask</b> <i>mask</i>

Router CLI Command	SNMP Command
<b>match nexthop address</b> <i>[[ip-address][mask   / nn]]</i>	<b>cnfTopFlowsMatchNhAddress</b> <i>ip-address</i> <b>cnfTopFlowsMatchNhAddressType</b> <i>type</i> <b>cnfTopFlowsMatchNhAddressMask</b> <i>mask</i>
<b>match source port min</b> <i>port</i>	<b>cnfTopFlowsMatchSrcPortLo</b> <i>port</i>
<b>match source port max</b> <i>port</i>	<b>cnfTopFlowsMatchSrcPortHi</b> <i>port</i>
<b>match destination port min</b> <i>port</i>	<b>cnfTopFlowsMatchDstPortLo</b> <i>port</i>
<b>match destination port max</b> <i>port</i>	<b>cnfTopFlowsMatchDstPortHi</b> <i>port</i>
<b>match source as</b> <i>as-number</i>	<b>cnfTopFlowsMatchSrcAS</b> <i>as-number</i>
<b>match destination as</b> <i>as-number</i>	<b>cnfTopFlowsMatchDstAS</b> <i>as-number</i>
<b>match input-interface</b> <i>interface</i>	<b>cnfTopFlowsMatchInputIf</b> <i>interface</i>
<b>match output-interface</b> <i>interface</i>	<b>cnfTopFlowsMatchOutputIf</b> <i>interface</i>
<b>match tos</b> [ <i>tos-value</i>   <b>dscp</b> <i>dscp-value</i>   <b>precedence</b> <i>precedence-value</i> ]	<b>cnfTopFlowsMatchTOSByte</b> <i>tos-value</i>
<b>match protocol</b> [ <i>protocol-number</i>   <b>tcp</b>   <b>udp</b> ]	<b>cnfTopFlowsMatchProtocol</b> <i>protocol-number</i>
<b>match flow-sampler</b> <i>flow-sampler-name</i>	<b>cnfTopFlowsMatchSampler</b> <i>flow-sampler-name</i>
<b>match class-map</b> <i>class</i>	<b>cnfTopFlowsMatchClass</b> <i>class</i>
<b>match packet-range min</b> <i>minimum-range</i>	<b>cnfTopFlowsMatchMinPackets</b> <i>minimum-range</i>
<b>match packet-range max</b> <i>maximum-range</i>	<b>cnfTopFlowsMatchMaxPackets</b> <i>maximum-range</i>
<b>match byte-range min</b> <i>minimum-range</i>	<b>cnfTopFlowsMatchMinBytes</b> <i>minimum-range</i>
<b>match byte-range max</b> <i>maximum-range</i>	<b>cnfTopFlowsMatchMaxPackets</b> <i>maximum-range</i>
<b>direction</b> [ <b>ingress</b>   <b>egress</b> ]	<b>cnfTopFlowsMatchDirection</b> [ <b>flowDirNone(0)</b>   <b>flowDirIngress(1)</b>   <b>flowDirEgress(2)</b> ]

<sup>1</sup> The only IP version type that is currently supported is IPv4 (type 1).

## Examples

The following example shows how you enter NetFlow top talkers configuration mode and specify that the top talkers are to contain the following characteristics:

- The list of top talkers will have a source IP address that begins with 10.10.0.0 and subnet a mask of 255.255.0.0 (/16).

```
Router(config)# ip flow-top-talkers
Router(config-flow-top-talkers)# match source address 10.10.0.0/16
Router(config-flow-top-talkers)# top 4
Router(config-flow-top-talkers)# sort-by bytes
```

The following example shows the output of the **show ip flow top talkers** command when the configuration from the previous example is used:

```
Router# show ip flow top-talkers

SrcIf          SrcIPAddress   DstIf          DstIPAddress   Pr SrcP DstP Bytes
Et2/0          10.10.11.3     Et1/0.1        172.16.10.7    06 0041 0041 30K
Et0/0.1        10.10.11.4     Et1/0.1        172.16.10.8    06 0041 0041 30K
Et3/0          10.10.11.2     Et1/0.1        172.16.10.6    06 0041 0041 29K
Et3/0          10.10.18.1     Null           172.16.11.5    11 00A1 00A1 28K
4 of 4 top talkers shown. 10 of 27 flows matched
```

The following example shows how you enter NetFlow top talkers configuration mode and specify that the top talkers are to contain the following characteristics:

- The list of top talkers will have a source IP address that begins with 10.10.0.0 and subnet mask of 255.255.0.0 (/16).
- The list of top talkers will have a destination IP address that begins with 172.16.11.0 and a subnet mask of 255.255.255.0 (/24)

```
Router(config)# ip flow-top-talkers
Router(config-flow-top-talkers)# match source address 10.10.0.0/16
Router(config-flow-top-talkers)# match destination address 172.16.11.0/24
Router(config-flow-top-talkers)# top 4
Router(config-flow-top-talkers)# sort-by bytes
```

The following example shows the output of the **show ip flow top talkers** command when the configuration from the previous example is used:

```
Router# show ip flow top-talkers

SrcIf          SrcIPAddress   DstIf          DstIPAddress   Pr SrcP DstP Bytes
Et3/0          10.10.18.1     Null           172.16.11.5    11 00A1 00A1 67K
Et3/0          10.10.19.1     Null           172.16.11.6    11 00A2 00A2 67K
2 of 4 top talkers shown. 2 of 30 flows matched
```

## Related Commands

Command	Description
<b>cache-timeout</b>	Specifies the length of time for which the list of top talkers (heaviest traffic patterns and most-used applications in the network) for the NetFlow MIB and top talkers feature is retained.
<b>ip flow-top-talkers</b>	Enters the configuration mode for the NetFlow MIB and top talkers (heaviest traffic patterns and most-used applications in the network) feature.
<b>show ip cache flow</b>	Displays a summary of the NetFlow accounting statistics.

<b>Command</b>	<b>Description</b>
<b>show ip cache verbose flow</b>	Displays a detailed summary of the NetFlow accounting statistics.
<b>show ip flow interface</b>	Displays NetFlow accounting configuration for interfaces.
<b>show ip flow top-talkers</b>	Displays the statistics for the top talkers (heaviest traffic patterns and most-used applications in the network).
<b>sort-by</b>	Specifies the sorting criterion for top talkers (heaviest traffic patterns and most-used applications in the network) to be displayed for the NetFlow MIB and top talkers feature.
<b>top</b>	Specifies the maximum number of top talkers (heaviest traffic patterns and most-used applications in the network) to be displayed for the NetFlow MIB and top talkers feature.

## mls aging fast

To configure the fast-aging time for unicast entries in the Layer 3 table, use the **mls aging fast** command in global configuration mode. To restore the MLS fast-aging time to the default settings, use the **no** form of this command.

**mls aging fast** [**threshold** *packet-count* [**time** *seconds*]]

**mls aging fast** [**time** *seconds* [**threshold** *packet-count*]]

**no mls aging fast**

### Syntax Description

<b>threshold</b> <i>packet-count</i>	(Optional) Specifies the packet count of the fast-aging threshold for Layer 3 fast aging; valid values are from 1 to 128.
<b>time</b> <i>seconds</i>	(Optional) Specifies how often entries are checked; valid values are from 1 to 128 seconds.

### Command Default

The defaults are as follows:

- Fast aging is disabled.
- If fast aging is enabled, the default *packet-count* value is 100 packets and the *seconds* default is 32 seconds.

### Command Modes

Global configuration

### Command History

Release	Modification
12.2(14)SX	Support for this command was introduced on the Supervisor Engine 720.
12.2(17d)SXB	Support for this command on the Supervisor Engine 2 was extended to the 12.2 SX release.
12.2(33)SRA	This command was integrated into Cisco IOS Release 12.2(33)SRA.

### Usage Guidelines

This command has no effect when you configure sampled NetFlow. You must disable sampled NetFlow to allow this command to take effect.

**Examples**

This example shows how to configure the MLS fast-aging threshold:

```
Router(config)# mls aging fast threshold 50
Router(config)#
```

**Related Commands**

Command	Description
<b>show mls netflow</b>	Displays configuration information about the NetFlow hardware.

## mls aging long

To configure the long-aging time for unicast entries in the Layer 3 table, use the **mls aging long** command in global configuration mode. To restore the MLS long-aging time to the default settings, use the **no** form of this command.

**mls aging long** *seconds*

**no mls aging long**

### Syntax Description

<i>seconds</i>	Layer 3 long-aging timeout ; valid values are from 64 to 1920 seconds.
----------------	--

### Command Default

1920 seconds

### Command Modes

Global configuration

### Command History

Release	Modification
12.2(14)SX	Support for this command was introduced on the Supervisor Engine 720.
12.2(17d)SXB	Support for this command on the Supervisor Engine 2 was extended to the 12.2 SX release.
12.2(33)SRA	This command was integrated into Cisco IOS Release 12.2(33)SRA.

### Usage Guidelines

This command has no effect when you configure sampled NetFlow. You must disable sampled NetFlow to allow this command to take effect.

### Examples

This example shows how to configure the MLS long-aging threshold:

```
Router(config)# mls aging long 800
Router(config)#
```

### Related Commands

Command	Description
<b>show mls netflow</b>	Displays configuration information about the NetFlow hardware.



## mls aging normal

To configure the normal-aging time for unicast entries in the Layer 3 table, use the **mls aging normal** command in global configuration mode. To restore the MLS normal-aging time to the default settings, use the **no** form of this command.

**mls aging normal** *seconds*

**no mls aging normal**

### Syntax Description

<i>seconds</i>	Normal aging timeout for Layer 3; valid values are from 32 to 4092 seconds.
----------------	---

### Command Default

300 seconds

### Command Modes

Global configuration

### Command History

Release	Modification
12.2(14)SX	Support for this command was introduced on the Supervisor Engine 720.
12.2(17d)SXB	Support for this command on the Supervisor Engine 2 was extended to the 12.2 SX release.
12.2(33)SRA	This command was integrated into Cisco IOS Release 12.2(33)SRA.

### Usage Guidelines

This command has no effect when you configure sampled NetFlow. You must disable sampled NetFlow to allow this command to take effect.

### Examples

This example shows how to configure the MLS normal-aging threshold:

```
Router(config)# mls aging normal 200
Router(config)#
```

### Related Commands

Command	Description
<b>show mls netflow</b>	Displays configuration information about the NetFlow hardware.

## mls exclude acl-deny

To disable the creation of NetFlow entries for ingress ACL denied flows, use the **mls exclude acl-deny** command in global configuration mode. To disable the creation of NetFlow entries for ACL denied flows, use the **no** form of this command.

**mls exclude acl-deny**

**no mls exclude acl-deny**

**Syntax Description** This command has no arguments or keywords.

**Command Default** By default, the creation of NetFlow entries for ACL denied flows is enabled.

**Command Modes** Global configuration

Command History	Release	Modification
	12.2(33)SXH	This command was integrated into Cisco IOS Release 12.2(33)SXH.

**Examples** This example shows how to disable the creation of NetFlow entries for ACL denied flows:

```
Router(config)#
mls exclude acl-deny
Router(config)#
```

### Related Commands

Command	Description
<b>show mls netflow ip</b>	Displays NetFlow IP entries.
<b>show mls netflow usage</b>	Displays NetFlow table usage.

## mls flow

To configure the flow mask for NDE, use the **mls flow** command in global configuration mode. To specify a null flow mask, use the **no** form of this command. To restore the default flow mask, use the **default** form of this command.

```
mls flow {ip| ipv6} {destination| destination-source| full| interface-destination-source| interface-full|
source}
```

```
no mls flow {ip| ipv6}
```

```
default mls flow {ip| ipv6}
```

### Syntax Description

<b>ip</b>	Enables the flow mask for MLS IP packets.
<b>ipv6</b>	Enables the flow mask for MLS IPv6 packets.
<b>destination</b>	Uses the destination IP address as the key to the Layer 3 table.
<b>destination-source</b>	Uses the destination and the source IP address as the key to the Layer 3 table.
<b>full</b>	Uses the source and destination IP address, the IP protocol (UDP or TCP), and the source and destination port numbers as the keys to the Layer 3 table.
<b>interface-destination-source</b>	Uses all the information in the destination and source flow mask and the source VLAN number as the keys to the Layer 3 table.
<b>interface-full</b>	Uses all the information in the full flow mask and the source VLAN number as the keys to the Layer 3 table.
<b>source</b>	Uses the source IP address as the key to the Layer 3 table.

### Command Default

The defaults are as follows:

- For Cisco 7600 series routers that are configured with a Supervisor Engine 2, the default flow mask is **destination**.
- For Cisco 7600 series routers that are configured with a Supervisor Engine 720, the default flow mask is null.
- For IPv4, the default flow mask is null.

- For IPv6, the default flow mask is null.

**Command Modes**

Global configuration

**Command History**

Release	Modification
12.2(14)SX	Support for this command was introduced on the Supervisor Engine 720.
12.2(17b)SXA	This command was changed to support the <b>ipv6</b> keyword.
12.2(17d)SXB	Support for this command on the Supervisor Engine 2 was extended to the 12.2 SX release.
12.2(33)SRA	This command was integrated into Cisco IOS Release 12.2(33)SRA.
12.2(33)SRB	This command was changed to accommodate per-interface NetFlow.

**Usage Guidelines**

This command collects statistics for the supervisor engine.

In Cisco IOS Release 12.2(33)SRB and later, the interface-destination-source and interface-full flow masks are the only masks supported for IPv4 traffic. This change was made to accommodate the per-interface NetFlow feature. If other flow mask values are used, the router upgrades them as follows:

- Source, destination, and destination-source flow masks are treated as interface-destination-source.
- Full flow masks are treated as interface-full.

**Note**

To ensure that the Optimized Edge Routing passive-monitoring feature can use NetFlow, you must change the IPv4 flow mask to interface-full.

**Examples**

This example shows how to set the desired flow mask used to populate the hardware cache for IPv4 NetFlow Data Export:

```
Router(config)#
mls flow ip full
Router(config)#
```

**Related Commands**

Command	Description
<b>show mls netflow</b>	Displays configuration information about the NetFlow hardware.

## mls ip nat netflow-frag-l4-zero

To zero out the Layer 4 information in the NetFlow lookup table for fragmented packets, use the `mls ip nat netflow-frag-l4-zero` command in global configuration mode. To restore the default settings, use the `no` form of this command.

**mls ip nat netflow-frag-l4-zero**

**no mls ip nat netflow-frag-l4-zero**

**Syntax Description** This command has no arguments or keywords.

**Command Default** This command has no default settings.

**Command Modes** Global configuration

Command History	Release	Modification
	12.2(17d)SXB	Support for this command was introduced on the Supervisor Engine 720 and the Supervisor Engine 2.
	12.2(33)SRA	This command was integrated into Cisco IOS Release 12.2(33)SRA.

**Usage Guidelines** This command is supported in PFC3BXL or PFC3B mode only.

Use the `mls ip nat netflow-frag-l4-zero` command to prevent matching the first fragment to the NetFlow shortcut (normal operation) that is sent to the software. The next fragments that are sent to the software are translated based on the Layer 4 port information from the first fragment. The translation based on the Layer 4 port information from the first fragment occurs because there are no fragment bits for matching in the NetFlow key.

When there is a large feature configuration on an interface that requires a large number of ACL TCAM entries/masks that are programmed in TCAM, if the interface is configured as a NAT-inside interface, the feature configuration may not fit in the ACL TCAM and the traffic on the interface may get switched in the software.

**Examples** This example shows how to zero out the Layer 4 information in the NetFlow lookup table for fragmented packets:

```
Router (config)#
mls ip nat netflow-frag-l4-zero
Router (config)#
```

## mls nde flow

To specify the filter options for NDE, use the **mls nde flow** command in global configuration mode. To clear the NDE flow filter and reset the filter to the default settings, use the **no** form of this command.

```
mls nde flow {include|exclude} {dest-port port-num|destination ip-addr ip-mask|protocol {tcp|udp}|source ip-addr ip-mask|src-port port-num}
```

```
no mls nde flow {include|exclude}
```

### Syntax Description

<b>include</b>	Allows exporting of all flows except the flows matching the given filter.
<b>exclude</b>	Allows exporting of all flows matching the given filter.
<b>dest-port</b> <i>port-num</i>	Specifies the destination port to filter; valid values are from 1 to 100.
<b>destination</b> <i>ip-addr ip-mask</i>	Specifies a destination IP address and mask to filter.
<b>protocol</b>	Specifies the protocol to include or exclude.
<b>tcp</b>	Includes or excludes TCP.
<b>udp</b>	Includes or excludes UDP.
<b>source</b> <i>ip-addr ip-mask</i>	Specifies a source IP address and subnet mask bit to filter.
<b>src-port</b> <i>port-num</i>	Specifies the source port to filter.

### Command Default

The defaults are as follows:

- All expired flows are exported until the filter is specified explicitly.
- Interface export is disabled (**no mls nde interface**).

### Command Modes

Global configuration

### Command History

Release	Modification
12.2(14)SX	Support for this command was introduced on the Supervisor Engine 720.

Release	Modification
12.2(17d)SXB	Support for this command on the Supervisor Engine 2 was extended to the 12.2 SX release.
12.2(33)SRA	This command was integrated into Cisco IOS Release 12.2(33)SRA.

### Usage Guidelines

The **mls nde flow** command adds filtering to the NDE. The expired flows matching the specified criteria are exported. These values are stored in NVRAM and do not clear when NDE is disabled. If any option is not specified in this command, it is treated as a wildcard. The NDE filter in NVRAM does not clear when you disable NDE.

Only one filter can be active at a time. If you do not enter the **exclude** or **include** keyword, the filter is assumed to be an inclusion filter.

The include and exclude filters are stored in NVRAM and are not removed if you disable NDE.

*ip-addr maskbits* is the simplified long subnet address format. The mask bits specify the number of bits of the network masks. For example, 172.22.252.00/22 indicates a 22-bit subnet address. The *ip-addr* is a full host address, such as 193.22.253.1/22.

### Examples

This example shows how to specify an interface flow filter so that only expired flows to destination port 23 are exported (assuming that the flow mask is set to ip-flow):

```
Router(config)#
mls nde flow include dest-port 35
Router(config)#
```

### Related Commands

Command	Description
<b>show mls netflow</b>	Displays configuration information about the NetFlow hardware.

## mls nde interface

To populate the additional fields in the NDE packets, use the **mls nde interface** command in interface configuration mode. To disable the population of the additional fields, use the **no** form of this command.

**mls nde interface**

**no mls nde interface**

**Syntax Description** This command has no arguments or keywords.

**Command Default** The defaults are as follows:

- Supervisor Engine 2--Disabled
- Supervisor Engine 720--Enabled

**Command Modes** Interface configuration

### Command History

Release	Modification
12.2(14)SX	Support for this command was introduced on the Supervisor Engine 720.
12.2(17d)SXB	Support for this command on the Supervisor Engine 2 was extended to the 12.2 SX release.
12.2(33)SRA	This command was integrated into Cisco IOS Release 12.2(33)SRA.

### Usage Guidelines

You can configure NDE to populate the following additional fields in the NDE packets:

- Egress interface SNMP index
- Source-autonomous system number
- Destination-autonomous system number
- IP address of the next-hop router

The ingress-interface SNMP index is always populated if the flow mask is interface-full or interface-src-dst.

For detailed information, refer to the “Configuring NDE” chapter of the Cisco 7600 Series Router Cisco IOS Software Configuration Guide .

### Examples

This example shows how to populate the additional fields in the NDE packets:

```
Router(config)#
```



```
mls nde interface
Router(config)#
```

This example shows how to disable the population of the additional fields:

```
Router(config)#
no mls nde interface
Router(config)#
```

### Related Commands

Command	Description
<b>mls netflow</b>	Enables NetFlow to gather statistics.
<b>mls netflow sampling</b>	Enables the sampled NetFlow on an interface.

## mls nde sender

To enable MLS NDE export, use the **mls nde sender** command in global configuration mode. To disable MLS NDE export, use the **no** form of this command.

**mls nde sender** [*version version*]

**no mls nde sender**

### Syntax Description

<b>version</b> <i>version</i>	(Optional) Specifies the NDE version; valid values are <b>5</b> and <b>7</b> .
-------------------------------	--

### Command Default

The defaults are as follows:

- MLS NDE export is disabled.
- *version* is **7**

### Command Modes

Global configuration

### Command History

Release	Modification
12.2(14)SX	Support for this command was introduced on the Supervisor Engine 720.
12.2(17d)SXB	Support for this command on the Supervisor Engine 2 was extended to the 12.2 SX release.
12.2(33)SRA	This command was integrated into Cisco IOS Release 12.2(33)SRA.

### Usage Guidelines

**Note** If MLS NDE export is enabled, do not use version 7.

### Examples

This example shows how to enable MLS NDE export:

```
Router(config)#
 mls nde sender
Router(config)#
```

This example shows how to disable MLS NDE export:

```
Router(config)#
```

```
no mls nde sender
Router(config)#
```

**Related Commands**

Command	Description
<b>show mls nde</b>	Displays information about the NDE hardware-switched flow.

# mls netflow

To enable NetFlow to gather statistics, use the **mls netflow** command in global configuration mode. To disable NetFlow from gathering statistics, use the **no** form of this command.

**mls netflow** [**interface**| **cache**| **usage notify** [*threshold seconds*]]

**no mls netflow** [**interface**| **cache**| **usage notify**]

## Syntax Description

<b>interface</b>	(Optional) Specifies statistics gathering per interface.
<b>cache</b>	(Optional) Caches the total active flow count in the Policy Feature Card (PFC) or Distributed Forwarding Cards (DFCs).
<b>usage notify</b>	(Optional) Sends a notification when NetFlow table usage crosses the configured threshold limit.
<i>threshold</i>	(Optional) Threshold percentage. The range is from 20 to 100.
<i>seconds</i>	(Optional) Time interval in seconds.

## Command Default

NetFlow statistics are enabled.

## Command Modes

Global configuration (config)

## Command History

Release	Modification
12.2(14)SX	This command was introduced on the Supervisor Engine 720.
12.2(17d)SXB	This command was integrated into Cisco IOS Release 12.2(17d)SXB.
12.2(33)SRA	This command was integrated into Cisco IOS Release 12.2(33)SRA.
15.0(1)S1	This command was modified. The <b>cache</b> keyword was added.

## Usage Guidelines

NetFlow gathers statistics from traffic that flows through the Cisco 7600 series router and stores the statistics in the NetFlow table. You can gather the statistics globally based on a protocol or optionally per interface.

If you are not using NetFlow Data Export (NDE) or Cisco IOS features that use the hardware NetFlow table (non-Reverse Path Forwarding [non-RPF] multicast traffic, microflow quality of service [QoS], the Web

Cache Communications Protocol [WCCP], TCP intercept, or reflexive access control lists), you can safely disable the use and maintenance of the hardware NetFlow table using the **no mls netflow** command in global configuration mode.

Use the **cache** keyword to enable NetFlow to cache the total active flow count in the PFC or DFC. If caching is disabled, the active flow count is retrieved from the router, which causes delay affecting Simple Network Management Protocol (SNMP)-based applications. When this option is enabled, the total active count in the PFC or DFC is cached every 30 seconds, and the cached value is used for statistics.

## Examples

The following example shows how to enable NetFlow to gather statistics:

```
Router(config)#
 mls netflow
```

The following example shows how to disable NetFlow from gathering the statistics:

```
Router(config)# no mls netflow
Disabling MLS netflow entry creation.
```

The following example shows how to enable NetFlow to cache the total active flow count:

```
Router(config)#
 mls netflow cache
```

The following example shows how to set the threshold value for NetFlow table utilization:

```
Router(config)#
 mls netflow usage notify 75 500
```

## Related Commands

Command	Description
<b>show mls netflow</b>	Displays configuration information about the NetFlow hardware.

# mls netflow interface

To enable the creation of NetFlow entries on a per-VLAN basis, use the **mls netflow interface** command in global configuration mode. To disable the creation of NetFlow entries, use the **no** form of this command.

**mls netflow interface**

**no mls netflow interface**

**Syntax Description** This command has no arguments or keywords.

**Command Default** Creation of NetFlow entries on a per-VLAN basis disabled.

**Command Modes** Global configuration (config)

Command History	Release	Modification
	12.2(33)SXH	This command was introduced on the Catalyst 6500 series switches.

**Usage Guidelines** Entering the **mls netflow interface** command creates NetFlow entries for all VLANs. NetFlow entries are created both for VLANs on which bridged-flow statistics is enabled and for VLANs on which NetFlow entry creation is enabled.

For example, if you enable Layer 3 per-VLAN entry creation on VLANs 100 and 200 and at the same time you want to enable bridged-flow statistics on VLANs 150 and 250, NetFlow entry creation and bridged-flow statistics are both enabled on all four VLANs. To collect only bridged-flow statistics for VLAN 150 and 250, you must disable the per-VLAN entry creation feature.

**Examples** This example shows how to create NetFlow entries on a per-VLAN basis:

```
Router(config)# mls netflow interface
```

## mls netflow maximum-flows

To configure the maximum flow allocation in the NetFlow table, use the **mls netflow maximum-flows** command in global configuration mode. To return to the default settings, use the **no** form of this command.

**mls netflow maximum-flows** [ *maximum-flows* ]

**no mls netflow maximum-flows**

### Syntax Description

<i>maximum-flows</i>	(Optional) Maximum number of flows; valid values are <b>16, 32, 64, 80, 96, and 128</b> . See the “Usage Guidelines” section for additional information.
----------------------	--

### Command Default

128

### Command Modes

Global configuration

### Command History

Release	Modification
12.2(18)SXD	Support for this command was introduced on the Supervisor Engine 2.
12.2(33)SRA	This command was integrated into Cisco IOS Release 12.2(33)SRA.

### Usage Guidelines

This command is not supported on Cisco 7600 series routers that are configured with a Supervisor Engine 720.

The value that you specify for the maximum number of flows is that value times 1000. For example, if you enter 32, you specify that 32,000 is the maximum number of permitted flows.

### Examples

This example shows how to configure the maximum flow allocation in the NetFlow table:

```
Router(config)#
 mls netflow maximum-flows 96
Router(config)#
```

This example shows how to return to the default setting:

```
Router(config)# no mls netflow maximum-flows
Router(config)#
```

**Related Commands**

Command	Description
<b>show mls netflow table-contention</b>	Displays configuration information at the table contention level for the NetFlow hardware.



# mls netflow sampling

To enable sampled NetFlow on an interface, use the **mls netflow sampling** command in interface configuration mode. To disable sampled NetFlow on an interface, use the **no** form of this command.

**mls netflow sampling**

**no mls netflow sampling**

**Syntax Description** This command has no arguments or keywords.

**Command Default** Disabled

**Command Modes** Interface configuration

Command History	Release	Modification
	12.2(14)SX	Support for this command was introduced on the Supervisor Engine 720.
	12.2(17d)SXB	Support for this command on the Supervisor Engine 2 was extended to the 12.2 SX release.
	12.2(33)SRA	This command was integrated into Cisco IOS Release 12.2(33)SRA.
	12.2(33)SRB	This command was changed to support per-interface NetFlow for IPv4 traffic.

**Usage Guidelines** In Cisco IOS Release 12.2SRA and earlier, the sampled NetFlow can be global or per interface, depending on the current flow mask. For interface-full and interface-destination-source flow masks, sampled NetFlow is enabled on a per-interface basis. For all the other flow masks, sampled NetFlow is always global and is turned on or off for all interfaces.

Enter the **mls sampling** command to enable sampled NetFlow globally.

Cisco IOS Release 12.2(33)SRB and later support per-interface NetFlow for IPv4 traffic. Per-interface NetFlow has the following configuration requirements:

- In addition to issuing the **mls sampling** command (to globally enable NetFlow on the router), you must also issue the **ip flow ingress** and **mls netflow sampling** commands on individual interfaces to enable sampled NetFlow on the interface.
- The only flow masks allowed for IPv4 traffic are interface-destination-source and interface-full. If other flow mask values are used, the router upgrades them as follows:
  - Source, destination, and destination-source flow masks are treated as interface-destination-source.
  - Full flow masks are treated as interface-full.

**Note**

In addition to populating the hardware NetFlow cache, the **flow hardware mpls-vpn ipvrf-id** command also enables sampled NetFlow for IPv4 traffic flows on an MPLS VPN VRF interface.

**Examples**

This example shows how to enable sampled NetFlow on an interface:

```
Router(config-if)# mls netflow sampling
Router(config-if)#
```

This example shows how to disable sampled NetFlow on an interface:

```
Router(config-if)# no mls netflow sampling
Router(config-if)#
```

**Related Commands**

Command	Description
<b>flow hardware mpls-vpn ip</b>	Enables NetFlow to create and export hardware NetFlow cache entries for IPv4 traffic on an MPLS VPN VRF interface.
<b>ip flow ingress</b>	Enables (ingress) NetFlow accounting for traffic arriving on an interface.
<b>mls flow ip</b>	Configures the flow mask to use for NetFlow Data Export.
<b>mls sampling</b>	Enables the sampled NetFlow and specifies the sampling method.
<b>show mls sampling</b>	Displays information about the sampled NDE status.

## mls netflow usage notify

To monitor the NetFlow table usage on the switch processor and the DFCs, use the **mls netflow usage notify** command in global configuration mode. To return to the default settings, use the **no** form of this command.

**mls netflow usage notify** *threshold interval*

**no mls netflow usage notify**

### Syntax Description

<i>threshold</i>	Percentage threshold that, if exceeded, displays a warning message; valid values are from 20 to 100 percent.
<i>interval</i>	Frequency that the NetFlow table usage is checked; valid values are from 120 to 1000000 seconds.

### Command Default

Disabled

### Command Modes

Global configuration

### Command History

Release	Modification
12.2(17d)SXB1	Support for this command was introduced on the Supervisor Engine 720 and the Supervisor Engine 2.
12.2(33)SRA	This command was integrated into Cisco IOS Release 12.2(33)SRA.

### Usage Guidelines

If the NetFlow table usage monitoring is enabled and the NetFlow table usage exceeds the percentage threshold, a warning message is displayed.

NetFlow gathers statistics from traffic and stores the statistics in the NetFlow table. You can gather statistics globally based on a protocol or optionally per interface.

If you are not using NDE or the Cisco IOS features that use the hardware NetFlow table (micro-flow QoS, WCCP, TCP Intercept, or Reflexive ACLs), you may safely disable the use and maintenance of the hardware NetFlow table using the **no mls netflow** command in global configuration mode.

### Examples

This example shows how to configure the monitoring of the NetFlow table usage on the switch processor and the DFCs:

```
Router (config) #
```

```
mls netflow usage notify 80 300
Router(config)#
```

**Related Commands**

Command	Description
show mls netflow usage	Displays configuration information about the NetFlow hardware.

## mls sampling

To enable the sampled NetFlow and specify the sampling method, use the **mls sampling** command in global configuration mode. To disable the sampled NetFlow, use the **no** form of this command.

**mls sampling** {**time-based** *rate*| **packet-based** *rate* [ *interval* ]}

**no mls sampling**

### Syntax Description

<b>time-based</b> <i>rate</i>	Specifies the time-based sampling rate; valid values are <b>64</b> , <b>128</b> , <b>256</b> , <b>512</b> , <b>1024</b> , <b>2046</b> , <b>4096</b> , and <b>8192</b> . See the “Usage Guidelines” section for additional information.
<b>packet-based</b> <i>rate</i>	Specifies the packet-based sampling rate; valid values are <b>64</b> , <b>128</b> , <b>256</b> , <b>512</b> , <b>1024</b> , <b>2046</b> , <b>4096</b> , and <b>8192</b> .
<i>interval</i>	(Optional) Sampling interval; valid values are from 8000 to 16000 milliseconds.

### Command Default

Disabled

### Command Modes

Global configuration

### Command History

Release	Modification
12.2(14)SX	Support for this command was introduced on the Supervisor Engine 720.
12.2(17a)SX	This command was changed as follows: <ul style="list-style-type: none"> <li>The minimum sampling interval for each rate and period was changed from 4000 to 8000 milliseconds.</li> <li>The time pair for each sampling rate of time-based sampling was changed; the table below lists the new time pairs.</li> </ul>
12.2(17d)SXB	Support for this command on the Supervisor Engine 2 was extended to the 12.2 SX release.
12.2(33)SRA	This command was integrated into Cisco IOS Release 12.2(33)SRA.
12.2(33)SRB	This command was changed to support per-interface NetFlow for IPv4 traffic.

**Usage Guidelines**

The sampled NetFlow is supported on Layer 3 interfaces only.

You can enable the sampled NetFlow even if NDE is disabled, but no flows are exported.

With packet-based sampling, a flow with a packet count of  $n$  is sampled  $nm$  times, where  $m$  is the sampling rate.

Cisco IOS Release 12.2(33)SRB and later support per-interface NetFlow for IPv4 traffic. Per-interface NetFlow has the following configuration requirements:

- In addition to issuing the **mls sampling** command (to globally enable NetFlow on the router), you must also issue the **ip flow ingress** and **mls netflow sampling** commands on individual interfaces to enable sampled NetFlow on the interface.
- The **flow hardware mpls-vpn ipvrf-id** command enables sampled NetFlow for IPv4 traffic flows on an MPLS VPN VRF interface.
- The only flow masks allowed for IPv4 traffic are interface-destination-source and interface-full. If other flow mask values are used, the router upgrades them as follows:
  - Source, destination, and destination-source flow masks are treated as interface-destination-source.
  - Full flow masks are treated as interface-full.

The time-based sampling is based on a preset interval for each sampling rate.

The table below lists the sample intervals for each rate and period.

**Table 5: Time-Based Sampling Intervals**

Sampling Rate	Sampling Time (milliseconds)	Export Interval (Milliseconds)
1 in 64	128	8192
1 in 128	64	8192
1 in 256	32	8192
1 in 512	16	8192
1 in 1024	8	8192
1 in 2048	4	8192
1 in 4096	4	16384
1 in 8192	4	32768

**Examples**

This example shows how to enable the time-based NetFlow sampling and set the sampling rate:

```
Router(config)
```

```
)# mls sampling time-based 1024
Router(config)#
```

This example shows how to enable the packet-based NetFlow sampling and set the sampling rate and interval:

```
Router(config
)# mls sampling packet-based 1024 8192
Router(config)#
```

### Related Commands

Command	Description
<b>flow hardware mpls-vpn ip</b>	Enables NetFlow to create and export hardware NetFlow cache entries for IPv4 traffic on an MPLS VPN VRF interface.
<b>ip flow ingress</b>	Enables (ingress) NetFlow accounting for traffic arriving on an interface.
<b>mls flow ip</b>	Configures the flow mask to use for NetFlow Data Export.
<b>mls netflow sampling</b>	Enables the sampled NetFlow on an interface.
<b>show mls sampling</b>	Displays information about the sampled NDE status.

## mode (flow sampler configuration)

To specify a packet interval for random sampled NetFlow accounting and enable the flow sampler map, use the **mode** command in NetFlow flow sampler configuration mode.

**mode random one-out-of** *packet-interval*

### Syntax Description

<b>random</b>	Specifies that sampling uses the random mode.
<b>one-out-of</b> <i>packet-interval</i>	Specifies the packet interval (1 out of every <i>n</i> packets). For <i>n</i> , you can specify from 1 to 65535 packets.

### Command Default

The random sampling mode and packet sampling interval are undefined.

### Command Modes

NetFlow flow sampler configuration

### Command History

Release	Modification
12.3(2)T	This command was introduced.
12.2(18)S	This command was integrated into Cisco IOS Release 12.2(18)S.
12.0(26)S	This command was integrated into Cisco IOS Release 12.0(26)S.
12.2(27)SBC	This command was integrated into Cisco IOS Release 12.2(27)SBC.
12.2(18)SXF	This command was integrated into Cisco IOS Release 12.2(18)SXF.
12.2(33)SRA	This command was integrated into Cisco IOS Release 12.2(33)SRA.

### Usage Guidelines

The **mode random one-out-of** command does not have a **no** format to remove it from the configuration. To disable NetFlow random sampling and packet interval you must remove the flow sampler map that you enabled with the **mode random one-out-of** command.

If you want to change the value that you entered for the *packet-interval* argument repeat the **mode random one-out-of** *packet-interval* command using the new value for *packet-interval*.

Random sampled NetFlow accounting cannot be run concurrently with (ingress) NetFlow accounting, egress NetFlow accounting, or NetFlow accounting with input filter sampling on the same interface, or subinterface. In order to run random sampled NetFlow accounting, you must first disable (ingress) NetFlow accounting, egress NetFlow accounting, or NetFlow accounting with input filter sampling.



You must enable either Cisco Express Forwarding (CEF) or distributed CEF (dCEF) before using this command.



**Tip** If you disable dCEF globally using the **no ip cef [distributed]** command, the **flow-sampler sampler-map-name** command is removed from any interfaces that you previously configured for random sampled NetFlow accounting. You must reenter the **flow-sampler sampler-map-name** command after you reenables CEF or dCEF to reactivate random sampled NetFlow accounting.



**Tip** If your router is running Cisco IOS release 12.2(14)S or a later release, or Cisco IOS Release 12.2(15)T or a later release, NetFlow accounting might be enabled through the use of the **ip flow ingress** command instead of the **ip route-cache flow** command. If your router has NetFlow accounting enabled through the use of **ip flow ingress** command you must disable NetFlow accounting, using the **no** form of this command, before you apply a random sampler map for random sampled NetFlow accounting on an interface otherwise the full, un-sampled traffic will continue to be seen.

## Examples

The following example shows how to create and enable a random sampler map for random sampled (ingress) NetFlow accounting with CEF switching on Ethernet interface 0/0:

```
Router(config)# ip cef
Router(config)# flow-sampler-map my-map
Router(config-sampler)# mode random one-out-of 100
Router(config-sampler)# interface ethernet 0/0
Router(config-if)# no ip route-cache flow
Router(config-if)# ip
    route-cache cef
Router(config-if)# flow-sampler my-map
```

The following example shows how to create and enable a random sampler map for random sampled egress NetFlow accounting with CEF switching on Ethernet interface 1/0:

```
Router(config)# ip cef
Router(config)# flow-sampler-map my-map
Router(config-sampler)# mode random one-out-of 100
Router(config-sampler)# interface ethernet 1/0
Router(config-if)# no
    ip flow egress
Router(config-if)# ip
    route-cache cef
Router(config-if)# flow-sampler my-map egress
```

The following output from the **show flow-sampler** command verifies that random sampled NetFlow accounting is active:

```
Router# show flow-sampler

Sampler : my-map, id : 1, packets matched : 7, mode : random sampling mode
    sampling interval is : 100
```

## Related Commands

Command	Description
<b>flow-sampler</b>	Applies a flow sampler map for random sampled NetFlow accounting to an interface.

Command	Description
<b>flow-sampler-map</b>	Defines a flow sampler map for random sampled NetFlow accounting.
<b>netflow-sampler</b>	Enables NetFlow accounting with input filter sampling.
<b>show flow-sampler</b>	Displays the status of random sampled NetFlow (including mode, packet interval, and number of packets matched for each flow sampler).
<b>show ip cache flow</b>	Displays a summary of the NetFlow accounting statistics.
<b>show ip cache verbose flow</b>	Displays a detailed summary of the NetFlow accounting statistics.
<b>show ip flow interface</b>	Displays NetFlow accounting configuration for interfaces.

## mpls netflow egress

To enable Multiprotocol Label Switching (MPLS) egress NetFlow accounting on an interface, use the **mpls netflow egress** command in interface configuration mode. To disable MPLS egress NetFlow accounting, use the **no** form of this command.

**mpls netflow egress**

**no mpls netflow egress**

**Syntax Description** This command has no arguments or keywords.

**Command Default** This command is disabled.

**Command Modes** Interface configuration (config-if)

Release	Modification
12.0(10)ST	This command was introduced.
12.1(5)T	This command was integrated into Cisco IOS Release 12.1(5)T.
12.2(33)SRA	This command was integrated into Cisco IOS Release 12.2(33)SRA.
12.2SX	This command is supported in the Cisco IOS Release 12.2SX train. Support in a specific 12.2SX release of this train depends on your feature set, platform, and platform hardware.
12.2(33)SCA	This command was integrated into Cisco IOS Release 12.2(33)SCA.

**Usage Guidelines** Use this command to configure the provider edge (PE) to customer edge (CE) interface of a PE router.

**Examples** The following example shows how to enable MPLS egress NetFlow accounting on the egress PE interface that connects to the CE interface at the destination Virtual Private Network (VPN) site:

```
Router(config-if)# mpls netflow egress
```

### Related Commands

Command	Description
<b>debug mpls netflow</b>	Enables debugging of MPLS egress NetFlow accounting.

Command	Description
<b>show mpls forwarding-table</b>	Displays a message that the quick flag is set for all prefixes learned from the MPLS egress NetFlow accounting enabled interface.
<b>show mpls interfaces</b>	Displays the value of the output_feature_state.

# netflow-sampler

To enable NetFlow accounting with input filter sampling, use the **netflow-sampler** command in QoS policy-map class configuration mode. To disable NetFlow accounting with input filter sampling, use the **no** form of this command.

**netflow-sampler** *sampler-map-name*

**no netflow-sampler** *sampler-map-name*

## Syntax Description

<i>sampler-map-name</i>	Name of the NetFlow sampler map to apply to the class.
-------------------------	--

## Command Default

NetFlow accounting with input filter sampling is disabled.

## Command Modes

QoS policy-map class configuration

## Command History

Release	Modification
12.3(4)T	This command was introduced.
12.2(25)S	This command was integrated into Cisco IOS Release 12.2(25)S.
12.2(27)SBC	This command was integrated into Cisco IOS Release 12.2(27)SBC.
12.2(31)SB2	This command was integrated into Cisco IOS Release 12.2(31)SB2.
12.2(33)SRA	This command was integrated into Cisco IOS Release 12.2(33)SRA.
12.2SX	This command is supported in the Cisco IOS Release 12.2SX train. Support in a specific 12.2SX release of this train depends on your feature set, platform, and platform hardware.

## Usage Guidelines

NetFlow accounting with input filter sampling cannot be run concurrently with (ingress) NetFlow accounting, egress NetFlow accounting, or random sampled NetFlow on the same interface, or subinterface. In order to run NetFlow accounting with input filter sampling, you must first disable (ingress) NetFlow accounting, egress NetFlow accounting, or random sampled NetFlow.

You can assign only one NetFlow input filter sampler to a class. Assigning another NetFlow input filter sampler to a class overwrites the previous one.

Samplers, also known as filters, are based on classes, but they are enabled on interfaces. You assign a NetFlow input filters sampler to a class by using the **netflow-sampler** command in QoS policy-map class configuration. You use the **service-policy** command to attach the policy map you defined to one or more interfaces.

**Tip**

If your router is running Cisco IOS release 12.2(14)S or a later release, or Cisco IOS Release 12.2(15)T or a later release, NetFlow accounting might be enabled through the use of the **ip flow ingress** command instead of the **ip route-cache flow** command. If your router has NetFlow accounting enabled through the use of **ip flow ingress** command you must disable NetFlow accounting, using the **no** form of this command, before you apply a random sampler map for random sampled NetFlow accounting on an interface otherwise the full, un-sampled traffic will continue to be seen.

You must enable either Cisco Express Forwarding (CEF) or distributed CEF (dCEF) before using this command.

**Examples**

The following example shows how to enable NetFlow accounting with input filter sampling for one class of traffic (traffic with 10 as the first octet of the IP source address):

```
Router(config)# ip cef
Router(config)# flow-sampler-map network-10
Router(config-sampler)# mode random one-out-of 100
Router(config-sampler)# exit
Router(config)# class-map match-any network-10
Router(config-cmap)# match access-group 100
Router(config-cmap)# exit
Router(config)# policy-map network-10
Router(config-pmap)# class network-10
Router(config-pmap-c)# netflow-sampler network-10
Router(config-pmap-c)# exit
Router(config-pmap)# exit
Router(config)# interface Ethernet0/0
Router(config-if)# no ip route-cache flow
Router(config-if)# ip route-cache cef
Router(config-if)# interface ethernet 0/0.1
Router(config-if)# service-policy input network-10
Router(config-if)# exit
Router(config)# access-list 100 permit ip 10.0.0.0 0.255.255.255 any
```

The following output from the **show flow-sampler** command verifies that the NetFlow accounting with input filter sampling is active:

```
Router# show flow-sampler

Sampler : network-10, id : 1, packets matched : 546, mode : random sampling mode
sampling interval is : 100
```

The following output from the **show ip cache verbose flow** command shows that combination of the **access-list 100 permit ip 10.0.0.0 0.255.255.255 any** command and the **match access-group 100** command has filtered out any traffic in which the source IP address does not have 10 as the first octet:

```
Router# show ip cache verbose flow
IP packet size distribution (116 total packets):
  1-32   64   96  128  160  192  224  256  288  320  352  384  416  448  480
  .000 .155 .000 .000 .000 .000 .000 .000 .000 .000 .000 .000 .000 .000 .000
    512  544  576 1024 1536 2048 2560 3072 3584 4096 4608
  .000 .000 .000 .258 .586 .000 .000 .000 .000 .000 .000
IP Flow Switching Cache, 278544 bytes
  7 active, 4089 inactive, 66 added
  3768 ager polls, 0 flow alloc failures
  Active flows timeout in 1 minutes
  Inactive flows timeout in 120 seconds
IP Sub Flow Cache, 21640 bytes
  6 active, 1018 inactive, 130 added, 62 added to flow
```

```

0 alloc failures, 0 force free
1 chunk, 1 chunk added
last clearing of statistics never
Protocol      Total      Flows      Packets Bytes  Packets Active (Sec) Idle (Sec)
-----      -
Flows        /Sec      /Flow  /Pkt  /Sec      /Flow      /Flow
TCP-Telnet    6          0.0        1     940    0.0        8.8        51.6
TCP-FTP       5          0.0        1     640    0.0        6.9        53.4
TCP-SMTP      2          0.0        3    1040    0.0       41.7       18.5
TCP-other    36          0.0        1    1105    0.0       18.8       41.5
UDP-other     6          0.0        3     52     0.0       54.8        5.5
ICMP         4          0.0        1    628    0.0       11.3       48.8
Total:       59          0.0        1    853    0.1       20.7       39.6
SrcIf          SrcIPAddress      DstIf          DstIPAddress      Pr TOS Flgs Pkts
Port Msk AS      Port Msk AS      NextHop          B/Pk Active
Et0/0.1        10.10.10.3      Et1/0.1        172.16.10.3      06 80 00      1
0016 /0 0
Sampler: 1 Class: 1
Et0/0.1        10.10.10.3      Et1/0.1*      172.16.10.3      06 80 00      1
0016 /0 0
Sampler: 1 Class: 1 FFlags: 01
Et0/0.1        10.10.11.3      Et1/0.1        172.16.10.7      06 80 00      1
0041 /0 0
Sampler: 1 Class: 1
Et0/0.1        10.10.11.1      Et1/0.1        172.16.10.5      06 80 00      3
0019 /0 0
Sampler: 1 Class: 1
Et0/0.1        10.10.11.1      Et1/0.1*      172.16.10.5      06 80 00      1
0019 /0 0
Sampler: 1 Class: 1 FFlags: 01
Et0/0.1        10.1.1.2        Et1/0.1        172.16.10.10     06 80 00      2
0041 /0 0
Sampler: 1 Class: 1
Et0/0.1        10.10.10.1      Et1/0.1        172.16.10.1      01 80 10      1
0000 /0 0
Sampler: 1 Class: 1

```

## Related Commands

Command	Description
<b>flow-sampler</b>	Applies a flow sampler map for random sampled NetFlow accounting to an interface.
<b>flow-sampler-map</b>	Defines a flow sampler map for random sampled NetFlow accounting.
<b>mode (flow sampler configuration)</b>	Specifies a packet interval for NetFlow accounting random sampling mode and enables the flow sampler map.
<b>class-map</b>	Creates a class map to be used for matching packets to a specified class.
<b>policy-map</b>	Creates or modifies a policy map that can be attached to one or more interfaces to specify a service policy
<b>service-policy</b>	Attaches a policy map to an input interface or virtual circuit (VC).
<b>show flow-sampler</b>	Displays the status of random sampled NetFlow (including mode, packet interval, and number of packets matched for each flow sampler).

Command	Description
<b>show ip cache flow</b>	Displays a summary of the NetFlow accounting statistics.
<b>show ip cache verbose flow</b>	Displays a detailed summary of the NetFlow accounting statistics.
<b>show ip flow interface</b>	Displays NetFlow accounting configuration for interfaces.



# platform netflow rp sampling scale

To enable applying of sampling scale equivalent to the configured platform sampling ratio on the software-switched flows exported by the NetFlow software, use the **platform netflow rp sampling scale** command in global configuration mode. To disable sampling of software-switched flows by the NetFlow software, use the **no** form of this command.

**platform netflow rp sampling scale**

**no platform netflow rp sampling scale**

**Syntax Description** This command has no arguments or keywords.

**Command Default** Software switched flows are exported and not sampled by the NetFlow software.

**Command Modes** Global configuration (config)

Command History	Release	Modification
	12.2(33)SRB5	This command was introduced.
	12.2(33)SRC3	This command was integrated into Cisco IOS Release 12.2(33)SRC3.
	12.2(33)SRD1	This command was integrated into Cisco IOS Release 12.2(33)SRD1.

**Usage Guidelines** Use this command to scale the exported information for flows handled by the Route Processor (RP) equivalent to the platform sampling ratio. Without this command, a NetFlow collector assumes all flows exported by a router are uniformly sampled and multiplies the nonsampled RP flows by the sampling factor, and therefore overestimates the traffic handled by the RP.

The applicable sampling scale is obtained from the Cisco 7600-specific router platform **mls sampling** command.

Based on configuration, the RP software divides the exported packet/byte counts for a V5 and V9 export by the configured platform sampling ratio. The platform configuration is accomplished using the **mls netflow sampling** command. If no such configuration is present, the RP exports the value it observes, and does not divide the exported packet/byte count.



**Note** If the division result is zero, the value 1 is substituted.

**Examples** The following example shows how to enable sampling for flows switched in the RP software:

```
Router(config)
```

```
)# platform netflow rp sampling scale
```

**Related Commands**

Command	Description
<b>mls netflow sampling</b>	Enables sampled NetFlow on an interface.
mls sampling	Enables the sampled NetFlow and specifies the sampling method.

## reliability (NetFlow SCTP)

To specify the level of reliability for the reliable export of NetFlow accounting information in NetFlow cache entries, use the **reliability** command in NetFlow ip flow export stream control transmission protocol (SCTP) configuration mode. To return to the default behavior, use the no form of this command.

**reliability** {full| none| partial buffer-limit}

**no reliability** {full| none| partial buffer-limit *limit*}

### Syntax Description

<i>ip-address</i>   <i>hostname</i>	IP address or hostname of the workstation to which you want to send the NetFlow information.
<b>full</b>	Configures guaranteed reliable, ordered delivery of messages to a export destination. This is the default behavior.
<b>none</b>	Specifies that each message is sent once. The message is not stored in a buffer and cannot be retransmitted if it is not received by the export destination.
<b>partial</b>	Specifies the limit on the amount of memory the router will use to buffer messages while waiting for them to be acknowledged by the export destination.
<b>buffer-limit</b> <i>limit</i>	Specifies the amount of memory that is available for the buffering of messages that have not been acknowledged by the export destination. Range: 1 to 35000 packets.

### Command Default

NetFlow reliable export uses full reliability mode by default.

### Command Modes

NetFlow ip flow export SCTP (config-flow-export-sctp)

### Command History

Release	Modification
12.4(4)T	This command was introduced.

### Usage Guidelines

#### NetFlow Reliable Export Using SCTP with Partial Reliability

If a stream is specified as unreliable, the packet is simply sent once and not buffered on the exporter at all. If the packet is lost en route to the receiver, the exporter is not notified and cannot re-transmit it

When a stream is specified as partially reliable, a limit can be placed on how much memory should be dedicated to storing un-acknowledged packets. The limit is configurable. If the limit is exceeded and the router attempts to buffer another packet, the oldest un-acknowledged packet is discarded. When SCTP discards the oldest unacknowledged packet a message called a forward-tsn (transmit sequence number) is sent to the export destination to indicate that this packet will not be received. This prevents NetFlow from consuming all the free memory on a router when a situation has arisen which requires a large number of packets to be buffered, for example when you are experiencing long response times from an SCTP peer connection.

When SCTP is operating in partially-reliable mode, the limit on how much memory should be dedicated to storing un-acknowledged packets should initially be set as high as possible. The limit on how much memory should be dedicated to storing unacknowledged packets can be reduced if other processes on the router begin to run out of memory. Deciding on the best value for the limit on how much memory should be dedicated to storing un-acknowledged packets involves a trade off between avoiding starving other processes of the memory that they require to operate, and dropping SCTP messages that have not been acknowledged by the export destination.

### NetFlow Reliable Export Using SCTP with Reliability Disabled

When an SCTP connection is specified as unreliable, exported messages are sent once only and are not buffered. If the message is lost en route to the export destination, it cannot be retransmitted. Unreliable SCTP can be used when the export destination that you are using doesn't support UDP as a transport protocol for receiving NetFlow export datagrams, and you do not want to allocate the resources on your router required to provide reliable, or partially reliable, SCTP connections.

## Examples

The following example shows how to configure the networking device to use full SCTP reliability:

```
Router(config)# ip flow-export destination 172.16.10.2 78 sctp
Router(config-flow-export-sctp)# reliability full
```

The following example shows how to configure the networking device to use partial SCTP reliability, with a maximum value for the buffer limit of 35000 export packets:

```
Router(config)# ip flow-export destination 172.16.10.2 78 sctp
Router(config-flow-export-sctp)# reliability partial buffer-limit 35000
```

The following example shows how to configure the networking device to use SCTP with no reliability:

```
Router(config)# ip flow-export destination 172.16.10.2 78 sctp
Router(config-flow-export-sctp)# reliability none
```

## Related Commands

Command	Description
<b>backup</b>	Configures a backup destination for the reliable export of NetFlow accounting information in NetFlow cache entries
<b>ip flow-export destination sctp</b>	Enables the reliable export of NetFlow accounting information in NetFlow cache entries.
<b>show ip flow export</b>	Displays the status and the statistics for NetFlow accounting data export.

# show flow-sampler

To display the status and statistics for random sampled NetFlow (including mode, packet interval, and number of packets matched for each flow sampler), use the show flow-sampler command in user EXEC or privileged EXEC mode.

**show flow-sampler** [ *sampler-map-name* ]

## Syntax Description

<i>sampler-map-name</i>	(Optional) Name of a flow sampler map.
-------------------------	--

## Command Modes

User EXEC Privileged EXEC

## Command History

Release	Modification
12.3(2)T	This command was introduced.
12.2(18)S	This command was integrated into Cisco IOS Release 12.2(18)S.
12.0(26)S	This command was integrated into Cisco IOS Release 12.0(26)S.
12.2(27)SBC	This command was integrated into Cisco IOS Release 12.2(27)SBC.
12.2(18)SXF	This command was integrated into Cisco IOS Release 12.2(18)SXF.
12.2(33)SRA	This command was integrated into Cisco IOS Release 12.2(33)SRA.

## Examples

The following is sample output from the show flow-sampler command for all flow samplers:

```
Router> show flow-sampler
Sampler : mysampler1, id : 1, packets matched : 10, mode : random sampling mode
  sampling interval is : 100
Sampler : myflowsampler2, id : 2, packets matched : 5, mode : random sampling mode
  sampling interval is : 200
```

The following is sample output from the show flow-sampler command for a flow sampler named mysampler1:

```
Router> show flow-sampler mysampler1
Sampler : mysampler1, id : 1, packets matched : 0, mode : random sampling mode
  sampling interval is : 100
```

The table below describes the fields shown in the displays.

**Table 6: show flow-sampler Field Descriptions**

Field	Description
Sampler	Name of the flow sampler
id	Unique ID of the flow sampler
packets matched	Number of packets matched for the flow sampler
mode	Flow sampling mode
sampling interval is	Flow sampling interval (in packets)

**Related Commands**

Command	Description
<b>flow-sampler</b>	Applies a flow sampler map for random sampled NetFlow accounting to an interface.
<b>flow-sampler-map</b>	Defines a flow sampler map for random sampled NetFlow accounting.
<b>mode (flow sampler configuration)</b>	Specifies a packet interval for NetFlow accounting random sampling mode.
<b>netflow-sampler</b>	Enables NetFlow accounting with input filter sampling.
<b>show ip cache flow</b>	Displays a summary of the NetFlow accounting statistics.
<b>show ip cache verbose flow</b>	Displays a detailed summary of the NetFlow accounting statistics.
<b>show ip flow interface</b>	Displays NetFlow accounting configuration for interfaces.

# show fm nat netflow data

To display the information about the NAT-related NetFlow data, use the **show fm nat netflow data** command in user EXEC or privileged EXEC mode.

**show fm nat netflow data**

**Syntax Description** This command has no arguments or keywords.

**Command Default** This command has no default settings.

**Command Modes** User EXEC Privileged EXEC

Command History	Release	Modification
	12.2(14)SX	Support for this command was introduced on the Supervisor Engine 720.
	12.2(17d)SXB	Support for this command on the Supervisor Engine 2 was extended to Release 12.2(17d)SXB.
	12.2(18)SXD	The output was changed to display the information about the NetFlow lookup mode state for fragments.
	12.2(33)SRA	This command was integrated into Cisco IOS Release 12.2(33)SRA.

**Examples** This example shows how to display the information about the NAT-related NetFlow data:

```
Router> show fm nat netflow data
FM Pattern with stat push disabled: 1
Default/TCP/UDP Timeouts:
Def s/w timeout: 86400 h/w timeout: 300 Pattern(ingress): 4
Pattern(egress): 4 Push interval: 1333
TCP s/w timeout: 86400 h/w timeout: 300 Pattern(ingress): 4
Pattern(egress): 4 Push interval: 1333
UDP s/w timeout: 300 h/w timeout: 300 Pattern(ingress): 3
Pattern(egress): 3 Push interval: 100
Port Timeouts:
Idle timeout :3600 secs
Fin/Rst timeout :10 secs
Fin/Rst Inband packets sent per timeout :10000
Netflow mode to Zero-out Layer4 information for fragment packet lookup :
Enabled
Router>
```

## Related Commands

Command	Description
<b>show fm summary</b>	Displays a summary of FM Information.





## show fm netflow

To display the feature manager (FM) Netflow information, use the **show fm netflow** command in User EXEC or privileged EXEC mode.

**show fm netflow** {counters| pattern| slotinfo}

### Syntax Description

<b>counters</b>	Displays feature manager Netflow counters.
<b>pattern</b>	Displays feature manager Netflow pattern information.
<b>slotinfo</b>	Displays feature manager Netflow slot information.

### Command Default

This command has no default settings.

### Command Modes

User EXEC (>) Privileged EXEC (#)

### Command History

Release	Modification
12.2(17)SX	Support for this command was introduced.
12.2(33)SXI	The output was changed to include the chassis number for virtual switch systems (VSS) only.

### Examples

This example shows how to display the information about the feature manager Netflow counters:

```
Router# show fm netflow counters
FM Netflow Counters          IPv4          IPv6
-----
Netflow Install Request Counters:
Netflow Install Reply Counters:
Netflow Delete Requests Counters:
Netflow Delete Reply Counters:
Netflow nodes in database:          0              0
FM Netflow Outstanding Adjacency Replies, Slot[1] = 0
FM Safe inband mode : Active
FM No. of dummy inbands : 8
FM Netflow Disable shortcut Flag : 0
FM Inband Reply Mode : Inband err reply
FM Netflow Adjacency Block Size : 1024
FM Netflow Max Adjacency Threshold : 131072
FM Number of Items in Netflow Clr Database=0
```

This example shows how to display the information about the feature manager Netflow patterns:

```
Router# show fm netflow pattern
```

```

Feature                Pattern  StatPush  Agetime
-----
SLB                    7        0         0       10
INSPECT                6        0         0        1
TCP_INTERCEPT       5        0        300        1
WCCP_EGRESS           5        0        300        1
NAT_INGRESS           4       1333       300        1
NAT_EGRESS             4       1333       300        1
IP_ACCESS_INGRESS     3        100       300        1
IP_ACCESS_EGRESS      3        100       300        1
NAT_INGRESS           3        100       300        1
NAT_EGRESS             3        100       300        1
IPV6_RACL_EGRESS      3        100       300        1
NF_AGING               2         0         10         1
DEFAULT_NO_STAT       1         0         0          1

```

This example shows how to display the slot information about the feature manager Netflow:

```

Router# show fm netflow slotinfo
Slotnum=1      free_index=0      num_free_adj=128      adj_arr_size=128

```

## Examples

This example shows how to display the information about the feature manager Netflow counters on a VSS:

```

Router# show fm netflow counters
FM Netflow Counters          IPv4          IPv6
-----
Netflow Install Request Counters:
Netflow Install Reply Counters:
Netflow Delete Requests Counters:
Netflow Delete Reply Counters:
Netflow nodes in database:          0          0
FM Netflow Outstanding Adjacency Replies, Slot[1/1] = 0
FM Netflow Outstanding Adjacency Replies, Slot[1/2] = 0
FM Safe inband mode : Active
FM No. of dummy inbands : 8
FM Netflow Disable shortcut Flag : 0
FM Inband Reply Mode : Inband err reply
FM Netflow Adjacency Block Size : 1024
FM Netflow Max Adjacency Threshold : 131072
FM Number of Items in Netflow Clr Database=0

```

This example shows how to display the slot information about the feature manager Netflow on a VSS:

```

Router# show fm netflow slotinfo
Slotnum=1/1      free_index=0      num_free_adj=128      adj_arr_size=128
Slotnum=1/2      free_index=0      num_free_adj=128      adj_arr_size=128
Slotnum=2/5      free_index=0      num_free_adj=128      adj_arr_size=128
Slotnum=2/8      free_index=0      num_free_adj=128      adj_arr_size=128

```

## Related Commands

Command	Description
<b>show fm summary</b>	Displays a summary of feature manager information.

# show ip cache flow

To display a summary of the NetFlow accounting statistics, use the **show ip cache flow** command in user EXEC or privileged EXEC mode.

**show ip cache** [*prefix mask*] [*type number*] **flow**

## Syntax Description

<i>prefix mask</i>	(Optional) Displays only the entries in the cache that match the prefix and mask combination.
<i>type number</i>	(Optional) Displays only the entries in the cache that match the interface type and number combination.

## Command Modes

User EXEC Privileged EXEC

## Command History

Release	Modification
11.1	This command was introduced.
11.1CA	The information display for the command was updated.
12.2(14)S	This command was integrated into Cisco IOS Release 12.2(14)S.
12.3(1)	Support for the NetFlow Multicast Support feature was added.
12.2(18)S	Support for the NetFlow Multicast Support feature was added.
12.3(4)T, 12.3(6), 12.2(20)S	The <b>execute-on</b> command was implemented on the Cisco 7500 platforms to include the remote execution of the <b>show ip cache flow</b> command.
12.3(11)T	Support for egress flow accounting was added, and the [ <i>prefix mask</i> ] and [ <i>type number</i> ] arguments were removed.
12.2(27)SBC	This command was integrated into Cisco IOS Release 12.2(27)SBC.
12.2(14)SX	Support for this command was introduced on the Supervisor Engine 720.
12.2(17b)SXA	The output was changed to include hardware-entry information.
12.2(17d)SXB	Support for this command on the Supervisor Engine 2 was extended to the 12.2 SX release.
12.2(18)SXF	This command was integrated into Cisco IOS Release 12.2(18)SXF.
12.2(31)SB2	This command was integrated into Cisco IOS Release 12.2(31)SB2.

Release	Modification
12.2(33)SRB	This command was modified to show the VPN name and VPN ID in the display output.

### Usage Guidelines

Some of the content in the display of the **show ip cache flow** command uses multiline headings and multiline data fields. Below is an example of the output from the **show ip cache verbose flow** to show how to associate the headings with the correct data fields when there are two or more lines of headings and two or more lines of data fields. The first line of the headings is associated with the first line of data fields. The second line of the headings is associated with the second line of data fields, and so on.

When other features such as IP Multicast are configured, the number of lines in the headings and data fields increases. The method for associating the headings with the correct data fields remains the same.

```
Router# show ip cache verbose flow
IP packet size distribution (25229 total packets):
  1-32  64  96 128 160 192 224 256 288 320 352 384 416 448 480
  .000 .000 .000 .000 .000 .000 .000 .000 .000 .000 .000 .000 .000 .000 .000
  512 544 576 1024 1536 2048 2560 3072 3584 4096 4608
  .000 .000 .000 .206 .793 .000 .000 .000 .000 .000 .000 .000
```

```
IP Flow Switching Cache, 278544 bytes
  6 active, 4090 inactive, 17 added
  505 ager polls, 0 flow alloc failures
  Active flows timeout in 1 minutes
  Inactive flows timeout in 10 seconds
IP Sub Flow Cache, 25736 bytes
  12 active, 1012 inactive, 39 added, 17 added to flow
  0 alloc failures, 0 force free
  1 chunk, 1 chunk added
  last clearing of statistics never
```

Protocol	Total	Flows	Packets	Bytes	Packets	Active (Sec)	Idle (Sec)
-----	Flows	/Sec	/Flow	/Pkt	/Sec	/Flow	/Flow
TCP-Telnet	1	0.0	362	940	2.7	60.2	0.0
TCP-FTP	1	0.0	362	840	2.7	60.2	0.0
TCP-FTPD	1	0.0	362	840	2.7	60.1	0.1
TCP-SMTP	1	0.0	361	1040	2.7	60.0	0.1
UDP-other	5	0.0	1	66	0.0	1.0	10.6
ICMP	2	0.0	8829	1378	135.8	60.7	0.0
Total:	11	0.0	1737	1343	147.0	33.4	4.8

SrcIf	SrcIPAddress	DstIf	DstIPAddress	Pr	TOS	Flgs	Pkts
Port Msk AS		Port Msk AS	NextHop	B/Pk		Active	
Et0/0.1	10.251.138.2	Et1/0.1	172.16.10.2	06	80	00	65
0015 /0 0		0015 /0 0	0.0.0.0	840		10.8	
MAC: (VLAN id) aaaa.bbbb.cc03	(005)		aaaa.bbbb.cc06	(006)			
Min plen: 840			Max plen: 840				
Min TTL: 59			Max TTL: 59				
IP id: 0							

127034

### Displaying Detailed NetFlow Cache Information on Platforms Running Distributed Cisco Express Forwarding

On platforms running distributed Cisco Express Forwarding (dCEF), NetFlow cache information is maintained on each line card or Versatile Interface Processor. To display this information on a distributed platform by use of the **show ip cache flow** command, you must enter the command at a line card prompt.

### Cisco 7600 Series Platforms

The **module num** keyword and argument are supported on DFC-equipped modules only.

The VPN name and ID are shown in the display output in the format VPN:vpn-id.

### Cisco 7500 Series Platform

The Cisco 7500 series platforms are not supported by Cisco IOS Release 12.4T and later. Cisco IOS Release 12.4 is the last Cisco IOS release to support the Cisco 7500 series platforms.

To display NetFlow cache information using the **show ip cache flow** command on a Cisco 7500 series router that is running dCEF, enter the following sequence of commands:

```
Router# if-con
slot-number
LC-
slot-number
# show ip cache flow
```

For Cisco IOS Releases 12.3(4)T, 12.3(6), and 12.2(20)S and later, enter the following command to display NetFlow cache information:

```
Router# execute-on
slot-number
show ip cache flow
```

### Cisco 12000 Series Platform

To display NetFlow cache information using the **show ip cache flow** command on a Cisco 12000 Series Internet Router, enter the following sequence of commands:

```
Router# attach
slot-number
LC-
slot-number
# show ip cache flow
```

For Cisco IOS Releases 12.3(4)T, 12.3(6), and 12.2(20)S and later, enter the following command to display NetFlow cache information:

```
Router# execute-on
slot-number
show ip cache flow
```

## Examples

The following is a sample display of a main cache using the **show ip cache flow** command:

```
Router# show ip cache flow
IP packet size distribution (2381 total packets):
 1-32   64   96  128  160  192  224  256  288  320  352  384  416  448  480
 .092 .000 .003 .000 .141 .048 .000 .000 .000 .093 .000 .000 .000 .000 .000
  512  544  576 1024 1536 2048 2560 3072 3584 4096 4608
 .000 .000 .048 .189 .381 .000 .000 .000 .000 .000 .000 .000
IP Flow Switching Cache, 278544 bytes
 22 active, 4074 inactive, 45 added
2270 aged polls, 0 flow alloc failures
Active flows timeout in 1 minutes
Inactive flows timeout in 100 seconds
```

## show ip cache flow

```

IP Sub Flow Cache, 25736 bytes
 23 active, 1001 inactive, 47 added, 45 added to flow
 0 alloc failures, 0 force free
 1 chunk, 1 chunk added
 last clearing of statistics never

```

Protocol	Total Flows	Flows /Sec	Packets /Flow	Bytes /Pkt	Packets /Sec	Active(Sec) /Flow	Idle(Sec) /Flow
TCP-FTP	4	0.0	67	840	2.6	59.4	0.7
TCP-SMTP	1	0.0	67	168	0.6	59.4	0.5
TCP-BGP	1	0.0	68	1140	0.6	60.3	0.4
TCP-NNTP	1	0.0	68	1340	0.6	60.2	0.2
TCP-other	7	0.0	68	913	4.7	60.3	0.4
UDP-TFTP	1	0.0	68	156	0.6	60.2	0.1
UDP-other	4	0.0	36	151	1.4	45.6	14.7
ICMP	4	0.0	67	529	2.7	60.0	0.2
Total:	23	0.2	62	710	14.3	57.5	2.9

```

SrcIf      SrcIPAddress      DstIf      DstIPAddress      Pr  SrcP  DstP  Pkts
-----
Et2/0      192.168.137.78     Et3/0*     192.168.10.67     06 0041 0041   39
Et2/0      172.19.216.196    Et3/0*     192.168.10.38     06 0077 0077   39
Et0/0.1    10.56.78.128      Et1/0.1    172.16.30.231     06 00B3 00B3   48
Et0/0.1    10.10.18.1        Et1/0.1    172.16.30.112     11 0043 0043   47
Et0/0.1    10.162.37.71      Et1/0.1    172.16.30.218     06 027C 027C   48
Et0/0.1    172.16.6.1        Null       224.0.0.9         11 0208 0208   1
Et0/0.1    10.231.159.251    Et1/0.1    172.16.10.2       06 00DC 00DC   48
Et2/0      10.234.53.1       Et3/0*     192.168.10.32     06 0016 0015   39
Et2/0      10.210.211.213    Et3/0*     192.168.10.127    06 006E 006E   38
Et0/0.1    10.234.53.1       Et1/0.1    172.16.30.222     01 0000 0000   47
Et0/0.1    10.90.34.193      Et1/0.1    172.16.10.2       06 0016 0015   48
Et0/0.1    10.10.10.2        Et1/0.1    172.16.10.2       06 0016 0015   48
Et2/0      10.10.18.1        Et3/0*     192.168.10.162    11 0045 0045   39
Et0/0.1    192.168.3.185     Et1/0.1    172.16.10.2       06 0089 0089   48
Et0/0.1    10.10.11.1        Et1/0.1    172.16.30.51      06 0019 0019   49
Et0/0.1    10.254.254.235    Et1/0.1    172.16.10.2       11 00A1 00A1   48
Et2/0      192.168.23.2      Et3/0*     192.168.10.2      01 0000 0000   39
Et0/0.1    10.251.10.1       Et1/0.1    172.16.10.2       01 0000 0800   47
R3#

```



## Note

The asterisk (\*) immediately following the □DstIf□ field indicates that the flow being shown is an egress flow.

The following output of the **show ip cache flow** command on a Cisco 7600 series router shows the source interface some of the traffic in the NetFlow hardware cache on the PFC is VPN Red.

```

PE1# show ip cache flow
-----
MSFC:
IP packet size distribution (3139 total packets):
 1-32  64  96 128 160 192 224 256 288 320 352 384 416 448 480
 .000 .685 .309 .000 .000 .000 .000 .003 .000 .000 .000 .000 .000 .000 .000
 512 544 576 1024 1536 2048 2560 3072 3584 4096 4608
 .000 .000 .000 .000 .000 .000 .000 .000 .000 .000 .000 .000 .000
IP Flow Switching Cache, 278544 bytes
 2 active, 4094 inactive, 56 added
20904 ager polls, 0 flow alloc failures
Active flows timeout in 30 minutes
Inactive flows timeout in 15 seconds
IP Sub Flow Cache, 33992 bytes
 0 active, 1024 inactive, 4 added, 4 added to flow
 0 alloc failures, 0 force free
 1 chunk, 2 chunks added
 last clearing of statistics never

```

Protocol	Total Flows	Flows /Sec	Packets /Flow	Bytes /Pkt	Packets /Sec	Active(Sec) /Flow	Idle(Sec) /Flow
TCP-BGP	10	0.0	1	49	0.0	0.0	15.3
TCP-other	6	0.0	2	49	0.0	4.5	15.5
UDP-other	28	0.0	74	63	0.1	320.5	12.7
IP-other	6	0.0	153	80	0.0	1488.3	1.7
Total:	50	0.0	60	68	0.2	358.6	12.2

```

SrcIf      SrcIPaddress  DstIf      DstIPaddress  Pr  SrcP  DstP  Pkts
Fal/1      172.16.1.1    Null       224.0.0.2     11 0286 0286   74
Fal/1      172.16.1.1    Null       224.0.0.5     59 0000 0000   33
-----

```

PFC:

Displaying Hardware entries in Module 5

```

SrcIf      SrcIPaddress  DstIPaddress  Pr      SrcP      Dss
Fal/1      172.20.1.2    172.20.1.3    0       0         0
Fal/1      172.20.1.3    172.20.1.2    0       0         0
Fal/1      172.16.1.2    172.16.2.6    0       0         0
Fal/1      172.16.1.1    224.0.0.2     udp     646      64
vpn:red   10.2.0.2     10.1.1.1     0      0       0
.
.
.

```

PE1#

The table below describes the significant fields shown in the flow switching cache lines of the display.

**Table 7: show ip cache flow Field Descriptions in Flow Switching Cache Display**

Field	Description
bytes	Number of bytes of memory used by the NetFlow cache.
active	Number of active flows in the NetFlow cache at the time this command was entered.
inactive	Number of flow buffers that are allocated in the NetFlow cache, but were not currently assigned to a specific flow at the time this command was entered.
added	Number of flows created since the start of the summary period.
ager polls	Number of times the NetFlow code looked at the cache to cause entries to expire (used by Cisco for diagnostics only).
flow alloc failures	Number of times the NetFlow code tried to allocate a flow but could not.
last clearing of statistics	Standard time output (hh:mm:ss) since the <b>clear ip flow stats</b> privileged EXEC command was executed. This time output changes to hours and days after the time exceeds 24 hours.

The table below describes the significant fields shown in the activity by protocol lines of the display.

**Table 8: show ip cache flow Field Descriptions in Activity by Protocol Display**

Field	Description
Protocol	IP protocol and the well-known port number. (Refer to <a href="http://www.iana.org">http://www.iana.org</a> , Protocol Assignment Number Services , for the latest RFC values.)  <b>Note</b> Only a small subset of all protocols is displayed.
Total Flows	Number of flows in the cache for this protocol since the last time the statistics were cleared.
Flows/Sec	Average number of flows for this protocol per second; equal to the total flows divided by the number of seconds for this summary period.
Packets/Flow	Average number of packets for the flows for this protocol; equal to the total packets for this protocol divided by the number of flows for this protocol for this summary period.
Bytes/Pkt	Average number of bytes for the packets for this protocol; equal to the total bytes for this protocol divided by the total number of packets for this protocol for this summary period.
Packets/Sec	Average number of packets for this protocol per second; equal to the total packets for this protocol divided by the total number of seconds for this summary period.
Active(Sec)/Flow	Number of seconds from the first packet to the last packet of an expired flow divided by the number of total flows for this protocol for this summary period.
Idle(Sec)/Flow	Number of seconds observed from the last packet in each nonexpired flow for this protocol until the time at which the <b>show ip cache verbose flow</b> command was entered divided by the total number of flows for this protocol for this summary period.

The table below describes the significant fields in the NetFlow record lines of the display.

**Table 9: show ip cache flow Field Descriptions in NetFlow Record Display**

Field	Description
SrcIf	Interface on which the packet was received.



Field	Description
SrcIPAddress	IP address of the device that transmitted the packet.
DstIf	Interface from which the packet was transmitted. <b>Note</b> If an asterisk (*) immediately follows the DstIf field, the flow being shown is an egress flow.
DstIPAddress	IP address of the destination device.
Pr	IP protocol □ well-known □ port number, displayed in hexadecimal format. (Refer to <a href="http://www.iana.org">http://www.iana.org</a> , Protocol Assignment Number Services , for the latest RFC values.)
SrcP	The source protocol port number in hexadecimal.
DstP	The destination protocol port number in hexadecimal.
Pkts	Number of packets switched through this flow.

### Related Commands

Command	Description
<b>clear ip flow stats</b>	Clears the NetFlow accounting statistics.
<b>show ip cache verbose flow</b>	Displays a detailed summary of the NetFlow accounting statistics.
<b>show ip flow interface</b>	Displays NetFlow accounting configuration for interfaces.
<b>show ip interface</b>	Displays the usability status of interfaces configured for IP.

## show ip cache flow aggregation

To display the NetFlow accounting aggregation cache statistics, use the show ip cache flow aggregation command in user EXEC or privileged EXEC mode.

**show ip cache** [*prefix mask*] [*interface-type interface-number*] [**verbose**] **flow aggregation** {**as**| **as-tos**| **bgp-nexthop-tos**| **destination-prefix**| **destination-prefix-tos**| **prefix**| **prefix-port**| **prefix-tos**| **protocol-port**| **protocol-port-tos**| **source-prefix**| **source-prefix-tos**}

### Syntax Description

<i>prefix mask</i>	(Optional) Displays only the entries in the cache that match the prefix and mask combination.
<i>interface-type interface-number</i>	(Optional) Displays only the entries in the cache that match the interface type and interface number combination.
<b>verbose</b>	(Optional) Displays additional information from the aggregation cache.
<b>as</b>	Displays the configuration of the autonomous system aggregation cache scheme.
<b>as-tos</b>	Displays the configuration of the autonomous system type of service (ToS) aggregation cache scheme.
<b>bgp-nexthop-tos</b>	Displays the BGP next hop and ToS aggregation cache scheme.  <b>Note</b> This keyword is not supported on the Cisco ASR 1000 Series Aggregation Services Router.
<b>destination-prefix</b>	Displays the configuration of the destination prefix aggregation cache scheme.
<b>destination-prefix-tos</b>	Displays the configuration of the destination prefix ToS aggregation cache scheme.
<b>prefix</b>	Displays the configuration of the prefix aggregation cache scheme.
<b>prefix-port</b>	Displays the configuration of the prefix port aggregation cache scheme.
<b>prefix-tos</b>	Displays the configuration of the prefix ToS aggregation cache scheme.
<b>protocol-port</b>	Displays the configuration of the protocol port aggregation cache scheme.

<b>protocol-port-tos</b>	Displays the configuration of the protocol port ToS aggregation cache scheme.
<b>source-prefix</b>	Displays the configuration of the source prefix aggregation cache scheme.
<b>source-prefix-tos</b>	Displays the configuration of the source prefix ToS aggregation cache scheme.

**Command Modes**

User EXEC Privileged EXEC

**Command History**

<b>Release</b>	<b>Modification</b>
12.0(3)T	This command was introduced.
12.0(15)S	This command was modified to include new <b>show</b> output for ToS aggregation schemes.
12.2(14)S	This command was integrated into Cisco IOS Release 12.2(14)S.
12.3(1)	Support for the BGP Next Hop Support feature was added.
12.2(18)S	Support for the BGP Next Hop Support feature was added.
12.0(26)S	Support for the BGP Next Hop Support feature was added.
12.2(27)SBC	This command was integrated into Cisco IOS Release 12.2(27)SBC.
12.2(14)SX	Support for this command was introduced on the Supervisor Engine 720.
12.2(17b)SXA	The output was changed to include hardware-entry information.
12.2(17d)SXB	Support for this command on the Supervisor Engine 2 was extended to the 12.2 SX release.
12.2(18)SXF	This command was integrated into Cisco IOS Release 12.2(18)SXF.
12.2(33)SRA	This command was integrated into Cisco IOS Release 12.2(33)SRA.
12.2(31)SB2	This command was integrated into Cisco IOS Release 12.2(31)SB2.
12.2(33)SRB	This command was modified to show the VPN name and VPN ID in the display output.

**Usage Guidelines**

Some of the content in the display of the **show ip cache flow aggregation** command uses multiline headings and multiline data fields. Below is an example of the output from the **show ip cache verbose flow** to show

how to associate the headings with the correct data fields when there are two or more lines of headings and two or more lines of data fields. The first line of the headings is associated with the first line of data fields. The second line of the headings is associated with the second line of data fields, and so on.

When other features such as IP Multicast are configured, the number of lines in the headings and data fields increases. The method for associating the headings with the correct data fields remains the same.

```

Router# show ip cache verbose flow
IP packet size distribution (25229 total packets):
  1-32  64  96 128 160 192 224 256 288 320 352 384 416 448 480
  .000 .000 .000 .000 .000 .000 .000 .000 .000 .000 .000 .000 .000 .000 .000
  512 544 576 1024 1536 2048 2560 3072 3584 4096 4608
  .000 .000 .000 .206 .793 .000 .000 .000 .000 .000 .000 .000

IP Flow Switching Cache, 278544 bytes
  6 active, 4090 inactive, 17 added
  505 ager polls, 0 flow alloc failures
  Active flows timeout in 1 minutes
  Inactive flows timeout in 10 seconds
IP Sub Flow Cache, 25736 bytes
  12 active, 1012 inactive, 39 added, 17 added to flow
  0 alloc failures, 0 force free
  1 chunk, 1 chunk added
  last clearing of statistics never

Protocol          Total    Flows    Packets Bytes  Packets Active(Sec) Idle(Sec)
-----          -----
Flows            /Sec    /Flow  /Pkt  /Sec    /Flow    /Flow
TCP-Telnet        1        0.0      362   940     2.7     60.2     0.0
TCP-FTP           1        0.0      362   840     2.7     60.2     0.0
TCP-FTPD          1        0.0      362   840     2.7     60.1     0.1
TCP-SMTP          1        0.0      361  1040     2.7     60.0     0.1
UDP-other         5        0.0        1    66      0.0      1.0     10.6
ICMP              2        0.0     8829  1378   135.8    60.7     0.0
Total:            11        0.0     1737  1343   147.0    33.4     4.8

```

```

SrcIf      SrcIPAddress  DstIf      DstIPAddress  Pr  TOS  Flgs  Pkts
Port Msk AS  Port Msk AS  NextHop      B/Pk Active
Et0/0.1   10.251.138.2 Et1/0.1    172.16.10.2  06 80 00    65
0015 /0 0  0015 /0 0    0.0.0.0      840 10.8
MAC: (VLAN id) aaaa.bbbb.cc03 (005)
Min plen:      840
Min TTL:        59
IP id:          0

```

127034

### Cisco 7600 Series Platforms

If you enter the **show ip cache flow aggregation** command without the **module num**, the software-switched aggregation cache on the RP is displayed.

The **module num** keyword and argument are supported on DFC-equipped modules only.

The VPN name and ID are shown in the display output in the format VPN:vpn-id.

### Displaying Detailed NetFlow Cache Information on Platforms Running Distributed Cisco Express Forwarding

On platforms running Distributed Cisco Express Forwarding (dCEF), NetFlow cache information is maintained on each line card or Versatile Interface Processor. To display this information on a distributed platform by use of the **show ip cache flow** command, you must enter the command at a line card prompt.

### Cisco 7500 Series Platform

The Cisco 7500 series platforms are not supported by Cisco IOS Release 12.4T and later. Cisco IOS Release 12.4 is the last Cisco IOS release to support the Cisco 7500 series platforms.

To display NetFlow cache information using the **show ip cache flow** command on a Cisco 7500 series router that is running dCEF, enter the following sequence of commands:

```
Router# if-con
```

```
slot-number
LC-
slot-number
# show ip cache flow
```

For Cisco IOS Releases 12.3(4)T, 12.3(6), and 12.2(20)S and later, enter the following command to display NetFlow cache information:

```
Router# execute-on
slot-number
show ip cache flow
```

### Cisco 12000 Series Platform

To display NetFlow cache information using the **show ip cache flow** command on a Cisco 12000 Series Internet Router, enter the following sequence of commands:

```
Router# attach
```

```
slot-number
LC-
slot-number
# show ip cache flow
```

For Cisco IOS Releases 12.3(4)T, 12.3(6), and 12.2(20)S and later, enter the following command to display NetFlow cache information:

```
Router# execute-on
slot-number
show ip cache flow
```

## Examples

The following is a sample display of an autonomous system aggregation cache with the **show ip cache flow aggregation as** command:

```
Router# show ip cache flow aggregation as
IP Flow Switching Cache, 278544 bytes
  2 active, 4094 inactive, 13 added
  178 ager polls, 0 flow alloc failures
Src If      Src AS  Dst If      Dst AS  Flows  Pkts  B/Pk  Active
Fal/0      0      Null        0        1      2     49    10.2
Fal/0      0      Se2/0       20       1      5    100    0.0
```

The following is a sample display of an autonomous system aggregation cache for the prefix mask 10.0.0.0 255.0.0.0 with the **show ip cache flow aggregation as** command:

```
Router# show ip cache 10.0.0.0 255.0.0.0 flow aggregation as
IP Flow Switching Cache, 278544 bytes
  2 active, 4094 inactive, 13 added
  178 ager polls, 0 flow alloc failures
Src If      Src AS  Dst If      Dst AS  Flows  Pkts  B/Pk  Active
e1/2      0      Null        0        1      2     49    10.2
e1/2      0      e1/2       20       1      5    100    0.0
```

The following is a sample display of an destination prefix TOS cache with the **show ip cache flow aggregation destination-prefix-tos** command:

```
Router# show ip cache flow aggregation destination-prefix-tos
IP Flow Switching Cache, 278544 bytes
 7 active, 4089 inactive, 21 added
5970 aged polls, 0 flow alloc failures
Active flows timeout in 5 minutes
Inactive flows timeout in 15 seconds
IP Sub Flow Cache, 25736 bytes
 7 active, 1017 inactive, 21 added, 21 added to flow
 0 alloc failures, 0 force free
 1 chunk, 1 chunk added
Dst If      Dst Prefix      Msk AS    TOS Flows  Pkts B/Pk  Active
Null        224.0.0.0      /24 0       C0      2     6     72   132.1
Et1/0.1     172.16.30.0    /24 0       00      2    134   28   121.1
Et1/0.1     172.16.30.0    /24 0       80     12   804   780   124.6
Et1/0.1     172.16.10.0    /24 0       00      4    268  1027  121.1
Et1/0.1     172.16.10.0    /24 0       80     12   804   735   123.6
Et3/0       192.168.10.0   /24 0       80     10   669   755   121.8
Et3/0       192.168.10.0   /24 0       00      2    134   28   121.2
Router#
```

The following is a sample display of an prefix port aggregation cache with the **show ip cache flow aggregation prefix-port** command:

```
Router# show ip cache flow aggregation prefix-port
IP Flow Switching Cache, 278544 bytes
 21 active, 4075 inactive, 84 added
26596 aged polls, 0 flow alloc failures
Active flows timeout in 5 minutes
Inactive flows timeout in 15 seconds
IP Sub Flow Cache, 25736 bytes
 0 active, 1024 inactive, 0 added, 0 added to flow
 0 alloc failures, 0 force free
 1 chunk, 1 chunk added
Src If      Src Prefix      Msk Dst If      Dst Prefix      Msk Flows  Pkts
Et0/0.1     0.0.0.0        /0  Et1/0.1     172.16.10.0     /24      2     132
Et0/0.1     0.0.0.0        /0  Et1/0.1     172.16.30.0     /24      1     66
Et0/0.1     0.0.0.0        /0  Et1/0.1     172.16.30.0     /24      1     67
Et0/0.1     0.0.0.0        /0  Et1/0.1     172.16.30.0     /24      1     67
Et0/0.1     0.0.0.0        /0  Et1/0.1     172.16.10.0     /24      1     66
Et0/0.1     0.0.0.0        /0  Et1/0.1     172.16.30.0     /24      1     66
Et0/0.1     0.0.0.0        /0  Et1/0.1     172.16.30.0     /24      1     66
Et0/0.1     0.0.0.0        /0  Et1/0.1     172.16.10.0     /24      1     66
Et0/0.1     0.0.0.0        /0  Et1/0.1     172.16.10.0     /24      1     67
Et0/0.1     172.16.6.0     /24 Null        224.0.0.0       /24      1     3
Et0/0.1     0.0.0.0        /0  Et1/0.1     172.16.10.0     /24      1     66
Et2/0       0.0.0.0        /0  Et3/0       192.168.10.0    /24      1     66
Et2/0       0.0.0.0        /0  Et3/0       192.168.10.0    /24      1     66
Et0/0.1     0.0.0.0        /0  Et1/0.1     172.16.30.0     /24      1     66
Et2/0       0.0.0.0        /0  Et3/0       192.168.10.0    /24      1     66
Et0/0.1     0.0.0.0        /0  Et1/0.1     172.16.30.0     /24      1     67
Et2/0       0.0.0.0        /0  Et3/0       192.168.10.0    /24      1     67
Et0/0.1     0.0.0.0        /0  Et1/0.1     172.16.10.0     /24      1     66
Et0/0.1     0.0.0.0        /0  Et1/0.1     172.16.10.0     /24      1     66
Et2/0       0.0.0.0        /0  Et3/0       192.168.10.0    /24      1     67
Router#
```

The following is a sample display of an prefix port aggregation cache for the prefix mask 172.16.0.0 255.255.0.0 with the **show ip cache 172.16.0.0 255.255.0.0 flow aggregation prefix-port** command:

```
Router# show ip cache 172.16.0.0 255.255.0.0 flow aggregation prefix-port
IP Flow Switching Cache, 278544 bytes
 21 active, 4075 inactive, 105 added
33939 aged polls, 0 flow alloc failures
Active flows timeout in 5 minutes
Inactive flows timeout in 15 seconds
IP Sub Flow Cache, 25736 bytes
```

```

0 active, 1024 inactive, 0 added, 0 added to flow
0 alloc failures, 0 force free
1 chunk, 1 chunk added
Src If      Src Prefix    Msk  Dst If      Dst Prefix    Msk  Flows  Pkts
Et0/0.1    0.0.0.0      /0   Et1/0.1     172.16.10.0  /24   6     404
Et0/0.1    0.0.0.0      /0   Et1/0.1     172.16.30.0  /24   3     203
Et0/0.1    0.0.0.0      /0   Et1/0.1     172.16.30.0  /24   3     203
Et0/0.1    0.0.0.0      /0   Et1/0.1     172.16.30.0  /24   3     202
Et0/0.1    0.0.0.0      /0   Et1/0.1     172.16.10.0  /24   3     203
Et0/0.1    0.0.0.0      /0   Et1/0.1     172.16.30.0  /24   3     201
Et0/0.1    0.0.0.0      /0   Et1/0.1     172.16.30.0  /24   3     202
Et0/0.1    0.0.0.0      /0   Et1/0.1     172.16.10.0  /24   3     202
Et0/0.1    0.0.0.0      /0   Et1/0.1     172.16.10.0  /24   3     202
Et0/0.1    172.16.6.0   /24  Null        224.0.0.0    /24   2      6
Et0/0.1    0.0.0.0      /0   Et1/0.1     172.16.10.0  /24   3     203
Et0/0.1    0.0.0.0      /0   Et1/0.1     172.16.30.0  /24   3     203
Et0/0.1    0.0.0.0      /0   Et1/0.1     172.16.30.0  /24   3     203
Et0/0.1    0.0.0.0      /0   Et1/0.1     172.16.10.0  /24   3     202
Et0/0.1    0.0.0.0      /0   Et1/0.1     172.16.10.0  /24   3     203
Router#

```

The following is a sample display of an protocol port aggregation cache with the **show ip cache flow aggregation protocol-port** command:

```

Router# show ip cache flow aggregation protocol-port
IP Flow Switching Cache, 278544 bytes
 19 active, 4077 inactive, 627 added
150070 aged polls, 0 flow alloc failures
Active flows timeout in 5 minutes
Inactive flows timeout in 300 seconds
IP Sub Flow Cache, 25736 bytes
0 active, 1024 inactive, 0 added, 0 added to flow
0 alloc failures, 0 force free
1 chunk, 2 chunks added
Protocol  Source Port  Dest Port  Flows  Packets  Bytes/Packet  Active
0x01     0x0000      0x0000     4      270      28            242.4
0x01     0x0000      0x0000     8      541      290            244.4
0x06     0x0041      0x0041     4      271      1140           243.3
0x06     0x0041      0x0041     4      271      1140           243.4
0x11     0x00A1      0x00A1     4      271      156            243.4
0x11     0x0043      0x0043     4      271      156            243.4
0x06     0x00B3      0x00B3     4      271      1140           243.4
0x06     0x0035      0x0035     4      270      1140           242.5
0x11     0x0045      0x0045     4      271      156            243.3
0x06     0x0016      0x0015     4      270      840            242.5
0x06     0x0016      0x0015    12      810      840            244.5
0x06     0x0077      0x0077     4      271      1340           243.3
0x01     0x0000      0x0800     4      270      1500           242.5
0x06     0x0019      0x0019     4      271      168            243.4
0x06     0x0089      0x0089     4      271      296            243.4
0x11     0x0208      0x0208     3        9        72            222.1
0x06     0x00DC      0x00DC     4      271      1140           243.4
0x06     0x006E      0x006E     4      271      296            243.4
0x06     0x027C      0x027C     4      271      1240           243.4
Router#

```

The table below describes the significant fields shown in the output of the **show ip cache flow aggregation** command.

**Table 10: Field Descriptions for the show ip cache flow aggregation command**

Field	Description
bytes	Number of bytes of memory used by the NetFlow cache.
active	Number of active flows in the NetFlow cache at the time this command was entered.

Field	Description
inactive	Number of flow buffers that are allocated in the NetFlow cache, but are not currently assigned to a specific flow at the time this command is entered.
added	Number of flows created since the start of the summary period.
ager polls	Number of times the NetFlow code looked at the cache to cause entries to expire. (Used by Cisco for diagnostics only.)
Src If	Specifies the source interface.
Src AS	Specifies the source autonomous system.
Src Prefix	The prefix for the source IP addresses.
Msk	The numbers of bits in the source or destination prefix mask.
Dst If	Specifies the destination interface.
AS	Autonomous system. This is the source or destination AS number as appropriate for the keyword used. For example, if you enter the <b>show ip cache flow aggregation destination-prefix-tos</b> command, this is the destination AS number.
TOS	The value in the type of service (ToS) field in the packets.
Dst AS	Specifies the destination autonomous system.
Dst Prefix	The prefix for the destination IP addresses
Flows	Number of flows.
Pkts	Number of packets.
B/Pk	Average number of bytes observed for the packets seen for this protocol (total bytes for this protocol or the total number of flows for this protocol for this summary period).
Active	The time in seconds that this flow has been active at the time this command was entered.



Field	Description
Protocol	IP protocol □ well-known □ port number, displayed in hexadecimal format. (Refer to <a href="http://www.iana.org">http://www.iana.org</a> , Protocol Assignment Number Services , for the latest RFC values.)
Source Port	The source port value in hexadecimal.
Dest Port	The destination port value in hexadecimal.
Packets	The number of packets sene in the aggregated flow.
Bytes/Packet	The average size of packets sene in the aggregated flow.

### Related Commands

Command	Description
<b>cache</b>	Defines operational parameters for NetFlow accounting aggregation caches.
<b>enabled (aggregation cache)</b>	Enables a NetFlow accounting aggregation cache.
<b>export destination (aggregation cache)</b>	Enables the exporting of NetFlow accounting information from NetFlow aggregation caches.
<b>ip flow-aggregation cache</b>	Enables NetFlow accounting aggregation cache schemes.
<b>mask (IPv4)</b>	Specifies the source or destination prefix mask for a NetFlow accounting prefix aggregation cache.
<b>show ip cache flow aggregation</b>	Displays a summary of the NetFlow aggregation cache accounting statistics.
<b>show ip cache verbose flow</b>	Displays a detailed summary of the NetFlow accounting statistics.
<b>show ip flow export</b>	Displays the statistics for the data export.
<b>show ip flow interface</b>	Displays NetFlow accounting configuration for interfaces.

# show ip cache verbose flow

To display a detailed summary of the NetFlow accounting statistics, use the **show ip cache verbose flow** command in user EXEC or privileged EXEC mode.

**show ip cache** [*prefix mask*] [*type number*] **verbose flow**

## Syntax Description

<i>prefix mask</i>	(Optional) Displays only the entries in the cache that match the prefix and mask combination.
<i>type number</i>	(Optional) Displays only the entries in the cache that match the interface type and number combination.

## Command Modes

User EXEC (>) Privileged EXEC (#)

## Command History

Release	Modification
11.1	This command was introduced.
11.1CA	The information display for the command was updated.
12.3(1)	Support for the NetFlow Multicast Support feature was added.
12.0(24)S	Multiprotocol Label Switching (MPLS) flow records were added to the command output.
12.3(4)T	The <b>execute-on</b> command was implemented on the Cisco 7500 platforms to include the remote execution of the <b>show ip cache verbose flow</b> command.
12.3(6)	This command was integrated into Cisco IOS Release 12.3(6).
12.2(14)S	This command was integrated into Cisco IOS Release 12.2(14)S.
12.2(18)S	Support for the NetFlow Multicast Support feature was added.
12.3(8)T	MPLS flow records were added to the command output for Cisco IOS Release 12.3(8)T.
12.3(11)T	Support for egress flow accounting was added, and the [ <i>prefix mask</i> ] and [ <i>type number</i> ] arguments were removed.
12.3(14)T	Support for NetFlow Layer 2 and Security Monitoring Exports was added.
12.2(27)SBC	This command was integrated into Cisco IOS Release 12.2(27)SBC.

Release	Modification
12.2(14)SX	Support for this command was introduced on the Supervisor Engine 720.
12.2(17b)SXA	The output was changed to include hardware-entry information.
12.2(17d)SXB	Support for this command on the Supervisor Engine 2 was extended to the 12.2 SX release.
12.2(18)SXE	The output was changed to add fragment offset (FO) information on the Supervisor Engine 720 only.
12.2(18)SXF	This command was integrated into Cisco IOS Release 12.2(18)SXF.
12.2(33)SRA	This command was integrated into Cisco IOS Release 12.2(33)SRA.
12.2(31)SB2	This command was integrated into Cisco IOS Release 12.2(31)SB2.

### Usage Guidelines

Use the **show ip cache verbose flow** command to display flow record fields in the NetFlow cache in addition to the fields that are displayed with the **show ip cache flow** command. The values in the additional fields that are shown depend on the NetFlow features that are enabled and the flags that are set in the flow.



#### Note

The flags, and therefore the fields, might vary from flow to flow.

Some of the content in the display of the **show ip cache verbose flow** command uses multiline headings and multiline data fields. The figure below uses an example of the output from the **show ip cache verbose flow** to show how to associate the headings with the correct data fields when there are two or more lines of headings and two or more lines of data fields. The first line of the headings is associated with the first line of data fields. The second line of the headings is associated with the second line of data fields, and so on.

When other features such as IP Multicast are configured, the number of lines in the headings and data fields increases. The method for associating the headings with the correct data fields remains the same.

```

Router# show ip cache verbose flow
IP packet size distribution (25229 total packets):
  1-32  64  96 128 160 192 224 256 288 320 352 384 416 448 480
  .000 .000 .000 .000 .000 .000 .000 .000 .000 .000 .000 .000 .000 .000 .000
  512 544 576 1024 1536 2048 2560 3072 3584 4096 4608
  .000 .000 .000 .206 .793 .000 .000 .000 .000 .000 .000

IP Flow Switching Cache, 278544 bytes
  6 active, 4090 inactive, 17 added
  505 ager polls, 0 flow alloc failures
  Active flows timeout in 1 minutes
  Inactive flows timeout in 10 seconds
IP Sub Flow Cache, 25736 bytes
  12 active, 1012 inactive, 39 added, 17 added to flow
  0 alloc failures, 0 force free
  1 chunk, 1 chunk added
  last clearing of statistics never

```

Protocol	Total Flows	Flows /Sec	Packets /Flow	Bytes /Pkt	Packets /Sec	Active(Sec) /Flow	Idle(Sec) /Flow
TCP-Telnet	1	0.0	362	940	2.7	60.2	0.0
TCP-FTP	1	0.0	362	840	2.7	60.2	0.0
TCP-FTPD	1	0.0	362	840	2.7	60.1	0.1
TCP-SMTP	1	0.0	361	1040	2.7	60.0	0.1
UDP-other	5	0.0	1	66	0.0	1.0	10.6
ICMP	2	0.0	8829	1378	135.8	60.7	0.0
Total:	11	0.0	1737	1343	147.0	33.4	4.8

```


```

SrcIf	SrcIPaddress	DstIf	DstIPaddress	Pr	TOS	Flgs	Pkts
Port Msk AS		Port Msk AS	NextHop				Active
Et0/0.1	10.251.138.2	Et1/0.1	172.16.10.2	06	80	00	65
0015 /0 0		0015 /0 0	0.0.0.0				840 10.8
MAC: (VLAN id) aaaa.bbbb.cc03	(005)		aaaa.bbbb.cc06	(006)			
Min plen: 840			Max plen: 840				
Min TTL: 59			Max TTL: 59				
IP id: 0							

127034

## NetFlow Multicast Support

When the NetFlow Multicast Support feature is enabled, the **show ip cache verbose flow** command displays the number of replicated packets and the packet byte count for NetFlow multicast accounting. When you configure the NetFlow Version 9 Export Format feature, this command displays additional NetFlow fields in the header.

## MPLS-aware NetFlow

When you configure the MPLS-aware NetFlow feature, you can use the **show ip cache verbose flow** command to display both the IP and MPLS portions of MPLS flows in the NetFlow cache on a router line card. To display the IP portion of the flow record in the NetFlow cache when MPLS-aware NetFlow is configured, use the **show ip cache flow** command. NetFlow accounts for locally destined MPLS to IP VPN packets and displays the destination interface as Null instead of Local for these packets.

## NetFlow BGP Nexthop

The NetFlow **bgp-nexthop** command can be configured when either the Version 5 export format or the Version 9 export format is configured. The following caveats apply to the **bgp-nexthop** command:

- The values for the BGP nexthop IP address are exported to a NetFlow collector only when the Version 9 export format is configured.

- In order for the BGP information to be populated in the main cache you must either have a NetFlow export destination configured or NetFlow aggregation configured.

### Displaying Detailed NetFlow Cache Information on Platforms Running Distributed Cisco Express Forwarding

On platforms running distributed Cisco Express Forwarding, NetFlow cache information is maintained on each line card or Versatile Interface Processor. If you want to use the **show ip cache verbose flow** command to display this information on a distributed platform, you must enter the command at a line card prompt.

#### Cisco 7600 Series Platforms

The **module number** keyword and argument are supported on Distributed Forwarding Card-equipped (DFC) modules only.

#### Cisco 7500 Series Platform

The Cisco 7500 series platforms are not supported by Cisco IOS Release 12.4T and later. Cisco IOS Release 12.4 is the last Cisco IOS release to support the Cisco 7500 series platforms.

To display detailed NetFlow cache information on a Cisco 7500 series router that is running distributed Cisco Express Forwarding, enter the following sequence of commands:

```
Router# if-con  
  
slot-number  
LC-  
slot-number  
# show ip cache verbose  
  flow
```

For Cisco IOS Releases 12.3(4)T, 12.3(6), and 12.2(20)S and later, enter the following command to display detailed NetFlow cache information:

```
Router# execute-on  
slot-number  
show ip cache verbose  
  flow
```

#### Gigabit Switch Router (GSR)

To display detailed NetFlow cache information on a Gigabit Switch Router, enter the following sequence of commands:

```
Router# attach  
  
slot-number  
LC-  
slot-number  
# show ip cache verbose  
  flow
```

For Cisco IOS Releases 12.3(4)T, 12.3(6), and 12.2(20)S and later, enter the following command to display detailed NetFlow cache information:

```
Router# execute-on  
slot-number  
show ip cache verbose  
  flow
```

**Examples**

The following is sample output from the **show ip cache verbose flow** command:

```
Router# show ip cache verbose flow
IP packet size distribution (25229 total packets):
 1-32  64  96 128 160 192 224 256 288 320 352 384 416 448 480
.000 .000 .000 .000 .000 .000 .000 .000 .000 .000 .000 .000 .000 .000 .000
 512 544 576 1024 1536 2048 2560 3072 3584 4096 4608
.000 .000 .000 .206 .793 .000 .000 .000 .000 .000 .000 .000
```

The preceding output shows the percentage distribution of packets by size. In this display, 20.6 percent of the packets fall in the 1024-byte size range and 79.3 percent fall in the 1536-byte range.

The next section of the output can be divided into three sections. The section and the table corresponding to each are as follows:

```
IP Flow Switching Cache, 278544 bytes
 6 active, 4090 inactive, 17 added
 505 aged polls, 0 flow alloc failures
 Active flows timeout in 1 minutes
 Inactive flows timeout in 10 seconds
IP Sub Flow Cache, 25736 bytes
 12 active, 1012 inactive, 39 added, 17 added to flow
 0 alloc failures, 0 force free
 1 chunk, 1 chunk added
 last clearing of statistics never
```

Protocol	Total	Flows	Packets	Bytes	Packets	Active (Sec)	Idle (Sec)
-----	Flows	/Sec	/Flow	/Pkt	/Sec	/Flow	/Flow
TCP-Telnet	1	0.0	362	940	2.7	60.2	0.0
TCP-FTP	1	0.0	362	840	2.7	60.2	0.0
TCP-FTPD	1	0.0	362	840	2.7	60.1	0.1
TCP-SMTP	1	0.0	361	1040	2.7	60.0	0.1
UDP-other	5	0.0	1	66	0.0	1.0	10.6
ICMP	2	0.0	8829	1378	135.8	60.7	0.0
Total:	11	0.0	1737	1343	147.0	33.4	4.8

```
SrcIf          SrcIPAddress      DstIf          DstIPAddress    Pr TOS Flgs  Pkts
Port Msk AS    Port Msk AS      NextHop         B/Pk Active
Et0/0.1        10.251.138.218   Et1/0.1        172.16.10.2    06 80 00     65
0015 /0 0      0015 /0 0        0.0.0.0         840    10.8
MAC: (VLAN id) aaaa.bbbb.cc03 (005)      aaaa.bbbb.cc06 (006)
Min plen:      840                Max plen:      840
Min TTL:       59                Max TTL:       59
IP id:         0
Et0/0.1        172.16.6.1       Et1/0.1        172.16.10.2    01 00 00     4880
0000 /0 0      0000 /0 0        0.0.0.0         1354   20.1
MAC: (VLAN id) aaaa.bbbb.cc03 (005)      aaaa.bbbb.cc06 (006)
Min plen:      772                Max plen:      1500
Min TTL:       255                Max TTL:       255
ICMP type:     0                  ICMP code:     0
IP id:         2943                FO:           185
Et2/0          192.168.137.78  Et3/0*         192.168.10.67  06 80 00     3
0041 /0 0      0041 /24 0       172.17.7.2     1140   1.8
FFlags: 01
MAC: (VLAN id) aabb.cc00.2002 (000)      aabb.cc00.2201 (000)
Min TTL:       59                Max TTL:       59
IP id:         0
Et0/0.1        10.10.13.1       Et1/0.1        172.16.10.2    06 80 00     65
0017 /0 0      0017 /0 0        0.0.0.0         940    10.8
MAC: (VLAN id) aaaa.bbbb.cc03 (005)      aaaa.bbbb.cc06 (006)
Min plen:      940                Max plen:      940
Min TTL:       59                Max TTL:       59
IP id:         0
Et2/0          10.234.53.1      Et3/0*         192.168.10.32  06 80 00     3
0016 /0 0      0015 /24 0       172.17.7.2     840    1.7
FFlags: 01
MAC: (VLAN id) aabb.cc00.2002 (000)      aabb.cc00.2201 (000)
Min TTL:       59                Max TTL:       59
IP id:         0
Et0/0.1        10.106.1.1       Et1/0.1        172.16.10.2    01 00 00     1950
```

```

0000 /0 0          0000 /0 0          0.0.0.0          1354      8.6
MAC: (VLAN id) aaaa.bbbb.cc03 (005)  aaaa.bbbb.cc06 (006)
Min plen:      772          Max plen:      1500
Min TTL:       59          Max TTL:       59
ICMP type:     0           ICMP code:     0
IP id:         13499       FO:           185
Et2/0         10.10.18.1   Et3/0*        192.168.10.162 11 80 10      4
0045 /0 0          0045 /24 0       172.17.7.2     156      2.7
FFlags: 01
MAC: (VLAN id) aabb.cc00.2002 (000)  aabb.cc00.2201 (000)
Min TTL:       59          Max TTL:       59
IP id:         0

```

**Note**

The asterisk (\*) immediately following the □DstIf□ field indicates that the flow being shown is an egress flow.

The table below describes the significant fields shown in the NetFlow cache section of the output.

**Table 11: Field Descriptions in the NetFlow Cache Section of the Output**

Field	Description
bytes	Number of bytes of memory used by the NetFlow cache.
active	Number of active flows in the NetFlow cache at the time this command was entered.
inactive	Number of flow buffers that are allocated in the NetFlow cache but that were not assigned to a specific flow at the time this command was entered.
added	Number of flows created since the start of the summary period.
ager polls	Number of times the NetFlow code caused entries to expire (used by Cisco for diagnostics only).
flow alloc failures	Number of times the NetFlow code tried to allocate a flow but could not.
last clearing of statistics	The period of time that has passed since the <b>clear ip flow stats</b> privileged EXEC command was last executed. The standard time output format of hours, minutes, and seconds (hh:mm:ss) is used for a period of time less than 24 hours. This time output changes to hours and days after the time exceeds 24 hours.

The table below describes the significant fields shown in the activity by protocol section of the output.

**Table 12: Field Descriptions in the Activity by Protocol Section of the Output**

Field	Description
Protocol	The types of IP protocols that are in the flows.
Total Flows	Number of flows in the cache for this protocol since the last time the statistics were cleared.
Flows/Sec	Average number of flows for this protocol per second; equal to the total flows divided by the number of seconds for this summary period.
Packets/Flow	Average number of packets for the flows for this protocol; equal to the total packets for this protocol divided by the number of flows for this protocol for this summary period.
Bytes/Pkt	Average number of bytes for the packets for this protocol; equal to the total bytes for this protocol divided by the total number of packets for this protocol for this summary period.
Packets/Sec	Average number of packets for this protocol per second; equal to the total packets for this protocol divided by the total number of seconds for this summary period.
Active(Sec)/Flow	Number of seconds from the first packet to the last packet of an expired flow divided by the number of total flows for this protocol for this summary period.
Idle(Sec)/Flow	Number of seconds observed from the last packet in each nonexpired flow for this protocol until the time at which the <b>show ip cache verbose flow</b> command was entered divided by the total number of flows for this protocol for this summary period.

The table below describes the significant fields in the NetFlow record section of the output.

**Table 13: Field Descriptions for the NetFlow Record Section of the Output**

Field	Description
SrcIf	Interface on which the packet was received.
Port Msk AS	Source port number (displayed in hexadecimal format), IP address mask, and autonomous system number. The value of this field is always set to 0 in MPLS flows.



Field	Description
SrcIPAddress	IP address of the device that transmitted the packet.
DstIf	Interface from which the packet was transmitted. <b>Note</b> If an asterisk (*) immediately follows the DstIf field, the flow being shown is an egress flow.
Port Msk AS	Destination port number (displayed in hexadecimal format), IP address mask, and autonomous system. This is always set to 0 in MPLS flows.
DstIPAddress	IP address of the destination device.
NextHop	The BGP next-hop address. This is always set to 0 in MPLS flows.
Pr	IP protocol <input type="checkbox"/> well-known <input type="checkbox"/> port number, displayed in hexadecimal format. (Refer to <a href="http://www.iana.org">http://www.iana.org</a> , Protocol Assignment Number Services, for the latest RFC values.)
ToS	Type of service, displayed in hexadecimal format.
B/Pk	Average number of bytes observed for the packets seen for this protocol.
Flgs	TCP flags, shown in hexadecimal format (result of bitwise OR of TCP flags from all packets in the flow).
Pkts	Number of packets in this flow.
Active	The time in seconds that this flow has been active at the time this command was entered.
MAC	Source and destination MAC addresses from the Layer 2 frames in the flow.
VLAN id	Source and destination VLAN IDs from the Layer 2 frames in the flow.
Min plen	Minimum packet length for the packets in the flows. <b>Note</b> This value is updated when a datagram with a lower value is received.
Max plen	Maximum packet length for the packets in the flows. <b>Note</b> This value is updated when a datagram with a higher value is received.

Field	Description
Min TTL	Minimum Time-To-Live (TTL) for the packets in the flows. <b>Note</b> This value is updated when a datagram with a lower value is received.
Max TTL	Maximum TTL for the packets in the flows. <b>Note</b> This value is updated when a datagram with a higher value is received.
IP id	IP identifier field for the packets in the flow.
ICMP type	Internet Control Message Protocol (ICMP) type field from the ICMP datagram in the flow.
ICMP code	ICMP code field from the ICMP datagram in the flow.
FO	Value of the fragment offset field from the first fragmented datagram in the second flow.

The following example shows the NetFlow output from the **show ip cache verbose flow** command in which the sampler, class ID, and general flags are set. What is displayed for a flow depends on what flags are set in the flow. If the flow was captured by a sampler, the output shows the sampler ID. If the flow was marked by Modular QoS CLI (MQC), the display includes the class ID. If any general flags are set, the output includes the flags.

```
Router# show ip cache verbose flow
.
.
.
SrcIf          SrcIPAddress      DstIf          DstIPAddress    Pr TOS Flgs Pkts
Port Msk AS    Port Msk AS    NextHop
BGP: BGP NextHop
Et1/0         10.8.8.8          Et0/0*        10.9.9.9        01 00 10    3
0000 /8 302          0800 /8 300    10.3.3.3        100    0.1
BGP: 2.2.2.2          Sampler: 1 Class: 1 FFlags: 01
```

The table below describes the significant fields shown in the NetFlow output for a sampler, for an MQC policy class, and for general flags.

**Table 14: show ip cache verbose flow Field Descriptions for a NetFlow Sampler, an MQC Policy Class, and General Flags**

Field (with Sample Values)	Description
Sampler	ID of the sampler that captured the flow. The sampler ID in this example is 1.
Class	ID of the Modular QoS CLI (MQC) traffic class. The class ID in this example is 1.

Field (with Sample Values)	Description
FFlags	<p>General flow flag (shown in hexadecimal format), which is either the bitwise or one or more of the following:</p> <ul style="list-style-type: none"> <li>• 01 indicates an output (or egress) flow. (If this bit is not set, the flow is an input [or ingress] flow.)</li> <li>• 02 indicates a flow that was dropped (for example, by an access control list [ACL]).</li> <li>• 04 indicates a Multiprotocol Label Switching (MPLS) flow.</li> <li>• 08 indicates an IP version 6 (IPv6) flow.</li> </ul> <p>The flow flag in this example is 01 (an egress flow).</p>

The following example shows the NetFlow output from the **show ip cache verbose flow** command when NetFlow BGP next-hop accounting is enabled:

```
Router# show ip cache verbose flow
.
.
.
SrcIf          SrcIPAddress  DstIf          DstIPAddress  Pr TOS Flgs  Pkts
Port Msk AS    Port Msk AS    NextHop
BGP:BGP_NextHop
Et0/0/2       10.0.0.2      Et0/0/4        10.0.0.5      01 00 10     20
0000 /8 0      0800 /8 0      10.0.0.6      100          0.0
BGP:26.0.0.6
Et0/0/2       10.0.0.2      Et0/0/4        10.0.0.7      01 00 10     20
0000 /8 0      0800 /8 0      10.0.0.6      100          0.0
BGP:26.0.0.6
Et0/0/2       10.0.0.2      Et0/0/4        10.0.0.7      01 00 10     20
0000 /8 0      0000 /8 0      10.0.0.6      100          0.0
BGP:26.0.0.6
```

The table below describes the significant fields shown in the NetFlow BGP next-hop accounting lines of the output.

**Table 15: show ip cache verbose flow Field Descriptions in NetFlow BGP Next-Hop Accounting Output**

Field	Description
BGP:BGP_NextHop	Destination address for the BGP next hop.

The following example shows the NetFlow output from the **show ip cache verbose flow** command when NetFlow multicast accounting is configured:

```
Router# show ip cache verbose flow
```

```
.
.
.
```

```

SrcIf          SrcIPAddress  DstIf          DstIPAddress  Pr TOS Flgs Pkts
Port Msk AS   OBytes         Port Msk AS   NextHop       B/Pk Active
IPM:OPkts
IPM: 0        0
Et1/1/1       10.0.0.1      Null           192.168.1.1   01 55 10    100
0000 /8 0     2800          0000 /0 0     0.0.0.0      28    0.0
IPM: 100
Et1/1/1       10.0.0.1      Se2/1/1.16    192.168.1.1   01 55 10    100
0000 /8 0     0             0000 /0 0     0.0.0.0      28    0.0
IPM: 0
Et1/1/2       10.0.0.1      Et1/1/4       192.168.2.2   01 55 10    100
0000 /8 0     0             0000 /0 0     0.0.0.0      28    0.1
Et1/1/2       10.0.0.1      Null           192.168.2.2   01 55 10    100
0000 /8 0     2800          0000 /0 0     0.0.0.0      28    0.1
IPM: 100

```

The table below describes the significant fields shown in the NetFlow multicast accounting lines of the output.

**Table 16: show ip cache verbose flow Field Descriptions in NetFlow Multicast Accounting Output**

Field	Description
OPkts	Number of IP multicast (IPM) output packets.
OBytes	Number of IPM output bytes.
DstIPAddress	Destination IP address for the IPM output packets.

The following example shows the output for both the IP and MPLS sections of the flow record in the NetFlow cache when MPLS-aware NetFlow is enabled:

```

Router# show ip cache verbose flow
.
.
.
SrcIf          SrcIPAddress  DstIf          DstIPAddress  Pr TOS Flgs Pkts
Port Msk AS   Port Msk AS   NextHop       B/Pk Active
PO3/0         10.1.1.1     PO5/1         10.2.1.1     01 00 10    9
0100 /0 0     0200 /0 0     0.0.0.0      100    0.0
Pos:Lbl-Exp-S 1:12305-6-0 (LDP/10.10.10.10) 2:12312-6-1

```

The table below describes the significant fields for the IP and MPLS sections of the flow record in the output.

**Table 17: show ip cache verbose flow Field Descriptions for the IP and MPLS Sections of the Flow Record in the Output**

Field	Description
Pos	Position of the MPLS label in the label stack, starting with 1 as the top label.
Lbl	Value given to the MPLS label by the router.
Exp	Value of the experimental bit.
S	Value of the end-of-stack bit. Set to 1 for the oldest entry in the stack and to 0 for all other entries.
LDP/10.10.10.10	Type of MPLS label and associated IP address for the top label in the MPLS label stack.

**Related Commands**

<b>Command</b>	<b>Description</b>
<b>attach</b>	Connects to a specific line card for the purpose of executing monitoring and maintenance commands on that line card only.
<b>clear ip flow stats</b>	Clears the NetFlow accounting statistics.
<b>execute-on</b>	Executes commands on a line card.
<b>show ip cache flow</b>	Displays a summary of the NetFlow accounting statistics.
<b>show ip flow interface</b>	Displays NetFlow accounting configuration for interfaces.
<b>show ip interface</b>	Displays the usability status of interfaces configured for IP.

## show ip cache verbose flow aggregation

To display the aggregation cache configuration, use the show ip cache verbose flow aggregation command in user EXEC and privileged EXEC mode.

```
show ip cache [prefix mask] [interface-type interface-number] [verbose] flow aggregation {as| as-tos|
bgp-nexthop-tos| destination-prefix| destination-prefix-tos| prefix| prefix-port| prefix-tos| protocol-port|
protocol-port-tos| source-prefix| source-prefix-tos| exp-bgp-prefix}
```

### Syntax Description

<i>prefix mask</i>	(Optional) Displays only the entries in the cache that match the prefix and mask combination.
<i>interface-type interface-number</i>	(Optional) Displays only the entries in the cache that match the interface type and interface number combination.
<b>verbose</b>	(Optional) Displays additional information from the aggregation cache.
<b>as</b>	Displays the configuration of the autonomous system aggregation cache scheme.
<b>as-tos</b>	Displays the configuration of the autonomous system type of service (ToS) aggregation cache scheme.
<b>bgp-nexthop-tos</b>	Displays the BGP next hop and ToS aggregation cache scheme.  <b>Note</b> This keyword is not supported on the Cisco ASR 1000 Series Aggregation Services Router.
<b>destination-prefix</b>	Displays the configuration of the destination prefix aggregation cache scheme.
<b>destination-prefix-tos</b>	Displays the configuration of the destination prefix ToS aggregation cache scheme.
<b>prefix</b>	Displays the configuration of the prefix aggregation cache scheme.
<b>prefix-port</b>	Displays the configuration of the prefix port aggregation cache scheme.
<b>prefix-tos</b>	Displays the configuration of the prefix ToS aggregation cache scheme.
<b>protocol-port</b>	Displays the configuration of the protocol port aggregation cache scheme.

<b>protocol-port-tos</b>	Displays the configuration of the protocol port ToS aggregation cache scheme.
<b>source-prefix</b>	Displays the configuration of the source prefix aggregation cache scheme.
<b>source-prefix-tos</b>	Displays the configuration of the source prefix ToS aggregation cache scheme.
<b>exp-bgp-prefix</b>	Displays the configuration of the exp-bgp-prefix aggregation cache scheme.

**Command Modes**

User EXEC Privileged EXEC

**Command History**

<b>Release</b>	<b>Modification</b>
12.0(3)T	This command was introduced.
12.0(15)S	This command was modified to include new <b>show</b> output for ToS aggregation schemes.
12.2(14)S	This command was integrated into Cisco IOS Release 12.2(14)S.
12.3(1)	Support for the BGP Next Hop Support feature was added.
12.2(18)S	Support for the BGP Next Hop Support feature was added.
12.2(27)SBC	This command was integrated into Cisco IOS Release 12.2(27)SBC.
12.2(14)SX	Support for this command was introduced on the Supervisor Engine 720.
12.2(17b)SXA	The output was changed to include hardware-entry information.
12.2(17d)SXB	Support for this command on the Supervisor Engine 2 was extended to the 12.2 SX release.
12.2(18)SXE	The output was changed to add fragment offset (FO) information on the Supervisor Engine 720 only.
12.2(18)SXF	This command was integrated into Cisco IOS Release 12.2(18)SXF.
12.2(33)SRA	This command was integrated into Cisco IOS Release 12.2(33)SRA.
12.2(31)SB2	This command was integrated into Cisco IOS Release 12.2(31)SB2. The <b>exp-bgp-prefix</b> aggregation cache was added.

**Usage Guidelines**

Use the **show ip cache verbose flow aggregation** command to display flow record fields in the NetFlow aggregation cache in addition to the fields that are displayed with the **show ip cache flow aggregation** command. The values in the additional fields that are shown depend on the NetFlow features that are enabled and the flags that are set in the flow.

**Note**

The flags, and therefore the fields, might vary from flow to flow.

Some of the content in the display of the **show ip cache verbose flow aggregation** command uses multiline headings and multiline data fields. Below is an example of the output from the **show ip cache verbose flow** to show how to associate the headings with the correct data fields when there are two or more lines of headings and two or more lines of data fields. The first line of the headings is associated with the first line of data fields. The second line of the headings is associated with the second line of data fields, and so on.

When other features such as IP Multicast are configured, the number of lines in the headings and data fields increases. The method for associating the headings with the correct data fields remains the same

```
Router# show ip cache verbose flow
IP packet size distribution (25229 total packets):
 1-32  64  96 128 160 192 224 256 288 320 352 384 416 448 480
 .000 .000 .000 .000 .000 .000 .000 .000 .000 .000 .000 .000 .000 .000 .000
 512  544  576 1024 1536 2048 2560 3072 3584 4096 4608
 .000 .000 .000 .206 .793 .000 .000 .000 .000 .000 .000
```

```
IP Flow Switching Cache, 278544 bytes
6 active, 4090 inactive, 17 added
505 ager polls, 0 flow alloc failures
Active flows timeout in 1 minutes
Inactive flows timeout in 10 seconds
```

```
IP Sub Flow Cache, 25736 bytes
12 active, 1012 inactive, 39 added, 17 added to flow
0 alloc failures, 0 force free
1 chunk, 1 chunk added
last clearing of statistics never
```

Protocol	Total Flows	Flows /Sec	Packets /Flow	Bytes /Pkt	Packets /Sec	Active (Sec) /Flow	Idle (Sec) /Flow
TCP-Telnet	1	0.0	362	940	2.7	60.2	0.0
TCP-FTP	1	0.0	362	840	2.7	60.2	0.0
TCP-FTPD	1	0.0	362	840	2.7	60.1	0.1
TCP-SMTP	1	0.0	361	1040	2.7	60.0	0.1
UDP-other	5	0.0	1	66	0.0	1.0	10.6
ICMP	2	0.0	8829	1378	135.8	60.7	0.0
Total:	11	0.0	1737	1343	147.0	33.4	4.8

SrcIf	SrcIPaddress	DstIf	DstIPaddress	Pr	TOS	Flgs	Pkts
Port Msk AS		Port Msk AS	NextHop				Active
Et0/0.1	10.251.138.2	Et1/0.1	172.16.10.2	06	80	00	65
0015 /0 0		0015 /0 0	0.0.0.0				840 10.8
MAC: (VLAN id) aaaa.bbbb.cc03	(005)		aaaa.bbbb.cc06	(006)			
Min plen: 840			Max plen: 840				
Min TTL: 59			Max TTL: 59				
IP id: 0							

127034



### NetFlow Multicast Support

When the NetFlow Multicast Support feature is enabled, the **show ip cache verbose flow** command displays the number of replicated packets and the packet byte count for NetFlow multicast accounting. When you configure the NetFlow Version 9 Export Format feature, this command displays additional NetFlow fields in the header.

### MPLS-aware NetFlow

When you configure the MPLS-aware NetFlow feature, you can use the **show ip cache verbose flow** command to display both the IP and MPLS portions of MPLS flows in the NetFlow cache on a router line card. To display only the IP portion of the flow record in the NetFlow cache when MPLS-aware NetFlow is configured, use the **show ip cache flow** command.

### NetFlow BGP Nexthop

The NetFlow **bgp-nexthop** command can be configured when either the Version 5 export format or the Version 9 export format is configured. The following caveats apply to the **bgp-nexthop** command:

- The values for the BGP nexthop IP address are exported to a NetFlow collector only when the Version 9 export format is configured.
- In order for the BGP information to be populated in the main cache you must either have a NetFlow export destination configured or NetFlow aggregation configured.

### Displaying Detailed NetFlow Cache Information on Platforms Running Distributed Cisco Express Forwarding

On platforms running distributed Cisco Express Forwarding, NetFlow cache information is maintained on each line card or Versatile Interface Processor. If you want to use the **show ip cache verbose flow** command to display this information on a distributed platform, you must enter the command at a line card prompt.

#### Cisco 7600 Series Platforms

The **module num** keyword and argument are supported on DFC-equipped modules only.

#### Cisco 7500 Series Platform

The Cisco 7500 series platforms are not supported by Cisco IOS Release 12.4T and later. Cisco IOS Release 12.4 is the last Cisco IOS release to support the Cisco 7500 series platforms.

To display detailed NetFlow cache information on a Cisco 7500 series router that is running distributed Cisco Express Forwarding, enter the following sequence of commands:

```
Router# if-con  
  
slot-number  
LC-  
slot-number  
# show ip cache verbose  
  flow
```

For Cisco IOS Releases 12.3(4)T, 12.3(6), and 12.2(20)S and later, enter the following command to display detailed NetFlow cache information:

```
Router# execute-on  
slot-number  
show ip cache verbose  
  flow
```

#### Cisco 12000 Series Platform

To display detailed NetFlow cache information on a Cisco 12000 Series Internet Router, enter the following sequence of commands:

```
Router# attach

slot-number
LC-
slot-number
# show ip cache verbose
flow
```

For Cisco IOS Releases 12.3(4)T, 12.3(6), and 12.2(20)S and later, enter the following command to display detailed NetFlow cache information:

```
Router# execute-on
slot-number
show ip cache verbose
flow
```

## Examples

The following is a sample display of an prefix port aggregation cache with the **show ip cache verbose flow aggregation prefix-port** command:

```
Router# show ip cache verbose flow aggregation prefix-port
IP Flow Switching Cache, 278544 bytes
 20 active, 4076 inactive, 377 added
 98254 aged polls, 0 flow alloc failures
 Active flows timeout in 5 minutes
 Inactive flows timeout in 15 seconds
IP Sub Flow Cache, 25736 bytes
 0 active, 1024 inactive, 0 added, 0 added to flow
 0 alloc failures, 0 force free
 1 chunk, 1 chunk added
Src If          Src Prefix      Dst If          Dst Prefix      TOS Flows      Pkts
                Port Msk                Port Msk        Pr  B/Pk  Active
Et0/0.1        0.0.0.0         Et1/0.1         172.16.10.0    80   2     136
                0016 /0         0015 /24        06   840   62.2
Et0/0.1        0.0.0.0         Et1/0.1         172.16.30.0    80   1     68
                00B3 /0         00B3 /24        06  1140   60.3
Et0/0.1        0.0.0.0         Et1/0.1         172.16.30.0    80   1     68
                0043 /0         0043 /24        11   156   60.3
Et0/0.1        0.0.0.0         Et1/0.1         172.16.30.0    00   1     68
                0000 /0         0000 /24        01   28    60.3
Et0/0.1        0.0.0.0         Et1/0.1         172.16.10.0    80   1     68
                0035 /0         0035 /24        06  1140   60.3
Et0/0.1        0.0.0.0         Et1/0.1         172.16.30.0    80   1     68
                0041 /0         0041 /24        06  1140   60.3
Et2/0          0.0.0.0         Et3/0           192.168.10.0   80   1     68
                006E /0         006E /24        06   296   60.3
FFlags: 01
Et0/0.1        0.0.0.0         Et1/0.1         172.16.30.0    80   1     68
                0016 /0         0015 /24        06   840   60.3
Et0/0.1        0.0.0.0         Et1/0.1         172.16.10.0    00   1     68
                0000 /0         0000 /24        01   554   60.3
Et0/0.1        0.0.0.0         Et1/0.1         172.16.10.0    80   1     68
                00A1 /0         00A1 /24        11   156   60.3
Et0/0.1        0.0.0.0         Et1/0.1         172.16.10.0    80   1     67
                00DC /0         00DC /24        06  1140   59.4
Et2/0          0.0.0.0         Et3/0           192.168.10.0   00   1     68
                0000 /0         0000 /24        01   28    60.2
FFlags: 01
Et2/0          0.0.0.0         Et3/0           192.168.10.0   80   1     67
                0041 /0         0041 /24        06  1140   59.4
FFlags: 01
Et0/0.1        0.0.0.0         Et1/0.1         172.16.30.0    80   1     68
                0019 /0         0019 /24        06   168   60.3
Et2/0          0.0.0.0         Et3/0           192.168.10.0   80   1     68
                0016 /0         0015 /24        06   840   60.3
FFlags: 01
```

```

Et0/0.1      0.0.0.0      Et1/0.1      172.16.30.0   80    1    67
              027C /0
Et2/0        0.0.0.0      Et3/0        192.168.10.0  80    1    68
              0077 /0
FFlags: 01
Et0/0.1      0.0.0.0      Et1/0.1      172.16.10.0   00    1    68
              0000 /0
Et0/0.1      0.0.0.0      Et1/0.1      172.16.10.0   80    1    68
              0089 /0
Et2/0        0.0.0.0      Et3/0        192.168.10.0  80    1    68
              0045 /0
FFlags: 01
Router#

```

The table below describes the significant fields shown in the output of the **show ip cache verbose flow aggregation prefix-port** command.

**Table 18: show ip cache verbose flow aggregation Field Descriptions**

Field	Description
Src If	Specifies the source interface.
Src AS	Specifies the source autonomous system.
Src Prefix	The prefix for the source IP addresses.
Msk	The numbers of bits in the source or destination prefix mask.
Dst If	Specifies the destination interface.
AS	Autonomous system. This is the source or destination AS number as appropriate for the keyword used. For example, if you enter the <b>show ip cache flow aggregation destination-prefix-tos</b> command, this is the destination AS number.
TOS	The value in the type of service (ToS) field in the packets.
Dst AS	Specifies the destination autonomous system.
Dst Prefix	The prefix for the destination IP addresses
Flows	Number of flows.
Pkts	Number of packets.
Port	The source or destination port number.
Msk	The source or destination prefix mask.

Field	Description
Pr	IP protocol <input type="checkbox"/> well-known <input type="checkbox"/> port number, displayed in hexadecimal format. (Refer to <a href="http://www.iana.org">http://www.iana.org</a> , Protocol Assignment Number Services , for the latest RFC values.)
B/Pk	Average number of bytes observed for the packets seen for this protocol (total bytes for this protocol or the total number of flows for this protocol for this summary period).
Active	The time in seconds that this flow has been active at the time this command was entered.

The following is a sample display of an exp-bgp-prefix aggregation cache with the **show ip cache verbose flow aggregation exp-bgp-prefix** command:

```
Router# show ip cache verbose flow aggregation exp-bgp-prefix
IP Flow Switching Cache, 278544 bytes
  1 active, 4095 inactive, 4 added
  97 ager polls, 0 flow alloc failures
  Active flows timeout in 30 minutes
  Inactive flows timeout in 15 seconds
IP Sub Flow Cache, 17032 bytes
  1 active, 1023 inactive, 4 added, 4 added to flow
  0 alloc failures, 0 force free
  1 chunk, 1 chunk added
Src If      BGP NextHop    Label  MPLS EXP    Flows    Pkts    B/Pk    Active
Gi4/0/0.102 10.40.40.40    0      0           1        5       100     0.0
```

The table below describes the significant fields shown in the output of the **show ip cache verbose flow aggregation exp-bgp-prefix** command.

**Table 19: show ip cache verbose flow aggregation Field Descriptions**

Field	Description
Src If	Specifies the source interface.
Flows	Number of flows.
Pkts	Number of packets.
B/Pk	Average number of bytes observed for the packets seen for this protocol (total bytes for this protocol or the total number of flows for this protocol for this summary period).
Active	Number of active flows in the NetFlow cache at the time this command was entered.
BGP NextHop	The exit point from the MPLS cloud.

Field	Description
Label	The MPLS label value. <b>Note</b> This value is set to zero on the Cisco 10000.
MPLS EXP	The 3-bit value of the MPLS labels EXP field.

**Related Commands**

Command	Description
<b>cache</b>	Defines operational parameters for NetFlow accounting aggregation caches.
<b>enabled (aggregation cache)</b>	Enables a NetFlow accounting aggregation cache.
<b>export destination (aggregation cache)</b>	Enables the exporting of NetFlow accounting information from NetFlow aggregation caches.
<b>ip flow-aggregation cache</b>	Enables NetFlow accounting aggregation cache schemes.
<b>mask (IPv4)</b>	Specifies the source or destination prefix mask for a NetFlow accounting prefix aggregation cache.
<b>show ip cache flow aggregation</b>	Displays a summary of the NetFlow aggregation cache accounting statistics.
<b>show ip cache verbose flow</b>	Displays a detailed summary of the NetFlow accounting statistics.
<b>show ip flow export</b>	Displays the statistics for the data export.
<b>show ip flow interface</b>	Displays NetFlow accounting configuration for interfaces.

# show ip flow export

To display the status and the statistics for NetFlow accounting data export, including the main cache and all other enabled caches, use the show ip flow export command in user EXEC or privileged EXEC mode.

**show ip flow export [sctp] [verbose] [template| nbar]**

## Syntax Description

<b>sctp</b>	(Optional) Displays the status and statistics for export destinations that are configured to use the Stream Control Transmission Protocol (SCTP).
<b>verbose</b>	(Optional) Displays the current values for the SCTP fail-over and restore-time timers in addition to the status and statistics that are displayed by the <b>show ip flow export sctp</b> command.  For a Multiprotocol Label Switching (MPLS) Prefix/Application/Label (PAL) record, displays additional export information, such as the number of MPLS PAL records exported to a NetFlow collector.
<b>template</b>	(Optional) Displays the data export statistics (such as template timeout and refresh rate) for the template-specific configurations.
<b>nbar</b>	(Optional) Displays cumulative Network-Based Application Recognition (NBAR) statistics.

## Command Modes

User EXEC (>) Privileged EXEC (#)

## Command History

Release	Modification
11.1CC	This command was introduced.
12.2(2)T	This command was modified to display multiple NetFlow export destinations.
12.0(24)S	The <b>template</b> keyword was added.
12.3(1)	Support for the NetFlow v9 Export Format feature was added.
12.2(14)S	This command was integrated into Cisco IOS Release 12.2(14)S.
12.2(18)S	Support for the NetFlow v9 Export Format, and Multiple Export Destination features was added.

Release	Modification
12.2(27)SBC	This command was integrated into Cisco IOS Release 12.2(27)SBC.
12.2(14)SX	Support for this command was introduced on the Supervisor Engine 720.
12.2(18)SXD	The output was changed to include information about NDE for hardware-switched flows.
12.2(18)SXF	This command was integrated into Cisco IOS Release 12.2(18)SXF.
12.4(4)T	The <b>sctp</b> and <b>verbose</b> keywords were added.
12.2(28)SB	The number of MPLS PAL records exported by NetFlow was added to the <b>verbose</b> keyword output.
12.2(33)SRA	This command was integrated into Cisco IOS Release 12.2(33)SRA.
12.2(31)SB2	This command was integrated into Cisco IOS Release 12.2(31)SB2.
12.2(33)SXI	The output was modified to display the data export version and aggregation cache scheme.
12.4(24)T	The output was modified to display information about Border Gateway Protocol (BGP) next-hop.
12.2(18)ZYA2	This command was modified. The <b>nbar</b> keyword was added.

## Examples

The following is sample output from the **show ip flow export** command with NetFlow export over User Datagram Protocol (UDP) (the default NetFlow export transport protocol) configured on the networking device:



**Note** No NetFlow export over SCTP destinations are configured.

```
Router# show ip flow export
Flow export v9 is enabled for main cache
  Exporting flows to 172.17.10.2 (100)
  Exporting using source interface Loopback0
  Version 9 flow records, origin-as bgp-nexthop
  Cache for as aggregation v9
  62 flows exported in 17 udp datagrams
  0 flows failed due to lack of export packet
  8 export packets were sent up to process level
  0 export packets were dropped due to no fib
  0 export packets were dropped due to adjacency issues
  0 export packets were dropped due to fragmentation failures
  0 export packets were dropped due to encapsulation fixup failures
  0 export packets were dropped enqueueing for the RP
  0 export packets were dropped due to IPC rate limiting
  0 export packets were dropped due to output drops
```

The following is sample output from the **show ip flow export** command with NetFlow export over UDP and NetFlow SCTP export destinations configured:

```
Router# show ip flow export

Flow export v9 is enabled for main cache
  Exporting flows to 172.17.10.2 (100)
  Exporting flows to 172.16.45.57 (100) via SCTP
  Exporting using source interface Loopback0
  Version 9 flow records, origin-as bgp-nexthop
  Cache for as aggregation v9
    Exporting flows to 192.168.247.198 (200) via SCTP
    Exporting using source IP address 172.16.254.254
  479 flows exported in 318 udp datagrams
  467 flows exported in 315 sctp messages
  0 flows failed due to lack of export packet
  159 export packets were sent up to process level
  0 export packets were dropped due to no fib
  0 export packets were dropped due to adjacency issues
  0 export packets were dropped due to fragmentation failures
  0 export packets were dropped due to encapsulation fixup failures
```

The table below describes the significant fields shown in the display of the **show ip flow export** command.

**Table 20: show ip flow export Field Descriptions**

Field	Description
Exporting flows to	Indicates the export destinations and ports. The ports are in parentheses.  <b>Note</b> When the export destination is configured with the NetFlow Reliable Transport Using SCTP feature the port number is followed by the text “via SCTP” in the display output.
Exporting using source IP address or Exporting using source interface	Indicates the source IP address or source interface.  <b>Note</b> The source interface is used when you have configured the <b>ip flow-export sourceinterface-type interface-number</b> command.
Version flow records	Displays the version of the flow records.
Cache for destination-prefix aggregation	Indicates the type of NetFlow aggregation caches that are configured.  <b>Note</b> The indented lines below the name of the NetFlow aggregation cache indicate the export parameters that are configured for this cache.
Flows exported in udp datagrams	Indicates the total number of export packets (datagrams) sent over UDP, and the total number of flows contained within them.



Field	Description
Flows exported in sctp messages	Displays the total number of export packets (messages) sent over SCTP, and the total number of flows contained within them.  <b>Note</b> SCTP is a message-oriented transport protocol. Therefore, SCTP traffic is referred to as messages instead of datagrams.
Flows failed due to lack of export packet	Indicates the number of flows that failed because no memory was available to create an export packet.
Export packets were sent up to process level	The packet could not be processed by Cisco Express Forwarding or by fast switching.
Export packets were dropped due to no fib Export packets were dropped due to adjacency issues	Indicates the number of packets that Cisco Express Forwarding was unable to switch, or forward to the process level.
Export packets were dropped due to fragmentation failures Export packets were dropped due to encapsulation fixup failures	Indicates the number of packets that were dropped because of problems constructing the IP packet.
Export packets were dropped enqueueing for the RP Export packets were dropped due to IPC rate limiting	Indicates the number of times that there was a problem transferring the export packet between the RP and the line card.
Export packets were dropped due to output drops	Indicates the number of times the packets were dropped when the send queue was full.

The following is sample output from the **show ip flow export sctp** command with NetFlow SCTP export primary and backup SCTP export destinations configured for the NetFlow main cache and the NetFlow destination-prefix aggregation cache. The primary SCTP export destinations are active:

```
Router# show ip flow export sctp

IPv4 main cache exporting to 172.16.45.57, port 100, none
status: connected
backup mode: fail-over
912 flows exported in 619 sctp messages.
0 packets dropped due to lack of SCTP resources
fail-over time: 25 milli-seconds
restore time: 25 seconds
backup: 192.168.247.198, port 200
status: not connected
fail-overs: 2
9 flows exported in 3 sctp messages.
0 packets dropped due to lack of SCTP resources
destination-prefix cache exporting to 172.16.12.200, port 100, full
status: connected
backup mode: redundant
682 flows exported in 611 sctp messages.
0 packets dropped due to lack of SCTP resources
fail-over time: 25 milli-seconds
```

```

restore time: 25 seconds
backup: 192.168.247.198, port 200
  status: connected
  fail-overs: 8
  2 flows exported in 2 sctp messages.
  0 packets dropped due to lack of Sctp resources

```

The following is sample output from the **show ip flow export sctp** command with NetFlow Sctp export primary and backup Sctp export destinations configured for the NetFlow main cache and the NetFlow destination-prefix aggregation cache. The backup Sctp export destinations are active because the primary Sctp export destinations are unavailable.

```
Router# show ip flow export sctp
```

```

IPv4 main cache exporting to 172.16.45.57, port 100, none
status: fail-over
backup mode: fail-over
922 flows exported in 625 sctp messages.
0 packets dropped due to lack of Sctp resources
fail-over time: 25 milli-seconds
restore time: 25 seconds
backup: 192.168.247.198, port 200
  status: connected, active for 00:00:24
  fail-overs: 3
  11 flows exported in 4 sctp messages.
  0 packets dropped due to lack of Sctp resources
destination-prefix cache exporting to 172.16.12.200, port 100, full
status: fail-over
backup mode: redundant
688 flows exported in 617 sctp messages.
0 packets dropped due to lack of Sctp resources
fail-over time: 25 milli-seconds
restore time: 25 seconds
backup: 192.168.247.198, port 200
  status: connected, active for 00:00:00
  fail-overs: 13
  2 flows exported in 2 sctp messages.
  0 packets dropped due to lack of Sctp resources
Router#

```

The table below describes the significant fields shown in the display of the **show ip flow export sctp** and the **show ip flow export sctp verbose** commands.

**Table 21: show ip flow export sctp Field Descriptions**

Field	Description
IPv4 main cache exporting to 172.16.45.57, port 100, none	<p>Indicates the type of cache, the IP address and port number used to reach the destination, and the level of reliability for the association:</p> <ul style="list-style-type: none"> <li>• IPv4 main cache--The type of NetFlow cache to which the display output applies.</li> <li>• 172.16.45.57--The IP address used for the Sctp export destination.</li> <li>• port 100--The Sctp port used for the Sctp export destination.</li> <li>• none--The level of reliability for this association.</li> </ul> <p><b>Note</b> The reliability options are full and none.</p>

Field	Description
status	<p>The current state of each association. The states are:</p> <ul style="list-style-type: none"> <li>• initializing--The association is being established.</li> <li>• connected--The association is established.</li> </ul> <p><b>Note</b> If this is a backup SCTP export destination configured for fail-over mode, you see an additional message indicating how long the association has been active. For example, active for 00:00:01.</p> <ul style="list-style-type: none"> <li>• not connected--The association will be established when the primary SCTP export backup destination is no longer available.</li> <li>• fail-over--The primary SCTP export destination is no longer available. The backup SCTP export destination is being used.</li> <li>• re-establishing--An association that has been active before is being reestablished.</li> </ul>
backup mode	<p>The backup mode of each association. The modes are:</p> <ul style="list-style-type: none"> <li>• redundant--The association is established (connected).</li> </ul> <p><b>Note</b> The fact that the association is established does not mean that it is being used to export NetFlow data.</p> <ul style="list-style-type: none"> <li>• fail-over--The association will be established after the primary association fails.</li> </ul>
flows exported in sctp messages	<p>Indicates the total number of export packets (messages) sent over SCTP, and the total number of flows contained within them.</p> <p><b>Note</b> SCTP is a message-oriented transport protocol. Therefore, SCTP traffic is referred to as messages instead of datagrams.</p>
packets dropped due to lack of SCTP resources	<p>The number of packets that were dropped due to lack of SCTP resources.</p>

Field	Description
fail-over time: milli-seconds	<p>The period of time that the networking device waits after losing connectivity to the primary SCTP export destination before attempting to use a backup SCTP export destination.</p> <p><b>Note</b> This field is displayed when you use the <b>verbose</b> keyword after the <b>show ip flow export sctp</b> command.</p>
restore time: seconds	<p>The period of time that the networking device waits before reverting to the primary SCTP export destination after connectivity to it has been restored.</p> <p><b>Note</b> This field is displayed when you use the <b>verbose</b> keyword after the <b>show ip flow export sctp</b> command.</p>
backup: 192.168.247.198 port 200	<p>The IP address and SCTP port used for the SCTP export backup destination.</p> <ul style="list-style-type: none"> <li>• 192.168.247.198--The IP address of the SCTP backup association.</li> <li>• port 200--The SCTP port used for the SCTP backup association.</li> </ul>
fail-overs	The number of times that fail-over has occurred.
destination-prefix cache exporting to 172.16.12.200, port 100, full	<p>Indicates the type of cache configures, the destination address and port number for the SCTP export, and the level of reliability for the association:</p> <ul style="list-style-type: none"> <li>• destination-prefix cache--The type of NetFlow aggregation cache configured.</li> <li>• 172.16.12.200--The IP address used for the SCTP export destination.</li> <li>• port 100--Indicates the SCTP port used for the SCTP export destination.</li> <li>• full--The level of reliability for this association,</li> </ul>

The following is sample output from the **show ip flow export template** command:

```
Router# show ip flow export template
  Template Options Flag = 1
  Total number of Templates added = 4
  Total active Templates = 4
  Flow Templates active = 3
  Flow Templates added = 3
  Option Templates active = 1
  Option Templates added = 1
  Template ager polls = 2344
```

```

Option Template ager polls = 34
Main cache version 9 export is enabled
Template export information
  Template timeout = 30
  Template refresh rate = 20
Option export information
  Option timeout = 800
  Option refresh rate = 300
Aggregation cache destination-prefix version 9 export is enabled
Template export information
  Template timeout = 30
  Template refresh rate = 20
Option export information
  Option timeout = 30
  Option refresh rate = 20

```

The table below describes the significant fields shown in the display of the **show ip flow export template** command.

**Table 22: show ip flow export template Field Descriptions**

Field	Description
Template Options Flag	<p>Identifies which options are enabled.</p> <p>The values are:</p> <ul style="list-style-type: none"> <li>• 0--No option template configured.</li> <li>• 1--Version 9 option export statistics configured.</li> <li>• 2--Random sampler option template configured.</li> <li>• 4--Version 9 option export statistics for IPv6 configured.</li> </ul>
Total number of Templates added	<p>Indicates the number of Flow Templates and Option Templates that have been added since Version 9 export was first configured.</p> <p>The value in this field is the sum of the “Flow Templates added” and the “Option Templates added” fields.</p> <p>The value is incremented when a new template is created, because each template requires a unique ID.</p>
Total active Templates	<p>Sum of the values in the “Flow Templates active” and “Option Templates” active fields.</p> <p>The value in this field is incremented when a new data template or option template is created.</p>

Field	Description
Flow Templates active	<p>Indicates the number of (data) templates in use for Version 9 data export.</p> <p>When a new data template is created, this count, the “Total active Templates,” the “Flow Templates added,” and the “Total number of Templates added” counts are all incremented.</p> <p><b>Note</b> When a data template is removed, only the “Flow Templates active” count and the “Total active Templates” count are decremented.</p>
Flow Templates added	<p>Indicates the number of Flow Templates and Option Templates that have been added since Version 9 export was first configured.</p> <p>The value is incremented when a new flow template is created, because each template requires a unique ID.</p>
Option Templates active	<p>Indicates the number of option templates which are currently in use for Version 9 options export.</p> <p>Configuring a new option increments this count and also the “Total active Templates,” the “Option Templates added,” and the “Total number of Templates added” counts.</p> <p>Removing (unconfiguring) an option decrements only the “Option Templates active” count and the “Total active Templates” count.</p>
Option Templates added	<p>Indicates the number of Option Templates that have been added since Version 9 export was first configured.</p> <p>The count is incremented when a new option template is created, because each template requires a unique ID.</p>
Template ager polls	<p>The number of times, since Version 9 export was configured, that the (data) template ager has run.</p> <p>The template ager checks up to 20 templates per invocation, resending any that need refreshed.</p>
Option Template ager polls	<p>The number of times, since Version 9 export was configured, that the option template ager has run.</p> <p>The template ager checks up to 20 templates per invocation, resending any that need refreshed.</p>
Main cache version 9 export is enabled	<p>NetFlow export Version 9 is enabled for the main NetFlow cache.</p>

Field	Description
Template export information	<p>Template timeout--The interval (in minutes) that the router waits after sending the templates (flow and options) before they are sent again. You can specify from 1 to 3600 minutes. The default is 30 minutes.</p> <ul style="list-style-type: none"> <li>• Template refresh rate--The number of export packets that are sent before the options and flow templates are sent again. You can specify from 1 to 600 packets. The default is 20 packets.</li> </ul>
Option export information	<ul style="list-style-type: none"> <li>• Option timeout--The interval (in minutes) that the router will wait after sending the options records before they are sent again. You can specify from 1 to 3600 minutes. The default is 30 minutes.</li> <li>• Option refresh rate--The number of packets that are sent before the configured options records are sent again. You can specify from 1 to 600 packets. The default is 20 packets.</li> </ul>
Aggregation cache destination-prefix version 9 export is enabled	NetFlow export Version 9 is enabled for the NetFlow destination-prefix aggregation cache.

The following example displays the additional line in the **show ip flow export** command output when the **verbose** keyword is specified and MPLS PAL records are being exported to a NetFlow collector:

```
Router# show ip flow export verbose
Flow export v9 is enabled for main cache
  Exporting flows to 10.23.0.5 (4200)
  Exporting using source IP address 10.2.72.35
  Version 9 flow records, origin-as bgp-nexthop
  Cache for destination-prefix aggregation:
    Exporting flows to 10.2.0.1 (4200)
    Exporting using source IP address 10.2.72.35
    182128 MPLS PAL records exported
    189305 flows exported in 6823 udp datagrams
    0 flows failed due to lack of export packet
    0 export packets were sent up to process level
    0 export packets were dropped due to no fib
    0 export packets were dropped due to adjacency issues
    0 export packets were dropped due to fragmentation failures
    0 export packets were dropped due to encapsulation fixup failures swat72f3#
```

The line of output added for the MPLS PAL records precedes the “x flows exported in y UDP datagrams” line. In this example, the additional line of output precedes “189305 flows exported in 6823 UDP datagrams.”

The following example shows the sample output of the **show ip flow export nbar** command:

```
Router# show ip flow export nbar
Nbar netflow is enabled
10 nbar flows exported
0 nbar flows failed to export due to lack of internal buffers
```

**Related Commands**

Command	Description
<b>ip flow-export</b>	Enables export of NetFlow accounting information in NetFlow cache entries.
<b>show ip cache flow</b>	Displays a summary of the NetFlow accounting statistics.
<b>show ip cache verbose flow</b>	Displays a detailed summary of the NetFlow accounting statistics.
<b>show ip flow interface</b>	Displays the NetFlow accounting configuration on interfaces.
<b>show mpls flow mappings</b>	Displays the full MPLS PAL table.



## show ip flow top

The documentation for the **show ip flow top** command was merged with the **show ip flow top-talkers** command in Cisco IOS Release 12.4(9)T.

# show ip flow top-talkers

To display the statistics for the NetFlow aggregated top talkers or unaggregated top flows, use the **show ip flow top-talkers** command in user EXEC or privileged EXEC mode.

## Cisco IOS Releases 12.4(9)T and Newer

```
{show ip flow top-talkers [verbose]} [number [from-cache main] aggregate aggregate-field [sorted-by
{aggregate| bytes| flows| packets} [ascending| descending]] [match match-field match-value]]}
```

## Cisco IOS Releases 12.4(4)T and 12.4(6)

```
show ip flow top number [from-cache main] aggregate aggregate-field [sorted-by {aggregate| bytes|
flows| packets} [ascending| descending]] [match match-field match-value]
```

```
show ip flow top-talkers [verbose]
```

## Cisco IOS Releases Prior to 12.4(4)T

```
show ip flow top-talkers [verbose]
```

### Syntax Description

<b>verbose</b>	(Optional) Displays additional details for the unaggregated top flows.
<i>number</i>	(Optional) Specifies the number of top talkers to show in the display. The range is 1 to 100.
<b>from-cache</b>	(Optional) Specifies the cache that the display output is generated from.
<b>main</b>	Display output is generated from the main cache.
<b>aggregate</b> <i>aggregate-field</i>	(Optional) The combination of the <b>aggregate</b> and the <i>aggregate-field</i> keywords and arguments specifies which field to aggregate for the display output. See the table below.

<b>sorted-by</b>	(Optional) Specifies which field to sort by. If this keyword is specified, you must select one of the following keywords: <ul style="list-style-type: none"> <li>• <b>aggregate</b> --Sort by the aggregated field in the display data.</li> <li>• <b>bytes</b> --Sort by the number of bytes in the display data.</li> <li>• <b>flows</b> --Sort by the number of flows in the display data.</li> <li>• <b>packets</b> --Sort by number of packets in the display data.</li> </ul>
<b>ascending</b>	(Optional) Arranges the display output in ascending order.
<b>descending</b>	(Optional) Arranges the display output in descending order.
<b>match</b> <i>match-field match-value</i>	(Optional) The combination of the <b>match</b> , <i>match-field</i> , and <i>match-value</i> keywords and arguments specifies the field from the flows - and the value in the field - to match. See the table below.

**Command Default**

The **show ip flow top-talkers** *number* command string displays output in descending order based on the value in the **sorted-by** field.

The **show ip flow top-talkers** *number* command string displays data from the main NetFlow cache.

**Command Modes**

User EXEC Privileged EXEC

**Command History**

<b>Release</b>	<b>Modification</b>
Original version of the show ip flow top-talkers command (unaggregated top flows)	
12.2(25)S	This command was introduced.
12.3(11)T	This feature was integrated into Cisco IOS Release 12.3(11)T.
12.2(27)SBC	This feature was integrated into Cisco IOS Release 12.2(27)SBC.

Release	Modification
12.2(33)SRA	This feature was integrated into Cisco IOS Release 12.2(33)SRA.
12.2(31)SB2	This command was integrated into Cisco IOS Release 12.2(31)SB2.
Original version of the show ip flow top command (aggregated top talkers)	
12.4(4)T	This command was introduced.
Merged show ip flow top-talkers and show ip flow top commands	
12.4(9)T	The <b>show ip flow top</b> command was merged into the <b>show ip flow top-talkers</b> command.
12.2SX	This command is supported in the Cisco IOS Release 12.2SX train. Support in a specific 12.2SX release of this train depends on your feature set, platform, and platform hardware.

### Usage Guidelines

You must have NetFlow configured before you can use the **show ip flow top-talkers** command.

The **show ip flow top-talkers** command can be used to display statistics for unaggregated top flows or aggregated top talkers. Prior to Cisco IOS release 12.4(9)T the **show ip flow top-talkers** command could only be used to display statistics for unaggregated top flows. In Cisco IOS release 12.4(9)T and newer releases, the **show ip flow top-talkers** command can be used to display statistics for both unaggregated top flows and aggregated top talkers.

Refer to the following sections for more information on using either of these methods:

#### Unaggregated Top Flows--All Cisco IOS Releases Prior to 12.4(9)T

When you use the **show ip flow top-talkers** command in releases prior to Cisco IOS release 12.4(9)T, the display output shows only separate (unaggregated) statistics for the number of top flows that you specified with the **top** command.



#### Note

The **sort-by** and **top** commands must be configured before you enter the **show ip flow top-talkers [verbose]** command. Optionally, the **match** command can be configured to specify additional matching criteria. Refer to the configuration documentation for the “ NetFlow MIB and Top Talkers ” feature for more information on using the **top**, **sort-by**, and **match** commands.

This method of viewing flow statistics is useful for identifying the unique flows that are responsible for the highest traffic utilization in your network. For example, if you have a centralized WEB server farm and you want to see statistics for the top 50 flows between your servers and your users regardless of the network protocol or application in use, you can configure **top 50** and use the **show ip flow top-talkers verbose** command to view the statistics from the 50 top flows.

**Tip**

If you want to limit the flows that are displayed to specific protocols or IP addresses, you can configure match criteria with the **match** command.

Displaying information on individual top flows will not provide you with a true map of your network utilization when the highest volume application or protocol traffic on your network is being generated by a large number of users who are sending small amounts of traffic. For example, if you configure **top 10** and there are ten or more users generating more FTP traffic than any other type of traffic in your network, you will see the FTP traffic as the top flows even though there might be 10,000 users using HTTP to access web sites at much lower individual levels of network utilization that account for a much larger aggregated traffic volume. In this situation you need to aggregate the traffic patterns across flows using the **show ip flow top-talkers [number]** command string.

The timeout period as specified by the **cache-timeout** command does not start until the **show ip flow top-talkers** command is entered. From that time, the same top talkers are displayed until the timeout period expires. To recalculate a new list of top talkers before the timeout period expires, you can change the parameters of the **cache-timeout**, **top**, or **sort-by** command prior to entering the **show ip flow top-talkers** command.

A long timeout period for the **cache-timeout** command limits the system resources that are used by the NetFlow MIB and Top Talkers feature. However, the list of top talkers is calculated only once during the timeout period. If a request to display the top talkers is made more than once during the timeout period, the same results are displayed for each request, and the list of top talkers is not recalculated until the timeout period expires.

A short timeout period ensures that the latest list of top talkers is retrieved; however too short a period can have undesired effects:

- The list of top talkers is lost when the timeout period expires. You should configure a timeout period for at least as long as it takes the network management system (NMS) to retrieve all the required NetFlow top talkers.
- The list of top talkers is updated every time the top talkers information is requested, possibly causing unnecessary usage of system resources.

A good method to ensure that the latest information is displayed, while also conserving system resources, is to configure a large value for the timeout period, but cause the list of top talkers to be recalculated by changing the parameters of the **cache-timeout**, **top**, or **sort-by** command prior to entering the **show ip flow top-talkers** command to display the top talkers. Changing the parameters of the **cache-timeout**, **top**, or **sort-by** command causes the list of top talkers to be recalculated upon receipt of the next command line interface (CLI) or MIB request.

### Aggregated Top Talkers--Cisco IOS Releases 12.4(9)T and Newer

The **show ip flow top** command was merged with the **show ip flow top-talkers** command in Cisco IOS release 12.4(9)T. The two commands were merged to make it easier for you to display cache information on either unaggregated top flows, or aggregated top talkers, using the same root command.

The CLI help for the **show ip flow top-talkers** command was modified to help you differentiate between the two command formats.

```
Router# show ip flow top-talkers ?
Display aggregated top talkers:
<1-100> Number of aggregated top talkers to show
Display unaggregated top flows:
  verbose Display extra information about unaggregated top flows
  |         Output modifiers
```

```
<cr>
Router#
```

When you use the **show ip flow top-talkers** *[number]* command the display output will consist of aggregated statistics from the flows (aggregated top talkers) for the number of top talkers that you specified with the *number* argument.

Unlike the **show ip flow top-talkers** *[verbose]* command, the **show ip flow top-talkers** *[number]* command string does not require:

- Any pre-configuration of the router for the **show ip flow top-talkers** *[number]* command string itself. You can use the **show ip flow top-talkers** *[number]* command string immediately after enabling NetFlow on at least one interface in the router.
- Manipulating a cache timeout parameter to force a recalculation of the aggregated top talkers. The information in the display output of the **show ip flow top-talkers** *[number]* command string always contains the latest, most up-to-date information because it is not cached.

The arguments that are available with the **show ip flow top-talkers** *[number]* command enable you to quickly modify the criteria to be used for generating the display output. Refer to the configuration documentation for the “NetFlow Dynamic Top Talkers CLI” feature which is included in the Cisco IOS Release 12.4(4)T module “Detecting and Analyzing Network Threats With NetFlow”, for additional information using the **show ip flow top-talkers** *[number]* command string.

For additional usage guidelines on displaying statistics for aggregated top talkers using the **show ip flow top-talkers** *[number]* command string, see the following sections:

#### Top Traffic Flows

Using the **show ip flow top-talkers** command to display the aggregated statistics from the flows on a router for the highest volume applications and protocols in your network helps you identify, and classify, security problems such as a denial of service (DoS) attacks because DoS attack traffic almost always show up as one of the highest volume protocols in your network when a DoS attack is in progress. Displaying the aggregated statistics from the flows on a router is also useful for traffic engineering, diagnostics and troubleshooting.

#### Data Displayed by the show ip flow top command

The data in the display output from the **show ip flow top-talkers** command is not flow centric. You cannot identify individual flows with the **show ip flow top-talkers** command.

For example, when you use the **show ip flow top-talkers 5 aggregate destination-address** command:

- If you do not specify any match criteria, the aggregated statistics for the top five destination IP addresses from the flows on a router are displayed.
- If you specify match criteria, the aggregated statistics for the top five destination IP addresses that meet the match criteria that you specified is displayed.

#### Top Talkers Display Output With Aggregation Only

If you do not use any of the optional parameters the **show ip flow top-talkers** command displays the aggregated statistics from the flows on the router for the aggregation field that you enter. For example, to aggregate the flows based on the destination IP addresses, and display the top five destination IP addresses, you use the **show ip flow top-talkers 5 aggregate destination-address** command.

#### Top Talkers Display Output With Aggregation and Match Criteria

You can limit the display output by adding an optional match criterion. For example, to aggregate the statistics from the flows based on the destination IP addresses, and display the top five destination IP addresses that

contain TCP traffic, you use the **show ip flow top-talkers 5 aggregate destination-address match protocol tcp** command.

### Top Talkers Display Output in Ascending Order With Aggregation and Match Criteria

You can change the default sort order of the display output by using the **sorted-by** keyword. For example, to aggregate the statistics from the flows based on the destination IP addresses, and display the top five destination IP addresses that contain TCP traffic sorted on the aggregated field in ascending order, you use the **show ip flow top-talkers 5 aggregate destination-address sorted-by aggregate ascending match protocol tcp** command.



#### Tip

This usage of the **show ip flow top-talkers 5 aggregate destination-address sorted-by aggregate ascending match protocol tcp** command string is useful for capacity planning because it shows the smallest flows first. The smallest flows indicate the minimum amount of capacity that you need to provide.

### Aggregate-field and Match-field Match-value Keywords, Arguments, and Descriptions

The table below shows the keywords and descriptions for the *aggregate-field* argument of the **show ip flow top-talkers number aggregate aggregate-field** command. You must enter one of the keywords from this table.

**Table 23: Keywords and Descriptions for aggregate-field Argument**

Keyword	Description
<b>bgp-nexthop</b>	Flows that have the same value in the bgp-nexthop field are aggregated.
<b>bytes</b>	Flows that have the same number of bytes are aggregated.
<b>destination-address</b>	Flows that have the same value in the destination-address field are aggregated.
<b>destination-as</b>	Flows that have the same value in the destination-as field are aggregated.
<b>destination-interface</b>	Flows that have the same value in the destination-interface field are aggregated.
<b>destination-port</b>	Flows that have the same value in the destination-port field are aggregated.
<b>destination-vlan</b>	Flows that have the same value in the destination-vlan field are aggregated.
<b>dscp</b>	Flows that have the same value in the dscp field are aggregated.
<b>fragment-offset</b>	Flows that have the same value in the fragment-offset field are aggregated.

<b>Keyword</b>	<b>Description</b>
<b>icmp</b>	Flows that have the same value in the icmp-type and icmp code fields are aggregated.
<b>icmp-code</b>	Flows that have the same value in the icmp-code field are aggregated.
<b>icmp-type</b>	Flows that have the same value in the icmp-type field are aggregated.
<b>incoming-mac</b>	Flows that have the same value in the incoming-mac address field are aggregated.
<b>ip-id</b>	Flows that have the same value in the ip-id field are aggregated.
<b>ip-nexthop-address</b>	Flows that have the same value in the ip-nexthop-address field are aggregated.
<b>max-packet-length</b>	Flows that have the same value in the max-packet-length field are aggregated.
<b>max-ttl</b>	Flows that have the same value in the max-ttl field are aggregated.
<b>min-packet-length</b>	Flows that have the same value in the min-packet-length field are aggregated.
<b>min-ttl</b>	Flows that have the same value in the min-ttl field are aggregated.
<b>outgoing-mac</b>	Flows that have the same value in the outgoing-mac address field are aggregated.
<b>packets</b>	Flows that have the same number of packets are aggregated.
<b>precedence</b>	Flows that have the same value in the precedence field are aggregated.
<b>protocol</b>	Flows that have the same value in the protocol field are aggregated.
<b>source-address</b>	Flows that have the same value in the source-address field are aggregated.
<b>source-as</b>	Flows that have the same value in the source-as field are aggregated.



Keyword	Description
<b>source-interface</b>	Flows that have the same value in the source-interface field are aggregated.
<b>source-port</b>	Flows that have the same value in the source-port field are aggregated.
<b>source-vlan</b>	Flows that have the same value in the source-vlan field are aggregated.
<b>tcp-flags</b>	Flows that have the same value in the tcp-flags field are aggregated.
<b>tos</b>	Flows that have the same value in the tos field are aggregated.

The table below shows the keywords, arguments, and descriptions for the *match-field match-value* arguments for the **show ip flow top-talkers number aggregate aggregate-field match match-field match-value** command. These keywords are all optional.

**Note**

In the table below, the match criteria that you select must be available in the cache. For example, if you use the **show ip flow top 20 aggregate destination-address match destination-vlan 1** command, and you have not configured the **ip flow-capture vlan-id** command, the “% VLAN id is not available for this cache” error message is displayed.

**Note**

In the table below, the *match-field* is the keyword in the keyword column and the *match-value* is the argument(s) for the keyword. For example, for the keyword **bgp-nexthop**, **bgp-nexthop** is the *match-field* and [*ip-address | hostname*] is the *match-value*.

Many of the values shown in the display output of the **show ip cache verbose flow** command are in hexadecimal. If you want to match these values using the **show ip flow top-talkers** command with the **match** keyword, you must enter the field value that you want to match in hexadecimal. For example, to match on the destination port of 0x00DC in the following excerpt from the **show ip cache verbose flow** command, you would use the **match destination-port 0x00DC** keywords and argument for the **show ip flow top-talkers** command.

```
R3# show ip cache verbose flow
.
.
.
SrcIf          SrcIPAddress  DstIf
              DstIPAddress  Pr TOS Flgs  Pkts
Port Msk AS
Msk AS      NextHop          B/Pk Active
Et0/0.1     10.10.11.4          Et1/0.1    172.16.10.8    06 00 00    209
0023
/0 0
/0 0      0.0.0.0          40 281.4
.
```

Table 24: Keywords, Arguments, and Descriptions for match-field match-value

Keyword	Description
<b>bgp-nexthop</b> { <i>ip-address</i>   <i>hostname</i> }	IP address or hostname of the BGP nexthop router to match in the flows.
<b>bytes</b> {[ <i>bytes</i> ]   [ <b>minbytes</b> ] [ <b>maxbytes</b> ] }	<p>Range of bytes to match in the flows.</p> <ul style="list-style-type: none"> <li>• <b>min</b> --Minimum number of bytes to match.</li> <li>• <b>max</b> --Maximum number of bytes to match.</li> <li>• Range: 0 to 4294967295</li> </ul> <p><b>Note</b> If you want to use <b>min bytes</b> you must enter it before <b>max bytes</b>.</p>
<b>destination-as</b> <i>as-number</i>	Destination Autonomous System number to match in the flows. The range is 0 to 65535.
<b>destination-interface</b> <i>interface-type</i> <i>interface-number</i>	Destination interface to match in the flows.
<b>destination-port</b> {[ <i>port</i> ]   [ <b>minport</b> ] [ <b>maxport</b> ] }	<p>The range of destination ports to match in the flows.</p> <ul style="list-style-type: none"> <li>• <b>min</b> --Minimum port number to match.</li> <li>• <b>max</b> --Maximum port number to match.</li> <li>• Range: 0 to 65535</li> </ul> <p><b>Note</b> If you want to use <b>min port</b> you must enter it before <b>max port</b>.</p>
<b>destination-prefix</b> <i>prefix /mask</i>	<p>Destination IP address prefix and mask to match in the flows.</p> <p><b>Note</b> Enter the prefix-mask by using the CIDR method of /number-of-bits. For example, 192.0.0.0/8.</p>
<b>destination-vlan</b> <i>vlan-id</i>	<p>Destination VLAN ID to match in the flows.</p> <ul style="list-style-type: none"> <li>• Range: 0 to 4095</li> </ul>
<b>dscp</b> <i>dscp</i>	<p>Value in the DSCP field to match in the flows.</p> <ul style="list-style-type: none"> <li>• Range: 0x0 to 0x3F</li> </ul>

Keyword	Description
<b>flows</b> {[ <i>flows</i> ]   [ <b>min</b> <i>flows</i> ] [ <b>max</b> <i>flows</i> ]}	<p>The range of flows in the aggregated data to match in the flows.</p> <ul style="list-style-type: none"> <li>• <b>min</b> --Minimum number of flows to match.</li> <li>• <b>max</b> --Maximum number of flows to match.</li> <li>• Range: 0 to 4294967295</li> </ul> <p><b>Note</b> If you want to use <b>min</b> <i>flows</i> you must enter it before <b>max</b> <i>flows</i>.</p>
<b>fragment-offset</b> <i>fragment-offset</i>	<p>Value in the fragment offset field to match in the flows.</p> <ul style="list-style-type: none"> <li>• Range: 0 to 8191</li> </ul>
<b>icmp type</b> <i>type</i> <b>code</b> <i>code</i>	<p>ICMP type and code values to match in the flows.</p> <ul style="list-style-type: none"> <li>• Range for <i>type</i> and <i>code</i>: 0 to 255.</li> </ul>
<b>icmp-code</b> <i>code</i>	<p>ICMP code value to match in the flows.</p> <ul style="list-style-type: none"> <li>• Range: 0 to 255</li> </ul>
<b>icmp-type</b> <i>type</i>	<p>ICMP type value to match in the flows.</p> <ul style="list-style-type: none"> <li>• Range: 0 to 255</li> </ul>
<b>incoming-mac</b> <i>mac-address</i>	<p>Incoming MAC address to match in the flows.</p>
<b>ip-id</b> <i>ip-id</i>	<p>IP ID value to match in the flows.</p> <ul style="list-style-type: none"> <li>• Range: 0 to 65535</li> </ul>
<b>ip-nexthop-prefix</b> <i>prefix/mask</i>	<p>IP nexthop address prefix and mask to match in the flows.</p> <p><b>Note</b> Enter the prefix-mask by using the CIDR method of /number-of-bits. For example, 192.0.0.0/8.</p>

Keyword	Description
<b>max-packet-length</b> {[ <i>max-packet-length</i> ]   [ <b>min</b> <i>max-packet-length</i> ] [ <b>max</b> <i>max-packet-length</i> ]}	<p>The range of maximum packet length values to match in the flows.</p> <ul style="list-style-type: none"> <li>• <b>min</b> --Minimum value in the maximum packet length field to match.</li> <li>• <b>max</b> --Maximum value in the maximum packet length field to match.</li> <li>• Range: 0 to 65535</li> </ul> <p><b>Note</b> If you want to use <b>min</b> <i>max-packet-length</i> you must enter it before <b>max</b> <i>max-packet-length</i>.</p>
<b>max-ttl</b> {[ <i>max-ttl</i> ]   [ <b>min</b> <i>max-ttl</i> ] [ <b>max</b> <i>max-ttl</i> ]}	<p>The range of maximum TTL values to match in the flows.</p> <ul style="list-style-type: none"> <li>• <b>min</b> --Minimum value in the maximum TTL field to match.</li> <li>• <b>max</b> --Maximum value in the maximum TTL field to match.</li> <li>• Range: 0 to 255</li> </ul> <p><b>Note</b> If you want to use <b>min</b> <i>max-ttl</i> you must enter it before <b>max</b> <i>max-ttl</i>.</p>
<b>min-packet-length</b> {[ <i>min-packet-length</i> ]   [ <b>min</b> <i>min-packet-length</i> ] [ <b>max</b> <i>min-packet-length</i> ]}	<p>The range of minimum packet length values to match in the flows.</p> <ul style="list-style-type: none"> <li>• <b>min</b> --Minimum value in the minimum packet length field to match.</li> <li>• <b>max</b> --Maximum value in the minimum packet length field to match.</li> <li>• Range: 0 to 65535</li> </ul> <p><b>Note</b> If you want to use <b>min</b> <i>min-packet-length</i> you must enter it before <b>max</b> <i>min-packet-length</i>.</p>

Keyword	Description
<b>min-ttl</b> {[ <i>min-ttl</i> ]   [ <b>min</b> <i>min-ttl</i> ] [ <b>max</b> <i>min-ttl</i> ]}	<p>The range of minimum TTL values to match in the flows.</p> <ul style="list-style-type: none"> <li>• <b>min</b> --Minimum value in the minimum TTL field to match.</li> <li>• <b>max</b> --Maximum value in the minimum TTL field to match.</li> <li>• Range: 0 to 255</li> </ul> <p><b>Note</b> If you want to use <b>min</b> <i>min-ttl</i> you must enter it before <b>max</b> <i>min-ttl</i>.</p>
<b>outgoing-mac</b> <i>mac-address</i>	Outgoing MAC address to match in the flows.
<b>packets</b> {[ <i>packet-size</i> ]   [ <b>min</b> <i>packet-size</i> ] [ <b>max</b> <i>packet-size</i> ]}	<p>The range of packet sizes to match in the flows.</p> <ul style="list-style-type: none"> <li>• <b>min</b> --Minimum size of packets to match.</li> <li>• <b>max</b> --Maximum size of packets to match.</li> <li>• Range: 0 to 4294967295</li> </ul> <p><b>Note</b> If you want to use <b>min</b> <i>packet-size</i> you must enter it before <b>max</b> <i>packet-size</i>.</p>
<b>precedence</b> <i>precedence</i>	<p>Precedence value to match in the flows.</p> <ul style="list-style-type: none"> <li>• Range: 0 to 7</li> </ul>
<b>protocol</b> {[ <i>protocol-number</i> ]   [ <b>tcp</b>   <b>udp</b>   <b>icmp</b>   <b>igmp</b>   <b>ip-in-ip</b>   <b>gre</b>   <b>ipv6-in-ipv6</b> ]}	<p>Protocol value to match in the flows.</p> <ul style="list-style-type: none"> <li>• Range: 0 to 255</li> </ul> <p><b>Note</b> TCP, UDP, ICMP, IGMP, IP-in-IP, GRE, and IPv6-in-IPv6 are the protocols that NetFlow tracks for the protocols summary in the display output of the <b>show ip cache verbose flow</b> command. Other protocols can be matched by specifying their numeric values.</p>
<b>source-as</b> <i>source-as</i>	<p>Source autonomous system value to match in the flows.</p> <ul style="list-style-type: none"> <li>• Range: 0 to 65535</li> </ul>
<b>source-interface</b> <i>interface-type</i> <i>interface-number</i>	Source interface to match in the flows.

Keyword	Description
<b>source-port</b> {[ <i>port</i> ]   [[ <b>min port</b> ] [ <b>max port</b> ]]}	The range of source port values to match in the flows. <ul style="list-style-type: none"> <li>• <b>min</b> --Source port value to match.</li> <li>• <b>max</b> --Source port value to match.</li> <li>• Range: 0 to 65535</li> </ul> <p><b>Note</b> If you want to use <b>min port</b> you must enter it before <b>max port</b>.</p>
<b>source-prefix</b> <i>prefix/mask</i>	Source address prefix and mask to match in the flows. <p><b>Note</b> Enter the prefix-mask by using the CIDR method of /number-of-bits. For example, 192.0.0.0/8.</p>
<b>source-vlan</b> <i>vlan-id</i>	Source VLAN ID to match in the flows. <ul style="list-style-type: none"> <li>• Range: 0 to 4095</li> </ul>
<b>tcp-flags</b> <i>flag</i>	Value in the TCP flag field to match in the flows. <ul style="list-style-type: none"> <li>• Range: 0x0 to 0xFF</li> </ul>
<b>tos</b> <i>tos</i>	Value in the TOS flag field to match in the flows. <ul style="list-style-type: none"> <li>• Range: 0x0 to 0xFF</li> </ul>

### The Order That Aggregation Occurs in

With the exception of the **flows** keyword in the table above, all matches made with the *match-fieldmatch-value* arguments are performed prior to aggregation, and only matching flows are aggregated. For example, the **show ip flow top-talkers 5 aggregate destination-address match destination-prefix 172.16.0.0/16** command analyzes all of the available flows looking for any flows that have destination addresses that match the **destination-prefix** value of *172.16.0.0/16*. If it finds any matches it aggregates them, and then displays the number of aggregated **destination-address** flows that is equal to the number of top talkers that were requested in the command-in this case five.

The **flows** keyword matches the number of aggregated flows post-aggregation. For example, the **show ip flow top 2 aggregate destination-address match flows 6** command aggregates all of the flows on the values in their destination IP address field, and then displays the top talkers that have 6 aggregated flows.

### Number of Flows Matched

If you do not specify match criteria and there are flows in the cache that include the field that you used to aggregate the flows on, all of the flows will match. For example, if your router has 20 flows with IP traffic and you enter the **show ip flow top-talkers 10 aggregate destination-address** command the display will indicate that 20 of 20 flows matched, and the 10 top talkers will be displayed.

If you use the match keyword to limit the flows that are aggregated to the flows with a destination prefix of 224.0.0.0/3, and only one flow matches this criterion the output will indicate that one out of 20 flows matched. For example, if your router has 20 flows with IP traffic, but only one of them has a destination prefix of

224.0.0.0/3, and you enter the **show ip flow top-talkers 10 aggregate destination-address match destination-prefix 224.0.0.0/3** command, the display will indicate that 1 of 20 flows matched.

If the total number of top talkers is less than the number of top talkers that were requested in the command, the available number of top talkers is displayed. For example, if you enter a value of five for the number of top talkers to display and there are only three top talkers that match the criteria that you used, the display will only include three top talkers.

When a match criterion is included with the **show ip flow top-talkers** command, the display output will indicate “N of M flows matched” where N is the number of matched flows, M is the total number of flows seen, and N is less than or equal to M. The numbers of flows seen could potentially be more than the total number of flows in the cache if some of the analyzed flows were expired from the cache and new flows were created, as the top talkers feature scans through the cache. Therefore, M is NOT the total number of flows in the cache, but rather, the number of flows observed in the cache by the top talkers feature.

If you attempt to display the top talkers by aggregating them on a field that is not in the cache you will see the “% aggregation-field is not available for this cache” message. For example, if you use the **show ip flow top5 aggregate source-vlan** command, and you have not enabled the capture of VLAN IDs from the flows, you will see the “% VLAN id is not available for this cache” message.

### TCP-Flags

If you want to use the **tcp-flags flag** match criteria you must enter the hexadecimal values for the type of TCP flag that you want to match.

The TCP flags as used in the **tcp-flags flag** match criteria are provided in the table below.

**Table 25: Values for the tcp-flags flag match criteria**

Hexadecimal Value	Field Name
0x01	FIN-Finish; end of session
0x02	SYN-Synchronize; indicates request to start session
0x04	RST-Reset; drop a connection
0x08	PUSH-Push; packet is sent immediately
0x10	ACK-Acknowledgement
0x20	URG-Urgent
0x40	ECE-Explicit Congestion Notification Echo
0x80	CWR-Congestion Window Reduced

For more information on TCP and TCP flags, refer to RFC 3168 at the following URL: <http://www.ietf.org/rfc/rfc3168.txt>.

### Examples

The **show ip flow top-talkers** command can be used to display information for unaggregated top flows or aggregated top talkers. Refer to the following sections for examples on using either of these methods:

**Examples**

The following example shows the output of the **show ip flow top-talkers** command.

In the example, the NetFlow MIB and Top Talkers feature has been configured to allow a maximum of five top talkers to be viewed. The display output is configured to be sorted by the total number of bytes in each top talker, and the list of top talkers is configured to be retained for 2 seconds (2000 milliseconds).

```
Router(config)# ip flow-top-talkers
Router(config-flow-top-talkers)# top 5
Router(config-flow-top-talkers)# sort-by bytes
Router(config-flow-top-talkers)# cache-timeout 2000
Router# show ip flow top-talkers
SrcIf          SrcIPAddress  DstIf          DstIPAddress  Pr  SrcP  DstP  Bytes
Et0/0.1        10.10.18.1    Et1/0.1        172.16.10.232 11 00A1 00A1 144K
Et0/0.1        10.10.19.1    Et1/0.1        172.16.10.2   11 00A2 00A2 144K
Et0/0.1        172.30.216.196 Et1/0.1        172.16.10.2   06 0077 0077 135K
Et0/0.1        10.162.37.71  Et1/0.1        172.16.10.2   06 0050 0050 125K
Et0/0.1        10.92.231.235 Et1/0.1        172.16.10.2   06 0041 0041 115K
5 of 5 top talkers shown. 11 flows processed
```

The table below describes the significant fields shown in the display.

**Table 26: show ip flow top-talkers Field Descriptions**

Field	Description
SrcIf	Source interface
SrcIPAddress	Source IP address
DstIf	Destination interface
DstIPAddress	Destination IP address
Pr	Protocol number
SrcP	Source port
DstP	Destination port
Bytes	Total number of bytes in each top talker
X of Y top talkers shown	Y-The number of Top Talkers specified by the <b>top</b> command. X-The number of flows displayed. The value for "X" is always <= the value for "Y". For example, if "Y" = 5 and there are 3 Top Talkers, the display will show 3 of 5 top talkers shown.
flows processed	The number of flows observed in the NetFlow cache.

The table below shows messages that could be received in response to the **show ip flow top-talkers** command and their explanations.



**Table 27: show ip flow top-talkers Message Descriptions**

Message	Description
% Top talkers not configured	The NetFlow MIB and Top Talkers feature has not yet been configured.
% Cache is not enabled	The cache is not enabled
% Cache is empty	There are no flows in the cache to be viewed.
% There are no matching flows to show	The match criteria that were specified do not match any flows in the cache.

**Examples**

The following example looks for up to 10 top talkers, aggregates them on the protocol type, sorts them by the number of packets in the flows, and displays the output in descending order:

```
Router# show ip flow top-talkers 10 aggregate protocol sorted-by packets descending
There are 3 top talkers:
IPV4 PROT      bytes          pkts          flows
=====
      1  2009729203    1455464        11
      6   33209300     30690         19
      17         92         1           1
31 of 31 flows matched.
```

Things to note in this display output:

- All 31 flows in the router are aggregated into three top talkers. In this example all of the flow traffic is top talker traffic.
- The majority of the traffic that is aggregated into the first flow is ICMP traffic (IP protocol type 1). This might indicate an ICMP DoS attack is in progress.

The table below describes the significant fields shown in the display.

**Table 28: show ip flow top-talkers 10 aggregate protocol sorted-by packets descending Field Descriptions**

Field	Description
There are top X talkers	The number of top talkers (X) is displayed.
IPV4 PROT <sup>2</sup>	This position in the display output is used to show the field that you selected to aggregate the flows on.  The <b>protocol</b> keyword aggregates IPv4 traffic in the flows based on the IPv4 protocol type. In this example there are three IPv4 protocol types in the flows: <ul style="list-style-type: none"> <li>• 1--ICMP</li> <li>• 6--TCP</li> <li>• 17--UDP</li> </ul>

Field	Description
bytes	Displays the numbers of bytes in the aggregated flows for each top talker.
pkts	Displays the numbers of packets in the aggregated flows for each top talker.
flows	Displays the numbers of aggregated flows for each top talker.
X of Y flows matched.	Y-Number of flows seen in the cache. X-Number of flows in the cache that matched the criteria you specified.

- <sup>2</sup> IPV4 is shown in upper-case (capital) letters because it is the field that the display is aggregated on. In this example this is the keyword protocol in the show ip flow top-talkers 10 aggregate protocol sorted-by packets descending command.

The following example looks for up to five top talkers, aggregates them on the source IP address, sorts them in descending order by the numbers of packets, matches on the ICMP type value of 8, and displays the output in descending order:

```
Router# show ip flow top-talkers 5 aggregate source-address sorted-by packets descending
match icmp-type 8
There are 3 top talkers:
IPV4 SRC-ADDR      bytes      pkts      flows
-----
192.168.87.200    23679120   16501     1
10.234.53.1       18849000   12566     1
172.30.231.193    12094620   8778      1
3 of 29 flows matched.
```

The following example looks for up to five top talkers, aggregates them on the destination IP address, sorts them in descending order by the numbers of packets, matches on the ICMP type value of 8, and displays the output in descending order:

```
Router# show ip flow top-talkers 5 aggregate destination-address sorted-by packets descending
match icmp-type 8
There are 2 top talkers:
IPV4 DST-ADDR      bytes      pkts      flows
-----
172.16.1.2         32104500   21403     2
172.16.10.2        2128620    2134      1
3 of 32 flows matched.
```

The table below describes the significant fields shown in the display.

**Table 29: show ip flow top-talkers 5 aggregate {source-address | destination-address} sorted-by packets descending match icmp-type 8 Field Descriptions**

Field	Description
There are top X talkers	The number of top talkers (X) is displayed.

Field	Description
IPV4 SRC-ADDR <sup>3</sup>	This position in the display output is used to show the field that you selected to aggregate the flows on.  The <b>source-address</b> keyword aggregates IPv4 traffic in the flows based on the source IPv4 IP address. In this example there are 3 IP source addresses in the flows: <ul style="list-style-type: none"> <li>• 192.168.87.200</li> <li>• 10.234.53.1</li> <li>• 172.30.231.193</li> </ul>
IPV4 DST-ADDR <sup>4</sup>	This position in the display output is used to show the field that you selected to aggregate the flows on.  The <b>destination-address</b> keyword aggregates IPv4 traffic in the flows based on the destination IPv4 IP address. In this example there are 2 IP destination addresses in the flows: <ul style="list-style-type: none"> <li>• 172.16.1.2</li> <li>• 172.16.10.2</li> </ul>
bytes	Displays the numbers of bytes in the aggregated flows for each top talker.
pkts	Displays the numbers of packets in the aggregated flows for each top talker.
flows	Displays the numbers of aggregated flows for each top talker.
X of Y flows matched.	Y-Number of flows seen in the cache.  X-Number of flows in the cache that matched the criteria you specified.

<sup>3</sup> IPV4 SRC-ADDR is shown in upper-case (capital) letters because it is the field that the display is aggregated on. In this example this is the keyword source-address in the show ip flow top-talkers 5 aggregate source-address sorted-by packets descending match icmp-type 8 command.

<sup>4</sup> IPV4 DST-ADDR is shown in upper-case (capital) letters because it is the field that the display is aggregated on. In this example this is the keyword destination-address in the show ip flow top-talkers 5 aggregate destination-address sorted-by packets descending match icmp-type 8 command.

The following example looks for up to five top talkers, aggregates them on the source IP address, sorts them in descending order by the number of bytes in the flow, matches on the port range of 20 to 21 (FTP Data and control ports, respectively), and displays the output in descending order:

```
Router# show ip flow top-talkers 5 aggregate source-address sorted-by bytes descending match
destination-port min 20 max 21
There are 5 top talkers:
IPV4 SRC-ADDR      bytes      pkts      flows
```

```

=====
10.231.185.254      920      23      2
10.10.12.1         480      12      2
10.251.138.218    400      10      2
10.132.221.111    400      10      2
10.71.200.138     280      7       1
9 of 34 flows matched.

```

**Tip**

You can enter the port numbers in their decimal values as shown (20 and 21), or in their hexadecimal equivalents of 0x14 and 0x15.

The table below describes the significant fields shown in the display.

**Table 30: show ip flow top-talkers 5 aggregate source-address sorted-by packets descending match icmp-type 8 Field Descriptions**

Field	Description
There are top X talkers	The number of top talkers (X) is displayed.
IPV4 SRC-ADDR	This position in the display output is used to show the field that you selected to aggregate the flows on. The <b>source-address</b> keyword aggregates IPv4 traffic in the flows based on the source IPv4 IP address. In this example there are 5 IP source addresses in the flows: <ul style="list-style-type: none"> <li>• 10.231.185.254</li> <li>• 10.10.12.1</li> <li>• 10.251.138.218</li> <li>• 10.132.221.111</li> <li>• 10.71.200.138</li> </ul>
bytes	Displays the numbers of bytes in the aggregated flows for each top talker.
pkts	Displays the numbers of packets in the aggregated flows for each top talker.
flows	Displays the numbers of aggregated flows for each top talker.
X of Y flows matched.	Y-Number of flows seen in the cache. X-Number of flows in the cache that matched the criteria you specified.

The following example looks for up to five top talkers, aggregates them on the source IP address, sorts them in descending order by the aggregated field (source IP address), and displays the output in descending order:

```
Router# show ip flow top-talkers 5 aggregate source-address sorted-by aggregate descending
```

```
There are 5 top talkers:
IPV4 SRC-ADDR      bytes      pkts      flows
=====
172.16.1.85        97360      2434      2
172.16.1.84        97320      2433      2
10.251.138.218     34048      1216      1
10.231.185.254     34048      1216      1
10.132.221.111     34076      1217      1
7 of 18 flows matched.
```

The table below describes the significant fields shown in the display.

**Table 31: show ip flow top-talkers 5 aggregate source-address sorted-by aggregate descending Field Descriptions**

Field	Description
There are top X talkers	The number of top talkers (X) is displayed.
IPV4 SRC-ADDR	This position in the display output is used to show the field that you selected to aggregate the flows on.  The <b>source-address</b> keyword aggregates IPv4 traffic in the flows based on the source IPv4 IP address. In this example there are 5 IP source addresses in the flows: <ul style="list-style-type: none"> <li>• 172.16.1.85</li> <li>• 172.16.1.84</li> <li>• 10.251.138.218</li> <li>• 10.231.185.254</li> <li>• 10.132.221.111</li> </ul>
bytes	Displays the numbers of bytes in the aggregated flows for each top talker.
pkts	Displays the numbers of packets in the aggregated flows for each top talker.
flows	Displays the numbers of aggregated flows for each top talker.
X of Y flows matched.	Y-Number of flows seen in the cache.  X-Number of flows in the cache that matched the criteria you specified.

**Related Commands**

<b>Command</b>	<b>Description</b>
<b>cache-timeout</b>	Specifies the length of time for which the list of top talkers (heaviest traffic patterns and most-used applications in the network) for the NetFlow MIB and Top Talkers feature is retained.
<b>ip flow-top-talkers</b>	Enters the configuration mode for the NetFlow MIB and Top Talkers (heaviest traffic patterns and most-used applications in the network) feature.
<b>match (NetFlow)</b>	Specifies match criteria for the NetFlow MIB and Top Talkers (heaviest traffic patterns and most-used applications in the network) feature.
<b>sort-by</b>	Specifies the sorting criterion for top talkers (heaviest traffic patterns and most-used applications in the network) to be displayed for the NetFlow MIB and Top Talkers feature.
<b>top</b>	Specifies the maximum number of top talkers (heaviest traffic patterns and most-used applications in the network) to be displayed for the NetFlow MIB and Top Talkers feature.
<b>show ip cache flow</b>	Displays a summary of the NetFlow accounting statistics.
<b>show ip cache verbose flow</b>	Displays a detailed summary of the NetFlow accounting statistics.
<b>show ip flow interface</b>	Displays NetFlow accounting configuration for interfaces.

## show mls ip non-static

To display information for the software-installed nonstatic entries, use the **show mls ip non-static** command in user EXEC or privileged in the EXEC mode.

**show mls ip non-static** [**count** [**module number**]] [**detail** [**module number**]] **module number**

### Syntax Description

<b>count</b>	(Optional) Displays the total number of nonstatic entries.
<b>module number</b>	(Optional) Designates the module number.
<b>detail</b>	(Optional) Specifies a detailed per-flow output.

### Command Modes

User EXEC (>) Privileged EXEC (#)

### Command History

Release	Modification
12.2(14)SX	Support for this command was introduced on the Supervisor Engine 720.
12.2(17a)SX	This command is supported on releases prior to Release 12.2(17a)SX only.
12.2(17b)SXA	This command is replaced by the <b>show mls netflow ip</b> command.

### Usage Guidelines

This command is not supported on Cisco 7600 series routers that are configured with a Supervisor Engine 2.

### Examples

This sections contains examples from the **show mls ip non-static** command. The fields shown in the display are self-explanatory.

This example shows how to display the software-installed nonstatic entries:

```
Router> show mls ip non-static
Displaying Netflow entries in Supervisor Earl
DstIP          SrcIP          Prot:SrcPort:DstPort  Src i/f:AdjPtr
-----
Pkts           Bytes         Age   LastSeen  Attributes
-----
Router>
```

This example shows how to display detailed information for the software-installed nonstatic entries:

```
Router> show mls ip non-static detail
Displaying Netflow entries in Supervisor Earl
DstIP          SrcIP          Prot:SrcPort:DstPort  Src i/f:AdjPtr
-----
```

```
Pkts          Bytes          Age    LastSeen  Attributes
-----+-----+-----+-----+-----+-----+-----+-----+
QoS    Police Count Threshold    Leak    Drop Bucket  Use-Tbl Use-Enable
-----+-----+-----+-----+-----+-----+-----+-----+
```

```
Router>
```

This example shows how to display the total number of software-installed nonstatic entries:

```
Router> show mls ip non-static count
Displaying Netflow entries in Supervisor Earl
Number of shortcuts = 0
Router>
```



# show mls ip routes

To display the NetFlow routing entries, use the **show mls ip routes** command in user EXEC or privileged EXEC mode.

**show mls ip routes** [**non-static**|**static**] [**count** [**module number**]] **detail** [**module number**]| **module number**]

## Syntax Description

<b>non-static</b>	(Optional) Displays the software-installed nonstatic entries.
<b>static</b>	(Optional) Displays the software-installed static entries.
<b>count</b>	(Optional) Displays the total number of NetFlow routing entries.
<b>module number</b>	(Optional) Displays the entries that are downloaded on the specified module; see the "Usage Guidelines" section for valid values.
<b>detail</b>	(Optional) Specifies a detailed per-flow output.

## Command Modes

User EXEC (>) Privileged EXEC (#)

## Command History

Release	Modification
12.2(14)SX	Support for this command was introduced on the Supervisor Engine 720.
12.2(17a)SX	This command is supported on releases prior to Release 12.2(17a)SX only.
12.2(17b)SXA	This command is replaced by the <b>show mls netflow ip sw-installed</b> command

## Usage Guidelines

This command is not supported on Cisco 7600 series routers that are configured with a Supervisor Engine 2.

## Examples

This section contains examples of the **show mls ip routes non-static** command. The fields shown in the display are self-explanatory.

This example shows how to display the software-installed nonstatic routing entries:

```
Router> show mls ip routes non-static
```

```

Displaying Netflow entries in Supervisor Earl
DstIP          SrcIP          Prot:SrcPort:DstPort  Src i/f:AdjPtr
-----
Pkts           Bytes           Age    LastSeen  Attributes
-----
Router>

```

This example shows how to display detailed information for the software-installed nonstatic routing entries:

```

Router> show mls ip routes non-static detail
Displaying Netflow entries in Supervisor Earl
DstIP          SrcIP          Prot:SrcPort:DstPort  Src i/f:AdjPtr
-----
Pkts           Bytes           Age    LastSeen  Attributes
-----
      QoS      Police Count Threshold    Leak    Drop Bucket  Use-Tbl Use-Enable
-----+-----+-----+-----+-----+-----+-----+
Router>

```

This example shows how to display the total number of software-installed routing entries:

```

Router> show mls ip routes count
Displaying Netflow entries in Supervisor Earl
Number of shortcuts = 0
Router>

```

#### Related Commands

Command	Description
<b>show mls netflow ip sw-installed</b>	Displays information for the software-installed IP entries.

# show mls ip static

To display the information for the software-installed static IP entries, use the **show mls ip static** command in user EXEC or privileged EXEC mode.

**show mls ip static** [**count** [**module number**]] [**detail** [**module number**]] **module number**

## Syntax Description

<b>count</b>	(Optional) Displays the total number of static entries.
<b>module number</b>	(Optional) Designates the module number.
<b>detail</b>	(Optional) Specifies a detailed per-flow output.

## Command Modes

User EXEC (>) Privileged EXEC (#)

## Command History

Release	Modification
12.2(14)SX	Support for this command was introduced on the Supervisor Engine 720.
12.2(17a)SX	This command is supported on releases prior to Release 12.2(17a)SX only.
12.2(17b)SXA	This command is replaced by the <b>show mls netflow ip sw-installed</b> command.

## Usage Guidelines

This command is not supported on Cisco 7600 series routers that are configured with a Supervisor Engine 2.

## Examples

This section contains examples from the **show mls ip static** command. The fields shown in the display are self-explanatory.

This example shows how to display the software-installed static entries:

```
Router> show mls ip static
Displaying Netflow entries in Supervisor Earl
DstIP          SrcIP          Prot:SrcPort:DstPort  Src i/f:AdjPtr
-----
Pkts           Bytes          Age   LastSeen  Attributes
-----
Router>
```

This example shows how to display detailed information for the software-installed static entries:

```
Router> show mls ip static detail
Displaying Netflow entries in Supervisor Earl
DstIP          SrcIP          Prot:SrcPort:DstPort  Src i/f:AdjPtr
-----
```

```
Pkts      Bytes      Age      LastSeen  Attributes
-----+-----+-----+-----+-----+-----+-----+-----+
      QoS      Police Count Threshold      Leak      Drop Bucket  Use-Tbl Use-Enable
-----+-----+-----+-----+-----+-----+-----+-----+
```

```
Router>
```

This example shows how to display the total number of software-installed static entries:

```
Router> show mls ip static count
Displaying Netflow entries in Supervisor Earl
Number of shortcuts = 0
Router>
```

## show mls nde

To display information about the NetFlow Data Export (NDE) hardware-switched flow, use the **show mls nde** command in user EXEC or privileged EXEC mode.

**show mls nde**

**Syntax Description** This command has no arguments or keywords.

**Command Default** This command has no default settings.

**Command Modes** User EXEC (>) Privileged EXEC (#)

Command History	Release	Modification
	12.2(14)SX	Support for this command was introduced on the Supervisor Engine 720.
	12.2(17d)SXB	Support for this command on the Supervisor Engine 2 was extended to the 12.2 SX release.
	12.2(18)SXD	The output for Cisco 7600 series routers that are configured with a Supervisor Engine 720 was changed to include the current NDE mode.
	12.2(33)SRA	This command was integrated into Cisco IOS Release 12.2(33)SRA.
	12.2(33)SXI	The output was modified to display the data export version and aggregation cache scheme.

**Usage Guidelines** The output for Cisco 7600 series routers that are configured with a Supervisor Engine 720 includes the current NDE mode.

### Examples

**Examples** This example shows the output from Cisco 7600 series routers that are configured with a Supervisor Engine 2.

This example shows how to display information about the NDE status on a Cisco 7600 series router that is configured with a Supervisor Engine 2:

```
Router# show mls nde
  Netflow Data Export is Enabled
Router#
```

**Examples**

This example shows how to display information about the NDE hardware-switched flow on a Cisco 7600 series router that is configured with a Supervisor Engine 720:

```
Router# show mls nde
Netflow Data Export enabled (Interface Mode)
Exporting flows to 172.20.55.71 (9991)
Exporting flows from 10.6.60.120 (59020)
Version: 9
Include Filter not configured
Exclude Filter not configured
Total Netflow Data Export Packets are:
as aggregation v9 0 packets, 0 no packets, 0 records
Router#
```

**Related Commands**

Command	Description
<b>mls nde sender</b>	Enables MLS NDE export.
<b>show ip flow-export</b>	Displays the information about the hardware-switched and software-switched flows for the data export, including the main cache and all other enabled caches.
<b>show mls netflow</b>	Displays configuration information about the NetFlow hardware.

## show mls netflow

To display configuration information about the NetFlow hardware, use the **show mls netflow** command in user EXEC or privileged EXEC mode.

```
show mls netflow {aging| aggregation flowmask| creation| flowmask| {table-contention detailed| summary}}
```

### IPv6, MLPS, and software Configuration

```
show mls netflow [ip| ipv6| mpls] [any| count| destination {hostname| ip-address}| detail| dynamic| flow {tcp| udp}| module number| nowrap| source {hostname| ip-address}| sw-installed [non-static| static]]
```

#### Syntax Description

<b>aging</b>	Displays the NetFlow-aging information.
<b>aggregation flowmask</b>	Displays the flow mask that is set for the current NetFlow aggregations.
<b>creation</b>	Displays the configured protocol-creation filters.
<b>flowmask</b>	Displays the current NetFlow IP and IPX flow mask.
<b>table-contention</b>	Displays the NetFlow table-contention level information.
<b>detailed</b>	Displays detailed NetFlow table-contention level information.
<b>summary</b>	Displays a summary of NetFlow table-contention levels.
<b>ip</b>	(Optional) Displays information about the NetFlow IP table; see the <b>show mls netflow ip</b> command.
<b>ipv6</b>	(Optional) Displays information about the NetFlow IPv6 table; see the <b>show mls netflow ipv6</b> command.
<b>mpls</b>	(Optional) Displays information about the NetFlow Multiprotocol Label Switching(MPLS) table.
<b>any</b>	(Optional) Displays detailed NetFlow table-entry information with no test wrap.
<b>count</b>	(Optional) Displays the total number of MLS NetFlow IP entries.
<b>destination</b> <i>hostname</i>	(Optional) Displays the entries for a specific destination hostname.

<b>destination</b> <i>ip-address</i>	(Optional) Displays the entries for a specific destination IP address.
<b>detail</b>	(Optional) Specifies a detailed output.
<b>dynamic</b>	(Optional) Displays the hardware-created dynamic entries; see the <b>show mls netflow ip dynamic</b> command.
<b>flow tcp</b>	(Optional) Displays information about the TCP flows.
<b>flow udp</b>	(Optional) Displays information about the User Datagram Protocol(UDP) flows.
<b>module</b> <i>number</i>	(Optional) Displays the entries that are downloaded on the specified module; see the "Usage Guidelines" section for valid values.
<b>nowrap</b>	(Optional) Displays information without text wrap.
<b>source</b> <i>hostname</i>	(Optional) Displays the entries for a specific source address.
<b>source</b> <i>ip-address</i>	(Optional) Displays the entries for a specific source IP address.
<b>sw-installed</b>	(Optional) Displays the routing NetFlow entries; see the <b>show mls netflow ip sw-installed</b> command.
<b>non-static</b>	(Optional) Displays information for software-installed non-static IP entries; see the <b>show mls netflow ip sw-installed</b> command.
<b>static</b>	(Optional) Displays information for the software-installed static IP entries; see the <b>show mls netflow ip sw-installed</b> command.

**Command Default**

This command has no default settings.

**Command Modes**

User EXEC Privileged EXEC

**Command History**

Release	Modification
12.2(14)SX	This command was introduced on the Supervisor Engine 720.



Release	Modification
12.2(17a)SX	This command was changed as follows: <ul style="list-style-type: none"> <li>Enhanced the <b>show mls netflow aggregation flowmask</b> command output to include a list of aggregation caches with minimum flow mask and NetFlow-aggregation schemes such as destination-prefix, source-prefix, protocol-port, and prefix.</li> <li>Included support for the <b>ipv6</b> option.</li> </ul>
12.2(17b)SXA	This command was changed to add the following keywords and arguments: <ul style="list-style-type: none"> <li><b>details</b></li> <li><b>nowrap</b></li> <li><b>module</b> <i>num</i></li> <li>Changed the syntax from <b>show mls [ip   ipv6   mpls]</b> to <b>show mls netflow [ip   ipv6   mpls]</b>.</li> </ul>
12.2(17d)SXB	Support for this command on the Supervisor Engine 2 was extended to the 12.2SX train.
12.2(18)SXD	The <b>creation</b> keyword was added.
12.2(33)SRA	This command was integrated into Cisco IOS Release 12.2(33)SRA.

### Usage Guidelines

**Note** The **creation** keyword is not supported in releases prior to Release 12.2(18)SXD.

The **ipv6** and **mpls** keywords are not supported on Cisco 7600 series routers that are configured with a Supervisor Engine 2.

When you view the output, note that a colon (:) is used to separate the fields.

For TCP intercept flows, the packet count is 0 on DFC. TCP intercept will install a zero count entry in each DFC and PFC for each intercepted flow because TCP intercept is a global feature.

### Examples

This example shows how to display the NetFlow-aging configuration:

```
Router#
show mls netflow aging
      enable timeout  packet threshold
      -----
normal aging true      300          N/A
fast aging   true       32           100
long aging   true       900          N/A
Router#
```

This example shows how to display the configured protocol-creation filters:

```
Router
# show mls netflow creation
Excluded protocols:
port protocol
-----+-----
10      tcp
8       udp/tcp
Router#
```

## Examples

These examples show the output from Cisco 7600 series routers that are configured with a Supervisor Engine 720.

This example shows how to display the flow mask that is set for the current NetFlow aggregation:

```
Router#
show mls netflow aggregation flowmask

Current flowmask set for netflow aggregation : Dest only
Minimum flowmask required for netflow aggregation schemes
-----+-----
Aggregation Scheme Min. Flowmask Status
-----+-----
as Intf Src Dest disabled
protocol-port Full Flow disabled
source-prefix Intf Src Dest disabled
destination-prefix Dest only enabled
prefix Intf Src Dest disabled
Router#
```

This example shows how to display detailed information about the NetFlow table-contention level:

```
Router# show mls netflow table-contention detailed
Earl in Module 2
Detailed Netflow CAM (TCAM and ICAM) Utilization
=====
TCAM Utilization   :    0%
ICAM Utilization   :    0%
Netflow TCAM count :    0
Netflow ICAM count :    0
Router#
```

This example shows how to display a summary of the NetFlow table-contention level:

```
Router# show mls netflow table-contention summary
Earl in Module 2
Summary of Netflow CAM Utilization (as a percentage)
=====
TCAM Utilization   :    0%
ICAM Utilization   :    0%
Router#
```

## Examples

These examples show the output from Cisco 7600 series routers that are configured with a Supervisor Engine 2.

This example shows how to display the flow mask that is set for the current NetFlow aggregations:

```
Router#
show mls netflow aggregation flowmask

Current flowmask set for netflow aggregation : interface and full flow
Minimum flowmask required for netflow aggregation schemes
-----+-----
Aggregation Scheme Min. Flowmask Status
```

```

-----+-----+-----
as if-dst-src enabled
protocol-port full enabled
source-prefix if-dst-src enabled
destination-prefix dst enabled
prefix if-dst-src enabled
Router#

```

This example shows how to display detailed information about the NetFlow table-contention level:

```

Router# show mls netflow table-contention detailed
Earl in Module 1
Detailed Table Contention Level Information
=====
Layer 3
-----
L3 Contention Level:      0
Page Hits Requiring 1 Lookup   =      0
Page Hits Requiring 2 Lookups  =      0
Page Hits Requiring 3 Lookups  =      0
Page Hits Requiring 4 Lookups  =      0
Page Hits Requiring 5 Lookups  =      0
Page Hits Requiring 6 Lookups  =      0
Page Hits Requiring 7 Lookups  =      0
Page Hits Requiring 8 Lookups  =      0
Page Misses                  =      0
Router#

```

This example shows how to display a summary of the NetFlow table-contention level:

```

Router# show mls netflow table-contention summary
Earl in Module 1
Summary of Table Contention Levels (on a scale of 0 (lowest) to 5 (highest))
=====
L3 Contention Level: 0
Router#

```

## Related Commands

Command	Description
<b>ip flow-aggregation cache</b>	Creates a flow-aggregation cache and enters aggregation cache configuration mode.
<b>mls netflow usage notify</b>	Monitors the NetFlow table usage on the Switch Processor and the DFCs.
<b>show ip cache flow</b>	Displays a summary of the NetFlow cache-flow entries.

## show mls netflow ip

To display information about MLS NetFlow IP traffic, use the **show mls netflow ip** command in user EXEC or privileged EXEC mode.

**show mls netflow ip any**

**show mls netflow ip count** [*module number*]

**show mls netflow ip destination** {*hostname*|*ip-address*} [**slash** *ip-mask*] [**count** [*module number*]] **detail** **dynamic**| **flow** {*icmp*|*tcp*|*udp*}| **module number**| **nowrap**| **qos**| **source** {*hostname*|*ip-address*} [**slash** *ip-mask*]| **sw-installed** [**non-static**|**static**]]

**show mls netflow ip detail** [*module number*] **nowrap** [*module number*]]

**show mls netflow ip dynamic** [**count** [*module number*]] [**detail**] [*module number*] [**nowrap** [*module number*]] [**qos** [*module number*]] [**nowrap** [*module number*]]

**show mls netflow ip flow** {*icmp*|*tcp*|*udp*} [**count** [*module number*]] **destination** {*hostname*|*ip-address*} [**slash** *ip-mask*]] **detail** **dynamic**| **flow** {*icmp*|*tcp*|*udp*}| **module number**| **nowrap**| **qos**| **source** {*hostname*|*ip-address*}| **sw-installed** [**non-static**|**static**]]

**show mls netflow ip module** *number*

**show mls netflow ip qos** [*module number*] **nowrap** [*module number*]]

{**show mls netflow ip source** {*hostname*|*ip-address*} [**slash** *ip-mask*] [**count** [*module number*]]] **detail** **dynamic**| **flow** {*icmp*|*tcp*|*udp*}| **module number**| **nowrap**| **qos**| **sw-installed** [**non-static**|**static**]]}

### Syntax Description

<b>any</b>	Displays detailed NetFlow table-entry information with no test wrap.
<b>count</b>	Displays the total number of MLS NetFlow IP entries.
<b>destination</b> <i>hostname</i>	Displays the entries for a specific destination hostname.
<b>destination</b> <i>ip-address</i>	Displays the entries for a specific destination IP address.
<b>detail</b>	(Optional) Specifies a detailed output.
<b>dynamic</b>	Displays the hardware-created dynamic entries; see the <b>show mls netflow ip dynamic</b> command.
<b>flow icmp</b>	Displays information about the ICMP flows.
<b>flow tcp</b>	Displays information about the TCP flows.
<b>flow udp</b>	Displays information about the UDP flows.
/ <i>ip-mask</i>	Masks the IP address.

<b>module</b> <i>number</i>	Displays the entries on the specified module; see the “Usage Guidelines” section for valid values.
<b>nowrap</b>	Displays information without text wrap.
<b>qos</b>	Displays QoS microflow policing information.
<b>source</b> <i>hostname</i>	Displays the entries for a specific source address.
<b>source</b> <i>ip-address</i>	Displays the entries for a specific source IP address.
<b>sw-installed</b>	(Optional) Displays the routing NetFlow entries; see the <b>show mls netflow ip sw-installed</b> command.
<b>non-static</b>	(Optional) Displays information for software-installed static IP entries; see the <b>show mls netflow ip sw-installed</b> command.
<b>static</b>	(Optional) Displays information for the software-installed nonstatic IP entries; see the <b>show mls netflow ip sw-installed</b> command.

**Command Default**

This command has no default settings.

**Command Modes**

User EXEC Privileged EXEC

**Command History**

Release	Modification
12.2(14)SX	Support for this command was introduced on the Supervisor Engine 720.
12.2(17a)SX	This command was changed as follows: <ul style="list-style-type: none"> <li>Enhanced the <b>show mls netflow aggregation flowmask</b> command output to include a list of aggregation caches with minimum flow mask and NetFlow-aggregation schemes such as destination-prefix, source-prefix, protocol-port, and prefix.</li> <li>Included support for the <b>ipv6</b> option.</li> </ul>
12.2(17b)SXA	Changed the syntax from <b>show mls [ip   ipv6   mpls]</b> to <b>show mls netflow [ip   ipv6   mpls]</b> and added the <b>nowrap</b> keyword.
12.2(17d)SXB	Support for this command on the Supervisor Engine 2 was extended to Release 12.2(17d)SXB.

Release	Modification
12.2(18)SXD	This command was changed to include the following keywords: <ul style="list-style-type: none"> <li>• The <b>icmp</b> keyword to display information about ICMP flows.</li> <li>• The <b>qos</b> keyword to display QoS microflow policing information.</li> </ul>
12.2(18)SXF	This command was changed to remove support for the <b>any</b> keyword.
12.2(33)SRA	This command was integrated into Cisco IOS Release 12.2(33)SRA.
12.2(33)SRB	This command was modified to show the VPN name and VPN ID in the display output. In addition, the command was modified to support per-interface NetFlow.

### Usage Guidelines

If you enter the **show mls netflow ip** command with no arguments, the output of the **show mls netflow ip sw-installed** and **show mls netflow ip dynamic** commands are displayed.

When you view the output, note that a colon (:) is used to separate the fields.

The **multicast** keyword appears on systems that are not configured with a Supervisor Engine 720.

In Cisco IOS Release 12.2SR and later, the NetFlow cache might contain null entries (with an IP source and destination address of 0.0.0.0). This behavior is the result of changes made to support per-interface NetFlow, which allows you to enable NetFlow for IPv4 traffic on individual interfaces. By default, the hardware cache is populated with information about packets received on all IP interfaces. However, if NetFlow is not enabled on an IP interface, a null flowmask is used, which results in a null cache entry being created for the interface.

### Examples

This example shows how to display information about any MLS NetFlow IP:

```
Router# show mls netflow ip
Displaying Netflow entries in Supervisor Earl
DstIP SrcIP Prot:SrcPort:DstPort Src i/f:AdjPtr
-----
Pkts Bytes Age LastSeen Attributes
-----
10.1.1.2 11.1.1.2 tcp :3 :5 Fa5/11 :0x0
459983 21159218 6 07:45:13 L3 - Dynamic
10.1.1.2 11.1.1.3 tcp :3 :5 Fa5/11 :0x0
459984 21159264 6 07:45:13 L3 - Dynamic
Router#
```

This example shows how to display detailed NetFlow table-entry information:

```
Router# show mls netflow ip detail
Displaying Netflow entries in Supervisor Earl
DstIP SrcIP Prot:SrcPort:DstPort Src i/f:AdjPtr
-----
Pkts Bytes Age LastSeen Attributes
-----
Mask Pi R CR Xt Prio Dsc IP_EN OP_EN Pattern Rpf FIN_RDT FIN/RST
-----+-----+-----+-----+-----+-----+-----+-----+-----+
Ig/acli Ig/aclo Ig/qosi Ig/qoso Fpkt Gemini MC-hit Dirty Diags
-----+-----+-----+-----+-----+-----+-----+-----+-----+
QoS Police Count Threshold Leak Drop Bucket Use-Tbl Use-Enable
-----+-----+-----+-----+-----+-----+-----+-----+-----+
172.30.46.2 172.30.45.2 4 :0 :0 Gi7/1: 0x0
140063 6442898 15 01:42:52 L3 - Dynamic
```

```

1 1 0 0 1 0 0 1 1 0 0 0 0
0 0 0 0 0 0 0 0 0 0
0x0 672645504 0 0 NO 31784 NO NO
Router#

```

This example shows how to display NetFlow table-entry information with no test wrap:

```

Router# show mls netflow ip nowrap
Displaying Netflow entries in Supervisor Earl
DstIP SrcIP Prot:SrcPort:DstPort Src i/f
:AdjPtr Pkts Bytes Age LastSeen Attributes
-----

```

```

-----
10.1.1.2 11.1.1.92 udp :63 :63 Fa5/11
:0x0 176339 8111594 912 22:31:15 L3 - Dynamic
10.1.1.2 11.1.1.93 udp :63 :63 Fa5/11
:0x0 176338 8111548 912 22:31:15 L3 - Dynamic
10.1.1.2 11.1.1.94 udp :63 :63 Fa5/11
:0x0 176338 8111548 912 22:31:15 L3 - Dynamic
10.1.1.2 11.1.1.95 udp :63 :63 Fa5/11
:0x0 176338 8111548 912 22:31:15 L3 - Dynamic
10.1.1.2 11.1.1.96 udp :63 :63 Fa5/11
:0x0 176338 8111548 912 22:31:15 L3 - Dynamic
10.1.1.2 11.1.1.97 udp :63 :63 Fa5/11
:0x0 176337 8111502 912 22:31:15 L3 - Dynamic
10.1.1.2 11.1.1.98 udp :63 :63 Fa5/11
:0x0 176337 8111502 912 22:31:15 L3 - Dynamic
10.1.1.2 11.1.1.99 udp :63 :63 Fa5/11
:0x0 176337 8111502 912 22:31:15 L3 - Dynamic
10.1.1.2 11.1.1.100 udp :63 :63 Fa5/11
:0x0 176337 8111502 912 22:31:15 L3 - Dynamic
Router#

```

This example shows how to display information about the MLS NetFlow on a specific interface:

```

Router#
show mls netflow ip interface FastEthernet 3/1
Displaying Netflow entries in Supervisor Earl
DstIP SrcIP Prot:SrcPort:DstPort Src i/f:AdjPtr
-----
Pkts Bytes Age LastSeen Attributes
-----
172.20.52.19 0.0.0.0 0 :0 :0 0 : 0
0 0 1635 11:05:26 L3 - Dynamic
Router#

```

This example shows how to display information about the MLS NetFlow on a specific IP address:

```

Router#
show mls netflow ip destination 172.20.52.122
Displaying Netflow entries in Supervisor Earl
DstIP SrcIP Prot:SrcPort:DstPort Src i/f:AdjPtr
-----
Pkts Bytes Age LastSeen Attributes
-----
Router#

```

This example shows how to display information about the MLS NetFlow on a specific flow:

```

Router#
show mls netflow ip flow udp
Displaying Netflow entries in Supervisor Earl
DstIP SrcIP Prot:SrcPort:DstPort Src i/f:AdjPtr
-----
Pkts Bytes Age LastSeen Attributes
-----
172.20.52.19 0.0.0.0 0 :0 :0 0 : 0
0 0 1407 11:01:32 L3 - Dynamic
Router#

```

This example shows how to display detailed information about the MLS NetFlow on a full-flow mask:

```
Router#
show mls netflow ip detail
Displaying Netflow entries in Supervisor Earl
DstIP          SrcIP          Prot:SrcPort:DstPort  Src i/f:AdjPtr
-----
Pkts           Bytes           Age           LastSeen      Attributes
-----
      QoS       Police Count  Threshold    Leak         Drop Bucket  Use-Tbl Use-Enable
-----+-----+-----+-----+-----+-----+-----+-----+
172.20.52.19   0.0.0.0         0             :0           :0           0           : 0
0
0x0            0              1464         11:02:31    L3 - Dynamic
0             0              0            0           NO          64          NO        NO
Router#
```

This example shows how to display detailed information about a specific flow type:

```
Router#
show mls netflow ip flow icmp
Displaying Netflow entries in Supervisor Earl
DstIP SrcIP Prot:SrcPort:DstPort Src i/f
:AdjPtr
>
>
-----
-
-
Pkts Bytes Age LastSeen Attributes
-----
10.1.1.2 11.1.10.151 icmp:0 :0 Fa5/11
:0x0
1945 89470 1062 08:45:15 L3 - Dynamic
10.1.1.2 11.1.10.153 icmp:0 :0 Fa5/11
:0x0
1945 89470 1062 08:45:15 L3 - Dynamic
10.1.1.2 11.1.10.155 icmp:0 :0 Fa5/11
:0x0
1945 89470 1062 08:45:15 L3 - Dynamic
10.1.1.2 11.1.10.157 icmp:0 :0 Fa5/11
:0x0
1945 89470 1062 08:45:15 L3 - Dynamic
10.1.1.2 11.1.10.159 icmp:0 :0 Fa5/11
:0x0
1945 89470 1062 08:45:15 L3 - Dynamic
10.1.1.2 11.1.10.161 icmp:0 :0 Fa5/11
:0x0
1945 89470 1062 08:45:15 L3 - Dynamic
10.1.1.2 11.1.10.163 icmp:0 :0 Fa5/11
:0x0
Router#
```

This example shows how to display QoS information:

```
Router
# show mls netflow ip qos
Displaying netflow qos information in Supervisor Earl
DstIP          SrcIP          Prot:SrcPort:DstPort  Src i/f:AdjPtr
-----
Pkts           Bytes           LastSeen      QoS         PoliceCount  Threshold  Leak
-----
Drop Bucket
-----
xxx.xxxx.xxx.xxx xxx.xxx.xxx.xxx xxxx:63      :63         Fa5/11 :0x0
772357         35528422       17:59:01    xxx      xxx         xxx      xxx
xxx      xxx
Router#
```

This example shows how to display VPN information on a Cisco 7600 series router:

```
Router# show mls netflow ip module 5
Displaying Netflow entries in module 5
```



```

DstIP          SrcIP          Prot:SrcPort:DstPort  Src i/f          :AdjPtr
-----
Pkts           Bytes           Age    LastSeen  Attributes
-----
10.1.1.1       10.2.0.2        0      :0        :0        vpn:red
:0x0
504            398020          1      23:20:48  L3 - Dynamic
224.0.0.5     172.16.1.1     89     :0        :0        Fa1/1          :0x0
1              84              7      23:20:42  L2 - Dynamic
0.0.0.0       0.0.0.0        0      :0        :0        --            :0x0
2238          1582910        33     23:20:48  L3 - Dynamic
224.0.0.2     172.16.1.1     udp :646 :646     Fa1/1          :0x0
5              310             21     23:20:46  L2 - Dynamic
172.16.2.6    172.16.1.2     0      :0        :0        Fa1/1          :0x0
1              140             22     23:20:27  L2 - Dynamic
Router#

```

**Related Commands**

Command	Description
<b>flow hardware mpls-vpn ip</b>	Enables NetFlow to create and export hardware cache entries for traffic entering the router on the last MPLS hop of an IPv4 MPLS VPN network.
<b>ip flow ingress</b>	Enables (ingress) NetFlow accounting for traffic arriving on an interface.
<b>mls flow ip</b>	Configures the flow mask to use for NetFlow Data Export.
<b>show mls netflow ip dynamic</b>	Displays the statistics for NetFlow IP entries.
<b>show mls netflow ip sw-installed</b>	Displays information for the software-installed IP entries.
<b>show mls netflow ip routes</b>	Displays the NetFlow IP routing entries.

## show mls netflow ipv6

To display information about the hardware NetFlow IPv6 configuration, use the **show mls netflow ipv6** command in privileged EXEC mode.

**show mls netflow ipv6 any**

**show mls netflow ipv6 count** [*module number*]

**show mls netflow ipv6 destination** *ipv6-address* [ */ipv6-prefix* ] [**count** [*module number*]] **detail**| **dynamic**| **flow** {**icmp**| **tcp**| **udp**}| *module number*| **nowrap**| **qos**| **source** *ipv6-address* [ */ipv6-prefix* ]| **sw-installed** [**non-static**| **static**]]

**show mls netflow ipv6 detail** [*module number*| **nowrap** [*module number*]]

**show mls netflow ipv6 dynamic** [**count** [*module number*]] [**detail**] [*module number*] [**nowrap** [*module number*]] [**qos** [*module number*]] [**nowrap** [*module number*]]

**show mls netflow ipv6 flow** {**icmp**| **tcp**| **udp**} [**count** [*module number*]] **destination** *ipv6-address* [ */ipv6-prefix* ]| **detail**| **dynamic**| **flow** {**icmp**| **tcp**| **udp**}| *module number*| **nowrap**| **qos**| **source** *ipv6-address* [ */ipv6-prefix* ]| **sw-installed** [**non-static**| **static**]]

**show mls netflow ipv6** [*module number*]

**show mls netflow ipv6 qos** [*module number*| **nowrap** [*module number*]]

**show mls netflow ipv6 source** *ipv6-address* [ */ipv6-prefix* ] [**count** [*module number*]] **detail**| **dynamic**| **flow** {**icmp**| **tcp**| **udp**}| *module number*| **nowrap**| **qos**| **sw-installed** [**non-static**| **static**]]

### Syntax Description

<b>any</b>	Displays the NetFlow-aging information.
<b>count</b>	Displays the total number of Multilayer Switching (MLS) NetFlow IPv6 entries.
<b>module</b> <i>number</i>	(Optional) Displays the entries that are downloaded on the specified module; see the "Usage Guidelines" section for valid values.
<b>destination</b> <i>ipv6-address</i>	Displays the entries for a specific destination IPv6 address.
<i>/ ipv6-prefix</i>	(Optional) IPv6 prefix; valid values are from 0 to 128.
<b>detail</b>	Specifies a detailed output.
<b>dynamic</b>	Displays the hardware-created dynamic entries.
<b>flow</b> <b>icmp</b>   <b>tcp</b>   <b>udp</b>	Specifies the flow type.
<b>nowrap</b>	Turns off text wrapping.

<b>qos</b>	Displays information about quality of service (QoS) statistics.
<b>source</b> <i>ipv6-address</i>	(Optional) Displays the entries for a specific source IPv6 address.
<b>sw-installed</b>	(Optional) Displays the routing NetFlow entries.
<b>non-static</b>	(Optional) Displays information about the software-installed static IPv6 entries.
<b>static</b>	(Optional) Displays information about the software-installed nonstatic IPv6 entries.

**Command Modes**

Privileged EXEC (#)

**Command History**

Release	Modification
12.2(17a)SX	This command was introduced on the Supervisor Engine 720.
12.2(17d)SXB	Support for this command on the Supervisor Engine 2 was extended to Release 12.2(17d)SXB.
12.2(18)SXE	This command was changed to add the show mls netflow ipv6 qos [ <b>module number</b> ] [ nowrap ] keywords and argument on the Supervisor Engine 720 only.
12.2(18)SXF	This command was changed as follows: <ul style="list-style-type: none"> <li>• Removed support for the <b>any</b> keyword.</li> <li>• Added the / <i>ipv6-prefix</i> argument.</li> </ul>
12.2(33)SRA	This command was integrated into Cisco IOS Release 12.2(33)SRA.

**Examples**

This example shows how to display information about the hardware NetFlow configuration:

```

Router# show mls netflow ipv6
Displaying Netflow entries in Supervisor Earl
DstIP                               SrcIP
-----
Prot:SrcPort:DstPort  Src i/f      :AdjPtr
Pkts      Bytes      Age  LastSeen    Attributes
-----
50::2
tcp :16      :32      V147         :0x0
23758      1425480   4    23:48:36   L3 (IPv6) - Dynamic
50::2
tcp :16      :32      V147         :0x0

```

## show mls netflow ipv6

```

23758      1425480      4      23:48:36      L3 (IPv6) - Dynamic
50::2                                           47::4
tcp :16      :32      V147      :0x0
23758      1425480      4      23:48:36      L3 (IPv6) - Dynamic
50::2                                           47::5
tcp :16      :32      V147      :0x0
23758      1425480      4      23:48:36      L3 (IPv6) - Dynamic
50::2                                           47::6
tcp :16      :32      V147      :0x0
23758      1425480      4      23:48:36      L3 (IPv6) - Dynamic

```

This example shows how to display IPv6 microflow policing information:

```

Router# show mls netflow ipv6 qos
Displaying Netflow entries in Supervisor Earl
DstIP                               SrcIP
-----
Prot:SrcPort:DstPort  Src i/f          :AdjPtr  Pkts      Bytes
-----
LastSeen  QoS    PoliceCount  Threshold  Leak      Drop  Bucket
-----
101::3    :0     --          100::2    0x0      0     0
icmp:0
22:22:09  0x0    0           0         0        0     NO  0
101::2    :0     --          100::2    0x0      0     0
icmp:0
22:22:09  0x0    0           0         0        0     NO  0

```

This example shows how to display IPv6 microflow policing information for a specific module:

```

Router# show mls netflow ipv6 qos module 7
Displaying Netflow entries in module 7
DstIP                               SrcIP
-----
Prot:SrcPort:DstPort  Src i/f          :AdjPtr  Pkts      Bytes
-----
LastSeen  QoS    PoliceCount  Threshold  Leak      Drop  Bucket
-----
101::2    :0     --          100::2    0x0      0     0
icmp:0
22:22:56  0x0    0           0         0        0     NO  0
101::3    :0     --          100::2    0x0      0     0
icmp:0
22:22:56  0x0    0           0         0        0     NO  0

```

This example shows the output display when you turn off text wrapping:

```

Router# show mls netflow ipv6 qos nowrap
Displaying Netflow entries in Supervisor Earl
DstIP                               SrcIP
Prot:SrcPort:DstPort  Src i/f          :AdjPtr  Pkts      Bytes      LastSeen
QoS    PoliceCount  Threshold  Leak      Drop  Bucket
-----
101::3    :0     --          100::2    0x0      0           22:22:19  icmp:0
:0     --          0x0      NO  0         0           0x0      0
101::2    :0     --          100::2    0x0      0           22:22:19  icmp:0
:0     --          0x0      NO  0         0           0x0      0

```

This example shows the output display when you turn off text wrapping for a specific module:

```

Router# show mls netflow ipv6 qos nowrap module 7
Displaying Netflow entries in module 7
DstIP                               SrcIP
Prot:SrcPort:DstPort  Src i/f          :AdjPtr  Pkts      Bytes      LastSeen
QoS    PoliceCount  Threshold  Leak      Drop  Bucket
-----
101::3    :0     --          100::2    0x0      0           22:22:38  icmp:0
:0     --          0x0      NO  0         0           0x0      0
101::2    :0     --          100::2    0x0      0           icmp:0

```

```
:0      --      0      0      0x0      0      0      22:22:38      0x0      0
```

**Related Commands**

Command	Description
<b>clear mls netflow</b>	Clears the MLS NetFlow-shortcut entries.

# show mls netflow ip dynamic

To display the statistics for NetFlow IP entries, use the **show mls netflow ip dynamic** command in user EXEC or privileged EXEC mode.

**show mls netflow ip dynamic** [**count** [**module number**]] [**detail** [**module number**]] **module number**

## Syntax Description

<b>count</b>	(Optional) Displays the total number of NetFlow entries.
<b>module number</b>	(Optional) Displays the entries that are downloaded on the specified module; see the “Usage Guidelines” section for valid values.
<b>detail</b>	(Optional) Specifies a detailed per-flow output.

## Command Default

This command has no default settings.

## Command Modes

User EXEC Privileged EXEC

## Command History

Release	Modification
12.2(14)SX	Support for this command was introduced on the Supervisor Engine 720.
12.2(17a)SX	This command replaced the <b>show mls netflow ip statistics</b> command.
12.2(17d)SXB	Support for this command on the Supervisor Engine 2 was extended to the 12.2 SX release.
12.2(33)SRA	This command was integrated into Cisco IOS Release 12.2(33)SRA.

## Usage Guidelines

The **show mls netflow ip statistics** command is supported on releases prior to Release 12.2(17a)SX. For Release 12.2(17a)SX and later releases, use the **show mls netflow ip dynamic** command.

## Examples

This example shows how to display the statistics for the NetFlow IP entries:

```
Router> show mls netflow ip dynamic
Displaying Netflow entries in Supervisor Earl
DstIP          SrcIP          Prot:SrcPort:DstPort  Src i/f:AdjPtr
-----
Pkts           Bytes         Age   LastSeen  Attributes
```

```
-----
Router>
```

This example shows how to display the statistics for the NetFlow IP entries:

```
Router> show mls netflow ip dynamic detail
Displaying Netflow entries in Supervisor Earl
DstIP          SrcIP          Prot:SrcPort:DstPort  Src i/f:AdjPtr
-----
Pkts           Bytes         Age   LastSeen  Attributes
-----
      QoS      Police Count Threshold   Leak   Drop Bucket  Use-Tbl Use-Enable
-----+-----+-----+-----+-----+-----+-----+
Router>
```

### Related Commands

Command	Description
<b>show mls netflow ip</b>	Displays information about MLS NetFlow IP traffic.
<b>show mls netflow ip dynamic</b>	Displays the statistics for NetFlow IP entries.
<b>show mls netflow ip sw-installed</b>	Displays information for the software-installed IP entries.
<b>show mls netflow ip routes</b>	Displays the NetFlow IP routing entries.

# show mls netflow ip routes

To display the NetFlow IP routing entries, use the **show mls netflow ip routes** command in user EXEC or privileged EXEC mode.

**show mls netflow ip routes** [**non-static**|**static**] [**count** [**module number**]] [**detail** [**module number**]] [**module number**]

## Syntax Description

<b>non-static</b>	(Optional) Displays the software-installed routing entries.
<b>static</b>	(Optional) Displays the software-installed static routing entries.
<b>count</b>	(Optional) Displays the total number of NetFlow IP routing entries.
<b>module number</b>	(Optional) Displays the entries that are downloaded on the specified module; see the “Usage Guidelines” section for valid values.
<b>detail</b>	(Optional) Specifies a detailed per-flow output.

## Command Default

This command has no default settings.

## Command Modes

User EXEC Privileged EXEC

## Command History

Release	Modification
12.2(14)SX	Support for this command was introduced on the Supervisor Engine 720.
12.2(17a)SX	This command was changed to the <b>show mls netflow ip sw-installed</b> command.

## Usage Guidelines

The **show mls netflow ip routes** command is supported on releases prior to Release 12.2(17a)SX. For Release 12.2(17a)SX and later releases, use the **show mls netflow ip sw-installed** command.

This command is not supported on Cisco 7600 series routers that are configured with a Supervisor Engine 2.



**Examples**

This example shows how to display the software-installed nonstatic routing entries:

```
Router> show mls netflow ip routes non-static
Displaying Netflow entries in Supervisor Earl
DstIP          SrcIP          Prot:SrcPort:DstPort  Src i/f:AdjPtr
-----
Pkts           Bytes          Age    LastSeen  Attributes
-----
Router>
```

This example shows how to display detailed information for the software-installed nonstatic routing entries:

```
Router> show mls netflow ip routes non-static detail
Displaying Netflow entries in Supervisor Earl
DstIP          SrcIP          Prot:SrcPort:DstPort  Src i/f:AdjPtr
-----
Pkts           Bytes          Age    LastSeen  Attributes
-----
      QoS      Police Count Threshold   Leak   Drop Bucket  Use-Tbl Use-Enable
-----+-----+-----+-----+-----+-----+-----+-----+
Router>
```

This example shows how to display the total number of software-installed routing entries:

```
Router> show mls netflow ip routes count
Displaying Netflow entries in Supervisor Earl
Number of shortcuts = 0
Router>
```

**Related Commands**

Command	Description
show mls netflow ip	Displays information about MLS NetFlow IP traffic.
<b>show mls netflow ip dynamic</b>	Displays the statistics for NetFlow IP entries.
show mls netflow ip sw-installed	Displays information for the software-installed IP entries.

# show mls netflow ip sw-installed

To display information for the software-installed IP entries, use the **show mls netflow ip sw-installed** command in user EXEC or privileged EXEC mode.

**show mls netflow ip sw-installed** {**non-static**|**static**} [**count** [**module number**]] **detail** [**module number**]  
**module number**]

## Syntax Description

<b>non-static</b>	Displays the software-installed routing entries.
<b>static</b>	Displays the software-installed static routing entries.
<b>count</b>	(Optional) Displays the total number of nonstatic entries.
<b>module number</b>	(Optional) Displays the entries that are downloaded on the specified module; see the “Usage Guidelines” section for valid values.
<b>detail</b>	(Optional) Specifies a detailed per-flow output.

## Command Default

This command has no default settings.

## Command Modes

User EXEC Privileged EXEC

## Command History

Release	Modification
12.2(17a)SX	The <i>show mls netflow ip routes</i> command was changed to the <b>show mls netflow ip sw-installed</b> command.
12.2(17d)SXB	Support for this command on the Supervisor Engine 2 was extended to the 12.2 SX release.
12.2(33)SRA	This command was integrated into Cisco IOS Release 12.2(33)SRA.

## Examples

This example shows how to display the software-installed nonstatic entries:

```
Router> show mls netflow ip sw-installed non-static
Displaying Netflow entries in Supervisor Earl
DstIP          SrcIP          Prot:SrcPort:DstPort  Src i/f:AdjPtr
-----
Pkts           Bytes         Age   LastSeen  Attributes
```

-----  
 Router>  
 This example shows how to display detailed information for the software-installed nonstatic entries:

```
Router> show mls netflow ip sw-installed non-static detail
Displaying Netflow entries in Supervisor Earl
DstIP          SrcIP          Prot:SrcPort:DstPort  Src i/f:AdjPtr
-----
Pkts           Bytes          Age   LastSeen  Attributes
-----
      QoS      Police Count Threshold   Leak   Drop Bucket  Use-Tbl Use-Enable
-----+-----+-----+-----+-----+-----+-----+-----+-----+
Router>
```

This example shows how to display the total number of software-installed nonstatic entries:

```
Router> show mls netflow ip sw-installed non-static count
Displaying Netflow entries in Supervisor Earl
Number of shortcuts = 0
Router>
```

### Related Commands

Command	Description
<b>show mls netflow ip</b>	Displays information about MLS NetFlow IP traffic.
<b>show mls netflow ip dynamic</b>	Displays the statistics for NetFlow IP entries.
<b>show mls netflow ip routes</b>	Displays the NetFlow IP routing entries.

## show mls netflow ipx

To display MLS NetFlow IPX information in the EXEC command mode, use the **show mls netflow ipx** command.

**show mls netflow ipx** [**count**| **destination** {*hostname*| *ipx-address*}| **detail**| **flow** {**tcp**| **udp**}| **interface** *interface interface-number*| **vlan** *vlan-id*| **macd** *destination-mac-address*| **macs** *source-mac-address*| **routes num**| **module number**| **source** {*hostname*| *ipx-address*}| **statistics**]

### Syntax Description

<b>count</b>	(Optional) Displays the total number of MLS NetFlow IPX entries.
<b>destination</b> <i>hostname</i>	(Optional) Displays the entries for a specific destination IPX hostname.
<b>destination</b> <i>ipx-address</i>	(Optional) Displays the entries for a specific destination IPX address.
<b>detail</b>	(Optional) Specifies a detailed output.
<b>flow</b>	(Optional) Changes the flow type.
<b>tcp</b>   <b>udp</b>	Specifies the flow type.
<b>interface</b>	(Optional) Specifies the interface.
<i>interface</i>	(Optional) Interface type; possible valid values are <b>ethernet</b> , <b>fastethernet</b> , <b>gigabitethernet</b> , <b>tengigabitethernet</b> , <b>pos</b> , <b>atm</b> , and <b>ge-wan</b> .
<i>interface-number</i>	(Optional) Module and port number; see the “Usage Guidelines” section for valid values.
<b>vlan</b> <i>vlan-id</i>	(Optional) Specifies the VLAN ID; valid values are from 1 to 4094.
<b>macd</b> <i>destination-mac-address</i>	(Optional) Specifies the destination MAC address.
<b>macs</b> <i>source-mac-address</i>	(Optional) Specifies the source MAC address.
<b>routes</b> <i>num</i>	(Optional) Displays the routing NetFlow entries.
<b>module</b> <i>number</i>	(Optional) Displays the entries that are downloaded on the specified module; see the “Usage Guidelines” section for valid values.

<b>source</b> <i>hostname</i>	(Optional) Displays the entries for a specific source address.
<b>source</b> <i>ipx-address</i>	(Optional) Displays the entries for a specific destination IPX address.
<b>statistics</b>	(Optional) Displays the statistics for NetFlow entries.

**Command Default** This command has no default settings.

**Command Modes** EXEC

<b>Command History</b>	<b>Release</b>	<b>Modification</b>
	12.2(17d)SXB	Support for this command on the Supervisor Engine 2 was extended to Release 12.2(17d)SXB.

**Usage Guidelines** The **show mls netflow ipx** command is only supported on systems that have a version 2 Supervisor Engine. The **interface**, **macd**, and **macs** keywords are not supported. When you enter the *ipx-network*, the format is N.H.H.H. When you enter the *destination-mac-address*, the format for the 48-bit MAC address is H.H.H. The *interface-number* argument designates the module and port number. Valid values for *interface-number* depend on the specified interface type and the chassis and module used. For example, if you specify a Gigabit Ethernet interface and have a 48-port 10/100BASE-T Ethernet module installed in a 13-slot chassis, valid values for the module number are from 1 to 13 and valid values for the port number are from 1 to 48. These valid values also apply when entering the **module number** keyword and argument.

**Examples** The output from the **show mls netflow ipx** commands is similar to the **show mls netflow ip** commands.

<b>Related Commands</b>	<b>Command</b>	<b>Description</b>
	<b>show mls netflow ip</b>	Displays information about the hardware NetFlow IP.

# show mls sampling

To display information about the sampled NDE status, use the **show mls sampling** command in user EXEC or privileged EXEC mode.

**show mls sampling**

**Syntax Description** This command has no keywords or arguments.

**Command Default** This command has no default settings.

**Command Modes** User EXEC Privileged EXEC

Release	Modification
12.2(14)SX	Support for this command was introduced on the Supervisor Engine 720.
12.2(17d)SXB	Support for this command on the Supervisor Engine 2 was extended to the 12.2 SX release.
12.2(33)SRA	This command was integrated into Cisco IOS Release 12.2(33)SRA.

**Usage Guidelines** Sampled NetFlow is supported on Layer 3 interfaces only.

**Examples** This example shows how to display information about the sampled NDE status:

```
Router# show mls sampling
time-based sampling is enabled
1 out of every 1024 packets is being sampled.
Sampling Interval and Period is 4 millisec per 4096 millisec
Router#
```

## Related Commands

Command	Description
<b>mls netflow sampling</b>	Enables the sampled NetFlow on an interface.
<b>mls sampling</b>	Enables the sampled NetFlow and specifies the sampling method.

## sort-by

To specify the sorting criterion for the NetFlow top talkers (unaggregated top flows), use the **sort-by** command in NetFlow top talkers configuration mode. To disable NetFlow top talkers, use the **no** form of this command.

**sort-by** [bytes| packets]

**no sort-by** [bytes| packets]

### Syntax Description

<b>bytes</b>	Sorts the list of top talkers by the total number of bytes in each Top Talker.
<b>packets</b>	Sort the list of top talkers by the total number of packets in each Top Talker.

### Command Default

No default behavior or values.

### Command Modes

NetFlow top talkers configuration

### Command History

Release	Modification
12.2(25)S	This command was introduced.
12.3(11)T	This feature was integrated into Cisco IOS Release 12.3(11)T.
12.2(27)SBC	This feature was integrated into Cisco IOS Release 12.2(27)SBC.
12.2(33)SRA	This command was integrated into Cisco IOS Release 12.2(33)SRA.
12.2SX	This command is supported in the Cisco IOS Release 12.2SX train. Support in a specific 12.2SX release of this train depends on your feature set, platform, and platform hardware.

### Usage Guidelines

#### Configuring NetFlow Top Talkers

You must enable NetFlow on at least one interface in the router; and configure NetFlow top talkers before you can use the **show ip flow top-talkers** command to display the traffic statistics for the unaggregated top flows in the network. NetFlow top talkers also requires that you configure the **sort-by** and **top** commands. Optionally, the **match** command can be configured to specify additional matching criteria.

**Examples**

In the following example, a maximum of four top talkers is configured. The sort criterion is configured to sort the list of top talkers by the total number of bytes for each top talker.

```
Router(config)# ip flow-top-talkers
Router(config-flow-top-talkers)# top 4
Router(config-flow-top-talkers)# sort-by bytes
```

The following example shows the output of the **show ip flow top talkers** command with the configuration from the previous example:

```
Router# show ip flow top-talkers
```

```
SrcIf      SrcIPAddress  DstIf      DstIPAddress  Pr SrcP DstP Bytes
Et0/0.1    10.10.18.1    Et1/0.1    172.16.10.232 11 00A1 00A1 349K
Et0/0.1    10.10.19.1    Et1/0.1    172.16.10.2   11 00A2 00A2 349K
Et0/0.1    172.30.216.196 Et1/0.1    172.16.10.2   06 0077 0077 328K
Et0/0.1    10.162.37.71 Et1/0.1    172.16.10.2   06 0050 0050 303K
4 of 4 top talkers shown. 11 flows processed
```

**Related Commands**

Command	Description
<b>cache-timeout</b>	Specifies the length of time for which the list of top talkers (heaviest traffic patterns and most-used applications in the network) for the NetFlow MIB and top talkers feature is retained.
<b>ip flow-top-talkers</b>	Enters the configuration mode for the NetFlow MIB and top talkers (heaviest traffic patterns and most-used applications in the network) feature.
<b>match (NetFlow)</b>	Specifies match criteria for the NetFlow MIB and top talkers (heaviest traffic patterns and most-used applications in the network) feature.
<b>show ip cache flow</b>	Displays a summary of the NetFlow accounting statistics.
<b>show ip cache verbose flow</b>	Displays a detailed summary of the NetFlow accounting statistics.
<b>show ip flow interface</b>	Displays NetFlow accounting configuration for interfaces.
<b>show ip flow top-talkers</b>	Displays the statistics for the NetFlow accounting top talkers (heaviest traffic patterns and most-used applications in the network).
<b>top</b>	Specifies the maximum number of top talkers (heaviest traffic patterns and most-used applications in the network) to be displayed for the NetFlow MIB and top talkers feature.





# top

To specify the maximum number of NetFlow top talkers (unaggregated top flows) to display the statistics for, use the **top** command in NetFlow top talkers configuration mode. To disable NetFlow top talkers, use the **no** form of this command.

**top** *number*

**no top**

## Syntax Description

<i>number</i>	The maximum number of top talkers that will be displayed. The range is 1 to 200.
---------------	--

## Command Default

No default behavior or values.

## Command Modes

NetFlow top talkers configuration

## Command History

Release	Modification
12.2(25)S	This command was introduced.
12.3(11)T	This feature was integrated into Cisco IOS Release 12.3(11)T.
12.2(27)SBC	This feature was integrated into Cisco IOS Release 12.2(27)SBC.
12.2(33)SRA	This command was integrated into Cisco IOS Release 12.2(33)SRA.
12.2SX	This command is supported in the Cisco IOS Release 12.2SX train. Support in a specific 12.2SX release of this train depends on your feature set, platform, and platform hardware.

## Usage Guidelines

### Configuring NetFlow Top Talkers

You must enable NetFlow on at least one interface in the router; and configure NetFlow top talkers before you can use the **show ip flow top-talkers** command to display the traffic statistics for the unaggregated top flows in the network. NetFlow top talkers also requires that you configure the **sort-by** and **top** commands. Optionally, the **match** command can be configured to specify additional matching criteria.

## Examples

In the following example, a maximum of four top talkers is configured. The sort criterion is configured to sort the list of top talkers by the total number of bytes for each top talker.

```
Router(config)# ip flow-top-talkers
```

```
Router(config-flow-top-talkers)# top 4
Router(config-flow-top-talkers)# sort-by bytes
```

The following example shows the output of the **show ip flow top talkers** command with the configuration from the previous example:

```
Router# show ip flow top-talkers
```

```
SrcIf      SrcIPAddress  DstIf      DstIPAddress  Pr SrcP DstP Bytes
Et0/0.1    10.10.18.1    Et1/0.1    172.16.10.232 11 00A1 00A1 349K
Et0/0.1    10.10.19.1    Et1/0.1    172.16.10.2   11 00A2 00A2 349K
Et0/0.1    172.30.216.196 Et1/0.1    172.16.10.2   06 0077 0077 328K
Et0/0.1    10.162.37.71 Et1/0.1    172.16.10.2   06 0050 0050 303K
4 of 4 top talkers shown. 11 flows processed
```

## Related Commands

Command	Description
<b>cache-timeout</b>	Specifies the length of time for which the list of top talkers (heaviest traffic patterns and most-used applications in the network) for the NetFlow MIB and top talkers feature is retained.
<b>ip flow-top-talkers</b>	Enters the configuration mode for the NetFlow MIB and top talkers (heaviest traffic patterns and most-used applications in the network) feature.
<b>match (NetFlow)</b>	Specifies match criteria for the NetFlow MIB and top talkers (heaviest traffic patterns and most-used applications in the network) feature.
<b>show ip cache flow</b>	Displays a summary of the NetFlow accounting statistics.
<b>show ip cache verbose flow</b>	Displays a detailed summary of the NetFlow accounting statistics.
<b>show ip flow interface</b>	Displays NetFlow accounting configuration for interfaces.
<b>show ip flow top-talkers</b>	Displays the statistics from to the top talkers (heaviest traffic patterns and most-used applications in the network).
<b>sort-by</b>	Specifies the sorting criterion for top talkers (heaviest traffic patterns and most-used applications in the network) to be displayed for the NetFlow MIB and top talkers feature.

