



Cisco Prime Provisioning 7.1 Release Notes

September 4, 2018

All documentation, including this Cisco Prime Provisioning 7.1 Release Notes document and any or all parts of the Cisco Prime Provisioning 7.1 documentation set, might be upgraded over time. Therefore, we recommend you to access the Prime Provisioning 7.1 documentation set online at:

<http://www.cisco.com/go/provisioning>

You can also navigate to this documentation set by clicking **Help** on the Home Page of the Prime Provisioning 7.1 product.

The information in this release notes provides an overview of this release and helps you understand it at a high level. After reading the *Cisco Prime Provisioning 7.1 Documentation Overview*, please read this release note prior to reading any other documentation for Prime Provisioning 7.1.

URL's for base information about Prime Provisioning 7.1, a product overview, and suggested reading order of these documents is given in [Related Documentation, page 20](#).

Contents

This document includes the following sections:

- [Contents, page 1](#)
- [Introduction, page 2](#)
- [Installing Prime Provisioning 7.1, page 2](#)
- [New Features and Enhancements in Prime Provisioning 7.1, page 3](#)
- [Prime Provisioning 7.1 Resolved and Open Bugs, page 18](#)
- [Web Browser Support, page 17](#)
- [Finding Known Problems in Prime Provisioning 7.1, page 20](#)
- [Related Documentation, page 20](#)
- [Accessibility Features in Prime Provisioning, page 20](#)
- [Obtaining Documentation and Submitting a Service Request, page 21](#)



Americas Headquarters:
Cisco Systems, Inc., 170 West Tasman Drive, San Jose, CA 95134-1706 USA

Introduction

Prime Provisioning is a management solution for network provisioning that enables the automation and scaling of complex, policy-driven network provisioning tasks to produce consistent and reliable service deployments. Prime Provisioning does this by planning, provisioning, and auditing services across core, aggregation, access, and consumer premises equipment devices.

Cisco Prime Provisioning enables fast deployment and time-to-market of Multiprotocol Label Switching (MPLS) and Carrier Ethernet technologies. In addition, the Prime Provisioning Traffic Engineering Management (TEM) module is Cisco's exclusive planning and provisioning tool for Cisco MPLS Traffic Engineering-enabled routers. MPLS Transport Profile (TP) provides service providers with a reliable packet-based technology that is based upon circuit-based transport networking, and hence is expected to align with current organizational processes and large-scale work procedures similar to other packet transport technologies.

The Cisco Prime Provisioning solution has management capabilities for MPLS VPN, L2VPN and Carrier Ethernet, MPLS TP, and MPLS Traffic Engineering. These capabilities that comprise Cisco Prime Provisioning can be used in a stand-alone manner or can be integrated with the Prime Carrier Management September 2018 suite.

Cisco Prime Provisioning 7.1 includes many new and enhancement features whose highlights are listed below:

- L2 Features
 - Support for L2VPN IOS-XE syntax in ASR-902 and ASR 903.
 - Support for Bridge Group in L2 EVC services in VFI Management
- L3 Features
 - Support for BGP additional paths and ip helper address for L3VPN configuration for ASR 902 and ASR 903 devices, which is a new syntax support for ASR 902 and ASR 903 devices
 - Support for L3 EVC services with autopick bridge domain name with new L3-X format.
 - Support for Bridge Group in L3 EVC Services in VFI Management
 - Support for Bundle Interface in Prime Provisioning
 - L3VPN IOS-XE new syntax support in ASR 902 and ASR 903 devices
- RHEL Support
 - Supports RHEL 7.1 version.
- General Features
 - EFP-Trunk support for ASR902 and ASR 903
 - Supports device picker with filter option for Hub and Backup Hub selection
 - Platform certification Support for: IOS-R 6.4.1

Installing Prime Provisioning 7.1

When purchasing Prime Provisioning you will be prompted to select either delivery by

- eDelivery, in which case you will receive an email with a download link, or physical DVD media

If the version is not the latest, you are advised to upgrade. The latest Prime Provisioning 6.x version can be ordered for download by eDelivery (or DVD shipment) free of charge, provided that you have a Software and Services (SAS) contract. The minor upgrade can be ordered through the Product Upgrade Tool (PUT):

<http://tools.cisco.com/gct/Upgrade/jsp/productUpgrade.jsp>

Additionally, you are strongly advised to apply the latest available service patch. Prime Provisioning patches are available at

<http://software.cisco.com/download/navigator.html?mdfid=284127465&flowid=37682>

For information about the installation process, see the *Cisco Prime Provisioning Installation Guide 7.1*.

Installation Notes

After the Patch upgrade, certain host configuration properties are not retained. So, it is advisable to create a backup of all the DCPL settings, by running the following script.

```
$PRIMEF_HOME/bin/extractproperties.sh
```

Once you upgrade, run the following script to restore the DCPL settings.

```
$PRIMEF_HOME/bin/extractproperties.sh -replace
```

New Features and Enhancements in Prime Provisioning 7.1

This section describes features and enhancements added or modified in Prime Provisioning 7.1.

For system recommendations, refer to the *Cisco Prime Provisioning Installation Guide 7.1*, and for device and platform support, refer to [Cisco Prime Provisioning Supported Devices](#). It includes the network devices and related software supported with Prime Provisioning 7.1. We recommend that you thoroughly review this list before even planning your installation, to be sure you have all the hardware and software needed for a successful installation.

Prime Provisioning 7.1 is based on Cisco Prime Provisioning 7.0.

Prime Provisioning 7.1 includes problems fixed since Cisco Prime Provisioning 7.0. See [Prime Provisioning 7.1 Resolved and Open Bugs, page 18](#).



Note

Cisco Prime Provisioning 7.1 is compatible with Cisco Prime Central 2.0. Make sure you upgrade Cisco Prime Central to version 2.0 before upgrading and integrating the current version of Prime Provisioning.



Note

- Prime Provisioning can be used as a standalone product or as a part of Prime Carrier Management September 2018. When installed as part of the suite, you can launch Prime Provisioning from the Prime Central portal. For more information about Prime Central, see the documentation for [Cisco Prime Central](#).
 - Cisco Prime for IP Next Generation Networks (IP NGN) has been renamed as Cisco Prime for Evolved Programmable Networks (EPN). Please keep this in mind when viewing the suite and application documentation for the upcoming Cisco Prime Carrier Management release.
-

Items specific to Prime Provisioning 7.1 include the new and changed information as documented in the following sections:

- Features introduced in Prime Provisioning 6.8.1
 - [General Features, page 4](#)
 - [L2EVC/TDM-CEM New Features, page 6](#)
 - [API New Features, page 8](#)
- Features introduced in Prime Provisioning 6.8.2
 - [General Features, page 9](#)
 - [L3 Features, page 9](#)
- Features introduced in Prime Provisioning 7.0.
 - [L2 EVC Features, page 13](#)
 - [L3VPN/MPLS Services Features, page 14](#)

Features Introduced in Prime Provisioning 6.8.1

General Features

This section summarizes the general features that were added in Prime Provisioning 6.8.1.

Supporting NBI for IPv6 Address Pool

From this release, NBI support has been extended for **IPv6 Address** pool. IPv6 Address pool is used by MPLS services while automatically assigning the IPv6 Addresses from the pool.

Below is a sample **NBI XML** highlighting the tags, attributes and values required for creation of a new IPV6 Address pool.

```
<soapenv:Envelope>
  <soapenv:Header>
    <ns0:message id="199" timestamp="2016-07-05T17:15:38.885Z"
    sessiontoken="E4DBF8A8E61BF4A77FF8B6106819C433" />
  </soapenv:Header>
  <soapenv:Body>
    <ns1:createInstance>
      <objectPath xsi:type="ns1:CIMObjectPath">
        <className xsi:type="xsd:string">IPv6AddressPool</className>
        <properties xsi:type="ns1:CIMPropertyList" soapenc:arrayType="ns1:CIMProperty[]">
          <item xsi:type="ns1:CIMProperty">
            <name xsi:type="xsd:string">IPv6AddressPool</name>
            <value xsi:type="xsd:string">2090:588:af23::/110</value>
          </item>
          <item xsi:type="ns1:CIMProperty">
            <name xsi:type="xsd:string">SubnetMask</name>
            <value xsi:type="xsd:string">127</value>
          </item>
          <item xsi:type="ns1:CIMProperty">
            <name xsi:type="xsd:string">Region</name>
            <value xsi:type="xsd:string">Reg_00X</value>
          </item>
        </properties>
      </objectPath>
    </ns1:createInstance>
  </soapenv:Body>
</soapenv:Envelope>
```

```

    </item>
  </properties>
</objectPath>
</ns1:createInstance>
</soapenv:Body>
</soapenv:Envelope>

```

NBI Support for Automatically Assigning the IPv6 Addresses

From this release, Prime Provisioning extended NBI support for automatically assigning the **IPv6 Addresses** for MPLS Services from the pool.

IPv6 Address allocation is supported only for **Regular: PE-CE MPLS** policy and services.

Below are the sample **NBI XML** snippets highlighting the tags, attributes and values required for automatically assigning the **IPv6 Addresses** from the pool during creation/modification of MPLS Policies.

```

<item xsi:type="ns1:CIMProperty">
  <name xsi:type="xsd:string">Auto_Assign_IPv6_Address</name>
  <value xsi:type="xsd:string">true</value>
  <qualifier xsi:type="ns1:CIMQualifier">
    <name xsi:type="xsd:string">editable</name>
    <value xsi:type="xsd:string">true</value>
  </qualifier>
</item>

<item xsi:type="ns1:CIMProperty">
  <name xsi:type="xsd:string">IPv6_Address_pool_type</name>
  <value xsi:type="xsd:string">Region Pool</value>
  <qualifier xsi:type="ns1:CIMQualifier">
    <name xsi:type="xsd:string">editable</name>
    <value xsi:type="xsd:string">true</value>
  </qualifier>
</item>

<item xsi:type="ns1:CIMProperty">
  <name xsi:type="xsd:string">IPv6_Address_pool_mask</name>
  <value xsi:type="xsd:string">126</value>
  <qualifier xsi:type="ns1:CIMQualifier">
    <name xsi:type="xsd:string">editable</name>
    <value xsi:type="xsd:string">true</value>
  </qualifier>
</item>

```



Note

To create an IPv6 addressing based MPLS-SR via NBI, the Policy must be created with IP numbering scheme as **IPv6 Numbered**.

Deprecating Config Audit Functionality

From this release, Prime Provisioning deprecates the Config Audit functionality.

In Prime Provisioning, whenever an SR is deployed, configlets are pushed into the devices and config audit functionality compares the generated configlet against the one downloaded to the device.

During subsequent modification of SR, config audit only compares the additional/modified configlets which are pushed into the device. This doesn't serve any purpose as it doesn't check whether the initial configlets pushed into the devices are still available and valid.

Config Audit functionality can be reactivated using DCPL properties. If the value of the DCPL property is set to true, Prime Provisioning will not perform config audit. If the value is set to false, Prime Provisioning will perform config audit. The default value of DCPL property is true.

DCPL Path:

Provisioning\ProvDrv\DeprecateConfigAudit



Note

Once the DCPL property is set to false, Prime Provisioning need to be restarted to re-display the Config Audit in the Task Manager.

L2EVC/TDM-CEM New Features

This section summarizes features that were added to enhance EVC services in Prime Provisioning 6.8.1.

Supporting Trunk EFP for ASR920 UPE device

In Prime Provisioning 6.8.1, a new attribute **Enable Trunk EFP** has been added in Service Request screens for UPE device, which gives flexibility to make many Layer 2 flow points within one interface. One interface can have only one trunk support and doesn't provide support for switchport trunk. Enable Trunk EFP attribute supports flex. It appears in the screen only when the Links with L2 Access Nodes or Rings contain ASR920 device. It provides support only for ASR920 IOS device.

If Enable Trunk EFP check box is enabled user will get “**service instance trunk <id> ethernet and encapsulation dot1q add <id>/ encapsulation dot1q remove <id>**” commands. If this check box is checked, Inner VLAN, Autopick Outer VLAN and Autopick Inner VLAN are not supported. For Rewrite Type only Pop is supported.



Note

In SR modification, Encapsulation of VLAN Id does not support add and remove commands together due to XDE framework limitation. As a workaround, same can be achieved by using policy customization.

This is feature is supported through GUI, NBI and Physical Rings.

Below are the sample configlets:

```
service instance trunk <id> ethernet
  encapsulation dot1q add <value>
  rewrite ingress tag pop <id> symmetric
  bridge-domain from-encapsulation
```

Extending E-Tree Functionality

From Prime Provisioning 6.8.1, E-Tree role functionality has been extended to generate neighbor commands under vfi for hubs with E-Tree role as root or leaf for EVC services.

In accordance with this functionality, when the **E-Tree** role of the **HUB** node is set as **ROOT**, under vfi, neighbor commands gets generated for all the other hubs, and when the **E-Tree** role of the **HUB** node is set as **LEAF**, under vfi, neighbor commands gets generated for only the hub node with E-tree role as root.

Below are the sample configlets.

Example: HVPLS SR with E-Tree (2 HUBs_root, 2 HUBs_leaf)

cl-test-l2-7600-5 (HUB-root)	isc-cl-test-l2-asr9006-3 (HUB_leaf)
<pre> bridge-domain 558 l2 vfi vpn1-85254 manual vpn id 85254 neighbor 192.18.156.71 encapsulation mpls neighbor 192.168.5.49 encapsulation mpls neighbor 192.169.105.65 encapsulation mpls vlan 558 exit interface GigabitEthernet2/2 service instance 885 ethernet description EVC-JOBID:15 encapsulation dot1q 747 bridge-domain 558 exit interface Vlan558 no ip address description EVC-JOBID:15 xconnect vfi vpn1-85254 no shutdown </pre>	<pre> interface GigabitEthernet0/1/0/12.552 l2transport description EVC-JOBID:15 encapsulation dot1q 552 no shutdown l2vpn bridge group Customer1 bridge-domain ISC-vpn1-85254 interface GigabitEthernet0/1/0/12.552 split-horizon group vfi vpn1-85254 neighbor 171.16.150.47 pw-id 85254 neighbor 192.18.156.71 pw-id 85254 </pre>
isc-asr903 (HUB_root)	isc-cl-test-me3800x-1 (HUB_leaf)
<pre> bridge-domain 669 exit l2 vfi vpn1-85254 manual vpn id 85254 bridge-domain 669 neighbor 171.16.150.47 encapsulation mpls neighbor 192.168.5.49 encapsulation mpls neighbor 192.169.105.65 encapsulation mpls interface GigabitEthernet0/0/3 service instance 996 ethernet description EVC-JOBID:15 encapsulation dot1q 369 bridge-domain 669 exit </pre>	<pre> bridge-domain 550 exit l2 vfi vpn1-85254 manual vpn id 85254 neighbor 171.16.150.47 9632 encapsulation mpls no-split-horizon neighbor 192.18.156.71 9632 encapsulation mpls no-split-horizon vlan 550 exit interface GigabitEthernet0/14 switchport mode trunk switchport trunk allowed vlan none service instance 554 ethernet description EVC-JOBID:15 encapsulation dot </pre>

Supporting SONET to SONET Provisioning

From this release, Prime Provisioning extended SONET–SONET provision support for EVC TDM-CEM services which will allow users to select **SONET** as a controller at A-End and Z-End. Prior to this release users were able to select SONET as a controller only at Z-End. In accordance with this functionality for CEM Container Type, a new value **SONET** controller has been introduced in both Policy editor screen and Service Request editor screen to provision SONET to SONET connectivity.

Supported Attributes are, when Framing Type is SDH:

- tug-3 Number: (ranges: 1-3)
- tug-2 Number: (ranges: 1-7)
- e1-Number: (ranges: 1-3)
- Time Slots: (1, 10-20, 24), (ranges: 1-31)

When Framing Type is SONET:

- sts-Number: (ranges: 1-3)

- VGT Number: (ranges: 1-7)
- T1 line-Number: (ranges: 1-4)
- Time Slots: (1, 10-20, 24), (ranges: 1-24)

These attributes are available in SR Link attribute at SR level.

Below are the sample configlets.

Example 1: Service Options: **SATop_UNFRAMED**, CEM Container Type: **SONET** and Framing Type: **SONET**

isc-asr903b (A Terminal)	isc-cl-test-l2-7600-6 (Z Terminal)
<pre>Configlet #4, Job ID 81 (Created: 2016-11-11 02:55:04) controller SONET 0/2/1 sts-1 2 mode vt-15 vtg 7 t1 3 cem-group 201 unframed interface CEM0/2/1 cem 201 xconnect 192.168.5.49 453 encapsulation mpls</pre>	<pre>Configlet #3, Job ID 81 (Created: 2016-11-11 02:57:56) controller SONET 3/0/0 sts-1 2 vtg 6 t1 3 cem-group 908 unframed interface CEM3/0/0 cem 908 xconnect 1.1.78.79 453 encapsulation mpls</pre>

Example 2: Service Options: **CESoPN_TIMESLOT**, CEM Container Type: **SONET** and Framing Type: **SDH**

isc-asr903b _A Terminal	ems7606c _Z Terminal
<pre>Configlet #1, Job ID 35 (Created: 2016-11-09 04:53:26) controller SONET 0/2/2 au-4 1 tug-3 1 tug-2 1 e1 1 cem-group 342 timeslots 10 interface CEM0/2/2 cem 342 xconnect 20.10.10.100 5667 encapsulation mpls</pre>	<pre>Configlet #1, Job ID 35 (Created: 2016-11-09 04:53:26) controller SONET 3/3/0 au-4 1 tug-3 1 tug-2 1 e1 1 cem-group 1 timeslots 10 interface CEM3/3/0 cem 1 xconnect 1.1.78.79 5667 encapsulation mpls</pre>

API New Features

All Application Programming Interface (API) features are explained in detail in the [Cisco Prime Provisioning API Programmer Guide 7.0](#) and the accompanying [Cisco Prime Provisioning API Programmer Reference 7.0](#).

New features added in Prime Provisioning are generally available via both the GUI and APIs. See the respective sections in this document for a description of new features under each service.

Features Introduced in Prime Provisioning 6.8.2

General Features

This section summarizes the general feature that were added in Prime Provisioning 6.8.2.

initdb Script Enhancements to Retain DCPL Values with Configured Values

During Prime Provisioning upgrade, to retain the Dynamic Component Properties Library (DCPL) property values without a reset, use the following CLI commands:

```
./prime.sh stop
./prime.sh startdb
./prime.sh initdb.sh noreset
./prime.sh start
```

The values are retained or updated in the Prime Provisioning repository based on the following criteria.

1. When the *initdb.sh* script is run without any argument, Prime Provisioning reads the DCPL properties from *vpnsd.properties* and updates them in the Prime Provisioning repository.
2. When the *initdb.sh* script is run with *noreset* argument, Prime Provisioning retains the DCPL values which are already configured.
3. When the *initdb.sh* script is run with some irrelevant argument other than the *noreset* argument, Prime Provisioning will display an error message; “The only supported argument for *initdb.sh* is *noreset*.”

L3 Features

Supporting Manual Allocation of IPv6 Address from IPv6 Address Pool

From this release, you can enter an IPv6 address manually in the IP Address Scheme window of Cisco Prime Provisioning (CPP) while creating an MPLS service request. The IPv6 address entered must be available in the IPv6 address pools. If the IPv6 address belongs to a valid IPv6 block, then the IPv6 address is blocked as allocated and is updated in the respective IPv6 pool. The IPv6 address pool is then split as valid IPv6 address blocks or pools.

While entering the IPv6 address, ensure that you remember the following conditions:

1. The subnet mask that you enter should be same as that of the IPv6 pool mask.
2. The IPv6 address mask of the Provider Edge (PE) interface and the Customer Edge (CE) interface must be under the same subnet mask as that of the IPv6 address pool.

Once the allocation is successful, you can view the valid IPv6 address pools with Allocated status in the Resource Pools window of CPP.

To remove the MPLS service request, you need to release the IPv6 address back to the available pool. The pools that are split as blocks are combined again into a single pool. For this, you can either decommission the service or perform force delete of the IPv6 allocated block or pool.

Extending VLAN-ID Range to Support BVI Interfaces with Values Range

Prime Provisioning 6.8.2 release allows you to create MPLS SR with VLAN-ID that ranges between 1-65535 for L3VPN/MPLS services on ASR9K series devices, only when the **EVC Service** is enabled.



Note This functionality supports only PE devices of IOS-XR type.

When you enable the **EVC Service** checkbox in the **MPLS Service Request Editor** page, the VLAN-ID value is automatically updated/changed to support VLAN-ID ranges of 1-65535.

It is recommended to enter the VLAN-ID ranges within the specified range otherwise, an exemption occurs in the following instances:

- On clicking **Next**, an invalid VLAN-ID error message is displayed when the value entered is greater than 65535.
- If the selected device is IOS and the given VLAN-ID value is more than 4094 an error message is displayed.



Note Enabling EVC service on L3VPN creates BVI virtual interfaces to allow routing through BVI interfaces. BVI interfaces can be configured in the range of 1-65535. This is because Prime Provisioning does not have an option to provide BVI interface and thus uses the VLAN-ID value as BVI interface value. The extended value of 1-65535 specified in the **VLAN-ID** range field allows you to create BVI interface with BVI interface number range 1-65535.

Supporting EVPN-VPWS Attributes through a Customization XML File

From this release, EVPN-VPWS configurations are supported by importing a EVPN-VPWS customization.xar file as part of Prime Provisioning policies and service requests to manage various Ethernet Virtual Circuit services.

Before you Begin

To view or edit the EVPN-VPWS attributes in the **Policy Editor** window or the **EVC Service Request Editor** window, make sure that you have completed the following prerequisite.

1. Import the **EVPNVPWSCustomization.xar** file under \$PRIMEP_HOME/packages/std, which is already copied as part of Prime Provisioning product (PP6.8.2 or greater). The customization XML uses merge mode as “Combine”. For more information about how to Import customization files, see [Importing and Exporting Customizations](#) section in the Cisco Prime Provisioning 6.8 User Guide.



Note The EVPN-VPWS attributes are visible in the **Policy Editor** or the **EVC Service Request Editor** window only when you import the **EVPNVPWSCustomization.xar** file.

2. Make sure that the supported platform includes ASR9K with IOS-XR version 6.0 or later.

Enter or Modify EVPN-VPWS Attributes

To enter the EVPN-VPWS Attributes:

1. Create an EVC PW policy and import the “EVPNVPWSCustomization.xml”. Below is a configuration sample:

```
interface GigabitEthernet0/1/0/13.315 12transport
```

```

description EVC-JOBID:53
encapsulation dot1q 315
no shutdown
l2vpn
xconnect group ISC
  p2p ELINE888
    interface GigabitEthernet0/1/0/13.315
      neighbor evpn evi 4341 target 64123 source 64222

```

2. In the **Policy Editor** window, in the **Source ac-id** field, enter the range between 1 and 16777215.
3. In the **Remote ac-id** field, enter the range between 1 and 16777215.
4. Click **Finish** to save the EVC Policy.

**Note**

You can also create an SR (VPWS) using this policy with XR devices and enter the values for the attributes.

Supporting EVPN-VPLS Attributes through a Customization XML File

From this release, EVPN-VPLS configurations are supported by importing a EVPN-VPLS customization.xar file as part of Prime Provisioning policies and service requests to manage various Ethernet Virtual Circuit services.

Before you Begin

To view or edit the EVPN-VPLS attributes in the **Policy Editor** window or the **EVC Service Request Editor** window, make sure that you have completed the following prerequisite.

1. Import the **EVPNVPLSCustomization.xar** file under \$PRIMEP_HOME/packages/std, which is already copied as part of Prime Provisioning product (PP6.8.2 or greater). The customization XML uses merge mode as “Combine”. For more information about how to Import customization files, see [Importing and Exporting Customizations](#) section in the Cisco Prime Provisioning 6.8 User Guide.

**Note**

The EVPN-VPLS attributes are visible in the **Policy Editor** or the **EVC Service Request Editor** window only when you import the **EVPNVPLSCustomization.xar** file.

2. Make sure that the supported platform includes ASR9K with IOS-XR version 6.0 or later.
3. Before configuring the EVPN-VPLS, configure BGP with new EVPN Address family as in the sample configuration below:

```

router bgp 64
  bgp router-id 1.100.100.100
  address-family l2vpn evpn
  !
  neighbor 2.100.100.100
    remote-as 64
    update-source Loopback0
  address-family l2vpn evpn

```

Enable or Modify EVPN-VPLS Attributes

To enter the EVPN-VPLS Attributes:

1. Create an EVC VPLS policy and import the “EVPNVPLSCustomization.xml”. Below is a configuration sample:

```
interface GigabitEthernet0/1/0/17.2017 l2transport
  description EVC-JOBID:216
  encapsulation dot1q 2017
  no shutdown
l2vpn
  bridge group BGNevpn1
  bridge-domain BDNevpn1
  mtu 345
  interface GigabitEthernet0/1/0/17.2017
  vfi wppq
  evi 2001
evpn
  evi 2001
  load-balancing flow-label static
-----
evpn
  evi 2001
  advertise-mac
-----
evpn
  evi 2001
  unknown-unicast-suppress
-----
evpn
  evi 2001
  control-word-disable
-----
evpn
  evi 2001
  bgp
  route-target import 200:101
  route-target export 200:101
```

2. In the **Policy Editor** window, the following EVPN-EVI attributes are added.

Field	Description
Load Balancing	To provision the EVPN load balancing command and to view the load balancing policy name in the Service Request Manager, check the Load Balancing check box.
Enable Advertise Mac	To provision advertise Mac command, check the Enable Advertise Mac check box.
Unknown Unicast Supress	To provision the Unknown unicast supress command, check the Unknown Unicast Supress check box.
Control Word Disable	To provision the control word disable command, check the Control Word Disable check box.
Enable BGP	To provision the BGP command, check the Enable BGP check box.

Field	Description
Route Target Import	Enter the format for Route Target Import . For example: 1234:5678([0-9]:[0-9])
Route Target Export	Provide the format for Route Target Export . For example: 1234:5678([0-9]:[0-9])

**Note**

You can also create an SR (VPLS) using this policy with XR devices and enter the values for the required attributes.

Features Introduced in Prime Provisioning 7.0

This release contains the following new and enhancements feature under different service blades and infrastructure.

All the new features introduced in Prime Provisioning 6.8.1, Prime Provisioning 6.8.2 and Prime Provisioning 7.1 release are explained in [Prime Provisioning User Guide 7.0](#).

L2 EVC Features

This section summarizes features that were added to enhance EVC services in Prime Provisioning 7.1.

Supporting Pseudowire Interface for EVC-Pseudowire Policies

From this release, Prime Provisioning supports new CLI that define pseudowire interface and cross connect between the service instance to the Pseudowire interface.

In new XE versions you can use both, old and new CLIs and support is provided only for ASR920 devices and applicable only for EVC-Pseudowire policies.

ASR920 supports only flex in Prime Provisioning and this feature is applicable only for flex services.

You can create an EVC Service Request (SR) with Use Pseudowire Interface feature for ASR 920 devices. If the selected device is other than ASR 920 devices, and when you try to create an EVC SR by enabling Use Pseudowire Interface, Prime Provisioning will report an error message.

For more information, see the section in the Prime Provisioning 7.0 User Guide.

**Note**

Prime Provisioning does not support enabling the following attributes together at a time:
 “Use Pseudowire Interface’ and ‘Configure Bridge Domain’
 “Use Pseudowire Interface” and “Use Pseudowire Class”
 Also, the minimum allowed direct link should be 2.

Supporting Autopick Bridge Domain Name for L2 Services

Prime Provisioning supports L2 services with Autopick Bridge Domain Name with new format L2-X.

Create L2 services with autopick bridge domain name, with the format of L2-X, where X will be the range between 1 to 60000 for the newly created service request. For example, "bridge-domain L2-40001".

As soon as the starting range value is set through the DCPL property as (Provisioning\Service\ fsm\bridgeDomainName) for the first service request, Prime Provisioning will consider the set value as a starting range value for autopick bridge domain name automatically, and for the next service request onwards the value is incremented with +1.

If the default value for bridgeDomainName property is zero, the existing behavior will not change.

L3VPN/MPLS Services Features

This section summarizes features that were added to enhance L3VPN/MPLS services in Prime Provisioning 7.1

Supporting BGP Additional Multipaths for ASR920 Devices

Prime Provisioning allows you to create MPLS services with BGP additional path configuration CLI for Install or Select backup.

Supporting IP Helper Addresses for ASR 920 Devices

You can provide DHCP Helper IP parameters for ASR920 devices, while creating MPLS service requests for the selected PE interface type you can view the IP helper address details of a server, VRF, GRT, MTU in CLI under the interface node.

In the MPLS Service Request Editor-Interface area, check the **Use EVC Service** check box to enable the following DHCP Helper IP fields:

- **DHCP Helper Server IP (a.b.c.d)**
- **DHCP Helper GRT IP (a.b.c.d)**
- **DHCP Helper VRF IP (a.b.c.d)**
- **MTU (68 - 9216)**

Supporting Auto RD Configuration

Create, modify, and decommission MPLS Service Request with auto RD Value for ASR9k devices. Prime Provisioning notifies an error if the selected device is IOS and the specified Rd value is "auto" while creating a MPLS Service request.

Supporting Modification of Site of Origin

From this release, you can edit Site Of Origin pool while editing a customer site, You can edit SOO pool with available pool values or with other than pool value, if required.

Features Introduced in Prime Provisioning 7.1

This release contains the following new and enhancements feature under different service blades and infrastructure.

All the new features introduced in Prime Provisioning 6.8.2, Prime Provisioning 7.0 and Prime Provisioning 7.1 release are explained in [Prime Provisioning User Guide 7.1](#).

L2 EVC Features

This section summarizes features that were added to enhance EVC services in Prime Provisioning 7.1.

Supporting Pseudowire Interface for EVC-Pseudowire Policies

From this release, Prime Provisioning supports new CLI that define pseudowire interface and cross connect between the service instance to the Pseudowire interface.

In new XE versions you can use both, old and new CLIs and support is provided only for ASR902 and ASR 903 devices and applicable only for EVC-Pseudowire policies.

ASR902 and ASR 903 supports only flex in Prime Provisioning and this feature is applicable only for flex services.

You can create an EVC Service Request (SR) with Use Pseudowire Interface feature for ASR 902 and ASR 903 devices. If the selected device is other than ASR 902 and ASR 903 devices, and when you try to create an EVC SR by enabling Use Pseudowire Interface, Prime Provisioning will report an error message.

For more information, see the section in the Prime Provisioning 7.1 User Guide.



Note

Prime Provisioning does not support enabling the following attributes together at a time:
 “Use Pseudowire Interface’ and ‘Configure Bridge Domain’
 “Use Pseudowire Interface” and “Use Pseudowire Class”
 Also, the minimum allowed direct link should be 2.

Supporting Bridge Group in L2 EVC Services in VFI Management

From Prime Provisioning 7.1, auto pick bridge group shows “bridge group <VFI-NAME>” for local core types, when DCPL property (Provisioning\Service\mpls\bridgeDomainName) is 'true' and Autopick bridgeGroupName is checked.

L3VPN/MPLS Services Features

This section summarizes features that were added to enhance L3VPN/MPLS services in Prime Provisioning 7.1.

Supporting BGP Additional Multipaths for ASR902 and ASR 903 Devices

Prime Provisioning allows you to create MPLS services with BGP additional path configuration CLI for Install or Select backup.

Supporting IP Helper Addresses for ASR 902 and ASR 903 Devices

You can provide DHCP Helper IP parameters for ASR902 and ASR 903 devices, while creating MPLS service requests for the selected PE interface type you can view the IP helper address details of a server, VRF, GRT, MTU in CLI under the interface node.

Supporting Autopick Bridge Domain Name for L3 Services

Prime Provisioning supports L3 services with Autopick Bridge Domain Name with new format L3-X.

Create L3 services with autopick bridge domain name, with the format of L3-X, where X will be the range between 1 to 60000 for the newly created service request. For example, "bridge-domain L3-40001".

As soon as the starting range value is set through the DCPL property as (Provisioning\Service\mpls\bridgeDomainName) for the first service request, Prime Provisioning will consider the set value as a starting range value for autopick bridge domain name automatically, and for the next service request onwards the value is incremented with +1.

If the default value for bridgeDomainName property is zero, the existing behavior will not change..

EFP-Trunk Support

Trunk EFP supports ASR902 and ASR903 IOS devices in Prime Provisioning.

Device Picker Filter Option for Hub and Backup Hub

Prime Provisioning supports device filter option for HUB & BACKUP HUB device picker for HVPLS and ETree policy services. If you want to select Hub devices:

- In the EVC Service Request Editor window, in the Direct Connect Links area, Click **Add** to Select **Device** and **UNI**.
- Check the **Edit** check box, and then choose the SPOKE option. The Hub and Backup Hub Device Selection window appears. You can use toggle picker and choose the Hub device names using the quick filters in the **Device Selection** window.

Supporting Bridge Group in L3 EVC Services in VFI Management

From Prime Provisioning 7.1, auto pick BG takes VRF name instead of provider name (for example, bridge group VRFtest1), when auto pick bridge group name is checked and DCPL property (Provisioning\Service\mpls\bridgeGroupName) is set to 'true'. If VRF name contains special character(. , : , <Space>) you can replace with "_" in the VRF user name.

Supporting Bundle Interface

Bundle interface is supported for IOS-XR devices. When you create a MPLS SR using bundle interface, a new CLI, ' bundle load-balancing hash auto' is generated in the configlets.

Web Browser Support

- Prime Provisioning 7.1 GUI is supported by the following browsers:
 - Internet Explorer 9, 10, and 11.
 - Firefox browser standard version 30, 31, 37 and 55.
 - Firefox browser version ESR 24, 31, 52.

Version Supported

You can install Prime Provisioning 7.1 on Prime Provisioning 6.8.1.5/6.8.2.3/7.0.0.1. Schema upgrade is supported from 6.8.1.2, 6.8.2, 7.0 to 7.1 migration can only be performed from 6.8.1.2, 6.8.2, 7.0. To migrate from earlier releases (prior to 6.8), you must first upgrade to Prime Provisioning 6.8.1.5/6.8.2.3/7.0.0.1 release. See [“Upgrading Prime Provisioning” section on page 17](#) .

The procedure for upgrading from earlier releases is documented in the [Cisco Prime Provisioning Installation Guide 7.1](#).

The Linux platform supported by Prime Provisioning includes: Red Hat Enterprise Linux, 64 bit, version 6.7, 6.8, 6.9, 7.0, 7.1 and 7.4. End of support by Redhat version 6.5 and 7.2.

Device Supported

In Prime Provisioning 7.1, IOS-XR 6.4.1-SDR on NCS6K platform certification is supported.

Upgrading Prime Provisioning

If you want to migrate from an existing installation to Prime Provisioning 7.1, your upgrade path depends on which release you are upgrading from. This process is explained in detail in Chapter 4, “Upgrading Prime Provisioning” of the [Cisco Prime Provisioning Installation Guide 7.1](#).

Upgrade Matrix

The various possible upgrade paths are described in [Table 1](#).

Table 1 *Upgrade Path to Prime Provisioning 7.1*

Current Prime Provisioning Version	Procedure	Steps to Upgrade to Prime Provisioning 7.0 (run in order stated)	Supported Oracle Database	Supported OS
<ul style="list-style-type: none"> • 6.8.1.5 • 6.8.2.3 • 7.0.0.1 	Direct	<Prime Provisioning installation directory>/upgradeTool	Enterprise Oracle 12C	Linux (Red Hat)
<ul style="list-style-type: none"> • 6.8 	Upgrade to 6.8.2.3 and then to 7.1	<Prime Provisioning installation directory>/upgradeTool	Enterprise Oracle 12C	Linux (Red Hat)

Table 1 Upgrade Path to Prime Provisioning 7.1

Current Prime Provisioning Version	Procedure	Steps to Upgrade to Prime Provisioning 7.0 (run in order stated)	Supported Oracle Database	Supported OS
<ul style="list-style-type: none"> 6.6 	Upgrade to 6.6.1.8 and then to 6.8.2.3 and then follow steps to upgrade to 7.1	<Prime Provisioning installation directory>/upgradeTool	Enterprise Oracle 12C	Linux (Red Hat)
<ul style="list-style-type: none"> 6.5 	Upgrade to 6.5.0.9 and then to 6.7.1, then to 6.8.2.3 and then follow steps to upgrade to 7.1	<Prime Provisioning installation directory>/upgradeTool	Enterprise Oracle 12C	Linux (Red Hat)
<ul style="list-style-type: none"> Prior to 4.2.5 		E-mail isc-mktg@cisco.com for upgrade instructions	Enterprise Oracle 12C	Linux (Red Hat)

Prime Provisioning 7.1 Resolved and Open Bugs

Resolved Bugs

The following bugs were resolved in Prime Provisioning 7.1:

Bug	Description
CSCvm17573	Modify of Inner vlan value to autopick on deployed SR throws Inner VLAN ID can't be null
CSCvm15575	Unable to create customer or policy in upgraded server
CSCvm10562	pp-pc integration:After pp-pc integration,httpd process is not starting
CSCvk43016	Not able to uncheck 'Use Pseudowire Interface' in SR page
CSCvk33705	Getting wrong validation error when enable 'UsePseudowireClass' with asr920
CSCvk23282	PP releasing the allocated outer vlan from the pool whenever editing any other parameters in the SR
CSCvk20477	Unable to start db after 7.1 upgrade from 6.8.1.4
CSCvk10166	Preview configlets throw error on HVPLS modify scenarios (true DCPL Propert autopick bname)
CSCvk05669	Decommission on VPLS successfully deployed SR goes to invalid state and not decommissioned(true)
CSCvk05643	Preview decommission of VPLS by setting DCPL property as true for bridgeGroupName throws error
CSCvk05577	Decommission on VPLS successfully deployed SR goes to invalid state and not decommissioned properly

Bug	Description
CSCvk05485	Preview decommission on VPLS SR with BGname DCPL property false throws error
CSCvk03387	Version details need to be modified in Suite Sybase 7.1 Server
CSCvj97143	Mpls Sr without Evc:'load balancing ..' cmd not generated when bundle intf is used.
CSCvj83243	Apache Batik AbstractDocument Information Disclosure Vulnerability
CSCvj66378	Unnecessary device gets populated in preview configlets of HVPLS Etree non flex feature
CSCvj58164	SQL Exception null error thrown while saving the DHR HVPLS SR
CSCvj53134	MPLS SR with Asr9k: pp accepts vlan Id higher than allowed value(4094)
CSCvj49209	cerc creation using NBI:PP accepts cerc with names duplicated.
CSCvj37357	Decommission on H-VPLS successfully deployed SR goes to invalid state and not decommissioned properly
CSCvj37331	Pseudowire class is not showing proper configlets and deployed properly
CSCvj37294	Modification of deployed Pseudowire SRs with Outer VLAN values are not giving proper configlets
CSCvj37266	Preview Decommission is not showing proper configlets on EFP Trunk support on ASR902 and 903 devices
CSCvj37165	Mpls Sr:Outer Vlan is not released back to pool after Sr decommission
CSCvj37164	Preview Configlets should give proper configuration details for VFI management for BG in L2 EVC
CSCvi97446	PP generated wrong preview configlets when asr903 is used in A end.

Open Bugs

The following open bugs apply to Prime Provisioning 7.1.

Bug	Description
CSCvm04698	Apache CXF Vulnerability issues
CSCvj37549	Decommission of EVC_HVPLS/VPLS DHR ends in throwing SQL command not ended properly error message
CSCvj37279	After disabling "BGP Multipath Load sharing" in PP its negating and Reconfiguring IP Helper Address
CSCvj37148	PP should truncate trailing zeroes for flag 'bridgeDomainName'
CSCvj37118	MPLS with BD-autopick:PP should throw error when special symbol(Full point) is given as BD name
CSCvk64380	Decommission of deployed PW_DHR with DCPL true throw "Sql command not Properly Ended" java exception

Finding Known Problems in Prime Provisioning 7.1

To find known problems in Prime Provisioning 7.1, use the following URL:

<https://tools.cisco.com/bugsearch/search>

You must log into Cisco.com.

You can search for specific bugs or search for a range by product name. This tool enables you to query for keywords, severity, range, or version.

Use the following search criteria to locate bugs for Prime Provisioning 7.1:

- Product category: **Cloud and Systems Management > Routing and Switching Management > Fulfillment Products.**
- Product: **Cisco Prime Provisioning (6.3 to 7.1).**

The results display bug ID and title, found-in version, fixed-in version, and status. The bug ID is a hyper link to detailed information for the bug ID's product, component, severity, first found-in, and release notes. The results could be displayed in a feature matrix or spreadsheet.

Related Documentation

See the [Cisco Prime Provisioning 7.1 Documentation Overview](#) for a list of all Prime Provisioning guides.

We sometimes update the documentation after original publication. Therefore, you should also review the documentation on Cisco.com for any updates.

Other Cisco Prime Product Documentation

If you are deploying Prime Provisioning as part of the Prime Carrier Management suite, then see also the documentation for the other suite components:

- [Cisco Prime Central 2.0](#)
- [Cisco Prime Network 5.1](#)
- [Cisco Prime Optical 10.7](#)
- [Cisco Prime Performance Manager 1.7](#)

Accessibility Features in Prime Provisioning

For a list of accessibility features in Prime Provisioning, visit Cisco's [Voluntary Product Accessibility Template \(VPAT\)](#) website, or contact accessibility@cisco.com.

- All product documents are accessible except for images, graphics and some charts. If you would like to receive the product documentation in audio format, braille, or large print, contact accessibility@cisco.com.

Obtaining Documentation and Submitting a Service Request

For information on obtaining documentation, using the Cisco Bug Search Tool (BST), submitting a service request, and gathering additional information, see [What's New in Cisco Product Documentation](#).

To receive new and revised Cisco technical content directly to your desktop, you can subscribe to the [What's New in Cisco Product Documentation RSS feed](#). The RSS feeds are a free service.

Cisco and the Cisco logo are trademarks or registered trademarks of Cisco and/or its affiliates in the U.S. and other countries. To view a list of Cisco trademarks, go to this URL: www.cisco.com/go/trademarks. Third-party trademarks mentioned are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (1721R)

Any Internet Protocol (IP) addresses and phone numbers used in this document are not intended to be actual addresses and phone numbers. Any examples, command display output, network topology diagrams, and other figures included in the document are shown for illustrative purposes only. Any use of actual IP addresses or phone numbers in illustrative content is unintentional and coincidental.

©2018 Cisco Systems, Inc. All rights reserved.

Printed in the USA on recycled paper containing 10% postconsumer waste.