



## Caveats

This chapter describes open and resolved severity 1 and 2 caveats and select severity 3 caveats:

- The “Open Caveats” sections list open caveats that apply to the current release and may apply to previous releases. A caveat that is open for a prior release and is still unresolved applies to all future releases until it is resolved.
- The “Resolved Caveats” sections list caveats resolved in a specific release, but open in previous releases.

The bug IDs are sorted alphanumerically.



**Note** The Caveats section includes the bug ID and a short description of the bug. For details on the symptoms, conditions, and workaround for a specific caveat you must use the Bug Search Tool.

- [Resolved Caveats - Cisco IOS XE Dublin 17.10.1, on page 1](#)
- [Resolved Caveats - Cisco IOS XE Dublin 17.10.1 - Platform Independent, on page 2](#)
- [Open Caveats - Cisco IOS XE Dublin 17.10.1, on page 2](#)
- [Open Caveats - Cisco IOS XE Dublin 17.10.1 - Platform Independent, on page 2](#)
- [Cisco Bug Search Tool, on page 2](#)

## Resolved Caveats - Cisco IOS XE Dublin 17.10.1

Identifier	Headline
<a href="#">CSCwb82994</a>	RSTP loop can be noticed when the router becomes alive
<a href="#">CSCwc41135</a>	Continuous assertion and clear of LAIS on protect channel causing IPC failure
<a href="#">CSCwb55575</a>	TPOP: enabling RTP is not inserting RTP header in TPOP until DCR is configured
<a href="#">CSCwb78907</a>	DS3_RX_RAI is shown in both facility-alarm and facility-condition status cli
<a href="#">CSCwb76150</a>	STS1e ⇒ vt-15 ⇒ Difference in ifName string format for controller up/down syslog messages
<a href="#">CSCwb60002</a>	Router may experience an unexpected reset when configuring or using interface BDI >= 4097

Identifier	Headline
<a href="#">CSCwb90111</a>	APS-ACR config/unconfig results in traffic drop
<a href="#">CSCwb69025</a>	Change in SD-BER threshold value to 10e-9 causes SD alarm assertion
<a href="#">CSCwc53354</a>	Alarm assertion/clearing not happening for port x+1 when complete sonet config for port x is removed
<a href="#">CSCwb65890</a>	A900-IMA1Z8S-CXMS MLPPP: Fake AIS alarm is seen on controller during channel group config
<a href="#">CSCwc25182</a>	Synchronization Status Messaging (S1) Processing and Generation issue

## Resolved Caveats - Cisco IOS XE Dublin 17.10.1 - Platform Independent

There are no platform independent resolved caveats for this release.

## Open Caveats - Cisco IOS XE Dublin 17.10.1

Identifier	Headline
<a href="#">CSCwd28107</a>	RSP3: Bundle rommon version 15.6(57r)S to polaris_dev
<a href="#">CSCwc77502</a>	Unexpected router reload due to MLDPv6
<a href="#">CSCwc93296</a>	Port Te0/0/10 went admin down after successive reloads
<a href="#">CSCwd05362</a>	Performance issue on ASR900 platform
<a href="#">CSCwc65971</a>	RSP3: MPLS pseudowirte - Incorrect label stack pushed to packet

## Open Caveats - Cisco IOS XE Dublin 17.10.1 - Platform Independent

There are no platform independent open caveats for this release.

## Cisco Bug Search Tool

[Cisco Bug Search Tool](#) (BST), the online successor to Bug Toolkit, is designed to improve effectiveness in network risk management and device troubleshooting. You can search for bugs based on product, release, and keyword, and aggregates key data such as bug details, product, and version. For more details on the tool, see the help page located at <http://www.cisco.com/web/applicat/cbsshhelp/help.html>