



Release Notes for IoT Field Network Director, Release 3.1.x

First Published: September 23, 2016

This release note contains the latest information about using Release 3.1 user interface for the IoT Field Network Director (IoT FND), IPv6 mesh endpoints, Cisco 1000 Series Connected Grid Routers (CGR 1000 or CGR), Cisco 800 Series Integrated Services Routers (C800s), Cisco 500 Series WPAN Industrial Routers (IR 500), and Cisco 800 Series Industrial Integrated Services Routers (IR809 and IR829).

Note: IoT FND was previously named Connected Grid Network Management System (CG-NMS) for releases 2.x and 1.x.

Organization

This guide includes the following sections:

Conventions	Conventions used in this document.
New Features	New features in Release 3.1.
IoT FND Licenses	Summary of supported licenses for Release 3.1.
About Cisco IoT FND	Description of the IoT FND application.
System Requirements	System requirements for Release 3.1.
Installation Notes	Procedures for downloading software.
Important Notes	Notes about Release 3.1.
Limitations and Restrictions	Known limitations in IoT FND.
Caveats	Open and resolved caveats in Release 3.1.
Related Documentation	Links to the documentation associated with this release.

Conventions

This document uses the following conventions.

Conventions	Indication
bold font	Commands and keywords and user-entered text appear in bold font .
<i>italic font</i>	Document titles, new or emphasized terms, and arguments for which you supply values are in <i>italic font</i> .
[]	Elements in square brackets are optional.
{x y z }	Required alternative keywords are grouped in braces and separated by vertical bars.
[x y z]	Optional alternative keywords are grouped in brackets and separated by vertical bars.

New Features

Conventions	Indication
string	A nonquoted set of characters. Do not use quotation marks around the string or the string will include the quotation marks.
courier font	Terminal sessions and information the system displays appear in courier font.
< >	Nonprinting characters such as passwords are in angle brackets.
[]	Default responses to system prompts are in square brackets.
!, #	An exclamation point (!) or a pound sign (#) at the beginning of a line of code indicates a comment line.

Note: Means *reader take note*. Notes contain helpful suggestions or references to material not covered in the manual.

Caution: Means *reader be careful*. In this situation, you might perform an action that could result in equipment damage or loss of data.

Warning: IMPORTANT SAFETY INSTRUCTIONS

Means danger. You are in a situation that could cause bodily injury. Before you work on any equipment, be aware of the hazards involved with electrical circuitry and be familiar with standard practices for preventing accidents. Use the statement number provided at the end of each warning to locate its translation in the translated safety warnings that accompanied this device.

SAVE THESE INSTRUCTIONS

New Features

Table 1 lists new features that are in IoT FND 3.1.x.

New Features

Table 1 New Features in IoT FND 3.1

Feature	Description	First released	Related Documentation
LoRaWAN Interface Module Management	The LoRaWAN interface module extends connectivity of Cisco 809 and 829 Industrial Integrated Services Routers to include low-power wide-area (LPWA) access. Information on the module can be found on the following pages: Field Devices, Modem list for IR800 (IR809/IR829), Field Devices, Firmware Image Update Page, Events and Issues.	3.1.0-131	For more information, see <i>Cisco IoT Field Network Director User Guide, Release 3.1.x</i> at: http://www.cisco.com/go/fnd
IR509: DSCP and Raw Socket Support	At the Config > Firmware Update page for Endpoints, you can use the configuration template to apply DSCP and Raw Socket settings to the IR509 Industrial Router	3.1.0-131	
Tunnel Status Search for Head-end Routers and Field Area Routers	At the Operations > Tunnel Status page, you can search for the following parameters: Router name, Router interface, Admin Status, Operational Status, IP, and Protocol (IPSec, PIM, GRE). A wild card search in the value field is also supported.	3.1.0-131	
Zero Touch Discovery (ZTD) with no IPSec	You no longer need to configure IPSec Tunnel Provisioning between FARs and HERs prior to deployment of the FAR in your network. Instead you can initiate ZTD with no IPSec configured by ensuring that the Tunnel Provisioning Template is empty of any CLI. This approach of bringing up your network without a factory configuration, does not preclude subsequent use of IPSec in your network.	3.1.0-131	
Label search for Events	At the Operations > Events page, you can search and filter events based on Label names tagged to Field Devices.	3.1.0-131	
Certificate Expiration Events and Issues	Creates an event and an issue when a router's certificate is about to a) expire or b) has expired.	3.1.0-131	
WPAN Image Upgrades independent of the IOS Image (IOS-CGR)	At the Config > Firmware Update page, you can upload the independent WPAN images (IOS-WPAN-RF or IOS-WPAN-PLC) to IoT FND using the Images sub-tab (left-hand side) and Upload Image button like other image upgrades. This process is known as a non-integrated WPAN firmware upgrade. The WPAN firmware image integrated with the IOS CGR image option is still supported. Also, if only the WPAN firmware upgrade from the image bundled with IOS image is desired (for example, when the WPAN firmware upgrade option was not checked during IOS upgrade), the "Install from Router" option is also provided under respective WPAN image types (IOS-WPAN-RF or IOS-WPAN-PLC).	3.1.0-131	

IoT FND Licenses

Table 1 New Features in IoT FND 3.1 (continued)

Feature	Description	First released	Related Documentation
Firmware Update Restart Retains Previous State for Endpoint Devices	At the Config > Firmware Update page, when you upload a new firmware image to devices, the system retains the previous state for those devices and does not reinitialize the upload status to 0%.	3.1.0-131	
Excluding Subnets from Firmware Actions	At the Config > Firmware Update page, when you select a check box for a Pan Id (bottom of page), that subnet will be excluded from the firmware action.	3.1.0-131	
Firmware Update Progress by Subnet	At the Config > Firmware Update page, you can now view details of a subnet such as Pan ID, Subnet Prefix, Nodes in group, Total in subnet, Upload Status and Last Message sent.	3.1.0-131	
Filtering by Device	At the Config > Firmware Update page, you can sort entries (ascending/descending) and define filters for the PanId and Subnet Prefix (bottom of page) by hovering over the column name to expose an arrow, which allows you define the action.	3.1.0-131	
Java 7 to Java 8 upgrade	IoT FND 3.1 software bundle includes the required Java version, Java 8. When you upgrade your system to IoT FND 3.1 software, the upgrade from Java 7 to 8 occurs automatically.	3.1.0-131	For more information, see <i>Cisco IoT Field Network Director User Guide, Release 3.1.x</i> at: http://www.cisco.com/go/fnd

IoT FND Licenses

Table 2 provides a summary of licenses supported on IoT FND, Release 3.1.x. Contact your Cisco partner to obtain the necessary licenses.

Table 2 Summary of IoT FND Licenses

PID	License
L-IOTFND-C800	IoT FND device license for managing the Cisco 800 Series Integrated Services Routers.
L-IOTFND-CGR1K	IoT FND device license for managing CGR 1000 Series Connected Grid Routers.
L-IOTFND-IR509	IoT FND device license for managing Cisco 500 Series Wireless Personal Area Network (WPAN) Industrial Routers.
L-IOTFND-IR800	IoT FND device license for managing the IR800 Industrial Integrated Services Routers.
L-IOTFND-EP-1K	IoT FND device license for managing 1000 endpoints.
L-IOTFND-K9	IoT FND software license for bare-metal deployment (RPMs).
L-IOTFND-V-K9	IoT FND software license for virtual deployments (VMs)
L-IOTFND-LORAWAN	IoT FND software license for LoRaWAN module.

About Cisco IoT FND

The IoT Field Network Director (IoT FND) is a software platform to manage a multi-service network and security infrastructure for IoT applications such as smart grid applications including advanced metering infrastructure (AMI). IoT FND is a scalable, highly secure, modular, and open-platform with an extensible architecture. IoT FND is a multi-vendor, multi-service, communications network management platform that enables network connectivity to an open ecosystem of power grid devices.

Through the browser-based interface, utility operators manage and monitor devices in a Cisco Connected Grid Field Area Network (FAN) solution, using IPv6 over Low-power Wireless Personal Area Networks (6LoWPANs). The FAN includes the following devices:

- Cisco 1000 Series Connected Grid Routers (CGRs), also called pole-top or DIN-rail-mount routers. These devices are identified by model (for example, CGR1000, CGR1120, or CGR1240) on the Field Devices page.
- Cisco 800 Series Industrial Integrated Services Routers (IR 800s) are ruggedized small-form factor cellular routers for mobile/vehicle applications. IR829 include WiFi providing connectivity in non-carpeted IT spaces, industrials, utilities, transportation, infrastructure, industrial M2M application, asset monitoring, Smart Grid, and utility applications. These devices are referred to as FARs in this document; and identified by product ID (for example, IR800) on the Field Devices page. You can use IoT FND to manage the following IR 800 models: IR809 and IR829.
- Cisco 800 Series Integrated Services Routers (C800s) are used in most networks as edge routers or gateways to provide WAN connectivity (cellular, satellite over Ethernet, and WiFi) to an end device (energy-distribution automation devices, other verticals such as ATMs, and mobile deployments). These devices are referred to as FARs in this document and identified by product ID (for example, C800 or C819) on the Field Devices page.

You can use IoT FND to manage the following hardened Cisco 819H:

- C819HG-4G-V-K9
- C819HG-4G-A-K9
- C819HG-U-K9
- C819HGW-S-A-K9
- C819H-K9
- C819G-B-K9

About Cisco IoT FND

- C819G-U-K9
- C819G-4G-V-K9
- C819G+7-K9
- Cisco 500 Series Wireless Personal Area Network (WPAN) Industrial Routers (IR500) supply RF mesh connectivity to IPv4 and serial Internet of Things (IoT) devices (for example, recloser control, cap bank control, voltage regulator controls, and other remote terminal units).

Note: CGRs, C800s, IR800s, IR 500s and other types of mesh endpoint devices can coexist on a network, but cannot be in the same device group (see *Creating Device Groups and Working with Mesh Endpoint Firmware Images*) or firmware management group. Refer to the following sections with the *IoT Field Network Director User Guide, Release 3.0* for more information: “Creating Device Groups and Working with Mesh Endpoint Firmware Images” and “Configuring Firmware Group Settings.”

- Cisco Interface Module for LoRaWAN is an extension module for the industrial routers, Cisco IR809 and IR829, and serve as carrier-grade gateways for outdoor deployments. The module provides unlicensed low-power wide area (LPWA) wireless connectivity for a range of Internet of Things (IoT) use cases such as asset tracking, water and gas metering, street lighting, smart parking/building/agriculture and environment monitoring. There are two models supported, which are differentiated by their band support (863-870 MHz ISM or 902-928 MHz ISM). The module is identified by product ID (for example IXM-LORA-800-H-V2)
 - Cisco 800 Series Access Points are integrated access points on the Cisco 800 Series Integrated Services Routers (C800s). These access points are referred to as FARs in this document; and identified by product ID (for example, AP800).
- Note:** Both the C819 and IR829 have embedded APs and we support management of those two APs.
- Cisco ASR 1000 Series Aggregation Services Routers (ASRs) and Cisco ISR 3900 Series Integrated Service Routers (ISRs), referred to as *head-end routers* or HERs in this document.
 - Cisco IPv6 RF mesh endpoints (smart meters and range extenders).

Note: CGRs, C800s, IR800s, IR 500s and other types of mesh endpoint devices can coexist on a network, but cannot be in the same device group or firmware management group.

The software features enterprise-class fault, configuration, accounting, performance, and security (FCAPS) functionality, as defined in the OSI Network Management reference model.

Cisco IoT Features and Capabilities

- **Configuration Management** – Cisco IoT FND facilitates configuration of large numbers of Cisco CGRs, Cisco C800s, Cisco ASRs, and MEs. Use Cisco IoT FND to bulk-configure devices by placing them into configuration groups, editing settings in a configuration template, and then pushing the configuration to all devices in the group.
- **Device and Event Monitoring** – Cisco IoT FND displays easy-to-read tabular views of extensive information generated by devices, allowing you to monitor your network for errors. Cisco IoT FND provides integrated Geographic Information System (GIS) map-based visualization of FAN devices such as routers and smart meters. Use IoT FND to create CGR-specific work orders that include the required certificates to access the router.
- **Firmware Management** – Cisco IoT FND serves as a repository for Cisco CGR, Cisco C800s, Cisco IR800 (which has a different group for firmware management) and ME firmware images. Use Cisco IoT FND to upgrade the firmware running on groups of devices by loading the firmware image file onto the Cisco IoT FND server, and then uploading the image to the devices in the group. Once uploaded, use IoT FND to install the firmware image directly on the devices.
- **Zero Touch Deployment** – This ease-of-use feature automatically registers (enrolls) and distributes X.509 certificates and provisioning information over secure connections within a connected grid network.
- **Tunnel Provisioning** – Protects data exchanged between Cisco ASRs and Cisco CGRs and C800s, and prevents unauthorized access to Cisco CGRs, to provide secure communication between devices. Cisco IoT FND can execute CLI commands to provision secure tunnels between Cisco CGRs, Cisco C800s, Cisco IR800s and Cisco ASRs. Use Cisco IoT FND to bulk-configure tunnel provisioning using groups.

About Cisco IoT FND

- **IPv6 RPL Tree Polling** – The IPv6 Routing Protocol for Low-power and Lossy Networks (RPL) finds its neighbors and establishes routes using ICMPv6 message exchanges. RPL manages routes based on the relative position of the ME to the CGR that is the root of the routing tree. RPL tree polling is available through the mesh nodes and CGR periodic updates. The RPL tree represents the mesh topology, which is useful for troubleshooting. For example, the hop count information received from the RPL tree can determine the use of unicast or multicast for the firmware download process. IoT FND maintains a periodically updated snapshot of the RPL tree.
- **Dynamic Multipoint VPN and Flex VPN**– For Cisco C800 devices and Cisco IR800 devices, DMVPN and Flex VPN do not require IoT FND to apply device-specific tunnel configuration to the HER during tunnel provisioning. HER tunnel provisioning is only required for site-to-site VPN tunnels.
- **Dual PHY Support** – IoT FND can communicate with devices that support Dual PHY (RF and PLC) traffic. IoT FND identifies CGRs running Dual PHY, enables configuration to masters and slaves, and collects metrics from masters. IoT FND also manages security keys for Dual PHY CGRs. On the mesh side, IoT FND identifies Dual PHY nodes using unique hardware IDs, enables configuration pushes and firmware updates, and collects metrics, including RF and PLC traffic ratios.
- **Guest OS (GOS) Support** – For Cisco IOS CGR 1000 devices that support Guest OS, IoT FND allows approved users to manage applications running on the supported operating systems. IoT FND supports all phases of application deployment, and displays application status and the Hypervisor version running on the device.
- **Device Location Tracking** – For CGR 1000, C800, and IR800 devices, IoT FND displays real-time location and device location history.
- **Software Security Module (SSM)** – This is a low-cost alternative to the Hardware Security Module (HSM), and is used for signing CSMP messages sent to meters and IR500 devices.
- **Diagnostics and Troubleshooting** – The IoT FND rule engine infrastructure provides effective monitoring of triage-based troubleshooting. Device troubleshooting runs on-demand device path trace and ping on any CGR, Cisco C800, Cisco IR800, range extender, or meter (mesh endpoints).
- **High Availability** – To ensure uninterrupted network management and monitoring, you can deploy the Cisco IoT FND solution in a High Availability (HA) configuration. By using clusters of load-balanced IoT FND servers and primary and standby IoT FND databases, Cisco IoT FND constantly monitors the health of the system, including connectivity within clusters and server resource usage. If a server cluster member or database becomes unavailable or a tunnel fails, another takes its place seamlessly. Additionally, you can add reliability to your IoT FND solution by configuring redundant tunnels between a Cisco CGR and multiple Cisco ASRs.
- **Power Outage Notifications** – Connected Grid Endpoints (CGEs) implement a power outage notification service to support timely and efficient reporting of power outages. In the event of a power outage, CGEs perform the necessary functions to conserve energy and notify neighboring nodes of the outage. FARs relay the power outage notification to IoT FND, which then issues push notifications to customers to relate information on the outage.
- **Mesh Upgrade Support** – Over-the-air software and firmware upgrades to field devices such as Cisco CGRs and CGEs (for example, AMI meter endpoints).
- **Audit Logging** – Logs access information for user activity for audit, regulatory compliance, and Security Event and Incident Management (SEIM) integration. This simplifies management and enhances compliance by integrated monitoring, reporting, and troubleshooting capabilities.
- **North Bound APIs** – Eases integration of existing utility applications such as outage management system (OMS), meter data management (MDM), trouble-ticketing systems, and manager-of-managers.
- **Work Orders for Device Manager** – Credentialed field technicians can remotely access and update work orders.
- **Role-Based Access Controls** – Integrates with enterprise security policies and role-based access control for AMI network devices.

System Requirements

- **Event and Issue Management** – Fault event collection, filtering, and correlation for communication network monitoring. IoT FND supports a variety of fault-event mechanisms for threshold-based rule processing, custom alarm generation, and alarm event processing. Faults display on a color-coded GIS-map view for various endpoints in the utility network. This allows operator-level custom, fault-event generation, processing, and forwarding to various utility applications such as an outage management system. Automatic issue tracking is based on the events collected.

Related Products

In addition to Cisco IoT FND, you can use the following tools with the Cisco 1000 Series Connected Grid Routers:

Command Line Interface

Use the command line interface (CLI) to configure, manage, and monitor Cisco 1000 Series Connected Grid Routers. Learn more at www.cisco.com/go/cgr1000-docs

Cisco IoT Device Manager

The Cisco IoT Device Manager (IoT-DM or Device Manager) is a Windows-based application for field management of a single Cisco CGR. IoT-DM uses a local Ethernet or WiFi link to connect to the CGR. Learn more at www.cisco.com/go/cgr1000-docs

System Requirements

[Table 3](#) lists the hardware and software versions associated with this release.

Note: For a large scale system, refer to [Table 4](#) and [Table 5](#) for scale requirements.

System Requirements

Table 3 Minimum Hardware and Software Requirements for Cisco IoT FND and Supporting Systems

Component	Minimum Hardware Requirement	Minimum Software Release and Requirements
Cisco IoT FND application server (or comparable system that meets the minimum hardware and software requirements)	<ul style="list-style-type: none"> ■ Processor: <ul style="list-style-type: none"> – Intel Xeon x5680 2.27 GHz (64-bit) – 4 CPUs ■ RAM: 16 GB ■ Disk space: 100 GB ■ Hardware Security Module (HSM) or Software Security Module (SSM) 	<ul style="list-style-type: none"> ■ Red Hat Enterprise Linux 6.4 and above, 64-bit with all packages installed (software development and web server) <p>See Table 5 on page 14 for suggested application server resource allocation profiles.</p> <ul style="list-style-type: none"> ■ Internet connection <p>When you access IoT FND from a client browser, the browser connects to the Internet to download the necessary data files from the GIS maps provider.</p> <ul style="list-style-type: none"> ■ A license to use SafeNet for mesh endpoint security <p>Note: IoT FND software bundle includes required Java version.</p>
Cisco IoT FND TPS proxy	<ul style="list-style-type: none"> ■ Processor: <ul style="list-style-type: none"> – Intel Xeon x5680 2.27 GHz (64-bit) – 2 CPUs ■ RAM: 4 GB ■ Disk space: 25 GB 	<ul style="list-style-type: none"> ■ Red Hat Enterprise Linux 6.4 and above with all packages installed (software development and web server) ■ Internet connection <p>Note: IoT FND software bundle includes required Java version.</p>

System Requirements

Table 3 Minimum Hardware and Software Requirements for Cisco IoT FND and Supporting Systems (continued)

Component	Minimum Hardware Requirement	Minimum Software Release and Requirements
<p>Database server for IoT FND</p> <p>Scalable to 25 routers/10,000 endpoints with minimum hardware requirement. See Resource Management Guidelines for additional scale sizes.</p>	<ul style="list-style-type: none"> ■ Processor: Intel Xeon x5680 3.33 GHz (64-bit) ■ 2 CPUs ■ RAM: 16 GB ■ Disk space: 100 GB 	<p>Note: IoT FND 3.1.x supports both of the Oracle releases listed below.</p> <ul style="list-style-type: none"> ■ Oracle Database 12c Enterprise Edition Release 12.1.0.2.0 - 64bit Production (with Patch 20830993) ■ Oracle 11g Enterprise Edition (11.2.0.3 64-bit version only) <p>Note: Before installing Oracle, install the Linux packages referenced in “Installing the Linux Packages Required for Installing Oracle” in the Installing Cisco IoT FND chapter of the <i>Cisco IoT Field Network Director User Guide, Release 3.1.x</i></p> <p>See Table 4 on page 13 for suggested Oracle Database server resource allocation profiles.</p> <ul style="list-style-type: none"> ■ Red Hat Linux 6.4 and above, 64-bit with all packages installed (software development and web server)
Cisco IoT FND Client	<p>The client must meet the following minimum requirements to connect to the IoT FND application server and view IoT FND displays:</p> <ul style="list-style-type: none"> ■ Windows 7 or Win2000 R2 Server ■ RAM: 8 GB ■ Processor: 2 GHz ■ Resolution: 1024 x 768 	<ul style="list-style-type: none"> ■ Adobe Flash Version 9.0.115 or later (required for viewing charts) ■ Supported browsers: <ul style="list-style-type: none"> – Internet Explorer (IE): 11.0 – Mozilla Firefox: 3.5 or later – Windows 7 works with IE 11.0

System Requirements

Table 3 Minimum Hardware and Software Requirements for Cisco IoT FND and Supporting Systems (continued)

Component	Minimum Hardware Requirement	Minimum Software Release and Requirements
Cisco Network Registrar (CNR) (used as a DHCP server)	Server must have the following minimum requirements: <ul style="list-style-type: none"> ■ Free disk space: 146 GB ■ RAM: 4 GB (small network), 8 GB (average network), 16 GB (large network) ■ Hard drives: <ul style="list-style-type: none"> – SATA drives with 7500 RPM drive > 500 leases/second <i>or</i> – SAS drives with 15K RPM drive > 1000 leases/second 	The following software environment must exist before installing Cisco Network Registrar, software release 8.2 on the server: <ul style="list-style-type: none"> ■ Operating System: Windows Server 2008 ■ Development Kit (JDK) Java SE Runtime Environment (JRE) 8.0 (1.8.0_65-b17) or equivalent Java Development Kit (JDK). ■ User interfaces: Web browser and command-line interface (CLI) (Browser versions listed below): <ul style="list-style-type: none"> – Internet Explorer (IE) 11.0, Mozilla Firefox 3.0 or later ■ CNR license. Contact your Cisco partner for the necessary license.
IoT Device Manager (IoT-DM or Device Manager)	Laptop running Device Manager must have the following: <ul style="list-style-type: none"> ■ Microsoft Windows 7 Enterprise ■ 2 GHz or faster processor ■ 1 GB RAM minimum (for potential large log file processing) ■ WiFi or Ethernet interface ■ 4 GB disk storage space ■ Windows login enabled ■ Utility-signed Certificate Authority (CA) and Client Certificate for router authentication (obtained from your IT department) ■ Customer-specific IT security hardening to keep the Device Manager laptop secure 	<ul style="list-style-type: none"> ■ Version 5.0.0.16

System Requirements

Table 3 Minimum Hardware and Software Requirements for Cisco IoT FND and Supporting Systems (continued)

Component	Minimum Hardware Requirement	Minimum Software Release and Requirements
Cisco 1000 Series Connected Grid Router (CGR)	-	<ul style="list-style-type: none"> ■ Cisco IOS Release 15.5(3)M <ul style="list-style-type: none"> - You can also install Cisco IOS Release 15.6(3)M (although it is not the minimum requirement). ■ Cisco CG-OS Release CG4(3) and later <ul style="list-style-type: none"> - You can also install Cisco CG-OS CG(4) or CG(5) (although it is not the minimum requirement).
Cisco ISR 800 Series Integrated Services Router (C800)	-	<ul style="list-style-type: none"> ■ Cisco IOS Release 15.5(3)M <ul style="list-style-type: none"> - You can also install Cisco IOS Release 15.6(3)M (although it is not the minimum requirement).
Cisco 800 Series Access Points (AP800)	-	<ul style="list-style-type: none"> ■ AP802: ap802-k9w7-tar.153-3.JBB.tar ■ AP803: ap1g3-k9w7-tar.153-3.JBB2.tar
Cisco 800 Series Industrial Integrated Services Router (IR800)	-	<ul style="list-style-type: none"> ■ Cisco IOS Release 15.5(3)M <ul style="list-style-type: none"> - You can also install Cisco IOS Release 15.6(3)M (although it is not the minimum requirement).
Cisco 3900 Series Integrated Service Router (ISR)	-	<ul style="list-style-type: none"> ■ Cisco IOS Release 15.4(3)M ■ Cisco IOS Release 15.4(2)T
Cisco ASR 1001 or 1002 Aggregation Services Router (ASR) serving as a head-end router	-	<ul style="list-style-type: none"> ■ Cisco IOS XE Release 3.16.00S for Flex tunnels (IOS) ■ Cisco IOS XE Release 3.11S for Point to Point tunnels (CG-OS)
Note: ASRs and ISRs with different releases can co-exist on the network.		
Cisco 500 Series Wireless Personal Area Network (WPAN) Industrial Routers (IR500)	-	<ul style="list-style-type: none"> ■ Cisco IR509, DA Gateway device: Firmware version 5.6.10 ■ Cisco IR529, Range Extender: Firmware version 5.6.10
Cisco Connected Grid CG-Mesh Module and supported endpoints	-	<ul style="list-style-type: none"> ■ Firmware version 5.6.10 when communicating with CGR 1000s or Cisco ASRs and the minimum Cisco IOS software versions recommended for these routers in these release notes
Cisco Connected Grid RF Mesh endpoints	-	<ul style="list-style-type: none"> ■ Firmware version 5.6.10 when communicating with IR500

System Requirements

Table 3 Minimum Hardware and Software Requirements for Cisco IoT FND and Supporting Systems (continued)

Component	Minimum Hardware Requirement	Minimum Software Release and Requirements
Long Range Wide Area Network (LoRaWAN) Interface Module for Cisco 800 Series Industrial Integrated Services Routers (IR800)	-	<ul style="list-style-type: none"> ■ Cisco IOS 15.6(3)M
Hardware Security Module (HSM)	Luna SA appliance, with client software installed on the IoT FND application servers	Luna SA appliance: <ul style="list-style-type: none"> ■ Release 6.10.2 firmware <p>Note: Contact SafeNet to determine if you can run a higher version.</p> <ul style="list-style-type: none"> ■ Release 5.4.7-1 software, plus security patches Luna SA client software: <ul style="list-style-type: none"> ■ Release 5.4.7-1 software
Software Security Module (SSM)	<ul style="list-style-type: none"> ■ RAM: 8 GB ■ Processor: 2 GHz ■ 2 CPUs 	<ul style="list-style-type: none"> ■ Red Hat Enterprise Linux 6.4 or 7.1, 64-bit with all packages installed (software development and web server)

Note: If deploying a IoT FND server cluster, all nodes in the cluster should run on similar hardware. Additionally, all nodes must run the same version of IoT FND.

Resource Management Guidelines

Virtual machine (VM) configuration workload characterization is important. When using multiple VMs on the same physical host, allocate resources so that individual VMs do not impact the performance of other VMs. For example, to allocate 4 VMs on a 8-CPU host, do not allocate all 8 CPUs to ensure that one (or more) VM does not use all resources.

[Table 4 on page 13](#) lists example Oracle database server usage profiles for important resource parameters such as CPU, memory, and disk space.

Table 4 Oracle DB Server Hardware Requirements Example Profiles

Nodes (Routers/Endpoints)	CPU (Virtual Cores)	Memory (RAM GB)	Disk Space (GB)
25/10,000	2	16	100
50/50,000	4	16	200
500/500,000	8	32	500
1,000/1,000,000	12	48	1000
2,000/2,000,000	16	64	1000
5,000/5,000,000	20	96	1000

Table 5 on page 14 lists example IoT FND Application server usage profiles for important resource parameters such as CPU, memory, and disk space.

Table 5 Application Server Hardware Requirements Example Profile for Routers and Endpoints

Nodes (Routers/Endpoints)	CPU (Virtual Cores)	Memory (RAM GB)	Disk Space (GB)
25/10,000	2	16	100
50/50,000	4	16	200
500/500,000	4	16	250
1,000/1,000,000	8	16	250
2,000/2,000,000 ¹	8	16	500
5,000/5,000,000 ¹	8	16	500

1. Clustered installations.

Note: We strongly recommend RAID 10 for deployments of 2 million endpoints and above.

For Router Only Deployments

Information in Table 6 and Table 7 is relevant to Router Only deployments.

Table 6 Application Server Hardware Requirements Example Profile For Routers and LoRa Modules

Nodes (IR800/LoRa modules)	CPU (Virtual Cores)	Memory (RAM GB)	Disk Space (GB)
10,000/30,000	4	24	100

Table 7 Database Server Hardware Requirements Example Profile For Routers and LoRa Modules

Nodes (IR800/LoRa modules)	CPU (Virtual Cores)	Memory (RAM GB)	Disk Space (GB)
10,000/30,000	6	32	500

Installation Notes

The installation procedure for IoT FND comprises several tasks, as described in the *Cisco IoT Field Network Director User Guide, Release 3.x*. Contact your Cisco partner to obtain a copy of this guide.

You can also find details on upgrading from Oracle 11g to Oracle 12c for existing installations; and, instructions for installing Oracle 12c in new installations within the User Guide.

Important Notes

In [Limitations and Restrictions, page 15](#) and [Caveats, page 16](#), caveats that reference CG-NMS are also relevant to IoT FND. In cases where the caveat was first posted to CG-NMS, we left the CG-NMS reference.

OpenSSH Version

Since IoT FND is supported on a variety of Red Hat Enterprise Linux (RHEL) 5 Update releases, the OpenSSH version that comes with a given release might be an older version with known security holes. Consequently, we recommend ensuring that OpenSSH on the RHEL IoT FND server is up to date. On initial installation, upgrade the OpenSSH package in the IoT FND server to the latest version (6.4 or later).

Limitations and Restrictions

Cisco recommends that you review this section before you begin working with IoT FND. These are known limitations that will not be fixed, and there is not always a workaround for these issues. Some features might not work as documented, and some features might be affected by recent changes to the software.

■ CSCui54154

Symptom: On the **Device > Routers** or **Devices > Field Devices** page in List view with routers selected, on the Config tab the Config Error Details column may contain a hyperlink to the error description. If the Config tab is exported using the Export CSV option, the Config Error Details column is not included in the exported CSV file.

Conditions: This issue occurs when trying to export the Config tab with routers selected.

Workaround: There is no workaround for this issue.

■ CSCui54221

Symptom: On the **Device > Routers** or **Devices > Field Devices** page in List view with routers selected, on the Firmware tab the Firmware Error Details column may contain a hyperlink to the error description. If the Firmware tab is exported using the Export CSV option, Firmware Error Details column is not included in the exported CSV file.

Conditions: This issue occurs when trying to export the Firmware tab with routers selected.

Workaround: There is no workaround for this issue.

■ CSCuo96336

Symptom: A success message displays on metrics refresh although WSMA was timed out. No WSMA error displays.

Conditions: This issue occurs when you click Refresh Metrics and CG-NMS successfully refreshes, but WSMA was timed out.

Workaround: There is no workaround for this issue.

■ CSCur38441

Symptom: On the **Field Devices** page, in Map view with the Overlay option and a group selected, clicking a cluster icon displays the device count either as zero or an incorrect number.

Conditions: This issue occurs with the overlay feature enabled and set to All or Associated Endpoints/Routers, and the zoom level set so that a single marker denotes a group of devices.

Workaround: To display an accurate device count, zoom in until the icons no longer appear clustered and display as individual icons on the map.

■ CSCur44911

Symptom: During the ZTD process, illegal state exceptions display in the server logs indicating tunnel interface change traps occurred.

Conditions: This issue occurs when you add a new interface on the router that CG-NMS did not detect. Exceptions display in the server log when CG-NMS receives traps from that interface.

Caveats

Workaround: There is no workaround for this issue. Exceptions are not logged after CG-NMS detects the interface either during periodic inventory polling or user-triggered refresh metrics.

- **CSCuv32208**

Symptom: IoT FND GUI shows the database (DB) server in “down” state when checked under “Servers” section. All FND operations work correctly and no side effects are observed as a consequence of this apparent “down” state of the DB server. The database is marked “up” on the IoT FND application server restart but is soon marked “down” after 15 minutes of startup.

Conditions: This is caused under certain circumstances when periodic jobs responsible for updating the DB server status are stuck in the ACQUIRED state and never recover. This prevents the IoT FND application from updating the status of the DB server.

Workaround: The following workaround requires access to the DB server.

1. Stop the IoT FND application server.
2. Log in to the DB server as *cgms_dev_user*.
3. Update the State column for the CgnmsDbJobTrigger row in the QRTZ_TRIGGER tables from ACQUIRED to WAITING.
4. Commit the transaction.
5. Start the IoT FND application server.

- **CSCuy49541**

Symptom: When navigating to the Firmware page, the left pane and right pane do not show correct data.

Conditions: Navigating to the images tab before the firmware tab has finished loading.

Workaround: Wait for firmware tab to complete loading before navigating to the images tab.

Caveats

This section presents open and resolved caveats in this release and information on using the Bug Search Tool to view details on those caveats. Section topics are:

- [Open Caveats, page 16](#)
- [Resolved Caveats, page 19](#)
- [Accessing the Bug Search Tool, page 20](#)

Open Caveats

- **CSCtx50284**

Symptom: CG-NMS failed to shut down cleanly. The Cisco CG-NMS `server.log` file included exceptions.

Conditions: Occurred when the Cisco CG-NMS server was shut down or restarted using the Red Hat service commands **service cgms stop** or **service cgms restart** and Cisco CG-NMS internal server components shut down in an incorrect sequence.

Exceptions might have also appeared in the `server.log` file if any Cisco CG-NMS logging category is set to “Debug” level, as at this level, exceptions that represent normal internal activity might have been logged.

Caveats

If the Cisco CG-NMS server was not commanded to shut down using the service commands, then check the `cgms_watchdog.log` to see if watchdog restarted Cisco CG-NMS. If watchdog restarted Cisco CG-NMS, then there was a notation in `cgms_watchdog.log` providing the reason watchdog was triggered.

If the shutdown cannot be explained, then the exceptions might have indicated why the server shut down, and should be reviewed by the Cisco Technical Assistance Center (TAC).

Workaround: There is no workaround for this issue.

■ CSCty78770

Symptom: If two or more devices have the same GPS coordinate (which is likely if two Cisco CGRs are on the same pole), the icon in the map shows the devices as a cluster even at maximum zoom in.

Conditions: This issue occurs when two devices of the same type have the same GPS location.

Workaround: There is no workaround for this issue.

■ CSCtz29999

Symptom: On the Devices List page under “WiMAX Link Info”, the Base Station Identifier (BSID) field is not populated.

Conditions: The issue only occurs for WiMAX links.

Workaround: There is no workaround for this issue.

■ CSCub90976

Symptom: When configuring high availability (HA) on the secondary database at initial setup, the entire output of the database content copy is unexpectedly seen in the log output. Logging is inconsistent with logs when a new database is set up.

Conditions: The issue occurs when configuring or setting up a secondary CG-NMS database.

Workaround: There is no workaround for this issue.

■ CSCuc17916

Symptom: When reprovisioning or creating workorders for the Cisco CGR, a Cisco CGR SSID entry greater than 31 characters in the CSV import file does not throw an error during import, but creates other issues.

Conditions: The issue occurs when an SSID entry with more than 31 characters is found.

Workaround: Limit the number of characters to less than or equal to 31.

■ CSCuf95076, CSCuf95834

Symptom: During tunnel reprovisioning on a cluster failover, a System Error appears in the Reprovisioning Status column. Exceptions are listed in the log on the active NMS server when the CGR contacts it to complete the reprovisioning. Tunnel reprovisioning fails and snippets of exceptions display in the Error Message and Error Details columns, but the CGR can successfully register with the active NMS server.

Conditions: This issue occurs during CG-NMS cluster failovers.

Workaround: There is no workaround for this issue.

■ CSCug77724

Symptom: When using RPDON in the CG mesh solution, outage and registration messages from the smart meters are not handled correctly.

Caveats

Conditions: This issue occurs when one meter in the mesh is powered off and the RPDON heartbeat frequency and peer down count are set to maximum. On meter power-up the meter status and restore messages are not reported correctly.

Workaround: There is no workaround for this issue.

■ **CSCuj70073**

Symptom: Deleting a large number of elements from CG-NMS takes a long time.

Conditions: This issue occurs when you delete a large number of elements from CG-NMS and devices with issues are included in the operation. CG-NMS must lock all devices. Devices with issue rows in the NMS database increase the time of the delete operation.

Workaround: There is no workaround for this issue.

■ **CSCul02893**

Symptom: The Confirm dialog box does not display to start an SD Card Password push.

Conditions: This issue occurs during an SD card password enable or disable operation.

Workaround: There is no workaround for this issue.

■ **CSCul05847**

Symptom: On the **Config > Device Configuration > Push Configuration** page during a push SD card password operation, the start and end times displayed are the same.

Conditions: This issue occurs during an SD card password enable or disable operation.

Workaround: There is no workaround for this issue.

■ **CSCul51424**

Symptom: The same SSID is assigned to all CGRs in a group during reprovisioning.

Conditions: This issue occurs when generating a random SSID using the factory reprovisioning template and the prefix length is 31 characters, which is the valid length for the entire SSID. CG-NMS does not check the prefix length.

Workaround: There is no workaround for this issue.

■ **CSCuo96482**

Symptom: A CGR module hot swap causes a CG-NMS metric retrieval failure, and an error displays in CG-NMS during **show interfaces** command processing.

Conditions: This issue occurs during CGR reprovisioning where a module in the CGR was just swapped.

Workaround: There is no workaround for this issue. Avoid removing modules during CGR provisioning.

■ **CSCuz13240**

Symptom: Software Security Monitor (SSM) server cannot generate more than one custom certificate. When attempting to generate a second certificate, the script generates the keypair and a CSR without logging any error but the signature verification fails.

Conditions: SSM attempts to generate a second custom certificate. Red Hat Enterprise Linux 7.x was in use.

Workaround: There is no workaround.

■ **CSCva45081**

Symptom: When a Cellular interface is UP with 4G LTE on a C819HG-LTE-MNA-K9 system, the Cellular network type is displayed as GSM instead of LTE, under the Cellular Link Settings on the FND UI.

Caveats

Conditions: Router is provisioned with 4G.

Workaround: There is no workaround.

■ CSCvb12088

Symptom: Maps Overlay ALL Zoom In errors with IndexOutOfBounds Exception for C800 and IR800 routers.

Conditions: When Zoom In is clicked on the Maps for Overlay all view of C800 and IR800 routers, the operation should be successful and no errors should be displayed in the logs.

Workaround: Select Overlay “None” for routers and view the device details or Select All FAN Devices and view the devices on the Map.

■ CSCvb12216

Symptom: Devices with no GPS co-ordinates are displayed on the FND Maps with random coordinates at Overlay “All” view.

Conditions: When no co-ordinates are present for the device, it should not be shown on the Maps (in any view).

Workaround: There is no workaround.

■ CSCvb13546

Symptom: Selecting Overlay all drop-down on maps does not display appropriate meter data.

Conditions: Selection of Overlay drop-down should display appropriate data. Issue is not seen in IoT FND 3.1.

Workaround: There is no workaround.

■ CSCvb15255

Symptom: For a firmware upgrade progress chart, the histogram's Y-axis grid line numbers are exactly one greater than the counts shown through the tooltips hovering over the bar. This anomaly is more apparent when lower number of devices are being plotted.

Conditions: A firmware update job has been triggered and the user can see the progress of the job through the histogram chart which uses a logarithmic scale.

Workaround: There is no workaround.

■ CSCvb15297

Symptom: After a database HA failover, the secondary database is not displayed on the FND UI.

Conditions: When the DB Failover happens, the secondary DB should be listed in the Servers page of FND UI.

Workaround: There is no workaround.

Resolved Caveats

■ CSCut65807

Symptom: This bug is applicable only when CG-NMS is installed on a Red Hat Enterprise Linux 7.x server. CG-NMS fails to obtain DHCP leases (both IPv4 and IPv6) from the DHCP server during router configuration. You can observe the DHCP calls timing out in the CG-NMS log files. This affects router provisioning.

Conditions: This issue occurs when CG-NMS is configured to bind to all interfaces (that is, set to “0.0.0.0” for IPv4, and “::” for IPv6) for DHCP IPv4 and IPv6 client purposes, and CG-NMS fails to start client services on ports 67 and 547. As a result, CG-NMS fails to obtain leases for routers, which leads to router configuration failures.

Caveats

Workaround: This issue is resolved in IoT FND Release 3.1.0-131.

■ CSCuw88183

Symptom: Tunnel UP events not seen in Events UI.

Conditions: When ASR is polled and tunnel status moves to UP, NMS should generate a TUNNEL UP event.

Workaround: This issue is resolved in IoT FND Release 3.1.0-131.

■ CSCux61413

Symptom: User cannot see the 100 archived log files. Instead, only 50 log files are seen.

Conditions: User changed jboss-log4j.xml to show 100 files.

Workaround: This issue is resolved in IoT FND Release 3.1.0-131.

■ CSCuy20218

Symptom: Spelling errors exist in PRN.

Conditions: When restoration is sent from mesh nodes, user sees spelling errors in logs.

Workaround: This issue is resolved in IoT FND Release 3.1.0-131.

■ CSCuy34572

Symptom: Google Maps Javascript API not supported on IE11.

Conditions: When we opened IOT-FND in IE11, the maps were not shown. Instead a message was shown on the UI that stated: "You are using a browser that is not supported by the Google Maps JavaScript API. Consider changing your browser."

Workaround: This issue is resolved in IoT FND Release 3.1.0-131.

■ CSCuy68887

Symptom: .Mesh firmware update histogram does not display small values.

Conditions: During mesh firmware update, the histogram depicting upload progress does not show bars for buckets with smaller device counts as compared to large values. An example would be if the 100% bucket has 50,000 devices and the bucket for 60-70% has only 200 devices, the bar for 200 is not shown.

Workaround: This issue is resolved in IoT FND Release 3.1.0-131.

■ CSCuy74922

Symptom: Mesh Operator User does not see option in the GUI to upload meter/mesh image to IoT FND.

Conditions: User with Mesh Operator privileges.

Workaround: This issue is resolved in IoT FND Release 3.1.0-131.

Accessing the Bug Search Tool

You can use the Bug Search Tool to find information about caveats for this release, including a description of the problems and available workarounds. The Bug Search Tool lists both open and resolved caveats.

To access the Bug Search Tool, you need the following items:

- Internet connection

Related Documentation

- Web browser
- Cisco.com user ID and password

To access the Bug Search Tool, use the following URL: <https://tools.cisco.com/bugsearch/search>

To search using a specific bug ID, use the following URL: <https://tools.cisco.com/bugsearch/bug/<BUGID>>

Related Documentation

Find Cisco 1000 Series Connected Grid Routers and IoT Device Manager documentation at:

www.cisco.com/go/cgr1000-docs

For information on additional systems referenced in this release note, see the following documentation on Cisco.com:

- [Cisco ASR 1000 Series Aggregation Services Routers Configuration Guide](#)
- [Cisco 3945 Series Integrated Services Router](#)
- [Cisco 800 Series Integrated Services Routers](#)
- [Cisco 800 Series Industrial Integrated Services Routers](#)
- [Cisco 800 Series Access Points](#)
- [Cisco 500 Series WPAN Industrial Routers](#)
- [Cisco LoRaWAN Interface Module Hardware Installation Guide](#)

THE SPECIFICATIONS AND INFORMATION REGARDING THE PRODUCTS IN THIS MANUAL ARE SUBJECT TO CHANGE WITHOUT NOTICE. ALL STATEMENTS, INFORMATION, AND RECOMMENDATIONS IN THIS MANUAL ARE BELIEVED TO BE ACCURATE BUT ARE PRESENTED WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED. USERS MUST TAKE FULL RESPONSIBILITY FOR THEIR APPLICATION OF ANY PRODUCTS.

THE SOFTWARE LICENSE AND LIMITED WARRANTY FOR THE ACCOMPANYING PRODUCT ARE SET FORTH IN THE INFORMATION PACKET THAT SHIPPED WITH THE PRODUCT AND ARE INCORPORATED HEREIN BY THIS REFERENCE. IF YOU ARE UNABLE TO LOCATE THE SOFTWARE LICENSE OR LIMITED WARRANTY, CONTACT YOUR CISCO REPRESENTATIVE FOR A COPY.

The Cisco implementation of TCP header compression is an adaptation of a program developed by the University of California, Berkeley (UCB) as part of UCB's public domain version of the UNIX operating system. All rights reserved. Copyright © 1981, Regents of the University of California.

NOTWITHSTANDING ANY OTHER WARRANTY HEREIN, ALL DOCUMENT FILES AND SOFTWARE OF THESE SUPPLIERS ARE PROVIDED "AS IS" WITH ALL FAULTS. CISCO AND THE ABOVE-NAMED SUPPLIERS DISCLAIM ALL WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, WITHOUT LIMITATION, THOSE OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT OR ARISING FROM A COURSE OF DEALING, USAGE, OR TRADE PRACTICE.

IN NO EVENT SHALL CISCO OR ITS SUPPLIERS BE LIABLE FOR ANY INDIRECT, SPECIAL, CONSEQUENTIAL, OR INCIDENTAL DAMAGES, INCLUDING, WITHOUT LIMITATION, LOST PROFITS OR LOSS OR DAMAGE TO DATA ARISING OUT OF THE USE OR INABILITY TO USE THIS MANUAL, EVEN IF CISCO OR ITS SUPPLIERS HAVE BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

Related Documentation

Any Internet Protocol (IP) addresses and phone numbers used in this document are not intended to be actual addresses and phone numbers. Any examples, command display output, network topology diagrams, and other figures included in the document are shown for illustrative purposes only. Any use of actual IP addresses or phone numbers in illustrative content is unintentional and coincidental.

All printed copies and duplicate soft copies are considered un-Controlled copies and the original on-line version should be referred to for latest version.

Cisco has more than 200 offices worldwide. Addresses, phone numbers, and fax numbers are listed on the Cisco website at www.cisco.com/go/offices.

No combinations are authorized or intended under this document.

© 2016 Cisco Systems, Inc. All rights reserved.