



Storage Virtualization Commands

- [cluster datastore intdatastore](#), on page 2
- [cluster migrate-deployment](#), on page 3

cluster datastore intdatastore

To create a cluster, to do a cold migration of VMs, use the **cluster datastore intdatastore** command in privileged EXEC mode. To delete a cluster, use the no form of the command.

```
cluster cluster name { datastore [ intdatastore | extdatastore1 | extdatastore2 ] | size size number
| node ipv4 address address-type ipv4 | node ipv4 address address-type ipv4 | node ipv4 address address-type
ipv4 }
```

```
no cluster cluster name
```

Syntax Description

cluster cluster name	Specifies the name of the cluster.
datastore intdatastore extdatastore1 extdatastore2	Specifies the datastore to be selected for creating a cluster.
size size number	Specifies the size of the datastore.
node	Specifies the address and address type of the device in the cluster.



Note Three nodes must be added to the configuration, for the commit to be successful.

Command Default

None

Command Modes

Privileged EXEC (#)

Command History

Release	Modification
4.8.1	This command was introduced.

Example

```
nfvis(config)# cluster cluster1 datastore intdatastore size 10
nfvis(config-cluster-test) #node 209.165.200.225 address-type ipv4
nfvis(config-node-209.165.200.254) #exit
nfvis(config-cluster-test) #node 209.165.201.31 address-type ipv4
nfvis(config-node-209.165.200.224) #exit
nfvis(config-cluster-test) #node 209.165.201.1 address-type ipv4
nfvis(config-node-209.165.202.129) #commit
```

cluster migrate-deployment

To migrate deployments from a source node to a destination node, use the **cluster migrate-deployment** command in privileged EXEC mode.

```
cluster cluster name { migrate-deployment | source-node ip address | destination node ip address [ | all-deployments | deployment-list ] }
```

Syntax Description		
cluster <i>cluster name</i>		Specifies the cluster in which the deployments must be migrated.
source-node <i>ip address</i>		Specifies the node from which the deployment must be migrated.
destination node <i>ip address</i>		Specifies the node to which the deployment must be migrated.
all-deployments		Specifies that all deployments in the cluster need to be migrated.
deployment-list		Specifies the deployments to be migrated.

Command Default None

Command Modes Privileged EXEC (#)

Command History	Release	Modification
	4.8.1	This command was introduced.

Example

```
nfvis# cluster test migrate-deployment source-node 209.165.200.225 destination-node 209.165.201.31 all-deployments
```

```
nfvis# cluster test migrate-deployment source-node 209.165.200.225 destination-node 209.165.201.31 deployment-list [ centosvm4 centosvm5 ]
```

