



Apply

This is the crucial element that triggers the reconfiguration process. Until you select **Apply**, the changes remain **inactive** and will not affect the appliance's behavior. Reconfiguration refers to the process of implementing the changes you have made in the Admin TUI settings. It involves applying the new configurations to the running system of your appliance, often requiring adjustments to internal resources and processes.

- [Apply Configuration, on page 1](#)
- [Reboot Appliance, on page 2](#)

Apply Configuration

The process to apply configuration is as follows:

Procedure

Step 1 In Admin TUI, navigate to **Apply**.

Figure 1: Apply

```
-----Cisco Secure Malware Analytics - Appliance Administration-----
Your Malware Analytics appliance can be managed at:
Admin URL / MAC:
Application URL / MAC:
Password: *** set by user ***

n) Network
   Configure the system's network interfaces
r) Support Mode
   Allow remote access by customer support
u) Updates
   Download and optionally install updates
s) Snapshots
   Generate and submit snapshots
a) Apply
   Apply configuration
c) Console
   CLI-based configuration access
e) Exit
   Exit the management tool
```

Step 2 Select **Apply**.

Figure 2: Select Apply

```

Cisco Secure Malware Analytics - Appliance Administration
Your Malware Analytics appliance can be managed at:
Admin URL / MAC:
Application URL / MAC:
Password: *** set by user ***

Apply configurations
Status: No action needed

(a) Apply
    Apply Configuration Changes
(r) Reboot
    Reboot Appliance
(b) Back
    Back to main menu

```

Applies the new configuration.

Reboot Appliance

Within the apply menu you can reboot the appliance:

Procedure

Step 1 In Admin TUI, navigate to **apply**.

Step 2 Select **Reboot**.

Note The appliance will shut down and automatically restart. The reboot process may take several minutes. Once complete, you can access the Admin TUI again using the same method.

A confirmation message appears. Select OK to proceed with the reboot.