



INDEX

Symbols

\$ matches the end of a string **1-7**
() in commands **1-11**
* matches 0 or more sequences of a pattern **1-7**
+ matches 1 or more sequences of a pattern **1-7**
. matches any single character **1-7**
? command **1-1**
? matches 0 or 1 occurrence of a pattern **1-7**
^ matches the beginning of a string **1-7**
_ matches a comma (,), left brace ({), left parenthesis **1-7**
“ **1-10**

Numerics

10-Gigabit Ethernet uplink
 selecting **2-197**
 showing the mode **2-502, 2-503**
802.1Q trunk ports and native VLANs **2-842**
802.1Q tunnel ports

disabling send success packets **2-149**
enabling send success packets **2-149**
enabling on a port **2-148**
enabling on a VLAN **2-151**
returning delay time to default setting **2-150**
setting delay time on a port **2-150**
802.1X critical authentication
 configure parameters **2-21**
802.1X critical recovery delay, configuring **2-21**
802.1X Port Based Authentication
 debugging 802.1X Port Based Authentication **2-104**
 displaying port based authentication **2-482**
 enabling accounting for authentication sessions **2-4**
 enabling authentication on the system **2-165**
 enabling guest VLAN **2-152**
 enabling guest VLAN supplicant **2-146, 2-153**
 enabling manual control of auth state **2-161**
 enabling periodic re-authentication of the client **2-164**
 initializing re-authentication of dot1x ports **2-163**
 initializing state machines **2-156**
 receive session termination message upon reboot **2-5**
 setting maximum number for EAP requests **2-159**
 setting the reauthentication timer **2-166**

A

abbreviating commands
 context-sensitive help **1-1**
Access Gateway Module
 connecting to a module **2-18**
 connecting to a remote module **2-414**
 connecting to a specific remote module **2-426**
access-group

- displaying mac interface **2-609**
- show mode interface **2-445, 2-662**
- access groups
 - IP **2-6, 2-142**
- access-list hardware capture mode command **2-8**
- access lists
 - clearing an access template **2-69**
 - defining ARP **2-17**
 - displaying ARP information **2-448**
 - See also ACLs, MAC ACLs, and VACLs
- access maps
 - applying with VLAN filter **2-844**
- access-policies, applying using host-mode **2-25**
- ACLs
 - access-group mode **2-6**
 - balancing hardware regions **2-12**
 - determining ACL hardware programming **2-10**
 - disabling hardware statistics **2-192**
 - displaying mac access-group interface **2-609**
 - enabling hardware staticstics **2-192**
 - using ACL naming conventions for MAC ACLs **2-308**
- action clause
 - specifying drop or forward action in a VACL **2-13**
- addresses, configuring a maximum **2-380**
- adjacency
 - debugging the adjacency table **2-97**
 - disabling the debug facility **2-97**
 - displaying information about the adjacency table **2-446**
 - displaying IPC table entries **2-97**
- aggregate policer
 - displaying information **2-663**
- aging time
 - displaying MAC address aging time **2-612**
- alarms
 - displaying operational status **2-490**
- alternation
 - description **1-10**
- anchoring
 - description **1-10**
- ARP
 - access list, displaying detailed information **2-448**
 - defining access-lists **2-17**
 - ARP inspection
 - enforce certain types of checking **2-214**
 - ARP packet
 - deny based on DHCP bindings **2-136**
 - permit based on DHCP bindings **2-359**
 - authentication **2-21, 2-27**
 - changing the control-direction **2-19**
 - configure actions for events
 - configuring the actions **2-22**
 - configuring port-control **2-31**
 - enabling reauthentication **2-30**
 - enabling Webauth fallback **2-24**
 - host-mode configuration **2-25**
 - setting priority of methods **2-33**
 - setting the timer **2-35**
 - setting username **2-829**
 - specifying the order of methods **2-28**
 - using an MD5-type encryption method **2-829**
 - verifying MD5 signature **2-831**
 - verifying the checksum for Flash memory **2-831**
 - authentication control-direction command **2-19**
 - authentication critical recovery delay command **2-21**
 - authentication event command **2-22**
 - authentication fallback command **2-24**
 - authentication host-mode **2-25**
 - authentication methods, setting priority **2-33**
 - authentication methods, specifying the order of attempts **2-28**
 - authentication open command **2-27**
 - authentication order command **2-28**
 - authentication periodic command **2-30**
 - authentication port-control command **2-31**
 - authentication priority command **2-33**
 - authentication timer, setting **2-35**

authentication timer command **2-35**
 auth fail VLAN
 enable on a port **2-146**
 set max number of attempts **2-145**

Auth Manager
 configuring
 authentication timer **2-35**
 authorization state
 enabling manual control **2-161**
 authorization state of a controlled port **2-161**

automatic installation
 displaying status **2-453**
 automatic medium-dependent interface crossover
 See Auto-MDIX
 Auto-MDIX
 disabling **2-341**
 enabling **2-341**
 auto-negotiate interface speed
 example **2-763**
 auto-QoS
 configuring for VoIP **2-37**
 displaying configuration **2-454**

B

baby giants
 displaying the system MTU setting **2-694**
 setting the maximum Layer 2 payload size **2-810**
 BackboneFast
 displaying debugging messages **2-123**
 displaying spanning tree status **2-684**
 enabling debugging **2-123**
 bandwidth command **2-41**
 bindings
 store for DHCP snooping **2-225**
 BOOT environment variable
 displaying information **2-457**
 bootflash
 displaying information **2-455**

BPDUs
 debugging spanning tree activities **2-121**
 bridge protocol data units
 See BPDUs
 broadcast
 counters **2-94**
 broadcast suppression level
 configuring **2-764, 2-766**
 enabling **2-764, 2-766**

C

cable diagnostics
 TDR
 displaying test results **2-458**
 testing conditions of copper cables **2-812**
 call home
 displaying information **2-460**
 e-mailing output **2-49**
 entering configuration submode **2-44**
 executing **2-49**
 manually send test message **2-52**
 receiving information **2-47**
 sending alert group message **2-50**
 submitting information **2-47**
 call home destination profiles
 displaying **2-462**
 Catalyst 4507R **2-378**
 CDP
 configuring tunneling encapsulation rate **2-296**
 displaying
 neighbor information **2-465**
 enabling protocol tunneling for **2-291**
 set drop threshold for **2-294**
 CEF
 displaying next-hop information **2-539**
 displaying VLAN configuration information **2-539**
 chassis
 displaying

- chassis MAC address ranges **2-606**
 - current and peak traffic meter readings **2-606**
 - percentage of backplane utilization **2-606**
 - switching clock failure recovery mode **2-606**
 - cisco-desktop
 - macro apply **2-320**
 - Cisco Express Forwarding
 - See CEF
 - cisco-phone
 - macro apply **2-322**
 - cisco-router
 - macro apply **2-324**
 - cisco-switch
 - macro apply **2-326**
 - class-map command **2-60**
 - class maps
 - defining the match criteria **2-334**
 - clear commands
 - clearing Gigabit Ethernet interfaces **2-67**
 - clearing IGMP group cache entries **2-76**
 - clearing interface counters **2-62**
 - clearing IP access lists **2-69, 2-70**
 - clearing IP ARP inspection statistics VLAN **2-71**
 - clearing IP DHCP snooping database statistics **2-75**
 - clearing MFIB counters and routes **2-79**
 - clearing MFIB fastdrop entries **2-80**
 - clearing PAgP channel information **2-85**
 - clearing QoS aggregate counters **2-88**
 - clearing VLAN interfaces **2-68**
 - clear energywise neighbors command **2-64**
 - CLI string search
 - anchoring **1-10**
 - expressions **1-7**
 - filtering **1-6**
 - multiple-character patterns **1-8**
 - multipliers **1-9**
 - parentheses for recall **1-11**
 - searching outputs **1-6**
 - single-character patterns **1-7**
 - using **1-6**
 - command modes
 - accessing privileged EXEC mode **1-5**
 - exiting **1-5**
 - understanding user EXEC and configuration modes **1-5**
 - condition interface
 - debugging interface-related activities **2-99**
 - condition vlan
 - debugging VLAN output **2-102**
 - configuration, saving **1-11**
 - configuring
 - root as secondary **2-747**
 - configuring a SPAN session to monitor
 - limit SPAN source traffic **2-346**
 - configuring critical recovery **2-21**
 - configuring forward delay **2-743**
 - configuring root as primary **2-747**
 - CoPP
 - attaching
 - policy map to control plane **2-424**
 - displaying
 - policy-map class information **2-638**
 - entering configuration mode **2-92**
 - removing
 - service policy from control plane **2-424**
 - CoS
 - assigning to Layer 2 protocol packets **2-293**
 - counters
 - clearing interface counters **2-62**
 - critical authentication, configure 802.1X parameters **2-21**
 - critical recovery, configuring 802.1X parameter **2-21**
-
- ## D
- DAI
 - clear statistics **2-71**
 - DBL
 - displaying qos dbl **2-664**

- debug commands
- debugging backup events **2-98**
 - debugging DHCP snooping events **2-109**
 - debugging DHCP snooping messages **2-110**
 - debugging EtherChannel/PAgP/shim **2-105**
 - debugging IPC activity **2-108**
 - debugging IP DHCP snooping security messages **2-111**
 - debugging NVRAM activities **2-114**
 - debugging PAgP activities **2-115**
 - debugging port manager activities **2-118**
 - debugging spanning tree activities **2-121**
 - debugging spanning tree backbonefast **2-123**
 - debugging spanning tree UplinkFast **2-126**
 - debugging supervisor redundancy **2-120**
 - debugging VLAN manager activities **2-127**
 - displaying monitor activity **2-113**
 - displaying the adjacency table **2-97**
 - enabling debug dot1x **2-104**
 - enabling debugging messages for ISL VLAN IDs **2-130**
 - enabling debugging messages for VTP **2-131**
 - enabling debugging of UDLD activity **2-132**
 - enabling switch shim debugging **2-124**
 - enabling VLAN manager file system error tests **2-128**
 - limiting debugging output for VLANs **2-102**
 - limiting interface debugging output **2-99**
 - limiting output for debugging standby state changes **2-100**
 - shortcut to the debug condition interface **2-107**
- debugging
- activity monitoring **2-113**
 - DHCP snooping events **2-109**
 - DHCP snooping packets **2-110**
 - IPC activities **2-108**
 - IP DHCP snooping security packets **2-111**
 - NVRAM activities **2-114**
 - PAgP activities **2-115**
 - PAgP shim **2-105**
 - PM activities **2-118**
- spanning tree BackboneFast events **2-123**
 - spanning tree switch shim **2-124**
 - spanning tree UplinkFast events **2-126**
 - VLAN manager activities **2-127**
 - VLAN manager IOS file system error tests **2-128**
 - VTP protocol debug messages **2-131**
- debug spanning tree switch **2-124**
- debug sw-vlan vtp **2-131**
- default form of a command, using **1-6**
- DHCP
- clearing database statistics **2-75**
- DHCP bindings
- configuring bindings **2-223**
 - deny ARP packet based on matches **2-136**
 - permit ARP packet based on matches **2-359**
- DHCP snooping
- clearing binding entries **2-72**
 - clearing database **2-74**
 - displaying binding table **2-542**
 - displaying configuration information **2-540**
 - displaying status of DHCP database **2-545**
 - displaying status of error detection **2-493**
 - enabling DHCP globally **2-222**
 - enabling IP source guard **2-262**
 - enabling on a VLAN **2-232**
 - enabling option 82 **2-227, 2-229**
 - enabling option-82 **2-234**
 - enabling rate limiting on an interface **2-230**
 - enabling trust on an interface **2-231**
 - establishing binding configuration **2-223**
 - renew binding database **2-416**
 - store generated bindings **2-225**
- diagnostic fpga soft-error recover aggressive command **2-142**
- diagnostic test
- bootup packet memory **2-476**
 - displaying attributes **2-470**
 - display module-based results **2-472**
 - running **2-144**

- show results for TDR **2-458**
- testing conditions of copper cables **2-812**
- displaying error disable recovery **2-494**
- displaying inline power status **2-653**
- displaying monitoring activity **2-113**
- displaying PoE policing and monitoring status **2-661**
- displaying EEPROM information
 - GBIC** **2-504**
- displaying SPAN session information **2-694, 2-766**
- document conventions **1-xx**
- document organization **1-xix**
- DoS
 - CoPP
 - attaching policy map to control plane **2-424**
 - displaying policy-map class information **2-638**
 - entering configuration mode **2-92**
 - removing service policy from control plane **2-424**
 - entering
 - CoPP configuration mode **2-92**
- DOS attack
 - protecting system's resources **2-209**
- drop threshold, Layer 2 protocol tunneling **2-294**
- dual-capable port
 - selecting a connector **2-343**
- duplex mode
 - configuring autonegotiation on an interface **2-168**
 - configuring full duplex on an interface **2-168**
 - configuring half duplex on an interface **2-168**
- dynamic ARP inspection
 - preventing **2-209**
- Dynamic Host Configuration Protocol
 - See DHCP
- filters
 - routing updates, preventing **2-356**
- enabling
 - debugging for UDLD **2-132**
 - voice VLANs **2-779**
- enabling open access **2-27**
- EnergyWise
 - display power information through queries **2-177**
 - display setting, status of entity and PoE ports **2-486**
 - on an entity
 - enable, assign to domain, and set password **2-175**
 - on an entity, enable and configure **2-170**
 - on a PoE port
 - configuring on PoE port **2-172**
 - energywise (global configuration) command **2-170, 2-172**
 - energywise domain command **2-175**
 - EnergyWise neighbor table, deleting **2-64**
 - energywise query command **2-177**
 - environmental
 - alarms **2-490**
 - displaying information **2-490**
 - status **2-490**
 - temperature **2-490**
 - erase a file **2-181**
 - error disable detection
 - clearing error disable on an interface **2-65**
 - enabling error disable detection **2-65, 2-184**
 - enabling per-VLAN on BPDU guard **2-184**
 - error-disabled state
 - displaying **2-523**
 - error disable recovery
 - configuring recovery mechanism variables **2-186**
 - displaying recovery timer information **2-494**
 - enabling ARP inspection timeout **2-186**
 - specifying recovery cause **2-186**
 - EtherChannel
 - assigning interfaces to EtherChannel groups **2-53**
 - debugging EtherChannel **2-105**
 - debugging PAgP shim **2-105**

E**EAP**

restarting authentication process **2-159**

EDCS-587028 **2-449, 2-606**

EIGRP (Enhanced IGRP)

- debugging spanning tree activities [2-121](#)
 displaying information for a channel [2-496](#)
 removing interfaces from EtherChannel groups [2-53](#)
- EtherChannel guard
 detecting STP misconfiguration [2-733](#)
- Explicit Host Tracking
 clearing the database [2-78](#)
 enabling per-VLAN [2-246](#)
- expressions
 matching multiple expression occurrences [1-9](#)
 multiple-character patterns [1-8](#)
 multiplying pattern occurrence [1-11](#)
 single-character patterns [1-7](#)
- Extensible Authentication Protocol
 See EAP
-
- F**
- fallback profile, specifying [2-24](#)
 field replaceable unit (FRU)
 displaying status information [2-490](#)
 filters
 EIGRP
 routing updates, preventing [2-356](#)
- Flash memory file system
 displaying file system information [2-455](#)
 verifying checksum [2-831](#)
- flow control
 configuring a gigabit interface for pause frames [2-189](#)
 displaying per-interface statistics for flow control [2-500](#)
-
- G**
- GBIC
 displaying EEPROM information [2-504](#)
- Gigabit Ethernet interface
 clearing the hardware logic [2-67](#)
- Gigabit Ethernet uplink
- selecting [2-197](#)
 showing the mode [2-502, 2-503](#)
- global configuration mode
 using [1-5](#)
-
- H**
- hardware module
 resetting a module by toggling the power [2-194](#)
- hardware statistics
 disabling [2-192](#)
 enabling [2-192](#)
- hardware uplink
 selecting the mode [2-197](#)
 showing the mode [2-502, 2-503](#)
- helper addresses, IP [2-560](#)
- hot standby protocol
 debugging [2-100](#)
 disabling debugging [2-100](#)
 limiting output [2-100](#)
- hw-module uplink mode shared-backplane command [2-195](#)
-
- I**
- IDPROMs
 displaying EEPROM information
 chassis [2-504](#)
 clock module [2-504](#)
 fan trays [2-504](#)
 module [2-504](#)
 mux buffer [2-504](#)
 power supplies [2-504](#)
 supervisor engine [2-504](#)
- ifIndex persistence
 clearing SNMP ifIndex commands [2-717](#)
 compress SNMP ifIndex table format [2-726](#)
 disabling globally [2-725](#)
 disabling on an interface [2-719](#)

- enabling globally **2-725**
- enabling on an interface **2-719**
- IGMP**
 - applying filters for host joining on Layer 2 interfaces **2-236**
 - clearing IGMP group cache entries **2-76**
 - configuring frequency for IGMP host-query messages **2-239**
 - creating an IGMP profile **2-238**
 - displaying IGMP interface configuration information **2-547**
 - displaying profiles **2-549**
 - setting maximum group numbers **2-237**
- IGMP profiles**
 - displaying **2-549**
- IGMP snooping**
 - clearing the EHT database **2-78**
 - configuring a Layer 2 interface as a group member **2-252**
 - configuring a Layer 2 interface as a multicast router **2-250**
 - configuring a static VLAN interface **2-252**
 - displaying multicast information **2-556**
 - displaying VLAN information **2-550, 2-554, 2-557**
 - enabling **2-241**
 - enabling immediate-leave processing **2-248**
 - enabling on a VLAN **2-245**
 - enabling per-VLAN Explicit Host Tracking **2-246**
- informs**
 - enabling **2-721**
- inline power**
 - displaying inline power status **2-653**
- In Service Software Upgrade**
 - See ISSU
- inspection log**
 - clearing log buffer **2-70**
- interface**
 - displaying suppressed multicast bytes **2-517**
- interface capabilities**
 - displaying **2-513**
- interface configuration mode**
 - summary **1-5**
- interface link**
 - display cable disconnect time **2-520**
- interfaces**
 - configuring dot1q tunnel ports **2-786**
 - creating an interface-range macro **2-135**
 - debugging output of interface related activities **2-99**
 - displaying description **2-519**
 - displaying error-disabled state **2-523**
 - displaying information when tunneling is enabled **2-600**
 - displaying status **2-519**
 - displaying traffic for a specific interface **2-510**
 - entering interface configuration mode **2-201**
 - executing a command on multiple ports in a range **2-204**
 - selecting an interface to configure **2-201**
 - setting a CoS value for Layer 2 packets **2-293**
 - setting drop threshold for Layer 2 packets **2-294**
 - setting the interface type **2-786**
- interface speed**
 - configuring interface speed **2-761**
- interface transceiver**
 - displaying diagnostic data **2-527**
- internal VLAN allocation**
 - configuring **2-845**
 - default setting **2-845**
 - displaying allocation information **2-706**
- Internet Group Management Protocol**
 - See IGMP
- IP ARP**
 - applying ARP ACL to VLAN **2-207**
 - clearing inspection statistics **2-71**
 - clearing status of log buffer **2-70**
 - controlling packet logging **2-218**
 - enabling dynamic inspection **2-216**
 - limit rate of incoming requests **2-209**
 - set per-port config trust state **2-213**

- showing status of dynamic ARP inspection [2-534](#)
 - showing status of log buffer [2-537](#)
 - IPC**
 - debugging IPC activities [2-108](#)
 - IP DHCP Snooping**
 - See [DHCP snooping](#)
 - IP header validation**
 - disabling [2-261](#)
 - enabling [2-261](#)
 - IP interfaces**
 - displaying usability status [2-559](#)
 - IP multicast**
 - displaying multicast routing table information [2-565](#)
 - IP phone and standard desktop**
 - enabling Cisco-recommended features [2-322](#)
 - IP Port Security**
 - enabling [2-262](#)
 - IP source binding**
 - adding or deleting [2-258](#)
 - displaying bindingstagging [2-570](#)
 - IP source guard**
 - debugging messages [2-111](#)
 - displaying configuration and filters [2-571](#)
 - enabling on DHCP snooping [2-262](#)
 - IPv6 MLD**
 - configuring queries [2-268, 2-270](#)
 - configuring snooping
 - last-listener-query-intervals [2-270](#)
 - configuring snooping
 - listener-message-suppression [2-272](#)
 - configuring snooping robustness-variables [2-273](#)
 - configuring tcn topology change notifications [2-275](#)
 - counting snooping last-listener-queries [2-268](#)
 - displaying information [2-576](#)
 - displaying ports for a switch or VLAN [2-578](#)
 - displaying querier information [2-579](#)
 - enabling snooping [2-266](#)
 - enabling snooping on a VLAN [2-276](#)
 - ISSU**
 - cancelling process [2-278](#)
 - configuring rollback timer [2-290](#)
 - displaying capability [2-581](#)
 - displaying client information [2-583](#)
 - displaying compatibility matrix [2-585](#)
 - displaying endpoint information [2-590](#)
 - displaying entities [2-591](#)
 - displaying FSM session [2-592](#)
 - displaying messages [2-593](#)
 - displaying negotiated [2-595](#)
 - displaying rollback-timer [2-596](#)
 - displaying session information [2-597](#)
 - displaying software version [2-598](#)
 - displaying state [2-598](#)
 - forcing switchover to standby supervisor engine [2-288](#)
 - initiating an automatic ISSU upgrade procedure [2-282](#)
 - loading new image [2-284](#)
 - starting process [2-286](#)
 - stopping rollback timer [2-280](#)
-
- J**
- Jumbo frames**
 - enabling jumbo frames [2-352](#)
-
- L**
- LACP**
 - deselecting channeling protocol [2-55](#)
 - enabling LACP on an interface [2-55](#)
 - setting channeling protocol [2-55](#)
 - lacp port-priority command [2-298](#)
 - lacp system-priority command [2-299](#)
 - Layer 2**
 - displaying ACL configuration [2-609](#)
 - Layer 2 interface type**

- specifying a nontrunking, nontagged single VLAN interface [2-786](#)
 - specifying a trunking VLAN interface [2-786](#)
 - Layer 2 protocol ports
 - displaying [2-600](#)
 - Layer 2 protocol tunneling error recovery [2-296](#)
 - Layer 2 switching
 - enabling voice VLANs [2-779](#)
 - modifying switching characteristics [2-779](#)
 - Layer 2 traceroute
 - IP addresses [2-817](#)
 - Layer 3 switching
 - displaying information about an adjacency table [2-446](#)
 - displaying port status [2-525](#)
 - displaying status of native VLAN tagging [2-525](#)
 - link-status event messages
 - disabling
 - globally [2-300, 2-303](#)
 - on an interface [2-301, 2-304](#)
 - enabling
 - globally [2-300, 2-303](#)
 - on an interface [2-301, 2-304](#)
 - log buffer
 - show status [2-537](#)
 - logging
 - controlling IP ARP packets [2-218](#)
-
- M**
 - MAB, display information [2-606](#)
 - MAB, enable and configure [2-306](#)
 - mab command [2-306](#)
 - MAC Access Control Lists
 - See MAC ACLs
 - MAC ACLs
 - defining extended MAC access list [2-308](#)
 - displaying MAC ACL information [2-703](#)
 - naming an ACL [2-308](#)
 - MAC addresses
 - disabling MAC address learning per VLAN [2-315](#)
 - MAC address filtering
 - configuring [2-319](#)
 - disabling [2-319](#)
 - enabling [2-319](#)
 - MAC address learning on a VLAN, enabling [2-315](#)
 - MAC address table
 - adding static entries [2-331](#)
 - clearing dynamic entries [2-82, 2-84](#)
 - displaying dynamic table entry information [2-616](#)
 - displaying entry count [2-614](#)
 - displaying information [2-610](#)
 - displaying interface-based information [2-618](#)
 - displaying multicast information [2-620](#)
 - displaying notification information [2-622](#)
 - displaying protocol-based information [2-624](#)
 - displaying static table entry information [2-626](#)
 - displaying the MAC address aging time [2-612](#)
 - displaying VLAN-based information [2-629](#)
 - enabling authentication bypass [2-157](#)
 - enabling notifications [2-317](#)
 - learning in the protocol buckets [2-312](#)
 - removing static entries [2-331](#)
 - mac address-table learning vlan command [2-315](#)
 - MAC address tables
 - adding static entries [2-319](#)
 - deleting secure or specific addresses [2-86](#)
 - disabling IGMP snooping on static MAC addresses [2-319](#)
 - removing static entries [2-319](#)
 - mac-address-table static [2-319](#)
 - MAC address unicast filtering
 - dropping unicast traffic [2-319](#)
 - MAC authentication bypass (MAB), display information [2-606](#)
 - MAC authorization bypass(MAB), enable and configure [2-306](#)
 - macro
 - displaying descriptions [2-330](#)

macro keywords
 help strings **2-2**

macros
 adding a global description **2-330**
 cisco global **2-328**
 system-cpp **2-329**

mapping secondary VLANs to MST instance **2-399**

mapping VLAN(s) to an MST instance **2-199**

match (class-map configuration) command **2-14, 2-138, 2-139, 2-140, 2-141, 2-334, 2-767, 2-769, 2-771, 2-773, 2-777**

maximum transmission unit (MTU)
 displaying the system MTU setting **2-694**
 setting the maximum Layer 2 payload size **2-810**

MD5
 verifying MD5 signature **2-831**

message digest 5
 See MD5

MFIB
 clearing ip mfib counters **2-79**
 clearing ip mfib fastdrop **2-80**
 displaying all active MFIB routes **2-562**
 displaying MFIB fastdrop table entries **2-564**
 enabling IP MFIB fastdrops **2-255**

MLD
 configuring snooping
 last-listener-query-intervals **2-270**
 configuring snooping
 listener-message-suppression **2-272**
 configuring snooping robustness-variables **2-273**
 configuring topology change notifications **2-275**
 counting snooping last-listener-queries **2-268**
 enabling snooping **2-266**
 enabling snooping on a VLAN **2-276**

MLD snooping
 displaying **2-579**

modes
 access-group **2-6**
 show access-group interface **2-445, 2-662**
 switching between PVST+, MST, and Rapid PVST **2-738**

See also command modes

module password clearing **2-66**

module reset
 resetting a module by toggling the power **2-194**

--More-- prompt
 filter **1-6**
 search **1-7**

MST
 designating the primary and secondary root **2-747**
 displaying MST protocol information **2-689**
 displaying region configuration information **2-689**
 displaying spanning tree information **2-689**
 entering MST configuration submode **2-741**
 setting configuration revision number **2-418**
 setting path cost and port priority for instances **2-739**
 setting the forward delay timer for all instances **2-743**
 setting the hello-time delay timer for all instances **2-744**
 setting the max-age timer for all instances **2-745**
 setting the MST region name **2-353**
 specifying the maximum number of hops **2-746**
 switching between PVST+ and Rapid PVST **2-738**
 using the MST configuration submode revision command **2-418**
 using the submode name command **2-353**

MTU
 displaying global MTU settings **2-694**

multi-auth, setting **2-25**

Multicast Listener Discovery
 See MLD

multicast
 counters **2-94**
 enabling storm control **2-766**

multicast/unicast packets
 prevent forwarding **2-785**

Multicast Forwarding Information Base
 See MFIB

multi-domain, setting **2-25**

multiple-character patterns **1-8**

Multiple Spanning Tree

See MST

N

native VLAN

controlling tagging of traffic **2-806**

displaying ports eligible for native tagging **2-705**

displaying ports eligible for tagging **2-705**

enabling tagging on 802.1Q trunk ports **2-842**

specifying the tagging of traffic **2-807**

NetFlow

enabling NetFlow statistics **2-256**

including infer fields in routing statistics **2-256**

next-hop

displaying CEF VLAN information **2-539**

no form of a command, using **1-6**

NVRAM

debugging NVRAM activities **2-114**

O

open access on a port, enabling **2-27**

output

pattern searches **1-7**

P

packet forwarding

prevent unknown packets **2-785**

packet memory failure

direct switch action upon detection **2-143**

packet memory test

bootup, displaying results **2-476, 2-478**

ongoing, displaying results **2-480**

PACL

access-group mode **2-6**

paging prompt

see --More-- prompt

PAgP

clearing port channel information **2-85**

debugging PAgP activity **2-115**

deselecting channeling protocol **2-55**

displaying port channel information **2-635**

hot standby mode

returning to defaults **2-355**

selecting ports **2-355**

input interface of incoming packets

learning **2-354**

returning to defaults **2-354**

setting channeling protocol **2-55**

parentheses **1-11**

password

clearing on an intelligent line module **2-66**

establishing enhanced password security **2-829**

setting username **2-829**

PBR

displaying route maps **1-xx**

redistributing route maps **1-xx**

PM activities

debugging **2-118**

disabling debugging **2-118**

PoE policing

configure on an interface **2-386**

PoE policing and monitoring

displaying status **2-661**

police (percent) command **2-366**

police (two rates) command **2-368, 2-370**

police command **2-361**

policing, configure PoE **2-386**

policing and monitoring status

displaying PoE **2-661**

Policy Based Routing

See PBR

policy maps

creating **2-374**

marking **2-428**

See also QoS, hierarchical policies
 traffic classification
 defining the class
 defining trust states **2-820**
 port, dual-capable
 selecting the connector **2-343**
 Port Aggregation Protocol
 See PAgP
 port-based authentication
 displaying debug messages **2-104**
 displaying statistics and status **2-482**
 enabling 802.1X **2-161**
 host modes **2-154**
 manual control of authorization state **2-161**
 periodic re-authentication
 enabling **2-164**
 re-authenticating 802.1X-enabled ports **2-163**
 switch-to-client frame-retransmission number **2-159**
 port channel
 accessing **2-203**
 creating **2-203**
 displaying information **2-635**
 load distribution method
 resetting to defaults **2-376**
 setting **2-376**
 port control, changing from unidirectional or bidirectional **2-19**
 port-control value, configuring **2-31**
 port range
 executing **2-204**
 port security
 debugging ports security **2-119**
 deleting secure or specific addresses **2-86**
 displaying settings for an interface or switch **2-646**
 enabling **2-791**
 filter source IP and MAC addresses **2-262**
 setting action upon security violation **2-791**
 setting the rate limit for bad packets **2-791**
 sticky port **2-791**
 Port Trust Device
 displaying **2-665**
 power status
 displaying inline power **2-653**
 displaying power status **2-653**
 power supply
 configuring combined and redundant power on the Catalyst 4507R **2-378**
 configuring inline power **2-383**
 configuring power consumption **2-378**
 displaying the EEPROM **2-504**
 setting inline power state **2-382**
 priority command **2-390**
 priority-queue command **2-95**
 Private VLAN
 See PVLANs
 privileged EXEC mode, summary **1-5**
 prompts
 system **1-5**
 protocol tunneling
 configuring encapsulation rate **2-296**
 disabling **2-291**
 displaying port information **2-600**
 enabling **2-291**
 setting a CoS value for Layer 2 packets **2-293**
 setting a drop threshold for Layer 2 packets **2-294**
 PVLANs
 configuring isolated, primary, and community PVLANs **2-392**
 controlling tagging of native VLAN traffic **2-806**
 disabling sticky-ARP **2-259**
 displaying map information for VLAN SVIs **2-522**
 displaying PVLAN information **2-708**
 enabling interface configuration mode **2-786**
 enabling sticky-ARP **2-259**
 mapping VLANs to the same SVI **2-396**
 specifying host ports **2-786**
 specifying promiscuous ports **2-786**
 PVST+

switching between PVST and MST **2-738**

setting QoS group identifiers **2-439**

Q

QoS

account Layer 2 encapsulation **2-402**

attaching a policy-map to an interface **2-419**

automatic configuration **2-37**

class maps

defining the match criteria **2-334**

clearing aggregate counters **2-88**

configuring auto **2-37**

displaying aggregate policer information **2-663**

displaying auto configuration **2-454**

displaying class maps information **2-468**

displaying configuration information **2-454**

displaying configurations of policies **2-641**

displaying policy map information **2-637, 2-644**

displaying QoS information **2-662**

displaying QoS map information **2-667**

egress queue-sets

enabling the priority queue **2-95**

hierarchical policies

average-rate traffic shaping on a class **2-441**

bandwidth allocation for a class **2-41, 2-59**

creating a service policy **2-422**

marking **2-428**

strict priority queueing (LLQ) **2-390**

policy maps

creating **2-374**

marking **2-428**

traffic classifications

trust states **2-820**

setting the trust state **2-404**

specifying flow-based match criteria **2-337**

Supervisor Engine 6-E

setting CoS **2-430**

setting DSCP **2-433**

setting precedence values **2-436**

QoS CoS

configuring for tunneled Layer 2 protocol packets **2-293**

quality of service

See QoS

question command **1-1**

queueing information

displaying **2-665**

queue limiting

configuring packet limits **2-406**

R

Rapid PVST

switching between PVST and MST **2-738**

re-authenticating 802.1X-enabled ports **2-163**

re-authentication

periodic **2-164**

set the time **2-166**

reauthentication, enabling **2-30**

reboots

restoring bindings across **2-223**

redundancy

accessing the main CPU **2-408**

changing from active to standby supervisor engine **2-412**

displaying information **2-669**

displaying ISSU config-sync failure information **2-673**

displaying redundancy facility information **2-669**

displaying RF client list **2-669**

displaying RF operational counters **2-669**

displaying RF states **2-669**

enabling automatic synchronization **2-40**

forcing switchover to standby supervisor engine **2-412**

mismatched command listing **2-410**

set the mode **2-344**

- synchronizing the route processor configurations [2-331](#)
 - related documentation [1-xix](#)
 - remote SPAN
 - See RSPAN
 - renew commands
 - ip dhcp snooping database [2-416](#)
 - resetting PVLAN trunk
 - setting switchport to trunk [2-786](#)
 - retry failed authentication, configuring [2-22](#)
 - rj45 connector, selecting the connector [2-343](#)
 - ROM monitor mode
 - summary [1-6](#)
 - Route Processor Redundancy
 - See redundancy
 - RPF
 - disabling IPv4 exists-only checks [2-264](#)
 - enabling IPv4 exists-only checks [2-264](#)
 - RPR
 - set the redundancy mode [2-344](#)
 - RSPAN
 - converting VLAN to RSPAN VLAN [2-415](#)
 - displaying list [2-710](#)
-
- S**
 - saving configuration changes [1-11](#)
 - secure address, configuring [2-378](#)
 - secure ports, limitations [2-792](#)
 - server (AAA) alive actions, configuring [2-22](#)
 - server (AAA) dead actions, configuring [2-22](#)
 - service-policy command (policy-map class) [2-422](#)
 - session classification, defining [2-25](#)
 - set the redundancy mode [2-344](#)
 - sfp connector, selecting the connector [2-343](#)
 - shape command [2-441](#)
 - show authentication interface command [2-449](#)
 - show authentication registration command [2-449](#)
 - show authentication sessions command [2-449](#)
 - show commands
 - filtering parameters [1-7](#)
 - searching and filtering [1-6](#)
 - show platform commands [1-11](#)
 - show energlywise command [2-486](#)
 - show mab command [2-606](#)
 - Simple Network Management Protocol
 - See SNMP
 - single-character patterns
 - special characters [1-7](#)
 - single-host, setting [2-25](#)
 - slaveslot0
 - displaying information on the standby supervisor [2-680](#)
 - slot0
 - displaying information about the system [2-682](#)
 - SNMP
 - debugging spanning tree activities [2-121](#)
 - ifIndex persistence
 - clearing SNMP ifIndex commands [2-717](#)
 - compress SNMP ifIndex table format [2-726](#)
 - disabling globally [2-725](#)
 - disabling on an interface [2-719](#)
 - enabling globally [2-725](#)
 - enabling on an interface [2-719](#)
 - informs
 - disabling [2-721](#)
 - enabling [2-721](#)
 - traps
 - configuring to send when storm occurs [2-764](#)
 - disabling [2-721](#)
 - enabling [2-721](#)
 - mac-notification
 - adding [2-727](#)
 - removing [2-727](#)
 - SPAN commands
 - configuring a SPAN session to monitor [2-346](#)
 - displaying SPAN session information [2-694, 2-766](#)
 - SPAN enhancements

- displaying status **2-633**
- Spanning Tree Protocol
 - See STP
 - SPAN session
 - displaying session information **2-633**
 - filter ACLs **2-346**
 - specify encapsulation type **2-346**
 - turn off host learning based on ingress packets **2-346**
 - special characters
 - anchoring, table **1-10**
 - SSO **2-344**
 - standard desktop
 - enabling Cisco-recommended features **2-320**
 - standard desktop and Cisco IP phone
 - enabling Cisco-recommended features **2-322**
 - sticky address, configuring **2-379**
 - sticky-ARP
 - disabling on PVLANS **2-259**
 - enabling on PVLANS **2-259**
 - sticky port
 - deleting **2-86**
 - enabling security **2-791**
 - storm control
 - configuring for action when storm occurs **2-764**
 - disabling suppression mode **2-493**
 - displaying settings **2-692**
 - enabling **2-764**
 - enabling broadcast **2-764, 2-766**
 - enabling multicast **2-764, 2-766**
 - enabling suppression mode **2-493**
 - enabling timer to recover from error disable **2-186**
 - enabling unicast **2-764, 2-766**
 - multicast, enabling **2-766**
 - setting high and low levels **2-764**
 - setting suppression level **2-493**
 - STP
 - configuring link type for a port **2-736**
 - configuring tunneling encapsulation rate **2-296**
 - debugging all activities **2-121**
 - debugging spanning tree activities **2-121**
 - debugging spanning tree BackboneFast events **2-123**
 - debugging spanning tree UplinkFast **2-126**
 - detecting misconfiguration **2-733**
 - displaying active interfaces only **2-684**
 - displaying BackboneFast status **2-684**
 - displaying bridge status and configuration **2-684**
 - displaying spanning tree debug messages **2-121**
 - displaying summary of interface information **2-684**
 - enabling BPDU filtering by default on all PortFast ports **2-752**
 - enabling BPDU filtering on an interface **2-729**
 - enabling BPDU guard by default on all PortFast ports **2-754**
 - enabling BPDU guard on an interface **2-731**
 - enabling extended system ID **2-734**
 - enabling loop guard as a default on all ports **2-737**
 - enabling PortFast by default on all access ports **2-755**
 - enabling PortFast mode **2-750**
 - enabling protocol tunneling for **2-291**
 - enabling root guard **2-735**
 - enabling spanning tree BackboneFast **2-728**
 - enabling spanning tree on a per VLAN basis **2-759**
 - enabling spanning tree UplinkFast **2-757**
 - setting an interface priority **2-756**
 - setting drop threshold for **2-294**
 - setting pathcost **2-732**
 - setting the default pathcost calculation method **2-749**
 - subinterface configuration mode, summary **1-6**
 - SVI
 - creating a Layer 3 interface on a VLAN **2-206**
 - switching characteristics
 - excluding from link-up calculation **2-783**
 - modifying **2-783**
 - returning to interfaces
 - capture function **2-783**
 - switchport **2-807**
 - switchport interfaces
 - displaying status of Layer 3 port **2-525**

displaying status of native VLAN tagging **2-525**
 switch shim
 debugging **2-124**
 disabling debugging **2-124**
 switch to router connection
 enabling Cisco-recommended features **2-324**
 switch to switch connection
 enabling Cisco-recommended features **2-326**
 switch virtual interface
 See SVI
 sw-vlan **2-127**
 system prompts **1-5**

T

Tab key
 command completion **1-1**
 tables
 characters with special meaning **1-7**
 mac access-list extended subcommands **2-308**
 multipliers **1-9**
 relationship between duplex and speed commands **2-762**
 show cable-diagnostics tdr command output fields **2-459**
 show cdp neighbors detail field descriptions **2-467**
 show cdp neighbors field descriptions **2-466**
 show ip dhcp snooping command output **2-450, 2-606**
 show ip interface field descriptions **2-560**
 show policy-map control-plane field descriptions **2-640**
 show vlan command output fields **2-709**
 show vtp command output fields **2-714**
 special characters **1-9**
 special characters used for anchoring **1-10**
 speed command options **2-337, 2-762**
 valid interface types **2-201**
 TAC
 displaying information useful to TAC **2-695**

TCAM
 debugging spanning tree activities **2-121**
 TDR
 displaying cable diagnostic test results **2-458**
 test condition of copper cables **2-812**
 temperature readings
 displaying information **2-490**
 timer information **2-494**
 traffic monitor
 display status **2-606**
 traffic shaping
 enable on an interface **2-443**
 traps, enabling **2-721**
 trunk encapsulation
 setting format **2-807**
 trunk interfaces
 displaying trunk interfaces information **2-532**
 trust state
 setting **2-213**
 tunnel ports
 displaying information about Layer 2 protocol **2-600**
 TX queues
 allocating bandwidth **2-822**
 returning to default values **2-822**
 setting priority to high **2-822**
 specifying burst size **2-822**
 specifying traffic rate **2-822**

U

UDLD
 displaying administrative and operational status **2-697**
 enabling by default on all fiber interfaces **2-824**
 enabling on an individual interface **2-826**
 preventing a fiber interface from being enabled **2-826**
 resetting all shutdown ports **2-828**
 setting the message timer **2-824**

unicast

- counters **2-94**
- Unidirectional Link Detection
See UDLL
- unidirection port control, changing from bidirectional **2-19**
- unknown multicast traffic, preventing **2-785**
- unknown unicast traffic, preventing **2-785**
- user EXEC mode, summary **1-5**
- username
setting password and privilege level **2-829**
-
- V**
- VACLs
access-group mode **2-6**
applying VLAN access maps **2-844**
displaying VLAN access map information **2-703**
specifying an action in a VLAN access map **2-13**
specifying the match clause for a VLAN access-map sequence **2-332**
using a VLAN filter **2-844**
- VLAN
applying an ARP ACL **2-207**
configuring **2-833**
configuring service policies **2-838**
converting to RSPAN VLAN **2-415**
displaying CEF information **2-539**
displaying CEF next-hop information **2-539**
displaying information on switch interfaces **2-550, 2-554**
displaying information on VLAN switch interfaces **2-557**
displaying information sorted by group IP address **2-550, 2-554**
displaying IP address and version information **2-550, 2-554**
displaying Layer 2 VLAN information **2-699**
displaying statistical information **2-631**
displaying VLAN information **2-701**
enabling dynamic ARP inspection **2-216**
enabling Explicit Host Tracking **2-246**
enabling guest per-port **2-152**
enabling guest VLAN supplicant **2-146, 2-153**
entering VLAN configuration mode **2-838, 2-840**
native frames
enabling tagging on all 802.1Q trunk ports **2-842**
pruning the list for VTP **2-807**
setting the list of allowed **2-807**
- VLAN Access Control Lists
See VACLs
- VLAN access map
See VACLs
- VLAN database
resetting **2-417**
- VLAN debugging
limiting output **2-102**
- VLAN link-up calculation
excluding a switch port **2-783**
including a switch port **2-783**
- VLAN manager
debugging **2-127**
disabling debugging **2-127**
IOS file system error tests
debugging **2-128**
disabling debugging **2-128**
- VLAN Query Protocol
See VQP
- VLAN query protocol (VQPC)
debugging **2-134**
- VLANs
clearing
counters **2-90**
clearing hardware logic **2-68**
configuring
internal allocation scheme **2-845**
displaying
internal VLAN allocation information **2-706**
RSPAN VLANs **2-710**
entering VLAN configuration mode **2-840**

VMPS

- configuring servers [2-849](#)
- reconfirming dynamic VLAN assignments [2-134](#),
[2-847](#)

voice VLANs

- enabling [2-779](#)

VoIP

- configuring auto-QoS [2-37](#)

VQP

- per-server retry count [2-848](#)
- reconfirming dynamic VLAN assignments [2-134](#),
[2-847](#)

VTP

- configuring the administrative domain name [2-853](#)
- configuring the device in VTP client mode [2-852](#)
- configuring the device in VTP server mode [2-856](#)
- configuring the device in VTP transparent mode [2-857](#)
- configuring tunnel encapsulation rate [2-296](#)
- creating a VTP domain password [2-854](#)
- displaying domain information [2-713](#)
- displaying statistics information [2-713](#)
- enabling protocol tunneling for [2-291](#)
- enabling pruning in the VLAN database [2-855](#)
- enabling VTP version 2 mode [2-858](#)
- modifying the VTP configuration storage file name [2-851](#)
- set drop threshold for [2-294](#)

VTP protocol code

- activating debug messages [2-131](#)
- deactivating debug messages [2-131](#)

WWebauth fallback, enabling [2-24](#)

