



Cisco Unity Connection SRSV Supported Platforms List

This chapter contains the following sections:

- [Hardware Supported by Unity Connection SRSV, page 3-1](#)
- [Specifications for Virtual Platform Overlays Supported by Unity Connection SRSV, page 3-2](#)

Hardware Supported by Unity Connection SRSV

This section lists the supported hardware platforms and the minimum Cisco IOS software release required to support the hardware platform Cisco Unity Connection SRSV.

Table 3-1 *Specifications for Cisco Unity Connection SRSV*

Cisco Platform	Unity Connection SRSV on SM-SRE-900-K9	Unity Connection SRSV on SM-SRE-910-K9
Cisco 2911	15.1(4)M	15.1(4)M
Cisco 2921		
Cisco 2951		
Cisco 3925	15.1(4)M	15.1(4)M
Cisco 3945		
Cisco 3925E	15.1(4)M	15.1(4)M
Cisco 3945E		



Note

A different Cisco IOS software release may be required depending on the version of Cisco Unified Communications Manager Express or Cisco Unified Survivable Remote Site Telephony (SRST) being used. For more information refer to Cisco Unified Communications Manager Express documentation available at <http://www.cisco.com/en/US/products/sw/voicesw/ps4625/index.html>.

Specifications for Virtual Platform Overlays Supported by Unity Connection SRSV

This section lists the supported hardware platforms and the minimum Cisco IOS software release required to support the hardware platform Cisco Unity Connection SRSV.

Table 3-2 **Specifications for Virtual Platform Overlays for Unity Connection SRSV**

	Virtual Platform Overlay
Minimum Unity Connection SRSV Version	9.1(1)
vCPU (Number of Virtual Processors) Cores and Speed per Core	<i>Unity Connection 9.1(1) and later only: 1@a minimum of 1.8 GHz</i>
vRAM (Amount of Virtual RAM)	4 GB
vDisk (Size of Virtual Hard Disks)	1x160GB
Total number of available voice ports	12
Total number of users with mailboxes	500
Approximate message storage, G-711 codec, minutes	72,944
Number of public distribution lists	500
Number of Call Handlers	200
Number of languages supported	2