

# AireOS to Catalyst 9800 Wireless Controller Feature Comparison Matrix

This document lists support information for various AireOS features mapped to Cisco Catalyst 9800 Wireless Controller in Cisco IOS XE releases. This document is updated for Cisco IOS XE Bengaluru 17.6.1

Note: Last release for Wave 1 APs is 17.3.x

## Supported Features

Category	Feature Name	Platform	
		AireOS	Catalyst 9800
Infrastructure	CAPWAP Support	YES	16.10.1
	CAPWAP data keep-alive support	YES	16.10.1
	VLAN tagging support for CAPWAP packets	YES	16.10.1
	TACACS+ support	YES	16.10.1
	LSC	YES	16.10.1
	AP image pre-download	YES	16.10.1
	Support for interface groups	YES	16.10.1
	SSH File Transfer Protocol (SFTP)	YES	16.10.1
	Encryption of Neighbor Discovery Packet (NDP) packets	YES	16.10.1
	Support for APs behind NAT	YES	16.10.1
	DHCP Proxy	YES	16.10.1
	DHCP opt 60 + vendor name	YES	16.10.1
	DHCP opt 82 (AP_Eth_MAC)	YES	16.10.1
	VLAN select per DHCP dirty	YES	16.10.1
	LAG	YES	16.10.1
	RADIUS server overwrite interface	YES	16.10.1
	RADIUS selection by realm	YES	16.10.1
	Support for NTP Authentication	YES	16.10.1
	Load balancing per ethernet port utilization	YES	16.10.1
	Support for WLC webadmin SHA256 self-signed certificate	YES (8.10)	16.10.1
	Ability to upload the output of the show run-config to a FTP server by CLI	YES	16.10.1
	Ethernet VLAN tag on AP	YES	16.10.1
	New TACACS+ command sets	YES	16.10.1
	Ability to choose if local management users are Telnet capable or not	YES	16.10.1
	Ping from dynamic interface (extended ping)	YES	16.10.1
	Out of the box config persistent option	YES	16.10.1
	Ability to enable/disable AUX ethernet port on AP	YES	16.10.1

2700		
CLI addition - config ap cert-expiry-ignore {mic   ssc} enable	YES	16.10.1
Support for management user session accounting records	YES	16.10.1
Graphical User Interface (GUI) Service Port SSO	YES	16.10.1
WLC Service Port support with SSO enabled	YES	16.10.1
IPv6 support on 802.11ac Wave 2 APs	YES	16.10.1
Ability to disable syslog server per AP and/or global	YES	16.10.1
Maximum number of characters of mgmt user password length increased from 24 to 127	YES	16.10.1
Support for Secure Shell (SSH) standard login interface	YES	16.10.1
per AP group NTP server	YES	16.10.1
Login Banner File	YES	16.10.1
Telnet disabled by default	YES	16.10.1
Configurable timer when AP tries to join primary/secondary/tertiary WLC (Primed Join timeout)	YES	16.10.1
Ability to clear internal DHCP lease	YES	16.10.1
Ability to disable old crash files from WLC (clear crash-files...)	YES	16.10.1
DHCP opt 82 as American Standard Code for Information Interchange (ASCII) instead of binary	YES	16.10.1
IPv6 - Block of Router Advertisement (RA) from controller and AP	YES	16.10.1
IPv6 address visibility per client	YES	16.10.1
Extra DHCP opt 82 attributes	YES	16.10.1
Ability to backup 3rd party certificates from WLC	YES	16.10.1
Ping with source interface	YES	16.10.1
Ability to enable Telnet/SSH for all APs	YES	16.10.1
Link Aggregation (LAG) in Transition support	YES	16.10.1
Network Time Protocol (NTP) version 4 support	YES	16.10.1
RADIUS and TACACS+ DNS	YES	16.12.1
DHCP opt 82, sub-option 5 and sub-option 151/152	YES	16.12.1
Link Layer Discovery Protocol (LLDP) support	YES	16.12.1
Sending access points events through radius accounting	YES	17.1.1
IPv6 - Neighbor Discovery Protocol (NDP) proxy and rate limit of IPv6 packets	YES	17.2.1
Viewing AP LLDP Neighbor Info from the eWLC	YES	17.3.2
eWLC DHCP option-82 remote-id	YES	17.3.3
C9800 DHCP Behaviour change feature	YES	17.3.3

	Intermediate CA support for AP authentication	YES	17.5.1
	Support for both MIC and LSC APs to join the same C9800	YES	17.5.1
	9800 Special Character handling	YES	17.5.1
	Sourcing DHCP relay packets using SrcIP SVI but vlan tag of wireless mgmt interface	YES	17.5.1
	Additional PKI OPER information required for Radsec-WLC integration project	YES	17.5.1
	Control plane traffic out of SP port	YES	17.6.1
<b>Security &amp; Authentication</b>	802.1x + web authentication support	YES	16.10.1
	Conditional Web Redirect with 802.1x Authentication	YES	16.10.1
	Identity Pre-Shared Key (PSK)	YES	16.10.1
	Multiple Pre-Shared Key (MPSK)	YES	16.10.1
	Local Authentication	YES	16.10.1
	Local Web Authentication / Central Web Authentication Support (LWA/CWA)	YES	16.10.1
	Web Auth on MAC filter failure	YES	16.10.1
	Support for pre-auth ACL to block DNS for web authenticated clients	YES	16.10.1
	Support for Captive portal bypass	YES	16.10.1
	CNAME - IPv6 Support (PreAuth ACLs with IPv6)	YES	16.10.1
	User idle timeout per WLAN	YES	16.10.1
	User idle threshold per WLAN	YES	16.10.1
	802.11w - MFP	YES	16.10.1
	802.11k	YES	16.10.1
	Sleeping client support on web passthrough WLAN	YES	16.10.1
	Support for TLSv1.2 for web authentication and WebAdmin	YES	16.10.1
	Support to enable Network Admission Control-RADIUS (NAC-RADIUS) on Pre-Shared Key (PSK) wireless network with CWA	YES	16.10.1
	Flexibility for Cisco Centralized Key Management (CCKM) max timestamp validation	YES	16.10.1
	Apple Captive Bypass for IOS 7	YES	16.10.1
	Ability to change the SSID Name	YES	16.10.1
	Wi-Fi Protected Access/TKIP only configurable through CLI	YES	16.10.1
	Configurable webauth required timeout	YES	16.10.1
	WLC 5520/8510/8540 - Support Local EAP	YES	16.10.1
	TKIP Support for APs 1810/1830/1850/2800/3800	YES	16.10.1
ISE Simplification - Day0 RADIUS ISE default configuration	YES	16.10.1	
ISE Simplification - Default RADIUS configuration for ISE server	YES	16.10.1	

	Option to disable webauth success page	YES	16.10.1
	Splash page configuration per AP group (So same SSID can have multiple splash pages)	YES	16.10.1
	Temporal Key Integrity Protocol (TKIP) support for APs 2800/3800	YES	16.10.1
	Captive portal bypass per Service Set Identifier (SSID)	YES	16.10.1
	AP Authorization	YES	16.10.1
	Can specify delimiter for MAC address in auth/acct access-request	YES	16.10.1
	MAC addresses in called-station-id and calling-station-id now as lower case	YES	16.10.1
	Attributes for Called Station ID	YES	16.10.1
	ISE - Support for Guest Originating URL	YES	16.10.1
	Custom Network access server identifier (NAS-ID) for Remote Authentication Dial-In User Service (RADIUS) accounting	YES	16.10.1
	Configurable EAPOL-key timeout for FlexConnect Groups - local authentication	YES	16.10.1 (Global level knob)
	WPA3 support	YES	16.12.1
	Support Wired Guest access	YES	16.12.1
	Wired client Single Sign On (SSO)	YES	16.12.1
	Enhanced Open support	YES	17.1.1
	Identity PSK peer2peer blocking	YES	17.1.1
	Wave 2 APs - Support for Wired 802.1x Extensible Authentication Protocol-Transport Layer Security (EAP-TLS) and Protected EAP (PEAP)	YES	17.2.1
	Web Auth needs a separate HTTPS Server from MGMT GUI and Web-Auth	YES	17.3.1
	Tracking of client with locally administered MAC address	YES	17.3.1
	WPA/WPA2-PSK-WebAuth on MAC filter fail	YES	17.5.1
	Knob to disable Random MAC Clients	YES	17.5.1
	LDAP authentication using sAMAccountName on WLC-9800	YES	17.6.1
<b>RF &amp; Radio</b>	Band Select	YES	16.10.1
	Band Select mid-RSSI support	YES	16.10.1
	DFS	YES	16.10.1
	RFID tags support	YES	16.10.1
	Coverage Hole Detection per WLAN	YES	16.10.1
	Dynamic Bandwidth Selection (DBS)	YES	16.10.1
	Flexible DFS (Dynamic frequency selection)	YES	16.10.1
	FRA	YES	16.10.1
	Load Balancing	YES	16.10.1

Off-Channel scan defer	YES	16.10.1
Ability to set up upper and lower limits on TX power for RRM	YES	16.10.1
CleanAir	YES	16.10.1
CleanAir - Event-Driven Radio Resource Management (EDRRM)	YES	16.10.1
CleanAir - Unclassified Interference Threshold/Trap	YES	16.10.1
RF static group leader	YES	16.10.1
RF Profiles	YES	16.10.1
Default RF Profiles for High Density	YES	16.10.1
Dynamic Channel Assignment (DCA) in RF profiles	YES	16.10.1
Transmit Power Control (TPC) min/max values with bands enabled	YES	16.10.1
Radio monitor for 80MHz	YES	16.10.1
Support for -B domain APs	YES	16.10.1
Regulatory Domain -S change	YES	16.10.1
Support for AP -B domain	YES	16.10.1
Support of regulatory domain -K for Malaysia	YES	16.10.1
Command to Configure Smart Dynamic Frequency Selection (DFS) (config 802.11h smart-dfs {enable   disable})	YES	16.10.1
DCA algorithm redesigned to prevent pinning and cascading	YES	16.10.1
Event Driven-Radio Resource Management (ED-RRM) triggered by Wi-Fi interference too	YES	16.10.1
Increased Channel and Transmit (Tx) Power Support for some countries	YES	16.10.1
2800/3800 - Support for Client-Aware Flexible Radio Assignment (FRA)	YES	16.10.1
Support for HE PHY layer (and new MCS rates)	YES	16.11.1
20/40/80MHz off-channel scan on serving channel	YES	16.12.1
Support for -P domain	YES	16.12.1
Added regulatory domain -S for Hong Kong	YES	16.12.1
Country code KR is changed to KE (for Korea)	YES	16.12.1
Country code JP (for Japan) is removed	YES	16.12.1
Support for -F domain (Indonesia)	YES	16.12.1
Configuration of ClientLink only through CLI	YES	16.12.1
Support for -B domain APs	YES	16.12.1
Introduced -Z domain (Australia and New Zealand)	YES	16.12.1
China -H domain migration (allow indoor use of 5150 MHz to 5350 MHz)	YES	16.12.1
Added -R regulatory domain	YES	16.12.1
Regulatory approval for Chile and Russia	YES	16.12.1
Beamforming (also called ClientLink)	YES	16.12.1

	TPCv1 Channel Aware Mode	YES	16.12.1
	CleanAir - Persistent Device Avoidance	YES	17.1.1
	Support for -M regulatory domain in AP Industrial Wireless Local Area Network (IWLAN) 3700	YES	17.1.1s
	AP 3700 - Flexible Antenna port support	YES	17.1.1s
	Dropped channels 120, 124, 116 and 132	YES	17.3.1
	BLE Management/Scanning/Telemetry	YES	17.3.1
	Configurable -Q indoor & outdoor domain support for IW3702	YES	17.3.1
	Support for -F regulatory domain for Indonesia on IW3702	YES	17.3.1
	Support for -M regulatory domain for Saudi Arabia, Kuwait, Qatar, Iraq on IW3702	YES	17.3.1
	Flexible Antenna Port configuration for IW3702	YES	17.3.1
	3rd Radio in Monitor Mode	YES	17.3.1
	Spectrum intelligence for AX9115	YES	17.3.1
	Tri-radio Support(dynamic) for AX9130	YES	17.3.1
	DL OFDMA (37 users) Support for AX9130	YES	17.3.1
	TWT Feature Support for BRCM Aps	YES	17.4.1
	Capability to enable/disable 11ax features per WLAN	YES	17.5.1
	Increased 11ax OFDMA users on 9105/9115/9120	YES	17.5.1
	Downlink MU-MIMO support Catalyst 9105/9115/9120 series Aps	YES	17.5.1
	wLPs scanning with Third Radio in AP 4800	YES	17.5.1
	Provide granular reasons for power and channel change in Cisco DNA Assurance	YES	17.5.1
	Performance improvements in Catalyst 9105/9115 and 9120 APs with enhancement in advanced scheduler.	YES	17.5.1
	Regulatory: Add support for TDWR channels (120, 124, 128) for "-E" regulatory domain	YES	17.6.1
	Regulatory domain reduction	YES	17.6.1
<b>Mobility</b>	Mobiity - Foreign/Anchor	YES	16.10.1
	Mobility - Symetric tunneling	YES	16.10.1
	Opportunistic Key Caching (OKC) for Flex groups	YES	16.10.1
	Roam between WLC for static-IP clients (static-ip tunneling)	YES	16.10.1
	802.11r for AP in local mode (Fast Roaming)	YES	16.10.1
	Optimized roaming	YES	16.10.1
	Optimized roaming + 802.11v	YES	16.10.1
	Seamless roaming with Inter-release controller mobility (IRCM)	YES	16.10.1
	Ability to enable/disable Network Mobility Services Protocol (NMSP) port (config nmsp service	YES	16.10.1

	enable/disable)		
	Aeroscout removal from MSE	YES	16.12.1
	Rest Application Programming Interface (API) support on MSE	YES	16.12.1
	MSE exposes the RSSI for RFID tags	YES	16.12.1
	CSDL CT1674:SEC-CRY-PRIM-4: Mobility Cipher Configuration	YES	17.5.1
<b>Mesh</b>	Mesh Ethernet bridging	YES	16.10.1
	Mesh ethernet VLAN tagging	YES	16.10.1
	Mesh multicast mode for ethernet bridged clients (in/in-out)	YES	16.10.1
	Mesh multicast support for roaming L2/L3	YES	16.10.1
	Mesh - bridge data rate auto	YES	16.10.1
	Mesh - preferred parent selection	YES	16.10.1
	Mesh - 2.4 GHz as mesh backhaul	YES	16.10.1
	Mesh - Universal client access	YES	16.10.1
	Mesh - Native VLAN not sent to Mesh Access Point (MAP) Ethernet port when VLAN transparent mode enabled	YES	16.10.1
	Mesh LSC authentication (MAC bypass)	YES	16.10.1
	Mesh Daisy Chain	YES	16.10.1
	Mesh - Fast Convergence	YES	16.10.1
	Mesh - Multi-country WLC support for mesh APs	YES	16.10.1
	Mesh - RRM on 5GHz RAP	YES	16.10.1
	Multi Regulatory Domain (Country code) WLC support for Mesh APs	YES	16.10.1
	Mesh Convergence	YES	16.10.1
	Mesh - PSK provision support for Mesh Networks	YES	16.10.1
	Mesh Off Channel background Scanning (IOS AP)	YES	16.10.1
	Air Time Fairness (ATF) on mesh	YES	16.10.1
	Mesh - Can disable intrusion detection system (IDS) on outdoor Mesh	YES	16.10.1
	Mesh APs can be pinged before they join a controller	YES	16.10.1
	Mesh preferred parent per GUI	YES	16.10.1
	Mesh - 2.4 GHz mesh backhaul for Israel	YES	16.10.1
Mesh mode and Mesh ethernet bridging support on AP 1560	YES	16.10.1	
Network Address Translation / Port Address Translation (NAT/PAT) on RAP (Flex+Bridge AP mode)	YES	16.11.1	
Dynamic Host Configuration Protocol (DHCP) internal server on Root AP (RAP) (Flex+Bridge AP mode)	YES	16.11.1	
Mesh limited voice support (indoor)	YES	16.11.1	

	Mesh mode on wave 2 APs	YES	17.1.1
	AP 3700 - Daisy chain is supported	YES	17.1.1s
	Mesh - 2.4 GHz mesh backhaul for Israel	YES	17.3.1
	Mesh Off Channel background Scanning (IOS AP)	YES	17.3.1
	Enhanced mesh convergence	YES	17.3.1
	RAP Ethernet Daisy Chain on IW3702	YES	17.3.1
<b>Security</b>	Rogue detection per AP	YES	16.10.1
	Rogue auto-containment level	YES	16.10.1
	Rogue - Minimum RSSI for rogue detection/classification	YES	16.10.1
	Rogue - Rogue detection report interval	YES	16.10.1
	Rogue - Transient Rogue Interval	YES	16.10.1
	Rogue - Rogue AP Ignore List	YES	16.10.1
	Rogue Policy per security level	YES	16.10.1
	Rogue AP validation against AAA server	YES	16.10.1
	Rogue Client Information Detection for Auto Switch Port Trace (SPT)	YES	16.10.1
	WIPS - auto SPT	YES	16.10.1
	wIPS Attack containment	YES	16.10.1
	Password policies (Product Security Baseline [PSB])	YES	16.10.1
	Data rate selection for rogue containment	YES	16.10.1
	Validate rogue clients against Mobility Service Engine (MSE)	YES	16.10.1
	Wildcard SSID per rogue policy	YES	16.10.1
	Set rogue policy to delete a rogue from WLC database	YES	16.10.1
	Maximum RSSI for friendly rogue Aps	YES	16.10.1
	TrustSec enhancements	YES	16.10.1
	Support for certificates generated using OpenSSL v1.0	YES	16.10.1
	Enhanced rogue containment	YES	16.10.1
	Rogue enhancement	YES	16.12.1
	Automatically assign number of APs to contain a rogue	YES	16.12.1
	Online Certificate Status Protocol (OCSP)	YES	16.12.1
	Wireless Intrusion Prevention System (wIPS) support for 40/80 (MegaHertz) MHz and transmit capability	YES	17.1.1s
	Enhanced wIPS Support for Hyperlocation Module with Advanced Security	YES	17.1.1s
	WIPS: Advanced Security Enhancements on 9800 WLC (RTS/CTS)	YES	17.3.1
	Rogue enhancement on 9800 WLC	YES	17.3.1
	Hotspot 2.0 - Passpoint R3 WFA Certification	YES	17.3.1
	Support to provision SuiteB 192bit AVPs	YES	17.5.1



	Rejection on wrong WLAN ID on SSID	YES	17.5.1
	Disable clients with Random MAC Address	YES	17.5.1
	WIPS Additional Signatures	YES	17.6.1
	AWIPS Enhancement: Logging of the Rogue and AWIPS alarms from Controller	YES	17.6.1
	Fallback for AAA Overridden VLAN	YES	17.6.1
	AP PnP Onboarding with Dot1x Authentication	YES	17.6.1
<b>Resiliency</b>	HA AP SSO	YES	16.10.1
	HA Client SSO and Redundancy Port (RP) through L2 switch	YES	16.10.1
	HA-SSO Configurable keep-alive timers/retries	YES	16.10.1
	Fast AP failover	YES	16.10.1
	HA-SSO bulk sync status	YES	16.10.1
	HA-SSO support for 802.11ac	YES	16.10.1
	HA SSO (HA-SSO) - Traps for events (when WLC turns hot standby, bulk sync complete)	YES	16.10.1
	HA - show redundancy peer-system { statistics   cpu   memory }	YES	16.10.1
	Ability to disable AP HA Fallback	YES	16.10.1
	HA-SSO Support for internal DHCP server	YES	16.10.1
	HA-SSO Support for sleeping client feature	YES	16.10.1
	HA-SSO new debugs/shows	YES	16.12.1
	Internet Protocol security (IPSec) encryption for High Availability (HA)	YES	16.12.1
	HA-SSO replace peer Redundancy Management Interface (RMI) Internet Control Message Protocol (ICMP) ping with UDP message	YES	17.1.1
	HA SSO - Automatic recover from maintenance mode after network converges	YES	17.1.1
	HA-SSO default gateway reachability check enhancement	YES	17.1.1
	SSO enhancements on the GW check	YES	17.2.1
	Out of band access to standby WLC in a SSO pair	YES	17.3.1
	Gateway IP Check with Native IPv6(RMI IPv6)	YES	17.3.2
	Configuration of Gateway Failure Detection Interval	YES	17.3.2
	HA Parity	YES	17.3.3
	Gateway IP Check - HA parity with AirOS ( Network error handling )	YES	17.3.5
	RMI over IPv6	YES	17.4.1
	RMI/Default GW Enhancements	YES	17.4.1
	Standby Monitoring Enhancements	YES	17.5.1
	Default Gateway IP Reachability Check (AireOS Parity)	YES	17.5.1
	HA Management - Interface Status of the	YES	17.6.1

	Standby through the Active using SNMP		
<b>Flex</b>	Flex Local Authentication	YES	16.10.1
	Flex groups and local radius server	YES	16.10.1
	Flex fault tolerance	YES	16.10.1
	Flexconnect - P2P Blocking	YES	16.10.1
	Flexconnect - FlexConnect efficient AP Upgrade	YES	16.10.1
	Flexconnect - FlexConnect ACLs	YES	16.10.1
	Flexconnect - AAA Override to Assign Dynamic VLANs	YES	16.10.1
	Flexconnect - Fast Roam for Voice Clients	YES	16.10.1
	External Web-Auth for Local Switching FlexConnect	YES	16.10.1
	FlexConnect - Split tunneling	YES	16.10.1
	FlexConnect - 802.11r (Fast Transition) support in Central/Local switching	YES	16.10.1
	FlexConnect - Network Address Translation (NAT) and Port Address Translation (PAT) on locally switched WLAN	YES	16.10.1
	FlexConnect - WGB/Universal WGB support in FlexConnect Locally Switched mode	YES	16.10.1
	FlexConnect - VLAN-based local and central switching	YES	16.10.1
	Protected Extensible Authentication Protocol (PEAP) and Extensible Authentication Protocol-Transport Layer Security (EAP-TLS) for FlexConnect (Local Auth)	YES	16.10.1
	WLAN to VLAN maps for FlexConnect Groups and APs	YES	16.10.1
	Per client ACL on FlexConnect APs	YES	16.10.1
	QoS AAA Override for FlexConnect Local Switching	YES	16.10.1
	FlexConnect - Client load balancing support	YES	16.10.1
	FlexConnect VideoStream in local switching	YES	16.10.1
	FlexConnect AP joins WLC's multicast group	YES	16.10.1
	FlexConnect proxy ARP	YES	16.10.1
	FlexConnect + Mesh (bridge)	YES	16.10.1
	AVC for FlexConnect	YES	16.10.1
	FlexConnect Group VLAN support	YES	16.10.1
	FlexConnect AAA Override of VLAN name	YES	16.10.1
	Dynamic Bandwidth Selection (DBS) with Flex DFS	YES	16.10.1
	FlexConnect - Support TrustSec	YES	16.10.1
	FlexConnect IPv4 pre-auth DNS ACLs	YES	16.10.1
	VLAN transparent feature bridges all non-defined VLANs on flexconnect-mesh	YES	16.10.1
Support for FlexConnect AVC on vWLC	YES	16.10.1	
FlexConnect - Default FlexConnect group	YES	16.10.1	

	FlexConnect - AP will only join CAPWAP multicast group if it has a centrally switched WLAN	YES	16.10.1
	Wave 2 APs - Support for FlexConnect Proxy Address Resolution Protocol (ARP)	YES	16.10.1
	Wave 2 APs - Support for FlexConnect limit clients per radio / WLAN	YES	16.10.1
	Wave 2 APs - Support for FlexConnect VLAN name Authentication, Authorization, and Accounting (AAA) override	YES	16.10.1
	Support for RADIUS creation within FlexConnect groups (CLI changed)	YES	16.10.1
	FlexConnect on stand-alone can keep performing rogue containment	YES	16.10.1
	FlexConnect - Convert AP mode from Local to FlexConnect without reboot	YES	16.10.1
	Proxy ARP support on FlexConnect Local Switching 802.11ac Wave 2 APs.	YES	16.10.1
	FlexConnect NAT/PAT support for central DHCP on 802.11ac Wave 2 APs	YES	16.10.1
	Flexconnect AAA Quality of Service (QoS) override per client support on 802.11ac Wave 2 APs	YES	16.10.1
	Wave 2 APs - Support for FlexConnect IPv6 ACL for or web authentication	YES	16.11.1
	Wave 2 APs - Support for Management Frame Protection (MFP) (Not supported on 1800 series APs)	YES	16.12.1
	Flexconnect IPv6 EoGRE Tunnel support	YES	16.12.1
	FlexConnect - Support for 802.11u (HotSpot 2.0)	YES	16.12.1
	11w on Flex and Mesh APs	YES	16.12.1
	Flex Connect Overlap IP Address	NO	17.3.3
<b>Services</b>	Multiple WLANs with the same SSID	YES	16.10.1
	Transmission Control Protocol - Maximum Segment Size (TCP MSS) Adjustment	YES	16.10.1
	Rate shifting	YES	16.10.1
	Video/media stream	YES	16.10.1
	VLAN select per foreign WLC maps (foreign maps)	YES	16.10.1
	IGMP snooping support	YES	16.10.1
	Wi-Fi Direct & Peer-to-Peer (P2P) Blocking	YES	16.10.1
	Ability to specify name and SSID of AP on RADIUS CallStationID	YES	16.10.1
	NAS-ID per interface, WLAN or AP group	YES	16.10.1
	Global Positioning System (GPS) support for outdoor	YES	16.10.1
	Called Station ID for Accounting	YES	16.10.1
	Ethernet Fallback shutdown	YES	16.10.1
	HTTPS redirect	YES	16.10.1

Guest-Anchor redundancy	YES	16.10.1
ATF	YES	16.10.1
Support for hyperlocation module	YES	16.10.1
Dynamic Management User Login via AAA Server	YES	16.10.1
Smart Licensing	YES	16.10.1
AP Provisioning PnP	YES	16.10.1
URL domain filtering	YES	16.10.1
Fastlane support	YES	16.10.1
Radio Frequency IDentification (RFID) and Wi-Fi tag support	YES	16.10.1
Password encryption	YES	16.10.1
11v support (Directed Multicast Service [DMS] and BSS Max Idle Period)	YES	16.10.1
11r mixed mode support	YES	16.10.1
11v - Basic Service Set (BSS) Transition Management	YES	16.10.1
Access Control List (ACLs)	YES	16.10.1
Domain Based Filter ACL	YES	16.10.1
Passive clients	YES	16.10.1
WLAN AAA override - client interface override	YES	16.10.1
Limit number of clients per WLAN	YES	16.10.1
WMM non-compliant U-APSD client support	YES	16.10.1
Sleeping client support	YES	16.10.1
Client exclusion due to 802.1x timeout	YES	16.10.1
DHCP opt 82 - Can specify the name and SSID of the AP	YES	16.10.1
LDAP support	YES	16.10.1
Multicast - multicast	YES	16.10.1
L3 multicast roaming	YES	16.10.1
VLAN select & L2/L3 multicast optimization	YES	16.10.1
CAPWAPv6 AP multicast mode support	YES	16.10.1
Support for NetFlow protocol	YES	16.10.1
Netflow support on 3rd party NMS	YES	16.10.1
Native Sensor DHCP Support in Local and FlexConnect mode (Device Profiling)	YES	16.10.1
Support for RADIUS Client Profiling	YES	16.10.1
HTTP profiling for local and flex mode (RADIUS profiling)	YES	16.10.1
Ability to update Organizational Unique Identifier (OUI)/Device Profile list	YES	16.10.1
SNMP trap support for client association/disassociation	YES	16.10.1
SNMP traps via SNMPv3	YES	16.10.1
WGB with multiple VLANs	YES	16.10.1

Dynamic Link Exchange Protocol Client Support (DLEP) on WGB	YES	16.10.1
Call Admission Control (CAC) and U-APSD	YES	16.10.1
Load-based CAC	YES	16.10.1
Initiation Protocol - CAC (SIP CAC)	YES	16.10.1
802.11n voice Call Admission Control (CAC)	YES	16.10.1
Broadcast enabling/disabling independent of multicast	YES	16.10.1
Can specify a DNS server and AP domain on APs with static IP address	YES	16.10.1
CLI to disable Aggregated Mac Service Data Unit (A-MSDU) per priority	YES	16.10.1
DTLS support on vWLC	YES	16.10.1
Data DTLS on vWLC support	YES	16.10.1
11h channel switch (easier CLI configuration)	YES	16.10.1
11ac configuration on HA environment	YES	16.10.1
Can add Licenses to WLC HA SKU	YES	16.10.1
Windows 8 profile support	YES	16.10.1
Support for Universal Stock Keeping Unit SKU	YES	16.10.1
1st client is kicked off after IP address duplication is detected	YES	16.10.1
Cisco DNA Center PnP for 802.11ac Wave 2 APs	YES	16.10.1
Cisco DNA Center PnP for FlexConnect AP PnP	YES	16.10.1
802.11k and 802.11v enabled by default	YES	16.10.1
Parallel Redundancy Protocol Enhancement on AP and WGB	YES	NO
Wave 2 APs - Support for IPv6 PnP (Plug-n-Play)	YES	16.10.1
Transmission Control Protocol - Maximum Segment Size (TCP MSS) enabled by default with a value of 1250	YES	16.10.1
Upgrade of Access Points (APs) and Wireless LAN Controller (WLC) software with rolling AP upgrade with Prime Infrastructure 3.3	YES	16.10.1
Wave 2 APs - Support for DHCP Opt 60	YES	16.10.1
WLC only forward probing client Received Signal Strength Indication (RSSI) data if CMX is opted	YES	16.10.1
Custom Support configuration of Receiver Start of Packet (RX-SOP) values configurable through RF profiles	YES	16.10.1
Wave 2 APs - VxLAN AP Infra for eCA on 4800	YES	16.10.1
Wave 2 APs - Ability to disable AP fallback to DHCP when configured for static IP address	YES	16.10.1
Wave 2 APs - AP able to get time from network	YES	16.10.1
Wave 2 APs - Improved sniffer mode for Layer 1 information	YES	16.10.1

Ability to Disable Accounting Servers per WLAN	YES	16.10.1
ACL counters	YES	16.10.1
WGB VLAN client feature	YES	16.10.1
RADIUS servers per WLAN from 3 to 6	YES	16.10.1
Support for more DHCP opt 82 attributes	YES	16.10.1
Internal Policy Classification Engine	YES	16.10.1
IPv6 support (Phase III)	YES	16.10.1
IPv6 - Terminal Access Controller Access Control System (TACACS+) IPv6 support	YES	16.10.1
ATF Phase 2	YES	16.10.1
FlexConnect mode support on APs 1800/2800/3800	YES	16.10.1
Support for Cisco Hyperlocation in HA Environment	YES	16.10.1
Monitor support for APs 1540, 1560, 1810OEAP, 1810W, 1815, 1850 and 1830.	YES	16.10.1
Minimum interval time for volume metering	YES	16.10.1
Wave 2 APs - Support for wired 802.1x	YES	16.10.1
Wave 2 APs - Spectrum Intelligence	YES	16.10.1
Wave 2 APs - Support for Remote LAN (RLAN) on Aux port	YES	16.10.1
Wave 2 APs - Support for RLAN local switching on AP 1815W	YES	16.10.1
Wave 2 APs - NTP support	YES	16.10.1
Airtime fairness support on wave 2 APs	YES	16.10.1
Support for IOS WGB association to LWAPP AP	YES	16.10.1
AP in sniffer mode	YES	16.10.1
Non-Cisco WGB support	YES	16.10.1
Clients doing passive scan can join a WLAN with load balancing enable at first try	YES	16.10.1
ISE NAC Device profiler for WLC	YES	16.10.1
WLAN for voice auto-config	YES	16.10.1
OEAP - split tunneling	YES	16.10.1
OEAP - Higher priority for voice packets support (Voice QoS)	YES	16.10.1
RX SOP	YES	16.10.1
AP groups	YES	16.10.1 (Same behavior using New Config Model)
No support for fragmented pings	YES	16.10.1
IPSec (for Radius)	YES	16.10.1
Multicast improvement	YES	16.10.1
Multicast Direct	YES	16.12.1
High Speed roaming for WGB	YES	16.10.1

Layer 3 (L3) Interfaces for tunneling protocols (GRE tunnels)	YES	16.11.1
EoGRE on WLC	YES	16.11.1
EoGRE on AP	YES	16.11.1
Bonjour gateway (mDNS support - Phase I)	YES	16.11.1
mDNS bonjour message update with PTR RR	YES	16.11.1
WLC 2505 - Bonjour gateway support for up to 200 instance services	YES	16.11.1
Ethernet over Generic Routing Encapsulation (EoGRE) Virtual Local Area Network (VLAN) overridden withing the WLAN	YES	16.11.1
Client statistics forward based on CMX AP group subscription	YES	16.11.1
Introduction of config network ap-discovery nat-ip-only	YES	16.11.1
DHCP Option 82 for EoGRE Tunnel in Cisco Wave 2 APs	YES	16.12.1
Wave 2 Fabric - IPv6 Domain Name System (DNS) Access Control Lists (ACLs)	YES	16.12.1
Bi-directional rate limit per WLAN/User (bandwidth contract)	YES	16.12.1
Wave 2 Fabric - Post-auth IPv6 ACL support	YES	16.12.1
Intelligent capture support added to more APs - 1800s, 9115, 9117, 9120, IW3700, Cisco 6300 Embedded AP	YES	16.12.1
WLC Netflow Enhancement	YES	16.12.1
11u new features (hotspot)	YES	16.12.1
WLC 2500 - Wired guest access support	YES	16.12.1
mDNS phase 3 (ISE policies, profile enhancements, PI instant services)	YES	16.12.1
EoGRE deployment with multiple Tunnel Gateways (TGWs) enhancements	YES	16.12.1
EoGRE - IPv6 support	YES	16.12.1
Limit connections to 11n clients only	YES	16.12.1
MFP	YES	16.12.1
Passpoint 2.0 R2 Certification	YES	16.12.1
Secure Lightweight Directory Access Protocol (LDAP)	YES	16.12.1
EoGRE tunnel failover	YES	16.12.2
Chromecast service on Multicast Domain Name System (mDNS) default database	YES	17.1.1
Daisy Chain support for AP 1560 and 1542I/D	YES	17.1.1
Voice over IP (VoIP) Snooping (SIP voice calls)	YES	17.1.1
Adaptive 802.11r	YES	17.1.1
Wi-Fi Alliance Agile Multiband (MBO) support	YES	17.1.1

	Wave 2 APs - Flex+Bridge support	YES	17.1.1s
	Wave 2 APs - CMX FastLocate	YES	17.1.1s
	DNS radius feature changes	YES	17.1.1s
	mDNS Phase II (Location Specific Services [LSS], mDNS-AP, priority mac, origin of service)	YES	17.1.1s
	mDNS MAC based service policy	YES	NO
	Simple Network Management Protocol (SNMP) over IPsec supported over IPv6 interfaces	YES	17.1.1s
	SNMP traps over IPsec supported over IPv6 interfaces	YES	17.1.1s
	OfficeExtended AP (OEAP) mode on Wave 2 802.11ac APs	YES	17.2.1
	Wave 2 APs - Local switching of rlan traffic supported even when AP is in Local Mode	YES	17.2.1
	Guest User Management - Client Whitelisting	YES	17.2.1
	802.11u (Hotspot 2.0)	YES	17.2.1
	Mobility Express : Mdns policy	YES	17.3.1 (Supported on EWC)
	Passpoint R3	YES	17.3.1
	Spectrum intelligence for Salt Spring	YES	17.3.1
	Passpoint 2.0 - WFA Certification	YES	17.3.1
	Flash AP light-emitting diodes (LEDs) via SNMP and GUI	YES	17.3.1
	CAC running on AP	YES	17.3.2
	SNMP OID FOR Radius Access / Accept / Rejects	YES	17.3.2
	AP LLDP	YES	17.3.2
	AAA SNMP MIBs (RADIUS accepts,rejects,timeouts) are not working	YES	17.5.1
	Catalyst 9800 Special Character Handling	YES	17.5.1
	Link local bridging support	YES	17.6.1
	Block client association when AAA returns a VLAN that is NOT present on the WLC	YES	17.6.1
	eWLC needs to be able to handle AP's unable to reach NTP messages	YES	17.6.1
<b>QoS</b>	QoS DSCP	YES	16.10.1
	AVC with NBAR2	YES	16.10.1
	Protocol Pack update capability for AVC/NBAR2	YES	16.12.1
	AAA Override QoS support	YES	16.10.1
	AVC AAA override	YES	16.10.1
	AVC directional QoS	YES	16.10.1
	AVC integration with local profile	YES	16.10.1
	AVC per application, per client rate limit on WLAN	YES	16.10.1
	QoS Map (DSCP based)	YES	16.10.1
	QoS Mapping (DSCP)	YES	16.10.1



	DSCP/User Priority (UP) settings based on application traffic	YES	16.10.1
	QoS FastLane	YES	16.10.1
	Default Differentiated Services Code Point (DSCP) marking per Application Visibility and Control (AVC) profile	YES	16.10.1
	EDCA for spectralink phones	YES	16.10.1
	Trust DSCP between AP and controller	YES	16.10.1
	Last support for NBAR 3.7 (AVC v13)	YES	16.10.1
	NBAR and Netflow Updates (Pack 14.0)	YES	16.10.1
	NBAR Engine Upgrade on AP (NBAR2 Protocol Pack 19.1.0)	YES	16.10.1
	Support for NBAR2 Protocol Pack 19.1.0 (Optionally can upgrade to 24.0.0)	YES	16.10.1
	Fine QoS configuration	YES	16.12.1
	Ability to add AVC profile with fastlane enabled	YES	16.10.1
	Network Based Application Recognition (NBAR) update to engine 31 and protocol pack 33.0	YES	17.1.1
<b>Solution</b>	TrustSec SXP for WLCs	YES	16.12.1
	Security Group Tag (SGT) Exchange Protocol (SXP)	YES	16.12.1
	Fabric Enabled Wireless	YES	16.10.1
	Cisco Umbrella WLAN - OpenDNS support	YES	16.10.1
	StadiumVision Multicast	YES	16.10.1
	wIPS (Architecture/Supported signatures are different between the two platforms)	YES	17.1.1
	Bring your own device (BYOD) (ISE auto-provisioning)	YES	16.10.1
	DNA Spaces connector	YES	16.10.1
	TrustSec support on WLC 5520, 7510 and 8500	YES	16.12.1 (On equivalent C9800 Platform)
	AAA and DHCP Dashboard Network Services Analytics	YES	YES
<b>Scale</b>	9800	YES	<a href="https://salesconnect.cisco.com">https://salesconnect.cisco.com</a>
	9100	YES	<a href="https://salesconnect.cisco.com">https://salesconnect.cisco.com</a>
<b>AP Support (Please refer <a href="#">compati</a>)</b>	Support for AP 3700	YES	16.10.1
	Support for AP 2700	YES	16.10.1
	Support for AP 1700	YES	16.10.1
	Support for AP 1570	YES	16.10.1
	Support for AP 1850	YES	16.10.1

<b>Ability matrix for complete list of supported APs)</b>	Support for AP 1830	YES	16.10.1
	Support for AP 2800	YES	16.10.1
	Support for AP 3800	YES	16.10.1
	Support for AP 1810(W)	YES	16.10.1
	Support for AP 1560 (Local mode only)	YES	16.10.1
	Support for AP 1815i	YES	16.10.1
	Support for AP 1815	YES	16.10.1
	Support for AP 1815M	YES	16.10.1
	Support for AP 1542I/D	YES	16.10.1
	Support for APs 1540, 1815m and 1815t	YES	16.10.1
	Support for Catalyst 9115 and 9117 access points	YES	16.12.1s
	Support for Catalyst 9120-AXI access point	YES	16.12.2s
	Support for 9130-AXI	YES	16.12.2s
	support for 9120AXE, 9120AXP	YES	16.12.2s
	Support for AP IW3702	YES	17.1.1s
	Tri-radio Support(dynamic) - Axel 9130	YES	17.3.1
	UL OFDMA (37 users) Support for Axel 9130	YES	17.3.1
	DL OFDMA (37 users) Support for Axel 9130	YES	17.3.1
	.11ax UL MU-MIMO (160MHz) – 9130/9120/9115/9105	YES	17.3.1
	.11ax DL MU-MIMO (160MHz) – Axel 9130	YES	17.3.1
	CLI to enable/disable IW3702 heaters	YES	17.3.1
	eWLC CLIs for External Modules for 3800	YES	17.3.1
	Teleworker	YES	17.3.1
	C9124	YES	17.5.1
	C-ANT9104= Antenna support	YES	17.6.1
	<b>Serviceability</b>	CLI command to display number of voice calls in WLC (show cac voice stats [ 802.11a   802.11b ] <ap-name>)	NO
	Ability to clear queue-info-max stats (clear queue-info [detail <queue-id>/all/capwap/dot11/ipv6/mobility/redundancy])	YES	16.10.1
	Logs saved in flash prior WLC reboot (show logging last-reset)	YES	16.10.1
	Test AAA RADIUS command	YES	16.10.1
	Log of a Radio reset event	YES	16.10.1
	Wave 2 APs - Addition of command show controllers dot11radio 0/1 antenna	YES	16.10.1
	Wave 2 APs - Collection of support bundle (copy support-bundle { scp:   tftp: })	YES	16.10.1
	Wave 2 APs - Log history for radio reset (show history interface dot11radio { 0   1 } { reset   radar })	YES	16.10.1
	Selective client packet capture support for AP 2800/3800	YES	16.10.1

Wave 2 APs - Support for syslog facility	YES	16.10.1
Wave 2 APs - Support for ' ' include <string>' for all show commands	YES	16.10.1
Wave 2 APs - Command to show client exclusion list on Flex APs (#show flexconnect client exclusion-list)	YES	16.10.1
Wave 2 APs - Ability to filter debug traffic based on source/destination IP (#debug traffic wired filter...)	YES	16.10.1
Wave 2 APs - Ability to export capture as .pcap (#copy tmp APname_capture.pcap0 tftp...)	YES	16.10.1
Name of AP included in show client detail output	YES	16.10.1
Ability to debug multiple mac address	YES	16.10.1
AP packet-dump	YES	16.10.1
AP's IP address in show ap summary	YES	16.10.1
Add CLI - Grep support	YES	16.10.1
CLI command show queue-info addition	YES	16.10.1
IP address included in the output of show ap summary	YES	16.10.1
AP search per IP address on GUI	YES	16.10.1
Add CLI show system... to monitor WLC's performance	YES	16.10.1
Add CLI show run-config startup-commands	YES	16.10.1
AP CLI to choose AP mode #capwap ap mode local/bridge	YES	16.10.1
Add CLI show client detail displays profile/ssid name	YES	16.10.1
Add CLI show ap join stats shows current real name	YES	16.10.1
debug client shows AP name	YES	16.10.1
AP name during asso/reasso on debug client output	YES	16.10.1
CLI command to verify all certificates installed in the WLC (show certificate all)	YES	16.10.1
FlexConnect Client debugs on AP	YES	16.10.1
Wave 2 APs - Addition of command show controllers dot11radio 0/1 client <mac>	YES	16.10.1
Wave 2 APs - Ability to clear ap trace logs (#config ap client-trace clear)	YES	16.10.1
Wave 2 APs - Debug to check UP value for client downstream (#debug capwap client qos)	YES	16.10.1
Wave 2 APs - Log number of deauths sent by AP (#show dot11 clients deauth)	YES	16.10.1
Wave 2 APs - Log number of consecutive TX fails (#show controllers dot11radio 0/1 client aa:bb:cc:dd:ee:ff)	YES	16.10.1
Wave 2 APs - Ability to see rate per client on client	YES	16.10.1

	tracing (#debug dot11 client rate address aa:bb:cc:dd:ee:ff)		
	Wave 2 APs - Client count statistics (#show client summary)	YES	16.10.1
	Ability to see configuration history (show logging config-history)	YES	16.10.1
	Ability to Small Form-Factor Pluggable (SF) transceiver information (show port sfp-info)	YES	16.10.1
	Debug commands for bonjour/mDNS added (debug mdns client, shows mdns query stats, test mdsn)	YES	16.11.1
	Username are displayed in client summaries	YES	16.11.1
	CLI show rogue ap summary - extended options	YES	16.12.1
	Wildcard support in Change Filter in GUI	YES	16.12.1
	IP address in show client summary	YES	16.12.1
	Introduction of show ap bundle	YES	16.12.1
	Wave 2 APs - Command available to clear counters on show controller (#clear counters [ dot11radio   client ])	YES	16.12.1
	Wave 2 APs - Improved show dot11 interface dot11radio 0/1 statistics output	YES	16.12.1
	COS AP packet tracer phase 1	YES	17.3.1
	Need a way to download AP support bundle from the WLC UI	YES	17.3.1
	Client assoc/disassoc/reassoc syslogs	YES	17.3.1
<b>Certificat ion</b>	FIPS	YES	16.12.1
	FIPS 140-2	YES	16.12.1
	FIPS 140-2	YES	16.10.1
	Federal Information Processing Standard (FIPS) - Support for Data Datagram Transport Layer Security (DTLS) 1.2 for AP-WLC Control and Provisioning of Wireless Access Points (CAPWAP)	YES	16.10.1
	FIPS - Support new GCM cipher suites for DTLS	YES	16.10.1
	FIPS - New 802.11 encryption modes	YES	16.10.1
	FIPS - Simple Certificate Enrollment Protocol (SCEP) over HyperText Transfer Protocol over HTTPS support for Locally Significant Certificate (LSC)	YES	16.10.1
	FIPS - IPsec configuration is profile-based	YES	16.10.1
	FIPS - Syslog over IPsec support	YES	16.10.1
	FIPS - IKEv1/IKEv2 supported	YES	16.10.1
	FIPS - Certificate Signing Request (CSR) generation by WLC	YES	16.10.1

## Deprecated Features

Below is the list of AireOS features which are deprecated in Cisco Catalyst 9800 Wireless Controller platform for various reasons like – features cater to legacy technology, implications of new architecture of IOS-XE and much better alternatives available in Cisco Catalyst 9800 wireless controllers.

Client MFP
Packet capture files when controller's data plane crashes
128-bit WEP no longer available
40-MHz channels in 2.4GHz band
AP gives preference to WLC that has its same code version found on Discovery Response message
Spectrum Expert 4.0
Ability to enable/disable CDP per radio interface
Voice Diagnostic tools
CDP over the air
Support for SKC (sticky key caching)
Cisco Compatible Extensions version 6 (CCXv6)
Key Telephone System-based CAC (KTS-based CAC)
iWLAN AAA override - client interface/VLAN override
WLAN with 802.1X if MAC authentication with static Wired Equivalent Privacy (WEP) fails
New Mobility
L2 ACLS
New Mobility and Mobility Controller (MC) support
L2ACL FlexConnect
PMIPv6 (Proxy Mobile IPv6) - support for CWA/external web authentication
Layer 2 (L2) ACL GUI
Point-to-Point Protocol over Ethernet (PPPoE) client on FlexConnect AP
QinQ tag enhancement (802.1Q-in-Q VLAN tag)
Proxy Mobile IPv6 (PMIPv6) - FlexConnect as Mobile Access Gateway (MAG)
Ability to clear pmipv6 mag stats (clear pmipv6 mag stats)
Ability to disable MFP traps
Multiple User Datagram Protocol (UDP) source port support for RADIUS protocol
Microsoft (MS) Lync Software Defined Networking (SDN) Integration
Log source IP address on failed logins
Configurable dot1x exclusion attempts (1 to 10)
Multiple User Datagram Protocol (UDP) source port support for RADIUS protocol
FlexConnect group VLAN support override AP-specific
Mesh - Removal of Support for RX-SOP from Mesh Backhaul
PnP and Complex Programmable Logic Device (PLD) programmability
Link Layer Discovery Protocol (LLDP) on recovery image
WeChat authentication
FlexConnect - AP Easy Admin
Support for APeX
Wave 2 APs - Support for Mobile Concierge

Wave 2 APs - Ability to conver AP 2800/3800 into sensors
CPU ACLs
ARP padding
Context aware
Adder license without reboot
Alloy QoS
MSE - Virtual appliance
MSE - High availability
Faster reboot of WLC with restart instead of reset system
FIPS - Different CMX server Certificate authority (CA) certificate
FIPS - Support for CMX connectivity with TLSv1.2
ISE Simplification - Default Wireless Local Area Network (WLAN) configuration for ISE server
CleanAir with BLE Beacon disabled by default
Web authentication scaling improvements for Hypertext Transfer Protocol Secure (HTTPS) redirection
Improved radar detection
Dynamic Policy Enforcement / Usage Monitoring
Address Space Layout Rendomisation (ASLR) Support
Webhook
Debug arp added to debug client
Support to transfer upload of yang bundle through graphic interface

## Not Applicable Features

Below is the list of AireOS features which are not applicable in Cisco Catalyst 9800 Wireless Controller platform for various reasons like – features are only relevant to AireOS platforms and/or incompatible legacy access points.

GUI Web Color Theme
Support for WLC 5508
Support for 1522, 1524, 1130 and 1240 in mesh mode
OEAP support for APs 1130 and 1140
Before delete an ap-group all the APs need to be moved to a new group
Channels 120,124 and 128 disable on -E regulatory domain APs 1131, 1243 and 1252
Support for AP 3502
Support for 500 AP join/image download simultaneously
Support for WLC 7510
Support for WLC 2504
Support for WiSM 2
Support with ISE v1.0
Because of CSCur27551 Bug-Preview for CSCur27551, SSLv3 disable by default
Support for AP 3600
WiSM2 support for 1000 APs (500 before)

WiSM2 support for 15000 clients (7500 before)
WiSM2 data plane of 20G (10G before)
Flexconnect - Hybrid Remote Edge Access Point (H-REAP) is called FlexConnect from this release and so on
Central switching mode support on WLC 7500
Unlicensed National Information Infrastructure 2 (UNII-2) and UNII-2 extended for 1552 APs
Mesh - Indoor mesh support for AP 3600
600 OEAP - can disable local SSID and local ports trough CLI
600 OEAP - can configure power, channel and channel width
600 OEAP - dual RLAN support
Support for AP 2600
AP 1520/1550 support for local and flexconnect mode
Can upgrade from a Licensed Data Payload Encryption (LDPE) controller to a non-LDPE
Support for vWLC
Support for WLC 8500
Support for AP 2600
Support for AP 1552CU/EU
Support for AP802H
Honor based license (Right to Use [RTU] licenses)
FlexConnect - PPP and PPPoE support
AP group out of the box
802.11n video CAC (Traffic Specification [TSPEC]-based video calls, Cius and facetime calls)
Local/flex/sniffer/rogue detector/monitor support for 1520 and 1550
Support for AP 1600
WLC 2504 - Support to be anchor WLC
WLC 2504 - Support for Link Aggregation (LAG)
WLC 7500 - Support for LAG
WLC 8510 - Support for LAG
Support for Wireless Security and Spectrum Intelligence (WSSI) monitor module
N+1 support with HA SKU controller
Support for all signatures on Enhanced Local Mode (ELM)
Support of 802.11ac module (Wave 1) on AP 3600
Support for AP 700
Support for WLC 8500 as anchor controller
Support of SFP-10G-LR on WLC 7500
VLAN tag on 1552 APs
Maximum number of APs allowed per WLC
AP Rate limit on vWLC
No more support of PPPoE on FlexConnect Aps
BBX (Billboard Exchange)
Cisco License Manager (CLM) is no longer supported
Default 802.1p tags changed (Platinum to 5 from 6, Gold to 4 from 5, Silver 2 from 3)
OEAP support for APs 1130,1240,1040,1140,1600,2600,3500,3600

Support for AP 1530
Support for Universal Small Cell 5310 on AP 3600
DFS channels on Aps 700 -A domain
WLC 8500 - Does not support new mobility
Support for AP 700W
WLC 2500 - WLAN Express Setup
CleanAir Express for 1600 and 1700 AP
OEAP AP602 GUI Enhancements
OEAP AP602 Split Tunneling
702W (Power over Ethernet) PoE management (ability to disable PoE port)
702W VLAN tag per Ethernet port
vWLC support for 6,000 clients
HA-SSO support for OEAP 600 APs
WLC 2500 - Express setup available through AP or client connection to any port
Because of CSCur27551 Bug-Preview for CSCur27551 SSLv3 is disabled by default
Support for WLC 5520
Support for WLC 8540
No more support for new mobility - Mobility Controller
Kernel-based Virtual Machine (KVM) support for vWLC
vWLC - by default, the WLAN is locally switched
Support for CSCur13394 (USC) 8x18
Large Scale Virtual WLC (vWLC)
WLC 5520/8510/8540 - Support to use service port on a daily basis
Upgrade with extra image and installation procedure (for APs 802, 1550 and 1570)
vWLC on Hyper-v support
Support for HA N+1 on Virtual WLC (vWLC)
Remote LAN support on wired ports of AP 702W
No more support for APs 600, 1550, 1040, 1140 and 1260
Show command for the redundant port (RP port)
Support for WLC 3504
Support for HA N+1 on Virtual Wireless LAN Controller (vWLC)