



Release Notes for the Cisco Home Agent 1.2 Feature in Cisco IOS Release 12.2(8)ZB

December 2002

Cisco IOS Release 12.2(8)ZB is a special release that is based on Cisco IOS Release 12.2, with the addition of enhancements to the Cisco Home Agent feature. The Cisco IOS Release 12.2(8)ZB is a release optimized for the Cisco Home Agent Release 1.2 feature on the Cisco 7206VXR router platform, and the Cisco Multi-Processor WAN Application Module on the Cisco 6500 Catalyst Switch platform. 7206VXR images will be available starting with first maintenance release, 12.2(8)ZB1. The current image for the 7206VXR routers is 12.2(8)BY2.

Contents

These release notes include important information and caveats for the Cisco PDSN software feature provided in Cisco IOS 12.2(8)ZB for the Cisco 7206 series router platform.

Caveats for Cisco IOS Releases 12.2 can be found on CCO at:

<http://www.cisco.com/univercd/cc/td/doc/product/software/ios122/122cav/122mcav.htm>

Release notes for Cisco 7000 Family for Release 12.2T can be found on CCO at:

<http://www.cisco.com/univercd/cc/td/doc/product/software/ios122/122relnt/7000/rn7000t.htm>

Release notes for the Cisco 6000 Family for 12.2T can be found on CCO at:

<http://www.cisco.com/univercd/cc/td/doc/product/software/ios122/122relnt/cat6000/index.htm>

This release note includes the following topics:

- [Introduction, page 2](#)
- [System Requirements, page 2](#)
- [Caveats, page 5](#)
- [Related Documentation, page 6](#)
- [Obtaining Documentation, page 11](#)
- [Obtaining Technical Assistance, page 11](#)

Introduction

The Home Agent (HA) maintains mobile user registrations and tunnels packets destined for the mobile to the PDSN/FA. It supports reverse tunneling, and can securely tunnel packets to the PDSN using IPSec. Broadcast packets are not tunneled. Additionally, the HA performs dynamic home address assignment for the mobile. Home address assignment can be from address pools configured locally, through either DHCP server access, or from the AAA server.

System Requirements

This section describes the system requirements for Cisco IOS Release 12.2(8)ZB:

- [Memory Requirements, page 2](#)
- [Hardware Supported, page 3](#)
- [Software Compatibility, page 3](#)
- [Determining the Software Version, page 3](#)
- [Upgrading to a New Software Release, page 3](#)
- [MIBs, page 3](#)

Memory Requirements

Table 1 shows the memory requirements for the PDSN Software Feature Set that supports the Cisco 7206 router. The table also lists the memory requirements for the IP Standard Feature Set (for the Home Agent [HA]).

Table 1 *Memory Requirements for the Cisco 7206 Router and 6500 Catalyst Switch*

Platform	Software Feature Set	Image Name	Flash Memory Required	DRAM Memory Required	Runs From
Cisco 7206 Router	Cisco Home Agent Software Feature Set	c7200-h1is-mz.122-8-BY2 c7200-h1ik9s-mz.122-8-BY2	20 MB	512 MB	RAM
Cisco 6500 Switch	Cisco Home Agent Feature Set	c6svc-mwam-h1is-v12.bin	20 MB	512 MB	RAM

Hardware Supported

Cisco IOS Release 12.2(8)ZB is optimized for Cisco Home Agent Release 1.2 on the Cisco 7206VXR router platform, and the Cisco Multi-Processor WAN Application Module on the Cisco 6500 Catalyst Switch platform.

The recommended hardware configuration for a Release 1.2 Cisco Home Agent is a 7206VXR with NPE400-512MB and PA-FE-TX1 port adapters. This is the only configuration tested in the Cisco lab. Cisco does not support or test any other variations of this configuration. If you require a different configuration you should consult with your Cisco representative before you order.

The recommended hardware configuration for Home Agent Release 1.2 is based on a Catalyst 6500 chassis with a SUP2, and 512 MB of DRAM. The recommended MWAM configuration calls for 512 Meg RAM per processor, totalling 1Gigabyte per processor complex.

An IPSec Services Module (VPNSM) is required for hardware support of IPSec.

For a complete list of interfaces supported on 6500 platform, please refer to the on-line product information at Cisco.com home page. For hardware details on 6500 platform, please refer to the Catalyst 6500 product specifications at <http://www.cisco.com/en/US/products/hw/switches/ps708/index.html>.

Software Compatibility

Cisco IOS Release 12.2(8)ZB is a special release that is developed on Cisco IOS Release 12.2.

Cisco IOS Release 12.2(8)ZB supports the same features that are in Cisco IOS Release 12.2, with the addition of the Cisco Home Agent Release 1.2 feature.

Determining the Software Version

To determine the version of Cisco IOS software running on your router, log in to the router and enter the **show version** EXEC command:

```
Router# show version
Cisco Internetwork Operating System Software
IOS (tm) 6500 Software (C6500-H1IS-M), Version 12.2(8)BY, RELEASE SOFTWARE
```

Upgrading to a New Software Release

For information on upgrading to a new software release, see the product bulletin *Cisco IOS Software Upgrade Ordering Instructions* located at:

http://www.cisco.com/warp/public/cc/pd/iosw/prodlit/957_pp.htm

MIBs

Old Cisco Management Information Bases (MIBs) will be replaced in a future release. Currently, OLD-CISCO-* MIBs are being converted into more scalable MIBs—without affecting existing Cisco IOS products or NMS applications. You can update from deprecated MIBs to the replacement MIBs as shown in [Table 2](#).

Table 2 Deprecated and Replacement MIBs

Deprecated MIB	Replacement
OLD-CISCO-APPLETALK-MIB	RFC1243-MIB
OLD-CISCO-CHASSIS-MIB	ENTITY-MIB
OLD-CISCO-CPUK-MIB	To be decided
OLD-CISCO-DECNET-MIB	To be decided
OLD-CISCO-ENV-MIB	CISCO-ENVMON-MIB
OLD-CISCO-FLASH-MIB	CISCO-FLASH-MIB
OLD-CISCO-INTERFACES-MIB	IF-MIB CISCO-QUEUE-MIB
OLD-CISCO-IP-MIB	To be decided
OLD-CISCO-MEMORY-MIB	CISCO-MEMORY-POOL-MIB
OLD-CISCO-NOVELL-MIB	NOVELL-IPX-MIB
OLD-CISCO-SYS-MIB	(Compilation of other OLD* MIBs)
OLD-CISCO-SYSTEM-MIB	CISCO-CONFIG-COPY-MIB
OLD-CISCO-TCP-MIB	CISCO-TCP-MIB
OLD-CISCO-TS-MIB	To be decided
OLD-CISCO-VINES-MIB	CISCO-VINES-MIB
OLD-CISCO-XNS-MIB	To be decided

Cisco IOS Feature Sets

The Cisco IOS software is packaged in feature sets consisting of software images—depending on the platform. Each feature set contains a specific set of Cisco IOS features.

Cisco IOS Release 12.2(8)ZB supports the same feature sets as Cisco Release 12.2, with the exceptions that Cisco Release 12.2(8)ZB includes the Cisco Home Agent Release 1.2 feature. The Home Agent Release 1.2 feature is optimized for the Cisco 7206 router, and the Cisco 6500 Catalyst Switch.



Caution

Cisco IOS images with strong encryption (including, but not limited to 168-bit (3DES) data encryption feature sets) are subject to United States government export controls and have limited distribution. Strong encryption images to be installed outside the United States are likely to require an export license. Customer orders may be denied or subject to delay due to United States government regulations. When applicable, purchaser/user must obtain local import and use authorizations for all encryption strengths. Please contact your sales representative or distributor for more information, or send an e-mail to export@cisco.com.

Caveats

Caveats describe unexpected behavior in Cisco IOS software releases. Severity 1 caveats are the most serious caveats; severity 2 caveats are less serious.

Caveats for Cisco IOS Releases 12.2 can be found on CCO at

<http://www.cisco.com/univercd/cc/td/doc/product/software/ios122/122cav/122mcav.htm>

The “Open Caveats” section lists open caveats that apply to the current release and might also apply to previous releases.

The “Resolved Caveats” section lists caveats resolved in a particular release, which may have been open in previous releases.



Note

If you have an account with CCO, you can use Bug Navigator II to find caveats of any severity for any release. You can reach Bug Navigator II on CCO at **Software Center: Cisco IOS Software: Cisco Bug Toolkit: Cisco Bugtool Navigator II**, or at <http://www.cisco.com/support/bugtools>.

Open Caveats

This section describes possible unexpected behavior in Cisco IOS Release 12.2(8)ZB.

- CSCin24042

On the HA, data packets sent to MN immediately after the session establishment will be dropped. This happens only for the first MN on the tunnel, and with the tunnel scalability feature enabled.

There is no workaround.

- CSCin28187

On the HA, the tunnel input bytes in **show ip mobile tunnel** output indicates the wrong value (some extra bytes) when CEF is enabled.

There is no workaround.

Resolved Caveats

This section lists bugs that are resolved or closed in Cisco IOS Release 12.2(8)ZB.

- CSCdy52820

When multiple, redundant, RADIUS servers are configured for authentication on the HA, and the primary RADIUS server fails, MoIP sessions fail to come up. RRQs are rejected with "Identification Mismatch".

The HA compares the RRQ's timestamp with its own timestamp only after receiving an Access-Accept. In the abnormal case where the Access-Accept is delayed, the RRQ is rejected.

As a workaround, the timeout for the radius server may be set to a value less than the replay protection period.

- CSCdz32147

While opening and closing MOIP sessions using 6500 MWAM PDSN, the HA reloads when the **show ip mobile tunnel** command is issued.

There is no workaround.

- CSCdz37266

In the case of HA Redundancy, whenever a packet to the MN needs to be fragmented, but the DF bit is set, ICMP unreachable packet will not be sent to the sender of the packet.

A workaround is to disable the Tunnel scalability feature.

Related Documentation

Except for feature modules, documentation is available as printed manuals or electronic documents. Feature modules are available online on CCO and the Documentation CD-ROM.

Use these release notes with these documents:

- [Release-Specific Documents, page 6](#)
- [Platform-Specific Documents, page 7](#)
- [Feature Modules, page 7](#)
- [Cisco IOS Software Documentation Set, page 8](#)

Release-Specific Documents

The following documents are specific to Cisco IOS Release 12.2(8)BY1:

- *Cisco Mobile Wireless Home Agent* at the following url:

<http://www.cisco.com/univercd/cc/td/doc/product/software/ios122/122newft/122limit/122y/122by8/index.htm>

The following documents are specific to Release 12.2 and are located on CCO and the Documentation CD-ROM:

- *Cross-Platform Release Notes for Cisco IOS Release 12.2*

On CCO at:

Technical Documents: Cisco IOS Software Configuration: Cisco IOS Release 12.2: Release Notes: Cross-Platform Release Notes

On the Documentation CD-ROM at:

Cisco Product Documentation: Cisco IOS Software Configuration: Cisco IOS Release 12.1: Release Notes: Cross-Platform Release Notes

- *Caveats for Cisco IOS Release 12.1 T*

See *Caveats for Cisco IOS Release 12.2* and *Caveats for Cisco IOS Release 12.2T*, which contain caveats applicable to all platforms for all maintenance releases of Release 12.2 and Release 12.2 T.

On CCO at:

Technical Documents: Cisco IOS Software Configuration: Cisco IOS Release 12.2: Caveats

On the Documentation CD-ROM at:

Cisco Product Documentation: Cisco IOS Software Configuration: Cisco IOS Release 12.2: Caveats



Note If you have an account with CCO, you can use Bug Navigator II to find caveats of any severity for any release. You can reach Bug Navigator II on CCO at **Software Center: Cisco IOS Software: Cisco Bug Toolkit: Cisco Bugtool Navigator II**, or at <http://www.cisco.com/support/bugtools>.

- Product bulletins, field notices, and other release-specific documents on CCO at:
Technical Documents

Platform-Specific Documents

Documentation specific to the Cisco 7206 Router is located at the following locations:

- On CCO at: **Cisco Product Documentation: Core/High-End Routers: Cisco 7206**
- On the Documentation CD-ROM at: **Cisco Product Documentation: Core/High-End Routers: Cisco 7206**

Feature Modules

Feature modules describe new features supported by Release 12.2 and are updates to the Cisco IOS documentation set. A feature module consists of a brief overview of the feature, benefits, configuration tasks, and a command reference. As updates, the feature modules are available online only. Feature module information is incorporated in the next printing of the Cisco IOS documentation set.

On CCO at:

Technical Documents: Cisco IOS Software Configuration: Cisco IOS Release 12.2: New Feature Documentation

On the Documentation CD-ROM at:

Cisco Product Documentation: Cisco IOS Software Configuration: Cisco IOS Release 12.2: New Feature Documentation

Cisco IOS Software Documentation Set

The Cisco IOS software documentation set consists of the Cisco IOS configuration guides, Cisco IOS command references, and several other supporting documents that are shipped with your order in electronic form on the Documentation CD-ROM, unless you specifically ordered the printed versions.

Documentation Modules

Each module in the Cisco IOS documentation set consists of two books: a configuration guide and a corresponding command reference. Chapters in a configuration guide describe protocols, configuration tasks, Cisco IOS software functionality, and contain comprehensive configuration examples. Chapters in a command reference provide complete command syntax information. Use each configuration guide with its corresponding command reference.

On CCO and the Documentation CD-ROM, two master hot-linked documents provide information for the Cisco IOS software documentation set.

On CCO at:

Technical Documents: Cisco IOS Software Configuration: Cisco IOS Release 12.2: Configuration Guides and Command References

On the Documentation CD-ROM at:

Cisco Product Documentation: Cisco IOS Software Configuration: Cisco IOS Release 12.2: Configuration Guides and Command References

Release 12.2 Documentation Set

Table 3 describes the contents of the Cisco IOS Release 12.2 software documentation set, which is available in electronic form and in printed form when ordered.



Note

You can find the most current Cisco IOS documentation on CCO and the Documentation CD-ROM. These electronic documents may contain updates and modifications made after the hard-copy documents were printed.

On CCO at:

Technical Documents: Documentation Home Page: Cisco IOS Software Configuration: Cisco IOS Release 12.2

On the Documentation CD-ROM at:

Cisco Product Documentation: Cisco IOS Software Configuration: Cisco IOS Release 12.2

Table 3 Cisco IOS Software Release 12.2 Documentation Set

Books	Major Topics
<ul style="list-style-type: none"> • <i>Cisco IOS Configuration Fundamentals Configuration Guide</i> • <i>Cisco IOS Configuration Fundamentals Command Reference</i> 	Cisco IOS User Interfaces Cisco IOS File Management Cisco IOS System Management
<ul style="list-style-type: none"> • <i>Cisco IOS Bridging and IBM Networking Configuration Guide</i> • <i>Cisco IOS Bridging and IBM Networking Command Reference, Volume I</i> • <i>Cisco IOS Bridging and IBM Networking Command Reference, Volume II</i> 	Using Cisco IOS Software Overview of SNA Internetworking Bridging IBM Networking
<ul style="list-style-type: none"> • <i>Cisco IOS Dial Services Configuration Guide: Terminal Services</i> • <i>Cisco IOS Dial Services Configuration Guide: Network Services</i> • <i>Cisco IOS Dial Services Command Reference</i> 	Preparing for Dial Access Modem Configuration and Management ISDN and Signalling Configuration PPP Configuration Dial-on-Demand Routing Configuration Dial-Backup Configuration Terminal Service Configuration Large-Scale Dial Solutions Cost-Control Solutions Virtual Private Networks X.25 on ISDN Solutions Telco Solutions Dial-Related Addressing Services Interworking Dial Access Scenarios
<ul style="list-style-type: none"> • <i>Cisco IOS Interface Configuration Guide</i> • <i>Cisco IOS Interface Command Reference</i> 	Interface Configuration Overview Configuring LAN Interfaces Configuring Serial Interfaces Configuring Logical Interfaces
<ul style="list-style-type: none"> • <i>Cisco IOS IP and IP Routing Configuration Guide</i> • <i>Cisco IOS IP and IP Routing Command Reference</i> 	IP Addressing and Services IP Routing Protocols IP Multicast
<ul style="list-style-type: none"> • <i>Cisco IOS AppleTalk and Novell IPX Configuration Guide</i> • <i>Cisco IOS AppleTalk and Novell IPX Command Reference</i> 	AppleTalk and Novell IPX Overview Configuring AppleTalk Configuring Novell IPX
<ul style="list-style-type: none"> • <i>Cisco IOS Apollo Domain, Banyan VINES, DECnet, ISO CLNS, and XNS Configuration Guide</i> • <i>Cisco IOS Apollo Domain, Banyan VINES, DECnet, ISO CLNS, and XNS Command Reference</i> 	Apollo Domain, Banyan VINES, DECnet, ISO CLNS, and XNS Overview Configuring Apollo Domain Configuring Banyan VINES Configuring DECnet Configuring ISO CLNS Configuring XNS
<ul style="list-style-type: none"> • <i>Cisco IOS Multiservice Applications Configuration Guide</i> • <i>Cisco IOS Multiservice Applications Command Reference</i> 	Multiservice Applications Overview Voice Video Broadband

Table 3 Cisco IOS Software Release 12.2 Documentation Set (continued)

Books	Major Topics
<ul style="list-style-type: none"> • <i>Cisco IOS Quality of Service Solutions Configuration Guide</i> • <i>Cisco IOS Quality of Service Solutions Command Reference</i> 	Quality of Service Overview Classification Congestion Management Congestion Avoidance Policing and Shaping Signalling Link Efficiency Mechanisms Quality of Service Solutions
<ul style="list-style-type: none"> • <i>Cisco IOS Security Configuration Guide</i> • <i>Cisco IOS Security Command Reference</i> 	Security Overview Authentication, Authorization, and Accounting (AAA) Security Server Protocols Traffic Filtering and Firewalls IP Security and Encryption Other Security Features
<ul style="list-style-type: none"> • <i>Cisco IOS Switching Services Configuration Guide</i> • <i>Cisco IOS Switching Services Command Reference</i> 	Cisco IOS Switching Services Overview Cisco IOS Switching Paths Cisco Express Forwarding NetFlow Switching MPLS Switching Multilayer Switching Multicast Distributed Switching Virtual LANs LAN Emulation
<ul style="list-style-type: none"> • <i>Cisco IOS Wide-Area Networking Configuration Guide</i> • <i>Cisco IOS Wide-Area Networking Command Reference</i> 	Wide-Area Networking Overview Configuring ATM Configuring Frame Relay Configuring Frame Relay-ATM Interworking Configuring SMDS Configuring X.25 and LAPB
<ul style="list-style-type: none"> • <i>New Features in 12.1-Based Limited Lifetime Releases</i> • <i>New Features in Release 12.1 T</i> • Release Notes (Release note and caveat documentation for 12.1-based releases and various platforms) • <i>Cisco IOS Debug Command Reference</i> • <i>Cisco IOS Dial Services Quick Configuration Guide</i> 	

**Note**

Cisco Management Information Base (MIB) User Quick Reference is no longer published. If you have an account with CCO, you can find the current list of MIBs supported by Cisco. To reach the *Cisco Network Management Toolkit*, go to CCO, press **Login: Technical Support: Software Center: Network Mgmt Software: Cisco Network Management Toolkit: Cisco MIBs**.

Obtaining Documentation

World Wide Web

You can access the most current Cisco documentation on the World Wide Web (WWW) at <http://www.cisco.com>, <http://www-china.cisco.com>, or <http://www-europe.cisco.com>.

Documentation CD-ROM

Cisco documentation and additional literature are available in a CD-ROM package, which ships with your product. The Documentation CD-ROM is updated monthly. Therefore, it is probably more current than printed documentation. The CD-ROM package is available as a single unit or as part of an annual subscription.

Ordering Documentation

Registered CCO users can order the Documentation CD-ROM and other Cisco Product documentation through our online Subscription Services at <http://www.cisco.com/cgi-bin/subcat/kaojump.cgi>.

Nonregistered CCO users can order documentation through a local account representative by calling Cisco's corporate headquarters (California, USA) at 408 526-4000 or, in North America, call 800 553-NETS (6387).

Obtaining Technical Assistance

Cisco provides CCO as a starting point for all technical assistance. Warranty or maintenance contract customers can use the Technical Assistance Center (TAC). All customers can submit technical feedback on Cisco documentation using the web, e-mail, a self-addressed stamped response card included in many Cisco printed documents, or by sending mail to Cisco.

Cisco Connection Online

CCO is the foundation of a suite of interactive, networked services that provides immediate, open access to Cisco information and resources at anytime, from anywhere in the world. This highly integrated Internet application is a powerful, easy-to-use tool for doing business with Cisco.

CCO's broad range of features and services helps customers and partners to streamline business processes and improve productivity. Through CCO, you will find information about Cisco and our networking solutions, services, and programs. In addition, you can resolve technical issues with online support services, download and test software packages, and order Cisco learning materials and merchandise. Valuable online skill assessment, training, and certification programs are also available.

Customers and partners can register on CCO to obtain additional personalized information and services. Registered users may order products, check on the status of an order and view benefits specific to their relationships with Cisco.

You can access CCO in the following ways:

- WWW: www.cisco.com
- Telnet: [cco.cisco.com](telnet://cco.cisco.com)
- Modem using standard connection rates and the following terminal settings: VT100 emulation; 8 data bits; no parity; and 1 stop bit.
 - From North America, call 408 526-8070
 - From Europe, call 33 1 64 46 40 82

You can e-mail questions about using CCO to cco-team@cisco.com.

Technical Assistance Center

The Cisco TAC is available to warranty or maintenance contract customers who need technical assistance with a Cisco product that is under warranty or covered by a maintenance contract.

To display the TAC web site that includes links to technical support information and software upgrades and for requesting TAC support, use <http://www.cisco.com/public/support/tac>.

To contact by e-mail, use one of the following addresses:

Language	E-mail Address
English	tac@cisco.com
Hanzi (Chinese)	chinese-tac@cisco.com
Kanji (Japanese)	japan-tac@cisco.com
Hangul (Korean)	korea-tac@cisco.com
Spanish	tac@cisco.com
Thai	thai-tac@cisco.com

In North America, TAC can be reached at 800 553-2447 or 408 526-7209. For other telephone numbers and TAC e-mail addresses worldwide, consult the following web site:
<http://www.cisco.com/warp/public/687/Directory/DirTAC.shtml>.

Software Configuration Tips on the Cisco Technical Assistance Center Home Page

If you have a CCO login account, you can access the following URL, which contains links and tips on configuring your Cisco products:

http://www.cisco.com/kobayashi/technotes/serv_tips.shtml

This URL is subject to change without notice. If it changes, point your Web browser to CCO and click on this path: **Technical Assistance Center: Technical Tips**.

The following sections are provided from the Technical Tips page:

- Access Dial Cookbook—Contains common configurations or recipes for configuring various access routes and dial technologies.
- Field Notices—Notifies you of any critical issues regarding Cisco products and includes problem descriptions, safety or security issues, and hardware defects.
- Frequently Asked Questions—Describes the most frequently asked technical questions about Cisco hardware and software.
- Hardware—Provides technical tips related to specific hardware platforms.

- Hot Tips—Describes popular tips and hints gathered from the Cisco Technical Assistance Center (TAC). Most of these documents are available from the TAC Fax-on-demand service. To reach Fax-on-demand and receive documents at your fax machine from the United States, call 888-50-CISCO (888-502-4726). From other areas, call 650-596-4408.
- Internetworking Features—Lists tips on using Cisco IOS software features and services.
- Sample Configurations—Provides actual configuration examples that are complete with topology and annotations.

Documentation Feedback

If you are reading Cisco product documentation on the World Wide Web, you can submit technical comments electronically. Click **Feedback** in the toolbar and select **Documentation**. After you complete the form, click **Submit** to send it to Cisco.

You can e-mail your comments to bug-doc@cisco.com.

To submit your comments by mail, for your convenience many documents contain a response card behind the front cover. Otherwise, you can mail your comments to the following address:

Cisco Systems, Inc.
Document Resource Connection
170 West Tasman Drive
San Jose, CA 95134-9883

We appreciate and value your comments.

This document is to be used in conjunction with the documents listed in the “[Related Documentation](#)” section on page 6.

CCIP, the Cisco Arrow logo, the Cisco Powered Network mark, the Cisco Systems Verified logo, Cisco Unity, Follow Me Browsing, FormShare, iQ Breakthrough, iQ Expertise, iQ FastTrack, the iQ Logo, iQ Net Readiness Scorecard, Networking Academy, ScriptShare, SMARTnet, TransPath, and Voice LAN are trademarks of Cisco Systems, Inc.; Changing the Way We Work, Live, Play, and Learn, Discover All That's Possible, The Fastest Way to Increase Your Internet Quotient, and iQuick Study are service marks of Cisco Systems, Inc.; and Aironet, ASIST, BPX, Catalyst, CCDA, CCDP, CCIE, CCNA, CCNP, Cisco, the Cisco Certified Internetwork Expert logo, Cisco IOS, the Cisco IOS logo, Cisco Press, Cisco Systems, Cisco Systems Capital, the Cisco Systems logo, Empowering the Internet Generation, Enterprise/Solver, EtherChannel, EtherSwitch, Fast Step, GigaStack, Internet Quotient, IOS, IP/TV, LightStream, MGX, MICA, the Networkers logo, Network Registrar, Packet, PIX, Post-Routing, Pre-Routing, RateMUX, Registrar, SlideCast, StrataView Plus, Stratm, SwitchProbe, TeleRouter, and VCO are registered trademarks of Cisco Systems, Inc. and/or its affiliates in the U.S. and certain other countries.

All other trademarks mentioned in this document or Web site are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (0208R)

Copyright © 2002, Cisco Systems, Inc.
All rights reserved.

