



# Alerts Operation Config Mode Command Reference

---

- [alerts active, on page 1](#)
- [alerts add-silence, on page 2](#)
- [alerts add-silence matchers, on page 3](#)
- [alerts delete-silence, on page 4](#)
- [alerts history, on page 4](#)
- [alerts silence-by-id, on page 4](#)
- [alerts silences, on page 5](#)

## alerts active

Displays filtered list of active alerts.

**Command Modes** Exec > Global Configuration

**Syntax Description** `active filter alerts_filter active { false | true } silenced { false | true } inhibited { false | true } unprocessed { false | true } receiver regex`

### **active { false | true}**

Specify whether to display active alerts.

Must be one of the following:

- **false**
- **true**

Default Value: true.

### **filter *alerts\_filter***

Specify the alerts filter in the format *label expr value or regex*.

Must be a string.

**alerts add-silence****inhibited { false | true}**

Specify whether to display inhibited alerts.

Must be one of the following:

- **false**
- **true**

Default Value: false.

**receiver regex**

Specify a regex matching receivers to filter alerts.

Must be a string.

**silenced { false | true}**

Specify whether to display silenced alerts.

Must be one of the following:

- **false**
- **true**

Default Value: false.

**unprocessed { false | true}**

Specify whether to display unprocessed alerts.

Must be one of the following:

- **false**
- **true**

Default Value: false.

**Usage Guidelines**

Use this command to view filtered list of active alerts.

## alerts add-silence

Adds a silence.

**Command Modes**

Exec > Global Configuration

**Syntax Description**

```
add-silence id silence_id startsAt silence_start_time endsAt silence_end_time
createdBy silence_creator_id comment additional_info
```

**comment additional\_info**

Specify additional information for the silence.

Must be a string.

**createdBy *silence\_creator\_id***

Specify the silence creator identity.

Must be a string.

**endsAt *silence\_end\_time***

Specify the silence end time.

Must be a string in the date-and-time pattern. For information on the date-and-time pattern, see the Input Pattern Types section.

**id *silence\_id***

Specify the silence ID to add.

Must be a string in the uuid pattern. For information on the uuid pattern, see the Input Pattern Types section.

**startsAt *silence\_start\_time***

Specify the silence start time.

Must be a string in the date-and-time pattern. For information on the date-and-time pattern, see the Input Pattern Types section.

---

**Usage Guidelines**

Use this command to add a silence.

## alerts add-silence matchers

Configures the list of label values to filter alerts.

---

**Command Modes**

Exec > Global Configuration

---

**Syntax Description**

**matchers *alert\_label\_name value filter\_value isRegex { false | true }***

**isRegex { false | true }**

Specify whether the value is a regular expression or not.

Must be one of the following:

- **false**
- **true**

**value *filter\_value***

Specify the filter value.

Must be a string.

**alerts delete-silence*****alert\_label\_name***

Specify the alert label name.

Must be a string.

**Usage Guidelines** Use this command to configure the list of label values to filter alerts.

## alerts delete-silence

Deletes specified silence.

**Command Modes** Exec > Global Configuration**Syntax Description** **delete-silence id silence\_id\_to\_delete*****id silence\_id\_to\_delete***

Specify the ID of the silence to delete.

Must be a string in the uuid pattern. For information on the uuid pattern, see the Input Pattern Types section.

**Usage Guidelines** Use this command to delete specified silence.

## alerts history

Displays alerts history.

**Command Modes** Exec > Global Configuration**Syntax Description** **history filter alerts\_filter*****filter alerts\_filter***

Specify the comma-separated values to filter alerts.

Must be a string.

**Usage Guidelines** Use this command to view alerts history.

## alerts silence-by-id

Displays information about a specific silence.

**Command Modes** Exec > Global Configuration**Syntax Description** **silence-by-id id silence\_id**

**id silence\_id**

Specify the silence ID.

Must be a string in the uuid pattern. For information on the uuid pattern, see the Input Pattern Types section.

**Usage Guidelines**

Use this command to view information about a specific silence.

## alerts silences

Displays filtered list of silences.

**Command Modes**

Exec > Global Configuration

**Syntax Description**

**silences filter alerts\_filter**

**filter alerts\_filter**

Specify the alerts filter in the format *label expr value or regex*.

Must be a string.

**Usage Guidelines**

Use this command to view filtered list of silences.

■ alerts silences