

Ejemplo de Configuración de PIX/ASA 7.x PIX-to-PIX Dinámico-Static IPsec con NAT y Cliente VPN

Contenido

[Introducción](#)
[Prerequisites](#)
[Requirements](#)
[Componentes Utilizados](#)
[Convenciones](#)
[Configurar](#)
[Diagrama de la red](#)
[Configuraciones](#)
[Verificación](#)
[Troubleshoot](#)
[Claves previamente compartidas idénticas](#)
[Comandos para resolución de problemas](#)
[Ejemplos de Salida de Debug Correcto](#)
[Información Relacionada](#)

[Introducción](#)

En la mayoría de los casos, un PIX remoto que conecta con un PIX central no utiliza la Traducción de Dirección de Red (NAT). En su lugar, el PIX remoto utiliza una dirección IP externa estática. El caso de un PIX central que ejecuta 7.x y posteriores y conecta con un PIX remoto mediante NAT, es el mismo que una pequeña oficina en el hogar como un PIX 501 o 506 conectado con un módem de cable o DLS mediante DHCP (Dynamic Host Control Protocol). PIX 7.x y posteriores y Cisco Adaptive Security Device Manager (ASDM) no se ejecutan en un PIX 501 o 506. Por lo tanto, para este ejemplo el PIX remoto con DHCP y NAT se supone que es un PIX 501 o 506 que ejecuta el código 6.x. Esta configuración permite que el PIX central acepte conexiones IPsec dinámicas. El PIX remoto utiliza NAT para unirse a los dispositivos con dirección privada de detrás con la red de dirección privada que se encuentra tras el PIX central. El PIX remoto puede iniciar conexiones con el PIX central (sabe cuál es el punto final), aunque el PIX central no puede iniciar conexiones con el PIX remoto (no sabe cuál es el punto final).

En esta configuración de ejemplo, Tigre es el PIX remoto y León es el PIX central. Dado que se desconoce la dirección IP de Tiger, debe configurar Lion para que acepte dinámicamente las conexiones desde cualquier lugar que conozca la clave comodín previamente compartida. Tiger sabe qué tráfico se cifrará (porque lo especifica la lista de acceso) y dónde se encuentra el terminal de León. Tiger debe iniciar la conexión. Ambos lados realizan NAT y NAT 0 para eludir NAT para el tráfico IPsec.

Además, el usuario remoto en esta configuración se conecta con el PIX central (León) mediante Cisco VPN Client 4.x. El usuario remoto no puede conectarse al PIX remoto (Tiger) ya que ambos lados han asignado dinámicamente direcciones IP y no saben dónde enviar la solicitud.

Consulte [Configuración de PIX a PIX de IPsec dinámico a estático con NAT y Cisco VPN Client](#) para obtener más información sobre el mismo escenario en PIX 6.x con Cisco VPN Client 3.x.

Prerequisites

Requirements

No hay requisitos específicos para este documento.

Componentes Utilizados

La información que contiene este documento se basa en las siguientes versiones de software y hardware.

- Software Cisco PIX Firewall versión 7.x y posterior (PIX central)
- Software Cisco PIX Firewall versión 6.3.4 (PIX remoto)
- Cisco VPN Client versión 4.x

The information in this document was created from the devices in a specific lab environment. All of the devices used in this document started with a cleared (default) configuration. If your network is live, make sure that you understand the potential impact of any command.

Convenciones

Consulte [Convenciones de Consejos TécnicosCisco para obtener más información sobre las convenciones del documento.](#)


Configurar

En esta sección encontrará la información para configurar las funciones descritas en este documento.

Nota: Utilice la herramienta [Command Lookup](#) (sólo para clientes [registrados](#)) para obtener más información sobre los comandos utilizados en esta sección.

Diagrama de la red

En este documento, se utiliza esta configuración de red:



Configuraciones

En este documento, se utilizan estas configuraciones:

- [León](#)
- [Tigre](#)

León
<pre>PIX Version 7.0(0) names ! interface Ethernet0 nameif outside</pre>

```
security-level 0
ip address 172.18.124.166 255.255.255.0
!
interface Ethernet1
nameif inside
security-level 100
ip address 10.2.2.1 255.255.255.0
!
interface Ethernet2
shutdown
nameif intf2
security-level 4
no ip address
!
interface Ethernet3
shutdown
nameif intf3
security-level 6
no ip address
!
interface Ethernet4
shutdown
nameif intf4
security-level 8
no ip address
!
interface Ethernet5
shutdown
nameif intf5
security-level 10
no ip address
!
enable password 8Ry2YjIyt7RRXU24 encrypted
passwd 2KFQnbNIdI.2KYOU encrypted
hostname lion
domain-name cisco.com
boot system flash:/image.bin
ftp mode passive
access-list 100 extended permit ip 10.2.2.0
255.255.255.0 10.1.1.0 255.255.255.0
access-list 100 extended permit ip 10.2.2.0
255.255.255.0 10.3.3.0 255.255.255.0
pager lines 24
mtu outside 1500
mtu inside 1500
mtu intf2 1500
mtu intf3 1500
mtu intf4 1500
mtu intf5 1500
ip local pool clientpool 10.3.3.1-10.3.3.10
no failover
monitor-interface outside
monitor-interface inside
monitor-interface intf2
monitor-interface intf3
monitor-interface intf4
monitor-interface intf5
asdm image flash:/asdm-501.bin
asdm history enable
arp timeout 14400
nat-control
global (outside) 1 interface
nat (inside) 0 access-list 100
nat (inside) 1 0.0.0.0 0.0.0.0
```

```
route outside 0.0.0.0 0.0.0.0 172.18.124.1 1
timeout xlate 3:00:00
timeout conn 1:00:00 half-closed 0:10:00 udp 0:02:00
icmp 0:00:02
timeout sunrpc 0:10:00 h323 0:05:00 h225 1:00:00 mgcp
0:05:00
timeout mgcp-pat 0:05:00 sip 0:30:00 sip_media 0:02:00
timeout uauth 0:05:00 absolute
aaa-server TACACS+ protocol tacacs+
aaa-server RADIUS protocol radius
group-policy unityclient internal
group-policy unityclient attributes
wins-server value 10.1.1.3
dns-server value 10.1.1.3
vpn-idle-timeout 30
default-domain value cisco.com
user-authentication disable
username cisco password 3USUcOPFUimCO4Jk encrypted
http server enable
http 0.0.0.0 0.0.0.0 outside
http 0.0.0.0 0.0.0.0 inside
no snmp-server location
no snmp-server contact
snmp-server community public
snmp-server enable traps snmp
crypto ipsec transform-set myset esp-des esp-md5-hmac
crypto dynamic-map cisco 1 set transform-set myset
crypto map dyn-map 20 ipsec-isakmp dynamic cisco
crypto map dyn-map interface outside
isakmp enable outside
isakmp policy 20 authentication pre-share
isakmp policy 20 encryption des
isakmp policy 20 hash md5
isakmp policy 20 group 2
isakmp policy 20 lifetime 3600
isakmp policy 65535 authentication pre-share
isakmp policy 65535 encryption 3des
isakmp policy 65535 hash sha
isakmp policy 65535 group 2
isakmp policy 65535 lifetime 86400
telnet timeout 5
ssh timeout 5
ssh version 1
console timeout 0
tunnel-group DefaultL2LGroup type ipsec-l2l
tunnel-group DefaultL2LGroup general-attributes
    authentication-server-group none
tunnel-group DefaultL2LGroup ipsec-attributes
    pre-shared-key *
tunnel-group unityclient type ipsec-ra
tunnel-group unityclient general-attributes
    address-pool clientpool
    authentication-server-group none
    default-group-policy unityclient
tunnel-group unityclient ipsec-attributes
    pre-shared-key *
!
class-map inspection_default
    match default-inspection-traffic
!
!
policy-map global_policy
    class inspection_default
        inspect dns maximum-length 512
```

```
inspect ftp
inspect h323 h225
inspect h323 ras
inspect http
inspect netbios
inspect rsh
inspect rtsp
inspect skinny
inspect esmtp
inspect sqlnet
inspect sunrpc
inspect tftp
inspect sip
inspect xdmcp
!
service-policy global_policy global
Cryptochecksum:4e20a2153437d60c7f01054808d41b42
: end
```

Tigre

```
PIX Version 6.3(4)
interface ethernet0 auto
interface ethernet1 auto
interface ethernet2 auto shutdown
interface ethernet3 auto shutdown
interface ethernet4 auto shutdown
interface ethernet5 auto shutdown
nameif ethernet0 outside security0
nameif ethernet1 inside security100
nameif ethernet2 intf2 security4
nameif ethernet3 intf3 security6
nameif ethernet4 intf4 security8
nameif ethernet5 intf5 security10
enable password 8Ry2YjIyt7RRXU24 encrypted
passwd 2KFQnbNIdI.2KYOU encrypted
hostname tiger
domain-name cisco.com
fixup protocol dns maximum-length 512
fixup protocol ftp 21
fixup protocol h323 h225 1720
fixup protocol h323 ras 1718-1719
fixup protocol http 80
fixup protocol rsh 514
fixup protocol rtsp 554
fixup protocol sip 5060
fixup protocol sip udp 5060
fixup protocol skinny 2000
fixup protocol smtp 25
fixup protocol sqlnet 1521
fixup protocol tftp 69
names
access-list 101 permit ip 10.1.1.0 255.255.255.0
10.2.2.0 255.255.255.0
pager lines 24
mtu outside 1500
mtu inside 1500
mtu intf2 1500
mtu intf3 1500
mtu intf4 1500
mtu intf5 1500
!---- This command configures the outside interface !---
as a DHCP client and it is assumed that the IP address
```

```
!--- 172.18.124.167 is assigned by the DHCP server. ip
address outside dhcp ip address inside 10.1.1.1
255.255.255.0 no ip address intf2 no ip address intf3 no
ip address intf4 no ip address intf5 ip audit info
action alarm ip audit attack action alarm no failover
failover timeout 0:00:00 failover poll 15 no failover ip
address outside no failover ip address inside no
failover ip address intf2 no failover ip address intf3
no failover ip address intf4 no failover ip address
intf5 pdm history enable arp timeout 14400 nat (inside)
0 access-list 101 route outside 0.0.0.0 0.0.0.0
172.18.124.1 1 timeout xlate 3:00:00 timeout conn
1:00:00 half-closed 0:10:00 udp 0:02:00 rpc 0:10:00 h225
1:00:00 timeout h323 0:05:00 mgcp 0:05:00 sip 0:30:00
sip_media 0:02:00 timeout uauth 0:05:00 absolute aaa-
server TACACS+ protocol tacacs+ aaa-server TACACS+ max-
failed-attempts 3 aaa-server TACACS+ deadtime 10 aaa-
server RADIUS protocol radius aaa-server RADIUS max-
failed-attempts 3 aaa-server RADIUS deadtime 10 aaa-
server LOCAL protocol local no snmp-server location no
snmp-server contact snmp-server community public no
snmp-server enable traps floodguard enable sysopt
connection permit-ipsec crypto ipsec transform-set myset
esp-des esp-md5-hmac crypto map newmap 10 ipsec-isakmp
crypto map newmap 10 match address 101 crypto map newmap
10 set peer 172.18.124.166 crypto map newmap 10 set
transform-set myset crypto map newmap interface outside
isakmp enable outside isakmp key *****
172.18.124.166 netmask 255.255.255.255 isakmp policy 10
authentication pre-share isakmp policy 10 encryption des
isakmp policy 10 hash md5 isakmp policy 10 group 2
isakmp policy 10 lifetime 3600 telnet timeout 5 ssh
timeout 5 console timeout 0 terminal width 80
Cryptochecksum:906331b1b1ca162ea53e951588efb070 : end
```

Verificación

Use esta sección para confirmar que su configuración funciona correctamente.

[La herramienta Output Interpreter Tool \(clientes registrados solamente\) \(OIT\) soporta ciertos comandos show.](#) Utilice la OIT para ver un análisis del resultado del comando show.

Nota: Debe realizar los comandos **clear** en el modo config.

- **clear crypto ipsec sa:** restablece las asociaciones IPsec después de intentos fallidos de negociar un túnel VPN.
- **clear crypto isakmp sa:** restablece las asociaciones de seguridad de protocolo de administración de claves (ISAKMP) y asociación de seguridad de Internet después de intentos fallidos de negociar un túnel VPN.
- **show crypto engine ipsec:** muestra las sesiones cifradas.

Troubleshoot

Claves previamente compartidas idénticas

Si el túnel IPsec de LAN a LAN (L2L) no está establecido, verifique si la clave previamente

compartida para DefaultRAGroup y la clave previamente compartida para DefaultL2LGroup son iguales. Si este es el caso, entonces el PIX/ASA termina el túnel en el DefaultRAGroup primero y es probable que el túnel L2L luego falle. Asegúrese de que las claves previamente compartidas para los dos grupos de túnel predeterminados sean diferentes.

Comandos para resolución de problemas

La herramienta Output Interpreter Tool (clientes registrados solamente) (OIT) soporta ciertos comandos show. Utilice la OIT para ver un análisis del resultado del comando show.

Nota: Consulte [Información Importante sobre Comandos Debug](#) antes de utilizar los comandos debug.

- **debug crypto ipsec:** se utiliza para ver si un cliente negocia la parte IPsec de la conexión VPN.
- **debug crypto isakmp [/level]**—Se utiliza para ver si los peers negocian la parte ISAKMP de la VPN.

Ejemplos de Salida de Debug Correcto

Estos son ejemplos de algunos buenos resultados del comando debug:

- [PIX central \(7.0.0\)](#)
- [NAT dinámica PIX remota \(6.3.4\)](#)
- [Cliente VPN 4.0.5 en PIX 7.0 central](#)

[PIX central \(7.0.0\)](#)

```
lion(config)# 2nd try, on central PIX from remote PIXApr 05 16:48:31 [IKEv1 DEBUG]:  
IP = 172.18.124.167, processing SA payload  
Apr 05 16:48:31 [IKEv1 DEBUG]: IP = 172.18.124.167, Oakley proposal is acceptable  
Apr 05 16:48:31 [IKEv1 DEBUG]: IP = 172.18.124.167, processing IKE SA  
Apr 05 16:48:31 [IKEv1 DEBUG]: IP = 172.18.124.167, IKE SA Proposal # 1, Transform  
# 1 acceptable Matches global IKE entry # 3  
Apr 05 16:48:31 [IKEv1 DEBUG]: IP = 172.18.124.167, constructing ISA_SA for isakmp  
Apr 05 16:48:31 [IKEv1 DEBUG]: IP = 172.18.124.167, constructing Fragmentation VID  
+ extended capabilities payload  
Apr 05 16:48:31 [IKEv1]: IP = 172.18.124.167, IKE DECODE SENDING Message (msgid=0)  
with payloads : HDR + SA (1) + VENDOR (13) + NONE (0) total length : 104  
Apr 05 16:48:32 [IKEv1]: IP = 172.18.124.167, IKE DECODE RECEIVED Message (msgid=0)  
with payloads : HDR + KE (4) + NONCE (10) + VENDOR (13) + VENDOR (13)  
+ VENDOR (13) + NONE (0) total length : 256  
Apr 05 16:48:32 [IKEv1 DEBUG]: IP = 172.18.124.167, processing ke payload  
Apr 05 16:48:32 [IKEv1 DEBUG]: IP = 172.18.124.167, processing ISA_KE  
Apr 05 16:48:32 [IKEv1 DEBUG]: IP = 172.18.124.167, processing nonce payload  
Apr 05 16:48:32 [IKEv1 DEBUG]: IP = 172.18.124.167, processing VID payload  
Apr 05 16:48:32 [IKEv1 DEBUG]: IP = 172.18.124.167, Received xauth V6 VID  
Apr 05 16:48:32 [IKEv1 DEBUG]: IP = 172.18.124.167, processing VID payload  
Apr 05 16:48:32 [IKEv1 DEBUG]: IP = 172.18.124.167, Received DPD VID  
Apr 05 16:48:32 [IKEv1 DEBUG]: IP = 172.18.124.167, processing VID payload  
Apr 05 16:48:32 [IKEv1 DEBUG]: IP = 172.18.124.167, Received Cisco Unity client VID  
Apr 05 16:48:32 [IKEv1 DEBUG]: IP = 172.18.124.167, processing VID payload  
Apr 05 16:48:32 [IKEv1 DEBUG]: IP = 172.18.124.167, Processing IOS/PIX Vendor ID  
payload (version: 1.0.0, capabilities: 00000025)
```

```
Apr 05 16:48:32 [IKEv1 DEBUG]: IP = 172.18.124.167, constructing ke payload
Apr 05 16:48:32 [IKEv1 DEBUG]: IP = 172.18.124.167, constructing nonce payload
Apr 05 16:48:32 [IKEv1 DEBUG]: IP = 172.18.124.167, constructing Cisco Unity VID payload
Apr 05 16:48:32 [IKEv1 DEBUG]: IP = 172.18.124.167, constructing xauth V6 VID payload
Apr 05 16:48:32 [IKEv1 DEBUG]: IP = 172.18.124.167, Send IOS VID
Apr 05 16:48:32 [IKEv1 DEBUG]: IP = 172.18.124.167, Constructing ASA spoofing IOS
    Vendor ID payload (version: 1.0.0, capabilities: 20000001)
Apr 05 16:48:32 [IKEv1 DEBUG]: IP = 172.18.124.167, constructing VID payload
Apr 05 16:48:32 [IKEv1 DEBUG]: IP = 172.18.124.167, Send Altiga/Cisco VPN3000/Cisco
    ASA GW VID
Apr 05 16:48:32 [IKEv1]: IP = 172.18.124.167, Connection landed on tunnel_group
    DefaultL2LGroup
Apr 05 16:48:32 [IKEv1 DEBUG]: Group = DefaultL2LGroup, IP = 172.18.124.167,
    Generating keys for Responder...
Apr 05 16:48:32 [IKEv1]: IP = 172.18.124.167, IKE DECODE SENDING Message
    (msgid=0) with payloads : HDR + KE (4) + NONCE (10) + VENDOR (13) + VENDOR (13)
    + VENDOR (13) + VENDOR (13) + NONE (0) total length : 256
Apr 05 16:48:32 [IKEv1]: IP = 172.18.124.167, IKE DECODE RECEIVED Message (msg
id=0) with payloads : HDR + ID (5) + HASH (8) + NONE (0) total length : 71
Apr 05 16:48:32 [IKEv1 DEBUG]: Group = DefaultL2LGroup, IP = 172.18.124.167,
    Processing ID
Apr 05 16:48:32 [IKEv1 DEBUG]: Group = DefaultL2LGroup, IP = 172.18.124.167,
    processing hash
Apr 05 16:48:32 [IKEv1 DEBUG]: Group = DefaultL2LGroup, IP = 172.18.124.167,
    computing hash
Apr 05 16:48:32 [IKEv1]: IP = 172.18.124.167, Connection landed on tunnel_group
    DefaultL2LGroup
Apr 05 16:48:32 [IKEv1 DEBUG]: Group = DefaultL2LGroup, IP = 172.18.124.167,
    constructing ID
Apr 05 16:48:32 [IKEv1 DEBUG]: Group = DefaultL2LGroup, IP = 172.18.124.167,
    construct hash payload
Apr 05 16:48:32 [IKEv1 DEBUG]: Group = DefaultL2LGroup, IP = 172.18.124.167,
    computing hash
Apr 05 16:48:32 [IKEv1 DEBUG]: IP = 172.18.124.167, Constructing IOS keep
    alive payload: proposal=32767/32767 sec.
Apr 05 16:48:32 [IKEv1 DEBUG]: Group = DefaultL2LGroup, IP = 172.18.124.167,
    constructing dpd vid payload
Apr 05 16:48:32 [IKEv1]: IP = 172.18.124.167, IKE DECODE SENDING Message
    (msgid=0) with payloads : HDR + ID (5) + HASH (8) + IOS KEEPALIVE (14)
    + VENDOR (13) + NONE (0) total length : 102
Apr 05 16:48:33 [IKEv1]: IP = 172.18.124.167, IKE DECODE RECEIVED Message
    (msgid=ba80c56e) with payloads : HDR + HASH (8) + NOTIFY (11) + NONE (0)
    total length : 76
Apr 05 16:48:33 [IKEv1 DEBUG]: Group = DefaultL2LGroup, IP = 172.18.124.167,
    processing hash
Apr 05 16:48:33 [IKEv1 DEBUG]: Group = DefaultL2LGroup, IP = 172.18.124.167,
    Processing Notify payload
Apr 05 16:48:33 [IKEv1]: Received unexpected event EV_ACTIVATE_NEW_SA in
    state MM_TM_INIT_MODECFG_H
Apr 05 16:48:33 [IKEv1 DEBUG]: Group = DefaultL2LGroup, IP = 172.18.124.167,
    Delay Quick Mode processing, Cert/Trans Exch/RM DSID in progress
Apr 05 16:48:33 [IKEv1 DEBUG]: Group = DefaultL2LGroup, IP = 172.18.124.167,
    Resume Quick Mode processing, Cert/Trans Exch/RM DSID completed
Apr 05 16:48:33 [IKEv1]: Group = DefaultL2LGroup, IP = 172.18.124.167, PHASE 1COMPLETED
Apr 05 16:48:33 [IKEv1]: IP = 172.18.124.167, Keep-alive type for this connection: DPD
Apr 05 16:48:33 [IKEv1 DEBUG]: Group = DefaultL2LGroup, IP = 172.18.124.167,
    Starting phase 1 rekey timer: 3420000 (ms)
Apr 05 16:48:33 [IKEv1]: IP = 172.18.124.167, IKE DECODE RECEIVED Message
    (msgid=20c2120e) with payloads : HDR + HASH (8) + SA (1) + NONCE (10) + ID
    (5) + ID (5) + NONE (0) total length : 164
Apr 05 16:48:33 [IKEv1 DEBUG]: Group = DefaultL2LGroup, IP = 172.18.124.167,
    processing hash
Apr 05 16:48:33 [IKEv1 DEBUG]: Group = DefaultL2LGroup, IP = 172.18.124.167,
    processing SA payload
```

```

Apr 05 16:48:33 [IKEv1 DEBUG]: Group = DefaultL2LGroup, IP = 172.18.124.167,
processing nonce payload
Apr 05 16:48:33 [IKEv1 DEBUG]: Group = DefaultL2LGroup, IP = 172.18.124.167,
Processing ID
Apr 05 16:48:33 [IKEv1]: Group = DefaultL2LGroup, IP = 172.18.124.167,
Received remote IP Proxy Subnet data in ID Payload: Address 10.1.1.0,
Mask 255.255.255.0, Protocol 0, Port 0
Apr 05 16:48:33 [IKEv1 DEBUG]: Group = DefaultL2LGroup, IP = 172.18.124.167,
Processing ID
Apr 05 16:48:33 [IKEv1]: Group = DefaultL2LGroup, IP = 172.18.124.167,
Received local IP Proxy Subnet data in ID Payload: Address 10.2.2.0,
Mask 255.255.255.0, Protocol 0, Port 0
Apr 05 16:48:33 [IKEv1]: QM IsRekeyed old sa not found by addr
Apr 05 16:48:33 [IKEv1]: Group = DefaultL2LGroup, IP = 172.18.124.167,
IKE Remote Peer configured for SA: cisco
Apr 05 16:48:33 [IKEv1]: Group = DefaultL2LGroup, IP = 172.18.124.167,
processing IPSEC SA
Apr 05 16:48:33 [IKEv1 DEBUG]: Group = DefaultL2LGroup, IP = 172.18.124.167,
IPSec SA Proposal # 1, Transform # 1 acceptable Matches global IPSec SA entry # 1
Apr 05 16:48:33 [IKEv1]: Group = DefaultL2LGroup, IP = 172.18.124.167,
IKE: requesting SPI!
Apr 05 16:48:33 [IKEv1 DEBUG]: IKE got SPI from key engine: SPI = 0xd5243861
Apr 05 16:48:33 [IKEv1 DEBUG]: Group = DefaultL2LGroup, IP = 172.18.124.167,
oakley constucting quick mode
Apr 05 16:48:33 [IKEv1 DEBUG]: Group = DefaultL2LGroup, IP = 172.18.124.167,
constructing blank hash
Apr 05 16:48:33 [IKEv1 DEBUG]: Group = DefaultL2LGroup, IP = 172.18.124.167,
constructing ISA_SA for ipsec
Apr 05 16:48:33 [IKEv1 DEBUG]: Group = DefaultL2LGroup, IP = 172.18.124.167,
constructing ipsec nonce payload
Apr 05 16:48:33 [IKEv1 DEBUG]: Group = DefaultL2LGroup, IP = 172.18.124.167,
constructing proxy ID
Apr 05 16:48:33 [IKEv1 DEBUG]: Group = DefaultL2LGroup, IP = 172.18.124.167,
Transmitting Proxy Id:
    Remote subnet: 10.1.1.0 Mask 255.255.255.0 Protocol 0 Port 0
    Local subnet: 10.2.2.0 mask 255.255.255.0 Protocol 0 Port 0
Apr 05 16:48:33 [IKEv1 DEBUG]: Group = DefaultL2LGroup, IP = 172.18.124.167,
constructing qm hash
Apr 05 16:48:33 [IKEv1]: IP = 172.18.124.167, IKE DECODE SENDING Message
(msgid=20c2120e) with payloads : HDR + HASH (8) + SA (1) + NONCE (10) +
ID (5) + ID (5) + NONE (0) total length : 164
Apr 05 16:48:33 [IKEv1]: IP = 172.18.124.167, IKE DECODE RECEIVED Message
(msgid=20c2120e) with payloads : HDR + HASH (8) + NONE (0) total length : 48
Apr 05 16:48:33 [IKEv1 DEBUG]: Group = DefaultL2LGroup, IP = 172.18.124.167,
processing hash
Apr 05 16:48:33 [IKEv1 DEBUG]: Group = DefaultL2LGroup, IP = 172.18.124.167,
loading all IPSEC SAs
Apr 05 16:48:33 [IKEv1 DEBUG]: Group = DefaultL2LGroup, IP = 172.18.124.167,
Generating Quick Mode Key!
Apr 05 16:48:33 [IKEv1 DEBUG]: Group = DefaultL2LGroup, IP = 172.18.124.167,
Generating Quick Mode Key!
Apr 05 16:48:33 [IKEv1]: Group = DefaultL2LGroup, IP = 172.18.124.167,
Security negotiation complete for User (DefaultL2LGroup) Responder,
Inbound SPI = 0xd5243861, Outbound SPI = 0x7bb11ead
Apr 05 16:48:33 [IKEv1 DEBUG]: IKE got a KEY_ADD msg for SA: SPI = 0x7bb11ead
Apr 05 16:48:33 [IKEv1 DEBUG]: pitcher: rcv KEY_UPDATE, spi 0xd5243861
Apr 05 16:48:33 [IKEv1]: Group = DefaultL2LGroup, IP = 172.18.124.167,
PHASE 2 COMPLETED (msgid=20c2120e)

```

NAT dinámica PIX remota (6.3.4)

```

tiger(config)#
ISAKMP (0): beginning Main Mode exchange

```

```
crypto_isakmp_process_block:src:172.18.124.166, dest:172.18.124.167 spt:500
dpt:500 OAK_MM exchange
ISAKMP (0): processing SA payload. message ID = 0

ISAKMP (0): Checking ISAKMP transform 1 against priority 10 policy
ISAKMP:      encryption DES-CBC
ISAKMP:      hash MD5
ISAKMP:      default group 2
ISAKMP:      auth pre-share
ISAKMP:      life type in seconds
ISAKMP:      life duration (basic) of 3600
ISAKMP (0): atts are acceptable. Next payload is 0
ISAKMP (0): processing vendor id payload

ISAKMP (0): SA is doing pre-shared key authentication using id type
ID_FQDN return status is IKMP_NO_ERROR
crypto_isakmp_process_block:src:172.18.124.166, dest:172.18.124.167
spt:500 dpt:500 OAK_MM exchange
ISAKMP (0): processing KE payload. message ID = 0
ISAKMP (0): processing NONCE payload. message ID = 0
ISAKMP (0): processing vendor id payload
ISAKMP (0): processing vendor id payload
ISAKMP (0): received xauth v6 vendor id
ISAKMP (0): processing vendor id payload
ISAKMP (0): speaking to another IOS box!
ISAKMP (0): processing vendor id payload
ISAKMP (0): speaking to a VPN3000 concentrator
ISAKMP (0): ID payload
    next-payload : 8
    type         : 2
    protocol     : 17
    port          : 500
    length        : 19
ISAKMP (0): Total payload length: 23
return status is IKMP_NO_ERROR
crypto_isakmp_process_block:src:172.18.124.166, dest:172.18.124.167 spt:500 dpt:500
OAK_MM exchange
ISAKMP (0): processing ID payload. message ID = 0
ISAKMP (0): processing HASH payload. message ID = 0
ISAKMP (0): processing vendor id payload

ISAKMP (0): remote peer supports dead peer detection

ISAKMP (0): SA has been authenticated

ISAKMP (0): beginning Quick Mode exchange, M-ID of 549589518:20c2120eIPSEC(key_engine):
got a queue event...
IPSEC(spi_response): getting spi 0x7bb1lead(2075205293) for SA
from 172.18.124.166 to 172.18.124.167 for prot 3

return status is IKMP_NO_ERROR
ISAKMP (0): sending INITIAL_CONTACT notify
ISAKMP (0): sending NOTIFY message 24578 protocol 1
VPN Peer: ISAKMP: Added new peer: ip:172.18.124.166/500 Total VPN Peers:1
VPN Peer: ISAKMP: Peer ip:172.18.124.166/500 Ref cnt incremented to:1 Total VPN Peers:1
crypto_isakmp_process_block:src:172.18.124.166, dest:172.18.124.167 spt:500 dpt:500
OAK_QM exchange
oakley_process_quick_mode:
OAK_QM_IDLE
ISAKMP (0): processing SA payload. message ID = 549589518

ISAKMP : Checking IPSec proposal 1
```

```

ISAKMP: transform 1, ESP_DES
ISAKMP:   attributes in transform:
ISAKMP:     SA life type in seconds
ISAKMP:     SA life duration (basic) of 28800
ISAKMP:     SA life type in kilobytes
ISAKMP:     SA life duration (VPI) of 0x0 0x46 0x50 0x0
ISAKMP:     encaps is 1
ISAKMP:     authenticator is HMAC-MD5
ISAKMP (0): atts are acceptable.IPSEC(validate_proposal_request): proposal part #1,
(key eng. msg.) dest= 172.18.124.166, src= 172.18.124.167,
dest_proxy= 10.2.2.0/255.255.255.0/0/0 (type=4),
src_proxy= 10.1.1.0/255.255.255.0/0/0 (type=4),
protocol= ESP, transform= esp-des esp-md5-hmac ,
lifedur= 0s and 0kb,
spi= 0x0(0), conn_id= 0, keysize= 0, flags= 0x4

ISAKMP (0): processing NONCE payload. message ID = 549589518

ISAKMP (0): processing ID payload. message ID = 549589518
ISAKMP (0): processing ID payload. message ID = 549589518
ISAKMP (0): Creating IPSec SAs
    inbound SA from 172.18.124.166 to 172.18.124.167 (proxy 10.2.2.0 to 10.1.1.0)
    has spi 2075205293 and conn_id 1 and flags 4
    lifetime of 28800 seconds
    lifetime of 4608000 kilobytes
    outbound SA from 172.18.124.167 to 172.18.124.166 (proxy 10.1.1.0 to 10.2.2.0)
    has spi 3575920737 and conn_id 2 and flags 4
    lifetime of 28800 seconds
    lifetime of 4608000 kilobytesIPSEC(key_engine): got a queue event...
IPSEC(initialize_sas): ,
(key eng. msg.) dest= 172.18.124.167, src= 172.18.124.166,
dest_proxy= 10.1.1.0/255.255.255.0/0/0 (type=4),
src_proxy= 10.2.2.0/255.255.255.0/0/0 (type=4),
protocol= ESP, transform= esp-des esp-md5-hmac ,
lifedur= 28800s and 4608000kb,
spi= 0x7bb11ead(2075205293), conn_id= 1, keysize= 0, flags= 0x4IPSEC(initialize_sas): ,
(key eng. msg.) src= 172.18.124.167, dest= 172.18.124.166,
src_proxy= 10.1.1.0/255.255.255.0/0/0 (type=4),
dest_proxy= 10.2.2.0/255.255.255.0/0/0 (type=4),
protocol= ESP, transform= esp-des esp-md5-hmac ,
lifedur= 28800s and 4608000kb,
spi= 0xd5243861(3575920737), conn_id= 2, keysize= 0, flags= 0x4

```

VPN Peer: IPSEC: Peer ip:172.18.124.166/500 Ref cnt incremented to:2 Total VPN Peers:1
 VPN Peer: IPSEC: Peer ip:172.18.124.166/500 Ref cnt incremented to:3 Total VPN Peers:1
 return status is IKMP_NO_ERROR

[Cliente VPN 4.0.5 en PIX 7.0 central](#)

```

lion(config)# Apr 05 16:49:56 [IKEv1 DEBUG]: IP = 64.102.51.191, processing SA payload
Apr 05 16:49:56 [IKEv1 DEBUG]: IP = 64.102.51.191, processing ke payload
Apr 05 16:49:56 [IKEv1 DEBUG]: IP = 64.102.51.191, processing ISA_KE
Apr 05 16:49:56 [IKEv1 DEBUG]: IP = 64.102.51.191, processing nonce payload
Apr 05 16:49:56 [IKEv1 DEBUG]: IP = 64.102.51.191, Processing ID
Apr 05 16:49:56 [IKEv1 DEBUG]: IP = 64.102.51.191, processing VID payload
Apr 05 16:49:56 [IKEv1 DEBUG]: IP = 64.102.51.191, Received xauth V6 VID
Apr 05 16:49:56 [IKEv1 DEBUG]: IP = 64.102.51.191, processing VID payload
Apr 05 16:49:56 [IKEv1 DEBUG]: IP = 64.102.51.191, Received DPD VID
Apr 05 16:49:56 [IKEv1 DEBUG]: IP = 64.102.51.191, processing VID payload
Apr 05 16:49:56 [IKEv1 DEBUG]: IP = 64.102.51.191, Received NAT-Traversal ver02 VID
Apr 05 16:49:56 [IKEv1 DEBUG]: IP = 64.102.51.191, processing VID payload
Apr 05 16:49:56 [IKEv1 DEBUG]: IP = 64.102.51.191, Received Fragmentation VID
Apr 05 16:49:56 [IKEv1 DEBUG]: IP = 64.102.51.191, IKE Peer included IKE fragmentation

```

capability flags: Main Mode: True Aggressive Mode: False

Apr 05 16:49:56 [IKEv1 DEBUG]: IP = 64.102.51.191, processing VID payload

Apr 05 16:49:56 [IKEv1 DEBUG]: IP = 64.102.51.191, Received Cisco Unity client VID

Apr 05 16:49:56 [IKEv1]: IP = 64.102.51.191, Connection landed on tunnel_group unityclient

Apr 05 16:49:56 [IKEv1 DEBUG]: Group = unityclient, IP = 64.102.51.191, processing IKE SA

Apr 05 16:49:56 [IKEv1 DEBUG]: Group = unityclient, IP = 64.102.51.191, IKE SA Proposal # 1, Transform # 14 acceptable Matches global IKE entry # 3

Apr 05 16:49:56 [IKEv1 DEBUG]: Group = unityclient, IP = 64.102.51.191, constructing ISA_SA for isakmp

Apr 05 16:49:56 [IKEv1 DEBUG]: Group = unityclient, IP = 64.102.51.191, constructing ke payload

Apr 05 16:49:56 [IKEv1 DEBUG]: Group = unityclient, IP = 64.102.51.191, constructing nonce payload

Apr 05 16:49:56 [IKEv1 DEBUG]: Group = unityclient, IP = 64.102.51.191, Generating keys for Responder...

Apr 05 16:49:56 [IKEv1 DEBUG]: Group = unityclient, IP = 64.102.51.191, constructing ID

Apr 05 16:49:56 [IKEv1 DEBUG]: Group = unityclient, IP = 64.102.51.191, construct hash payload

Apr 05 16:49:56 [IKEv1 DEBUG]: Group = unityclient, IP = 64.102.51.191, computing hash

Apr 05 16:49:56 [IKEv1 DEBUG]: Group = unityclient, IP = 64.102.51.191, constructing Cisco Unity VID payload

Apr 05 16:49:56 [IKEv1 DEBUG]: Group = unityclient, IP = 64.102.51.191, constructing xauth V6 VID payload

Apr 05 16:49:56 [IKEv1 DEBUG]: Group = unityclient, IP = 64.102.51.191, constructing dpd vid payload

Apr 05 16:49:56 [IKEv1 DEBUG]: Group = unityclient, IP = 64.102.51.191, constructing Fragmentation VID + extended capabilities payload

Apr 05 16:49:56 [IKEv1 DEBUG]: Group = unityclient, IP = 64.102.51.191, constructing VID payload

Apr 05 16:49:56 [IKEv1 DEBUG]: Group = unityclient, IP = 64.102.51.191, Send Altiga/Cisco VPN3000/Cisco ASA GW VID

Apr 05 16:49:56 [IKEv1]: IP = 64.102.51.191, IKE DECODE SENDING Message
(msgid=0) with payloads : HDR + SA (1) + KE (4) + NONCE (10) + ID (5) +
HASH (8) + VENDOR (13) + VENDOR (13) + VENDOR (13) + VENDOR (13) + VENDOR
(13) + NONE (0) total length : 378

Apr 05 16:49:56 [IKEv1]: IP = 64.102.51.191, IKE DECODE RECEIVED Message
(msgid=0) with payloads : HDR + HASH (8) + NOTIFY (11) + VENDOR (13) +
VENDOR (13) + NONE (0) total length : 116

Apr 05 16:49:56 [IKEv1 DEBUG]: Group = unityclient, IP = 64.102.51.191, processing hash

Apr 05 16:49:56 [IKEv1 DEBUG]: Group = unityclient, IP = 64.102.51.191, computing hash

Apr 05 16:49:56 [IKEv1 DEBUG]: Group = unityclient, IP = 64.102.51.191, Processing Notify payload

Apr 05 16:49:56 [IKEv1 DEBUG]: Group = unityclient, IP = 64.102.51.191, processing VID payload

Apr 05 16:49:56 [IKEv1 DEBUG]: Group = unityclient, IP = 64.102.51.191, Processing IOS/PIX Vendor ID payload (version: 1.0.0, capabilities: 00000408)

Apr 05 16:49:56 [IKEv1 DEBUG]: Group = unityclient, IP = 64.102.51.191, processing VID payload

Apr 05 16:49:56 [IKEv1 DEBUG]: Group = unityclient, IP = 64.102.51.191, Received Cisco Unity client VID

Apr 05 16:49:56 [IKEv1]: IP = 64.102.51.191, IKE DECODE RECEIVED Message
(msgid=a0bb428) with payloads : HDR + HASH (8) + ATTR (14) + NONE (0)
total length: 196

Apr 05 16:49:56 [IKEv1 DEBUG]: process_attr(): Enter!

Apr 05 16:49:56 [IKEv1 DEBUG]: Processing cfg Request attributes

Apr 05 16:49:56 [IKEv1 DEBUG]: MODE_CFG: Received request for IPV4 address!

Apr 05 16:49:56 [IKEv1 DEBUG]: MODE_CFG: Received request for IPV4 net mask!

Apr 05 16:49:56 [IKEv1 DEBUG]: MODE_CFG: Received request for DNS server address!

Apr 05 16:49:56 [IKEv1 DEBUG]: MODE_CFG: Received request for WINS server address!

Apr 05 16:49:56 [IKEv1]: Group = unityclient, IP = 64.102.51.191, Received unsupported transaction mode attribute: 5

Apr 05 16:49:56 [IKEv1 DEBUG]: MODE_CFG: Received request for Banner!

```
Apr  05 16:49:56 [IKEv1 DEBUG]: MODE_CFG: Received request for Save PW setting!
Apr  05 16:49:56 [IKEv1 DEBUG]: MODE_CFG: Received request for Default Domain Name!
Apr  05 16:49:56 [IKEv1 DEBUG]: MODE_CFG: Received request for Split Tunnel List!
Apr  05 16:49:56 [IKEv1 DEBUG]: MODE_CFG: Received request for Split DNS!
Apr  05 16:49:56 [IKEv1 DEBUG]: MODE_CFG: Received request for PFS setting!
Apr  05 16:49:56 [IKEv1 DEBUG]: MODE_CFG: Received request for backup ipsec peer list!
Apr  05 16:49:56 [IKEv1 DEBUG]: MODE_CFG: Received request for Application Version!
Apr  05 16:49:56 [IKEv1]: Group = unityclient, IP = 64.102.51.191, Client Type: WinNT
    Client Application Version: 4.0.5 (Rel)
Apr  05 16:49:56 [IKEv1 DEBUG]: MODE_CFG: Received request for FWTYPE!
Apr  05 16:49:56 [IKEv1 DEBUG]: MODE_CFG: Received request for DHCP hostname
    for DDNS is: tthotus-xp!
Apr  05 16:49:56 [IKEv1 DEBUG]: MODE_CFG: Received request for UDP Port!
Apr  05 16:49:56 [IKEv1 DEBUG]: Group = unityclient, IP = 64.102.51.191,
    constructing blank hash
Apr  05 16:49:56 [IKEv1 DEBUG]: Group = unityclient, IP = 64.102.51.191,
    constructing qm hash
Apr  05 16:49:56 [IKEv1]: IP = 64.102.51.191, IKE DECODE SENDING Message
    (msgid=a0bb428) with payloads : HDR + HASH (8) + ATTR (14) + NONE (0)
    total length : 157
Apr  05 16:49:56 [IKEv1 DEBUG]: Group = unityclient, IP = 64.102.51.191,
    Delay Quick Mode processing, Cert/Trans Exch/RM DSID in progress
Apr  05 16:49:56 [IKEv1 DEBUG]: Group = unityclient, IP = 64.102.51.191,
    Resume Quick Mode processing, Cert/Trans Exch/RM DSID completed
Apr  05 16:49:56 [IKEv1]: Group = unityclient, IP = 64.102.51.191, PHASE 1 COMPLETED
Apr  05 16:49:56 [IKEv1]: IP = 64.102.51.191, Keep-alive type for this connection: DPD
Apr  05 16:49:56 [IKEv1 DEBUG]: Group = unityclient, IP = 64.102.51.191,
    Starting phase 1 rekey timer: 3420000 (ms)
Apr  05 16:49:56 [IKEv1 DEBUG]: Group = unityclient, IP = 64.102.51.191,
    sending notify message
Apr  05 16:49:56 [IKEv1 DEBUG]: Group = unityclient, IP = 64.102.51.191,
    constructing blank hash
Apr  05 16:49:56 [IKEv1 DEBUG]: Group = unityclient, IP = 64.102.51.191,
    constructing qm hash
Apr  05 16:49:56 [IKEv1]: IP = 64.102.51.191, IKE DECODE SENDING Message
    (msgid=9be7674c) with payloads : HDR + HASH (8) + NOTIFY (11) + NONE
    (0) total length : 84
Apr  05 16:49:57 [IKEv1]: IP = 64.102.51.191, IKE DECODE RECEIVED Message
    (msgid=833e7945) with payloads : HDR + HASH (8) + SA (1) + NONCE (10)
    + ID (5) + ID (5) + NONE (0) total length : 1022
Apr  05 16:49:57 [IKEv1 DEBUG]: Group = unityclient, IP = 64.102.51.191, processing hash
Apr  05 16:49:57 [IKEv1 DEBUG]: Group = unityclient, IP = 64.102.51.191,
    processing SA payload
Apr  05 16:49:57 [IKEv1 DEBUG]: Group = unityclient, IP = 64.102.51.191,
    processing nonce payload
Apr  05 16:49:57 [IKEv1 DEBUG]: Group = unityclient, IP = 64.102.51.191, Processing ID
Apr  05 16:49:57 [IKEv1]: Group = unityclient, IP = 64.102.51.191,
    Received remote Proxy Host data in ID Payload: Address 10.3.3.1, Protocol 0, Port 0
Apr  05 16:49:57 [IKEv1 DEBUG]: Group = unityclient, IP = 64.102.51.191, Processing ID
Apr  05 16:49:57 [IKEv1]: Group = unityclient, IP = 64.102.51.191,
    Received local IP Proxy Subnet data in ID Payload: Address 0.0.0.0,
    Mask 0.0.0.0, Protocol 0, Port 0
Apr  05 16:49:57 [IKEv1]: QM IsRekeyed old sa not found by addr
Apr  05 16:49:57 [IKEv1]: Group = unityclient, IP = 64.102.51.191,
    IKE Remote Peer configured for SA: cisco
Apr  05 16:49:57 [IKEv1]: Group = unityclient, IP = 64.102.51.191,
    processing IPSEC SA
Apr  05 16:49:57 [IKEv1 DEBUG]: Group = unityclient, IP = 64.102.51.191,
    IPSecSA Proposal # 14, Transform # 1 acceptable Matches global IPsec SA entry # 1
Apr  05 16:49:57 [IKEv1]: Group = unityclient, IP = 64.102.51.191, IKE: requesting SPI!
Apr  05 16:49:57 [IKEv1 DEBUG]: IKE got SPI from key engine: SPI = 0x05953824
Apr  05 16:49:57 [IKEv1 DEBUG]: Group = unityclient, IP = 64.102.51.191,
    oakley constucting quick mode
Apr  05 16:49:57 [IKEv1 DEBUG]: Group = unityclient, IP = 64.102.51.191,
```

```
constructing blank hash
Apr 05 16:49:57 [IKEv1 DEBUG]: Group = unityclient, IP = 64.102.51.191,
constructing ISA_SA for ipsec
Apr 05 16:49:57 [IKEv1]: Group = unityclient, IP = 64.102.51.191,
Overriding Initiator's IPSec rekeying duration from 2147483 to 28800 seconds
Apr 05 16:49:57 [IKEv1 DEBUG]: Group = unityclient, IP = 64.102.51.191,
constructing ipsec nonce payload
Apr 05 16:49:57 [IKEv1 DEBUG]: Group = unityclient, IP = 64.102.51.191,
constructing proxy ID
Apr 05 16:49:57 [IKEv1 DEBUG]: Group = unityclient, IP = 64.102.51.191,
Transmitting Proxy Id:
    Remote host: 10.3.3.1 Protocol 0 Port 0
    Local subnet: 0.0.0.0 mask 0.0.0.0 Protocol 0 Port 0
Apr 05 16:49:57 [IKEv1 DEBUG]: Group = unityclient, IP = 64.102.51.191,
    Sending RESPONDER LIFETIME notification to Initiator
Apr 05 16:49:57 [IKEv1 DEBUG]: Group = unityclient, IP = 64.102.51.191,
constructing qm hash
Apr 05 16:49:57 [IKEv1]: IP = 64.102.51.191, IKE DECODE SENDING Message
(msgid=833e7945) with payloads : HDR + HASH (8) + SA (1) + NONCE (10)
+ ID (5) + ID (5) + NOTIFY (11) + NONE (0) total length : 176
Apr 05 16:49:57 [IKEv1]: IP = 64.102.51.191, IKE DECODE RECEIVED Message
(msgid=833e7945) with payloads : HDR + HASH (8) + NONE (0) total length : 48
Apr 05 16:49:57 [IKEv1 DEBUG]: Group = unityclient, IP = 64.102.51.191,
processing hash
Apr 05 16:49:57 [IKEv1 DEBUG]: Group = unityclient, IP = 64.102.51.191,
loading all IPSEC SAs
Apr 05 16:49:57 [IKEv1 DEBUG]: Group = unityclient, IP = 64.102.51.191,
Generating Quick Mode Key!
Apr 05 16:49:57 [IKEv1 DEBUG]: Group = unityclient, IP = 64.102.51.191,
Generating Quick Mode Key!
Apr 05 16:49:57 [IKEv1]: Group = unityclient, IP = 64.102.51.191,
Security negotiation complete for User (unityclient) Responder,
Inbound SPI = 0x05953824, Outbound SPI = 0xd08c6486
Apr 05 16:49:57 [IKEv1 DEBUG]: IKE got a KEY_ADD msg for SA: SPI = 0xd08c6486
Apr 05 16:49:57 [IKEv1 DEBUG]: pitcher: rcv KEY_UPDATE, spi 0x5953824
Apr 05 16:49:57 [IKEv1]: Group = unityclient, IP = 64.102.51.191,
Adding static route for client address: 10.3.3.1
Apr 05 16:49:57 [IKEv1]: Group = unityclient, IP = 64.102.51.191, PHASE 2 COMP
LETED (msgid=833e7945)
Apr 05 16:50:07 [IKEv1]: IP = 64.102.51.191, IKE DECODE RECEIVED Message
(msgid=403ee701) with payloads : HDR + HASH (8) + NOTIFY (11) + NONE
(0) total length : 80
Apr 05 16:50:07 [IKEv1 DEBUG]: Group = unityclient, IP = 64.102.51.191,
processing hash
Apr 05 16:50:07 [IKEv1 DEBUG]: Group = unityclient, IP = 64.102.51.191,
Processing Notify payload
Apr 05 16:50:07 [IKEv1 DEBUG]: Group = unityclient, IP = 64.102.51.191,
Received keep-alive of type DPD R-U-THERE (seq number 0x4b55b6e4)
Apr 05 16:50:07 [IKEv1 DEBUG]: Group = unityclient, IP = 64.102.51.191,
Sending keep-alive of type DPD R-U-THERE-ACK (seq number 0x4b55b6e4)
Apr 05 16:50:07 [IKEv1 DEBUG]: Group = unityclient, IP = 64.102.51.191,
constructing blank hash
Apr 05 16:50:07 [IKEv1 DEBUG]: Group = unityclient, IP = 64.102.51.191,
constructing qm hash
Apr 05 16:50:07 [IKEv1]: IP = 64.102.51.191, IKE DECODE SENDING Message
(msgid=78998a29) with payloads : HDR + HASH (8) + NOTIFY (11) + NONE
(0) total length : 80
Apr 05 16:50:17 [IKEv1]: IP = 64.102.51.191, IKE DECODE RECEIVED Message
(msgid=dba719e9) with payloads : HDR + HASH (8) + NOTIFY (11) + NONE (0)
total length : 80
Apr 05 16:50:17 [IKEv1 DEBUG]: Group = unityclient, IP = 64.102.51.191, processing hash
Apr 05 16:50:17 [IKEv1 DEBUG]: Group = unityclient, IP = 64.102.51.191,
Processing Notify payload
Apr 05 16:50:17 [IKEv1 DEBUG]: Group = unityclient, IP = 64.102.51.191,
```

```
Received keep-alive of type DPD R-U-THERE (seq number 0x4b55b6e5)
Apr 05 16:50:17 [IKEv1 DEBUG]: Group = unityclient, IP = 64.102.51.191,
  Sending keep-alive of type DPD R-U-THERE-ACK (seq number 0x4b55b6e5)
Apr 05 16:50:17 [IKEv1 DEBUG]: Group = unityclient, IP = 64.102.51.191,
  constructing blank hash
Apr 05 16:50:17 [IKEv1 DEBUG]: Group = unityclient, IP = 64.102.51.191,
  constructing qm hash
Apr 05 16:50:17 [IKEv1]: IP = 64.102.51.191, IKE DECODE SENDING Message
  (msgid=40456779) with payloads : HDR + HASH (8) + NOTIFY (11) + NONE
  (0) total length : 80
```

Información Relacionada

- [Soporte de producto para dispositivos de seguridad adaptable Cisco ASA de la serie 5500](#)
- [Cisco PIX Firewall Software](#)
- [Referencias de Comandos de Cisco Secure PIX Firewall](#)
- [Avisos de campos de productos de seguridad \(incluido PIX\)](#)
- [Solicitudes de Comentarios \(RFC\)](#)
- [Soporte Técnico y Documentación - Cisco Systems](#)