

Enregistrement ESA et cheminement de l'extension de rétention d'informations

Contenu

[Introduction](#)

[Conditions préalables](#)

[Signaler des données](#)

[Cheminement des données](#)

[Informations connexes](#)

Introduction

Ce document décrit comment augmenter l'enregistrement et rétention d'informations de cheminement sur l'appliance de sécurité du courrier électronique de Cisco (ESA) afin de tenir compte de la superposition de données.

Conditions préalables

Cisco vous recommande de prendre connaissance des rubriques suivantes :

- Cisco ESA
- Appliance de Gestion de sécurité du contenu de Cisco (SMA)

Signaler des données

Quand un SMA est hors ligne ou inaccessible, l'ESA commence à aligner des données d'enregistrement. L'ESA par défaut retient 100 fichiers, chacun avec une durée 15-minute. Essentiellement, l'ESA retient des données pour le courant 1,500 minutes (15 x 100), qui est équivalent à 25 heures. Si le SMA est vers le bas pendant 30 heures, alors vous perdez les données d'enregistrement pour les 5 premières heures (30 heures - 25 heures).

Employez les informations dans cet exemple afin d'augmenter le nombre de fichiers qui sont retenus sur l'ESA :

```
example.com> reportingconfig
```

```
Choose the operation you want to perform:
```

```
- MAILSETUP - Configure reporting for the ESA.
```

```
- MODE - Enable centralized or local reporting for the ESA.
```

```
[> mailsetup
```

```
SenderBase timeout used by the web interface: 2 seconds
```

```
Sender Reputation Multiplier: 3
```

```
The current level of reporting data recording is: unlimited
```

```
No custom second level domains are defined.
```

```
Legacy mailflow report: Disabled
```

Choose the operation you want to perform:

- SENDERBASE - Configure SenderBase timeout for the web interface.
- MULTIPLIER - Configure Sender Reputation Multiplier.
- COUNTERS - Limit counters recorded by the reporting system.
- THROTTLING - Limit unique hosts tracked for rejected connection reporting.
- TLD - Add customer specific domains for reporting rollup.
- STORAGE - How long centralized reporting data will be stored on the C-series before being overwritten.
- LEGACY - Configure legacy mailflow report.

[> **storage**

While in centralized mode the C-series will store reporting data for the M-series to collect. If the M-series does not collect that data then eventually the C-series will begin to overwrite the oldest data with new data.

A maximum of 24 hours of reporting data will be stored.

How many hours of reporting data should be stored before data loss?

[24]> 30

Cheminement des données

De même, quand le SMA est hors ligne ou inaccessible, l'ESA commence à aligner dépister des données. L'ESA retient 60 fichiers, chacun avec une durée de trois-minute. Par conséquent, l'ESA retient les données pour les dernières 180 minutes (60 x 3). N'importe quelles données de cheminement qui ne sont pas récupérées de l'ESA et sont plus anciennes que trois heures sont perdues.

Employez les informations dans cet exemple afin d'augmenter le nombre maximal de dépister des fichiers :

example.com> **trackingconfig**

Choose the operation you want to perform:

- MODE - Set whether tracking is run on box or centralized.

[> **storage**

While in centralized mode the C-series will store tracking data for the M-series to collect. If the M-series does not collect that data then eventually the C-series will begin to overwrite the oldest data with new data.

A maximum of 60 files are presently stored. This means a maximum of 3 hours will be stored, though depending on load that time may be smaller.

How many files should be stored before data loss?

[60]> 500

[Informations connexes](#)

- [AsyncOS pour des guides utilisateurs de sécurité du courrier électronique](#)
- [Support et documentation techniques - Cisco Systems](#)