

Risoluzione dei problemi relativi a uno scenario con schemi Bulkstats e soluzioni consigliate in StarOS

Sommario

[Introduzione](#)

[Prerequisiti](#)

[Requisiti](#)

[Componenti usati](#)

[Premesse](#)

[Problema](#)

[Scenari di test](#)

[Soluzione](#)

Introduzione

Questo documento descrive uno scenario relativo all'aggiunta e all'eliminazione di schemi bulkstat in StarOS insieme a problemi e soluzioni consigliate per questi problemi.

Prerequisiti

Requisiti

Cisco raccomanda la conoscenza dei seguenti argomenti:

- Linux
- StarOS

Cisco consiglia di disporre dei privilegi di accesso:

- modalità nascosta per eseguire la **shell di debug** e accedere al prompt dei comandi di linux shell
- Accesso SFTP (Secure File Transfer Protocol) al nodo StarOS

Componenti usati

Il riferimento delle informazioni contenute in questo documento è StarOS versione 21.16.6.7063.

Le informazioni discusse in questo documento fanno riferimento a dispositivi usati in uno specifico ambiente di emulazione. Su tutti i dispositivi menzionati nel documento la configurazione è stata ripristinata ai valori predefiniti. Se la rete è operativa, valutare attentamente eventuali conseguenze derivanti dall'uso dei comandi.

Premesse

1. Per configurare un file di configurazione per l'archiviazione delle configurazioni relative alle statistiche bulk.
2. Il formato del comando è:

```
configure
    [no] bulkstats config [ schema | supplement ] <url>
end
```

Dove:

- La parola chiave **schema** facoltativa consente di sostituire solo lo schema utilizzando il file fornito e di mantenere la configurazione del server.
- La parola chiave opzionale **additional** consente di integrare la configurazione bulkstats in esecuzione con il contenuto del file di configurazione fornito. Queste parole chiave funzionano solo su file esistenti.
- URL specifica la posizione del file di configurazione bulkstats.

Problema

Impossibile aggiungere nuovi schemi o aggiungere nuovamente lo schema corrente (se eliminato) tramite il prompt dei comandi CLI.

Scenari di test

1. Si è verificato questo problema a causa dell'uso dello **schema di configurazione bulkstat** della cli **<URL>**.
2. Si tratta di un risultato previsto per ogni progetto quando viene utilizzato uno **schema di parole chiave facoltativo**.
3. Lo stesso scenario è stato testato in laboratorio. Ecco i risultati:
Scenario A. Inizialmente è stata configurata la **configurazione bulkstat <url>cli**.

```
[local]MME# show configuration bulkstats
config
    bulkstats collection
    bulkstats historical collection
    bulkstats config /hd-raid/file1
    bulkstats mode
    file 1
    header format Version-20.0,%ipaddr%,%date%-%time%,%localdate%-
%localtime%,%localtz%,%localtzoffset%,%localdate3%-%localtime3%,%swbuild%
```

footer format EndOfFile

card schema cardSch1 format

PPM,card,cardSch1,%epochtime%,%localdate%,%localtime%,%uptime%,%card%,%cpubusy%,%cpuidle%,%numproc%,%memused%,%memtotal%,%numcpu%,%cpu0-cpubusy%,%cpu0-cpuidle%,%cpu0-numproc%,%cpu0-memused%,%cpu0-memtotal%,%cpu0-name%,%cpu0-cpuused-user%,%cpu0-cpuused-sys%,%cpu0-cpuused-io%,%cpu0-cpuused-irq%,%cpu0-cpuused-idle%,%cpu1-cpubusy%,%cpu1-cpuidle%,%cpu1-numproc%,

card schema cardSch2 format

PPM,card,cardSch2,%epochtime%,%localdate%,%localtime%,%uptime%,%card%,%cpu1-memused%,%cpu1-memtotal%,%cpu1-name%,%cpu1-cpuused-user%,%cpu1-cpuused-sys%,%cpu1-cpuused-io%,%cpu1-cpuused-irq%,%cpu1-cpuused-idle%,%cpu2-cpubusy%,%cpu2-cpuidle%,%cpu2-numproc%,%cpu2-memused%,%cpu2-memtotal%,%cpu2-name%,%cpu2-cpuused-user%,%cpu2-cpuused-sys%,%cpu2-cpuused-io%,%cpu2-cpuused-irq%,%cpu2-cpuused-idle%,%cpu3-cpubusy%,%cpu3-cpuidle%,

card schema cardSch3 format

PPM,card,cardSch3,%epochtime%,%localdate%,%localtime%,%uptime%,%card%,%cpu3-numproc%,%cpu3-memused%,%cpu3-memtotal%,%cpu3-name%,%cpu3-cpuused-user%,%cpu3-cpuused-sys%,%cpu3-cpuused-io%,%cpu3-cpuused-irq%,%cpu3-cpuused-idle%,%15avg-cpubusy%,%15peak-cpubusy%,%5avg-cpubusy%,%5peak-cpubusy%,%1avg-cpubusy%,%15avg-memused%,%15peak-memused%,%5avg-memused%,%5peak-memused%,%1avg-memused%,%cpu0-15avg-cpubusy%,%cpu0-15peak-cpubusy%,

port schema portSch1 format

PPM,port,portSch1,%epochtime%,%localdate%,%localtime%,%uptime%,%card%,%port%,%maxrate%,%rxbytes%,%txbytes%,%ucast_inpackets%,%ucast_outpackets%,%mcast_inpackets%,%mcast_outpackets%,%bcast_inpackets%,%bcast_outpackets%,%rxpackets%,%txpackets%,%rxdiscbytes%,%rxdiscpackets%,%txdiscbytes%,%txdiscpackets%,%rxerrorbytes%,%rxerrorpackets%,%txerrorbytes%,%txerrorpackets%,

port schema portSch2 format

PPM,port,portSch2,%epochtime%,%localdate%,%localtime%,%uptime%,%card%,%port%,%frag-rcvd%,%pkt-reassembled%,%frag-tokernel%,%util-rx-curr%,%util-tx-curr%,%util-rx-5min%,%util-tx-5min%,%util-rx-15min%,%util-tx-15min%,%port-5peak-rx-util%,%port-5peak-tx-util%,%port-15peak-rx-util%,%port-15peak-tx-util%,

apn-expansion schema apn1 format PPM,apn-expansion,%epochtime%,%localdate%,%localtime%,

apn-expansion schema apn2 format PPM,apn-expansion,%epochtime%,%localdate%,%localtime%,

apn-expansion schema apn3 format PPM,apn-expansion,%epochtime%,%localdate%,%localtime%,

#exit

#exit

end

[local]MME# show bulkstats schemas

Bulk Statistics Server Configuration:

Server State:	Enabled
File Limit:	7500 KB
Sample Interval:	15 minutes (0D 0H 15M)
Transfer Interval:	480 minutes (0D 8H 0M)
Receiver Mode:	Secondary-on-failure
Historical Data Collection:	Enabled (15 samples stored)

Bulk Statistics Server Statistics:

Records awaiting transmission: 0
Bytes awaiting transmission: 0
Total records collected: 0
Total bytes collected: 0
Total records transmitted: 0
Total bytes transmitted: 0
Total records discarded: 0
Total bytes discarded: 0
Last collection time required: 0 second(s)
Last transfer time required: 0 second(s)
No successful data transfers
No attempted data transfers

File 1

Remote File Format: %date%-%time%

File Header: Version-20.0,%ipaddr%,%date%-%time%,%localdate%-%localtime%,%localtz%,%localtzoffset%,%localdate3%-%localtime3%,%swbuild%

File Footer: EndOfFile

No bulkstats receivers

File Statistics:

Records awaiting transmission: 0
Bytes awaiting transmission: 0
Total records collected: 0
Total bytes collected: 0
Total records transmitted: 0
Total bytes transmitted: 0
Total records discarded: 0
Total bytes discarded: 0
Last transfer time required: 0 second(s)
No successful data transfers

No attempted data transfers

File 2 not configured

File 3 not configured

File 4 not configured

----- Schemas for File 1-----

Type	Name	Active-Only	Format
card	cardSch1	No	PPM,card,cardSch1,%epochtime%,%localdate%,%localtime%,%uptime%,%card%,%cpubusy%,%cpuidle%,%numproc%,%memused%,%memtotal%,%numcpu%,%cpu0-cpubusy%,%cpu0-cpuidle%,%cpu0-numproc%,%cpu0-memused%,%cpu0-memtotal%,%cpu0-name%,%cpu0-cpuused-user%,%cpu0-cpuused-sys%,%cpu0-cpuused-io%,%cpu0-cpuused-irq%,%cpu0-cpuused-idle%,%cpu1-cpubusy%,%cpu1-cpuidle%,%cpu1-numproc%,
card	cardSch2	No	PPM,card,cardSch2,%epochtime%,%localdate%,%localtime%,%uptime%,%card%,%cpu1-memused%,%cpu1-memtotal%,%cpu1-name%,%cpu1-cpuused-user%,%cpu1-cpuused-sys%,%cpu1-cpuused-io%,%cpu1-cpuused-irq%,%cpu1-cpuused-idle%,%cpu2-cpubusy%,%cpu2-cpuidle%,%cpu2-numproc%,%cpu2-memused%,%cpu2-memtotal%,%cpu2-name%,%cpu2-cpuused-user%,%cpu2-cpuused-sys%,%cpu2-cpuused-io%,%cpu2-cpuused-irq%,%cpu2-cpuused-idle%,%cpu3-cpubusy%,%cpu3-cpuidle%,
card	cardSch3	No	PPM,card,cardSch3,%epochtime%,%localdate%,%localtime%,%uptime%,%card%,%cpu3-numproc%,%cpu3-memused%,%cpu3-memtotal%,%cpu3-name%,%cpu3-cpuused-user%,%cpu3-cpuused-sys%,%cpu3-cpuused-io%,%cpu3-cpuused-irq%,%cpu3-cpuused-idle%,%15avg-cpubusy%,%15peak-cpubusy%,%5avg-cpubusy%,%5peak-cpubusy%,%1avg-cpubusy%,%15avg-memused%,%15peak-memused%,%5avg-memused%,%5peak-memused%,%1avg-memused%,%cpu0-15avg-cpubusy%,%cpu0-15peak-cpubusy%,
port	portSch1	No	PPM,port,portSch1,%epochtime%,%localdate%,%localtime%,%uptime%,%card%,%port%,%maxrate%,%rxbytes%,%txbytes%,%ucast_inpackets%,%ucast_outpackets%,%mcast_inpackets%,%mcast_outpackets%,%bcast_inpackets%,%bcast_outpackets%,%rxpackets%,%txpackets%,%rxdiscbytes%,%rxdiscpackets%,%txdiscbytes%,%txdiscpackets%,%rxerrorbytes%,%rxerrorpackets%,%txerrorbytes%,%txerrorpackets%,
port	portSch2	No	PPM,port,portSch2,%epochtime%,%localdate%,%localtime%,%uptime%,%card%,%port%,%frag-rcvd%,%pkt-reassembled%,%frag-tokenel%,%util-rx-curr%,%util-tx-curr%,%util-rx-5min%,%util-tx-5min%,%util-rx-15min%,%util-tx-15min%,%port-5peak-rx-util%,%port-5peak-tx-util%,%port-15peak-rx-util%,%port-15peak-tx-util%,
apn-expansion	apn1	No	PPM,apn-expansion,%epochtime%,%localdate%,%localtime%,
apn-expansion	apn2	No	PPM,apn-expansion,%epochtime%,%localdate%,%localtime%,

```
apn-expansion apn3                No                PPM,apn-
expansion,%epochtime%,%localdate%,%localtime%,
mon-di-net   mdn1                No                PPM,%epochtime%,%localdate%,%localtime%,
```

```
[local]MME#
```

Scenario B. Per aggiungere lo schema della parola chiave opzionale, è necessario prima rimuovere la cli bulkstat **senza configurare bulkstats**. Quando si esegue **no bulkstats config**, tutti gli schemi correnti nel nodo vengono eliminati.

```
[local]MME#
```

```
[local]MME# configure
```

```
[local]MME(config)# bulkstats collection
```

```
[local]MME(config)# no bulkstats config
```

```
<cr>                - newline
```

```
[local]MME(config)# no bulkstats config
```

```
[local]MME(config)# end
```

```
[local]MME# show configuration bulkstats
```

```
config
```

```
bulkstats collection
```

```
bulkstats historical collection
```

```
bulkstats mode
```

```
file 1
```

```
header format Version-20.0,%ipaddr%,%date%-%time%,%localdate%-
%localtime%,%localtz%,%localtzoffset%,%localdate3%-%localtime3%,%swbuild%
```

```
footer format EndOfFile
```

```
#exit
```

```
#exit
```

```
end
```

```
[local]MME# show bulkstats schemas
```

```
Bulk Statistics Server Configuration:
```

```
Server State:                Enabled
```

```
File Limit:                  7500 KB
```

```
Sample Interval:            15 minutes (0D 0H 15M)
```

```
Transfer Interval:          480 minutes (0D 8H 0M)
```

```
Receiver Mode:               Secondary-on-failure
```

```
Historical Data Collection:  Enabled (15 samples stored)
```

Bulk Statistics Server Statistics:

Records awaiting transmission: 0
Bytes awaiting transmission: 0
Total records collected: 0
Total bytes collected: 0
Total records transmitted: 0
Total bytes transmitted: 0
Total records discarded: 0
Total bytes discarded: 0
Last collection time required: 0 second(s)
Last transfer time required: 0 second(s)
No successful data transfers
No attempted data transfers

File 1

Remote File Format: %date%-%time%

File Header: Version-20.0,%ipaddr%,%date%-%time%,%localdate%-%localtime%,%localtz%,%localtzoffset%,%localdate3%-%localtime3%,%swbuild%

File Footer: EndOfFile

No bulkstats receivers

File Statistics:

Records awaiting transmission: 0
Bytes awaiting transmission: 0
Total records collected: 0
Total bytes collected: 0
Total records transmitted: 0
Total bytes transmitted: 0
Total records discarded: 0
Total bytes discarded: 0
Last transfer time required: 0 second(s)

No successful data transfers

No attempted data transfers

File 2 not configured

File 3 not configured

File 4 not configured

[local]MME#

[local]MME#

Scenario C. Quindi la CLI **bulkstat - schema di configurazione <url>** è configurato. Tutte le configurazioni e gli schemi presenti nel file di configurazione vengono aggiunti al nodo.

[local]MME# configure

[local]MME(config)# bulkstats collection

[local]MME(config)# bulkstats config schema /hd-raid/file2

Info: config

Info: bulkstats mode

Info: file 2

Info: header format Version-20.0,%ipaddr%,%date%-%time%,%localdate%-%localtime%,%localtz%,%localtzoffset%,%localdate3%-%localtime3%,%swbuild%

Info: footer format EndOfFile

Info: diameter-auth schema diameter-authSch1 format PPM,diameter-auth,diameter-authSch1,%epochtime%,%localdate%,%localtime%,%uptime%,%vpnid%,%vpnname%,%ipaddr%,%port%,%servertype%,%group%,%der-req-id-sent%,%der-req-aka-chal-sent%,%der-req-retried%,%dea-chal-rcvd%,%dea-acpt-rcvd%,%dea-timeout%,%dea-badauth%,%dea-malformed%,%dea-malformed-avp%,%dea-dropped%,%rar-req-rcvd%,%raa-ans-acpt-sent%,%aar-req-sent%,%str-req-sent%,%str-req-retried%,

Info: diameter-auth schema diameter-authSch2 format PPM,diameter-auth,diameter-authSch2,%epochtime%,%localdate%,%localtime%,%uptime%,%vpnid%,%vpnname%,%ipaddr%,%port%,%sta-ans-acpt-rcvd%,%asr-req-rcvd%,%asa-rsp-acpt-sent%,%asa-rsp-rej-sent%,%req-sock-write-err%,%rsp-sock-write-err%,%any-sock-read-err%,%rem-disconnect%,%loc-disconnect%,

Info: diameter-auth schema diameter-authSch3 format PPM,diameter-auth,diameter-authSch3,%epochtime%,%localdate%,%localtime%,%uptime%,%vpnid%,%vpnname%,%ipaddr%,%port%,%peer%,%diameter-auth-msg-multiround%,%diameter-auth-msg-success%,%diameter-auth-msg-err-protocol%,%diameter-auth-msg-err-transient%,%diameter-auth-msg-err-permanent%,%diameter-auth-msg-err-other%,%aaa-req-received%,%aaa-req-timeouts%,%aaa-req-dropped%,

Info: schema systemSch1 format

PPM,system,systemSch1,%epochtime%,%localdate%,%localtime%,%uptime%,%sess-ttlarrived%,%sess-ttlrejected%,%sess-ttlconnected%,%sess-ttlfailed%,%sess-ttldisconn%,%sess-ttlhandoff%,%sess-

ttlrenewal%,%sess-ttlcallop%,%sess-ttlauthsucc%,%sess-ttlauthfail%,%sess-curaaaactive%,%sess-curaaaadeleting%,%sess-curaaaacctpending%,%sess-curaaaacctitemsused%,%sess-curaaaacctitemsmax%,%sess-curaaabuffused%,%sess-curaaabuffmax%,%sess-ttlaaacancauth%,%sess-ttlaaaacctpurged%,%sess-ttlradacctpurged%,%sess-ttllcpup%,

Info: schema systemSch10 format

PPM,system,systemSch10,%epochtime%,%localdate%,%localtime%,%uptime%,%aaa-ttlpseudoauthreq%,%aaa-curpseudoauthreq%,%aaa-ttlauthnulluser%,%aaa-ttlacctsucc%,%aaa-ttlacctpurged%,%aaa-ttlacctcancelled%,%aaa-ttlacctkeepalivesuccess%,%aaa-ttlacctkeepalivetimeout%,%aaa-ttlacctkeepalivepurged%,%aaa-ttlradacctreq%,%aaa-ttlradacctcancelled%,%aaa-ttlradacctpurged%,%aaa-ttlradacctreqretried%,%aaa-ttlradacctrspdropped%,%aaa-ttlmgrpurgedrequests%,%diamauth-msg-mareq%,%diamauth-msg-maans%,%diamauth-msg-marretry%,%diamauth-msg-maamtimeout%,%diamauth-msg-maadropped%,%diamauth-msg-sareq%,

Info: schema systemSch100 format

PPM,system,systemSch100,%epochtime%,%localdate%,%localtime%,%uptime%,%sess-bearerdur-24hr-qci6%,%sess-bearerdur-over24hr-qci6%,%sess-bearerdur-2day-qci6%,%sess-bearerdur-4day-qci6%,%sess-bearerdur-5day-qci6%,%sess-bearerdur-5sec-qci7%,%sess-bearerdur-10sec-qci7%,%sess-bearerdur-30sec-qci7%,%sess-bearerdur-1min-qci7%,%sess-bearerdur-2min-qci7%,%sess-bearerdur-5min-qci7%,%sess-bearerdur-15min-qci7%,%sess-bearerdur-30min-qci7%,%sess-bearerdur-1hr-qci7%,%sess-bearerdur-4hr-qci7%,%sess-bearerdur-12hr-qci7%,%sess-bearerdur-24hr-qci7%,%sess-bearerdur-over24hr-qci7%,%sess-bearerdur-2day-qci7%,%sess-bearerdur-4day-qci7%,%sess-bearerdur-5day-qci7%,

Info: sgs schema sgsSch1 format

PPM,sgs,sgsSch1,%epochtime%,%localdate%,%localtime%,%uptime%,%vpnname%,%vpnid%,%servname%,%servid%,%pag-req-tx%,%pag-req-retx%,%pag-req-rx%,%pag-rej-tx%,%pag-rej-retx%,%pag-rej-rx%,%service-req-tx%,%service-req-retx%,%service-req-rx%,%dl-ud-tx%,%dl-ud-retx%,%dl-ud-rx%,%ul-ud-tx%,%ul-ud-retx%,%ul-ud-rx%,%localupd-req-tx%,%localupd-req-retx%,

Info: sgs schema sgsSch2 format

PPM,sgs,sgsSch2,%epochtime%,%localdate%,%localtime%,%uptime%,%vpnname%,%vpnid%,%servname%,%servid%,%localupd-req-rx%,%localupd-accept-tx%,%localupd-accept-retx%,%localupd-accept-rx%,%localupd-rej-tx%,%localupd-rej-retx%,%localupd-rej-rx%,%tmsi-reloc-tx%,%tmsi-reloc-retx%,%tmsi-reloc-rx%,%alert-req-tx%,%alert-req-retx%,%alert-req-rx%,%alert-ack-tx%,%alert-ack-retx%,%alert-ack-rx%,%alert-rej-tx%,%alert-rej-retx%,%alert-rej-rx%,%ue-actind-tx%,%ue-actind-retx%,

Info: sgs schema sgsSch3 format

PPM,sgs,sgsSch3,%epochtime%,%localdate%,%localtime%,%uptime%,%vpnname%,%vpnid%,%servname%,%servid%,%ue-actind-rx%,%eps-detind-tx%,%eps-detind-retx%,%eps-detind-rx%,%eps-detack-tx%,%eps-detack-retx%,%eps-detack-rx%,%imsi-detind-tx%,%imsi-detind-retx%,%imsi-detind-rx%,%imsi-detack-tx%,%imsi-detack-retx%,%imsi-detack-rx%,,,,,,%mm-inforeq-tx%,%mm-inforeq-retx%,

Info: exit

[local]MME(config)# end

[local]MME#

[local]MME# show configuration bulkstats

config

bulkstats collection

bulkstats historical collection

bulkstats config schema /hd-raid/file2

bulkstats mode

file 1

header format Version-20.0,%ipaddr%,%date%-%time%,%localdate%

%localtime%,%localtz%,%localtzoffset%,%localdate3%-%localtime3%,%swbuild%

footer format EndOfFile

#exit

file 2

header format Version-20.0,%ipaddr%,%date%-%time%,%localdate%-
%localtime%,%localtz%,%localtzoffset%,%localdate3%-%localtime3%,%swbuild%

footer format EndOfFile

schema systemSch1 format

PPM,system,systemSch1,%epochtime%,%localdate%,%localtime%,%uptime%,%sess-ttlarrived%,%sess-ttlrejected%,%sess-ttlconnected%,%sess-ttlfailed%,%sess-ttldisconn%,%sess-ttlhandoff%,%sess-ttlrenewal%,%sess-ttlcallop%,%sess-ttlauthsucc%,%sess-ttlauthfail%,%sess-curaaaactive%,%sess-curaaaadeleting%,%sess-curaaaacctpending%,%sess-curaaaacctitemsused%,%sess-curaaaacctitemsmax%,%sess-curaaabuffused%,%sess-curaaabuffmax%,%sess-ttlaaacancauth%,%sess-ttlaaaacctpurged%,%sess-ttlradacctpurged%,%sess-ttllcpup%,

schema systemSch10 format

PPM,system,systemSch10,%epochtime%,%localdate%,%localtime%,%uptime%,%aaa-ttlpseudoauthreq%,%aaa-curpseudoauthreq%,%aaa-ttlauthnulluser%,%aaa-ttlacctsucc%,%aaa-ttlacctpurged%,%aaa-ttlacctcancelled%,%aaa-ttlacctkeepalivesuccess%,%aaa-ttlacctkeepalivetimeout%,%aaa-ttlacctkeepalivepurged%,%aaa-ttlradacctreq%,%aaa-ttlradacctcancelled%,%aaa-ttlradacctpurged%,%aaa-ttlradacctreqretried%,%aaa-ttlradacctrspdropped%,%aaa-ttlmgrpurgedrequests%,%diamauth-msg-mareq%,%diamauth-msg-maans%,%diamauth-msg-marretry%,%diamauth-msg-maamtimeout%,%diamauth-msg-maadropped%,%diamauth-msg-sareq%,

schema systemSch100 format

PPM,system,systemSch100,%epochtime%,%localdate%,%localtime%,%uptime%,%sess-bearerdur-24hr-qci6%,%sess-bearerdur-over24hr-qci6%,%sess-bearerdur-2day-qci6%,%sess-bearerdur-4day-qci6%,%sess-bearerdur-5day-qci6%,%sess-bearerdur-5sec-qci7%,%sess-bearerdur-10sec-qci7%,%sess-bearerdur-30sec-qci7%,%sess-bearerdur-1min-qci7%,%sess-bearerdur-2min-qci7%,%sess-bearerdur-5min-qci7%,%sess-bearerdur-15min-qci7%,%sess-bearerdur-30min-qci7%,%sess-bearerdur-1hr-qci7%,%sess-bearerdur-4hr-qci7%,%sess-bearerdur-12hr-qci7%,%sess-bearerdur-24hr-qci7%,%sess-bearerdur-over24hr-qci7%,%sess-bearerdur-2day-qci7%,%sess-bearerdur-4day-qci7%,%sess-bearerdur-5day-qci7%,

diameter-auth schema diameter-authSch1 format PPM,diameter-auth,diameter-authSch1,%epochtime%,%localdate%,%localtime%,%uptime%,%vpnid%,%vpnname%,%ipaddr%,%port%,%servertype%,%group%,%der-req-id-sent%,%der-req-aka-chal-sent%,%der-req-retried%,%dea-chal-rcvd%,%dea-acpt-rcvd%,%dea-timeout%,%dea-badauth%,%dea-malformed%,%dea-malformed-avp%,%dea-dropped%,%rar-req-rcvd%,%raa-ans-acpt-sent%,%aar-req-sent%,%str-req-sent%,%str-req-retried%,

diameter-auth schema diameter-authSch2 format PPM,diameter-auth,diameter-authSch2,%epochtime%,%localdate%,%localtime%,%uptime%,%vpnid%,%vpnname%,%ipaddr%,%port%,%staans-acpt-rcvd%,%asr-req-rcvd%,%asa-rsp-acpt-sent%,%asa-rsp-rej-sent%,%req-sock-write-err%,%rsp-sock-write-err%,%any-sock-read-err%,%rem-disconnect%,%loc-disconnect%,

diameter-auth schema diameter-authSch3 format PPM,diameter-auth,diameter-authSch3,%epochtime%,%localdate%,%localtime%,%uptime%,%vpnid%,%vpnname%,%ipaddr%,%port%,%peer%,%diameter-auth-msg-multiround%,%diameter-auth-msg-success%,%diameter-auth-msg-err-protocol%,%diameter-auth-msg-err-transient%,%diameter-auth-msg-err-permanent%,%diameter-auth-msg-err-other%,%aaa-req-received%,%aaa-req-timeouts%,%aaa-req-dropped%,

sgs schema sgsSch1 format

PPM,sgs,sgsSch1,%epochtime%,%localdate%,%localtime%,%uptime%,%vpnname%,%vpnid%,%servname%,%servid%,%pag-req-tx%,%pag-req-retx%,%pag-req-rx%,%pag-rej-tx%,%pag-rej-retx%,%pag-rej-rx%,%service-req-tx%,%service-req-retx%,%service-req-rx%,%dl-ud-tx%,%dl-ud-retx%,%dl-ud-rx%,%ul-ud-tx%,%ul-ud-retx%,%ul-ud-rx%,%localupd-req-tx%,%localupd-req-retx%,

sgs schema sgsSch2 format

```
PPM,sgs,sgsSch2,%epochtime%,%localdate%,%localtime%,%uptime%,%vpnname%,%vpnid%,%servname%,%servi  
d%,%localupd-req-rx%,%localupd-accept-tx%,%localupd-accept-retx%,%localupd-accept-rx%,%localupd-  
rej-tx%,%localupd-rej-retx%,%localupd-rej-rx%,%tmsi-reloc-tx%,%tmsi-reloc-retx%,%tmsi-reloc-  
rx%,%alert-req-tx%,%alert-req-retx%,%alert-req-rx%,%alert-ack-tx%,%alert-ack-retx%,%alert-ack-  
rx%,%alert-rej-tx%,%alert-rej-retx%,%alert-rej-rx%,%ue-actind-tx%,%ue-actind-retx%,
```

```
sgs schema sgsSch3 format
```

```
PPM,sgs,sgsSch3,%epochtime%,%localdate%,%localtime%,%uptime%,%vpnname%,%vpnid%,%servname%,%servi  
d%,%ue-actind-rx%,%eps-detind-tx%,%eps-detind-retx%,%eps-detind-rx%,%eps-detack-tx%,%eps-detack-  
retx%,%eps-detack-rx%,%imsi-detind-tx%,%imsi-detind-retx%,%imsi-detind-rx%,%imsi-detack-  
tx%,%imsi-detack-retx%,%imsi-detack-rx%,,,,,,%mm-inforeq-tx%,%mm-inforeq-retx%,
```

```
#exit
```

```
#exit
```

```
end
```

```
[local]MME#
```

Scenario D. In seguito non sarà possibile aggiungere nuovi schemi. Quando si tenta di rimuovere uno schema corrente e di aggiungerlo nuovamente, lo schema viene eliminato ma non sarà possibile aggiungerlo nuovamente. Tuttavia, lo schema corrente era ancora presente nel file di configurazione (file di configurazione presente nell'URL).

```
[local]MME# configure
```

```
[local]MME(config)# bulkstats mode
```

```
mode - Enters bulk statistics configuration mode, where you can define what  
statistics to collect
```

```
[local]MME(config)# bulkstats mode
```

```
[local]MME(config-bulkstats)# file 1
```

```
[local]MME(config-bulkstats-file-1)# mon-di-net schema mdn1 format PPM,%epochti  
me%,%localdate%,%localtime%,
```

```
[local]MME(config-bulkstats-file-1)# exit
```

```
[local]MME(config-bulkstats)# file 2
```

```
[local]MME(config-bulkstats-file-2)# mon-di-net schema mdn2 format PPM,%epochti  
me%,
```

```
[local]MME(config-bulkstats-file-2)# end
```

```
[local]MME# show bulkstats schemas
```

```
Bulk Statistics Server Configuration:
```

```
Server State: Enabled  
File Limit: 7500 KB  
Sample Interval: 15 minutes (0D 0H 15M)
```

Transfer Interval: 480 minutes (0D 8H 0M)
Receiver Mode: Secondary-on-failure
Historical Data Collection: Enabled (15 samples stored)

Bulk Statistics Server Statistics:

Records awaiting transmission: 0
Bytes awaiting transmission: 0
Total records collected: 0
Total bytes collected: 0
Total records transmitted: 0
Total bytes transmitted: 0
Total records discarded: 0
Total bytes discarded: 0
Last collection time required: 0 second(s)
Last transfer time required: 0 second(s)
No successful data transfers
No attempted data transfers

File 1

Remote File Format: %date%-%time%

File Header: Version-20.0,%ipaddr%,%date%-%time%,%localdate%-%localtime%,%localtz%,%localtzoffset%,%localdate3%-%localtime3%,%swbuild%

File Footer: EndOfFile

No bulkstats receivers

File Statistics:

Records awaiting transmission: 0
Bytes awaiting transmission: 0
Total records collected: 0
Total bytes collected: 0
Total records transmitted: 0
Total bytes transmitted: 0

Total records discarded: 0
Total bytes discarded: 0
Last transfer time required: 0 second(s)
No successful data transfers
No attempted data transfers

File 2

Remote File Format: %date%-%time%

File Header: Version-20.0,%ipaddr%,%date%-%time%,%localdate%-%localtime%,%localtz%,%localtzoffset%,%localdate3%-%localtime3%,%swbuild%

File Footer: EndOfFile

No bulkstats receivers

File Statistics:

Records awaiting transmission: 0
Bytes awaiting transmission: 0
Total records collected: 0
Total bytes collected: 0
Total records transmitted: 0
Total bytes transmitted: 0
Total records discarded: 0
Total bytes discarded: 0
Last transfer time required: 0 second(s)
No successful data transfers
No attempted data transfers

File 3 not configured

File 4 not configured

----- Schemas for File 2-----

Type	Name	Active-Only Format
------	------	--------------------

system systemSch1 No
PPM,system,systemSch1,%epochtime%,%localdate%,%localtime%,%uptime%,%sess-ttlarrived%,%sess-ttlrejected%,%sess-ttlconnected%,%sess-ttlfailed%,%sess-ttldisconn%,%sess-ttlhandoff%,%sess-ttlrenewal%,%sess-ttlcallop%,%sess-ttlauthsucc%,%sess-ttlauthfail%,%sess-curaaaactive%,%sess-curaaaadeleting%,%sess-curaaaacctpending%,%sess-curaaaacctitemsused%,%sess-curaaaacctitemsmax%,%sess-curaaaabuffused%,%sess-curaaaabuffmax%,%sess-ttlaaacanauth%,%sess-ttlaaacctpurged%,%sess-ttlradacctpurged%,%sess-ttllcpup%,

system systemSch10 No
PPM,system,systemSch10,%epochtime%,%localdate%,%localtime%,%uptime%,%aaa-ttlpseudoauthreq%,%aaa-curpseudoauthreq%,%aaa-ttlauthnulluser%,%aaa-ttlacctsucc%,%aaa-ttlacctpurged%,%aaa-ttlacctcancelled%,%aaa-ttlacctkeepalivesuccess%,%aaa-ttlacctkeepalivetimeout%,%aaa-ttlacctkeepalivepurged%,%aaa-ttlradacctreq%,%aaa-ttlradacctcancelled%,%aaa-ttlradacctpurged%,%aaa-ttlradacctreqretried%,%aaa-ttlradacctrspdropped%,%aaa-ttlmgrpurgedrequests%,%diamauth-msg-mareq%,%diamauth-msg-maans%,%diamauth-msg-marretry%,%diamauth-msg-maamtimeout%,%diamauth-msg-maadropped%,%diamauth-msg-sareq%,

system systemSch100 No
PPM,system,systemSch100,%epochtime%,%localdate%,%localtime%,%uptime%,%sess-bearerdur-24hr-qci6%,%sess-bearerdur-over24hr-qci6%,%sess-bearerdur-2day-qci6%,%sess-bearerdur-4day-qci6%,%sess-bearerdur-5day-qci6%,%sess-bearerdur-5sec-qci7%,%sess-bearerdur-10sec-qci7%,%sess-bearerdur-30sec-qci7%,%sess-bearerdur-1min-qci7%,%sess-bearerdur-2min-qci7%,%sess-bearerdur-5min-qci7%,%sess-bearerdur-15min-qci7%,%sess-bearerdur-30min-qci7%,%sess-bearerdur-1hr-qci7%,%sess-bearerdur-4hr-qci7%,%sess-bearerdur-12hr-qci7%,%sess-bearerdur-24hr-qci7%,%sess-bearerdur-over24hr-qci7%,%sess-bearerdur-2day-qci7%,%sess-bearerdur-4day-qci7%,%sess-bearerdur-5day-qci7%,

diameter-auth diameter-authSch1 No PPM,diameter-auth,diameter-authSch1,%epochtime%,%localdate%,%localtime%,%uptime%,%vpnid%,%vpnname%,%ipaddr%,%port%,%servertype%,%group%,%der-req-id-sent%,%der-req-aka-chal-sent%,%der-req-retried%,%dea-chal-rcvd%,%dea-acpt-rcvd%,%dea-timeout%,%dea-badauth%,%dea-malformed%,%dea-malformed-avp%,%dea-dropped%,%rar-req-rcvd%,%raa-ans-acpt-sent%,%aar-req-sent%,%str-req-sent%,%str-req-retried%,

diameter-auth diameter-authSch2 No PPM,diameter-auth,diameter-authSch2,%epochtime%,%localdate%,%localtime%,%uptime%,%vpnid%,%vpnname%,%ipaddr%,%port%,%staans-acpt-rcvd%,%asr-req-rcvd%,%asa-rsp-acpt-sent%,%asa-rsp-rej-sent%,%req-sock-write-err%,%rsp-sock-write-err%,%any-sock-read-err%,%rem-disconnect%,%loc-disconnect%,

diameter-auth diameter-authSch3 No PPM,diameter-auth,diameter-authSch3,%epochtime%,%localdate%,%localtime%,%uptime%,%vpnid%,%vpnname%,%ipaddr%,%port%,%peer%,%diameter-auth-msg-multiround%,%diameter-auth-msg-success%,%diameter-auth-msg-err-protocol%,%diameter-auth-msg-err-transient%,%diameter-auth-msg-err-permanent%,%diameter-auth-msg-err-other%,%aaa-req-received%,%aaa-req-timeouts%,%aaa-req-dropped%,

sgs sgsSch1 No
PPM,sgs,sgsSch1,%epochtime%,%localdate%,%localtime%,%uptime%,%vpnname%,%vpnid%,%servname%,%servid%,%pag-req-tx%,%pag-req-retx%,%pag-req-rx%,%pag-rej-tx%,%pag-rej-retx%,%pag-rej-rx%,%service-req-tx%,%service-req-retx%,%service-req-rx%,%dl-ud-tx%,%dl-ud-retx%,%dl-ud-rx%,%ul-ud-tx%,%ul-ud-retx%,%ul-ud-rx%,%localupd-req-tx%,%localupd-req-retx%,

sgs sgsSch2 No
PPM,sgs,sgsSch2,%epochtime%,%localdate%,%localtime%,%uptime%,%vpnname%,%vpnid%,%servname%,%servid%,%localupd-req-rx%,%localupd-accept-tx%,%localupd-accept-retx%,%localupd-accept-rx%,%localupd-rej-tx%,%localupd-rej-retx%,%localupd-rej-rx%,%tmsi-reloc-tx%,%tmsi-reloc-retx%,%tmsi-reloc-rx%,%alert-req-tx%,%alert-req-retx%,%alert-req-rx%,%alert-ack-tx%,%alert-ack-retx%,%alert-ack-rx%,%alert-rej-tx%,%alert-rej-retx%,%alert-rej-rx%,%ue-actind-tx%,%ue-actind-retx%,

sgs sgsSch3 No
PPM,sgs,sgsSch3,%epochtime%,%localdate%,%localtime%,%uptime%,%vpnname%,%vpnid%,%servname%,%servid%,%ue-actind-rx%,%eps-detind-tx%,%eps-detind-retx%,%eps-detind-rx%,%eps-detack-tx%,%eps-detack-retx%,%eps-detack-rx%,%imsi-detind-tx%,%imsi-detind-retx%,%imsi-detind-rx%,%imsi-detack-

tx%,%imsi-detack-retx%,%imsi-detack-rx%,,,,,,%mm-inforeq-tx%,%mm-inforeq-retx%,

[local]MME# configure

[local]MME(config)# bulkstats mode

[local]MME(config-bulkstats)# file 2

[local]MME(config-bulkstats-file-2)# no sgs

sgs - Removes sgs bulk statistics schema

[local]MME(config-bulkstats-file-2)# no sgs schema sgsSch1

[local]MME(config-bulkstats-file-2)# end

[local]MME# show bulkstats schemas

Bulk Statistics Server Configuration:

Server State:	Enabled
File Limit:	7500 KB
Sample Interval:	15 minutes (0D 0H 15M)
Transfer Interval:	480 minutes (0D 8H 0M)
Receiver Mode:	Secondary-on-failure
Historical Data Collection:	Enabled (15 samples stored)

Bulk Statistics Server Statistics:

Records awaiting transmission:	0
Bytes awaiting transmission:	0
Total records collected:	0
Total bytes collected:	0
Total records transmitted:	0
Total bytes transmitted:	0
Total records discarded:	0
Total bytes discarded:	0
Last collection time required:	0 second(s)
Last transfer time required:	0 second(s)
No successful data transfers	
No attempted data transfers	

File 1

Remote File Format: %date%-%time%

File Header: Version-20.0,%ipaddr%,%date%-%time%,%localdate%-%localtime%,%localtz%,%localtzoffset%,%localdate3%-%localtime3%,%swbuild%

File Footer: EndOfFile

No bulkstats receivers

File Statistics:

Records awaiting transmission: 0
Bytes awaiting transmission: 0
Total records collected: 0
Total bytes collected: 0
Total records transmitted: 0
Total bytes transmitted: 0
Total records discarded: 0
Total bytes discarded: 0
Last transfer time required: 0 second(s)
No successful data transfers
No attempted data transfers

File 2

Remote File Format: %date%-%time%

File Header: Version-20.0,%ipaddr%,%date%-%time%,%localdate%-%localtime%,%localtz%,%localtzoffset%,%localdate3%-%localtime3%,%swbuild%

File Footer: EndOfFile

No bulkstats receivers

File Statistics:

Records awaiting transmission: 0
Bytes awaiting transmission: 0
Total records collected: 0
Total bytes collected: 0
Total records transmitted: 0
Total bytes transmitted: 0
Total records discarded: 0

Total bytes discarded: 0
Last transfer time required: 0 second(s)
No successful data transfers
No attempted data transfers

File 3 not configured

File 4 not configured

----- Schemas for File 2-----

Type	Name	Active-Only	Format
system	systemSch1	No	PPM,system,systemSch1,%epochtime%,%localdate%,%localtime%,%uptime%,%sess-ttlarrived%,%sess-ttlrejected%,%sess-ttlconnected%,%sess-ttlfailed%,%sess-ttldisconnect%,%sess-ttlhandoff%,%sess-ttlrenewal%,%sess-ttlcallop%,%sess-ttlauthsucc%,%sess-ttlauthfail%,%sess-curaaaactive%,%sess-curaaaadeleting%,%sess-curaaaacctpending%,%sess-curaaaacctitemsused%,%sess-curaaaacctitemsmax%,%sess-curaaaabuffused%,%sess-curaaaabuffmax%,%sess-ttlaaacancauth%,%sess-ttlaaaaacctpurged%,%sess-ttlradacctpurged%,%sess-ttllcpup%,
system	systemSch10	No	PPM,system,systemSch10,%epochtime%,%localdate%,%localtime%,%uptime%,%aaa-ttlpseudoauthreq%,%aaa-curpseudoauthreq%,%aaa-ttlauthnulluser%,%aaa-ttlacctsucc%,%aaa-ttlacctpurged%,%aaa-ttlacctcancelled%,%aaa-ttlacctkeepalivesuccess%,%aaa-ttlacctkeepalivetimeout%,%aaa-ttlacctkeepalivepurged%,%aaa-ttlradacctreq%,%aaa-ttlradacctcancelled%,%aaa-ttlradacctpurged%,%aaa-ttlradacctreqretried%,%aaa-ttlradacctrspdropped%,%aaa-ttlmgrpurgedrequests%,%diamauth-msg-mareq%,%diamauth-msg-maans%,%diamauth-msg-marretry%,%diamauth-msg-maamtimeout%,%diamauth-msg-maadropped%,%diamauth-msg-sareq%,
system	systemSch100	No	PPM,system,systemSch100,%epochtime%,%localdate%,%localtime%,%uptime%,%sess-bearerdur-24hr-qci6%,%sess-bearerdur-over24hr-qci6%,%sess-bearerdur-2day-qci6%,%sess-bearerdur-4day-qci6%,%sess-bearerdur-5day-qci6%,%sess-bearerdur-5sec-qci7%,%sess-bearerdur-10sec-qci7%,%sess-bearerdur-30sec-qci7%,%sess-bearerdur-1min-qci7%,%sess-bearerdur-2min-qci7%,%sess-bearerdur-5min-qci7%,%sess-bearerdur-15min-qci7%,%sess-bearerdur-30min-qci7%,%sess-bearerdur-1hr-qci7%,%sess-bearerdur-4hr-qci7%,%sess-bearerdur-12hr-qci7%,%sess-bearerdur-24hr-qci7%,%sess-bearerdur-over24hr-qci7%,%sess-bearerdur-2day-qci7%,%sess-bearerdur-4day-qci7%,%sess-bearerdur-5day-qci7%,
diameter-auth	diameter-authSch1	No	PPM,diameter-auth,diameter-authSch1,%epochtime%,%localdate%,%localtime%,%uptime%,%vpnid%,%vpnname%,%ipaddr%,%port%,%servertype%,%group%,%der-req-id-sent%,%der-req-aka-chal-sent%,%der-req-retried%,%dea-chal-rcvd%,%dea-acpt-rcvd%,%dea-timeout%,%dea-badauth%,%dea-malformed%,%dea-malformed-avp%,%dea-dropped%,%rar-req-rcvd%,%raa-ans-acpt-sent%,%aar-req-sent%,%str-req-sent%,%str-req-retried%,
diameter-auth	diameter-authSch2	No	PPM,diameter-auth,diameter-authSch2,%epochtime%,%localdate%,%localtime%,%uptime%,%vpnid%,%vpnname%,%ipaddr%,%port%,%staans-acpt-rcvd%,%asr-req-rcvd%,%asa-rsp-acpt-sent%,%asa-rsp-rej-sent%,%req-sock-write-

```
err%,%rsp-sock-write-err%,%any-sock-read-err%,%rem-disconnect%,%loc-disconnect%,
diameter-auth diameter-authSch3          No          PPM,diameter-auth,diameter-
authSch3,%epochtime%,%localdate%,%localtime%,%uptime%,%vpnid%,%vpnname%,%ipaddr%,%port%,%peer%,%
diameter-auth-msg-multiround%,%diameter-auth-msg-success%,%diameter-auth-msg-err-
protocol%,%diameter-auth-msg-err-transient%,%diameter-auth-msg-err-permanent%,%diameter-auth-
msg-err-other%,%aaa-req-received%,%aaa-req-timeouts%,%aaa-req-dropped%,
```

```
sgs          sgsSch2          No
PPM,sgs,sgsSch2,%epochtime%,%localdate%,%localtime%,%uptime%,%vpnname%,%vpnid%,%servname%,%servi
d%,%localupd-req-rx%,%localupd-accept-tx%,%localupd-accept-retx%,%localupd-accept-rx%,%localupd-
rej-tx%,%localupd-rej-retx%,%localupd-rej-rx%,%tmsi-reloc-tx%,%tmsi-reloc-retx%,%tmsi-reloc-
rx%,%alert-req-tx%,%alert-req-retx%,%alert-req-rx%,%alert-ack-tx%,%alert-ack-retx%,%alert-ack-
rx%,%alert-rej-tx%,%alert-rej-retx%,%alert-rej-rx%,%ue-actind-tx%,%ue-actind-retx%,
```

```
sgs          sgsSch3          No
PPM,sgs,sgsSch3,%epochtime%,%localdate%,%localtime%,%uptime%,%vpnname%,%vpnid%,%servname%,%servi
d%,%ue-actind-rx%,%eps-detind-tx%,%eps-detind-retx%,%eps-detind-rx%,%eps-detack-tx%,%eps-detack-
retx%,%eps-detack-rx%,%imsi-detind-tx%,%imsi-detind-retx%,%imsi-detind-rx%,%imsi-detack-
tx%,%imsi-detack-retx%,%imsi-detack-rx%,,,,,,,%mm-inforeq-tx%,%mm-inforeq-retx%,
```

```
[local]MME# configure
```

```
[local]MME(config)# bulkstats mode
```

```
[local]MME(config-bulkstats)# file 2
```

```
[local]MME(config-bulkstats-file-2)# sgs schema sgsSch1 format PPM,sgs,sgsSch1,
%epochtime%,%localdate%,%localtime%,%uptime%,%vpnname%,%vpnid%,%servname%,%serv
id%,%pag-req-tx%,%pag-req-retx%,%pag-req-rx%,%pag-rej-tx%,%pag-rej-retx%,%pag-r
ej-rx%,%service-req-tx%,%service-req-retx%,%service-req-rx%,%dl-ud-tx%,%dl-ud-r
etx%,%dl-ud-rx%,%ul-ud-tx%,%ul-ud-retx%,%ul-ud-rx%,%localupd-req-tx%,%localupd-
req-retx%,
```

```
[local]MME(config-bulkstats-file-2)# end
```

```
[local]MME# show bulkstats schemas
```

```
Bulk Statistics Server Configuration:
```

```
Server State:          Enabled
File Limit:            7500 KB
Sample Interval:      15 minutes (0D 0H 15M)
Transfer Interval:    480 minutes (0D 8H 0M)
Receiver Mode:        Secondary-on-failure
Historical Data Collection: Enabled (15 samples stored)
```

```
Bulk Statistics Server Statistics:
```

```
Records awaiting transmission: 0
```

Bytes awaiting transmission: 0
Total records collected: 0
Total bytes collected: 0
Total records transmitted: 0
Total bytes transmitted: 0
Total records discarded: 0
Total bytes discarded: 0
Last collection time required: 0 second(s)
Last transfer time required: 0 second(s)
No successful data transfers
No attempted data transfers

File 1

Remote File Format: %date%-%time%

File Header: Version-20.0,%ipaddr%,%date%-%time%,%localdate%-%localtime%,%localtz%,%localtzoffset%,%localdate3%-%localtime3%,%swbuild%

File Footer: EndOfFile

No bulkstats receivers

File Statistics:

Records awaiting transmission: 0
Bytes awaiting transmission: 0
Total records collected: 0
Total bytes collected: 0
Total records transmitted: 0
Total bytes transmitted: 0
Total records discarded: 0
Total bytes discarded: 0
Last transfer time required: 0 second(s)
No successful data transfers
No attempted data transfers

File 2

Remote File Format: %date%-%time%

File Header: Version-20.0,%ipaddr%,%date%-%time%,%localdate%-%localtime%,%localtz%,%localtzoffset%,%localdate3%-%localtime3%,%swbuild%

File Footer: EndOfFile

No bulkstats receivers

File Statistics:

Records awaiting transmission: 0
Bytes awaiting transmission: 0
Total records collected: 0
Total bytes collected: 0
Total records transmitted: 0
Total bytes transmitted: 0
Total records discarded: 0
Total bytes discarded: 0
Last transfer time required: 0 second(s)
No successful data transfers
No attempted data transfers

File 3 not configured

File 4 not configured

----- Schemas for File 2-----

Table with 3 columns: Type, Name, Active-Only Format. It lists two system schemas: systemSch1 and systemSch10, each with a 'No' active-only format and a list of various session-related metrics.

ttlacctcancelled%,%aaa-ttlacctkeepalivesuccess%,%aaa-ttlacctkeepalivetimeout%,%aaa-ttlacctkeepalivepurged%,%aaa-ttlradaccreq%,%aaa-ttlradacctcancelled%,%aaa-ttlradacctpurged%,%aaa-ttlradaccreqretried%,%aaa-ttlradacctrspdropped%,%aaa-ttlmgrpurgedrequests%,%diamauth-msg-mareq%,%diamauth-msg-maans%,%diamauth-msg-marretry%,%diamauth-msg-matimeout%,%diamauth-msg-maadropped%,%diamauth-msg-sareq%,

system systemSch100 No PPM,system,systemSch100,%epochtime%,%localdate%,%localtime%,%uptime%,%sess-bearerdur-24hr-qci6%,%sess-bearerdur-over24hr-qci6%,%sess-bearerdur-2day-qci6%,%sess-bearerdur-4day-qci6%,%sess-bearerdur-5day-qci6%,%sess-bearerdur-5sec-qci7%,%sess-bearerdur-10sec-qci7%,%sess-bearerdur-30sec-qci7%,%sess-bearerdur-1min-qci7%,%sess-bearerdur-2min-qci7%,%sess-bearerdur-5min-qci7%,%sess-bearerdur-15min-qci7%,%sess-bearerdur-30min-qci7%,%sess-bearerdur-1hr-qci7%,%sess-bearerdur-4hr-qci7%,%sess-bearerdur-12hr-qci7%,%sess-bearerdur-24hr-qci7%,%sess-bearerdur-over24hr-qci7%,%sess-bearerdur-2day-qci7%,%sess-bearerdur-4day-qci7%,%sess-bearerdur-5day-qci7%,

diameter-auth diameter-authSch1 No PPM,diameter-auth,diameter-authSch1,%epochtime%,%localdate%,%localtime%,%uptime%,%vpnid%,%vpnname%,%ipaddr%,%port%,%servertype%,%group%,%der-req-id-sent%,%der-req-aka-chal-sent%,%der-req-retried%,%dea-chal-rcvd%,%dea-acpt-rcvd%,%dea-timeout%,%dea-badauth%,%dea-malformed%,%dea-malformed-avp%,%dea-dropped%,%rar-req-rcvd%,%raa-ans-acpt-sent%,%aar-req-sent%,%str-req-sent%,%str-req-retried%,

diameter-auth diameter-authSch2 No PPM,diameter-auth,diameter-authSch2,%epochtime%,%localdate%,%localtime%,%uptime%,%vpnid%,%vpnname%,%ipaddr%,%port%,%staans-acpt-rcvd%,%asr-req-rcvd%,%asa-rsp-acpt-sent%,%asa-rsp-rej-sent%,%req-sock-write-err%,%rsp-sock-write-err%,%any-sock-read-err%,%rem-disconnect%,%loc-disconnect%,

diameter-auth diameter-authSch3 No PPM,diameter-auth,diameter-authSch3,%epochtime%,%localdate%,%localtime%,%uptime%,%vpnid%,%vpnname%,%ipaddr%,%port%,%peer%,%diameter-auth-msg-multiround%,%diameter-auth-msg-success%,%diameter-auth-msg-err-protocol%,%diameter-auth-msg-err-transient%,%diameter-auth-msg-err-permanent%,%diameter-auth-msg-err-other%,%aaa-req-received%,%aaa-req-timeouts%,%aaa-req-dropped%,

sgs sgsSch2 No PPM,sgs,sgsSch2,%epochtime%,%localdate%,%localtime%,%uptime%,%vpnname%,%vpnid%,%servname%,%servid%,%localupd-req-rx%,%localupd-accept-tx%,%localupd-accept-retx%,%localupd-accept-rx%,%localupd-rej-tx%,%localupd-rej-retx%,%localupd-rej-rx%,%tmsi-reloc-tx%,%tmsi-reloc-retx%,%tmsi-reloc-rx%,%alert-req-tx%,%alert-req-retx%,%alert-req-rx%,%alert-ack-tx%,%alert-ack-retx%,%alert-ack-rx%,%alert-rej-tx%,%alert-rej-retx%,%alert-rej-rx%,%ue-actind-tx%,%ue-actind-retx%,

sgs sgsSch3 No PPM,sgs,sgsSch3,%epochtime%,%localdate%,%localtime%,%uptime%,%vpnname%,%vpnid%,%servname%,%servid%,%ue-actind-rx%,%eps-detind-tx%,%eps-detind-retx%,%eps-detind-rx%,%eps-detack-tx%,%eps-detack-retx%,%eps-detack-rx%,%imsi-detind-tx%,%imsi-detind-retx%,%imsi-detind-rx%,%imsi-detack-tx%,%imsi-detack-retx%,%imsi-detack-rx%,,,,,,,%mm-inforeq-tx%,%mm-inforeq-retx%,

[local]MME#

Scenario E. Il risultato è che ogni volta che si utilizza la parola chiave opzionale **schema**, non è possibile aggiungere nuovi schemi. È possibile eliminare gli schemi correnti (dal nodo) ma non aggiungerli di nuovo. Tuttavia, gli schemi correnti presenti nel file di configurazione (presente in <url>, non vengono influenzati dalle modifiche apportate nel nodo).

Soluzione

1. Viene utilizzato <url>**lo schema di configurazione cli bulkstat**, a causa del quale si è verificato il problema.
2. Si tratta di un risultato previsto per ogni progettazione, che si ottiene se viene utilizzato **lo schema** della parola chiave opzionale.
3. Per questo caso sono disponibili tre soluzioni:

A. Per rimuovere lo **schema di configurazione bulkstat** della cli **<url>** e controllare l'aggiunta/eliminazione degli schemi tramite il prompt dei comandi cli manuale.

B. Per utilizzare il **supplemento** opzionale della parola chiave nel bulkstat config cli. Con il **supplemento di configurazione bulkstat** della cli **<url>** è possibile aggiungere gli schemi presenti nel file di configurazione agli schemi del nodo corrente. È possibile aggiungere/eliminare nuovi schemi e anche gli schemi correnti possono essere eliminati/aggiunti nuovamente dal prompt dei comandi CLI.

C. Per aggiungere/eliminare gli schemi richiesti direttamente nel file di configurazione e quindi ricaricare le configurazioni con il file di configurazione (prima rimuovere la cli **senza utilizzare la configurazione bulkstat**, aggiungere gli schemi nel file di configurazione e quindi aggiungerli nuovamente con la configurazione **bulkstats <url>**). Per aggiungere gli schemi nel file di configurazione, è possibile utilizzare l'editor VI o SFTP il file

Con l'editor vi:

```
[local]MME-01# cli test-commands password <pswd>
Warning: Test commands enables internal testing and debugging commands
USE OF THIS MODE MAY CAUSE SIGNIFICANT SERVICE INTERRUPTION

[local]MME-01# debug shell
Last log in: Wed Dec 22 15:05:12 +0530 2021 on pts/3 from 10.227.224.108.
MME-01:card1-cpu0# ls -lrtha

total 16
-r--r--r-- 1 root root 952 Dec 15 23:30 .rhosts
-r--r--r-- 1 root root 1.7K Dec 15 23:30 .gdbinit
drwx----- 2 root root 100 Dec 15 23:30 .ssh
drwxr-xr-x 24 root root 500 Dec 15 23:30 ..
-rw----- 1 root root 118 Dec 21 14:48 .bash_history
-rw-r--r-- 1 root root 1 Dec 22 15:05 file
drwxr-xr-x 3 root root 140 Dec 22 15:05 .

MME-01:card1-cpu0# vi file
```

Spostare il file di configurazione da **<url>** nell'unità locale, modificarlo e reinserirlo nell'**<url>**.