

Cisco

VLAN Trunking Protocol (VTP) Multiple Vulnerabilities



20060913-vtp

20060913-vtp

2006-09-13 17:00

2016-01-06 18:17

Final

No Workarounds available

Cisco Bug ID :

Multiple vulnerabilities in Cisco Systems IOS VTP multiple vulnerabilities

Summary

2006-09-13 17:00 <http://www.securityfocus.com/archive/1/445896/30/0/threaded>

Systems IOS VTP multiple

vulnerabilities

Phenoelit

Group

Cisco Bug ID

- CSCsd52629 (Cisco Bug ID): VTP
- CSCse40078 (Cisco Bug ID): VTP
- CSCsd34855 (Cisco Bug ID): VTP
- CSCsg03449 (Cisco Bug ID): Etherswitch

Summary

VLAN Trunking

Protocol (VTP) Multiple Vulnerabilities

VLAN

ã, 'è«æ°ã ®ç®æ%œã Sè"ã®šã™ã, <ã¿...è| ãœæ, >ã—ã¾ã™ã€VTPã"ã, ·ã, 1ã, 3ç<-è

IOSã" Cisco
CatOSã, ·ã, 1ãftãfã, ½ãfãf^ã, |ã, šã, çã®ã, jãæ-1ãšã€ã»ã"ã, "ã©ã®Cisco
Catalystã, ·ãfãf¼ã, °è£½ã"ãšã½¿ç"ãšã¾ã™ã€,

ã"ã, CEã, %œã®è,, tã¼±æ€šã®ã½±éÿ¿ã, 'ã—ã'ã, <è£½ã"ãi¼š

- è©²ã½"ã™ã, <ãfãf¼ã, ãfšãf³ã®Cisco
IOS®ã, ½ãfãf^ã, |ã, šã, çã®ç"¼ãfã—ã€VTPã<ã½œãfçãf¼ãf%œãœãœã, ìãf¼ãfã€ã
- ã€œããf¼ãfã€ã¾ãÿã"ãœã, "ãf©ã, ìã, çãf³ãf^ã€ã"ã—ã|VTPã<ã½œãfçãf¼ãf
CatOSã®è©²ã½"ãfãf¼ã, ãfšãf³ã®ç"¼ãfã™ã, <ã, 1ã, ìãffãfã"ã"ã€ãœVTPãfãf"ã, ã
- VTPã<ã½œãfçãf¼ãf%œãœãœã, ìãf¼ãfã€ã¾ãÿã"ãœã, "ãf©ã, ìã, çãf³ãf^ã€ã®ã
1800/2600/2800/3600/3700/3800ã, ·ãfãf¼ã, °ãf«ãf¼ã, ¿ç"ã, ìãf¼ã, ìãfãfãf^ã, 1ã, ìãffãfãfçã

ã"ã, CEã, %œã®è,, tã¼±æ€šã®ã½±éÿ¿ã, 'ã—ã'ãªã,, è£½ã"ãi¼š

- VTPã<ã½œãfçãf¼ãf%œã, 'ãœãf^ãf©ãf³ã, 1ãfšã, çãf-ãf³ãf^ã€ã«è"ã®šã—ãÿã, 1ã, ìãffãfã
- ã€œããf¼ãfã€ã¾ãÿã"ãœã, "ãf©ã, ìã, çãf³ãf^ã€ã"ã—ã|VTPã<ã½œãfçãf¼ãf
VLANãã®ã®ãfãfãfã, jã, °ãf¼ãfãf¼ãfãfãf¼ã€ã¾ãÿã"ãœãœVTPãfãf¼ã, ãfšãf³ã

ã, 1ã, ìãffãfã"ã"ã®VTPãfçãf¼ãf%œã, 'çç°èã™ã, <ã«ã"ã€ãfãfãã, ìã, 1ã«ãfã, °ã, ìãf³ã—ã€
vtp statusã, ¾ãfžãf³ãf%œã, 'ç™°è;œã™ã, <ã<ã€CatOSãfãfãã, ìã, 1ãšshow vtp

domainã, ¾ãfžãf³ãf%œã, 'ç™°è;œã—ã¾ã™ã€VTPã<ã½œãfçãf¼ãf%œã"ã—ã|ãœserverã€

ãœããf¼ãfã€ãfçãf¼ãf%œãšã<ã½œã™ã, <VTPã, 'ã, "ã^ãÿCisco
IOSã, ½ãfãf^ã, |ã, šã, çã®ã¾ã, æ¬ã«çªã—ã¾ã™ã€,

<#root>

ios_switch#

show vtp status

```

VTP Version                : 2
Configuration Revision     : 0
Maximum VLANs supported locally : 1005
Number of existing VLANs   : 5
VTP Operating Mode        : Server
VTP Domain Name           : test
VTP Pruning Mode          : Disabled
VTP V2 Mode                : Enabled
VTP Traps Generation      : Disabled
MD5 digest                 : <removed>
Configuration last modified by 0.0.0.0 at 3-1-93 04:02:09
ios_switch#

```

~€Eãpf¼ãf ~€ ~fçãf¼ãf%ã Sã•ã½œã™ã, <VTPã, 'ã,™ã ^ã ÿCisco
CatOSã®ã¾ã, 'æ¬ã «çºã —ã¾ã™ã€,

<#root>

catos_switch> (enable)

show vtp domain

Version : running VTP1 (VTP3 capable)
Domain Name : test Password : not configured
Notifications: disabled Updater ID: 0.0.0.0

Feature	Mode	Revision
-----	-----	-----
VLAN	Server	2

Pruning : disabled
VLANs prune eligible: 2-1000
catos_switch> (enable)

[VTPãfãf¼ã,ãfSãf³(VTP Version)]ãfã,£ãf¼ãf«ãf%ã®DoS

Cisco

IOSã,½ãfãf^ã,ã,šã,çã®ç%ã¹ã®šã®ãfãf¼ã,ãfSãf³ã®VTPæ©ÿèf½ã~ãããf¼ã,«ãf«ãfãfã
Managerã®ã€Ewatchdog timeoutã€ã¾ãÿã~ã€CECPU
hogã€ã®ã„ãšã,CEãã®ãfãfã,»ãf¼ã,ã~ã€ã,ã,ããfãfããã,^ã£ã|ç"ÿæ^ãã•ã

CatOSã€ç¼ãfã™ã,ã,ã,ããfãfãã~ããããã®è,,ã¼±æ€Sã®ã½±éÿã,'ã—ãããšã€

"%VTP-2-RXINVSUMMARY:rx invalid summary from [port number]"

ç%ã¹ãÿã«ãSã!™ã«ç'ã•ãã,CEãÿè|ç'„ãfã,±ãfãfãã,ãã—ã¿ã™ã,ã¿...è|ããCEãã,ã,šãã

ãã"ã®è,,ã¼±æ€Sã«ã¾ã™ã,ã¿žé¿çããã,ã,šã¾ããã,ã,ã€,

VTPãf%ãfã,ã,ããfãfãã,ãfãf¼ãf%ã€Eèã®šãã,CEãÿã,ã,ããfãfããã~ããããã®ç¶šãããã

[CSCsd52629](#)(ç™»€E²ãfãf¼ã,¶ã°,ç™)ã¾ãÿã~ã€CSCsd34759(ç™»€E²ãfãf¼ã,¶ã°,ç™)ã®ã¿®æEã€CEã
IOSã,½ãfãf^ã,ã,šã,çã®ãfãf¼ã,ãfSãf³ã«ã,çãfãfã—ã,°ãfãf¼ãf%ã™ã,ããããã,ã,ã,ãSãã,ã

VTP VLANãã®ãfãfãfã,ã,ããf¼ãfãf¼ããfãf¼

Cisco

IOSã,½ãfãf^ã,ã,šã,çã®ç%ã¹ã®šã®ãfãf¼ã,ãfSãf³ã®VTPæ©ÿèf½ã~ãããfãfãã,ã,ããf¼ã
Length-

翻訳について

シスコは世界中のユーザにそれぞれの言語でサポート コンテンツを提供するために、機械と人による翻訳を組み合わせて、本ドキュメントを翻訳しています。ただし、最高度の機械翻訳であっても、専門家による翻訳のような正確性は確保されません。シスコは、これら翻訳の正確性について法的責任を負いません。原典である英語版（リンクからアクセス可能）もあわせて参照することを推奨します。