

brief,³ãfžãf³ãf%ã, 'ç™°è;Ĉĕ—ã|ã,ã,¹ãftãfãfãfšãf¼ã,'è;ç°ã—ã¾ã™ã€,ã,ã,¹ãftãfãf
IOS XR

Softwareã€ã®ã,^ãtãªaftã,ã,¹ãf^ãĈè;ç°ã•ã,Ĉĕã€ãfãfã,ã,ã,¹ãšCisco IOS
XRã,½ãf•ãf^ã,|ã,šã,çãĈĕã®ÿè;Ĉĕã•ã,Ĉĕã|ã,,ã,ã"ã"ã,çç°èªãšã¾ã™ã€,ã,½
IOS XR Softwareã"ã,,ãtãftã,ã,¹ãf^ã®¾Ĉĕã«è;ç°ã•ã,Ĉĕã¾ã™ã€,

æ¬ĳã®¾ãã™ã€Cisco IOS
XRã,½ãf•ãf^ã,|ã,šã,çãfªãfªãf¼ã,¹4.1.0ã,'ã®ÿè;Ĉĕ—ã|ã,,ã,çCisco ASR
9010ã,'ç°ã—ã|ã,,ã¾ã™ã€,

```
RP/0/0/CPU0:Router#show version brief  
Fri Jul 8 18:54:39.222 CEST
```

```
Cisco IOS XR Software, Version 4.1.0[Default]  
Copyright (c) 2011 by Cisco Systems, Inc.
```

```
ROM: System Bootstrap, Version 1.05(20101118:025914) [ASR9K ROMMON],
```

```
Router uptime is 9 weeks, 1 day, 5 hours, 53 minutes  
System image file is "bootflash:disk0/asr9k-os-mbi-4.1.0/mbiasr9k-rp.vm"
```

```
cisco ASR9K Series (MPC8641D) processor with 4194304K bytes of memory.  
MPC8641D processor at 1333MHz, Revision 2.2  
ASR-9010-CHASSIS
```

```
4 Management Ethernet  
8 WANPHY controller(s)  
8 TenGigE  
8 DWDM controller(s)  
40 GigabitEthernet  
4 SONET/SDH  
2 Packet over SONET/SDH  
1 MgmtMultilink  
219k bytes of non-volatile configuration memory.  
975M bytes of compact flash card.  
33994M bytes of hard disk.  
1605616k bytes of disk0: (Sector size 512 bytes).  
1605616k bytes of disk1: (Sector size 512 bytes).
```

ãfãfã,ã,ã,¹ãšã,çã,ãftã,£ãf-ã«ãªã£ã|ã,,ã,çSMUã,'çç°èªãšã¾ã™ã,ã«ãã™ã€show
install active

summary,³ãfžãf³ãf%ã, 'ç™°è;Ĉĕ—ã¾ã™ã€,ã"ã®ã,³ãfžãf³ãf%ãã™ã€æ¬ĳã®¾ãã¾ã«

```
RP/0/0/CPU0:Router#show install active summary  
Fri Jul 8 19:02:15.887 CEST
```

```
Active Packages:  
disk0:asr9k-doc-p-4.1.0  
disk0:asr9k-mini-p-4.1.0
```

disk0: asr9k-k9sec-p-4.1.0
disk0: asr9k-video-p-4.1.0

æ³¹¼šä, Šä ®â±°äš>ä ¯ã€ SMU asr9k-p-

4.1.0.CSCTR26695.tarã €ã, ¢ãf³ã, 'ãf^ãf¼ãf«ã •ã, €ã |ã,,ãªã,,ãf‡ãfã, ¢ã, 'ã, 'çªã —ã |ã

IOS

XRã, ½ãf•ãf^ã, |ã, šã, çã «ã ¯èªæ°ã ®SMUã, 'ã «ã,ã,ã «ã ¯ã €ã šããã€ãâ±°äš>ä

è, †ã¼±æ€šã, 'ã «ã, "ã šã,,ãªã,,ã "ã ¯ã €çç°èªãã•ã, €ã ÿè£½ã"

æ¬ãã®è£½ã"ã «ã ¯è, †ã¼±æ€šã €ãã°æ ¯ã —ãªã,,ã "ã ¯ã €çç°èªãã•ã, €ã |ã

- Cisco IOS
XRã, ½ãf•ãf^ã, |ã, šã, çã ®ã»æ,,ã®ãfãf¼ã,,ãfšãf³ã, 'ã®ÿè;€ã™ã, <Cisco Carrier Routing System(CRS)
- Cisco IOS
XRã, ½ãf•ãf^ã, |ã, šã, çã ®ã»æ,,ã®ãfãf¼ã,,ãfšãf³ã, 'ã®ÿè;€ã™ã, <Cisco XR 12000ã,ãfªãf¼ã, °ãf«ãf¼ã, ç
- Cisco IOSã, ½ãf•ãf^ã, |ã, šã, çã ®ã»æ,,ã®ãfãf¼ã,,ãfšãf³ã, 'ã®ÿè;€ã™ã, <Cisco 12000ã,ãfªãf¼ã, °ãf«ãf¼ã, ç
- Cisco IOSã, ½ãf•ãf^ã, |ã, šã, çã
- Cisco IOS XEã, ½ãf•ãf^ã, |ã, šã, çã
- Cisco NX-OSã, ½ãf•ãf^ã, |ã, šã, çã
- ã»æ,,ã®ãfãf¼ã,,ãfšãf³ã®ã, ½ãf•ãf^ã, |ã, šã, çã, 'ã®ÿè;€ã™ã, <Cisco ASR 1000ãšã, ^ã³5000ã,ãfªãf¼ã, °ãf«ãf¼ã, ç
- 4.1.0ã»æªãã®Cisco IOS XRã, ½ãf•ãf^ã, |ã, šã, çã, 'ã®ÿè;€ã—ã|ã,,ã, <Cisco ASR 9000ã,ãfªãf¼ã, °ãf«ãf¼ã, ç
- Cisco IOS XRã, ½ãf•ãf^ã, |ã, šã, çãfãf¼ã,,ãfšãf³4.1.0ã, 'ã®ÿè;€ã—ã€SMU asr9k-p-4.1.0.CSCTR26695.tarã €ã, ¢ãf³ã, 'ãf^ãf¼ãf«ã •ã, €ã |ã,,ã, <Cisco ASR 9000ã,ãfªãf¼ã, °ãf«ãf¼ã, ç

install active

summaryã,³ãfžãf³ãf%õã, 'ç™è;€ã—ã³ãã™ã€ã,ã "ã, €ã «ã, ^ã, Šã€ã, ¢ãf³ã, 'ãf^ãf¼ãf«ã

<#root>

RP/0/0/CPU0:Router#show install active summary
Fri Jul 8 19:02:15.887 CEST
Active Packages:

disk0: asr9k-p-4.1.0.CSCTR26695-1.0.0

翻訳について

シスコは世界中のユーザにそれぞれの言語でサポート コンテンツを提供するために、機械と人による翻訳を組み合わせて、本ドキュメントを翻訳しています。ただし、最高度の機械翻訳であっても、専門家による翻訳のような正確性は確保されません。シスコは、これら翻訳の正確性について法的責任を負いません。原典である英語版（リンクからアクセス可能）もあわせて参照することを推奨します。