





Cisco IOS#show controllers HDLC32

show controllers T1/E1

show controllers serial 0/0/0

Router#show controllers Serial0/0/0:0

Interface Serial0/0/0:0

Hardware is HDLC32

< output truncated >

Router#show controllers Serial0/0/0:0

Interface Serial0/0/0:0

Hardware is HDLC32

Router#show controllers Serial0/0/0:0

Interface Serial0/0/0:0

Hardware is HDLC32

< output truncated >

Router#show controllers Serial0/0/0:0

Interface Serial0/0/0:0

Hardware is HDLC32

< output truncated >

Router#show controllers Serial0/0/0:0

Interface Serial0/0/0:0

Hardware is HDLC32

< output truncated >

Router#show controllers Serial0/0/0:0

Interface Serial0/0/0:0

Hardware is HDLC32

Router#show controllers e1

E1 0 is up.

Applique type is Channelized E1 - balanced

!--- output truncated

Framing is CRC4, Line Code is HDB3, Clock Source is Line Primary.

!--- output truncated











12.2IRD	è,,†â¼±æ€§ãªã—
12.2IRE	è,,†â¼±æ€§ãªã—
12.2IRF	è,,†â¼±æ€§ãªã—
12.2IRG	è,,†â¼±æ€§ãªã—
12.2IRH	è,,†â¼±æ€§ãªã—
12.2IRI	è,,†â¼±æ€§ãªã—
12.2IXG	è,,†â¼±æ€§ãªã—
12.2IXH	è,,†â¼±æ€§ãªã—
12.2MC	è,,†â¼±æ€§ãªã—
12.2MRA	è,,†â¼±æ€§ãªã—
12.2MRB	è,,†â¼±æ€§ãªã—
12.2SB	è,,†â¼±æ€§ãªã—
12.2SCA	è,,†â¼±æ€§ãªã—
12.2SCB	è,,†â¼±æ€§ãªã—
12.2SCC	è,,†â¼±æ€§ãªã—
12.2SCD	è,,†â¼±æ€§ãªã—
12.2SCE	è,,†â¼±æ€§ãªã—
12.2SCF	è,,†â¼±æ€§ãªã—
12.2SCG	è,,†â¼±æ€§ãªã—
12.2SCH	è,,†â¼±æ€§ãªã—
12.2SE	è,,†â¼±æ€§ãªã—
12.2SEG	è,,†â¼±æ€§ãªã—
12.2SG	è,,†â¼±æ€§ãªã—
12.2SGA	è,,†â¼±æ€§ãªã—
12.2SM	è,,†â¼±æ€§ãªã—
12.2SQ	è,,†â¼±æ€§ãªã—



Affected 12.4-Based Releases	First Fixed Release
<p>15.0            15.0EA            15.0EB            15.0EC            15.0ED            15.0EH            15.0EJ            15.0EY            15.0EZ</p>	<p>First Fixed Release</p> <p>è,,†â¼±æ€§ãª—</p>
<p>15.0EX</p>	<p>Cisco IOS XE <a href="#">15.0EX</a>: <a href="#">Cisco IOS XE 15.0EX</a></p>
<p>15.0M</p>	<p>Vulnerable; <a href="#">15.0M</a> <a href="#">15.1M</a></p>
<p>15.0MR</p>	<p>è,,†â¼±æ€§ãª—</p>
<p>15.0S</p>	<p>Cisco IOS XE <a href="#">15.0S</a>: <a href="#">Cisco IOS XE 15.0S</a></p>
<p>15.0SE</p>	<p>è,,†â¼±æ€§ãª—</p>
<p>15.0SG</p>	<p>Cisco IOS XE <a href="#">15.0SG</a>: <a href="#">Cisco IOS XE 15.0SG</a></p>
<p>15.0SQA</p>	<p>Cisco IOS XE <a href="#">15.0SQA</a>: <a href="#">Cisco IOS XE 15.0SQA</a></p>
<p>15.0SQB</p>	<p>Cisco IOS XE <a href="#">15.0SQB</a>: <a href="#">Cisco IOS XE 15.0SQB</a></p>
<p>15.0SY</p>	<p>è,,†â¼±æ€§ãª—</p>
<p>15.0XA</p>	<p>Vulnerable; <a href="#">15.0XA</a> <a href="#">15.1M</a></p>
<p>15.0XO</p>	<p>Cisco IOS XE <a href="#">15.0XO</a>: <a href="#">Cisco IOS XE 15.0XO</a></p>

<p>ã½±éÿ;ã, 'ã—ã'ã, &lt; 15.1 ãf™ãf¼ã, 'ã®ãfããfãf¼ã, '1</p>	<p>First Fixed Releasei¼^ä;®æfã•ã, Æã</p>
15.1EY	è,,†ã¼±æ€§ãã—
15.1GC	Vulnerable; <a href="#">ãfããfãf¼ã, '1 15.1M</a> ãSã>°ã@šã•ã, Æã, <ç¬¬ 1
15.1M	15.1(4)M7
15.1MR	è,,†ã¼±æ€§ãã—
15.1MRA	è,,†ã¼±æ€§ãã—
15.1S	Cisco IOS XE ãf†ãfã, ãã, '1: <a href="#">Cisco IOS XE ã, ½ãf•ãf^ã, lã, šã, çã ã ç" æ€§ã,</a>
15.1SG	Cisco IOS XE ãf†ãfã, ãã, '1: <a href="#">Cisco IOS XE ã, ½ãf•ãf^ã, lã, šã, çã ã ç" æ€§ã,</a>
15.1SNG	è,,†ã¼±æ€§ãã—
15.1SNH	è,,†ã¼±æ€§ãã—
15.1SNI	è,,†ã¼±æ€§ãã—
15.1SVD	è,,†ã¼±æ€§ãã—
15.1SVE	è,,†ã¼±æ€§ãã—
15.1SVF	è,,†ã¼±æ€§ãã—
15.1SY	è,,†ã¼±æ€§ãã—
15.1T	Vulnerable; <a href="#">ãfããfãf¼ã, '1 15.1M</a> ãSã>°ã@šã•ã, Æã, <ç¬¬ 1
15.1XO	è,,†ã¼±æ€§ãã—
<p>è©²ã½“ã™ã, &lt; 15.2 ãf™ãf¼ã, 'ã®ãfããfãf¼ã, '1</p>	<p>First Fixed Releasei¼^ä;®æfã•ã, Æã</p>
15.2E	è,,†ã¼±æ€§ãã—
15.2GC	15.2(4)GC
15.2JA	15.2(4)JA1
15.2JAX	Vulnerable; ã"ã®ã, çãf%ooãfã, ãã, ¶ãfãã®ä;®æfã, ^ã;ã, ½ãf•ãf^ã, lã, šã, çãã çµ,, ç¹"ã«é€£çµjã—ã   ä,ãã•ãã,,ã€,
15.2JB	15.2(2)JB2





## 翻訳について

シスコは世界中のユーザにそれぞれの言語でサポート コンテンツを提供するために、機械と人による翻訳を組み合わせて、本ドキュメントを翻訳しています。ただし、最高度の機械翻訳であっても、専門家による翻訳のような正確性は確保されません。シスコは、これら翻訳の正確性について法的責任を負いません。原典である英語版（リンクからアクセス可能）もあわせて参照することを推奨します。