



è©²å¹½“è£¹½å“?

è,†å¹¼±æ€§å®®å,å,«è£¹½å”

å“å”è,,†å¹¼±æ€§å®®å¬̂å€å,å,å,¹å,³ åf—åf©å,°å,çåf³åf%åf—åf~å,¼^PnPí¼%å,“åf¼å,å,şåf³åf  
Cisco IOS å,½åf•åf^å,|å,şå,ç åfååfåf¼å,¹å³¼å¼Yå¬̂ IOS XE  
å,½åf•åf^å,|å,şå,çåfååfåf¼å,¹å,å®̂Yè;Çå™å,«å,å,¹å,³  
åf‡åfå,å,å,¹å«å½±éYçå,â,žå^å³¼å™å€,

PnP å,“åf¼å,å,şåf³åf^å¬̂å€åå™å¹å|å® Cisco IOS åŞå,^å³ IOS XE  
å,½åf•åf^å,|å,şå,ç  
åf—åf©åffåf^åf•å,©åf¼åf åşåf‡åf•å,©åf«åf^åşæœ%åŞ¹å«åªå€£å|å,,å³¼å™å€

- å,¹å,çåf¼åf^å,çåffåf— å,³åf³åf•å,£å,®åf¥åf~åf¼å,åfşåf³åÇå~åœ”å—åªå€,,å€,
- CLI å,å»«å—å| PnP  
åf—åfåfå,å,å,åf«å€è”å®şå•å,Çå€å,çå,¬åftå,£åf-åÇ-å•å,Çå|å,,å,å€,

è,,†å¹¼±æ€§å®®åÇå~åœ”å™å,« Cisco IOS å,½åf•åf^å,|å,şå,çåŞå,^å³ IOS XE  
å,½åf•åf^å,|å,şå,çå®̂åfååfåf¼å,¹å«åªå€,,å|å¬̂å€å”å®̂å,çåf%åfå,å,å,¶åfå®̂

**PnP**

åf—åfåfå,å,å,åf«å€è”å®şå•å,Çå€|å,,å,«å<å©åtå<å®çç°èª

åf‡åfå,å,å,¹åş PnP  
åf—åfåfå,å,å,åf«å€è”å®şå•å,Çå€|å,,å,«å<å©åtå<å,çç°èªå™å,«å«å¬̂å€Ç  
åŞ show pnp profile  
å,³åfżåf³åf%å,å¹½ç”å—å³¼å™å€,,æ¬ıå«å€å€Çetestå”å,,åtåå°å®̂å®̂

**PnP**

åf—åfåfå,å,å,åf«å€è”å®şå•å,Çå€å,çå,¬åftå,£åf-åÇ-å•å,Çå|å,,å,«å¹åå^å®̂å®̂  
show pnp profile å,³åfżåf³åf%å®̂å‡åŞ>å®̂¼å,çªå—å³¼å™å€,

<#root>

Device#

show pnp profile

Initiator Profile

test

: 0 open connections: 0 closing connections  
Encap: xmpp11  
WSSE header is not required. Configured authorization level is 1  
Countdown: Security Unlock 0, Service Lock: 0, Service Req Wait: 0, Prxoy Req Wait 0, Service

```
Max message (RX) is 50 Kbytes
XEP Faults are sent
Idle timeout infinite
Keepalive not configured
Reconnect time 60 seconds
Primary transport: xmpp socket to host 172.19.193.60, port 5222
Not connected, next reconnect attempt in 52 seconds
```

Device#

```
Device# show pnp profile
PnP Profiles:
Active:1
Created:1
Deleted:0, Hidden:0
```

Cisco IOS XE IOS XE

```
Device# show pnp profile
PnP Profiles:
Active:1
Created:1
Deleted:0, Hidden:0
Name          CBType Node          Primary-Path          Primary-Trans  Backup-Trans
pnp-zero-touch
  User  visible  pnp/WORK-REQUEST    HTTPS          none
Initiator Profile
pnp-zero-touch
: 0 open connections: 0 closing connections
  Encap: pnp
  WSSE header is not required. Configured authorization level is 1
  .
  .
  .
  Max message (RX) is 50 Kbytes
  XEP Faults are sent
  Idle timeout infinite
```

<#root>

Device#

show pnp profile

PnP Profiles:

Active:1

Created:1

, Deleted:0, Hidden:0

Name	CBType	Node	Primary-Path	Primary-Trans	Backup-Trans
pnp-zero-touch					
User	visible	pnp/WORK-REQUEST	HTTPS	none	

Initiator Profile

pnp-zero-touch

```
: 0 open connections: 0 closing connections
  Encap: pnp
  WSSE header is not required. Configured authorization level is 1
  .
  .
  .
  Max message (RX) is 50 Kbytes
  XEP Faults are sent
  Idle timeout infinite
```

```
Keepalive not configured
DNS Resolution: default
Reconnect time 60 seconds
Primary Transport:https to Host:-, IP:10.201.237.169, Port:443, Src-Intf:-, VRF:-, UR
Not connected, next reconnect attempt in 30 seconds
```

```
.
```

```

Cisco IOS
show version
Cisco IOS Software (C2951-UNIVERSALK9-M), Version 15.5(2)T1, RELEASE SOFTWARE (fc1)
Technical Support: http://www.cisco.com/techsupport
Copyright (c) 1986-2015 by Cisco Systems, Inc.
Compiled Mon 22-Jun-15 09:32 by prod_rel_team
```

### Cisco IOS

```

Cisco IOS
show version
Cisco IOS Software (C2951-UNIVERSALK9-M), Version 15.5(2)T1, RELEASE SOFTWARE (fc1)
Technical Support: http://www.cisco.com/techsupport
Copyright (c) 1986-2015 by Cisco Systems, Inc.
Compiled Mon 22-Jun-15 09:32 by prod_rel_team
```

```

Cisco IOS
show version
Cisco IOS Software (C2951-UNIVERSALK9-M), Version 15.5(2)T1, RELEASE SOFTWARE (fc1)
Technical Support: http://www.cisco.com/techsupport
Copyright (c) 1986-2015 by Cisco Systems, Inc.
Compiled Mon 22-Jun-15 09:32 by prod_rel_team
```

```

Cisco IOS
show version
Cisco IOS Software (C2951-UNIVERSALK9-M), Version 15.5(2)T1, RELEASE SOFTWARE (fc1)
Technical Support: http://www.cisco.com/techsupport
Copyright (c) 1986-2015 by Cisco Systems, Inc.
Compiled Mon 22-Jun-15 09:32 by prod_rel_team
```

```

Cisco IOS
show version
Cisco IOS Software (C2951-UNIVERSALK9-M), Version 15.5(2)T1, RELEASE SOFTWARE (fc1)
Technical Support: http://www.cisco.com/techsupport
Copyright (c) 1986-2015 by Cisco Systems, Inc.
Compiled Mon 22-Jun-15 09:32 by prod_rel_team
```

<#root>

Router>

show version

```

Cisco IOS Software, C2951 Software (C2951-UNIVERSALK9-M), Version 15.5(2)T1, RELEASE SOFTWARE (fc1)
Technical Support: http://www.cisco.com/techsupport
Copyright (c) 1986-2015 by Cisco Systems, Inc.
Compiled Mon 22-Jun-15 09:32 by prod_rel_team
```

```
.
```

Cisco IOS

[Cisco IOS and NX-OS Software Reference Guide](#)

### Cisco IOS XE

Cisco IOS XE  
show version  
Cisco IOS XE Software  
Cisco IOS XE Software

Cisco IOS XR 16.2.1

CAT3K\_CAA-UNIVERSALK9-M  
Cisco IOS XR Software

<#root>

ios-xe-device#

show version

Cisco IOS Software, Catalyst L3 Switch Software (CAT3K\_CAA-UNIVERSALK9-M), Version Denali 16.2.1, REL  
Technical Support: http://www.cisco.com/techsupport  
Copyright (c) 1986-2016 by Cisco Systems, Inc.  
Compiled Sun 27-Mar-16 21:47 by mcpre

Cisco IOS XE

[Cisco IOS and NX-OS Software Reference Guide](#)

Cisco IOS XR

Cisco IOS XR Software

Cisco IOS XR  
Cisco NX-OS

ã,½ãf•ãf^ã,|ã,šã,çã«ã-ã½±éÿã,ã,žã^ãã,,ã"ã"ã,çç°èã—ã¾ã—ãÿã€,

## ã>žéç-

ã"ã®è,,tã¼±æ€šã«ã¾ã±|ã™ã,ã>žéç-ã-ã,ã,šã¾ã>ã,"ã€,

## ã;®æ£æ,^ãçã,½ãf•ãf^ã,|ã,šã,ç

ã,ã,1ã,³ã-ã-ã-ã,çãf%ãã,ã,ã,ãfã«è~è¼%ã•ã,ããÿè,,tã¼±æ€šã«ã¾ã±|ã™ã,ç,,i  
ãfãf¼ã,ãfšãf³ã"ãf•ã,£ãf¼ããf£

ã,»ãffãf^ã«ã¾ã-ã|ã®ãçã"ãã,šã¾ã™ã€ã,ã-ã-ã®,^ãtããã,½ãf•ãf^ã,|ã,šã,

<https://www.cisco.com/c/en/us/products/end-user-license-agreement.html>

ã¾ãÿãã€ãšã®çæš~ããã,½ãf•ãf^ã,|ã,šã,çã,'ãfã,|ãf³ãfãf¼ãf%ãšãã,ã-ã-ã-ã€ã,ã,ã

ã,çãffãf-ã,°ãf-ãf¼ãf%ãšã™ã€ç,,jã,ÿã®ã,»ã,ãfããfãfã,£ã,½ãf•ãf^ã,|ã,šã,ç

ã,çãffãf-ãfãf¼ãf^ã«ã,^ã£ã|ã€ãšã®çæš~ã«æ-°ã-ã,,ã,½ãf•ãf^ã,|ã,šã,ç

ãfãã,ã,»ãf³ã,1ã€è:½ãšã,½ãf•ãf^ã,|ã,šã,çãfã,£ãf¼ããf£

ã,»ãffãf^ã€ã¾ãÿããfã,ãf£ãf¼ãfãã,ãfšãf³

ã,çãffãf-ã,°ãf-ãf¼ãf%ã«ã¾ã±|ã™ã,ãæ"©é™ãããã»ã,žã•ã,ãã,ã"ã-ã-ã,ã,šã¾ã

ã,½ãf•ãf^ã,|ã,šã,çãã,çãffãf-ã,°ãf-ãf¼ãf%ã,'ææœè"žã™ã,«és>ã«ã-ã€[ã,ã,1ã,³ã®ã,»ããf  
Security Advisories and Alerts[¼%]

ãfšãf¼ã,ãšã...¥æ%ããšããã,ã,ã,1ã,³è£½ã"ã®ã,çãf%ããã,ã,ã,ãfã,'ãšæœÿçš,ã«ãç,ç

ã,½ãfããfãf¼ã,ãfšãf³ã,'çç°èã-ã-ã|ãããããã•ã,,ã€,

ã,,ãšã,ãã®ã'ã^ã,,ã€ã,çãffãf-ã,°ãf-ãf¼ãf%ã™ã,ãfãããã,ã,1ã«ããã^ããããfããã  
Technical Assistance

Center[¼^TAC[¼%ã,,ã-ãããã-ã¥ç',ã-ã-ã|ã,,ã,ãfãf³ãfãfšãf³ã,1ãf-ãããã,ããããf¼ã«ã

## ã,ãf¼ãf"ã,1ã¥ç',ã,'ã"ã^ç"ãšããã,,ãšã®çæš~

ã,ã,1ã,³ã-ã,ãç'æž¥è¾ã...¥ã-ãÿããã Cisco Service Contract

ã,'ã"ã^ç"ã"ã,,ãÿããã,,ã|ã,,ãããã,,ã'ã^ã€ã¾ãÿãã€ã,ãf¼ãf%ããfãf¼ããfã,£ãf™

POSãã,ã,ã...¥æ%ããšããããã,,ã'ã^ã-ã€ã Cisco TAC

ã«é€£çãã-ã-ã|ã,çãffãf-ã,°ãf-ãf¼ãf%ã,'ã...¥æ%ãã-ã-ã|ãããããã•ã,,ã€,

<https://www.cisco.com/c/en/us/support/web/tsd-cisco-worldwide-contacts.html>

ç,,ã,ÿã,çãffãf-ã,°ãf-ãf¼ãf%ã®ã¾ã±|ã™ã,ã,ã"ã"ã,è"¼æ~žã-ã-ã|ã,,ãÿãã

URLã,'ã"ç"æ,,ãããããããã,,ã€,

## Cisco IOSãšã,^ã³ IOS XEã,½ãf•ãf^ã,|ã,šã,ç



XEã,½ãf•ãf^ã,|ã,§ã,øãf^ãfãf½ã,¹16.9.1ã»¥é™ã◊ã◊Sã◊ã◊-ã€◊ã,Çãffãf-ã,°ãf-ãf½ãf%ãã◊◊ã◊-ã,¹ãfzãf½ã  
IOS XE ã,¹ãf^ãfãf½ã,¹ 16.9.1

ã»¥é™ã◊ã◊◊ã,Çãffãf-ã,°ãf-ãf½ãf%ãã◊™ã,ã,°ã^ã@šã◊CEã◊,ã,ã,ã'ã^ã◊-ã€◊ã,¹ãfzãf½ãf^ã  
ãf@ã,ãã,»ãf³ã,¹è|◊ã»¶ã,¹æœœè¨Žã◊™ã,ã◊"ã◊¨ã,ã'ã◊Šã◊Sã,ã◊-ã◊¾ã◊™ã€ç,½ãŠ æf...ã ±ã◊  
[ã,¹ãfzãf½ãf^ãf@ã.ãã,»ãf³ã.¹ã€](#),

æ³T¹¼šã◊"ã◊@è,,tã½±æ€Sã◊◊◊ã¾ã◊™ã,ããz@æfã,¹ã◊◊ã,€Cisco IOSã◊Šã,^ã◊³IOS  
XEã,½ãf•ãf^ã,|ã,Sã,Çã◊@ãfãfãf½ã,¹ã◊Sã◊-ã€◊ã,½ãf½ãfã◊@IDã,¹ç°è^ã◊ã◊™ã,ã◊Yã,ã◊◊ã◊◊ã  
SAN ãf•ã,£ãf½ãf«ãf%ãã,¹ã€Cisco IOS ã◊¾ã◊Yã◊- IOS XE ãfããfã◊ã,ãã,¹ã◊@ PnP  
ãf-ãfãfã,ã,ããfãã◊Sè¨ã@šã◊ã,CEã◊|ã◊,,ã,ã PnP ã,½ãf½ãfã◊ã◊@ DNS  
ã◊◊ã◊¾ã◊Yã◊- IP ã,Çãf%ããf-ã,¹ã◊¨æ¨è½ãfã◊-ã◊¾ã◊™ã€,

ã,¹ãf³ãf-ãf-ãfYã,¹ã◊@ Cisco Application Policy Infrastructure Controller  
ã,¨ãf³ã,¹ãf½ãf-ãf@ã,ãã,°ãfçã,ãfYãf½ãf«i¹^APIC-EMi¹%ãã◊¾ã◊Yã◊- Cisco Digital  
Network Architecturei¹^DNAi¹%ãã,»ãf³ã,¹ãf½ã,¹ PnP

ã,½ãf½ãfã◊ã◊"ã◊-ã◊|ã½zç"¨ã◊-ã◊|ã◊,,ã,ã'ã^ã◊-ã€◊PnP  
ã,½ãf½ãfã◊ã◊@è¨½æ¨Žæ,ã◊◊æœ%ããŠ¹ã◊ª SAN

ãf•ã,£ãf½ãf«ãf%ãã◊CEã◊◊ã◊¾ã,CEã◊|ã◊,,ã,ã◊"ã◊¨ã,¹ç°è^ã◊ã◊™ã,ããz...è|◊ã◊CEã◊,ã,Šã◊¾ã◊  
SAN  
ãf•ã,£ãf½ãf«ãf%ãã◊CEã◊◊ã◊¾ã,CEã◊|ã◊,,ã◊ªã◊,ã'ã^ã◊ç@ççtè...ã◊-ã€◊é◊@ã^ããªª  
SAN  
ãf•ã,£ãf½ãf«ãf%ãã,¹ã◊◊ã,€è¨½æ¨Žæ,ç½²ã◊◊è|◊æ±,i¹^CSRI¹%ãã,¹ç¨Yæ^ã◊-ã€◊æ-°ã◊-ã◊,  
PnP ã,½ãf½ãfã◊ã◊◊ã,ããf³ã,¹ãf^ãf½ãf«ã◊™ã,ããz...è|◊ã◊CEã◊,ã,Šã◊¾ã◊™ã€,

Cisco APIC-EM ç¨¨ã◊@ CA  
ç½²ã◊◊ã»ã◊◊è¨½æ¨Žæ,ã,¹ã◊-ã¾-ã◊™ã,ãæ-¹æ³ã◊@è©³ç°ã◊◊ã◊ã◊,,ã◊|ã◊-ã€◊ã€ŽCisco  
Policy Infrastructure Controller Enterprise Module Administrator Guideã€◊ã◊@ã€CESecuring the  
Cisco APIC-EMã€◊ã◊@ç«ã,¹ã◊,ç...šã◊-ã◊|ã◊◊ã◊ã◊ã◊ã,ã€,Cisco DNA Center  
ã◊@è©³ç°ã◊◊ã◊ã◊,ã◊|ã◊-ã€◊ã€ŽCisco Digital Network Architecture Center Administrator  
Guideã€◊ã◊@ã€CEConfigure System  
Settingsã€◊ã◊@ç«ã,¹ã◊,ç...šã◊-ã◊|ã◊◊ã◊ã◊ã◊ã,ã€,

æœ%ããŠ¹ã◊ª SAN  
ãf•ã,£ãf½ãf«ãf%ãã,¹ã€CEã◊ã◊æèãã±ç½²ã◊◊è¨½æ¨Žæ,ã,¹ã'ã@šã◊™ã,ã◊Yã,ã◊@æ¨æ^ã◊CEã◊  
Technical Assistance Centeri¹^TACi¹%ãã◊¾ã◊Yã◊-ã'ç',ã◊-ã◊|ã◊,,ã,ãfjãf³ãfãfãfãã,¹  
ãf-ãfãfã,ããf£ãf½ãf«ã€é€ççµjã◊™ã,ã◊"ã◊¨ã,ã'ã◊Šã◊Sã,ã◊-ã◊¾ã◊™ã€,

ã,æfã^©ç¨¨ã^ã¾ãã◊¨ã...-ã½ãç™ºèj¨

Cisco Product Security Incident Response  
Teami¹^PSIRTi¹%ãã◊-ã€◊æœ-ã,Çãf%ããfã◊ã,ãã,¶ãfããã◊◊è¨¨è½%ãã◊ã,CEã◊|ã◊,,ã,ã,ã'ã^ãfããããã



å†°å...

æœ-è,†å¼±æ€šã-ã€ã,ã,1ã,³ãt...éfãšã®ã,»ã,ãfãfãftã,£ãftã,1ãfãã«ã,^ã£ã|ç™è|ã•ã,£ã¾ã-ãÿã€,

## URL

<https://sec.cloudapps.cisco.com/security/center/content/CiscoSecurityAdvisory/cisco-sa-20190327-pnp-cert>

æ”¹è,å±ÿæ´

ãfãf¼ã,ãfsãf³	èª-æŽ	ã,»ã,ã,ãfšãf³	ã,1ãf†ãf¼ã,¿ã,¹	æ—ÿã»~
1.0	å^å>žã...-é-ãfãfãf¼ã,¹	-	Final	2019 å¹´ 3 æœ^ 27 æ—ÿ

å^©ç”¹è!ç´,,

æœ-ã,çãf%ãfã,ãã,¶ã,¶ãfãã-ç,,jã¿èè¼ã®ã,,ã®ãã-ã-ã|ã”æã¾ãã-ã|ãšã,šã€  
æœ-ã,çãf%ãfã,ãã,¶ã,¶ãfãã®æf...å±ãšã,^ã³ãfãfãã,ã®ã½¿ç”¹ã«é-çã™ã,«è²-ã»ã®ã,€  
ã¾ãÿã€ã,ã,1ã,³ã-æœ-ãf%ã,ãfãfãfãfã®ãt...ã®1ã,¹ã°ãšããã-ã«ã%æ´ã-ã  
æœ-ã,çãf%ãfã,ãã,¶ã,¶ãfãã®è”è¿ãt...ã®1ã«é-çã-ã|æf...å±è...ã¿jã® URL  
ã,¿œç•ÿã-ã€ããç<-ã®è»çè¼%ã,,,æ,,è”³ã,æ-½ã-ãÿã´ã^ã€ã½”ç¾¾ã£ç®|ç  
ã”ã®ãf%ã,ãfãfãfãfã®æf...å±ã-ã€ã,ã,1ã,³è£½ã”ã®ã,ãfãf%ãf¼ã,¶ã,¹¾è±;ã

## 翻訳について

シスコは世界中のユーザにそれぞれの言語でサポート コンテンツを提供するために、機械と人による翻訳を組み合わせて、本ドキュメントを翻訳しています。ただし、最高度の機械翻訳であっても、専門家による翻訳のような正確性は確保されません。シスコは、これら翻訳の正確性について法的責任を負いません。原典である英語版（リンクからアクセス可能）もあわせて参照することを推奨します。