

Cisco IOS XR Software Intermediate System

ã «ã Šã 'ã, <ã, μãf¼ãf''ã, 1ã | ``ã®³ã ®è,, tã¼±



ã, çãf%ãfã, ðã, ¶ã, ¶ãfãf¼ID : cisco-sa-20190807-iosxr-isis-dos-1918

[CVE-2019-1918](#)

â^â...-é-<æ—¥ : 2019-08-07 16:00

æœ€gæ>'æ-°æ—¥ : 2019-08-20 15:38

ãfãf¼ã, ãfšãf³ 1.1 : Interim

CVSSã, 1ã, 3ã, ç : [7.4](#)

â>žéç- : No workarounds available

Cisco ãfã, ° ID : [CSCvp90854](#)

æ—¥æœ-èªžã «ã, ^ã, <æf...ã ±ã -ã€è<±èªžã «ã, ^ã, <ãžÿæ-†ã ®éžã...-ã¼ã

æ!, è!

Cisco IOS XR ã, ½ãf•ãf^ã, |ã, §ã, çã Šã® Intermediate System-to-Intermediate Systemi¼^IS-
ISi¼%ãf«ãf¼ãftã, £ãf³ã, °

ãf—ãfãfã, ³ãf«æ©ÿèf¼ã®ã®ÿè£...ã «ã Šã'ã, <è,, tã¼±æ€šã «ã, ^ã, Šã€ã®æã~ IS-IS
ã, ``ãfã, çã «ã~ãœ ``ã™ã, <æœªèªè¼ã®æ"»æ'fè€...ã®æã, μãf¼ãf''ã, 1ã | ``ã®³i¼^DoSi¼%çš

ã"ã®è,, tã¼±æ€šã -ã€IS-IS ãfãf³ã, -ã, 1ãftãf¼ãf^ãf—ãfãf^ã, ³ãf«ãfãf¼ã, ç
ãf!ãfãfãf'i¼^PDUi¼%ã®ã, é€©ã^†ãªã!ç®tã«èμ.ã>ã—ã¾ã®™ã€,
æ"»æ'fè€...ã®æã®ã!ç®tã.ã, Çã, <è©²ã½"ã, .ã, 1ãftãfã «ç%ã®šã®ãfãf³ã, -ã, 1ãftãf¼ãf^
PDU

ã, 'éçãçãªã™ã, ãã"ã"ã «ã, ^ã, Šã€ãã"ã®è,, tã¼±æ€šã, ä, çæ£ã^©ç""ã™ã, <ãèf½æ€šã
ä, çæ£ã^©ç""ã «æ^ãšÿã™ã, <ã"ã€æ"»æ'fè€...ã -ã€é†ããçã»ã'ãfãfçãf¼ãf^ã...±æœ
ãfãf³ã, -ã, °ãf«ãf¼ãf—i¼^SRLGi¼%ã¾ãÿã -IGP ãfãf-ã, ã, ãf-ãf«
ã, çãf«ã, 'ãfã, °ãfãšã€ã, çé©ã^†ãªãè^ç®—ã, 'è;Çãtã"ã"ã®æãšãã¾ã™ã€,
ã.ã, %ã«ã€ãfã, °ã, ã®ãf^ãf-ãf¼ã, 1ãfãffã, -ã, ç"ÿã~ã.ã>ãÿã, Šã€ã—ãçãã'ãfã
IS-IS

ãf—ãfã, »ã, 1ã®ã, -ãf©ãffã, .ãf¥ã, 'ç"ÿã~ã.ã>ãÿã, Šã™ã, <ãèf½æ€šã®æã, ã, Šã€ããã
DoS çš¶æ...ã®æç™ç"ÿã™ã, <ã'ã^ã,, ã, ã, Šã¾ã™ã€,

ã, .ã, 1ã, 3ã -ã"ã®è,, tã¼±æ€šã «ã¾ã!ã™ã, <ã, ½ãf•ãf^ã, |ã, šã, ç
ã, çãffãf—ãfãf¼ãf^ã, 'ãfãfãf¼ã, 1ã -ã¾ã -ãÿã€,
ã"ã®è,, tã¼±æ€šã «ã¾ã!ã™ã, <ã>žéç-ã -ã, ã, Šã¾ã>ã, "ã€,


```
net 49.0001.1921.6825.5091.00
address-family ipv4 unicast
!
interface TenGigE0/0/0/1
  address-family ipv4 unicast
  !
```

```
~$show ip interface TenGigE0/0/0/1
TenGigE0/0/0/1 is up, line protocol is up
  IP address: 192.168.1.1/24
  Bcast address: 192.168.1.255
  Multicast: enabled
  MTU 1500
  MAC address: 0800.200c.1a1a
  Vlan: 0
  Encapsulation ARPA
  Security: 0x00000000
  Hardware: Gigabit Ethernet
  Software: IOS XE
  Crypto: none
  Encapsulation: HDLC
  L2 Protocol: Ethernet
  L3 Protocol: IP
  Keepalive: disabled
  Loopback: disabled
  Service: none
  Source-interface: TenGigE0/0/0/1
  Source-interface-ip: 192.168.1.1
  Source-interface-mac: 0800.200c.1a1a
  Source-interface-vlan: 0
  Source-interface-encapsulation: ARPA
  Source-interface-security: 0x00000000
  Source-interface-hardware: Gigabit Ethernet
  Source-interface-software: IOS XE
  Source-interface-crypto: none
  Source-interface-encapsulation: HDLC
  Source-interface-l2-protocol: Ethernet
  Source-interface-l3-protocol: IP
  Source-interface-keepalive: disabled
  Source-interface-loopback: disabled
  Source-interface-service: none
  Source-interface-source-interface: TenGigE0/0/0/1
  Source-interface-source-interface-ip: 192.168.1.1
  Source-interface-source-interface-mac: 0800.200c.1a1a
  Source-interface-source-interface-vlan: 0
  Source-interface-source-interface-encapsulation: ARPA
  Source-interface-source-interface-security: 0x00000000
  Source-interface-source-interface-hardware: Gigabit Ethernet
  Source-interface-source-interface-software: IOS XE
  Source-interface-source-interface-crypto: none
  Source-interface-source-interface-encapsulation: HDLC
  Source-interface-source-interface-l2-protocol: Ethernet
  Source-interface-source-interface-l3-protocol: IP
  Source-interface-source-interface-keepalive: disabled
  Source-interface-source-interface-loopback: disabled
  Source-interface-source-interface-service: none
```

```
RP/0/RSP1/CPU0:IOSXR#
```

```
show isis adjacency
```

IS-IS p Level-1 adjacencies:

| System Id | Interface | SNPA | State | Hold | Changed | NSF | BFD |
|-----------|----------------|----------------|-------|------|----------|---------|------|
| 12a4 | P00/1/0/1 | *PtoP* | Up | 23 | 00:00:06 | Capable | Init |
| 12a4 | TenGigE0/0/0/1 | 0004.2893.f2f6 | Up | 56 | 00:04:01 | Capable | Up |

Total adjacency count: 2

```
!
```

~\$show ip interface TenGigE0/0/0/1

```
TenGigE0/0/0/1 is up, line protocol is up
  IP address: 192.168.1.1/24
  Bcast address: 192.168.1.255
  Multicast: enabled
  MTU 1500
  MAC address: 0800.200c.1a1a
  Vlan: 0
  Encapsulation ARPA
  Security: 0x00000000
  Hardware: Gigabit Ethernet
  Software: IOS XE
  Crypto: none
  Encapsulation: HDLC
  L2 Protocol: Ethernet
  L3 Protocol: IP
  Keepalive: disabled
  Loopback: disabled
  Service: none
  Source-interface: TenGigE0/0/0/1
  Source-interface-ip: 192.168.1.1
  Source-interface-mac: 0800.200c.1a1a
  Source-interface-vlan: 0
  Source-interface-encapsulation: ARPA
  Source-interface-security: 0x00000000
  Source-interface-hardware: Gigabit Ethernet
  Source-interface-software: IOS XE
  Source-interface-crypto: none
  Source-interface-encapsulation: HDLC
  Source-interface-l2-protocol: Ethernet
  Source-interface-l3-protocol: IP
  Source-interface-keepalive: disabled
  Source-interface-loopback: disabled
  Source-interface-service: none
```

~\$

```
show ip interface TenGigE0/0/0/1
```

```
TenGigE0/0/0/1 is up, line protocol is up
```

```
  IP address: 192.168.1.1/24
  Bcast address: 192.168.1.255
  Multicast: enabled
  MTU 1500
  MAC address: 0800.200c.1a1a
  Vlan: 0
  Encapsulation ARPA
  Security: 0x00000000
  Hardware: Gigabit Ethernet
  Software: IOS XE
  Crypto: none
  Encapsulation: HDLC
  L2 Protocol: Ethernet
  L3 Protocol: IP
  Keepalive: disabled
  Loopback: disabled
  Service: none
  Source-interface: TenGigE0/0/0/1
  Source-interface-ip: 192.168.1.1
  Source-interface-mac: 0800.200c.1a1a
  Source-interface-vlan: 0
  Source-interface-encapsulation: ARPA
  Source-interface-security: 0x00000000
  Source-interface-hardware: Gigabit Ethernet
  Source-interface-software: IOS XE
  Source-interface-crypto: none
  Source-interface-encapsulation: HDLC
  Source-interface-l2-protocol: Ethernet
  Source-interface-l3-protocol: IP
  Source-interface-keepalive: disabled
  Source-interface-loopback: disabled
  Source-interface-service: none
```

```
show ip interface TenGigE0/0/0/1
```

```
TenGigE0/0/0/1 is up, line protocol is up
```

```
  IP address: 192.168.1.1/24
  Bcast address: 192.168.1.255
  Multicast: enabled
  MTU 1500
  MAC address: 0800.200c.1a1a
  Vlan: 0
  Encapsulation ARPA
  Security: 0x00000000
  Hardware: Gigabit Ethernet
  Software: IOS XE
  Crypto: none
  Encapsulation: HDLC
  L2 Protocol: Ethernet
  L3 Protocol: IP
  Keepalive: disabled
  Loopback: disabled
  Service: none
  Source-interface: TenGigE0/0/0/1
  Source-interface-ip: 192.168.1.1
  Source-interface-mac: 0800.200c.1a1a
  Source-interface-vlan: 0
  Source-interface-encapsulation: ARPA
  Source-interface-security: 0x00000000
  Source-interface-hardware: Gigabit Ethernet
  Source-interface-software: IOS XE
  Source-interface-crypto: none
  Source-interface-encapsulation: HDLC
  Source-interface-l2-protocol: Ethernet
  Source-interface-l3-protocol: IP
  Source-interface-keepalive: disabled
  Source-interface-loopback: disabled
  Source-interface-service: none
```

```
show ip interface TenGigE0/0/0/1
```

```
TenGigE0/0/0/1 is up, line protocol is up
```

```
  IP address: 192.168.1.1/24
  Bcast address: 192.168.1.255
  Multicast: enabled
  MTU 1500
  MAC address: 0800.200c.1a1a
  Vlan: 0
  Encapsulation ARPA
  Security: 0x00000000
  Hardware: Gigabit Ethernet
  Software: IOS XE
  Crypto: none
  Encapsulation: HDLC
  L2 Protocol: Ethernet
  L3 Protocol: IP
  Keepalive: disabled
  Loopback: disabled
  Service: none
  Source-interface: TenGigE0/0/0/1
  Source-interface-ip: 192.168.1.1
  Source-interface-mac: 0800.200c.1a1a
  Source-interface-vlan: 0
  Source-interface-encapsulation: ARPA
  Source-interface-security: 0x00000000
  Source-interface-hardware: Gigabit Ethernet
  Source-interface-software: IOS XE
  Source-interface-crypto: none
  Source-interface-encapsulation: HDLC
  Source-interface-l2-protocol: Ethernet
  Source-interface-l3-protocol: IP
  Source-interface-keepalive: disabled
  Source-interface-loopback: disabled
  Source-interface-service: none
```

~\$

```
show ip interface TenGigE0/0/0/1
```

```
TenGigE0/0/0/1 is up, line protocol is up
```


æœ-ã,çãf%ãfã,ã,ã,ãfãã®è~è¿°ãt...ã®1ã«é-çã—ã|æf...ã±é...ãzjã® URL
ã,çœç•ã—ã€ããç<-ã®è»çè¼%ã,,æ,,è~³ã,'æ-½ã—ãÿã'ã^ã€ã½"ç³¼ãÇç®;ç
ã"ã®ãf%ã,ãfãf;ãf³ãf^ã®æf...ã±ã-ã€ã,ã,ã,ã,³è£½ã"ã®ã,ãf³ãf%ãf!ãf¼ã,ã,ã,ã³¼è±;ã

翻訳について

シスコは世界中のユーザにそれぞれの言語でサポート コンテンツを提供するために、機械と人による翻訳を組み合わせて、本ドキュメントを翻訳しています。ただし、最高度の機械翻訳であっても、専門家による翻訳のような正確性は確保されません。シスコは、これら翻訳の正確性について法的責任を負いません。原典である英語版（リンクからアクセス可能）もあわせて参照することを推奨します。