

Cisco Small Business

RV110W, RV130, RV130W, RV215W

Remote Command Execution (RCE) Vulnerability



CVE-2021-1459

Published: 2021-04-07 16:00

Version: 1.0 : Final

CVSS Score: 9.8

Workarounds: No workarounds available

Cisco ID: CSCvx05139

Remote Command Execution (RCE) Vulnerability

CVSS

Cisco Small Business RV110W, RV130, RV130W, RV215W

Web

Remote Command Execution (RCE) Vulnerability

Remote Command Execution (RCE) Vulnerability

Remote Command Execution (RCE) Vulnerability

HTTP

Remote Command Execution (RCE) Vulnerability

Remote Command Execution (RCE) Vulnerability

Remote Command Execution (RCE) Vulnerability

Remote Command Execution (RCE) Vulnerability

<https://tools.cisco.com/security/center/content/CiscoSecurityAdvisory/cisco-sa-rv-rce-q3rxHnvm>

CVSS

CVSS

Remote Command Execution (RCE) Vulnerability

Remote Command Execution (RCE) Vulnerability

- RV110W Wireless-N VPN
- RV130 VPN
- RV130W Wireless-N VPN
- RV215W Wireless-N VPN

Configuring VPN

Step 1: Configure the LAN interface

Configure the LAN interface with IP address 192.168.1.1 and subnet mask 255.255.255.0.

Step 2: Configure the WAN interface

Configure the WAN interface with IP address 192.168.1.1 and subnet mask 255.255.255.0.

Configure the WAN interface with IP address 192.168.1.1 and subnet mask 255.255.255.0.

Configure the WAN interface with IP address 192.168.1.1 and subnet mask 255.255.255.0.

Configure the WAN interface with IP address 192.168.1.1 and subnet mask 255.255.255.0.

Configure the WAN interface with IP address 192.168.1.1 and subnet mask 255.255.255.0.

Configure the WAN interface with IP address 192.168.1.1 and subnet mask 255.255.255.0.

Configure the WAN interface with IP address 192.168.1.1 and subnet mask 255.255.255.0.

Configure the WAN interface with IP address 192.168.1.1 and subnet mask 255.255.255.0.

Configuring VPN

Configure the WAN interface with IP address 192.168.1.1 and subnet mask 255.255.255.0.

Configuring VPN

Configure the WAN interface with IP address 192.168.1.1 and subnet mask 255.255.255.0.

Configure the WAN interface with IP address 192.168.1.1 and subnet mask 255.255.255.0.

Configure the WAN interface with IP address 192.168.1.1 and subnet mask 255.255.255.0.

Configuring VPN

Configure the WAN interface with IP address 192.168.1.1 and subnet mask 255.255.255.0.

Configure the WAN interface with IP address 192.168.1.1 and subnet mask 255.255.255.0.

Configure the WAN interface with IP address 192.168.1.1 and subnet mask 255.255.255.0.

Configure the WAN interface with IP address 192.168.1.1 and subnet mask 255.255.255.0.

Configure the WAN interface with IP address 192.168.1.1 and subnet mask 255.255.255.0.

翻訳について

シスコは世界中のユーザにそれぞれの言語でサポート コンテンツを提供するために、機械と人による翻訳を組み合わせて、本ドキュメントを翻訳しています。ただし、最高度の機械翻訳であっても、専門家による翻訳のような正確性は確保されません。シスコは、これら翻訳の正確性について法的責任を負いません。原典である英語版（リンクからアクセス可能）もあわせて参照することを推奨します。