

RV016€? RV042€? RV042G€? Š,^€?³RV0  
VPNƒ«ƒ¼,¿Š€?®PPPoE€?®è“å®š

ÇRÇŞ,,

### PPPoE(Point to Point Protocol over

è©²å¹½“ã?™ã, <ãƒ‡ãƒ?ã?ã, »ã, ¹

ãf» RV016  
ãf» RV042  
ãf» RV042G  
ãf» RV082

## [Software Version]

ãf» v4.2.1.02

## PPPoE

æ-]ã?®æ‰é tã?§ã?¬ã€?RVæœ‰ç·šãf«ãf¼ã,¿ã,·ãfªãf¼ã,ºã?§ã?®PPPoEã?®è” å®šã?«ã

ã, 'ãf†ãffãf— 1i<sup>1/4</sup>šRouter Configuration Utilityã«ãfã, °ã,¤ãf<sup>3</sup>ã—ã€Setup >  
Networkã®é tã«é,æŠzã—ã<sup>3/4</sup>ã™ã€,[Network]  
ãfšãf<sup>1/4</sup>ã, ,ãŒé—ã?ã?ã<sup>3/4</sup>ã?ã™ã€,

## Network

Host Name : router88c688 (Required by some ISPs)

Domain Name : router88c688.com (Required by some ISPs)

### IP Mode

Mode	WAN	LAN
<input checked="" type="radio"/> IPv4 Only	IPv4	IPv4
<input type="radio"/> Dual-Stack IP	IPv4 and IPv6	IPv4 and IPv6

IPv4  IPv6

### LAN Setting

MAC Address : AB:CD:EF:AB:CD:EF

Device IP Address : 192.168.1.1

Subnet Mask : 255.255.255.0

Multiple Subnet :  Enable

### WAN Setting

Interface	Connection Type	Configuration
WAN1	Obtain an IP automatically	
WAN2	Obtain an IP automatically	

### DMZ Setting

Enable DMZ

— 2 WAN

Setting [PPPoE, WAN Connection] —> Edit,

**Network**

### Edit WAN Connection

Interface : WAN1

WAN Connection Type : Obtain an IP automatically ▾

Use the Following DNS Server Address

DNS Server (Required) 1 : 0.0.0.0

2 : 0.0.0.0

MTU :  Auto  Manual 1500 bytes

---

**Save** **Cancel**

**Network**

Edit WAN Connection

Interface : WAN1

WAN Connection Type : Obtain an IP automatically ▾

Obtain an IP automatically  
Static IP  
PPPoE  
PPTP  
Transparent Bridge

DNS Server (Required) 1 : 2 : 0.0.0.0

MTU :  Auto  Manual 1500 bytes

Save Cancel

## Network

### Edit WAN Connection

Interface : WAN1

WAN Connection Type : PPPoE

Username : User1

Password : \*\*\*\*\*

Service Name : DSL

Connect on Demand : Max Idle Time 5 Min.

Keep Alive : Redial Period 30 Sec.

MTU :  Auto       Manual 1492 bytes

Save Cancel

æ‰œé†

4i¼š[Username]ãƒ•ã,£ãƒ¼ãƒ«ãƒ‰oã¢«ã€¢ISPã¢<ã,‰œ¢¢ä¾»ã¢•ã,Œã¢Ýãƒ'ãƒ¼ã,¶å¢¢ã,'å...¥

ã,ïäf†äffäf—

5i¼š[Password]ãƒ•ã,£ãƒ¼ãƒ«ãƒ‰oã¢«ã€¢ISPã¢<ã,‰œ¢¢ä¾»ã¢•ã,Œã¢Ýãƒã,¹ãf~ãƒ¼ãƒ‰oã,'å...¥

ã,ïäf†äffäf—6:i¼ã,^ã,^äf—ã,·ãƒ§ãƒ³i¼‰[Service

Namei¼ã,µf¼ãf“ã,^å¢¢i¼‰]ãƒ•ã,£ãƒ¼ãƒ«ãƒ‰oã¢«ã€¢æ¢¢ä¾»ã¢•ã,Œã,<ã,µãf¼ãf“ã,^ã,'è~å^

## Network

### Edit WAN Connection

Interface : WAN1

WAN Connection Type : PPPoE

Username : User1

Password : \*\*\*\*\*

Service Name : DSL

Connect on Demand : Max Idle Time 5 Min.

Keep Alive : Redial Period 30 Sec.

MTU :  Auto       Manual 1492 bytes

Save Cancel

æ‰œé†

7i¼šæŽ¥ç¶šæœŸé—“ã,’ç®¡ç¢¢†ã¢™ã,<ã¢«ã¢~ã€¢2ã¢¤ã¢®ã,^äf—ã,·ãƒ§ãƒ³ã¢Œã¢,ã,Šã¢ä¾ã¢

on Demand? Keep

## » Connect on Demand: Max Idle

Timei¼šã“ã®ã, ªf—ã, ·ãf§ãf³ã, ª½ç”“ã®™ã, <ã® “ã€ã, çã, »ãf%oãf«æ™, é—“ã®®å¾Œã®«ãidle

time&#8226;ã,£&#8226;%4&#8226;<&#8226;%oã&#8226;«è”å®šã&#8226;§ã&#8226;?ã&#8226;?3/4&#8226;™ã€,æœ€å¤§ã,çã,¤ãf%oãf«æ™,é-“ã&#8226;-ã€»

äf»ã,äf<sup>1</sup>/<sub>4</sub>äf—ã,çäf©ã,¤äf-ï<sup>1</sup>/<sub>4</sub>šãäf€ã,¤äf¤äf«æœŸé—“í<sup>1</sup>/<sub>4</sub>šã”ã◆®ã,³äf—ã,·äf§äf<sup>3</sup>ã◆—ã€◆äf«äf<sup>1</sup>/<sub>4</sub>ç§’ã◆§ã◆™ã€,

**Network**

**Edit WAN Connection**

Interface :	WAN1
WAN Connection Type :	PPPoE
Username :	User1
Password :	*****
Service Name :	DSL
<input checked="" type="radio"/> Connect on Demand : Max Idle Time 5 Min.	
<input type="radio"/> Keep Alive : Redial Period 30 Sec.	
MTU :	<input checked="" type="radio"/> Manual 1492 bytes
<input type="button" value="Save"/>	<input type="button" value="Cancel"/>

— Maximum Transmission

Uniti  $\frac{1}{4}$  æø€å¤§ä½é€?ãf|ãf<ãffãf^ï¼‰ã«ã?\_ã€?ãf#ãf½ã,¿ä½é€?ã?«ä½ç"å?\_èf½ã?

$\tilde{a}f \gg$

Manual:ISP ◊®ä»•æ§~ã◊«åÝä◊¥ã◊„ã◊|ã€◊å€¤ã,'æ‰¤«å<ã◊§å...¥åŠã◊—ã◊¾/ã◊™ã€,PI

ā, āf†āffāf—

9i1/4šSaveä,’ä,—äf<sup>a</sup>ffä,—ä—ä|ä€ PPPoEä♦SèiŒä,♦ä,Œä?Ýä?™ä?1ä|ä?Rè”å®šä,ä?ä

## 翻訳について

シスコは世界中のユーザにそれぞれの言語でサポート コンテンツを提供するために、機械と人による翻訳を組み合わせて、本ドキュメントを翻訳しています。ただし、最高度の機械翻訳であっても、専門家による翻訳のような正確性は確保されません。シスコは、これら翻訳の正確性について法的責任を負いません。原典である英語版（リンクからアクセス可能）もあわせて参照することを推奨します。