



Cisco Unified CME の設定例

次に、Cisco Unified CME で動作する SIP 電話機の設定例を示します。

```
voice service voip
  allow-connections sip to sip
  sip
  registrar server expires max 600 min 60
```

```
voice class codec 1
  codec preference 1 g711ulaw
```

```
voice hunt-group 1 parallel
  final 8000
  list 2000,1000,2101
  timeout 20
  pilot 9000
```

```
voice hunt-group 2 sequential
  final 1000
  list 2000,2300
  timeout 25
  pilot 9100 secondary 9200
```

```
voice hunt-group 3 peer
  final 2300
  list 2100,2200,2101,2201
  timeout 15
  hops 3
  pilot 9300
  preference 5
```

```
voice hunt-group 4 longest-idle
  final 2000
  list 2300,2100,2201,2101,2200
  timeout 15
  hops 5
  pilot 9400 secondary 9444
  preference 5 secondary 9
```

```
voice register global
  mode cme

  external-ring bellcore-dr3
```

```
voice register dn 1
  number 2300
  mwi
```

```
voice register dn 2
  number 2200
  call-forward b2bua all 1000
  call-forward b2bua mailbox 2200
  mwi
```

```
voice register dn 3
  number 2201
  after-hour exempt

voice register dn 4
  number 2100
  call-forward b2bua busy 2000
  mwi

voice register dn 5
  number 2101
  mwi

voice register dn 76
  number 2525
  call-forward b2bua unreachable 2300
  mwi
!
voice register template 1
!
voice register template 2
  no conference enable
  voicemail 7788 timeout 5
!

voice register pool 1
  id mac 000D.ED22.EDFE
  type 7960
  number 1 dn 1
  template 1
  preference 1
  no call-waiting
  codec g711alaw
!
voice register pool 2
  id mac 000D.ED23.CBA0
  type 7960
  number 1 dn 2
  number 2 dn 2
  template 1
  preference 1

  dtmf-relay rtp-nte
  speed-dial 3 2001
  speed-dial 4 2201
!
voice register pool 3
  id mac 0030.94C3.053E
  type 7960
  number 1 dn 3
  number 3 dn 3
  template 2

!
voice register pool 5
  id mac 0012.019B.3FD8
  type ATA
  number 1 dn 5
  preference 1
  dtmf-relay rtp-nte
  codec g711alaw

voice register pool 6
  id mac 0012.019B.3E88
  type ATA
  number 1 dn 6
  number 2 dn 7
  template 2
  dtmf-relay-rtp-nte
```

```
call-forward b2bua all 7778

voice register pool 7

voice register pool 8
  id mac 0006.D737.CC42
  type 7940
  number 1 dn 8
  template 2
  preference 1
  codec g711alaw

voice-port 1/0/0

voice-port 1/0/1

dial-peer voice 100 pots
  destination-pattern 2000
  port 1/0/0

dial-peer voice 101 pots
  destination-pattern 2010
  port 1/0/1

dial-peer voice 1001 voip
  preference 1
  destination-pattern 1...
  session protocol sipv2
  session target ipv4:10.15.6.13
  codec g711ulaw

sip-ua
  mwi-server ipv4:1.15.6.200 expires 3600 port 5060 transport udp

telephony-service
  load 7960-7940 POS3-07-2-00
  max-ephones 24
  max-dn 96
  ip source-address 10.15.6.112 port 2000
  create cnf-files version-stamp Aug 24 2004 00:00:00
  max-conferences 8
  after-hours block pattern 1 1...
  after-hours day Mon 17:00 07:00
```

