

Web Security Appliance에서 수동 DNS 항목을 구성하려면 어떻게 합니까?

목차

[질문](#)
[환경](#)

질문

Cisco Web Security Appliance에서 수동 DNS 항목을 구성하려면 어떻게 합니까?

환경

Cisco WSA(Web Security Appliance), 모든 AsyncOS 버전

CLI(Command Line Interface)에 다음과 같은 명령을 입력합니다.

```
WSA> dnsconfig
```

```
Choose the operation you want to perform:
```

- NEW - Add a new server.
- SETUP - Configure general settings.
- SEARCH - Configure DNS domain search list.

```
[> localhosts
```

```
Local IP to Host mappings:
```

```
Choose the operation you want to perform:
```

- NEW - Add new local IP to host mapping.
- DELETE - Delete an existing mapping.

```
[> new
```

```
Enter the IP address of the host you are adding.
```

```
[> 1.1.1.1
```

```
Enter the canonical host name and any additional aliases (separate values with spaces)
```

```
[> example.com
```

```
Local IP to Host mappings:
```

```
1. 1.1.1.1 example.com
```

```
Choose the operation you want to perform:
```

- NEW - Add new local IP to host mapping.
- DELETE - Delete an existing mapping.

```
[>
```

CLI 프롬프트에서 CLI 명령 - **commit** -를 사용하여 DNS 컨피그레이션 변경 사항을 커밋하십시오.

참고:CLI 명령 'dnsconfig'의 "*localhosts*" 옵션은 숨겨진 옵션입니다.