

Nexus EVN-VXLAN multi-site configureren met routeserver

Inhoud

[Inleiding](#)

[Voorwaarden](#)

[Vereisten](#)

[Gebruikte componenten](#)

[Achtergrondinformatie](#)

[Hoe is Multi-Site Nuttig?](#)

[Andere voordelen](#)

[Configureren](#)

[Netwerkdiagram](#)

[Configuratie van site 1-blad-1](#)

[Configuratie van site 1-blad-2](#)

[Configuratie van locatie 1 blad-3](#)

[Configuratie van locatie 1 blad-4](#)

[Configuratie van locatie 1 spine-1](#)

[Configuratie van site 1 border gateway-1](#)

[Configuratie van site 1-border gateway 2](#)

[Routerserver](#)

[Configuratie van site 2-border gateway 1](#)

[Configuratie van site 2-border gateway 2](#)

[Configuratie van site 2 in ruggengraat 1](#)

[Configuratie site 2-blad-1](#)

[Configuratie Site 2 Leaf-2](#)

[Configuratie Site 2 Leaf-3](#)

[Configuratie Site 2 Leaf-4](#)

[Verifiëren](#)

[Problemen oplossen](#)

Inleiding

Dit document beschrijft hoe de Ethernet VPN/Virtual Extensible LAN (EVN/VxLAN)-omgeving voor meerdere locaties op Cisco Nexus 9000 switches moet worden geconfigureerd en geverifieerd. Hierbij wordt gebruikgemaakt van virtueel weefsel in vPC-bladknooppunten.

Voor plaats-aan-plaats connectiviteit, wordt het concept van de routeserver verklaard.

Voorwaarden

Vereisten

Cisco raadt kennis van de volgende onderwerpen aan:

- Multiprotocol Label Switching (MPLS) Layer 3 VPN
- Multiprotocol-Border Gateway Protocol (MP-BGP)
- EVPN

Gebruikte componenten

De informatie in dit document is gebaseerd op de volgende software- en hardware-versies:

Alle pagina's	N9K-C936C-FX2 switch	NXOS: 10.2(3)
S1_ruggengraat1	N9K-C9364C switch	NXOS: 10.2(4)
S1_Spine2	N9K-C9364C switch	NXOS 9.3(5)
S1_Border Gateway1, S2_Border Gateway2, S2_Border Gateway1	N9K-C932C switch	NXOS: 9.3(9)
S1_border-gateway2	N9K-C932C switch	NXOS: 10.2(4)
Routeserver	N9K-C9396PX switch	NXOS: 9.2(2)
Host 1	N3K-C3264C-E switch	NXOS: 9.3(5)
Host 2 en Host 3	N3K-C3264C-E switch	NXOS: 9.2(2)

De informatie in dit document is gebaseerd op de apparaten in een specifieke laboratoriumomgeving. Alle apparaten die in dit document worden beschreven, hadden een opgeschoonde (standaard)configuratie. Als uw netwerk live is, moet u zorgen dat u de potentiële impact van elke opdracht begrijpt.

Achtergrondinformatie

Het datacenter is een resourcepool die rekenkracht, opslag en de nodige toepassingen bevat om elke zakelijke omgeving te ondersteunen. Een goede planning van het ontwerp van de datacenterinfrastructuur is van vitaal belang. Dit document heeft betrekking op kritieke vereisten, zoals voor ziekenhuisnetwerken, en de manier waarop aan deze vereisten moet worden voldaan of deze moeten worden overtroffen. Moderne IT-infrastructuren en datacenterimplementaties hebben behoefte aan hoge beschikbaarheid, de mogelijkheid om sneller te schalen en voortdurend hoge prestaties.

Een paar onderzochte vitale vereisten in de DC ontwerp/architectuur ruimte omvatten:

- De poortdichtheid wordt verbeterd door Fabric Extender (FEX).
- De computing-capaciteit wordt verbeterd door Hardware Virtualization (UCS).
- Access Layer uplink-bandbreedte wordt verbeterd door poortkanaal.
- Redundantie op chassisniveau is verbeterd door vPC.
- Software-Defined Networking (SDN)-fabric wordt verbeterd door Application Centric Infrastructure (ACI) - automatiseert onderlay en overlay in een fabric.
- Snelle implementatie en ondersteuning van nieuwe services worden verbeterd door Data Center Network Manager (DCNM).
- De bandbreedtebehoefte voor langeafstandstoepassingen wordt verbeterd door donkere glasvezel- of golflengtediensten.
- Vooral geografische redundantie en schalen zijn belangrijke kenmerken voor het weggooien/schalen van de datacenteromgeving. Multi-Site VxLAN/EVPN helpt ons om betere DCI-oplossingen (Data Center Interconnect) te hebben.

Hoe is Multi-Site Nuttig?

Externe connectiviteit omvat de verbinding van het datacenter met de rest van het netwerk: met het internet, het WAN of de campus. Alle opties die voor externe connectiviteit worden verstrekt zijn multi-huurderebewust en concentreren zich op Layer 3 (L3) vervoer aan de externe netwerkdomeinen.

- EVPN is een next-generation all-in-one VPN-oplossing.


- Het doet niet alleen het werk van veel andere VPN-technologieën, maar het is ook beter.
- Integratie met oudere netwerken.
- Selectieve advertentie/extensie:
 - Breid alleen Layer 2 (L2) uit - specifieke VLANâ€™s/subnetten die kunnen worden uitgebreid met Type-2-routes.
 - Uitbreiden van de enige L3 - specifieke L3 domeinen kunnen worden uitgebreid met Type-5 routes.
- Auto-ontdekking van redundantiegroep met Type-4 routes.
- Aliasring, massale intrekking van adressen, Split Horizon (SH) Multi Homing (MH) indicatie met Type 1 routes.
- Auto-ontdekking van multicast tunneleindpunten en multicast (MCAST) tunneltype met Type-3 routes.

Andere voordelen

- Werklastverdeling over datacenters en clouds.
- Proactieve respons op verstoringen - vermindert de risico's van het naderen van rampen, zoals orkanen en overstromingen.
- Onderhoud en migratie van datacenters - geplande evenementen die over een bepaalde periode worden gepland en integratie met oudere netwerken.
- Back-up en noodherstel als service (aaS).

Configureren

Netwerkdiagram



Topologie

Configuratie van site 1-blad-1

```

feature nxapi
cfs ipv4 distribute
nv overlay evpn
feature ospf
feature bgp
feature pim
feature fabric forwarding
feature interface-vlan
feature vn-segment-vlan-based
feature lacp
feature vpc
feature nv overlay

```

```
fabric forwarding anycast-gateway-mac 0000.1111.2222

ip pim rp-address 10.102.0.2 group-list 224.0.0.0/4
ip pim ssm range 232.0.0.0/8
ip igmp snooping vxlan

vlan 1,100,200,300-350,2001
vlan 100
  vn-segment 4000100
vlan 200
  vn-segment 4000200
vlan 301
  vn-segment 4000301
vlan 302
  vn-segment 4000302
vlan 303
  vn-segment 4000303
vlan 350
  name L3-VNI
  vn-segment 4000999
vlan 2001
  vn-segment 4000502

vrf context L3VNI4000999
  vni 4000999
  rd auto
  address-family ipv4 unicast
    route-target both auto
    route-target both auto evpn
vrf context vrf_1
  vni 4000501
  rd auto
  address-family ipv4 unicast
    route-target both auto
    route-target both auto evpn

vrf context vrf_2
  vni 4000502
  rd auto
  address-family ipv4 unicast
    route-target both auto
    route-target both auto evpn
vpc domain 100
  peer-switch
    peer-keepalive destination 10.197.214.54 source 10.197.214.53
    virtual peer-link destination 10.102.1.9 source 10.102.1.8 dscp 56
    delay restore 150
  peer-gateway
    ip arp synchronize

interface Vlan100
  no shutdown
  mtu 9216
  vrf member vrf_2
  no ip redirects
  ip address 192.168.100.254/24
  no ipv6 redirects
  fabric forwarding mode anycast-gateway

interface Vlan200
```

```
no shutdown
mtu 9216
vrf member vrf_2
no ip redirects
ip address 192.168.200.254/24
no ipv6 redirects
fabric forwarding mode anycast-gateway

interface Vlan301
no shutdown
mtu 9216
vrf member vrf_1
no ip redirects
ip address 172.16.11.254/24
no ipv6 redirects
fabric forwarding mode anycast-gateway

interface Vlan302
no shutdown
mtu 9216
vrf member vrf_1
no ip redirects
ip address 172.16.12.254/24
no ipv6 redirects
fabric forwarding mode anycast-gateway

interface Vlan303
no shutdown
mtu 9216
vrf member vrf_1
no ip redirects
ip address 172.16.13.254/24
no ipv6 redirects
fabric forwarding mode anycast-gateway

interface Vlan2001
no shutdown
mtu 9000
vrf member vrf_2
no ip redirects
ip forward
ipv6 address use-link-local-only
no ipv6 redirects

interface port-channel10
switchport
switchport mode trunk
switchport trunk allowed vlan 100,200,300-350,2001
spanning-tree port type network
vpc peer-link

interface port-channel100
switchport
switchport mode trunk
switchport trunk allowed vlan 100,200
mtu 9216
vpc 100

interface nve1
no shutdown
host-reachability protocol bgp
advertise virtual-rmac
```

```
source-interface loopback1
member vni 4000100
  suppress-arp
  mcast-group 231.0.0.1
member vni 4000200
  suppress-arp
  mcast-group 231.0.0.2
member vni 4000502 associate-vrf

interface Ethernet1/1
  switchport
  switchport mode trunk
  switchport trunk allowed vlan 100,200
  mtu 9216
  channel-group 100
  no shutdown

interface Ethernet1/2
  mtu 9216
  port-type fabric
  medium p2p
  ip address 192.168.17.12/24
  ip ospf network point-to-point
  ip router ospf 100 area 0.0.0.0
  ip pim sparse-mode
  no shutdown

interface loopback0
  ip address 10.102.0.5/32
  ip router ospf 100 area 0.0.0.0
  ip pim sparse-mode

interface loopback1
  ip address 10.102.1.8/32
  ip address 10.201.201.201/32 secondary
  ip router ospf 100 area 0.0.0.0
  ip pim sparse-mode

router ospf 100
  router-id 10.102.0.5
router bgp 100
  router-id 10.102.0.5
  log-neighbor-changes
  address-family l2vpn evpn
    advertise-pip
  neighbor 10.102.0.2
    remote-as 100
    update-source loopback0
    address-family ipv4 unicast
    address-family ipv6 unicast
      send-community
      send-community extended
    address-family l2vpn evpn
      send-community
      send-community extended
  neighbor 10.102.0.3
    remote-as 100
    update-source loopback0
    address-family ipv4 unicast
    address-family ipv6 unicast
      send-community
      send-community extended
```

```

address-family l2vpn evpn
  send-community
  send-community extended

evpn
  vni 4000100 12
    rd auto
    route-target import auto
    route-target export auto
  vni 4000200 12
    rd auto
    route-target import auto
    route-target export auto
  vni 4000301 12
    rd auto
    route-target import auto
    route-target export auto
  vni 4000302 12
    rd auto
    route-target import auto
    route-target export auto
  vni 4000303 12
    rd auto
    route-target import auto
    route-target export auto

```

Configuratie van site 1-blad-2

```

feature nxapi
feature sftp-server
cfs ipv4 distribute
nv overlay evpn
feature ospf
feature bgp
feature pim
feature fabric forwarding
feature interface-vlan
feature vn-segment-vlan-based
feature lacp
feature vpc
feature nv overlay
fabric forwarding anycast-gateway-mac 0000.1111.2222

ip pim rp-address 10.102.0.2 group-list 224.0.0.0/4
ip pim ssm range 232.0.0.0/8

vlan 1,100,200,300-350,2001

vlan 100
  vn-segment 4000100
vlan 200
  vn-segment 4000200
vlan 301
  vn-segment 4000301
vlan 302
  vn-segment 4000302
vlan 303
  vn-segment 4000303

```

```

vlan 350
  name L3-VNI
  vn-segment 4000999
vlan 2001
  vn-segment 4000502

vrf context L3VNI4000999
  vni 4000999
  rd auto
  address-family ipv4 unicast
    route-target both auto
    route-target both auto evpn

vrf context vrf_1
  vni 4000501
  rd auto
  address-family ipv4 unicast
    route-target both auto
    route-target both auto evpn

vrf context vrf_2
  vni 4000502
  rd auto
  address-family ipv4 unicast
    route-target both auto
    route-target both auto evpn

vpc domain 100
  peer-switch
  peer-keepalive destination 10.197.214.53 source 10.197.214.54
  virtual peer-link destination 10.102.1.8 source 10.102.1.9 dscp 56
  delay restore 150
  peer-gateway
  ip arp synchronize

interface Vlan100
  no shutdown
  mtu 9216
  vrf member vrf_2
  no ip redirects
  ip address 192.168.100.254/24
  no ipv6 redirects
  fabric forwarding mode anycast-gateway

interface Vlan200
  no shutdown
  mtu 9216
  vrf member vrf_2
  no ip redirects
  ip address 192.168.200.254/24
  no ipv6 redirects
  fabric forwarding mode anycast-gateway

interface Vlan301
  no shutdown
  mtu 9216
  vrf member vrf_1
  no ip redirects
  ip address 172.16.11.254/24
  no ipv6 redirects

  fabric forwarding mode anycast-gateway

```

```
interface Vlan302
  no shutdown
  mtu 9216
  vrf member vrf_1
  no ip redirects
  ip address 172.16.12.254/24
  no ipv6 redirects
  fabric forwarding mode anycast-gateway

interface Vlan303
  no shutdown
  mtu 9216
  vrf member vrf_1
  no ip redirects
  ip address 172.16.13.254/24
  no ipv6 redirects
  fabric forwarding mode anycast-gateway

interface Vlan2001
  no shutdown
  mtu 9000
  vrf member vrf_2
  no ip redirects
  ip forward
  ipv6 address use-link-local-only
  no ipv6 redirects

interface port-channel10
  switchport
  switchport mode trunk
  switchport trunk allowed vlan 100,200,300-350,2001
  spanning-tree port type network
  vpc peer-link

interface port-channel100
  switchport
  switchport mode trunk
  switchport trunk allowed vlan 100,200
  mtu 9216
  vpc 100

interface nve1
  no shutdown
  host-reachability protocol bgp
  advertise virtual-rmac
  source-interface loopback1
  member vni 4000100
    suppress-arp
    mcast-group 231.0.0.1
  member vni 4000200
    suppress-arp
    mcast-group 231.0.0.2
  member vni 4000502 associate-vrf

interface Ethernet1/1
  switchport
  switchport mode trunk
  switchport trunk allowed vlan 100,200
  mtu 9216
  channel-group 100
  no shutdown
```

```
interface Ethernet1/2
  mtu 9216
  port-type fabric
  medium p2p
  ip address 192.168.18.12/24
  ip ospf network point-to-point
  ip router ospf 100 area 0.0.0.0
  ip pim sparse-mode
  no shutdown

interface loopback0
  ip address 10.102.0.8/32
  ip router ospf 100 area 0.0.0.0
  ip pim sparse-mode

interface loopback1
  ip address 10.102.1.9/32
  ip address 10.201.201.201/32 secondary
  ip router ospf 100 area 0.0.0.0
  ip pim sparse-mode
  icam monitor scale

router ospf 100
  router-id 10.102.0.8
router bgp 100
  router-id 10.102.0.8
  log-neighbor-changes
  address-family l2vpn evpn
    advertise-pip
  neighbor 10.102.0.2
    remote-as 100
    update-source loopback0
    address-family ipv4 unicast
    address-family ipv6 unicast
      send-community
      send-community extended
    address-family l2vpn evpn
      send-community
      send-community extended
  neighbor 10.102.0.3
    remote-as 100
    update-source loopback0
    address-family ipv4 unicast
    address-family ipv6 unicast
      send-community
      send-community extended
    address-family l2vpn evpn
      send-community
      send-community extended
evpn
  vni 4000100 12
    rd auto
    route-target import auto
    route-target export auto
  vni 4000200 12
    rd auto
    route-target import auto
    route-target export auto
  vni 4000301 12
    rd auto
    route-target import auto
    route-target export auto
```

```

vni 4000302 12
  rd auto
  route-target import auto
  route-target export auto
vni 4000303 12
  rd auto
  route-target import auto
  route-target export auto

```

Configuratie van locatie 1 blad-3

```

feature nxapi
feature bash-shell
cfs ipv4 distribute
nv overlay evpn
feature ospf
feature bgp
feature pim
feature fabric forwarding
feature interface-vlan
feature vn-segment-vlan-based
feature lacp
feature vpc
feature nv overlay
feature ngoam

fabric forwarding anycast-gateway-mac 0000.1111.2222

ip pim rp-address 10.102.0.2 group-list 224.0.0.0/4
ip pim ssm range 232.0.0.0/8

vlan 1,100,200,300-350,2001

vlan 100
  vn-segment 4000100
vlan 200
  vn-segment 4000200
vlan 301
  vn-segment 4000301
vlan 302
  vn-segment 4000302
vlan 303
  vn-segment 4000303
vlan 350
  name L3-VNI
  vn-segment 4000999
vlan 2001
  vn-segment 4000502

vrf context L3VNI4000999
  vni 4000999
  rd auto
  address-family ipv4 unicast
    route-target both auto
    route-target both auto evpn

vrf context vrf_1
  vni 4000501

```

```

rd auto
address-family ipv4 unicast
  route-target both auto
  route-target both auto evpn

vrf context vrf_2
  vni 4000502
  rd auto
  address-family ipv4 unicast
    route-target both auto
    route-target both auto evpn

vpc domain 100
  peer-switch
  peer-keepalive destination 10.197.214.56 source 10.197.214.55
  virtual peer-link destination 10.102.0.10 source 10.102.0.9 dscp 56
  delay restore 150
  peer-gateway
  layer3 peer-router
  ip arp synchronize

interface Vlan100
  no shutdown
  mtu 9216
  vrf member vrf_2
  no ip redirects
  ip address 192.168.100.254/24
  no ipv6 redirects
  fabric forwarding mode anycast-gateway

interface Vlan200
  no shutdown
  mtu 9216
  vrf member vrf_2
  no ip redirects
  ip address 192.168.200.254/24
  no ipv6 redirects
  fabric forwarding mode anycast-gateway

interface Vlan2001
  no shutdown
  mtu 9000
  vrf member vrf_2
  no ip redirects
  ip forward
  ipv6 address use-link-local-only
  no ipv6 redirects

interface port-channel2
  switchport
  switchport mode trunk
  switchport trunk allowed vlan 100,200
  vpc 2

interface port-channel10
  switchport
  switchport mode trunk
  switchport trunk allowed vlan 100,200,300-500,2001
  spanning-tree port type network
  vpc peer-link

interface nve1

```

```
no shutdown
host-reachability protocol bgp
advertise virtual-rmac
source-interface loopback1
member vni 4000100
  suppress-arp
  mcast-group 231.0.0.1
member vni 4000200
  suppress-arp
  mcast-group 231.0.0.2
member vni 4000502 associate-vrf

interface Ethernet1/1
  switchport
  switchport mode trunk
  switchport trunk allowed vlan 200,300-305
  mtu 9216
  no shutdown

interface Ethernet1/2
  mtu 9216
  port-type fabric
  medium p2p
  ip address 192.168.19.12/24
  ip ospf network point-to-point
  ip router ospf 100 area 0.0.0.0
  ip pim sparse-mode
  no shutdown

interface Ethernet1/24
  switchport
  switchport mode trunk
  switchport trunk allowed vlan 100,200
  channel-group 2 mode active
  no shutdown

interface loopback0
  ip address 10.102.0.9/32
  ip router ospf 100 area 0.0.0.0
  ip pim sparse-mode

interface loopback1
  ip address 10.102.1.10/32
  ip address 10.202.202.202/32 secondary
  ip router ospf 100 area 0.0.0.0
  ip pim sparse-mode

interface loopback100
  vrf member vrf_2
  ip address 10.15.100.2/24

router ospf 100
  router-id 10.102.0.9
router bgp 100
  router-id 10.102.0.9
  log-neighbor-changes
  address-family l2vpn evpn
    advertise-pip
  neighbor 10.102.0.2
    remote-as 100
    update-source loopback0
    address-family ipv4 unicast
```

```

address-family ipv6 unicast
  send-community
  send-community extended
address-family l2vpn evpn
  send-community
  send-community extended
neighbor 10.102.0.3
  remote-as 100
  update-source loopback0
  address-family ipv4 unicast
  address-family ipv6 unicast
    send-community
    send-community extended
  address-family l2vpn evpn
    send-community
    send-community extended
      vrf vrf_2
  address-family ipv4 unicast
    network 10.15.100.2/32
    network 192.168.100.0/24
neighbor 192.168.100.253
  remote-as 65111
  update-source loopback100
  ebgp-multipath 10
  address-family ipv4 unicast
evpn
  vni 4000100 12
    rd auto
    route-target import auto
    route-target export auto
  vni 4000200 12
    rd auto
    route-target import auto
    route-target export auto
  vni 4000301 12
    rd auto
    route-target import auto
    route-target export auto
  vni 4000302 12
    rd auto
    route-target import auto
    route-target export auto
  vni 4000303 12
    rd auto
    route-target import auto
    route-target export auto

```

Configuratie van locatie 1 blad-4

```

feature nxapi
cfs ipv4 distribute
nv overlay evpn
feature ospf
feature bgp
feature pim
feature fabric forwarding
feature interface-vlan
feature vn-segment-vlan-based

```

```
feature lacp
feature vpc
feature nv overlay
feature ngoam

fabric forwarding anycast-gateway-mac 0000.1111.2222

ip pim rp-address 10.102.0.2 group-list 224.0.0.0/4
ip pim ssm range 232.0.0.0/8

vlan 1,100,200,300-350,2001

vlan 100
  vn-segment 4000100
vlan 200
  vn-segment 4000200
vlan 301
  vn-segment 4000301
vlan 302
  vn-segment 4000302
vlan 303
  vn-segment 4000303
vlan 350
  name L3-VNI
  vn-segment 4000999
vlan 2001
  vn-segment 4000502

vrf context L3VNI4000999
  vni 4000999
  rd auto
  address-family ipv4 unicast
    route-target both auto
    route-target both auto evpn

vrf context vrf_1
  vni 4000501
  rd auto
  address-family ipv4 unicast
    route-target both auto
    route-target both auto evpn

vrf context vrf_2
  vni 4000502
  rd auto
  address-family ipv4 unicast
    route-target both auto
    route-target both auto evpn

vpc domain 100
  peer-switch
  peer-keepalive destination 10.197.214.55 source 10.197.214.56
  virtual peer-link destination 10.102.0.9 source 10.102.0.10 dscp 56
  delay restore 150
  peer-gateway
  layer3 peer-router
  ip arp synchronize

interface Vlan100
  no shutdown
  mtu 9216
```

```
vrf member vrf_2
no ip redirects
ip address 192.168.100.254/24
no ipv6 redirects
fabric forwarding mode anycast-gateway

interface Vlan200
no shutdown
mtu 9216
vrf member vrf_2
no ip redirects
ip address 192.168.200.254/24
no ipv6 redirects
fabric forwarding mode anycast-gateway

interface Vlan2001
no shutdown
mtu 9000
vrf member vrf_2
no ip redirects
ip forward
ipv6 address use-link-local-only
no ipv6 redirects

interface port-channel2
switchport
switchport mode trunk
switchport trunk allowed vlan 100,200
vpc 2

interface port-channel10
switchport
switchport mode trunk
switchport trunk allowed vlan 100,200,300-500,2001
spanning-tree port type network
vpc peer-link

interface nve1
no shutdown
host-reachability protocol bgp
advertise virtual-rmac
source-interface loopback1
member vni 4000100
  suppress-arp
  mcast-group 231.0.0.1
member vni 4000200
  suppress-arp
  mcast-group 231.0.0.2
member vni 4000502 associate-vrf

interface Ethernet1/1
switchport
switchport mode trunk
switchport trunk allowed vlan 200,300-305
mtu 9216
no shutdown

interface Ethernet1/2
mtu 9216
port-type fabric
medium p2p
ip address 192.168.20.12/24
```

```
ip ospf network point-to-point
ip router ospf 100 area 0.0.0.0
ip pim sparse-mode
no shutdown

interface Ethernet1/24
switchport
switchport mode trunk
switchport trunk allowed vlan 100,200
channel-group 2 mode active
no shutdown

interface loopback0
ip address 10.102.0.10/32
ip router ospf 100 area 0.0.0.0
ip pim sparse-mode

interface loopback1
ip address 10.102.1.6/32
ip address 10.202.202.202/32 secondary
ip router ospf 100 area 0.0.0.0
ip pim sparse-mode

interface loopback100
vrf member vrf_2
ip address 10.15.100.1/24

router ospf 100
router-id 10.102.0.10
router bgp 100
router-id 10.102.0.10
log-neighbor-changes
address-family ipv4 unicast
address-family ipv4 mvpn
address-family l2vpn evpn
advertise-pip
neighbor 10.102.0.2
remote-as 100
update-source loopback0
address-family ipv4 unicast
address-family ipv6 unicast
address-family ipv4 mvpn
send-community
send-community extended
address-family l2vpn evpn
send-community
send-community extended
neighbor 10.102.0.3
remote-as 100
update-source loopback0
address-family ipv4 unicast
address-family ipv6 unicast
address-family ipv4 mvpn
send-community
send-community extended
address-family l2vpn evpn
send-community
send-community extended
vrf vrf_2
address-family ipv4 unicast
network 10.15.100.1/32
network 192.168.100.0/24
```

```

neighbor 192.168.100.253
  remote-as 65111
  update-source loopback100
  ebgp-multipath 3
  address-family ipv4 unicast
evpn
  vni 4000100 12
    rd auto
    route-target import auto
    route-target export auto
  vni 4000200 12
    rd auto
    route-target import auto
    route-target export auto
  vni 4000301 12
    rd auto
    route-target import auto
    route-target export auto
  vni 4000302 12
    rd auto
    route-target import auto
    route-target export auto
  vni 4000303 12
    rd auto
    route-target import auto
    route-target export auto

```

Configuratie van locatie 1 spine-1

```

feature nxapi
nv overlay evpn
feature ospf
feature bgp
feature pim
feature interface-vlan
feature vn-segment-vlan-based
feature lacp

ip pim rp-address 10.102.0.2 group-list 224.0.0.0/4
ip pim ssm range 232.0.0.0/8

vlan 1

interface Ethernet1/1
  mtu 9216
  medium p2p
  ip address 192.168.17.11/24
  ip ospf network point-to-point
  ip router ospf 100 area 0.0.0.0
  ip pim sparse-mode
  no shutdown

interface Ethernet1/2
  mtu 9216
  medium p2p
  ip address 192.168.18.11/24
  ip ospf network point-to-point

```

```
ip router ospf 100 area 0.0.0.0
ip pim sparse-mode
no shutdown
```

```
interface Ethernet1/3
  mtu 9216
  port-type fabric
  medium p2p
  ip address 192.168.19.11/24
  ip ospf network point-to-point
  ip router ospf 100 area 0.0.0.0
  ip pim sparse-mode
  no shutdown
```

```
interface Ethernet1/4
  mtu 9216
  medium p2p
  ip address 192.168.20.11/24
  ip ospf network point-to-point
  ip router ospf 100 area 0.0.0.0
  ip pim sparse-mode
  no shutdown
```

```
interface Ethernet1/5
  mtu 9216
  medium p2p
  ip address 192.168.15.11/24
  ip ospf network point-to-point
  ip router ospf 100 area 0.0.0.0
  ip pim sparse-mode
  no shutdown
```

```
interface Ethernet1/6
  mtu 9216
  medium p2p
  ip address 192.168.16.11/24
  ip ospf network point-to-point
  ip router ospf 100 area 0.0.0.0
  ip pim sparse-mode
  no shutdown
```

```
interface loopback0
  description "anycast RP address"
  ip address 10.102.0.2/32
  ip router ospf 100 area 0.0.0.0
  ip pim sparse-mode
  icam monitor scale
```

```
router ospf 100
  router-id 10.102.0.2
  router bgp 100
    router-id 10.102.0.2
    log-neighbor-changes
    address-family ipv4 unicast
    address-family ipv6 unicast
    address-family l2vpn evpn
    neighbor 10.31.1.1
      remote-as 100
      update-source loopback0
      address-family ipv4 unicast
      address-family ipv6 unicast
      address-family ipv4 mvpn
```

```
send-community
send-community extended
route-reflector-client
address-family l2vpn evpn
  send-community
  send-community extended
  route-reflector-client
neighbor 10.31.1.2
  remote-as 100
  update-source loopback0
  address-family ipv4 unicast
  address-family ipv6 unicast
    send-community
    send-community extended
    route-reflector-client
  address-family l2vpn evpn
    send-community
    send-community extended
    route-reflector-client
neighbor 10.102.0.5
  remote-as 100
  update-source loopback0
  address-family ipv4 unicast
  address-family ipv6 unicast
    send-community
    send-community extended
    route-reflector-client
  address-family l2vpn evpn
    send-community
    send-community extended
    route-reflector-client
neighbor 10.102.0.8
  remote-as 100
  update-source loopback0
  address-family ipv4 unicast
  address-family ipv6 unicast
  address-family ipv4 mvpn
    send-community
    send-community extended
    route-reflector-client
  address-family l2vpn evpn
    send-community
    send-community extended
    route-reflector-client
neighbor 10.102.0.9
  remote-as 100
  update-source loopback0
  address-family ipv4 unicast
  address-family ipv6 unicast
    send-community
    send-community extended
    route-reflector-client
  address-family l2vpn evpn
    send-community
    send-community extended
    route-reflector-client
neighbor 10.102.0.10
  remote-as 100
  update-source loopback0
  address-family ipv4 unicast
  address-family ipv6 unicast
    send-community
```

```

    send-community extended
    route-reflector-client
  address-family l2vpn evpn
    send-community
    send-community extended
    route-reflector-client
neighbor 10.133.133.133
  remote-as 100
  update-source loopback0
  address-family ipv4 unicast
  address-family ipv6 unicast
    send-community
send-community extended
  route-reflector-client
  address-family l2vpn evpn
    send-community
    send-community extended
    route-reflector-client

```

Configuratie van site 1 border gateway-1

```

S1-Bg1# show run
cfs ipv4 distribute
nv overlay evpn
feature ospf
feature bgp
feature pim
feature fabric forwarding
feature interface-vlan
feature vn-segment-vlan-based
feature lacp
feature nv overlay
evpn multisite border-gateway 100
  delay-restore time 300

fabric forwarding anycast-gateway-mac 0000.1111.2222

ip pim rp-address 10.102.0.2 group-list 224.0.0.0/4
ip pim ssm range 232.0.0.0/8

vlan 1,100,200,300-350,2001

vlan 100
  vn-segment 4000100
vlan 200
  vn-segment 4000200
vlan 301
  vn-segment 4000301
vlan 302
  vn-segment 4000302
vlan 303
  vn-segment 4000303
vlan 350
  name L3-VNI
  vn-segment 4000999
vlan 2001
  vn-segment 4000502

```

```
route-map REDIST-TO-SITE-EXT-DCI permit 10
  match tag 54321
route-map RETAIN-NEXT-HOP permit 10
  set ip next-hop unchanged

vrf context L3VNI4000999
  vni 4000999
  rd auto
  address-family ipv4 unicast
    route-target both auto
    route-target both auto evpn

vrf context vrf_1
  vni 4000501
  rd auto
  address-family ipv4 unicast
    route-target both auto
    route-target both auto evpn

vrf context vrf_2
  vni 4000502
  rd auto
  address-family ipv4 unicast
    route-target both auto
    route-target both auto evpn

interface Vlan100
  no shutdown
  mtu 9216
  vrf member vrf_2
  no ip redirects
  ip address 192.168.100.254/24
  no ipv6 redirects
  fabric forwarding mode anycast-gateway

interface Vlan200
  no shutdown
  mtu 9216
  vrf member vrf_2
  no ip redirects
  ip address 192.168.200.254/24
  no ipv6 redirects
  fabric forwarding mode anycast-gateway

interface Vlan301
  no shutdown
  mtu 9216
  vrf member vrf_1
  no ip redirects
  ip address 172.16.11.254/24
  no ipv6 redirects
  fabric forwarding mode anycast-gateway

interface Vlan302
  no shutdown
  mtu 9216
  vrf member vrf_1
  no ip redirects
  ip address 172.16.12.254/24
  no ipv6 redirects
  fabric forwarding mode anycast-gateway
```

```
interface Vlan303
    no shutdown
    mtu 9216
    vrf member vrf_1
    no ip redirects
    ip address 172.16.13.254/24
    no ipv6 redirects
    fabric forwarding mode anycast-gateway

interface Vlan2001
    no shutdown
    mtu 9000
    vrf member vrf_2
    no ip redirects
    ip forward
    ipv6 address use-link-local-only
    no ipv6 redirects

interface nve1
    no shutdown
    host-reachability protocol bgp
    source-interface loopback1
    multisite border-gateway interface loopback100
    member vni 4000100
        suppress-arp
        multisite ingress-replication
        mcast-group 231.0.0.1
    member vni 4000200
        suppress-arp
        multisite ingress-replication
        mcast-group 231.0.0.2
    member vni 4000502 associate-vrf

interface Ethernet1/1
    mtu 9216
    port-type fabric
    medium p2p
    ip address 192.168.15.12/24
    ip ospf network point-to-point
    ip router ospf 100 area 0.0.0.0
    ip pim sparse-mode
    no shutdown
    evpn multisite fabric-tracking

interface Ethernet1/3
    mtu 9216
    ip address 10.150.150.1/24 tag 54321
    ip router ospf 100 area 0.0.0.0
    no shutdown
    evpn multisite dci-tracking

interface loopback0
    ip address 10.31.1.1/32 tag 54321
    ip router ospf 100 area 0.0.0.0
    ip pim sparse-mode

interface loopback1
    ip address 10.133.133.133/32 tag 54321
    ip router ospf 100 area 0.0.0.0
    ip pim sparse-mode

interface loopback100
```

```
description "Multi-site VIP"
ip address 10.100.100.1/32 tag 54321
ip router ospf 100 area 0.0.0.0
ip pim sparse-mode
icam monitor scale

router ospf 100
  router-id 10.31.1.1
router bgp 100
  router-id 10.31.1.1
  log-neighbor-changes
  address-family ipv4 unicast
    redistribute direct route-map REDIST-TO-SITE-EXT-DCI
  address-family ipv4 mvpn
  address-family l2vpn evpn
  neighbor 10.32.1.1
    remote-as 300
    update-source loopback0
    ebgp-multipath 5
    peer-type fabric-external
    address-family ipv4 mvpn
      send-community
      send-community extended
      rewrite-rt-asn
    address-family l2vpn evpn
      send-community
      send-community extended
      rewrite-evpn-rt-asn
  neighbor 10.102.0.2
    remote-as 100
    update-source loopback0
    address-family ipv4 unicast
    address-family ipv6 unicast
    address-family ipv4 mvpn
      send-community
      send-community extended
    address-family l2vpn evpn
      send-community
      send-community extended
  neighbor 10.150.150.2
    remote-as 300
    address-family ipv4 unicast
evpn
  vni 4000100 12
    rd auto
    route-target import auto
    route-target export auto
  vni 4000200 12
    rd auto
    route-target import auto
    route-target export auto
  vni 4000301 12
    rd auto
    route-target import auto
    route-target export auto
  vni 4000302 12
    rd auto
    route-target import auto
    route-target export auto
  vni 4000303 12
    rd auto
    route-target import auto
```

```
route-target export auto
```

Configuratie van site 1-border gateway 2

```
S1_B2#
cfs ipv4 distribute
nv overlay evpn
feature ospf
feature bgp
feature pim
feature fabric forwarding
feature interface-vlan
feature vn-segment-vlan-based
feature lacp
feature nv overlay
evpn multisite border-gateway 100
  delay-restore time 300

fabric forwarding anycast-gateway-mac 0000.2222.4444

ip pim rp-address 10.102.0.2 group-list 224.0.0.0/4
ip pim ssm range 232.0.0.0/8

vlan 1,100,200,300-350,2001
vlan 100
  vn-segment 4000100
vlan 200
  vn-segment 4000200
vlan 301
  vn-segment 4000301
vlan 302
  vn-segment 4000302
vlan 303
  vn-segment 4000303
vlan 350
  name L3-VNI
  vn-segment 4000999
vlan 2001
  vn-segment 4000502

route-map REDIST-TO-SITE-EXT-DCI permit 10
  match tag 54321
route-map RETAIN-NEXT-HOP permit 10
  set ip next-hop unchanged

vrf context L3VNI4000999
  vni 4000999
  rd auto
  address-family ipv4 unicast
    route-target both auto
    route-target both auto evpn

vrf context vrf_1
  vni 4000501
  rd auto
  address-family ipv4 unicast
    route-target both auto
    route-target both auto evpn
```

```
vrf context vrf_2
  vni 4000502
  rd auto
  address-family ipv4 unicast
    route-target both auto
    route-target both auto evpn

interface Vlan100
  no shutdown
  mtu 9216
  vrf member vrf_2
  no ip redirects
  ip address 192.168.100.254/24
  no ipv6 redirects
  fabric forwarding mode anycast-gateway

interface Vlan200
  no shutdown
  mtu 9216
  vrf member vrf_2
  no ip redirects
  ip address 192.168.200.254/24
  no ipv6 redirects
  fabric forwarding mode anycast-gateway

interface Vlan301
  no shutdown
  mtu 9216
  vrf member vrf_1
  no ip redirects
  ip address 172.16.11.254/24
  no ipv6 redirects
  fabric forwarding mode anycast-gateway

interface Vlan302
  no shutdown
  mtu 9216
  vrf member vrf_1
  no ip redirects
  ip address 172.16.12.254/24
  no ipv6 redirects
  fabric forwarding mode anycast-gateway

interface Vlan303
  no shutdown
  mtu 9216
  vrf member vrf_1
  no ip redirects
  ip address 172.16.13.254/24
  no ipv6 redirects
  fabric forwarding mode anycast-gateway

interface Vlan2001
  no shutdown
  mtu 9000
  vrf member vrf_2
  no ip redirects
  ip forward
  ipv6 address use-link-local-only
  no ipv6 redirects
```

```
interface nve1
    no shutdown
    host-reachability protocol bgp
    source-interface loopback1
    multisite border-gateway interface loopback100
    member vni 4000100
        suppress-arp
        multisite ingress-replication
        mcast-group 231.0.0.1
    member vni 4000200
        suppress-arp
        multisite ingress-replication
        mcast-group 231.0.0.2
    member vni 4000502 associate-vrf

interface Ethernet1/1
    mtu 9216
    port-type fabric
    medium p2p
    ip address 192.168.16.12/24
    ip ospf network point-to-point
    ip router ospf 100 area 0.0.0.0
    ip pim sparse-mode
    no shutdown
    evpn multisite fabric-tracking

interface Ethernet1/3
    mtu 9216
    ip address 10.150.151.1/24 tag 54321
    ip router ospf 100 area 0.0.0.0
    no shutdown
    evpn multisite dci-tracking

interface loopback0
    ip address 10.31.1.2/32 tag 54321
    ip router ospf 100 area 0.0.0.0
    ip pim sparse-mode

interface loopback1
    ip address 10.134.134.134/32 tag 54321
    ip router ospf 100 area 0.0.0.0
    ip pim sparse-mode

interface loopback100
    description "Multi-site VIP"
    ip address 10.100.100.1/32 tag 54321
    ip router ospf 100 area 0.0.0.0
    ip pim sparse-mode
    icam monitor scale

router ospf 100
    router-id 10.31.1.2
router bgp 100
    router-id 10.31.1.2
    log-neighbor-changes
    address-family ipv4 unicast
        redistribute direct route-map REDIST-TO-SITE-EXT-DCI
    address-family ipv4 mvpn
    address-family l2vpn evpn
    neighbor 10.32.1.1
        remote-as 300
        update-source loopback0
```

```

ebgp-multipath 5
peer-type fabric-external
address-family ipv4 mvpn
  send-community
  send-community extended
  rewrite-rt-asn
address-family l2vpn evpn
  send-community
  send-community extended
  rewrite-evpn-rt-asn
neighbor 10.102.0.2
  remote-as 100
  update-source loopback0
  address-family ipv4 unicast
  address-family ipv6 unicast
    send-community
    send-community extended
  address-family l2vpn evpn
    send-community
    send-community extended
neighbor 10.150.151.2
  remote-as 300
  address-family ipv4 unicast
evpn
vni 4000100 12
  rd auto
  route-target import auto
  route-target export auto
vni 4000200 12
  rd auto
  route-target import auto
  route-target export auto
vni 4000301 12
  rd auto
  route-target import auto
  route-target export auto
vni 4000302 12
  rd auto
  route-target import auto
  route-target export auto
vni 4000303 12
  rd auto
  route-target import auto
  route-target export auto
S1_B2#

```

Routerserver

```

Router_Server#
nv overlay evpn
feature ospf
feature bgp
feature pim
feature interface-vlan

vlan 1

route-map REDIST-TO-SITE-EXT-DCI permit 10

```

```
match tag 54321
route-map RETAIN-NEXT-HOP permit 10
  set ip next-hop unchanged

interface Ethernet2/1
  no switchport
  ip address 10.150.150.2/24
  no shutdown

interface Ethernet2/2
  no switchport
  ip address 10.150.151.2/24
  no shutdown

interface Ethernet2/4
  no switchport
  ip address 10.150.152.2/24
  no shutdown

interface Ethernet2/5
  no switchport
  mtu 9216
  ip address 10.150.153.2/24
  no shutdown

interface loopback0
  ip address 10.32.1.1/32 tag 54321

router bgp 300
  router-id 10.32.1.1
  address-family ipv4 unicast
    redistribute direct route-map REDIST-T0-SITE-EXT-DCI
    maximum-paths 2
    retain route-target all
  address-family l2vpn evpn
    retain route-target all
  neighbor 10.31.1.1
    remote-as 100
    update-source loopback0
    ebgp-multipath 5
    address-family ipv4 unicast
      send-community
      send-community extended
      route-map RETAIN-NEXT-HOP out
      rewrite-rt-asn
    address-family l2vpn evpn
      send-community
      send-community extended
      route-map RETAIN-NEXT-HOP out
      rewrite-evpn-rt-asn
  neighbor 10.31.1.2
    remote-as 100
    update-source loopback0
    ebgp-multipath 5
    address-family ipv4 unicast
      send-community
      send-community extended
      route-map RETAIN-NEXT-HOP out
      rewrite-rt-asn
    address-family l2vpn evpn
      send-community
```

```

    send-community extended
    route-map RETAIN-NEXT-HOP out
    rewrite-evpn-rt-asn
neighbor 10.31.1.3
    remote-as 200
    update-source loopback0
    ebgp-multipath 5
    address-family ipv4 unicast
        send-community
        send-community extended
        route-map RETAIN-NEXT-HOP out
        rewrite-rt-asn
    address-family l2vpn evpn
        send-community
        send-community extended
        route-map RETAIN-NEXT-HOP out
        rewrite-evpn-rt-asn
neighbor 10.31.1.4
    remote-as 200
    update-source loopback0
    ebgp-multipath 5
    address-family ipv4 unicast
    address-family ipv4 mvpn
        send-community
        send-community extended
        route-map RETAIN-NEXT-HOP out
        rewrite-rt-asn
    address-family l2vpn evpn
        send-community
        send-community extended
        route-map RETAIN-NEXT-HOP out
        rewrite-evpn-rt-asn
neighbor 10.150.150.1
    remote-as 100
    address-family ipv4 unicast
neighbor 10.150.151.1
    remote-as 100
    address-family ipv4 unicast
neighbor 10.150.152.1
    remote-as 200
    address-family ipv4 unicast
neighbor 10.150.153.1
    remote-as 200
    address-family ipv4 unicast
Router_Server#

```

Configuratie van site 2-border gateway 1

```

cfs ipv4 distribute
nv overlay evpn
feature ospf
feature bgp
feature pim
feature fabric forwarding
feature interface-vlan
feature vn-segment-vlan-based
feature lacp
feature nv overlay

```

```
evpn multisite border-gateway 200
fabric forwarding anycast-gateway-mac 0000.2222.4444
ip pim rp-address 10.103.0.3 group-list 224.0.0.0/4
ip pim ssm range 232.0.0.0/8

vlan 1,100,200,300-350,2000-2001
vlan 100
  vn-segment 4000100
vlan 200
  vn-segment 4000200
vlan 301
  vn-segment 4000301
vlan 302
  vn-segment 4000302
vlan 303
  vn-segment 4000303
vlan 350
  name L3-VNI
  vn-segment 4000999
vlan 2000
  vn-segment 2000
vlan 2001
  vn-segment 4000502

route-map REDIST-TO-SITE-EXT-DCI permit 10
  match tag 54321
route-map RETAIN-NEXT-HOP permit 10
  set ip next-hop unchanged

vrf context L3VNI4000999
  vni 4000999
  rd auto
  address-family ipv4 unicast
    route-target both auto
    route-target both auto evpn

vrf context vrf_1
  vni 4000501
  rd auto
  address-family ipv4 unicast
    route-target both auto
    route-target both auto evpn

vrf context vrf_2
  vni 4000502
  rd auto
  address-family ipv4 unicast
    route-target both auto
    route-target both auto evpn

interface Vlan100
  no shutdown
  mtu 9216
  vrf member vrf_2
  no ip redirects
  ip address 192.168.100.254/24
  no ipv6 redirects
  fabric forwarding mode anycast-gateway

interface Vlan200
```

```
no shutdown
mtu 9216
vrf member vrf_2
no ip redirects
ip address 192.168.200.254/24
no ipv6 redirects
fabric forwarding mode anycast-gateway

interface Vlan301
no shutdown
mtu 9216
vrf member vrf_1
no ip redirects
ip address 172.16.11.254/24
no ipv6 redirects
fabric forwarding mode anycast-gateway

interface Vlan302
no shutdown
mtu 9216
vrf member vrf_1
no ip redirects
ip address 172.16.12.254/24
no ipv6 redirects
fabric forwarding mode anycast-gateway

interface Vlan303
no shutdown
mtu 9216
vrf member vrf_1
no ip redirects
ip address 172.16.13.254/24
no ipv6 redirects
fabric forwarding mode anycast-gateway

interface Vlan2001
no shutdown
mtu 9000
vrf member vrf_2
no ip redirects
ip forward
ipv6 address use-link-local-only
no ipv6 redirects

interface nve1
no shutdown
host-reachability protocol bgp
source-interface loopback1
multisite border-gateway interface loopback100
member vni 4000100
    suppress-arp
    mcast-group 231.0.0.1
member vni 4000200
    suppress-arp
    mcast-group 231.0.0.2
member vni 4000502 associate-vrf

interface Ethernet1/1
mtu 9216
port-type fabric
medium p2p
ip address 192.168.17.12/24
```

```
ip ospf network point-to-point
ip router ospf 200 area 0.0.0.0
ip pim sparse-mode
no shutdown
evpn multisite fabric-tracking

interface Ethernet1/3
mtu 9216
ip address 10.150.152.1/24 tag 54321
ip router ospf 200 area 0.0.0.0
no shutdown
evpn multisite dci-tracking

interface loopback0
ip address 10.31.1.3/32 tag 54321
ip router ospf 200 area 0.0.0.0
ip pim sparse-mode

interface loopback1
ip address 10.135.135.135/32 tag 54321
ip router ospf 200 area 0.0.0.0
ip pim sparse-mode

interface loopback100
description "Multi-site VIP"
ip address 10.100.100.2/32 tag 54321
ip router ospf 200 area 0.0.0.0
ip pim sparse-mode
icam monitor scale

router ospf 200
router bgp 200
  router-id 10.31.1.3
  log-neighbor-changes
  address-family ipv4 unicast
    redistribute direct route-map REDIST-T0-SITE-EXT-DCI
  address-family l2vpn evpn
  neighbor 10.32.1.1
    remote-as 300
    update-source loopback0
    ebgp-multipath 5
    peer-type fabric-external
      send-community
      send-community extended
      rewrite-rt-asn
    address-family l2vpn evpn
      send-community
      send-community extended
      rewrite-evpn-rt-asn
  neighbor 10.103.0.3
    remote-as 200
    update-source loopback0
    address-family ipv4 unicast
    address-family ipv6 unicast
      send-community
      send-community extended
    address-family l2vpn evpn
      send-community
      send-community extended
  neighbor 10.150.152.2
    remote-as 300
    address-family ipv4 unicast
```

```

evpn
  vni 4000100 12
    rd auto
    route-target import auto
    route-target export auto
  vni 4000200 12
    rd auto
    route-target import auto
    route-target export auto
  vni 4000301 12
    rd auto
    route-target import auto
    route-target export auto
  vni 4000302 12
    rd auto
    route-target import auto
    route-target export auto
  vni 4000303 12
    rd auto
    route-target import auto
    route-target export auto

```

Configuratie van site 2-border gateway 2

```

S2-BG2#
cfs ipv4 distribute
feature ngmvpn
nv overlay evpn
feature ospf
feature bgp
feature pim
feature fabric forwarding
feature interface-vlan
feature vn-segment-vlan-based
feature lacp
feature lldp
feature bfd
feature nv overlay
evpn multisite border-gateway 200
  delay-restore time 300

fabric forwarding anycast-gateway-mac 0000.2222.4444
ip pim rp-address 10.103.0.3 group-list 224.0.0.0/4
ip pim ssm range 232.0.0.0/8

vlan 1,100,200,301-303,350,2000-2001
vlan 100
  vn-segment 4000100
vlan 200
  vn-segment 4000200
vlan 301
  vn-segment 4000301
vlan 302
  vn-segment 4000302
vlan 303
  vn-segment 4000303
vlan 350
  name L3-VNI

```

```

vn-segment 4000999
vlan 2000
  vn-segment 2000
vlan 2001
  vn-segment 4000502

route-map REDIST-TO-SITE-EXT-DCI permit 10
  match tag 54321
route-map RETAIN-NEXT-HOP permit 10
  set ip next-hop unchanged

vrf context L3VNI4000999
  vni 4000999
  rd auto
  address-family ipv4 unicast
    route-target both auto
    route-target both auto evpn

vrf context vrf_1
  vni 4000501
  rd auto
  address-family ipv4 unicast
    route-target both auto
    route-target both auto evpn

vrf context vrf_2
  vni 4000502
  rd auto
  address-family ipv4 unicast
    route-target both auto
    route-target both auto evpn

```

```

interface Vlan100
  no shutdown
  mtu 9216
  vrf member vrf_2
  no ip redirects
  ip address 192.168.100.254/24
  no ipv6 redirects
  fabric forwarding mode anycast-gateway

interface Vlan200
  no shutdown
  mtu 9216
  vrf member vrf_2
  no ip redirects
  ip address 192.168.200.254/24
  no ipv6 redirects
  fabric forwarding mode anycast-gateway

interface Vlan301
  no shutdown
  mtu 9216
  vrf member vrf_1
  no ip redirects
  ip address 172.16.11.254/24
  no ipv6 redirects
  fabric forwarding mode anycast-gateway

```

```
interface Vlan302
  no shutdown
  mtu 9216
  vrf member vrf_1
  no ip redirects
  ip address 172.16.12.254/24
  no ipv6 redirects
  fabric forwarding mode anycast-gateway

interface Vlan303
  no shutdown
  mtu 9216
  vrf member vrf_1
  no ip redirects
  ip address 172.16.13.254/24
  no ipv6 redirects
  fabric forwarding mode anycast-gateway

interface Vlan2001
  no shutdown
  mtu 9000
  vrf member vrf_2
  no ip redirects
  ip forward
  ipv6 address use-link-local-only
  no ipv6 redirects

interface nve1
  no shutdown
  host-reachability protocol bgp
  source-interface loopback1
  multisite border-gateway interface loopback100
  member vni 4000100
    suppress-arp
    multisite ingress-replication
    mcast-group 231.0.0.1
  member vni 4000200
    suppress-arp
    multisite ingress-replication
    mcast-group 231.0.0.2
  member vni 4000502 associate-vrf

interface Ethernet1/1
  mtu 9216
  port-type fabric
  medium p2p
  ip address 192.168.18.12/24
  ip ospf network point-to-point
  ip router ospf 200 area 0.0.0.0
  ip pim sparse-mode
  no shutdown
  evpn multisite fabric-tracking

interface Ethernet1/3
  mtu 9216
  ip address 10.150.153.1/24 tag 54321
  ip router ospf 200 area 0.0.0.0
  no shutdown
  evpn multisite dci-tracking

interface loopback0
```

```
ip address 10.31.1.4/32 tag 54321
ip router ospf 200 area 0.0.0.0
ip pim sparse-mode

interface loopback1
    ip address 10.136.136.136/32 tag 54321
    ip router ospf 200 area 0.0.0.0
    ip pim sparse-mode

interface loopback100
    description "Multi-site VIP"
    ip address 10.100.100.2/32 tag 54321
    ip router ospf 200 area 0.0.0.0
    ip pim sparse-mode
    icam monitor scale

router ospf 200
router bgp 200
    router-id 10.31.1.4
    log-neighbor-changes
    address-family ipv4 unicast
        redistribute direct route-map REDIST-T0-SITE-EXT-DCI
    address-family l2vpn evpn
    neighbor 10.32.1.1
        remote-as 300
        update-source loopback0
        ebgp-multipath 5
        peer-type fabric-external
            send-community
            send-community extended
            rewrite-rt-asn
        address-family l2vpn evpn
            send-community
            send-community extended
            rewrite-evpn-rt-asn
    neighbor 10.103.0.3
        remote-as 200
        update-source loopback0
        address-family ipv4 unicast
        address-family ipv6 unicast
            send-community
            send-community extended
        address-family l2vpn evpn
            send-community
            send-community extended
    neighbor 10.150.153.2
        remote-as 300
        address-family ipv4 unicast
evpn
    vni 4000100 12
        rd auto
        route-target import auto
        route-target export auto
    vni 4000200 12
        rd auto
        route-target import auto
        route-target export auto
    vni 4000301 12
        rd auto
        route-target import auto
        route-target export auto
    vni 4000302 12
```

```
rd auto
route-target import auto
route-target export auto
vni 4000303 l2
rd auto
route-target import auto
route-target export auto
S2-BG2#
```

Configuratie van site 2 in ruggengraat 1

```
S2-Spine1#
feature nxapi
cfs ipv4 distribute
cfs eth distribute
nv overlay evpn
feature ospf
feature bgp
feature pim
feature fabric forwarding
feature interface-vlan
feature vn-segment-vlan-based
feature lacp
feature vpc
feature ngoam

ip pim rp-address 10.103.0.3 group-list 224.0.0.0/4
ip pim ssm range 232.0.0.0/8

interface Ethernet1/1
  mtu 9216
  medium p2p
  ip address 192.168.0.11/24
  ip ospf network point-to-point
  ip router ospf 200 area 0.0.0.0
  ip pim sparse-mode
  no shutdown

interface Ethernet1/2
  mtu 9216
  medium p2p
  ip address 192.168.1.11/24
  ip ospf network point-to-point
  ip router ospf 200 area 0.0.0.0
  ip pim sparse-mode
  no shutdown

interface Ethernet1/3
  mtu 9216
  medium p2p
  ip address 192.168.2.11/24
  ip ospf network point-to-point
  ip router ospf 200 area 0.0.0.0
  ip pim sparse-mode
  no shutdown

interface Ethernet1/4
  mtu 9216
```

```
medium p2p
ip address 192.168.3.11/24
ip ospf network point-to-point
ip router ospf 200 area 0.0.0.0
ip pim sparse-mode
no shutdown

interface Ethernet1/5
  mtu 9216
  medium p2p
  ip address 192.168.17.11/24
  ip ospf network point-to-point
  ip router ospf 200 area 0.0.0.0
  ip pim sparse-mode
  no shutdown

interface Ethernet1/6
  mtu 9216
  medium p2p
  ip address 192.168.18.11/24
  ip ospf network point-to-point
  ip router ospf 200 area 0.0.0.0
  ip pim sparse-mode
  no shutdown

interface loopback0
  description "anycast RP address"
  ip address 10.103.0.3/32
  ip router ospf 200 area 0.0.0.0
  ip pim sparse-mode
  icam monitor scale

router ospf 200
  router-id 10.202.0.3
router bgp 200
  router-id 10.103.0.3
  log-neighbor-changes
  address-family ipv4 unicast
  address-family ipv6 unicast
  address-family ipv4 mvpn
  address-family l2vpn evpn
  neighbor 10.31.1.3
    remote-as 200
    update-source loopback0
    address-family ipv4 unicast
    address-family ipv6 unicast
      send-community
      send-community extended
    address-family l2vpn evpn
      send-community
      send-community extended
  neighbor 10.31.1.4
    remote-as 200
    update-source loopback0
    address-family ipv4 unicast
    address-family ipv6 unicast
      send-community
      send-community extended
    address-family l2vpn evpn
      send-community
      send-community extended
  neighbor 10.103.0.5
```

```

remote-as 200
update-source loopback0
address-family ipv4 unicast
address-family ipv6 unicast
  send-community
  send-community extended
  route-reflector-client
address-family l2vpn evpn
  send-community
  send-community extended
  route-reflector-client
neighbor 10.103.0.8
  remote-as 200
  update-source loopback0
  address-family ipv4 unicast
  address-family ipv6 unicast
    send-community
    send-community extended
    route-reflector-client
  address-family l2vpn evpn
    send-community
    send-community extended
    route-reflector-client
neighbor 10.103.0.9
  remote-as 200
  update-source loopback0
  address-family ipv4 unicast
  address-family ipv6 unicast
  address-family ipv4 mvpn
    send-community
    send-community extended
    route-reflector-client
  address-family l2vpn evpn
    send-community
    send-community extended
    route-reflector-client
neighbor 10.103.0.10
  remote-as 200
  update-source loopback0
  address-family ipv4 unicast
  address-family ipv6 unicast
  address-family ipv4 mvpn
    send-community
    send-community extended
    route-reflector-client
  address-family l2vpn evpn
    send-community
    send-community extended
    route-reflector-client

```

S2-Spine1#

Configuratie site 2-blad-1

```

feature nxapi
cfs ipv4 distribute
nv overlay evpn
feature ospf
feature bgp

```

```
feature pim
feature fabric forwarding
feature interface-vlan
feature vn-segment-vlan-based
feature lacp
feature vpc
feature nv overlay

fabric forwarding anycast-gateway-mac 0000.1111.2222
ip pim rp-address 10.103.0.3 group-list 224.0.0.0/4
ip pim ssm range 232.0.0.0/8

vlan 1,100,200,300-350,2001
vlan 100
    vn-segment 4000100
vlan 200
    vn-segment 4000200
vlan 301
    vn-segment 4000301
vlan 302
    vn-segment 4000302
vlan 303
    vn-segment 4000303
vlan 350
    name L3-VNI
    vn-segment 4000999
vlan 2001
    vn-segment 4000502

route-map DIRECT permit 10
    match tag 12345
route-map DIRECT deny 90
vrf context L3VNI4000999
    vni 4000999
    rd auto
    address-family ipv4 unicast
        route-target both auto
        route-target both auto evpn

vrf context vrf_1
    vni 4000501
    rd auto
    address-family ipv4 unicast
        route-target both auto
        route-target both auto evpn

vrf context vrf_2
    vni 4000502
    rd auto
    address-family ipv4 unicast
        route-target both auto
        route-target both auto evpn

vpc domain 100
    peer-switch
    peer-keepalive destination 10.197.214.63
    virtual peer-link destination 10.103.1.9 source 10.103.1.8 dscp 56
    delay restore 150
    peer-gateway
        ip arp synchronize
```

```
interface Vlan100
    no shutdown
    mtu 9216
    vrf member vrf_2
    no ip redirects
    ip address 192.168.100.254/24
    no ipv6 redirects
    fabric forwarding mode anycast-gateway

interface Vlan200
    no shutdown
    mtu 9216
    vrf member vrf_2
    no ip redirects
    ip address 192.168.200.254/24
    no ipv6 redirects
    fabric forwarding mode anycast-gateway

interface Vlan301
    no shutdown
    mtu 9216
    vrf member vrf_1
    no ip redirects
    ip address 172.16.11.254/24
    no ipv6 redirects
    fabric forwarding mode anycast-gateway

interface Vlan302
    no shutdown
    mtu 9216
    vrf member vrf_1
    no ip redirects
    ip address 172.16.12.254/24
    no ipv6 redirects
    fabric forwarding mode anycast-gateway

interface Vlan303
    no shutdown
    mtu 9216
    vrf member vrf_1
    no ip redirects
    ip address 172.16.13.254/24
    no ipv6 redirects
    fabric forwarding mode anycast-gateway

interface Vlan2001
    no shutdown
    mtu 9000
    vrf member vrf_2
    no ip redirects
    ip forward
    ipv6 address use-link-local-only
    no ipv6 redirects

interface port-channel10
    switchport
    switchport mode trunk
    switchport trunk allowed vlan 100,200,300-500
    spanning-tree port type network
```

```
vpc peer-link

interface port-channel100
switchport
switchport mode trunk
switchport trunk allowed vlan 100,200,300-305
mtu 9216
vpc 100

interface nve1
no shutdown
host-reachability protocol bgp
advertise virtual-rmac
source-interface loopback1
member vni 4000100
    suppress-arp
    mcast-group 231.0.0.1
member vni 4000200
    suppress-arp
    mcast-group 231.0.0.2
member vni 4000502 associate-vrf

interface Ethernet1/1
switchport
switchport mode trunk
switchport trunk allowed vlan 100,200,300-305
mtu 9216
channel-group 100
no shutdown

interface Ethernet1/2
mtu 9216
port-type fabric
medium p2p
ip address 192.168.0.12/24
ip ospf network point-to-point
ip router ospf 100 area 0.0.0.0
ip pim sparse-mode
no shutdown

interface loopback0
ip address 10.103.0.5/32
ip router ospf 100 area 0.0.0.0
ip pim sparse-mode

interface loopback1
ip address 10.103.1.8/32
ip address 10.103.201.201/32 secondary
ip router ospf 100 area 0.0.0.0
ip pim sparse-mode
icam monitor scale

router ospf 100
router-id 10.102.0.5
router bgp 200
router-id 10.103.0.5
log-neighbor-changes
address-family ipv4 mvpn
address-family l2vpn evpn
    advertise-pip
neighbor 10.103.0.2
    remote-as 200
```

```

update-source loopback0
address-family ipv4 unicast
address-family ipv6 unicast
  send-community
  send-community extended
address-family l2vpn evpn
  send-community
  send-community extended
neighbor 10.103.0.3
  remote-as 200
update-source loopback0
address-family ipv4 unicast
address-family ipv6 unicast
  send-community
  send-community extended
address-family l2vpn evpn
  send-community
  send-community extended
evpn
vni 4000100 12
  rd auto
  route-target import auto
  route-target export auto
vni 4000200 12
  rd auto
  route-target import auto
  route-target export auto
vni 4000301 12
  rd auto
  route-target import auto
  route-target export auto
vni 4000302 12
  rd auto
  route-target import auto
  route-target export auto
vni 4000303 12
  rd auto
  route-target import auto
  route-target export auto

```

Configuratie Site 2 Leaf-2

```

S2-Leaf2#
feature nxapi
cfs ipv4 distribute
nv overlay evpn
feature ospf
feature bgp
feature pim
feature fabric forwarding
feature interface-vlan
feature vn-segment-vlan-based
feature lacp
feature vpc
feature nv overlay

fabric forwarding anycast-gateway-mac 0000.1111.2222
ip pim rp-address 10.103.0.3 group-list 224.0.0.0/4

```

```

ip pim ssm range 232.0.0.0/8

vlan 1,100,200,300-350,2001
vlan 100
  vn-segment 4000100
vlan 200
  vn-segment 4000200
vlan 301
  vn-segment 4000301
vlan 302
  vn-segment 4000302
vlan 303
  vn-segment 4000303
vlan 350
  name L3-VNI
  vn-segment 4000999
vlan 2001
  vn-segment 4000502

vrf context L3VNI4000999
  vni 4000999
  rd auto
  address-family ipv4 unicast
    route-target both auto
    route-target both auto evpn

vrf context vrf_1
  vni 4000501
  rd auto
  address-family ipv4 unicast
    route-target both auto
    route-target both auto evpn

vrf context vrf_2
  vni 4000502
  rd auto
  address-family ipv4 unicast
    route-target both auto
    route-target both auto evpn

vpc domain 100
  peer-switch
  peer-keepalive destination 10.197.214.62
  virtual peer-link destination 10.103.1.8 source 10.103.1.9 dscp 56
  delay restore 150
  peer-gateway
  ip arp synchronize

interface Vlan100
  no shutdown
  mtu 9216
  vrf member vrf_2
  no ip redirects
  ip address 192.168.100.254/24
  no ipv6 redirects
  fabric forwarding mode anycast-gateway

interface Vlan200

```

```
no shutdown
mtu 9216
vrf member vrf_2
no ip redirects
ip address 192.168.200.254/24
no ipv6 redirects
fabric forwarding mode anycast-gateway

interface Vlan301
no shutdown
mtu 9216
vrf member vrf_1
no ip redirects
ip address 172.16.11.254/24
no ipv6 redirects
fabric forwarding mode anycast-gateway

interface Vlan302
no shutdown
mtu 9216
vrf member vrf_1
no ip redirects
ip address 172.16.12.254/24
no ipv6 redirects
fabric forwarding mode anycast-gateway

interface Vlan303
no shutdown
mtu 9216
vrf member vrf_1
no ip redirects
ip address 172.16.13.254/24
no ipv6 redirects
fabric forwarding mode anycast-gateway

interface Vlan2001
no shutdown
mtu 9000
vrf member vrf_2
no ip redirects
ip forward
ipv6 address use-link-local-only
no ipv6 redirects

interface port-channel10
switchport
switchport mode trunk
switchport trunk allowed vlan 100,200,300-500
spanning-tree port type network
vpc peer-link

interface port-channel100
switchport
switchport mode trunk
switchport trunk allowed vlan 100,200,300-305
mtu 9216
vpc 100

interface nve1
no shutdown
host-reachability protocol bgp
advertise virtual-rmac
```

```
source-interface loopback1
member vni 4000100
  suppress-arp
  mcast-group 231.0.0.1
member vni 4000200
  suppress-arp
  mcast-group 231.0.0.2
member vni 4000502 associate-vrf

interface Ethernet1/1
switchport
switchport mode trunk
switchport trunk allowed vlan 100,200,300-305
mtu 9216
channel-group 100
no shutdown

interface Ethernet1/2
mtu 9216
port-type fabric
medium p2p
ip address 192.168.1.12/24
ip ospf network point-to-point
ip router ospf 100 area 0.0.0.0
ip pim sparse-mode
no shutdown

interface loopback0
ip address 10.103.0.8/32
ip router ospf 100 area 0.0.0.0
ip pim sparse-mode

interface loopback1
ip address 10.103.1.9/32
ip address 10.103.201.201/32 secondary
ip router ospf 100 area 0.0.0.0
ip pim sparse-mode
icam monitor scale

router ospf 100
  router-id 10.102.0.8
router bgp 200
  router-id 10.103.0.8
  log-neighbor-changes
  address-family l2vpn evpn
    advertise-pip
  neighbor 10.103.0.2
    remote-as 200
    update-source loopback0
    address-family ipv4 unicast
    address-family ipv6 unicast
      send-community
      send-community extended
    address-family l2vpn evpn
      send-community
      send-community extended
  neighbor 10.103.0.3
    remote-as 200
    update-source loopback0
    address-family ipv4 unicast
    address-family ipv6 unicast
    address-family ipv4 mvpn
```

```

    send-community
    send-community extended
  address-family l2vpn evpn
    send-community
    send-community extended
evpn
  vni 4000100 12
    rd auto
    route-target import auto
    route-target export auto
  vni 4000200 12
    rd auto
    route-target import auto
    route-target export auto
  vni 4000301 12
    rd auto
    route-target import auto
    route-target export auto
  vni 4000302 12
    rd auto
    route-target import auto
    route-target export auto
  vni 4000303 12
    rd auto
    route-target import auto
    route-target export auto
S2-Leaf2#

```

Configuratie Site 2 Leaf-3

```

S2-leaf3#
feature nxapi
cfs ipv4 distribute
nv overlay evpn
feature ospf
feature bgp
feature pim
feature fabric forwarding
feature interface-vlan
feature vn-segment-vlan-based
feature lacp
feature vpc
feature nv overlay

fabric forwarding anycast-gateway-mac 0000.1111.2222
ip pim rp-address 10.103.0.3 group-list 224.0.0.0/4
ip pim ssm range 232.0.0.0/8

vlan 1,100,200,300-350,2001
vlan 100
  vn-segment 4000100
vlan 200
  vn-segment 4000200
vlan 301
  vn-segment 4000301
vlan 302
  vn-segment 4000302
vlan 303

```

```

vn-segment 4000303
vlan 350
  name L3-VNI
  vn-segment 4000999
vlan 2001
  vn-segment 4000502

vrf context L3VNI4000999
  vni 4000999
  rd auto
  address-family ipv4 unicast
    route-target both auto
    route-target both auto evpn

vrf context vrf_1
  vni 4000501
  rd auto
  address-family ipv4 unicast
    route-target both auto
    route-target both auto evpn

vrf context vrf_2
  vni 4000502
  rd auto
  address-family ipv4 unicast
    route-target both auto
    route-target both auto evpn

vpc domain 100
  peer-switch
  peer-keepalive destination 10.197.214.65
  virtual peer-link destination 10.103.1.6 source 10.103.1.10 dscp 56
  delay restore 150
  peer-gateway
  ip arp synchronize

```

```

interface Vlan100
  no shutdown
  mtu 9216
  vrf member vrf_2
  no ip redirects
  ip address 192.168.100.254/24
  no ipv6 redirects
  fabric forwarding mode anycast-gateway

```

```

interface Vlan200
  no shutdown
  mtu 9216
  vrf member vrf_2
  no ip redirects
  ip address 192.168.200.254/24
  no ipv6 redirects
  fabric forwarding mode anycast-gateway

```

```

interface Vlan301
  no shutdown
  mtu 9216
  vrf member vrf_1

```

```
no ip redirects
ip address 172.16.11.254/24
no ipv6 redirects
fabric forwarding mode anycast-gateway

interface Vlan302
no shutdown
mtu 9216
vrf member vrf_1
no ip redirects
ip address 172.16.12.254/24
no ipv6 redirects
fabric forwarding mode anycast-gateway

interface Vlan303
no shutdown
mtu 9216
vrf member vrf_1
no ip redirects
ip address 172.16.13.254/24
no ipv6 redirects
fabric forwarding mode anycast-gateway

interface Vlan2001
no shutdown
mtu 9000
vrf member vrf_2
no ip redirects
ip forward
ipv6 address use-link-local-only
no ipv6 redirects

interface port-channel10
switchport
switchport mode trunk
switchport trunk allowed vlan 100,200,300-500
spanning-tree port type network
vpc peer-link

interface port-channel100
switchport
switchport mode trunk
switchport trunk allowed vlan 100,200,300-305
mtu 9216
vpc 100

interface nve1
no shutdown
host-reachability protocol bgp
advertise virtual-rmac
source-interface loopback1
member vni 4000100
suppress-arp
mcast-group 231.0.0.1
member vni 4000200
suppress-arp
mcast-group 231.0.0.2
member vni 4000502 associate-vrf

interface Ethernet1/2
mtu 9216
port-type fabric
```

```
medium p2p
ip address 192.168.2.12/24
ip ospf network point-to-point
ip router ospf 100 area 0.0.0.0
ip pim sparse-mode
no shutdown

interface Ethernet1/23
switchport
switchport mode trunk
switchport trunk allowed vlan 100,200,300-305
mtu 9216
channel-group 100
no shutdown

interface Ethernet1/24
switchport
switchport mode trunk
switchport trunk allowed vlan 100,200,300-305
mtu 9216
channel-group 100
no shutdown

interface loopback0
ip address 10.103.0.9/32
ip router ospf 100 area 0.0.0.0
ip pim sparse-mode

interface loopback1
ip address 10.103.1.10/32
ip address 10.103.202.202/32 secondary
ip router ospf 100 area 0.0.0.0
ip pim sparse-mode
icam monitor scale

router ospf 100
router-id 10.102.0.9
router bgp 200
router-id 10.103.0.9
log-neighbor-changes
address-family ipv4 mvpn
address-family l2vpn evpn
advertise-pip
neighbor 10.103.0.2
remote-as 200
update-source loopback0
address-family ipv4 unicast
address-family ipv6 unicast
address-family ipv4 mvpn
send-community
send-community extended
address-family l2vpn evpn
send-community
send-community extended
neighbor 10.103.0.3
remote-as 200
update-source loopback0
address-family ipv4 unicast
address-family ipv6 unicast
send-community
send-community extended
address-family l2vpn evpn
```

```

    send-community
    send-community extended
evpn
vni 4000100 12
    rd auto
    route-target import auto
    route-target export auto
vni 4000200 12
    rd auto
    route-target import auto
    route-target export auto
vni 4000301 12
    rd auto
    route-target import auto
    route-target export auto
vni 4000302 12
    rd auto
    route-target import auto
    route-target export auto
vni 4000303 12
    rd auto
    route-target import auto
    route-target export auto

```

Configuratie Site 2 Leaf-4

```

S2-Leaf4#
feature nxapi
cfs ipv4 distribute
nv overlay evpn
feature ospf
feature bgp
feature pim
feature fabric forwarding
feature interface-vlan
feature vn-segment-vlan-based
feature lacp
feature vpc
feature nv overlay

fabric forwarding anycast-gateway-mac 0000.1111.2222
ip pim rp-address 10.103.0.3 group-list 224.0.0.0/4
ip pim ssm range 232.0.0.0/8

vlan 1,100,200,300-350,2001
vlan 100
    vn-segment 4000100
vlan 200
    vn-segment 4000200
vlan 301
    vn-segment 4000301
vlan 302
    vn-segment 4000302
vlan 303
    vn-segment 4000303
vlan 350
    name L3-VNI
    vn-segment 4000999

```

```

vlan 2001
  vn-segment 4000502

vrf context L3VNI4000999
  vni 4000999
  rd auto
  address-family ipv4 unicast
    route-target both auto
    route-target both auto evpn

vrf context vrf_1
  vni 4000501
  rd auto
  address-family ipv4 unicast
    route-target both auto
    route-target both auto evpn

vrf context vrf_2
  vni 4000502
  rd auto
  address-family ipv4 unicast
    route-target both auto
    route-target both auto evpn

vpc domain 100
  peer-switch
  peer-keepalive destination 10.197.214.64
  virtual peer-link destination 10.103.1.10 source 10.103.1.6 dscp 56
  delay restore 150
  peer-gateway
  ip arp synchronize

```

```

interface Vlan100
  no shutdown
  mtu 9216
  vrf member vrf_2
  no ip redirects
  ip address 192.168.100.254/24
  no ipv6 redirects
  fabric forwarding mode anycast-gateway

```

```

interface Vlan200
  no shutdown
  mtu 9216
  vrf member vrf_2
  no ip redirects
  ip address 192.168.200.254/24
  no ipv6 redirects
  fabric forwarding mode anycast-gateway

```

```

interface Vlan301
  no shutdown
  mtu 9216
  vrf member vrf_1
  no ip redirects
  ip address 172.16.11.254/24
  no ipv6 redirects
  fabric forwarding mode anycast-gateway

```

```
interface Vlan302
    no shutdown
    mtu 9216
    vrf member vrf_1
    no ip redirects
    ip address 172.16.12.254/24
    no ipv6 redirects
    fabric forwarding mode anycast-gateway

interface Vlan303
    no shutdown
    mtu 9216
    vrf member vrf_1
    no ip redirects
    ip address 172.16.13.254/24
    no ipv6 redirects
    fabric forwarding mode anycast-gateway

interface Vlan2001
    no shutdown
    mtu 9000
    vrf member vrf_2
    no ip redirects
    ip forward
    ipv6 address use-link-local-only
    no ipv6 redirects

interface port-channel10
    switchport
    switchport mode trunk
    switchport trunk allowed vlan 100,200,300-500
    spanning-tree port type network
    vpc peer-link

interface port-channel100
    switchport
    switchport mode trunk
    switchport trunk allowed vlan 100,200,300-305
    mtu 9216
    vpc 100

interface nve1
    no shutdown
    host-reachability protocol bgp
    advertise virtual-rmac
    source-interface loopback1
    member vni 4000100
        suppress-arp
        mcast-group 231.0.0.1
    member vni 4000200
        suppress-arp
        mcast-group 231.0.0.2
    member vni 4000502 associate-vrf

interface Ethernet1/2
    mtu 9216
    port-type fabric
    medium p2p
    ip address 192.168.3.12/24
    ip ospf network point-to-point
    ip router ospf 100 area 0.0.0.0
```

```
ip pim sparse-mode
no shutdown

interface Ethernet1/23
switchport
switchport mode trunk
switchport trunk allowed vlan 100,200,300-305
mtu 9216
channel-group 100
no shutdown

interface Ethernet1/24
switchport
switchport mode trunk
switchport trunk allowed vlan 100,200,300-305
mtu 9216
channel-group 100
no shutdown

interface loopback0
ip address 10.103.0.10/32
ip router ospf 100 area 0.0.0.0
ip pim sparse-mode

interface loopback1
ip address 10.103.1.6/32
ip address 10.103.202.202/32 secondary
ip router ospf 100 area 0.0.0.0
ip pim sparse-mode
icam monitor scale

router ospf 100
router-id 10.102.0.10
router bgp 200
router-id 10.102.0.10
log-neighbor-changes
address-family l2vpn evpn
advertise-pip
neighbor 10.103.0.2
remote-as 200
update-source loopback0
address-family ipv4 unicast
address-family ipv6 unicast
address-family ipv4 mvpn
send-community
send-community extended
address-family l2vpn evpn
send-community
send-community extended
neighbor 10.103.0.3
remote-as 200
update-source loopback0
address-family ipv4 unicast
address-family ipv6 unicast
send-community
send-community extended
address-family l2vpn evpn
send-community
send-community extended
evpn
vni 4000100 12
rd auto
```

```

route-target import auto
route-target export auto
vni 4000200 12
rd auto
route-target import auto
route-target export auto
vni 4000301 12
rd auto
route-target import auto
route-target export auto
vni 4000302 12
rd auto
route-target import auto
route-target export auto
vni 4000303 12
rd auto
route-target import auto
route-target export auto
S2-Leaf4#

```

Verifiëren

Gebruik deze sectie om te controleren of uw configuratie goed werkt.

De [Cisco CLI Analyzer](#) (alleen geregistreerde klanten) ondersteunt bepaalde `show` opdrachten. Gebruik de Cisco CLI Analyzer om een analyse van `show` opdrachtoutput.

```

<#root>

Host2#
show ip int brief

IP Interface Status for VRF "default"(1)
Interface          IP Address      Interface Status
Vlan100            192.168.100.102 protocol-up/link-up/admin-up
Vlan200            192.168.200.102 protocol-up/link-up/admin-up
Lo100              10.2.3.4        protocol-up/link-up/admin-up
Host2#
Host2#

```

```

<#root>

Host2#
ping 192.168.200.103

PING 192.168.200.103 (192.168.200.103): 56 data bytes
64 bytes from 192.168.200.103: icmp_seq=0 ttl=254 time=1.21 ms
64 bytes from 192.168.200.103: icmp_seq=1 ttl=254 time=0.627 ms
64 bytes from 192.168.200.103: icmp_seq=2 ttl=254 time=0.74 ms
64 bytes from 192.168.200.103: icmp_seq=3 ttl=254 time=0.737 ms
64 bytes from 192.168.200.103: icmp_seq=4 ttl=254 time=0.542 ms
--- 192.168.200.103 ping statistics ---
5 packets transmitted, 5 packets received, 0.00% packet loss

```

```

round-trip min/avg/max = 0.542/0.771/1.21 ms
Host2#
Host2#
Host2#
ping 192.168.100.103

PING 192.168.100.103 (192.168.100.103): 56 data bytes
64 bytes from 192.168.100.103: icmp_seq=0 ttl=254 time=1.195 ms
64 bytes from 192.168.100.103: icmp_seq=1 ttl=254 time=0.613 ms
64 bytes from 192.168.100.103: icmp_seq=2 ttl=254 time=0.575 ms
64 bytes from 192.168.100.103: icmp_seq=3 ttl=254 time=0.522 ms
64 bytes from 192.168.100.103: icmp_seq=4 ttl=254 time=0.534 ms
--- 192.168.100.103 ping statistics ---
5 packets transmitted, 5 packets received, 0.00% packet loss
round-trip min/avg/max = 0.522/0.687/1.195 ms
Host2#
Host2#
Host2#
ping 192.168.100.100

PING 192.168.100.100 (192.168.100.100): 56 data bytes
64 bytes from 192.168.100.100: icmp_seq=0 ttl=254 time=1.029 ms
64 bytes from 192.168.100.100: icmp_seq=1 ttl=254 time=0.561 ms
64 bytes from 192.168.100.100: icmp_seq=2 ttl=254 time=0.579 ms
64 bytes from 192.168.100.100: icmp_seq=3 ttl=254 time=0.511 ms
64 bytes from 192.168.100.100: icmp_seq=4 ttl=254 time=0.496 ms
--- 192.168.100.100 ping statistics ---
5 packets transmitted, 5 packets received, 0.00% packet loss
round-trip min/avg/max = 0.496/0.635/1.029 ms
Host2#
Host2#
Host2#
ping 192.168.200.100

PING 192.168.200.100 (192.168.200.100): 56 data bytes
64 bytes from 192.168.200.100: icmp_seq=0 ttl=254 time=1.263 ms
64 bytes from 192.168.200.100: icmp_seq=1 ttl=254 time=0.816 ms
64 bytes from 192.168.200.100: icmp_seq=2 ttl=254 time=0.735 ms
64 bytes from 192.168.200.100: icmp_seq=3 ttl=254 time=0.659 ms
64 bytes from 192.168.200.100: icmp_seq=4 ttl=254 time=0.634 ms
--- 192.168.200.100 ping statistics ---
5 packets transmitted, 5 packets received, 0.00% packet loss
round-trip min/avg/max = 0.634/0.821/1.263 ms
Host2#


<#root>

HOST_3(config)#
HOST_3(config)#

ping 192.168.100.100

PING 192.168.100.100 (192.168.100.100): 56 data bytes
64 bytes from 192.168.100.100: icmp_seq=0 ttl=254 time=1.319 ms
64 bytes from 192.168.100.100: icmp_seq=1 ttl=254 time=0.77 ms

```

```
64 bytes from 192.168.100.100: icmp_seq=2 ttl=254 time=0.505 ms
64 bytes from 192.168.100.100: icmp_seq=3 ttl=254 time=0.542 ms
64 bytes from 192.168.100.100: icmp_seq=4 ttl=254 time=0.486 ms
--- 192.168.100.100 ping statistics ---
5 packets transmitted, 5 packets received, 0.00% packet loss
round-trip min/avg/max = 0.486/0.724/1.319 ms
HOST_3(config)#

HOST_3(config)#
ping 192.168.100.102

PING 192.168.100.102 (192.168.100.102): 56 data bytes
64 bytes from 192.168.100.102: icmp_seq=0 ttl=254 time=1.304 ms
64 bytes from 192.168.100.102: icmp_seq=1 ttl=254 time=0.853 ms
64 bytes from 192.168.100.102: icmp_seq=2 ttl=254 time=0.845 ms
64 bytes from 192.168.100.102: icmp_seq=3 ttl=254 time=0.564 ms
64 bytes from 192.168.100.102: icmp_seq=4 ttl=254 time=0.55 ms
--- 192.168.100.102 ping statistics ---
5 packets transmitted, 5 packets received, 0.00% packet loss
round-trip min/avg/max = 0.55/0.823/1.304 ms
HOST_3(config)#
HOST_3(config)#
HOST_3(config)#
ping 192.168.200.102

PING 192.168.200.102 (192.168.200.102): 56 data bytes
64 bytes from 192.168.200.102: icmp_seq=0 ttl=254 time=0.997 ms
64 bytes from 192.168.200.102: icmp_seq=1 ttl=254 time=0.766 ms
64 bytes from 192.168.200.102: icmp_seq=2 ttl=254 time=0.84 ms
64 bytes from 192.168.200.102: icmp_seq=3 ttl=254 time=0.734 ms
64 bytes from 192.168.200.102: icmp_seq=4 ttl=254 time=0.592 ms
--- 192.168.200.102 ping statistics ---
5 packets transmitted, 5 packets received, 0.00% packet loss
round-trip min/avg/max = 0.592/0.785/0.997 ms
HOST_3(config)#

HOST_3(config)#
ping 192.168.200.100

PING 192.168.200.100 (192.168.200.100): 56 data bytes
36 bytes from 192.168.200.103: Destination Host Unreachable
Request 0 timed out
64 bytes from 192.168.200.100: icmp_seq=1 ttl=254 time=1.376 ms
64 bytes from 192.168.200.100: icmp_seq=2 ttl=254 time=0.806 ms
64 bytes from 192.168.200.100: icmp_seq=3 ttl=254 time=0.77 ms
64 bytes from 192.168.200.100: icmp_seq=4 ttl=254 time=0.793 ms
--- 192.168.200.100 ping statistics ---
5 packets transmitted, 4 packets received, 20.00% packet loss
round-trip min/avg/max = 0.77/0.936/1.376 ms
HOST_3(config)#

```

Problemen oplossen

Deze sectie bevat informatie waarmee u problemen met de configuratie kunt oplossen.

De [Cisco CLI Analyzer](#) (alleen geregistreerde klanten) ondersteunt bepaalde `show` opdrachten. Gebruik de Cisco CLI Analyzer om een analyse van `show` opdrachtoutput.

```
<#root>

Host2#
show ip arp

Flags: * - Adjacencies learnt on non-active FHRP router
      + - Adjacencies synced via CFSoE
      # - Adjacencies Throttled for Glean
      CP - Added via L2RIB, Control plane Adjacencies
      PS - Added via L2RIB, Peer Sync
      RO - Re-Originated Peer Sync Entry
      D - Static Adjacencies attached to down interface
IP ARP Table for context default
Total number of entries: 8
Address          Age      MAC Address     Interface      Flags
192.168.100.100 00:06:52 6c8b.d3ff.00a7  Vlan100
192.168.100.103 00:07:54 6c8b.d3fe.ecb5  Vlan100
192.168.100.104 00:07:01  6c8b.d3fe.df3b  Vlan100
192.168.100.254 00:08:01  0000.1111.2222  Vlan100
192.168.200.100 00:14:46  6c8b.d3ff.00a7  Vlan200
192.168.200.103 00:07:07  6c8b.d3fe.ecb5  Vlan200
192.168.200.104 00:07:31  6c8b.d3fe.df3b  Vlan200
192.168.200.254 00:07:07  0000.1111.2222  Vlan200
Host2#
Host2#
show mac address-table

Legend:
* - primary entry, G - Gateway MAC, (R) - Routed MAC, O - Overlay MAC
age - seconds since last seen,+ - primary entry using vPC Peer-Link,
(T) - True, (F) - False, C - ControlPlane MAC, ~ - vsan
VLAN      MAC Address    Type   age   Secure NTFY Ports
-----+-----+-----+-----+-----+-----+
* 100     0000.1111.2222 dynamic 0       F     F     Po2
* 100     6c8b.d3fe.df3b dynamic 0       F     F     Po2
* 100     6c8b.d3fe.ecb5 dynamic 0       F     F     Po2
* 100     6c8b.d3ff.00a7 dynamic 0       F     F     Po2
* 200     0000.1111.2222 dynamic 0       F     F     Po2
* 200     6c8b.d3fe.df3b dynamic 0       F     F     Po2
* 200     6c8b.d3fe.ecb5 dynamic 0       F     F     Po2
* 200     6c8b.d3ff.00a7 dynamic 0       F     F     Po2
G  -     6c8b.d3fe.ff09 static   -       F     F     sup-eth1(R)
G 100    6c8b.d3fe.ff09 static   -       F     F     sup-eth1(R)
G 200    6c8b.d3fe.ff09 static   -       F     F     sup-eth1(R)
Host2#
Host2#
```

```
<#root>

HOST_3(config)#
show ip arp
```

```

Flags: * - Adjacencies learnt on non-active FHRP router
      + - Adjacencies synced via CFSoE
      # - Adjacencies Throttled for Glean
      CP - Added via L2RIB, Control plane Adjacencies
      PS - Added via L2RIB, Peer Sync
      RO - Re-Originated Peer Sync Entry
      D - Static Adjacencies attached to down interface

```

IP ARP Table for context default

Total number of entries: 8

Address	Age	MAC Address	Interface	Flags
192.168.200.100	00:00:07	6c8b.d3ff.00a7	Vlan200	
192.168.200.102	00:11:41	6c8b.d3fe.ff09	Vlan200	
192.168.200.104	00:18:38	6c8b.d3fe.df3b	Vlan200	
192.168.200.254	00:12:19	0000.1111.2222	Vlan200	
192.168.100.100	00:07:16	6c8b.d3ff.00a7	Vlan100	
192.168.100.102	00:11:51	6c8b.d3fe.ff09	Vlan100	
192.168.100.104	00:15:06	6c8b.d3fe.df3b	Vlan100	
192.168.100.254	00:11:37	0000.1111.2222	Vlan100	

HOST_3(config)#

<#root>

S1-Leaf1#

show bgp 12vpn evpn

```

BGP routing table information for VRF default, address family L2VPN EVPN
BGP table version is 3291, Local Router ID is 10.102.0.5
Status: s-suppressed, x-deleted, S-stale, d-dampened, h-history, *-valid, >-best
Path type: i-internal, e-external, c-confed, l-local, a-aggregate, r-redist, I-injected
Origin codes: i - IGP, e - EGP, ? - incomplete, | - multipath, & - backup, 2 - best2
      Network          Next Hop          Metric      LocPrf      Weight Path
Route Distinguisher: 100:4000100
*>i[2]:[0]:[0]:[48]:[10b3.d5c7.9fb]#[0]:[0.0.0.0]/216
              10.100.100.1          100          0 300 200 i
*>i[2]:[0]:[0]:[48]:[4ce1.75f7.3785]#[0]:[0.0.0.0]/216
              10.100.100.1          100          0 300 200 i
*>i[2]:[0]:[0]:[48]:[6c8b.d3fe.df3b]#[0]:[0.0.0.0]/216
              10.100.100.1          100          0 300 200 i
*>i[2]:[0]:[0]:[48]:[6c8b.d3fe.ecb5]#[0]:[0.0.0.0]/216
              10.100.100.1          100          0 300 200 i
*>i[2]:[0]:[0]:[48]:[cc7f.76d4.2ebf]#[0]:[0.0.0.0]/216
              10.100.100.1          100          0 300 200 i
*>i[2]:[0]:[0]:[48]:[cc7f.76d4.3aef]#[0]:[0.0.0.0]/216
              10.100.100.1          100          0 300 200 i
*>i[2]:[0]:[0]:[48]:[cc7f.76fa.04c3]#[0]:[0.0.0.0]/216
              10.100.100.1          100          0 300 200 i
*>i[2]:[0]:[0]:[48]:[cc7f.76fa.0a3f]#[0]:[0.0.0.0]/216
              10.100.100.1          100          0 300 200 i
*>i[2]:[0]:[0]:[48]:[6c8b.d3fe.df3b]#[32]:[192.168.100.104]/272
              10.100.100.1          100          0 300 200 i
*>i[2]:[0]:[0]:[48]:[6c8b.d3fe.ecb5]#[32]:[192.168.100.103]/272
              10.100.100.1          100          0 300 200 i

Route Distinguisher: 100:4000200
*>i[2]:[0]:[0]:[48]:[10b3.d5c7.9fb]#[0]:[0.0.0.0]/216
              10.100.100.1          100          0 300 200 i
*>i[2]:[0]:[0]:[48]:[4ce1.75f7.3785]#[0]:[0.0.0.0]/216
              10.100.100.1          100          0 300 200 i

```

*>i[2]:[0]:[0]:[48]:[6c8b.d3fe.df3b]:[0]:[0.0.0.0]/216			
10.100.100.1	100	0 300 200	i
*>i[2]:[0]:[0]:[48]:[6c8b.d3fe.ecb5]:[0]:[0.0.0.0]/216			
10.100.100.1	100	0 300 200	i
*>i[2]:[0]:[0]:[48]:[cc7f.76d4.2ebf]:[0]:[0.0.0.0]/216			
10.100.100.1	100	0 300 200	i
*>i[2]:[0]:[0]:[48]:[cc7f.76d4.3aef]:[0]:[0.0.0.0]/216			
10.100.100.1	100	0 300 200	i
*>i[2]:[0]:[0]:[48]:[cc7f.76fa.04c3]:[0]:[0.0.0.0]/216			
10.100.100.1	100	0 300 200	i
*>i[2]:[0]:[0]:[48]:[cc7f.76fa.0a3f]:[0]:[0.0.0.0]/216			
10.100.100.1	100	0 300 200	i
*>i[2]:[0]:[0]:[48]:[6c8b.d3fe.df3b]:[32]:[192.168.200.104]/272			
10.100.100.1	100	0 300 200	i
*>i[2]:[0]:[0]:[48]:[6c8b.d3fe.ecb5]:[32]:[192.168.200.103]/272			
10.100.100.1	100	0 300 200	

Route Distinguisher: 10.31.1.1:32867

*>i[2]:[0]:[0]:[48]:[4ce1.75f7.383d]:[0]:[0.0.0.0]/216			
10.133.133.133	100	0	

Route Distinguisher: 10.31.1.1:32967

*>i[2]:[0]:[0]:[48]:[4ce1.75f7.383d]:[0]:[0.0.0.0]/216			
10.133.133.133	100	0 i	

Route Distinguisher: 10.31.1.2:32867

*>i[2]:[0]:[0]:[48]:[4ce1.75f7.38c7]:[0]:[0.0.0.0]/216			
10.134.134.134	100	0 i	

Route Distinguisher: 10.31.1.2:32967

*>i[2]:[0]:[0]:[48]:[4ce1.75f7.38c7]:[0]:[0.0.0.0]/216			
10.134.134.134	100	0 i	

Route Distinguisher: 10.102.0.5:32867 (L2VNI 4000100)

*>i[2]:[0]:[0]:[48]:[10b3.d5c7.9fdb]:[0]:[0.0.0.0]/216			
10.100.100.1	100	0 300 200	i

*>i[2]:[0]:[0]:[48]:[4ce1.75f7.3785]:[0]:[0.0.0.0]/216			
10.100.100.1	100	0 300 200	i

*>i[2]:[0]:[0]:[48]:[4ce1.75f7.383d]:[0]:[0.0.0.0]/216			
10.133.133.133	100	0 i	

*>i[2]:[0]:[0]:[48]:[4ce1.75f7.38c7]:[0]:[0.0.0.0]/216			
10.134.134.134	100	0 i	

*>i[2]:[0]:[0]:[48]:[6c8b.d3fe.df3b]:[0]:[0.0.0.0]/216			
10.100.100.1	100	0 300 200	i

*>i[2]:[0]:[0]:[48]:[6c8b.d3fe.ecb5]:[0]:[0.0.0.0]/216			
10.100.100.1	100	0 300 200	i

* i[2]:[0]:[0]:[48]:[6c8b.d3fe.ff09]:[0]:[0.0.0.0]/216			
10.202.202.202	100	0 i	

*>i 10.202.202.202	100	0 i	
----------------------------------	-----	-----	--

*>l[2]:[0]:[0]:[48]:[6c8b.d3ff.00a7]:[0]:[0.0.0.0]/216			
10.201.201.201	100	32768	i

*>i[2]:[0]:[0]:[48]:[cc7f.76c6.a673]:[0]:[0.0.0.0]/216			
10.202.202.202	100	0 i	

*>i[2]:[0]:[0]:[48]:[cc7f.76d4.2ebf]:[0]:[0.0.0.0]/216			
10.100.100.1	100	0 300 200	i

*>i[2]:[0]:[0]:[48]:[cc7f.76d4.3aef]:[0]:[0.0.0.0]/216			
10.100.100.1	100	0 300 200	i

*>i[2]:[0]:[0]:[48]:[cc7f.76fa.04c3]:[0]:[0.0.0.0]/216			
10.100.100.1	100	0 300 200	i

*>i[2]:[0]:[0]:[48]:[cc7f.76fa.0a3f]:[0]:[0.0.0.0]/216			
10.100.100.1	100	0 300 200	i

```

*>l[2]:[0]:[0]:[48]:[cc7f.76fa.0adb]:[0]:[0.0.0.0]/216
    10.201.201.201                                100      32768 i
*>i[2]:[0]:[0]:[48]:[cc7f.76fa.118f]:[0]:[0.0.0.0]/216
    10.202.202.202                                100      0 i
*>i[2]:[0]:[0]:[48]:[6c8b.d3fe.df3b]:[32]:[192.168.100.104]/272
    10.100.100.1                                100      0 300 200 i
*>i[2]:[0]:[0]:[48]:[6c8b.d3fe.ecb5]:[32]:[192.168.100.103]/272
    10.100.100.1                                100      0 300 200 i
* i[2]:[0]:[0]:[48]:[6c8b.d3fe.ff09]:[32]:[192.168.100.102]/272
    10.202.202.202                                100      0 i
*>i
    10.202.202.202                                100      0 i
*>l[2]:[0]:[0]:[48]:[6c8b.d3ff.00a7]:[32]:[192.168.100.100]/272
    10.201.201.201                                100      32768 i

Route Distinguisher: 10.102.0.5:32967 (L2VNI 4000200)
*>i[2]:[0]:[0]:[48]:[10b3.d5c7.9fb9]:[0]:[0.0.0.0]/216
    10.100.100.1                                100      0 300 200 i
*>i[2]:[0]:[0]:[48]:[4ce1.75f7.3785]:[0]:[0.0.0.0]/216
    10.100.100.1                                100      0 300 200 i
*>i[2]:[0]:[0]:[48]:[4ce1.75f7.383d]:[0]:[0.0.0.0]/216
    10.133.133.133                                100      0 i
*>i[2]:[0]:[0]:[48]:[4ce1.75f7.38c7]:[0]:[0.0.0.0]/216
    10.134.134.134                                100      0 i
*>i[2]:[0]:[0]:[48]:[6c8b.d3fe.df3b]:[0]:[0.0.0.0]/216
    10.100.100.1                                100      0 300 200 i
*>i[2]:[0]:[0]:[48]:[6c8b.d3fe.ecb5]:[0]:[0.0.0.0]/216
    10.100.100.1                                100      0 300 200 i

* i[2]:[0]:[0]:[48]:[6c8b.d3fe.ff09]:[0]:[0.0.0.0]/216
    10.202.202.202                                100      0 i
*>i
    10.202.202.202                                100      0 i
*>l[2]:[0]:[0]:[48]:[6c8b.d3ff.00a7]:[0]:[0.0.0.0]/216
    10.201.201.201                                100      32768 i
*>i[2]:[0]:[0]:[48]:[cc7f.76c6.a673]:[0]:[0.0.0.0]/216
    10.202.202.202                                100      0 i
*>i[2]:[0]:[0]:[48]:[cc7f.76d4.2ebf]:[0]:[0.0.0.0]/216
    10.100.100.1                                100      0 300 200 i
*>i[2]:[0]:[0]:[48]:[cc7f.76d4.3aef]:[0]:[0.0.0.0]/216
    10.100.100.1                                100      0 300 200 i
*>i[2]:[0]:[0]:[48]:[cc7f.76fa.04c3]:[0]:[0.0.0.0]/216
    10.100.100.1                                100      0 300 200 i
*>i[2]:[0]:[0]:[48]:[cc7f.76fa.0a3f]:[0]:[0.0.0.0]/216
    10.100.100.1                                100      0 300 200 i
*>l[2]:[0]:[0]:[48]:[cc7f.76fa.0adb]:[0]:[0.0.0.0]/216
    10.201.201.201                                100      32768 i
*>i[2]:[0]:[0]:[48]:[cc7f.76fa.118f]:[0]:[0.0.0.0]/216
    10.202.202.202                                100      0 i
*>i[2]:[0]:[0]:[48]:[6c8b.d3fe.df3b]:[32]:[192.168.200.104]/272
    10.100.100.1                                100      0 300 200 i
*>i[2]:[0]:[0]:[48]:[6c8b.d3fe.ecb5]:[32]:[192.168.200.103]/272
    10.100.100.1                                100      0 300 200 i
* i[2]:[0]:[0]:[48]:[6c8b.d3fe.ff09]:[32]:[192.168.200.102]/272
    10.202.202.202                                100      0 i
*>i
    10.202.202.202                                100      0 i
*>l[2]:[0]:[0]:[48]:[6c8b.d3ff.00a7]:[32]:[192.168.200.100]/272
    10.201.201.201                                100      32768 i

Route Distinguisher: 10.102.0.9:5
*>i[2]:[0]:[0]:[48]:[cc7f.76fa.118f]:[0]:[0.0.0.0]/216
    10.202.202.202                                100      0 i
*>i[5]:[0]:[0]:[24]:[192.168.100.0]/224
    10.102.1.10                                 100      0 i

```

*>i[5]:[0]:[0]:[32]:[10.15.100.2]/224
 10.102.1.10 100 0 i

 Route Distinguisher: 10.102.0.9:32867
 *>i[2]:[0]:[0]:[48]:[6c8b.d3fe.ff09]:[0]:[0.0.0.0]/216
 10.202.202.202 100 0 i
 *>i[2]:[0]:[0]:[48]:[cc7f.76fa.118f]:[0]:[0.0.0.0]/216
 10.202.202.202 100 0 i
 *>i[2]:[0]:[0]:[48]:[6c8b.d3fe.ff09]:[32]:[192.168.100.102]/272
 10.202.202.202 100 0 i

 Route Distinguisher: 10.102.0.9:32967
 *>i[2]:[0]:[0]:[48]:[6c8b.d3fe.ff09]:[0]:[0.0.0.0]/216
 10.202.202.202 100 0 i
 *>i[2]:[0]:[0]:[48]:[cc7f.76fa.118f]:[0]:[0.0.0.0]/216
 10.202.202.202 100 0 i
 *>i[2]:[0]:[0]:[48]:[6c8b.d3fe.ff09]:[32]:[192.168.200.102]/272
 10.202.202.202 100 0 i

 Route Distinguisher: 10.102.0.10:5
 *>i[2]:[0]:[0]:[48]:[cc7f.76c6.a673]:[0]:[0.0.0.0]/216
 10.202.202.202 100 0 i
 *>i[5]:[0]:[0]:[24]:[192.168.100.0]/224
 10.102.1.6 100 0 i
 *>i[5]:[0]:[0]:[32]:[10.15.100.1]/224
 10.102.1.6 100 0 i

 Route Distinguisher: 10.102.0.10:32867
 *>i[2]:[0]:[0]:[48]:[6c8b.d3fe.ff09]:[0]:[0.0.0.0]/216
 10.202.202.202 100 0 i
 *>i[2]:[0]:[0]:[48]:[cc7f.76c6.a673]:[0]:[0.0.0.0]/216
 10.202.202.202 100 0 i
 *>i[2]:[0]:[0]:[48]:[6c8b.d3fe.ff09]:[32]:[192.168.100.102]/272
 10.202.202.202 100 0 i

 Route Distinguisher: 10.102.0.10:32967
 *>i[2]:[0]:[0]:[48]:[6c8b.d3fe.ff09]:[0]:[0.0.0.0]/216
 10.202.202.202 100 0 i
 *>i[2]:[0]:[0]:[48]:[cc7f.76c6.a673]:[0]:[0.0.0.0]/216
 10.202.202.202 100 0 i
 *>i[2]:[0]:[0]:[48]:[6c8b.d3fe.ff09]:[32]:[192.168.200.102]/272
 10.202.202.202 100 0 i

 Route Distinguisher: 10.102.0.5:5 (L3VNI 4000502)
 *>i[2]:[0]:[0]:[48]:[cc7f.76c6.a673]:[0]:[0.0.0.0]/216
 10.202.202.202 100 0 i
 *>l[2]:[0]:[0]:[48]:[cc7f.76fa.0adb]:[0]:[0.0.0.0]/216
 10.201.201.201 100 32768 i
 *>i[2]:[0]:[0]:[48]:[cc7f.76fa.118f]:[0]:[0.0.0.0]/216
 10.202.202.202 100 0 i
 *>i[2]:[0]:[0]:[48]:[6c8b.d3fe.df3b]:[32]:[192.168.100.104]/272
 10.100.100.1 100 0 300 200 i
 *>i[2]:[0]:[0]:[48]:[6c8b.d3fe.df3b]:[32]:[192.168.200.104]/272
 10.100.100.1 100 0 300 200 i
 *>i[2]:[0]:[0]:[48]:[6c8b.d3fe.ecb5]:[32]:[192.168.100.103]/272
 10.100.100.1 100 0 300 200 i
 *>i[2]:[0]:[0]:[48]:[6c8b.d3fe.ecb5]:[32]:[192.168.200.103]/272
 10.100.100.1 100 0 300 200 i
 * i[2]:[0]:[0]:[48]:[6c8b.d3fe.ff09]:[32]:[192.168.100.102]/272
 10.202.202.202 100 0 i
 *>i 10.202.202.202 100 0 i
 * i[2]:[0]:[0]:[48]:[6c8b.d3fe.ff09]:[32]:[192.168.200.102]/272

```

          10.202.202.202      100      0 i
*>i          10.202.202.202      100      0 i
* i[5]:[0]:[0]:[24]:[192.168.100.0]/224
          10.102.1.6      100      0 i
*>i          10.102.1.10      100      0 i
* i[5]:[0]:[0]:[32]:[10.15.100.1]/224
          10.102.1.6      100      0 i
*>i[5]:[0]:[0]:[32]:[10.15.100.2]/224
          10.102.1.10      100      0 i
S1-Leaf1#

```

<#root>

S1-Leaf1#

show vpc brief

Legend:

(*) - local vPC is down, forwarding via vPC peer-link

vPC domain id	:	100
Peer status	:	peer adjacency formed ok
vPC keep-alive status	:	peer is alive
Configuration consistency status	:	success
Per-vlan consistency status	:	success
Type-2 consistency status	:	success
vPC role	:	secondary
Number of vPCs configured	:	1
Peer Gateway	:	Enabled
Dual-active excluded VLANs	:	-
Graceful Consistency Check	:	Enabled
Auto-recovery status	:	Disabled
Delay-restore status	:	Timer is off.(timeout = 150s)
Delay-restore SVI status	:	Timer is off.(timeout = 10s)
Delay-restore Orphan-port status	:	Timer is off.(timeout = 0s)
Operational Layer3 Peer-router	:	Disabled
Virtual-peerlink mode	:	Enabled

vPC Peer-link status

id	Port	Status	Active vlans
1	Po10	up	100,200,300-350,2001

vPC status

Id	Port	Status	Consistency	Reason	Active vlans
100	Po100	up	success	success	100,200

Please check "show vpc consistency-parameters vpc <vpc-num>" for the consistency reason of down vpc and for type-2 consistency reasons for any vpc.

S1-Leaf1#

<#root>

S1-Leaf1#

S1-Leaf1#

```
show ip int brief
```

IP Interface Status for VRF "default"(1)			
Interface	IP Address	Interface Status	
Lo0	10.102.0.5	protocol-up/link-up/admin-up	
Lo1	10.102.1.8	protocol-up/link-up/admin-up	
Eth1/2	192.168.17.12	protocol-up/link-up/admin-up	

S1-Leaf1#

<#root>

S2-Leaf1#

```
show bgp l2vpn evpn
```

BGP routing table information for VRF default, address family L2VPN EVPN
BGP table version is 4016, Local Router ID is 10.103.0.5
Status: s-suppressed, x-deleted, S-stale, d-dampened, h-history, *-valid, >-best
Path type: i-internal, e-external, c-confed, l-local, a-aggregate, r-redist, I-injected
Origin codes: i - IGP, e - EGP, ? - incomplete, | - multipath, & - backup, 2 - best2

Network	Next Hop	Metric	LocPrf	Weight	Path
Route Distinguisher: 200:4000100					
*>i[2]:[0]:[48]:[4ce1.75f7.383d]:[0]:[0.0.0.0]/216	10.100.100.2	100	0 300 100	i	
*>i[2]:[0]:[48]:[4ce1.75f7.38c7]:[0]:[0.0.0.0]/216	10.100.100.2	100	0 300 100	i	
*>i[2]:[0]:[48]:[6c8b.d3fe.ff09]:[0]:[0.0.0.0]/216	10.100.100.2	100	0 300 100	i	
*>i[2]:[0]:[48]:[6c8b.d3ff.00a7]:[0]:[0.0.0.0]/216	10.100.100.2	100	0 300 100	i	
*>i[2]:[0]:[48]:[cc7f.76c6.a673]:[0]:[0.0.0.0]/216	10.100.100.2	100	0 300 100	i	
*>i[2]:[0]:[48]:[cc7f.76fa.0907]:[0]:[0.0.0.0]/216	10.100.100.2	100	0 300 100	i	
*>i[2]:[0]:[48]:[cc7f.76fa.0adb]:[0]:[0.0.0.0]/216	10.100.100.2	100	0 300 100	i	
*>i[2]:[0]:[48]:[cc7f.76fa.118f]:[0]:[0.0.0.0]/216	10.100.100.2	100	0 300 100	i	
*>i[2]:[0]:[48]:[6c8b.d3fe.ff09]:[32]:[192.168.100.102]/272	10.100.100.2	100	0 300 100	i	
*>i[2]:[0]:[48]:[6c8b.d3ff.00a7]:[32]:[192.168.100.100]/272	10.100.100.2	100	0 300 100	i	
Route Distinguisher: 200:4000200					
*>i[2]:[0]:[48]:[4ce1.75f7.383d]:[0]:[0.0.0.0]/216	10.100.100.2	100	0 300 100	i	
*>i[2]:[0]:[48]:[4ce1.75f7.38c7]:[0]:[0.0.0.0]/216	10.100.100.2	100	0 300 100	i	
*>i[2]:[0]:[48]:[6c8b.d3fe.ff09]:[0]:[0.0.0.0]/216	10.100.100.2	100	0 300 100	i	
*>i[2]:[0]:[48]:[6c8b.d3ff.00a7]:[0]:[0.0.0.0]/216	10.100.100.2	100	0 300 100	i	
*>i[2]:[0]:[48]:[cc7f.76c6.a673]:[0]:[0.0.0.0]/216	10.100.100.2	100	0 300 100	i	
*>i[2]:[0]:[48]:[cc7f.76fa.0907]:[0]:[0.0.0.0]/216	10.100.100.2	100	0 300 100	i	
*>i[2]:[0]:[48]:[cc7f.76fa.0adb]:[0]:[0.0.0.0]/216	10.100.100.2	100	0 300 100	i	
*>i[2]:[0]:[48]:[cc7f.76fa.118f]:[0]:[0.0.0.0]/216	10.100.100.2	100	0 300 100	i	

	10.100.100.2	100	0 300 100 i
*>i[2]:[0]:[0]:[48]:[6c8b.d3fe.ff09]:[32]:[192.168.200.102]/272	10.100.100.2	100	0 300 100 i
*>i[2]:[0]:[0]:[48]:[6c8b.d3ff.00a7]:[32]:[192.168.200.100]/272	10.100.100.2	100	0 300 100 i
 Route Distinguisher: 200:4000502			
*>i[5]:[0]:[0]:[24]:[192.168.100.0]/224	10.100.100.2	100	0 300 100 i
*>i[5]:[0]:[0]:[32]:[10.15.100.1]/224	10.100.100.2	100	0 300 100 i
*>i[5]:[0]:[0]:[32]:[10.15.100.2]/224	10.100.100.2	100	0 300 100 i
 Route Distinguisher: 10.31.1.3:32867			
*>i[2]:[0]:[0]:[48]:[4ce1.75f7.3785]:[0]:[0.0.0.0]/216	10.135.135.135	100	0 i
 Route Distinguisher: 10.31.1.3:32967			
*>i[2]:[0]:[0]:[48]:[4ce1.75f7.3785]:[0]:[0.0.0.0]/216	10.135.135.135	100	0 i
 Route Distinguisher: 10.31.1.4:32867			
*>i[2]:[0]:[0]:[48]:[10b3.d5c7.9fdbd]:[0]:[0.0.0.0]/216	10.136.136.136	100	0 i
 Route Distinguisher: 10.31.1.4:32967			
*>i[2]:[0]:[0]:[48]:[10b3.d5c7.9fdbd]:[0]:[0.0.0.0]/216	10.136.136.136	100	0 i
 Route Distinguisher: 10.102.0.10:5			
*>i[2]:[0]:[0]:[48]:[cc7f.76fa.04c3]:[0]:[0.0.0.0]/216	10.103.202.202	100	0 i
 Route Distinguisher: 10.102.0.10:32867			
*>i[2]:[0]:[0]:[48]:[6c8b.d3fe.df3b]:[0]:[0.0.0.0]/216	10.103.202.202	100	0 i
*>i[2]:[0]:[0]:[48]:[cc7f.76fa.04c3]:[0]:[0.0.0.0]/216	10.103.202.202	100	0 i
*>i[2]:[0]:[0]:[48]:[6c8b.d3fe.df3b]:[32]:[192.168.100.104]/272	10.103.202.202	100	0 i
 Route Distinguisher: 10.102.0.10:32967			
*>i[2]:[0]:[0]:[48]:[6c8b.d3fe.df3b]:[0]:[0.0.0.0]/216	10.103.202.202	100	0 i
*>i[2]:[0]:[0]:[48]:[cc7f.76fa.04c3]:[0]:[0.0.0.0]/216	10.103.202.202	100	0 i
*>i[2]:[0]:[0]:[48]:[6c8b.d3fe.df3b]:[32]:[192.168.200.104]/272	10.103.202.202	100	0 i
 Route Distinguisher: 10.103.0.5:32867 (L2VNI 4000100)			
*>i[2]:[0]:[0]:[48]:[10b3.d5c7.9fdbd]:[0]:[0.0.0.0]/216	10.136.136.136	100	0 i
*>i[2]:[0]:[0]:[48]:[4ce1.75f7.3785]:[0]:[0.0.0.0]/216	10.135.135.135	100	0 i
*>i[2]:[0]:[0]:[48]:[4ce1.75f7.383d]:[0]:[0.0.0.0]/216	10.100.100.2	100	0 300 100 i
*>i[2]:[0]:[0]:[48]:[4ce1.75f7.38c7]:[0]:[0.0.0.0]/216	10.100.100.2	100	0 300 100 i
* i[2]:[0]:[0]:[48]:[6c8b.d3fe.df3b]:[0]:[0.0.0.0]/216	10.103.202.202	100	0 i
*>i	10.103.202.202	100	0 i

*>l[2]:[0]:[0]:[48]:[6c8b.d3fe.ecb5]:[0]:[0.0.0.0]/216				
10.103.201.201	100	32768	i	
*>i[2]:[0]:[0]:[48]:[6c8b.d3fe.ff09]:[0]:[0.0.0.0]/216				
10.100.100.2	100	0	300 100	i
*>i[2]:[0]:[0]:[48]:[6c8b.d3ff.00a7]:[0]:[0.0.0.0]/216				
10.100.100.2	100	0	300 100	i
*>i[2]:[0]:[0]:[48]:[cc7f.76c6.a673]:[0]:[0.0.0.0]/216				
10.100.100.2	100	0	300 100	i
*>i[2]:[0]:[0]:[48]:[cc7f.76d4.2ebf]:[0]:[0.0.0.0]/216				
10.103.202.202	100	0	i	
*>i[2]:[0]:[0]:[48]:[cc7f.76fa.04c3]:[0]:[0.0.0.0]/216				
10.103.202.202	100	0	i	
*>i[2]:[0]:[0]:[48]:[cc7f.76fa.0907]:[0]:[0.0.0.0]/216				
10.100.100.2	100	0	300 100	i
*>l[2]:[0]:[0]:[48]:[cc7f.76fa.0a3f]:[0]:[0.0.0.0]/216				
10.103.201.201	100	32768	i	
*>i[2]:[0]:[0]:[48]:[cc7f.76fa.0adb]:[0]:[0.0.0.0]/216				
10.100.100.2	100	0	300 100	i
*>i[2]:[0]:[0]:[48]:[cc7f.76fa.118f]:[0]:[0.0.0.0]/216				
10.100.100.2	100	0	300 100	i
* i[2]:[0]:[0]:[48]:[6c8b.d3fe.df3b]:[32]:[192.168.100.104]/272				
10.103.202.202	100	0	i	
*>i	10.103.202.202	100	0	i
*>l[2]:[0]:[0]:[48]:[6c8b.d3fe.ecb5]:[32]:[192.168.100.103]/272				
10.103.201.201	100	32768	i	
*>i[2]:[0]:[0]:[48]:[6c8b.d3fe.ff09]:[32]:[192.168.100.102]/272				
10.100.100.2	100	0	300 100	i
*>i[2]:[0]:[0]:[48]:[6c8b.d3ff.00a7]:[32]:[192.168.100.100]/272				
10.100.100.2	100	0	300 100	i

Route Distinguisher: 10.103.0.5:32967 (L2VNI 4000200)

*>i[2]:[0]:[0]:[48]:[10b3.d5c7.9fdb]:[0]:[0.0.0.0]/216				
10.136.136.136	100	0	i	
*>i[2]:[0]:[0]:[48]:[4ce1.75f7.3785]:[0]:[0.0.0.0]/216				
10.135.135.135	100	0	i	
*>i[2]:[0]:[0]:[48]:[4ce1.75f7.383d]:[0]:[0.0.0.0]/216				
10.100.100.2	100	0	300 100	i
*>i[2]:[0]:[0]:[48]:[4ce1.75f7.38c7]:[0]:[0.0.0.0]/216				
10.100.100.2	100	0	300 100	i
* i[2]:[0]:[0]:[48]:[6c8b.d3fe.df3b]:[0]:[0.0.0.0]/216				
10.103.202.202	100	0	i	
*>i	10.103.202.202	100	0	i
*>l[2]:[0]:[0]:[48]:[6c8b.d3fe.ecb5]:[0]:[0.0.0.0]/216				
10.103.201.201	100	32768	i	
*>i[2]:[0]:[0]:[48]:[6c8b.d3fe.ff09]:[0]:[0.0.0.0]/216				
10.100.100.2	100	0	300 100	i
*>i[2]:[0]:[0]:[48]:[6c8b.d3ff.00a7]:[0]:[0.0.0.0]/216				
10.100.100.2	100	0	300 100	i
*>i[2]:[0]:[0]:[48]:[cc7f.76c6.a673]:[0]:[0.0.0.0]/216				
10.100.100.2	100	0	300 100	i
*>i[2]:[0]:[0]:[48]:[cc7f.76d4.2ebf]:[0]:[0.0.0.0]/216				
10.103.202.202	100	0	i	
*>i[2]:[0]:[0]:[48]:[cc7f.76fa.04c3]:[0]:[0.0.0.0]/216				
10.103.202.202	100	0	i	
*>i[2]:[0]:[0]:[48]:[cc7f.76fa.0907]:[0]:[0.0.0.0]/216				
10.100.100.2	100	0	300 100	i
*>l[2]:[0]:[0]:[48]:[cc7f.76fa.0a3f]:[0]:[0.0.0.0]/216				
10.103.201.201	100	32768	i	
*>i[2]:[0]:[0]:[48]:[cc7f.76fa.0adb]:[0]:[0.0.0.0]/216				
10.100.100.2	100	0	300 100	i
*>i[2]:[0]:[0]:[48]:[cc7f.76fa.118f]:[0]:[0.0.0.0]/216				
10.100.100.2	100	0	300 100	i

```

* i[2]:[0]:[0]:[48]:[6c8b.d3fe.df3b]:[32]:[192.168.200.104]/272
          10.103.202.202           100      0 i
*>i          10.103.202.202           100      0 i
*>l[2]:[0]:[0]:[48]:[6c8b.d3fe.ecb5]:[32]:[192.168.200.103]/272
          10.103.201.201           100      32768 i
*>i[2]:[0]:[0]:[48]:[6c8b.d3fe.ff09]:[32]:[192.168.200.102]/272
          10.100.100.2            100      0 300 100 i
*>i[2]:[0]:[0]:[48]:[6c8b.d3ff.00a7]:[32]:[192.168.200.100]/272
          10.100.100.2            100      0 300 100 i

Route Distinguisher: 10.103.0.9:5
*>i[2]:[0]:[0]:[48]:[cc7f.76d4.2ebf]:[0]:[0.0.0.0]/216
          10.103.202.202           100      0 i

Route Distinguisher: 10.103.0.9:32867
*>i[2]:[0]:[0]:[48]:[6c8b.d3fe.df3b]:[0]:[0.0.0.0]/216
          10.103.202.202           100      0 i
*>i[2]:[0]:[0]:[48]:[cc7f.76d4.2ebf]:[0]:[0.0.0.0]/216
          10.103.202.202           100      0 i
*>i[2]:[0]:[0]:[48]:[6c8b.d3fe.df3b]:[32]:[192.168.100.104]/272
          10.103.202.202           100      0 i

Route Distinguisher: 10.103.0.9:32967
*>i[2]:[0]:[0]:[48]:[6c8b.d3fe.df3b]:[0]:[0.0.0.0]/216
          10.103.202.202           100      0 i
*>i[2]:[0]:[0]:[48]:[cc7f.76d4.2ebf]:[0]:[0.0.0.0]/216
          10.103.202.202           100      0 i
*>i[2]:[0]:[0]:[48]:[6c8b.d3fe.df3b]:[32]:[192.168.200.104]/272
          10.103.202.202           100      0 i

Route Distinguisher: 10.103.0.5:5 (L3VNI 4000502)
*>i[2]:[0]:[0]:[48]:[cc7f.76d4.2ebf]:[0]:[0.0.0.0]/216
          10.103.202.202           100      0 i
*>i[2]:[0]:[0]:[48]:[cc7f.76fa.04c3]:[0]:[0.0.0.0]/216
          10.103.202.202           100      0 i
*>l[2]:[0]:[0]:[48]:[cc7f.76fa.0a3f]:[0]:[0.0.0.0]/216
          10.103.201.201           100      32768 i
* i[2]:[0]:[0]:[48]:[6c8b.d3fe.df3b]:[32]:[192.168.100.104]/272
          10.103.202.202           100      0 i
*>i          10.103.202.202           100      0 i
* i[2]:[0]:[0]:[48]:[6c8b.d3fe.df3b]:[32]:[192.168.200.104]/272
          10.103.202.202           100      0 i
*>i          10.103.202.202           100      0 i
*>i[2]:[0]:[0]:[48]:[6c8b.d3fe.ff09]:[32]:[192.168.100.102]/272
          10.100.100.2            100      0 300 100 i
*>i[2]:[0]:[0]:[48]:[6c8b.d3fe.ff09]:[32]:[192.168.200.102]/272
          10.100.100.2            100      0 300 100 i
*>i[2]:[0]:[0]:[48]:[6c8b.d3ff.00a7]:[32]:[192.168.100.100]/272
          10.100.100.2            100      0 300 100 i
*>i[2]:[0]:[0]:[48]:[6c8b.d3ff.00a7]:[32]:[192.168.200.100]/272
          10.100.100.2            100      0 300 100 i
*>i[5]:[0]:[0]:[24]:[192.168.100.0]/224
          10.100.100.2            100      0 300 100 i
*>i[5]:[0]:[0]:[32]:[10.15.100.1]/224
          10.100.100.2            100      0 300 100 i
*>i[5]:[0]:[0]:[32]:[10.15.100.2]/224
          10.100.100.2            100      0 300 100 i

```

S2-Leaf1#

Over deze vertaling

Cisco heeft dit document vertaald via een combinatie van machine- en menselijke technologie om onze gebruikers wereldwijd ondersteuningscontent te bieden in hun eigen taal. Houd er rekening mee dat zelfs de beste machinevertaling niet net zo nauwkeurig is als die van een professionele vertaler. Cisco Systems, Inc. is niet aansprakelijk voor de nauwkeurigheid van deze vertalingen en raadt aan altijd het oorspronkelijke Engelstalige document ([link](#)) te raadplegen.