

TechNote para solução de problemas de reinicialização do servidor UCS C-Series

Contents

[Introduction](#)

[Prerequisites](#)

[Requirements](#)

[Componentes Utilizados](#)

[Saída esperada para diferentes condições de reinicialização](#)

[Reinicialização do SO \(vSphere 5.0\)](#)

[Ciclo de energia da interface do usuário CIMC](#)

[Desligar da interface do usuário CIMC](#)

[Ligar da interface do usuário CIMC](#)

[Botão liga/desliga na frente do servidor \(DESLIGADO\)](#)

[Botão liga/desliga na frente do servidor \(LIGADO\)](#)

Introduction

Este documento fornece saída de `/var/log/messages` (também encontrada no log Onboard Failure Logging (OBFL)) para um C210-M2 que retrata a saída esperada durante diferentes condições de reinicialização. Quando você soluciona problemas de inicialização do servidor Cisco Unified Computing System (UCS) C-Series, um ponto a ser iniciado é `/var/log/messages` e os logs OBFL. Esses registros estão localizados nos arquivos de suporte técnico. A ideia é que você possa combinar a saída de uma mensagem de suporte técnico específica com a saída neste documento para confirmar o que disparou a reinicialização.

Prerequisites

Requirements

A Cisco recomenda que você tenha conhecimento destes tópicos:

- VMware vSphere 5.0
- Cisco Integrated Management Controller (CIMC)

Componentes Utilizados

Este documento não se restringe a versões de software e hardware específicas.

The information in this document was created from the devices in a specific lab environment. All of the devices used in this document started with a cleared (default) configuration. If your network is live, make sure that you understand the potential impact of any command.

Saída esperada para diferentes condições de reinicialização

Reinicialização do SO (vSphere 5.0)

```
5:2012 May 11 13:49:38:BMC:kernel:--<5>LPC Reset ISR -> ResetState: 1
7:2012 May 11 13:49:38:BMC:kernel:--<7>[peci_init_hardware]:490:peci:
  unregistered IRQ: [13]
7:2012 May 11 13:49:38:BMC:kernel:--<7>[block_transfer_deallocate_entire_list]:
  1141:block_transfer_deallocate_entire_list
7:2012 May 11 13:49:38:BMC:kernel:--<7>[block_transfer_deallocate_entire_list]:
  1185:block_transfer_deallocate_entire_list : Dumped: 0x0002 files.
5:2012 May 11 13:49:38:BMC:BIOSReader:391: BIOSReader.c:555:File Close :
  /var/nuova/BIOS/BiosTech_1.txt
5:2012 May 11 13:49:38:BMC:BIOSReader:391: BIOSReader.c:555:File Close :
  /var/nuova/BIOS/BiosTech_4.txt
5:2012 May 11 13:49:38:BMC:kernel:--<5>[block_transfer_fetch_host_request_for_app]:
  2125:block_transfer_fetch_host_request_for_app : BT_FILE_CLOSE :
  HostBTDescr = 126 : FName = BiosTech_1.txt
5:2012 May 11 13:49:38:BMC:kernel:--<5>[block_transfer_fetch_host_request_for_app]:
  2125:block_transfer_fetch_host_request_for_app : BT_FILE_CLOSE :
  HostBTDescr = 125 : FName = BiosTech_4.txt
5:2012 May 11 13:49:38:BMC:kernel:--<5>LPC Reset ISR -> ResetState: 0
7:2012 May 11 13:49:38:BMC:kernel:--<7>[peci_init_hardware]:472:peci:
  registered IRQ: [13]
5:2012 May 11 13:49:38:BMC:kernel:--<5>[lpc_reset_handler_Port80_Capture_setup]:
  630:BIOS_POST_CMPLT De-asserted --> BIOS is running
7:2012 May 11 13:49:38:BMC:kernel:--<7>[block_transfer_deallocate_entire_list]:
  1141:block_transfer_deallocate_entire_list
7:2012 May 11 13:49:38:BMC:kernel:--<7>[block_transfer_deallocate_entire_list]:
  1185:block_transfer_deallocate_entire_list : Dumped: 0x0000 files.
6:2012 May 11 13:49:38:BMC:avct_server:--: rvas_wait_for_changes failed
4:2012 May 11 13:49:38:BMC:avct_server:--: No Video Source Detected!
5:2012 May 11 13:49:39:BMC:bioscom:--: lv_mode_dimm_support.c:126:
  [lpc_reset_seen]LPC Reset Count is Different [0x28:0x29]
  Asserted LPC Reset Seen
5:2012 May 11 13:49:39:BMC:IPMI:585: Bridge.c:1388:audit from:kcs
  Fn:0x4 Cmd:0x28 Resp:0x0
5:2012 May 11 13:49:39:BMC:IPMI:585: Bridge.c:1415:audit data&colon; 0x9 0x80
5:2012 May 11 13:49:39:BMC:IPMI:585: Bridge.c:1388:audit from:kcs
  Fn:0x4 Cmd:0x28 Resp:0x0
5:2012 May 11 13:49:39:BMC:IPMI:585: Bridge.c:1415:audit data&colon; 0xa 0x80
5:2012 May 11 13:49:39:BMC:bioscom:--: lv_mode_dimm_support.c:197:
  [transition_function]Starting Transition to
  [High Voltage Mode] from [Unknown Mode]
5:2012 May 11 13:49:39:BMC:IPMI:585: Bridge.c:1388:audit from:kcs
  Fn:0x4 Cmd:0x28 Resp:0x0
5:2012 May 11 13:49:39:BMC:IPMI:585: Bridge.c:1415:audit data&colon; 0x9 0x80
5:2012 May 11 13:49:39:BMC:IPMI:585: Bridge.c:1388:audit from:kcs
  Fn:0x4 Cmd:0x28 Resp:0x0
5:2012 May 11 13:49:39:BMC:IPMI:585: Bridge.c:1415:audit data&colon; 0xa 0x80
5:2012 May 11 13:49:39:BMC:IPMI:585: Bridge.c:1388:audit from:kcs
  Fn:0x4 Cmd:0x26 Resp:0x0
5:2012 May 11 13:49:39:BMC:IPMI:585: Bridge.c:1415:audit data&colon;
  0x9 0x36 0x92 0x92 0x89 0x9f 0x9f 0xa8
5:2012 May 11 13:49:39:BMC:IPMI:585: Bridge.c:1388:audit from:kcs
  Fn:0x4 Cmd:0x26 Resp:0x0
5:2012 May 11 13:49:39:BMC:IPMI:585: Bridge.c:1415:audit data&colon;
  0xa 0x36 0x92 0x92 0x89 0x9f 0x9f 0xa8
5:2012 May 11 13:49:39:BMC:bioscom:--: lv_mode_dimm_support.c:217:
  [transition_function]Transition to [High Voltage Mode] Success
```

```

5:2012 May 11 13:49:39:BMC:IPMI:591: VirtualSEL.c:224:SEL Evt[04 00]<
    04 00 02 F3 18 AD 4F 20 00 04 25 53 08 00 FF FF >
5:2012 May 11 13:49:39:BMC:BIOSReader:391: BIOSReader.c:227:File Open :
    BiosTech_3.txt
5:2012 May 11 13:49:39:BMC:kernel:--<5>[block_transfer_fetch_host_request_for_app]:
    2063:block_transfer_fetch_host_request_for_app: BT_OPEN:
    HostDescriptor = 131 : Filename = BiosTech_3.txt
7:2012 May 11 13:49:39:BMC:kernel:--<7>[mailbox_isr]:276:
    Mailbox[0] Bit Change w/NULL Handler (01 - 10)!
7:2012 May 11 13:49:39:BMC:kernel:--<7>[mailbox_isr]:276:
    Mailbox[0] Bit Change w/NULL Handler (01 - 20)!
7:2012 May 11 13:49:39:BMC:kernel:--<7>[mailbox_isr]:276:
    Mailbox[0] Bit Change w/NULL Handler (01 - 40)!
5:2012 May 11 13:49:39:BMC:kernel:--<5>LPC Reset ISR -> ResetState: 1
7:2012 May 11 13:49:39:BMC:kernel:--<7>[peci_init_hardware]:490:peci:
    unregistered IRQ: [13]
7:2012 May 11 13:49:39:BMC:kernel:--<7>[block_transfer_deallocate_entire_list]:
    1141:block_transfer_deallocate_entire_list
7:2012 May 11 13:49:39:BMC:kernel:--<7>[block_transfer_deallocate_entire_list]:
    1185:block_transfer_deallocate_entire_list : Dumped: 0x0001 files.
5:2012 May 11 13:49:39:BMC:kernel:--<5>LPC Reset ISR -> ResetState: 0
7:2012 May 11 13:49:39:BMC:kernel:--<7>[peci_init_hardware]:472:peci:
    registered IRQ: [13]

```

Notas:

- Somente a inicialização do SO não imprime a saída "do_power". Você pode usar esse fato para determinar rapidamente se o servidor foi inicializado no SO.
- Somente a inicialização do SO imprime transições [High Voltage Mode].

Ciclo de energia da interface do usuário CIMC

```

5:2012 May 11 13:50:22:BMC:IPMI:585: Bridge.c:1388:audit from:kcs
    Fn:0x0 Cmd:0x2 Resp:0x0
5:2012 May 11 13:50:22:BMC:IPMI:585: Bridge.c:1415:audit data&colon; 0x2
7:2012 May 11 13:50:22:BMC:kernel:--<7>[do_power_off]:188:do_power_off
5:2012 May 11 13:50:22:BMC:kernel:--<5>[do_power_off]:190:Power Driver:
    Power Off Logic @ 181790792
6:2012 May 11 13:50:22:BMC:kernel:--<6>[press_button]:105:Power Driver:
    Press Power Button @ 181790793
5:2012 May 11 13:50:22:BMC:AUDIT:-- Server power state modify (op:power-cycle)
5:2012 May 11 13:50:26:BMC:kernel:--<5>LPC Reset ISR -> ResetState: 1
7:2012 May 11 13:50:26:BMC:kernel:--<7>[peci_init_hardware]:490:peci:
    unregistered IRQ: [13]
7:2012 May 11 13:50:26:BMC:kernel:--<7>[block_transfer_deallocate_entire_list]:
    1141:block_transfer_deallocate_entire_list
7:2012 May 11 13:50:26:BMC:kernel:--<7>[block_transfer_deallocate_entire_list]:
    1185:block_transfer_deallocate_entire_list : Dumped: 0x0001 files.
7:2012 May 11 13:50:26:BMC:kernel:--<7>USB FS: VDD Power WAKEUP- Power Good = OFF
7:2012 May 11 13:50:26:BMC:kernel:--<7>kbd_complete: -108, 0/8
7:2012 May 11 13:50:26:BMC:kernel:--<7>mouse_complete: -108, 0/6
7:2012 May 11 13:50:26:BMC:kernel:--<7>USB HS: VDD Power WAKEUP- Power Good = OFF
7:2012 May 11 13:50:26:BMC:kernel:--<7>bulk_out_complete: -108, 0/31, LUN[0][2]
7:2012 May 11 13:50:26:BMC:kernel:--<7>handle_exception: Handling
    MSD_STATE_DISCONNECT for interface[0]
7:2012 May 11 13:50:26:BMC:kernel:--<7>do_set_interface(): reset_interface
7:2012 May 11 13:50:26:BMC:kernel:--<7>handle_exception:
    Handling MSD_STATE_DISCONNECT for interface[1]
5:2012 May 11 13:50:26:BMC:kernel:--<5>[block_transfer_fetch_host_request_for_app]:
    2125:block_transfer_fetch_host_request_for_app : BT_FILE_CLOSE :
    HostBTDescr = 132 : FName = BiosTech_4.txt

```

```
6:2012 May 11 13:50:26:BMC:kernel:-:<6>kbdmouse_write:
    kbd write aborted for device reset.
6:2012 May 11 13:50:26:BMC:kernel:-:<6>kbdmouse_write:
    mouse write aborted for device reset.
6:2012 May 11 13:50:26:BMC:avct_server:-: rvas_wait_for_changes failed
5:2012 May 11 13:50:26:BMC:BIOSReader:391:
    BIOSReader.c:555:File Close : /var/nuova/BIOS/BiosTech_4.txt
```

Desligar da interface do usuário CIMC

```
5:2012 May 11 13:58:57:BMC:IPMI:585: Bridge.c:1388:audit from:kcs
    Fn:0x0 Cmd:0x2 Resp:0x0
7:2012 May 11 13:58:57:BMC:kernel:-:<7>[do_power_off]:188:do_power_off
5:2012 May 11 13:58:57:BMC:kernel:-:<5>[do_power_off]:190:Power Driver:
    Power Off Logic @ 182297296
6:2012 May 11 13:58:57:BMC:kernel:-:<6>[press_button]:105:Power Driver:
    Press Power Button @ 182297296
5:2012 May 11 13:58:57:BMC:IPMI:585: Bridge.c:1415:audit data&colon; 0x0
5:2012 May 11 13:58:57:BMC:AUDIT:-: Server power state modify (op:power-off)
5:2012 May 11 13:59:01:BMC:kernel:-:<5>LPC Reset ISR -> ResetState: 1
7:2012 May 11 13:59:01:BMC:kernel:-:<7>[peci_init_hardware]:490:peci:
    unregistered IRQ: [13]
7:2012 May 11 13:59:01:BMC:kernel:-:<7>[block_transfer_deallocate_entire_list]:
    1141:block_transfer_deallocate_entire_list
7:2012 May 11 13:59:01:BMC:kernel:-:<7>[block_transfer_deallocate_entire_list]:
    1185:block_transfer_deallocate_entire_list : Dumped: 0x0002 files.
7:2012 May 11 13:59:01:BMC:kernel:-:<7>USB FS: VDD Power WAKEUP- Power Good = OFF
7:2012 May 11 13:59:01:BMC:kernel:-:<7>USB HS: VDD Power WAKEUP- Power Good = OFF
7:2012 May 11 13:59:01:BMC:kernel:-:<7>bulk_out_complete: -108, 0/31, LUN[0][2]
7:2012 May 11 13:59:01:BMC:kernel:-:<7>handle_exception: Handling
    MSD_STATE_DISCONNECT for interface[0]
7:2012 May 11 13:59:01:BMC:kernel:-:<7>do_set_interface(): reset_interface
7:2012 May 11 13:59:01:BMC:kernel:-:<7>handle_exception: Handling
    MSD_STATE_DISCONNECT for interface[1]
5:2012 May 11 13:59:01:BMC:kernel:-:<5>[block_transfer_fetch_host_request_for_app]:
    2125:block_transfer_fetch_host_request_for_app : BT_FILE_CLOSE :
    HostBTDescr = 143 : FName = BiosTech_3.txt
5:2012 May 11 13:59:01:BMC:kernel:-:<5>[block_transfer_fetch_host_request_for_app]:
    2125:block_transfer_fetch_host_request_for_app : BT_FILE_CLOSE :
    HostBTDescr = 142 : FName = BiosTech_2.txt
6:2012 May 11 13:59:01:BMC:avct_server:-: rvas_wait_for_changes failed
5:2012 May 11 13:59:01:BMC:BIOSReader:391: BIOSReader.c:555:File Close :
    /var/nuova/BIOS/BiosTech_3.txt
5:2012 May 11 13:59:01:BMC:BIOSReader:391: BIOSReader.c:555:File Close :
    /var/nuova/BIOS/BiosTech_2.txt
```

Ligar da interface do usuário CIMC

```
5:2012 May 11 13:59:13:BMC:IPMI:585: Bridge.c:1388:audit from:
    kcs Fn:0x0 Cmd:0x2 Resp:0x0
5:2012 May 11 13:59:13:BMC:IPMI:585: Bridge.c:1415:audit data&colon; 0x1
7:2012 May 11 13:59:13:BMC:kernel:-:<7>[do_power_on]:226:do_power_on
5:2012 May 11 13:59:13:BMC:kernel:-:<5>[do_power_on]:231:Power Driver:
    Power On Logic Pulse for 250ms @ 182313079
6:2012 May 11 13:59:13:BMC:kernel:-:<6>[press_button]:105:Power Driver:
    Press Power Button @ 182313079
5:2012 May 11 13:59:13:BMC:AUDIT:-: Server power state modify (op:power-on)
6:2012 May 11 13:59:13:BMC:kernel:-:<6>[release_button]:115:Power Driver:
    Release Power Button @ 182313330
7:2012 May 11 13:59:13:BMC:kernel:-:<7>USB FS: VDD Power WAKEUP-
    Power Good = ON
```

```

6:2012 May 11 13:59:13:BMC:kernel:--:<6>se_pilot2_udc_usb_turnon:
    Passed USB1.1 register test (0)
7:2012 May 11 13:59:13:BMC:kernel:--:<7>USB HS: VDD Power WAKEUP-
    Power Good = ON
6:2012 May 11 13:59:13:BMC:kernel:--:<6>se_pilot2_udc_usb_turnon:
    Passed USB2.0 register test (11)
5:2012 May 11 13:59:13:BMC:kernel:--:<5>LPC Reset ISR -> ResetState: 0
7:2012 May 11 13:59:13:BMC:kernel:--:<7>[peci_init_hardware]:472:peci:
    registered IRQ: [13]
5:2012 May 11 13:59:13:BMC:kernel:--:<5>[lpc_reset_handler_Port80_Capture_setup]:
    630:BIOS_POST_CMPLT De-asserted --> BIOS is running
7:2012 May 11 13:59:13:BMC:kernel:--:<7>[block_transfer_deallocate_entire_list]:
    1141:block_transfer_deallocate_entire_list
7:2012 May 11 13:59:13:BMC:kernel:--:<7>[block_transfer_deallocate_entire_list]:
    1185:block_transfer_deallocate_entire_list : Dumped: 0x0000 files.
5:2012 May 11 13:59:13:BMC:IPMI:587: Pilot2SrvPower.c:394:
    Blade Power Changed To: [ ON ]
5:2012 May 11 13:59:13:BMC:kernel:--:<5>[do_power_on]:
    251:Power Driver: Power On Logic Done @ 182313832
5:2012 May 11 13:59:13:BMC:IPMI:590: Pilot2SrvPower.c:
    188:Pilot2SrvPowerOn
5:2012 May 11 13:59:14:BMC:IPMI:591: VirtualSEL.c:224:
    SEL Evt[25 00]< 25 00 02 32 1B AD 4F 20 00 04 25 52 08 01 FF FF >
5:2012 May 11 13:59:14:BMC:IPMI:591: VirtualSEL.c:224:
    SEL Evt[26 00]< 26 00 02 32 1B AD 4F 20 00 04 25 53 08 00 FF FF >
5:2012 May 11 13:59:14:BMC:IPMI:591: VirtualSEL.c:224:
    SEL Evt[27 00]< 27 00 02 32 1B AD 4F 20 00 04 08 62 0B 00 FF FF >
5:2012 May 11 13:59:14:BMC:kernel:--:<5>[block_transfer_fetch_host_request_for_app]:
    2063:block_transfer_fetch_host_request_for_app: BT_OPEN:
    HostDescriptor = 148 : Filename = BiosTech_1.txt
5:2012 May 11 13:59:14:BMC:BIOSReader:391: BIOSReader.c:227:
    File Open : BiosTech_1.txt
7:2012 May 11 13:59:14:BMC:kernel:--:<7>[mailbox_isr]:276:
    Mailbox[0] Bit Change w/NULL Handler (01 - 10)!
7:2012 May 11 13:59:14:BMC:kernel:--:<7>[mailbox_isr]:276:
    Mailbox[0] Bit Change w/NULL Handler (01 - 20)!
7:2012 May 11 13:59:14:BMC:kernel:--:<7>[mailbox_isr]:276:
    Mailbox[0] Bit Change w/NULL Handler (01 - 40)!
5:2012 May 11 13:59:14:BMC:kernel:--:<5>LPC Reset ISR -> ResetState: 1
7:2012 May 11 13:59:14:BMC:kernel:--:<7>[peci_init_hardware]:490:peci:
    unregistered IRQ: [13]
7:2012 May 11 13:59:14:BMC:kernel:--:<7>[block_transfer_deallocate_entire_list]:
    1141:block_transfer_deallocate_entire_list
7:2012 May 11 13:59:14:BMC:kernel:--:<7>[block_transfer_deallocate_entire_list]:
    1185:block_transfer_deallocate_entire_list : Dumped: 0x0001 files.
6:2012 May 11 13:59:14:BMC:avct_server:--: Clear RVAS regs
5:2012 May 11 13:59:14:BMC:kernel:--:<5>LPC Reset ISR -> ResetState: 0

```

Botão liga/desliga na frente do servidor (DESLIGADO)

```

6:2012 May 11 14:01:51:BMC:storage:--: SLOT-5:
    Time established as 05/11/12 14:01:27; (75 seconds since power on)
6:2012 May 11 14:01:51:BMC:avct_server:--:
    rvas_wait_for_changes failed
5:2012 May 11 14:01:51:BMC:kernel:--:<5>LPC Reset ISR -> ResetState: 1
7:2012 May 11 14:01:51:BMC:kernel:--:<7>[peci_init_hardware]:490:peci:
    unregistered IRQ: [13]
7:2012 May 11 14:01:51:BMC:kernel:--:<7>[block_transfer_deallocate_entire_list]:
    1141:block_transfer_deallocate_entire_list
7:2012 May 11 14:01:51:BMC:kernel:--:<7>[block_transfer_deallocate_entire_list]:
    1185:block_transfer_deallocate_entire_list : Dumped: 0x0002 files.
7:2012 May 11 14:01:51:BMC:kernel:--:<7>USB FS: VDD Power WAKEUP- Power Good = OFF

```

```
7:2012 May 11 14:01:51:BMC:kernel:-:<7>USB HS: VDD Power WAKEUP- Power Good = OFF
7:2012 May 11 14:01:51:BMC:kernel:-:<7>bulk_out_complete: -108, 0/31, LUN[0][0]
7:2012 May 11 14:01:51:BMC:kernel:-:<7>handle_exception: Handling
MSD_STATE_DISCONNECT for interface[0]
7:2012 May 11 14:01:51:BMC:kernel:-:<7>do_set_interface(): reset_interface
7:2012 May 11 14:01:51:BMC:kernel:-:<7>handle_exception: Handling
MSD_STATE_DISCONNECT for interface[1]
5:2012 May 11 14:01:51:BMC:BIOSReader:391: BIOSReader.c:555:File Close :
/var/nuova/BIOS/BiosTech_3.txt
5:2012 May 11 14:01:51:BMC:BIOSReader:391: BIOSReader.c:555:File Close :
/var/nuova/BIOS/BiosTech_2.txt
5:2012 May 11 14:01:51:BMC:kernel:-:<5>[block_transfer_fetch_host_request_for_app]:
2125:block_transfer_fetch_host_request_for_app : BT_FILE_CLOSE :
HostBTDescr = 150 : FName = BiosTech_3.txt
5:2012 May 11 14:01:51:BMC:kernel:-:<5>[block_transfer_fetch_host_request_for_app]:
2125:block_transfer_fetch_host_request_for_app : BT_FILE_CLOSE :
HostBTDescr = 149 : FName = BiosTech_2.txt
5:2012 May 11 14:01:51:BMC:IPMI:593: Pilot2SrvPower.c:394:
Blade Power Changed To: [ OFF ]
5:2012 May 11 14:01:51:BMC:IPMI:591: VirtualSEL.c:224:SEL Evt[33 00]<
33 00 02 CF 1B AD 4F 20 00 04 25 52 08 00 FF FF >
6:2012 May 11 14:01:51:BMC:IPMI:583: mcddI2CDrv.c:860:PI2CPerformOP:
ioctl to driver failed to read Bus[f4].Dev[5e]! ErrorStatus[32]
6:2012 May 11 14:01:52:BMC:IPMI:583: mcddI2CDrv.c:860:PI2CPerformOP:
ioctl to driver failed to read Bus[f4].Dev[5e]! ErrorStatus[32]
4:2012 May 11 14:01:52:BMC:avct_server:-: No Video Source Detected!
6:2012 May 11 14:01:52:BMC:avct_server:-: Video Source Detected!
5:2012 May 11 14:01:52:BMC:IPMI:591: VirtualSEL.c:224:
SEL Evt[34 00]< 34 00 02 D0 1B AD 4F 20 00 04 25 53 08 01 FF FF >
5:2012 May 11 14:01:52:BMC:bioscom:-: lv_mode_dimm_support.c:126:
[lpc_reset_seen]LPC Reset Count is Different [0x30:0x31]
Asserted LPC Reset Seen
```

Botão liga/desliga na frente do servidor (LIGADO)

```
5:2012 May 11 14:01:58:BMC:IPMI:591: VirtualSEL.c:224:
SEL Evt[35 00]< 35 00 02 D6 1B AD 4F 20 00 04 08 62 0B 00 FF FF >
7:2012 May 11 14:01:58:BMC:kernel:-:<7>USB FS: VDD Power WAKEUP-
Power Good = ON
6:2012 May 11 14:01:58:BMC:kernel:-:<6>se_pilot2_udc_usb_turnon:
Passed USB1.1 register test (0)
7:2012 May 11 14:01:58:BMC:kernel:-:<7>USB HS: VDD Power WAKEUP-
Power Good = ON
6:2012 May 11 14:01:58:BMC:kernel:-:<6>se_pilot2_udc_usb_turnon:
Passed USB2.0 register test (11)
5:2012 May 11 14:01:58:BMC:kernel:-:<5>LPC Reset ISR -> ResetState: 0
7:2012 May 11 14:01:58:BMC:kernel:-:<7>[peci_init_hardware]:472:peci:
registered IRQ: [13]
5:2012 May 11 14:01:58:BMC:kernel:-:<5>[lpc_reset_handler_Port80_Capture_setup]:
630:BIOS_POST_CMPLT De-asserted --> BIOS is running
7:2012 May 11 14:01:58:BMC:kernel:-:<7>[block_transfer_deallocate_entire_list]:
1141:block_transfer_deallocate_entire_list
7:2012 May 11 14:01:58:BMC:kernel:-:<7>[block_transfer_deallocate_entire_list]:
1185:block_transfer_deallocate_entire_list : Dumped: 0x0000 files.
5:2012 May 11 14:01:59:BMC:IPMI:587: Pilot2SrvPower.c:394:
Blade Power Changed To: [ ON ]
5:2012 May 11 14:01:59:BMC:kernel:-:<5>[block_transfer_fetch_host_request_for_app]:
2063:block_transfer_fetch_host_request_for_app: BT_OPEN:
HostDescriptor = 155 : Filename = BiosTech_1.txt
5:2012 May 11 14:01:59:BMC:BIOSReader:391: BIOSReader.c:227:File Open :
BiosTech_1.txt
5:2012 May 11 14:01:59:BMC:kernel:-:<5>LPC Reset ISR -> ResetState: 1
```

7:2012 May 11 14:01:59:BMC:kernel:-:<7>[peci_init_hardware]:490:peci:
unregistered IRQ: [13]

7:2012 May 11 14:01:59:BMC:kernel:-:<7>[block_transfer_deallocate_entire_list]:
1141:block_transfer_deallocate_entire_list

7:2012 May 11 14:01:59:BMC:kernel:-:<7>[block_transfer_deallocate_entire_list]:
1185:block_transfer_deallocate_entire_list : Dumped: 0x0001 files.

5:2012 May 11 14:01:59:BMC:kernel:-:<5>[block_transfer_fetch_host_request_for_app]:
2125:block_transfer_fetch_host_request_for_app : BT_FILE_CLOSE :
HostBTDescr = 155 : FName = BiosTech_1.txt

5:2012 May 11 14:01:59:BMC:BIOSReader:391: BIOSReader.c:555:File Close :
/var/nuova/BIOS/BiosTech_1.txt

5:2012 May 11 14:01:59:BMC:kernel:-:<5>LPC Reset ISR -> ResetState: 0

7:2012 May 11 14:01:59:BMC:kernel:-:<7>[peci_init_hardware]:472:peci:
registered IRQ: [13]

5:2012 May 11 14:01:59:BMC:kernel:-:<5>[lpc_reset_handler_Port80_Capture_setup]:
630:BIOS_POST_CMPLT De-asserted --> BIOS is running

7:2012 May 11 14:01:59:BMC:kernel:-:<7>[block_transfer_deallocate_entire_list]:
1141:block_transfer_deallocate_entire_list

7:2012 May 11 14:01:59:BMC:kernel:-:<7>[block_transfer_deallocate_entire_list]:
1185:block_transfer_deallocate_entire_list : Dumped: 0x0000 files.

6:2012 May 11 14:01:59:BMC:avct_server:-: Clear RVAS regs

5:2012 May 11 14:01:59:BMC:IPMI:591: VirtualSEL.c:224:SEL Evt[36 00]<
36 00 02 D7 1B AD 4F 20 00 04 25 52 08 01 FF FF >

6:2012 May 11 14:02:00:BMC:avct_server:-: Set TSTMUL reg to 0x00100000

5:2012 May 11 14:02:00:BMC:IPMI:591: VirtualSEL.c:224:SEL Evt[37 00]<
37 00 02 D8 1B AD 4F 20 00 04 25 53 08 00 FF FF >

6:2012 May 11 14:02:00:BMC:avct_server:-: Detected VGA Text Mode: 80 x 25 chars

6:2012 May 11 14:02:00:BMC:avct_server:-: Current Graphics Core Settings are:

6:2012 May 11 14:02:00:BMC:avct_server:-: 720 x 400, 4 bits per pixel, 640 pitch,
in VGA mode

6:2012 May 11 14:02:00:BMC:avct_server:-: Video Signal detected: 720 x 400,
color depth is: 4 bits

6:2012 May 11 14:02:00:BMC:avct_server:-: VGA Text mode

6:2012 May 11 14:02:00:BMC:avct_server:-: Change Detected before TFE start

5:2012 May 11 14:02:00:BMC:bioscom:-: lv_mode_dimm_support.c:126:
[lpc_reset_seen]LPC Reset Count is Different [0x31:0x32]
Asserted LPC Reset Seen