

如何測試郵件或內容過濾器以確保其運行正常？

目錄

[問題](#)

問題

如何測試郵件或內容過濾器以確保其運行正常？

可以通過調試過濾器來測試過濾器以確保它們正常工作。調試過濾器是一個需要系統隔離區的兩步過程。

在GUI中建立名為「FilterDebug」的新系統隔離區。隔離區在「監控」—>「隔離」下配置。如果您有一些可用的隔離區，請按一下「新增隔離區」按鈕以配置FilterDebug隔離區。如果沒有足夠的可用空間，您必須編輯其他隔離區，然後減少隔離區用來釋放一些可用空間的空間。

使用預期使用的規則（匹配條件）建立過濾器並將操作設定為「Quarantine('FilterDebug)」。

要調試匹配規則，請在相應的郵件策略（您希望其在生產中運行的位置）上啟用過濾器並生成流量。

與您的規則匹配的郵件將進入FilterDebug隔離區，您可以在那裡檢查這些郵件並滿足自己的要求，即您的規則與您想要的郵件完全匹配。從隔離區中釋放這些郵件，郵件將正常傳送。如果您想觀察一段時間，請將隔離保留期設定為某個可接受的短期，然後定期檢查隔離期，看哪些型別的郵件符合您的條件。

要調試過濾器操作，請建立一個只有一個測試收件人的新郵件策略。禁用所有其他郵件策略中的規則，並在新的郵件策略中啟用該規則。編輯規則以採取所需的操作。您可以刪除隔離規則。

生成流量，並在將消息傳送（或不傳送，取決於您的過濾器）到測試收件人時檢查該消息，以驗證這是您想要的。現在，您可以在郵件策略中為生產部署啟用已完成規則，並從測試收件人策略中禁用該規則。

類似的過程可用於調試消息過濾器。首先構建要在生產中使用的標準：

```
RedirectEarningsReports:
if (recv-listener == "InboundMail")
and (subject == "(?i)quarterly earnings") {
  quarantine ("FilterDebug");
}
```

此操作在CLI中完成：

```
smtp.example.com>filters
Choose the operation you want to perform:
- NEW - Create a new filter.
```

- DELETE - Remove a filter.
- IMPORT - Import a filter script from a file.
- EXPORT - Export filters to a file
- MOVE - Move a filter to a different position.
- SET - Set a filter attribute.
- LIST - List the filters.
- DETAIL - Get detailed information on the filters.
- LOGCONFIG - Configure log subscriptions used by filters.
- ROLLOVERNOW - Roll over a filter log file.

[]> new

Enter filter script. Enter '.' on its own line to end.

RedirectEarningsReports:

```
if (recv-listener == "InboundMail")
and (subject == "(?i)quarterly earnings") {
  quarantine ("FilterDebug");
}
```

.
1 filters added.

Choose the operation you want to perform:

- NEW - Create a new filter.
- DELETE - Remove a filter.
- IMPORT - Import a filter script from a file.
- EXPORT - Export filters to a file
- MOVE - Move a filter to a different position.
- SET - Set a filter attribute.
- LIST - List the filters.
- DETAIL - Get detailed information on the filters.
- LOGCONFIG - Configure log subscriptions used by filters.
- ROLLOVERNOW - Roll over a filter log file.

[]>

smtp.example.com >commit

Please enter some comments describing your changes:

[]> add RedirectEarningsReports filter test actions (incomplete)

Changes committed: Wed Nov 24 12:00:10 2004 MST

使用GUI檢查隔離的郵件並釋放郵件。繼續以這種方式觀看消息流，直到您滿意。接下來，將測試接收人新增到規則，並將操作更改為要在生產中運行的操作：

RedirectEarningsReports:

```
if (recv-listener == "InboundMail")
and (subject == "(?i)quarterly earnings")
and (rcpt-to == "(?i)alan@exchange\\.scu\\.com$") {
  alt-rcpt-to ("sam@exchange.scu.com");
}
```

在CLI中，您需要刪除並重新建立篩選條件：

smtp.example.com> filters

Choose the operation you want to perform:

- NEW - Create a new filter.
- DELETE - Remove a filter.
- IMPORT - Import a filter script from a file.
- EXPORT - Export filters to a file
- MOVE - Move a filter to a different position.
- SET - Set a filter attribute.
- LIST - List the filters.
- DETAIL - Get detailed information on the filters.
- LOGCONFIG - Configure log subscriptions used by filters.
- ROLLOVERNOW - Roll over a filter log file.

[]> list

Num Active Valid Name

Num	Active	Valid	Name
1	N	Y	betatest

```
2 N Y StripInboundExes
3 Y Y RedirectEarningsReports
```

Choose the operation you want to perform:

- NEW - Create a new filter.
- DELETE - Remove a filter.
- IMPORT - Import a filter script from a file.
- EXPORT - Export filters to a file
- MOVE - Move a filter to a different position.
- SET - Set a filter attribute.
- LIST - List the filters.
- DETAIL - Get detailed information on the filters.
- LOGCONFIG - Configure log subscriptions used by filters.
- ROLLOVERNOW - Roll over a filter log file.

```
[> delete
```

Enter the filter name, number, or range:

```
[> 3
```

1 filters deleted.

Choose the operation you want to perform:

- NEW - Create a new filter.
- DELETE - Remove a filter.
- IMPORT - Import a filter script from a file.
- EXPORT - Export filters to a file
- MOVE - Move a filter to a different position.
- SET - Set a filter attribute.
- LIST - List the filters.
- DETAIL - Get detailed information on the filters.
- LOGCONFIG - Configure log subscriptions used by filters.
- ROLLOVERNOW - Roll over a filter log file.

```
[> new
```

Enter filter script. Enter '.' on its own line to end.

RedirectEarningsReports:

```
if (recv-listener == "InboundMail")
and (subject == "(?i)quarterly earnings")
and (rcpt-to == "(?i)alan@exchange\\.scu\\.com$") {
  alt-rcpt-to ("sam@exchange.scu.com");
}
```

```
.
```

1 filters added.

Choose the operation you want to perform:

- NEW - Create a new filter.
- DELETE - Remove a filter.
- IMPORT - Import a filter script from a file.
- EXPORT - Export filters to a file
- MOVE - Move a filter to a different position.
- SET - Set a filter attribute.
- LIST - List the filters.
- DETAIL - Get detailed information on the filters.
- LOGCONFIG - Configure log subscriptions used by filters.
- ROLLOVERNOW - Roll over a filter log file.

```
[>
```

```
smtp.example.com> commit
```

Please enter some comments describing your changes:

```
[> set RedirectEarningsReports to test recipient
```

Changes committed: Wed Nov 24 12:10:07 2004 MST

確認運算子合您的要求。（根據您的篩選器，您還可以驗證mail_logs中的某些操作。）最後，通過刪除測試收件人將最終篩選器放在一起：

RedirectEarningsReports:

```
if (recv-listener == "InboundMail")
and (subject == "(?i)quarterly earnings") {
  alt-rcpt-to ("sam@exchange.scu.com");
}
```

過濾器 and 隔離區的一個潛在令人困惑的方面是郵件正文與郵件標頭的處理。在ESA中，報文正文和標題分別處理。如果您在應用操作後檢查隔離區中的郵件，將不會看到對郵件執行任何標題操作（但會在傳遞時完成）。這是因為郵件在管道中傳輸時，標題處理是單獨並行完成的。郵件在傳送前與其（可能修改的）標頭重新統一，但在隔離區中看不到此郵件。您將在隔離區中看到對郵件正文所做的任何更改，例如刪除附件或標籤頁尾。