

Network

Host Name : (Required by some ISPs)

Domain Name : (Required by some ISPs)

IP Mode

Mode	WAN	LAN
<input checked="" type="radio"/> IPv4 Only	IPv4	IPv4
<input type="radio"/> Dual-Stack IP	IPv4 and IPv6	IPv4 and IPv6

IPv4

LAN Setting

MAC Address : AB:CD:EF:AB:CD:EF

Device IP Address :

Subnet Mask : ▼

Multiple Subnet : Enable

WAN Setting

Interface	Connection Type	Configuration
WAN1	Obtain an IP automatically	
WAN2	Obtain an IP automatically	

DMZ Setting

Enable DMZ

æŸé©Ÿ2.âœ“WAN

Settingi¼^WANè“â®šr¼%ä,¼¼EæE%ä,€ä,«è◆â•Ÿç““ PPPoEçš„WANä»«é◆Ççš„Editâœ—ç“ªâ€ç.·è¼V

Network

Edit WAN Connection

Interface : WAN1

WAN Connection Type : Obtain an IP automatically ▼

Use the Following DNS Server Address

DNS Server (Required) 1 : 0.0.0.0

2 : 0.0.0.0

MTU : Auto Manual 1500 bytes

Network

Edit WAN Connection

Interface : WAN1

WAN Connection Type : Obtain an IP automatically ▼

Use the Following DNS Server Address

DNS Server (Required) 1 : 0.0.0.0

2 : 0.0.0.0

MTU : Auto Manual 1500 bytes

æ¥é©ÿ3.â¼žWANé€£ç.šžžâ¥(WAN Connection Type)ä, <æ<%oé,â-®ä,é,æ“‡PPPoEã€,

Network

Edit WAN Connection

Interface : WAN1

WAN Connection Type : PPPoE

Username : User1

Password :

Service Name : DSL

Connect on Demand : Max Idle Time 5 Min.
 Keep Alive : Redial Period 30 Sec.
 Auto Manual 1492 bytes

MTU :

Save Cancel

æŸ©ÿ4.åœ“Usernameæ¬,ä½ä,¼æ¼,å...ŸISPæäçš,,ä½ç” è€...åç” ±ã€,

æŸ©ÿ5.åœ“Passwordæ¬,ä½ä,¼æ¼,å...ŸISPæäçš,,ä½ç¼ã€,

æŸ©ÿ6ã€i¼^äé,¼%åœ“ãœææ™äç” ±ã€æ¬,ä½ä,¼æ¼,å...Ÿä,åœæäç” ±ä»Ÿ

Network

Edit WAN Connection

Interface : WAN1

WAN Connection Type : PPPoE

Username : User1

Password :

Service Name : DSL

Connect on Demand : Max Idle Time 5 Min.
 Keep Alive : Redial Period 30 Sec.
 Auto Manual 1492 bytes

MTU :

Save Cancel

æŸ©ÿ7.æœ%å...ç”®æ-1æ³åä»Ÿç®;çté€çššæ™,é-“æ®µã€,é€™ä°æ~ãœæœ%éœé€ç
 on Demand)åœæœæäçæœé€çššæœ(Keep
 Alive)ã€,æœ%ä,å,ç,æ†%çš,,ä-®é,æœ%é^¼š

·æŒ%œœ€€€Œç·š!¼šæœ€â¤šç©°é-’æ™,é-“ â€”

æ¤é,é ...â ¯è”æ,“âœ”ãŒŒæœ€â¤šç©°é-’æ™,é-“ã€æ¬,,ä½ ä,ç,°èŒç½®è” â®šç%â®š
idle

timeæŒ†â®šèŒŒçµ,æçâ%œèŒç½®è™·æ-¼ç©°é-’çœæ...çš,,æ™,é-“é†ã€æ¬ ç·¼ä½ç

·äç æŒ æ’â·¼šé† æ’¥é€±æœÿ â€”

æ¤é,é ...â çç”äç è”ç”±â™” âšçµ,éŒŒç·šâ°Internetã€é† æ’¥é€±æœÿæŒ†â®šè”ç”±â™”

Network

Edit WAN Connection

Interface : WAN1

WAN Connection Type : PPPoE

Username : User1

Password :

Service Name : DSL

Connect on Demand : Max Idle Time 5 Min.

Keep Alive : Redial Period 30 Sec.

MTU : Auto Manual 1492 bytes

Save Cancel

æ¥é©ÿ8.MTUi¼^æœ€â¤šâ,³è¼,â-®â...fi¼%œœ%â...©â€œ,é ...i¼Œç”” æ-¼çç°â®šè³†æ-™â,³è¼çš

·è†ââœ” â€” è”ç”±â™”è†ââœ”è”â®šâ€¼ã€,”

·æ%œâœ” â€”

ä½çç”èœ...æ 1æ”šISPèç”,,æ%œâœ”è¼,â...¥â€¼ã€,PPPoEçš,,æœ€â¤šâ¤šâ°ç,°1492ã€,

æ¥é©ÿ9.æŒ%œä, €ä, **Save**,²â”æ”PPPoEä, Šæ%œâœ”šçš,,æ%œœæœ%œé...ç½®ã€,

關於此翻譯

思科已使用電腦和人工技術翻譯本文件，讓全世界的使用者能夠以自己的語言理解支援內容。請注意，即使是最佳機器翻譯，也不如專業譯者翻譯的內容準確。Cisco Systems, Inc. 對這些翻譯的準確度概不負責，並建議一律查看原始英文文件（提供連結）。