

Advanced Routing

IPv4

IPv6

Dynamic Routing

Working Mode : Gateway Router

RIP : Enabled Disabled

Receive RIP versions :

Transmit RIP versions :

Static Routing

Destination IP :

Subnet Mask :

Default Gateway :

Hop Count (Metric, max. is 15) :

Interface :

Add to list

Delete

Add New

View

Save

Cancel

Static Routing

Destination IP :

Subnet Mask :

Default Gateway :

Hop Count (Metric, max. is 15) :

Interface :

192.51.51.24

2. Destination

IP address of the destination network.

3. Subnet

Subnet mask of the destination network.

4. Default

Default gateway IP address of the destination network.

5. Hop

Number of hops to reach the destination network.

Interface through which the traffic will be sent.

- WAN1 or WAN2
- LAN

7. Add to

List of static routes.

Static Routing

Destination IP :

Subnet Mask :

Default Gateway :

Hop Count (Metric, max. is 15) :

Interface :

192.51.51.24
192.4.19.89

æŸ©Ÿ8.i¼^â é ,i¼%oâ | ,æžœè | æ'æ-°é œæ...è-ç"±i¼Œè«â¾žè-ç"±æ,...â-®ä,é,æ"†è-ç"±i¼Œ

æŸ©Ÿ9.i¼^â é ,i¼%oâ | ,æžœè | â¾žé œæ...è-ç"±æ,...â-®ä,â^a é™œ é œæ...è-ç"±i¼Œè«â¾žæ

æŸ©Ÿ10ã€ ,i¼^â é ,i¼%oè | â°†â | ä,€â€œæ-°çš,,é œæ...è-ç"±æ-°âçžâ^æ,...â-®ä,i¼Œè«æŒ%
Newã€,â,æžœè æ-°âçžæ-°çš,,é œæ...è-ç"±i¼Œè«âŸ-è;ŒæŸ©Ÿ2e†³6ã€.

æŸ©Ÿ11.æŒ%oä, €ä, <ã€ Saveã€ ä»¥â,,²â~çµ,,æ...ã€,

æ,"ç ¾åœ " â²æ^ âšŸåœ " RV016ã€ RV042ã€ RV042Gâ'ŒRV082
 VPNè-ç"±â™ " ä,Šé... ç½®é œæ...è-ç"±è " â®šã€,

關於此翻譯

思科已使用電腦和人工技術翻譯本文件，讓全世界的使用者能夠以自己的語言理解支援內容。請注意，即使是最佳機器翻譯，也不如專業譯者翻譯的內容準確。Cisco Systems, Inc. 對這些翻譯的準確度概不負責，並建議一律查看原始英文文件（提供連結）。